Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with 30 TAC 213.

Administrative Review

- 1. <u>Edwards Aquifer applications</u> must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.
 - To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: http://www.tceq.texas.gov/field/eapp.
- 2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
- 3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
- 4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.
 - An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.
- 5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
- 6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

- 1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
- 2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

- clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.
- 3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
- 4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: DRIPPING SPRINGS HIGH SCHOOL #2				2. Regulated Entity No.:					
3. Customer Name: DRIPPING SPRINGS ISD			4. Customer No.: 601259435						
5. Project Type: (Please circle/check one)	New	\bigcup	Modif	ication	1	Exter	sion	Exception	
6. Plan Type: (Please circle/check one)	WPAP	CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Resident	ial (Non-r	Non-residential 8. S		8. Sit	e (acres):	155.74	
9. Application Fee:	\$10,000		10. P	10. Permanent BMP(s):			s):	BATCH DETEN STRIP	TION, VEGETATIVE FILTER
11. SCS (Linear Ft.):			12. A	12. AST/UST (No. Tanks):			ıks):		
13. County:	HAYS		14. W	aters	hed:			ONION CREEK	

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region			
County:	Hays	Travis	Williamson
Original (1 req.)	<u>X</u>		_
Region (1 req.)	<u> </u>	_	
County(ies)	<u>X</u>		_
Groundwater Conservation District(s)	Edwards Aquifer AuthorityBarton Springs/ Edwards Aquifer X_Hays TrinityPlum Creek	Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	AustinBuda X_Dripping SpringsKyleMountain CitySan MarcosWimberleyWoodcreek	AustinBee CavePflugervilleRollingwoodRound RockSunset ValleyWest Lake Hills	AustinCedar ParkFlorenceGeorgetownJerrellLeanderLiberty HillPflugervilleRound Rock

	Sa	an Antonio Region			
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)					
Region (1 req.)			_		
County(ies)					
Groundwater Conservation District(s)	Edwards Aquifer Authority Trinity-Glen Rose	Edwards Aquifer Authority	Kinney	EAA Medina	EAA Uvalde
City(ies) Jurisdiction	Castle HillsFair Oaks RanchHelotesHill Country VillageHollywood ParkSan Antonio (SAWS)Shavano Park	Bulverde Fair Oaks Ranch Garden Ridge New Braunfels Schertz	NA	San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the apparent application is hereby submitted to TCEQ for administ	
DAVID P. SMITH, P.E.	
Print Name of Customer/Authorized Agent	
Haville Truth	06-04-2025
Signature of Customer/Authorized Agent	Date

FOR TCEQ INTERNAL USE ONI	LY			
Date(s)Reviewed:		Date Administratively Complete:		
Received From:		Correct Number of Copies:		
Received By:		Distribution Date:		
EAPP File Number:		Complex:		
Admin. Review(s) (No.):		No. AR Rounds:		
Delinquent Fees (Y/N):		Review Time Spent:		
Lat./Long. Verified:		SOS Customer Verification:		
Agent Authorization Complete/Notarized (Y/N):		Fee	Payable to TCEQ (Y	//N):
Core Data Form Complete (Y/N):		Check: Signed (Y/N):		
Core Data Form Incomplete Nos.:			Less than 90 days o	ld (Y/N):

Contributing Zone Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Contributing Zone to the Edwards Aquifer and Relating to 30 TAC §213.24(1), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Contributing Zone Plan Application** is hereby submitted for TCEQ review and Executive Director approval. The application was prepared by:

Print Name of Customer/Agent: DAVID P. SMITH, P.E.

Date: 6-4-2025

Signature of Customer/Agent:

Regulated Entity Name: DRIPPING SPRINGS HIGH SCHOOL #2

Project Information

1. County: HAYS

2. Stream Basin: ONION CREEK

3. Groundwater Conservation District (if applicable): HAYS TRINITY

4. Customer (Applicant):

Contact Person: <u>JAMES CONKLE</u> Entity: DRIPPING SPRINGS ISD

Mailing Address: 300 SPORTSPLEX DRIVE

City, State: $\underline{\mathsf{DRIPPI}}\mathsf{NG}$ SPRINGS, TX

Telephone: 512-858-3079 Email Address: james.conkle@dsisdtx.us Zip: ⁷⁸⁶²⁰ Fax: ___

5.	Agent/Representative (If any):
	Contact Person: _DAVID P. SMITH, P.E. Entity: _WALKER PARTNERS, LLC Mailing Address: _6504 BRIDGE POINT PARKWAY, SUITE 200 City, State: _AUSTIN, TX
6.	Project Location:
	 ☐ The project site is located inside the city limits of ☐ The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) ofDRIPPING SPRINGS ☐ The project site is not located within any city's limits or ETJ.
7.	The location of the project site is described below. Sufficient detail and clarity has been provided so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation. SE CORNER OF DARDEN HILL RD AND SAWYER RANCH RD, DRIFTWOOD, TX 78619
8.	Attachment A - Road Map. A road map showing directions to and the location of the project site is attached. The map clearly shows the boundary of the project site.
9.	X Attachment B - USGS Quadrangle Map. A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') is attached. The map(s) clearly show:
	× Project site boundaries.× USGS Quadrangle Name(s).
10.	Attachment C - Project Narrative. A detailed narrative description of the proposed project is attached. The project description is consistent throughout the application and contains, at a minimum, the following details:
	 Area of the site Offsite areas Impervious cover Permanent BMP(s) Proposed site use Site history Previous development Area(s) to be demolished
11.	Existing project site conditions are noted below:
	Existing commercial site Existing industrial site Existing residential site

X Undeveloped (Cl	 Existing paved and/or unpaved roads Undeveloped (Cleared) Undeveloped (Undisturbed/Not cleared) Other: DRIPPING SPRINGS ELEMENTARY SCHOOL NO. 5 				
12. The type of project i	12. The type of project is:				
Residential: # of Lots: Residential: # of Living Unit Equivalents: Commercial Industrial Other: HIGH SCHOOL					
13. Total project area (s	ize of site): 155.74 Acres				
Total disturbed area	: <u>93.53</u> Acres				
14. Estimated projected	population: 2,500 STUDE	NTS			
15. The amount and typ below:	e of impervious cover ex	spected after construction	n is complete is shown		
Table 1 - Impervious	Cover				
Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres		
Impervious Cover of		Sq. Ft./Acre ÷ 43,560 =	Acres 8.80		
Impervious Cover of Proposed Project	Sq. Ft.	-			
Impervious Cover of Proposed Project Structures/Rooftops	Sq. Ft. 383,200	÷ 43,560 =	8.80		
Impervious Cover of Proposed Project Structures/Rooftops Parking	Sq. Ft. 383,200 516,300	÷ 43,560 = ÷ 43,560 =	8.80 11.85		
Impervious Cover of Proposed Project Structures/Rooftops Parking Other paved surfaces Total Impervious Cover Total Impervious Cover 16. X Attachment D - Infactors that coul	Sq. Ft. 383,200 516,300 1,442,700 2,342,220 253.77 ÷ Total Acreage 1 Factors Affecting Surface d affect surface water questions.	÷ 43,560 = ÷ 43,560 = ÷ 43,560 =	8.80 11.85 33.12 53.77 spervious Cover led description of all icable, this includes the		
Impervious Cover of Proposed Project Structures/Rooftops Parking Other paved surfaces Total Impervious Cover Total Impervious Cover 16. X Attachment D - I factors that coul location and des construction.	Sq. Ft. 383,200 516,300 1,442,700 2,342,220 Factors Affecting Surface d affect surface water queription of any discharge	÷ 43,560 = ÷ 43,560 = ÷ 43,560 = ÷ 43,560 = ÷ 43,560 = 55.74 X 100 = 34.5 % Implication of the second control of the second con	8.80 11.85 33.12 53.77 Apervious Cover led description of all icable, this includes the al activity other than		
Impervious Cover of Proposed Project Structures/Rooftops Parking Other paved surfaces Total Impervious Cover Total Impervious Cover 16. X Attachment D - I factors that coul location and des construction.	Sq. Ft. 383,200 516,300 1,442,700 2,342,220 Factors Affecting Surface d affect surface water queription of any discharge rials as defined by 30 TAC	÷ 43,560 = ÷ 43,560 = ÷ 43,560 = ÷ 43,560 = ÷ 43,560 = 55.74 X 100 = 34.5 % Implication of the second control of the second con	8.80 11.85 33.12 53.77 Apervious Cover led description of all icable, this includes the al activity other than		
Impervious Cover of Proposed Project Structures/Rooftops Parking Other paved surfaces Total Impervious Cover Total Impervious Cover 16. X Attachment D - I factors that coul location and des construction. 17. X Only inert mater For Road Proje	Sq. Ft. 383,200 516,300 1,442,700 2,342,220 Factors Affecting Surface d affect surface water queription of any discharge rials as defined by 30 TAC ects Only	÷ 43,560 = ÷ 43,560 = ÷ 43,560 = ÷ 43,560 = ÷ 43,560 = 55.74 X 100 = 34.5 % Implication of the second control of the second con	8.80 11.85 33.12 53.77 Apervious Cover led description of all icable, this includes the al activity other than material.		

18. Type of project:
 TXDOT road project. County road or roads built to county specifications. City thoroughfare or roads to be dedicated to a municipality. Street or road providing access to private driveways.
19. Type of pavement or road surface to be used:
Concrete Asphaltic concrete pavement Other:
20. Right of Way (R.O.W.):
Length of R.O.W.: feet. Width of R.O.W.: feet. $L \times W = $ $Ft^2 \div 43,560 Ft^2/Acre = acres.$
21. Pavement Area:
Length of pavement area: feet. Width of pavement area: feet. L x W = Ft ² ÷ 43,560 Ft ² /Acre = acres. Pavement area acres ÷ R.O.W. area acres x 100 = % impervious cover.
22. A rest stop will be included in this project.
A rest stop will not be included in this project.
23. Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.
Stormwater to be generated by the Proposed Project
24. Attachment E - Volume and Character of Stormwater. A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on area and type of impervious cover. Include the runof coefficient of the site for both pre-construction and post-construction conditions.
Wastewater to be generated by the Proposed Project
25. Wastewater is to be discharged in the contributing zone. Requirements under 30 TAC §213.6(c) relating to Wastewater Treatment and Disposal Systems have been satisfied. X N/A

26. Wastewater will be	disposed of by:		
On-Site Sewage	Facility (OSSF/Septic Ta	nk):	
will be used licensing au the land is s the requirer relating to C Each lot in t size. The sy	to treat and dispose of the thority's (authorized age uitable for the use of priments for on-site sewage Facilities. his project/development stem will be designed by	the wastewater from this ent) written approval is at ivate sewage facilities and facilities as specified und this at least one (1) acre (4) a licensed professional ed installer in compliance versions.	site. The appropriate tached. It states that will meet or exceed der 30 TAC Chapter 285 3,560 square feet) in engineer or registered
		: DRIPPING SF ne wastewater to the	PRINGS HIGH SCHOOL NO (name) Treatment
Existing. X Proposed.			
□ N/A			
Gallons	' - 33 if this project inclu	rage Tanks(AST) des the installation of AS	
27. Tanks and substance	e stored:		
Table 2 - Tanks and			
AST Number	Size (Gallons)	Substance to be Stored	Tank Material
1			
2			
3			
4			
5			
	•	Tot	al x 1.5 = Gallons
	•	ment structure that is size city of the system. For fac	•

5 of 11

•	stem, the containm umulative storage c		ed to capture one and	d one-half (1 1/2)
for providir		nment are proposed	ent Methods. Alternd. Specifications sho	
29. Inside dimensi	ons and capacity of	containment structu	ure(s):	
Table 3 - Second	dary Containment	t .		
Length (L)(Ft.)	Width(W)(Ft.)	Height (H)(Ft.)	L x W x H = (Ft3)	Gallons
			То	tal: Gallons
Some of the structure. The piping The piping of the piping of the piping of the contain substance (state of the contain substance).	e piping to dispense will be aboveground will be underground nment area must be s) being stored. The	ers or equipment wild d constructed of and e proposed containn	ings. A scaled drawi	containment vious to the e constructed of:
	nt structure is attacl		-	
Interna Tanks cl Piping c	· -	=	wall and floor thickno collection of any spi	
storage tan			or collection and rec controlled drainage a	
<u></u>		pillage will be remo	ved from the contain	nment structure

In the event of a spill, any spillage will be drained from the containment structure through a drain and valve within 24 hours of the spill and disposed of properly. The drain and valve system are shown in detail on the scaled drawing.
Site Plan Requirements
tems 34 - 46 must be included on the Site Plan.
34. $\boxed{\times}$ The Site Plan must have a minimum scale of 1" = 400'.
Site Plan Scale: $1'' = \frac{100}{}$ '.
35. 100-year floodplain boundaries:
 Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled. No part of the project site is located within the 100-year floodplain. The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FIRM PANEL 48209C 0120G, EFFECTIVE DATE 1/17/2025
36. X The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot contour intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
37. $\boxed{\times}$ A drainage plan showing all paths of drainage from the site to surface streams.
38. $\overline{ imes}$ The drainage patterns and approximate slopes anticipated after major grading activities.
39. $\boxed{ imes}$ Areas of soil disturbance and areas which will not be disturbed.
40. X Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
41. $\boxed{ imes}$ Locations where soil stabilization practices are expected to occur.
42. X Surface waters (including wetlands).
□ N/A
13. X Locations where stormwater discharges to surface water.
There will be no discharges to surface water.
14. Temporary aboveground storage tank facilities.
X Temporary aboveground storage tank facilities will not be located on this site.

45. 🗌	Permanent aboveground storage tank facilities.
X	Permanent aboveground storage tank facilities will not be located on this site.
46. X	Legal boundaries of the site are shown.
Peri	manent Best Management Practices (BMPs)
Practi	ces and measures that will be used during and after construction is completed.
47. X	Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
] N/A
48. 🗌	These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
	 The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site. A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is:
] N/A
49. 🛚 🗙	Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
] N/A
les pe pe wh Ap	here a site is used for low density single-family residential development and has 20 % or as impervious cover, other permanent BMPs are not required. This exemption from ermanent BMPs must be recorded in the county deed records, with a notice that if the ercent impervious cover increases above 20% or land use changes, the exemption for the nole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to oplication Processing and Approval), may no longer apply and the property owner must obtify the appropriate regional office of these changes.
	 The site will be used for low density single-family residential development and has 20% or less impervious cover. The site will be used for low density single-family residential development but has more than 20% impervious cover. The site will not be used for low density single-family residential development.

family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
Attachment I - 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached. The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.
The site will not be used for multi-family residential developments, schools, or small business sites.
52. X Attachment J - BMPs for Upgradient Stormwater.
 A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached. No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached. Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
53. X Attachment K - BMPs for On-site Stormwater.
 A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached. Permanent BMPs or measures are not required to prevent pollution of surface wate or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
54. X Attachment L - BMPs for Surface Streams. A description of the BMPs and measures that prevent pollutants from entering surface streams is attached.
□ N/A
Attachment M - Construction Plans. Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and

	structural plans and specifications, and appropriate details.
	N/A
56. X	Attachment N - Inspection, Maintenance, Repair and Retrofit Plan . A site and BMP specific plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan fulfills all of the following:
	 Prepared and certified by the engineer designing the permanent BMPs and measures Signed by the owner or responsible party Outlines specific procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofit. Contains a discussion of record keeping procedures
	N/A
57.	Attachment O - Pilot-Scale Field Testing Plan. Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
X	N/A
58. X	Attachment P - Measures for Minimizing Surface Stream Contamination. A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that result in water quality degradation.
	N/A
•	ponsibility for Maintenance of Permanent BMPs and sures after Construction is Complete.
59. X	The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or

60. X A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a

multiple single-family residential development, a multi-family residential development,

10 of 11

ownership is transferred.

or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.

Administrative Information

- 61. X Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions.
- 62. X Any modification of this Contributing Zone Plan may require TCEQ review and Executive Director approval prior to construction, and may require submission of a revised application, with appropriate fees.
- 63. X The site description, controls, maintenance, and inspection requirements for the storm water pollution prevention plan (SWPPP) developed under the EPA NPDES general permits for stormwater discharges have been submitted to fulfill paragraphs 30 TAC §213.24(1-5) of the technical report. All requirements of 30 TAC §213.24(1-5) have been met by the SWPPP document.
 - | The Temporary Stormwater Section (TCEQ-0602) is included with the application.


ATTACHMENT A – ROAD MAP



NOT TO SCALE N.T.S

ATTACHMENT B – USGS QUADRANGLE MAP

DRIPPING SPRINGS 7.5' TOPO



ATTACHMENT C - Project Narrative

The subject property consists of 155.74 acres located at the southeast corner of the intersection of Darden Hill Road and Sawyer Ranch Road. The natural terrain is gently sloping. This Contributing Zone Plan is being submitted for the construction of a new High School campus, including an on-site wastewater treatment facility and land application of treated wastewater. The WWTP and TLAP applications will be submitted separately.

The existing land uses are ranchland with 4.45 acres of existing impervious cover, and Dripping Springs Elementary School No. 5 with 10.03 acres of impervious cover. The existing school (now renamed Cypress Springs Elementary) was constructed in 2021. The Contributing Zone Plan Modification approval letter for this school was issued on October 30, 2020 under EAPP ID 11002109.

The proposed improvements include the main high school building, sports facilities, concession and maintenance buildings, associated drives and parking lots, and all associated water, wastewater, and drainage improvements. The proposed impervious cover for Dripping Springs High School #2 is 2,342,200 sf (53.77 ac). Two batch detention water quality controls with detention ponds are proposed to treat the storm water from this site. Vegetative filter strips are proposed to treat runoff from one of the access drives. Off-site drainage areas will be diverted around the proposed BMPs.

In accordance with the West Travis County Public Utility Agency Water and Sewer Service and Development Policies, this project is required to adopt one of the alternative water quality measures required as specified in the "Memorandum of Understanding" between LCRA and the USFWS. The alternative water quality measures to be employed on this project are designed to comply with the TCEQ "Optional Enhanced Measures for Protection of Water Quality in the Edwards Aquifer" (RG-348 Appendix A and Appendix B).

In accordance with the "Optional Enhanced Measures", a Geologic Assessment was performed to identify any sensitive features, and stream buffers were established based on drainage areas contributing flow to the streams. No sensitive features are identified in the Geologic Assessment. See copy of report attached.

Batch detention ponds #1 & #2 will serve as temporary sediment basins during construction. The capture volumes of 177,365 c.f. was calculated in accordance with RG-348 Appendix A (see Pond Plan and Pond Details sheets in the plans). In accordance with "Optional Enhanced Measures" the project will limit the peak rate of runoff for the 2-yr, 24-hour storm from the developed portion of the site to 50% of the undeveloped rate for that event (see table on Pond Drainage Area Map sheet in the plans).

Water Quality Controls

The required amount of TSS removal is based on the methodology in RG-348 Appendix A which requires the removal of 80% of the increase in TSS load in the runoff from the site. Based on the Project Area of 155.74 acres and the new impervious cover of 53.77 acres, the required amount of TSS Load Removal (LM) is 45,083 lbs.

The two batch detention ponds and vegetative filter strip (VFS) are proposed as Best Management Practices (BMPs) for the project.

<u>Pond #1:</u> Drainage Area 'PR1-1' (60.34 ac with 39.22 ac impervious) drains to batch detention pond #1 which removes 41,063 lbs, more than the required 33,066 lbs.

<u>Pond #2:</u> Drainage Area 'PR2-1' (33.53 ac with 14.08 ac impervious) drains to batch detention pond #2 which removes 14,948 lbs, more than the required 12,873 lbs.

<u>VFS-1:</u> Drainage Area 'PR1-2' includes an access drive which drains 0.50 ac of impervious cover across an adjacent VFS which removes 783 lbs, more than the required 457 lbs.

The total TSS removal (LR) by these BMPs is 56,794 lbs which exceeds the required 46,396 lbs.

In accordance with the requirement to protect stream morphology portion of the Enhanced Measures, the peak stormwater release rates for the 2-yr 24-hr developed condition event must be limited to 50% of the release rates for the same event under undeveloped conditions. HEC-HMS 4.10 was used to model the hydrology of the site.

Drainage

Drainage/grading improvements proposed throughout the project will convey runoff to the water quality treatment measures.

Water

Domestic water service and fire flow will be supplied by the Headwaters MUD who purchases water from the West Travis County Public Utility Agency (WTCPUA)

Wastewater

Wastewater from the proposed facility will be collected via gravity by a 10" PVC service line and conveyed to a proposed on-site wastewater treatment plant. The effluent will be land applied on-site. The WWTP and TLAP applications will be submitted separately.

Geologic Assessment

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: Richard V. Klar, P.G. Telephone: 210-699-9090

Date: March 2, 2020 Fax: 210-699-6426

Representing: Raba Kistner, Inc., TBPG Firm #50220 / TBPE Firm #3257 for Corgan

(Name of Company and TBPG or TBPE registration number)

Signature of Geologist:

RICHARD V. KLAR
GEOLOGY
259
CENSE
OF TELAGO
RICHARD V. KLAR
RICHAR V. KLAR
RICHAR V.

Regulated Entity Name: <u>Dripping Springs Elementary School No. 5 Property</u>

Project Information

1.	Date(s) of Geologic Asse	essment was performed	: <u>February 18-21, 2020</u>
2.	Type of Project:		
	WPAP	AST	Contributing Zone Plan
	SCS	UST	
3.	Location of Project:		

	 ☐ Recharge Zone ☐ Transition Zone ☐ Contributing Zone within the Transition Zone ☐ Contributing Zone
4.	Attachment A – Geologic Assessment Table. Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
5.	Soil cover on the project site is summarized in the table below and uses the SCS

5. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the Site Geologic Map or a separate soils map.

Table 1 - Soil Units, Infiltration Characteristics and Thickness

Soil Name Group* Thickness (feet) Bolar clay loam, 1 to 3% slopes (BrB) В 2-2.5 Brackett-Rock outcrop-Real complex, C 1-2 steep (BtD) Comfort-Rock outcrop complex, 0.5-1.5 D undulating (CrD) Doss silty clay, 1 to 5% slopes (DoC) C 1-2 Purves clay, 1 to 5% slopes (PuC) C 1-2 Real-Comfort-Doss complex, C/D 0.5-1.5 undulating (RcD) Sunev clay loam, 1 to 3% slopes (SuB) 2-3

*Soil Group Definitions (Abbreviated)

- A. Soils having a high infiltration rate when thoroughly wetted.
- B. Soils having a moderate infiltration rate when thoroughly wetted.
- C. Soils having a slow infiltration rate when thoroughly wetted.
- D. Soils having a very slow infiltration rate when thoroughly wetted

Note: Bolar and Purves Series soils are not explicitly classified by the NRCS (1986).

BrB and PuC soil units are classified as Group B and C, respectively based on information presented in The Soil Survey of Comal and Hays Counties, Texas prepared by the U.S.D.A. (June 1984).

6. Attachment B – Stratigraphic Column. A stratigraphic column showing formations, members, and thickness is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.

7.	Attachment C – Site Geology. A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
8.	Attachment D – Site Geologic Map(s). The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1":400'.
	Applicant's Site Plan Scale: $1'' = 200'$ Site Geologic Map Scale: $1'' = 200'$ Site Soils Map Scale (if more than 1 soil type): $1'' = 400'$
9.	Method of collecting positional data:
	☐ Other method(s). Please describe method of data collection:
10.	The project site boundaries are clearly shown and labeled on the Site Geologic Map.
11.	Surface geologic units are shown and labeled on the Site Geologic Map.
12.	Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
	Geologic or manmade features were not discovered on the project site during the field investigation.
13.	The Recharge Zone boundary is shown and labeled, if appropriate.
	All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section. There are 21 (#) test holes present on the project site and the location is shown and and labeled. (Check all of the following that apply.) The test holes are not in use and have been properly abandoned. The test holes are not in use and will be properly abandoned. The wells are in use and comply with 16 TAC Chapter 76. There are no wells or test holes of any kind known to exist on the project site.
Aa	lministrative Information
	Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

ATTACHMENTS

ATTACHMENT A

GEOLOGIC ASSESSMENT TABLE (TCEQ-0585-TABLE)

COMMENTS TO GEOLOGIC ASSESSMENT TABLE

SOIL PROFILE

SITE SOILS MAP

				Dripping Springs Elementary School No. 5 Property - Dripping Springs, Hays County, Texas																
GEOLOGIC ASSESSMENT TABLE					PROJE	ECT NA	ME:	RKI Projec	t No. AS	SF20-019-0	0)									
LOCATION FEATURE CHARACTERISTICS						•									EV	ALUATI	ON	F	PHYSICA	L SETTING
1A	1B *	1C*	2A	2B	3		4		5	5A	6	7	8A	8B	9	1	10		11	12
FEATURE ID	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIM	ENSIONS (F	EET)	TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENS	YTIVITI		ENT AREA RES)	TOPOGRAPHY
						Х	Y	Z		10						<40	<u>>40</u>	<1.6	<u>>1.6</u>	
S-1	N30 8 43.4	W98 0 28.7	CD	5	Kgr	19.0	6.0	0.5	NW-SE				F	6	11	✓		✓		Hilltop
S-2	N30 8 48.7	W98 0 29.2	CD	5	Kgr	26.0	7.0	0.7	NW-SE				F	6	11	✓		✓		Hilltop
S-3	N30 8 52.1	W98 0 13.1	CD	5	Kgr	28.0	12.0	0.8	E-W				F	6	11	✓		✓		Hilltop
S-4	N30 8 51.0	W98 0 10.0	CD	5	Kgr	9.0	6.0	1.5	NW-SE				F	6	11	✓		✓		Hilltop
S-5	N30 8 57.5	W98 0 7.6	CD	5	Kgr	75.0	51.0	~2+	N-S				F	6	11	✓			✓	Drainage
S-6	N30 9 12.0	W98 0 17.0	CD	5	Kgr	68.0	12.0	1.0	NW-SE				F	6	11	✓		✓		Hilltop
S-7	N30 9 12.5	W98 0 10.2	CD	5	Kgr	108.0	21.0	0.7	NE-SW	10			F	6	21	✓		✓		Hilltop
S-8	N30 9 2.3	W98 0 1.9	CD	5	Kgr	124.0	30.0	1.0	E-W				F	6	11	✓		✓		Hilltop
S-9	N30 9 0.7	W98 0 4.6	CD	5	Kgr	33.0	5.5	1.7	N-S				F	6	11	✓		✓		Hilltop
S-10	N30 8 59.8	W98 0 4.4	CD	5	Kgr	27.0	3.5	1.3	N-S				F	6	11	✓		✓		Hilltop
S-11	N30 9 2.6	W98 0 7.5	CD	5	Kgr	340.0	258.0	~4+	N-S				F	6	11	✓			✓	Drainage
S-12	N30 9 6.8	W98 0 7.3	CD	5	Kgr	100.0	96.0	~3+	N-S				F	6	11	✓			✓	Drainage
S-13	N30 9 8.7	W98 0 7.6	CD	5	Kgr	32.0	8.0	2.0	N-S				F	6	11	✓			✓	Drainage
S-14	N30 8 46.4	W98 0 26.5	MB (G)	30	Kgr	430.0	4.0	~6-8					F/X	8	38	✓		✓		Hilltop
S-15	N30 9 10.6	W98 0 16.9	MB (TH, DH-T1 West)	30	Kgr	0.4		300.0					F/X	8	38	✓		✓		Hilltop
S-16	N30 9 10.4	W98 0 13.8	MB (TH, DH-T2 East)	30	Kgr	0.4		300.0					F/X	8	38	✓		✓		Hilltop
S-17	N30 9 12.2	W98 0 32.2	MB (PTH, P-1)	30	Kgr	0.3		6.0					F/X	6	36	✓		✓		Hilltop
S-18	N30 9 6.04	W98 0 24.6	MB (PTH, P-2)	30	Kgr	0.3		6.0					F/X	6	36	✓		✓		Hilltop
S-19	N30 9 1.8	W98 0 26.8	MB (PTH, P-3)	30	Kgr	0.3		6.0					F/X	6	36	✓		✓		Hilltop
S-20	N30 9 0.1	W98 0 17.5	MB (PTH, P-4)	30	Kgr	0.3		6.0					F/X	6	36	✓		✓		Hilltop
S-21	N30 8 56.2	W98 0 26.6	MB (PTH, P-5)	30	Kgr	0.3		6.0					F/X	6	36	✓		✓		Hilltop
S-22	N30 8 55.3	W98 0 21.2	MB (PTH, P-6)	30	Kgr	0.3		6.0					F/X	6	36	✓		✓		Hilltop
S-23	N30 8 55.0	W98 0 25.7	MB (PTH, B-1)	30	Kgr	0.3		40.0					F/X	6	36	✓		✓		Hilltop
S-24	N30 8 54.5	W98 0 23.8	MB (PTH, B-2)	30	Kgr	0.3		40.0					F/X	6	36	✓		✓		Hilltop
S-25	N30 8 54.1	W98 0 22.4	MB (PTH, B-3)	30	Kgr	0.3		25.0					F/X	6	36	✓		✓		Hilltop
S-26	N30 8 55.0	W98 0 25.7	MB (PTH, B-4)	30	Kgr	0.3		42.3					F/X	6	36	✓		✓		Hilltop
S-27	N30 8 54.2	W98 0 24.8	MB (PTH, B-5)	30	Kgr	0.3		25.0					F/X	6	36	✓		✓		Hilltop
S-28	N30 8 53.6	W98 0 25.8	MB (PTH, B-6)	30	Kgr	0.3		40.0					F/X	6	36	✓		✓		Hilltop
S-29	N30 8 53.2	W98 0 24.1	MB (PTH, B-7)	30	Kgr	0.3		25.0					F/X	6	36	✓		✓		Hilltop
S-30	N30 8 52.9	W98 0 22.4	MB (PTH, B-8)	30	Kgr	0.3		25.0					F/X	6	36	✓		✓		Hilltop
S-31	N30 8 52.4	W98 0 20.8	MB (PTH, B-9)	30	Kgr	0.3		25.0					F/X	6	36	✓		✓		Hilltop
S-32	N30 8 51.9	W98 0 23.6	MB (PTH, B-10)	30	Kgr	0.3		40.0					F/X	6	36	✓		✓		Hilltop
S-33	N30 8 51.2	W98 0 21.9	MB (PTH, B-11)	30	Kgr	0.3		40.0					F/X	6	36	✓		✓		Hilltop
S-34	N30 8 51.8	W98 0 27.3	MB (PTH, F-1)	30	Kgr	0.3		15.0					F/X	6	36	✓		✓		Hilltop
S-35	N30 8 51.2	W98 0 24.7	MB (PTH, F-2)	30	Kgr	0.3		15.0					F/X	6	36	✓		✓		Hilltop

* DATUM: *NAD 83*

Features: G = natural gas pipeline; TH = test hole; PTH = plugged test hole Kgr = G = G Rose Formation

2A TYPE	TYPE	2B POINTS
С	Cave	30
SC	Solution cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
0	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30

	8A INFILLING					
N	None, exposed bedrock					
С	Coarse - cobbles, breakdown, sand, gravel					
0	Loose or soft mud or soil, organics, leaves, sticks, dark colors					
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors					
V	Vegetation. Give details in narrative description					
FS	S Flowstone, cements, cave deposits					
Χ	Other materials: Granular bedding materials for utility line (Feature S-14), bentonite and crushed stone (Features					
	S-15 and S-16), and site-derived soil cuttings (Features S-17 through S-35).					
	12 TOPOGRAPHY					
Cliff,	Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed					

I have read, I understood, and I have followed the Texas Natural Resource Conservation Commission's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field.

My signature certifies that I am qualified as a geologist as defined by 30 TAC 213

RICHARD V. KLAR

GEOLOGY

259

CENSE

ONAL ** GEOS

Date:	3/2/2020				
Sheet	<u>1</u> of <u>1</u>				

COMMENTS TO GEOLOGIC ASSESSMENT TABLE Dripping Springs Elementary School No. 5 Property Dripping Springs, Hays County, Texas

The locations of the following features are indicated on the *Site Geologic Map* provided as *Attachment D* of this report.

Non Karst Closed Depressions

Features S-1 and S-2 (CD-Subsidence):





Features S-1 and S-2 consist of non-karst closed depressions apparently formed from subsidence or surface scour adjacent to an existing natural gas pipeline utility (**Feature S-14**). The features are located in the southwest corner of the property. Feature dimensions are reported in length, width, and depth, respectively as follows:

Feature S-1: 19 x 6 x 0.5 feet.
Feature S-2: 26 x 7 x 0.7 feet.

The features are limited to the soil horizon with no connection to the underlying limestone bedrock.

Features S-3, S-4, S-6, S-7, and S-8 (CD-Surface Scours):











Features S-3, S-4, S-6, S-7, and S-8 consist of non-karst closed depressions formed by surface scour along earthen berms constructed historically in conjunction with ranch operations to direct storm water towards the ephemeral drainage feature that crosses the east part of the property from north to south.

The drainage feature connects to an unnamed tributary of Onion Creek located south of the SITE. Feature dimensions are reported in length, width, and depth, respectively as follows:

• *Feature S-3:* 28 x 12 x 0.8 feet.

• *Feature S-4:* 9 x 6 x 1.5 feet.


• Feature S-6: 68 x 12 x 1 feet.

• Feature S-7: 108 x 21 x 0.7 feet.

• Feature S-8: 124 x 30 x 1 feet.

The features are limited to the soil horizon with no connection to the underlying limestone bedrock. **Features S-6** and **S-7** were observed to contain ponded water.

Features S-9, S-10, and S-13 (CD-Ephemeral Drainage Scours):







Features 5-9, S-10, and S-13 consist of non-karst closed depressions formed by scour within the ephemeral drainage feature that crosses from north to south within the east part of the property. The drainage feature hosts three stock ponds utilized historically to support ranch operations. As described

below with respect to *Features S-5, S-11*, and *S-12*. The feature dimensions are reported in length, width, and depth, respectively as follows:

Feature S-9: 33 x 5.5 x 0.7 feet.
Feature S-10: 27 x 3.5 x 1.3 feet.
Feature S-13: 32 x 8 x 2 feet.

Bedrock exposures were present along the channel floor at *Features S-9* and *S-10*. Ponded water was observed in *Features S-9* and *S-13*.

Features S-5. S-11, and S-12 (CD-Stock Ponds):

Feature S-5 (CD):



Feature S-5 consists of a small stock pond containing water. The feature is located within the east-central part of the SITE, just south of a fence line that crosses the property from west to east. The feature dimensions are on the order of 75 x 51 in length and width, respectively. The depth of the stock pond is estimated to be approximately 2+ feet.

Feature S-11 (CD):



Feature S-11 consists of a large stock pond containing water. The feature is located within the east-central portion of the property. The feature dimensions are on the order of 340 x 258 feet in length and width, respectively. The depth of the stock pond is estimated to be approximately 4+ feet. A manmade berm was observed along the south edge of the stock pond. Patchy limestone exposures were observed around the north, east, and west sides of the feature.

Feature S-12 (CD):



Feature S-12 consists of a small stock pond containing water. The feature is located north of the large stock pond (**Feature S-11**) within the east portion of the property. The feature dimensions are on the order of 100×96 feet in length and width, respectively. The depth of the stock pond is estimated to be approximately 3+ feet.

Manmade Features

Feature S-14 (MB-Utility):



Feature S-14 consists of a natural gas transmission pipeline. According to the Railroad Commission of Texas (RRC) Public GIS Viewer website http://gis.rrc.texas.gov/GISViewer/, the pipeline is operated by Enterprise Products Operating LLC. On the basis of our observations, it is inferred that the trench hosting the utility line is installed 6-8 feet or more into the Glen Rose formation. The length of the utility trench within the project area is estimated on the order of 430 linear feet.

Features S-15 and S-16 (MB-Test Holes)






Features S-15 and S-16 consist of test borings installed by Geothermal Resource Technologies, Inc. on October 17, 2019 to perform thermal conductivity testing to support the design of a geothermal heating, ventilation, and air conditioning (HVAC) system for the proposed school. Both test holes were reportedly installed to depths of 300 feet below ground surface (bgs). The test holes are existing with a bentonite surface seal. Electrical tubing is present and sealed within each of the borings, but is currently capped for possible future testing.

Features S-17 through S-35 (MB):

Features S-17 through S-35 consists of eighteen test holes drilled from December 19, 2019 through December 31, 2019 for a geotechnical engineering study prepared by **Raba Kistner, Inc.** The borings were installed to evaluate soil conditions within the building footprint, pavement area, and athletic field area for the proposed school development. These test holes were reportedly installed to depths on the order of 6-42.3 feet below ground surface. Based on our interpretation of the boring log data, the borings were terminated in the upper member of the Glen Rose formation. The test holes appear to have been effectively plugged using site-derived (clay) soil cuttings and abandoned following the completion of drilling activities.



SOIL PROFILE Dripping Springs Elementary School No. 5 Property Dripping Springs, Hays County, Texas

SOIL SERIES	THICKNESS ON SITE	DESCRIPTION		
Bolar	2-2.5 feet	Bolar clay loam,1-3% slopes (BrB): This is a moderately deep, gently sloping soil on concave valley slopes and foot slopes of hills on uplands in the Edwards Plateau, which consist of long and narrow areas. The surface layer is a dark grayish brown and dark brown, clay loam approximately 14 inches thick. The subsoil is a brown clay loam extending to depths of approximately 28 inches. The soil is moderately alkaline and calcareous throughout.		
Brackett	Brackett-Rock outcrop-Comfort complex, undulating (BtD consists of shallow, loamy soils and Rock outcrop on upland Plateau. On average, Brackett soils make up 50% of the conductrop makes up 20% and the Comfort soil makes up 15% The surface layer of the Brackett soil is grayish brown gratypically about 6 inches thick. The subsoil is a very pale yellow gravelly clay loam extending to a depth of approxing The underlying material is weakly cemented limestone in thin layers of indurated limestone. The soil is moderated calcareous throughout. The surface layers of the Comfort's extremely stony clay approximately 4 inches thick. The sudark reddish brown extremely stony clay extending to a define underlying material is fractured limestone.			
Comfort 0.5-1.5 feet		Comfort-Rock outcrop complex, undulating (CrD): This complex comprises shallow clayey soils and limestone outcrops on side slopes, hilltops, and ridgetops in the Edwards Plateau. On average, Comfort soils make of 70% of the complex with the Rock outcrop averaging 15%. Areas of limestone outcrop form narrow horizontal bands, and Comfort soils occur between the bands. The surface layer of the Comfort soil is dark brown, extremely stony clay, typically about 6 inches thick. Cobbles to 4 feet in diameter are abundant. The subsoil is dark reddish-brown clay, extremely stony and occurs to depths of about 13 inches.		
Doss	1-2 feet	Doss silty clay, 1-5% slopes (DoC): This complex comprises a shallow, gently sloping soil on convex slopes of low hills and ridges on uplands in the Edwards Plateau. The surface layer is typically a dark grayish brown silty clay approximately 9 inches thick. The subsoil is a yellowish brown clay loam extending to a depth of 18 inches. The underlying material is weakly cemented limestone and marl extending to a depth of 24 inches. The soil is moderately alkaline and calcareous throughout with a few noncalcareous surface layer area.		

Purves	1-2 feet	Purves clay, 1-5% slopes (PuC): This complex comprises shallow gently sloping soil on uplands with long and narrow areas. The surface layer of the is a very dark gray clay, typically about 10 inches thick. The subsoil layers are a dark gray clay to a depth of 16 inches, which is underlain to a depth of 19 inches by dark grayish brown clay that consists of approximately 10% of coarse fragments of limestone. The underlying layer is fractured indurated limestone bedrock.					
Real	0.5-1.5 feet	Real-Comfort-Doss complex, undulating (RcD): This complex comprises shallow, loamy clayey soils on low hills and ridges on uplands in the Edwards Plateau. On average, Real soils make up 40% of the complex with Comfort soils and Doss soils making up 30% and 20%, respectively. The surface layer of the Real soils is very dark grayish brown gravelly loam about 8 inches thick. The underlying material is weakly cemented limestone interbedded with thin layers of inundated limestone. The surface layer of the Comfort soil is dark brown very stony clay approximately 8 inches. The subsoil is dark reddish-brown clay, extremely stony and occurs to depths of about 13 inches. The surface layer of the Doss soils is typically dark brown clay loam about 7 inches thick. The subsoil extends to a depth of 13 inches of a reddish brown clay loam (approximately 15% limestone and caliche gravel). The underlying material is weakly cemented limestone and marl.					
Sunev	2-3 feet	Sunev clay loam (SuB): The areas of this complex are long and narrow consisting of a deep, gently sloping soil on valley slopes and foot slopes on uplands in the Edwards Plateau. The surface layer is a dark grayish brown clay approximately 11 inches thick. The subsoil extends to a depth of 35 inches and consists of brown clay loam. The underlying material is a reddish yellow clay loam that, by volume, is approximately 15% comprised of soft masses and concretions of calcium carbonate. The soil is moderately alkaline and calcareous throughout.					

The preceding table was prepared on the basis of information provided in the *Soils Survey of Comal and Hays Counties, Texas (June 1984)* in addition to field observations. As presented on the attached *Site Soils Map*, various soil units are mapped throughout the subject property including: (i) Bolar clay loam,1-3% slopes (BrB) [30.7 acres], (ii) Brackett-Rock outcrop-Comfort complex, undulating (BtD) [51.6 acres] (iii) Comfort-Rock outcrop complex, undulating (CrD) [18.0 acres], (iv) Doss silty clay, 1-5% slopes (DoC) [2.6 acres], (v) Purves clay, 1-5% slopes (PuC) [20.7 acres], (vi) Real-Comfort-Doss complex, undulating (RcD) [9.2 acres], and (vii) Sunev clay loam (SuB) [20.2 acres]. Each of the referenced soils are weakly-developed and relatively thin, occurring over weathered limestone units of the upper Glen Rose Formation. The soil units are reported to exhibit low to moderate permeability (0.06-0.2 inches/hour to 0.6-2 inches/hour). All soils are reported as having low to moderate shrink-swell potential with the exception the Purves soils (i.e., high shrink-swell potential).

Reported test hole data (**RKI**, 2020) confirms approximately 2-4 feet of brown clayey soils, which are generally consistent with the soil types mapped along the west portion of the SITE.

ATTACHMENT B STRATIGRAPHIC COLUMN

STRATIGRAPHIC COLUMN Dripping Springs Elementary School No. 5 Property Dripping Springs, Hays County, Texas

STRATIGRAPHIC FORMATION	THICKNESS	DESCRIPTION
Edwards Limestone		Not present at the SITE.
Glen Rose Formation (Kgr)		
Upper Member (Kgru)	350-500 feet	Yellowish tan thinly bedded limestone and marl typically exhibiting "stair-step" topography comprised of alternating limestone and marl units with minor evaporate layers. The Upper Glen Rose is more dolomitic and less fossiliferous than the Lower Glen Rose. Patchy exposures were observed at the base of the hill and along the base of the ephemeral drainage feature.
Lower Member (Kgrl)	160 feet	Includes alternating resistant and recessive beds of limestone, dolomite, and marl; limestone is light gray to yellowish-gray, aphanitic to fine-grained, hard to soft, marly; dolomite is fine-grained, porous, yellowish-brown. <i>Not present at the SITE.</i>

Note: Stratigraphic Column adapted from Barnes (1981) and Small and Hanson (1995).

ATTACHMENT C NARRATIVE OF SITE SPECIFIC GEOLOGY

SITE GEOLOGY NARRATIVE Dripping Springs Elementary School No. 5 Property Dripping Springs, Hays County, Texas

Introduction

The following discussion is a site-specific assessment of existing geological conditions and potential recharge features within the referenced project site. This assessment was performed by **Raba Kistner**, **Inc.** (**RKI**) for Corgan, pursuant to a Memorandum of Understanding (MOU) established by the U.S. Fish and Wildlife Service (USFWS) and Lower Colorado River Authority (LCRA). The MOU requires that Optional Enhanced Measures for environmental protection stipulated by the Texas Commission on Environmental Quality (TCEQ) be implemented in conjunction with land development, which includes the performance of a Geologic Assessment. This assessment report was prepared in accordance with the revised *Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zones (TCEQ-0585*), which are applicable to submittals received by the TCEQ after October 1, 2004.

This geologic assessment report documents conditions observed by **RKI** within the project boundaries from February 18-21, 2020.

Site Description

Site Location. The subject property comprises a 155.8-acre tract of undeveloped ranch land located southeast of Darden Hill Road and Sawyer Ranch Road, in Dripping Springs, Hays County, Texas (i.e., hereinafter referred to as SITE). The west portion of the SITE will host an elementary school facility with associated parking and athletic field. Based on review of official maps published by the Texas Commission on Environmental Quality (TCEQ), the SITE is fully-located within the Edwards Aquifer Contributing Zone (EACZ).

Topography and Drainage. Topographic information on the U.S. Geological Survey (USGS, 2012 and 2013) 7.5-minute topographic maps (i.e., Dripping Springs and Signal Hill Quadrangles) was reviewed to evaluate general surface conditions and drainage patterns for the SITE. Topographic conditions for the SITE consists of gently sloping land surrounding a prominent hill feature, which comprises the west-central portion of the property. The maximum elevation is approximately 1160 feet above mean sea level (msl) and slopes to the southwest and southeast to elevations of approximately 1100 msl. As indicated by topographic contours presented on the **Site Geologic Map**, the surface drainage patterns for the SITE are generally away from the circular hilltop in all directions. Surface runoff from the hill to the northeast, east, and southeast is directed toward an ephemeral drainage feature that crosses the SITE from the north to south by series of manmade soil berms. Surface water entering the drainage channel is impounded at three locations by existing stock ponds, with some drainage exiting the southeast corner of the property. Ultimate storm water discharge is to Onion Creek, which is located approximately 1.5 miles to the west. A review of Flood Insurance Rate Map (FEMA, 2009) indicates that no portion of the SITE is located within 100-year or 500-year floodplain areas as depicted on official maps.

Historical Property Use. Although research pertaining to past SITE operations and historical land use activities was beyond the scope of this assessment, historical aerial imagery was reviewed to evaluate historical land use and the presence of lineations that could indicate the presence of normal faulting. The following aerial photographs from Google Earth™ were reviewed: 1995, 2002, 2006, 2009, 2012, 2014, 2016, and 2018. The aerial images from 1995 to 2018 indicate that the SITE was undeveloped as part of a larger ranch property. Manmade soil berms are visually present in all aerials reviewed. The SITE conditions appear essentially unchanged with negligible differences in vegetation in comparison with previous aerial imagery. As presented on the attached Site Geologic Map, current adjacent properties include vacant land and residential (i.e., ranch properties) to the north, west, south, and east.

Classification of Recharge Features: As further described herein, no naturally-occurring features attributing to karstification of limestone terrain and/or erosional processed were identified within SITE boundaries. Features identified and discussed below include 21 manmade features (i.e., test holes). The significance of these features was assessed using definitions and guidance provided in Instructions to Geologists (TCEQ-0585-Instructions, revised October 1, 2004). All features within the SITE that met the criteria presented in this reference were mapped. The characteristics of all mapped features and the assessments of these features, as defined by the TCEQ, are presented in the attached Geologic Assessment Table (TCEQ-0585).

Stratigraphy

As presented in the attached *Stratigraphic Column*, information pertaining to the lithology of the geologic unit underlying the SITE was taken from Small and Hanson (1995). The published data referenced indicates that the SITE is underlain by the Upper Glen Rose Limestone (Kgru). The Kgru is comprised of dolomite and marl in alternating resistant and recessive beds forming a stair step topography ranging from 350 to 500 feet. The upper member is known to support karst feature development and springs. Review of the test hole data (**RKI**, 2020) is consistent with the published geology (i.e, tan weathered limestone to gray limestone). Patchy exposures of the Kgru were observed at the base of the hill and along the base of the ephemeral drainage feature in the west and east portions of the SITE, respectively

Structure

This SITE is located along the southern edge of the Balcones Fault Zone and, as such, is expected to exhibit a similar dominant structural trend. The Balcones Fault Zone generally consists of a northeast-southwest trending, *en echelon* normal fault system, which juxtaposes Upper Cretaceous lithologies in the southeast with Lower Cretaceous lithologies in the northwest. As a result of this large-scale regional faulting, minor internal fault sequences and fractures exist within this zone which generally follow the same structural trend and accommodate localized displacement.

Based on review of historical aerial photographs, published maps, and in conjunction with field mapping efforts, no indications of lineations that could be associated with normal faulting were identified within the boundaries of the SITE.

Karst Features

Although patchy exposures of limestone bedrock were identified along the west (base of the hill) and along east (base of the ephemeral drainage feature) portions of the SITE, the results of field mapping activities within SITE boundaries did not reveal the presence of any features that could be attributed to karstification of the underlying limestone terrain. Soil cover is greater than 1-2 feet is generally present throughout the SITE.

Non-Karst Closed Depressions

A total of 13 non-karst closed depressions were identified during field reconnaissance. Provided below is information pertaining to each non-karst closed depression mapped:

- **Features S-1** and **S-2** appear to have formed from surface scour or differential settlement along an existing natural gas pipeline utility located in the southwest corner of the property. The features are not connected directly to the subsurface. Both features are classified as not sensitive owing to the non-karst origin of the closed depressions and estimated low relative infiltration rate (i.e., no evidence of capacity for rapid infiltration).
- Features S-3, S-4, S-6, S-7, and S-8 appear to have formed by surface scour from the conveyance of storm water along constructed earthen berms towards the ephemeral drainage feature. The features are located in the southeast, north, and east portions of the property. These features are limited to the soil zone with no apparent connection to underlying bedrock. Pursuant to point assignment criteria and professional judgment, the non-karst closed depressions are collectively classified as not sensitive, having low potential of transmitting fluids to the subsurface.
- Features S-9, S-10, and S-13 consist of non-karst closed depressions formed by scour within the ephemeral drainage feature that crosses the property from the north to south. Although bedrock exposures were present along the channel floor at Features S-9 and S-10, ponded water was observed in Features S-9 and S-13. These features are collectively classified as not sensitive and as having low potential of transmitting fluids to the subsurface.
- **Features S-5, S-11, and S-12** consist of manmade stock ponds as clearly indicated in the aerial photographs since at least 1995. The features, vary in size owing to rainfall and runoff, are located in the east-central portion of the SITE. Given the function (i.e., ranching purposes) of the ponds and presence of ponded water, the features are collectively classified as not sensitive and as having a low potential of transmitting fluids into the subsurface.

Manmade Features

As presented on the *Site Geologic Map*, a total of 21 manmade features were identified that may potentially serve to enhance the transmission of surface runoff to the subsurface. The features consist of existing and former test holes that meet the criteria for assessment as manmade features in bedrock. None of the manmade features were observed in conjunction with any naturally-occurring recharge features.

- Features S-15 and S-16 (State of Texas Well Report Tracking Nos. 5307742 and 530777, respectively) consist of existing closed-loop geothermal borings based on information reviewed in the Texas Water Development Board (TWDB) Water Interactive Data (WID) website https://www2.twdb.texas.gov/apps/WaterDataInteractive/GroundwaterDataViewer/?map=sdr. The annular seal for the boreholes is comprised of bentonite to total depth (Feature S-15) and to a depth of 30 feet underlain by 3/8-inch gravel (Feature S-16). The bentonite seal and piping were observed to be intact and capped, respectively.
- Features S-17 through S-35 are geotechnical soil borings installed by Raba Kistner, Inc. from December 19 through December 31, 2019 to evaluate engineering characteristics as necessary to develop structural, pavement, and athletic field recommendations. The borings were reportedly drilled to depths on the order of 6 to 42.3 feet and plugged with site-derived (clay) soil cuttings upon completion of drilling activities.

The existing and former test holes are collectively classified as not sensitive as these are either fully plugged or contain a bentonite surface seal. These classifications are based upon the point assignment criteria presented in the *Geologic Assessment Table (TCEQ-0585)* and professional judgment.

Potential for Fluid Migration to the Edwards Aquifer

The majority of the SITE is characterized by intact limestone with overlying clay soils having very slow to moderate published infiltration rates. Based on our review of SITE geology, topography and drainage conditions, in addition to the results of our detailed mapping efforts, the overall potential for fluid movement (i.e., surface-derived flow) to the subsurface is considered to be low. The following assessment findings support this conclusion.

- The Edwards Limestone does not exist at the SITE and the subject property is fully located within the Edwards Aquifer Contributing Zone.
- The capacity for direct infiltration of surface runoff or is limited owing to presence of clay soils overlying thinly-bedded, clayey limestone strata of the Upper Glen Rose Formation.
- No sensitive or other naturally-occurring recharge features were identified within SITE boundaries
 that may be attributed to karstification of limestone terrain. All natural features identified were
 erosional in nature and exhibited a propensity for holding as opposed to transmitting water to the
 subsurface.

References

Barnes, V. L., 1974, Geologic Atlas of Texas Austin Sheet; Bureau of Economic Geology, The University of Texas at Austin, Austin, Texas.

Google Earth[™], January 1995, October 2005, April 2006, November 2009, August 2012, December 2014, February 2016, August 2018 orthoimageries.

- National Flood Insurance Program, 2005, Flood Insurance Rate Map, Hays County, Texas and Incorporated Areas; Federal Emergency Management Agency, Map 48209C0120F.
- Raba Kistner, Inc., 2020, Geotechnical Engineering Study, Interim Report, Project No. AAA19-111-00, February 7, 2020.
- Railroad Commission of Texas website http://gis.rrc.texas.gov/GISViewer/, accessed February 27, 2020.
- Small, T. A. and Hanson, J. A., 1995, Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Outcrop, Hays County, Texas: U.S. Geological Survey Water Resources Investigations Report 95-464.
- Texas Commission on Environmental Quality Edwards Aquifer Protection Program, Edwards Aquifer Map, https://tceq.maps.arcgis.com/apps/webappviewer/index.html?id=2e5afa3ba8144c30a49d3 https://dcea.maps.arcgis.com/apps/webappviewer/index.html?id=2e5afa3ba8144c30a49d3 https://dcea.maps.arcgis.com/apps/webappviewer/index.html?id=2e5afa3ba8144c30a49d3 https://dcea.maps.arcgis.com/apps/webappviewer/index.html?id=2e5afa3ba8144c30a49d3 https://dcea.maps.arcgis.com/apps/webappviewer/index.html?id=2e5afa3ba8144c30a49d3 https://dcea.maps.arcgis.com/apps/webappviewer/index.html?
- Texas Water Development Board, Water Data Interactive (WDI) Groundwater Data Viewer, https://www2.twdb.texas.gov/apps/WaterDataInteractive/GroundwaterDataViewer/?map=sdr, accessed February 24, 2020.
- United States Geological Survey (USGS), 2012, Dripping Springs and 2013, Signal Hill Quadrangles; USGS, Denver, Colorado.
- United States Department of Agriculture (USDA), 1984, Soil Survey of Comal and Hays Counties, Texas; USDA / Soil Conservation Service / Texas Agricultural Experiment Station.
- United States Department of Agriculture (USDA), 1986, Urban Hydrology for Small Watersheds; USDA / Natural Resource Conservation Service, Technical Release (TR-) 55, June 1986.

ATTACHMENT D

FEATURE POSITION TABLE (GPS COORDINATES) SITE GEOLOGIC MAP

March 2, 2020 1

FEATURE POSITION TABLE

Dripping Springs Elementary School No. 5 Property
Dripping Springs, Hays County, Texas
RKI Project No. ASF20-019-00

Feature Designation	Feature Type	Date Collected	North Latitude	West Longitude	UTM Northing (meters)	UTM Easting (meters)
S-1	Non-karst closed depression	2/18/2020	N30 8 43.4	W98 0 28.7	3335466	595539
S-2	Non-karst closed depression	2/18/2020	N30 8 48.7	W98 0 29.2	3335474	595526
S-3	Non-karst closed depression	2/19/2020	N30 8 52.1	W98 0 13.1	3335584	595954
S-4	Non-karst closed depression	2/19/2020	N30 8 51.0	W98 0 10.0	3335549	596040
S-5	Non-karst closed depression	2/19/2020	N30 8 57.5	W98 0 7.6	3335450	596103
S-6	Non-karst closed depression	2/19/2020	N30 9 12.0	W98 0 17.0	3336196	595848
S-7	Non-karst closed depression	2/19/2020	N30 9 12.5	W98 0 10.2	3336210	596027
S-8	Non-karst closed depression	2/19/2020	N30 9 2.3	W98 0 1.9	3335901	596253
S-9	Non-karst closed depression	2/19/2020	N30 9 0.7	W98 0 4.6	3335849	596183
S-10	Non-karst closed depression	2/19/2020	N30 8 59.8	W98 0 4.4	3335823	596187
S-11	Non-karst closed depression	2/19/2020	N30 9 2.6	W98 0 7.5	3335908	596103
S-12	Non-karst closed depression	2/19/2020	N30 9 6.8	W98 0 7.3	3336036	596107
S-13	Non-karst closed depression	2/20/2020	N30 9 8.7	W98 0 7.6	3336094	596099
S-14	Manmade Feature in Bedrock (Natural Gas Pipeline)	2/18/2020	N30 8 46.4	W98 0 26.5	3336010	595643
S-15	Manmade Feature in Bedrock (Plugged Test Hole, DH-T1 West)	2/19/2020	N30 9 10.6	W98 0 16.9	3336151	595848
S-16	Manmade Feature in Bedrock (Plugged Test Hole, DH-T2 East)	2/19/2020	N30 9 10.4	W98 0 13.8	3336145	595934
S-17	Manmade Feature in Bedrock (Plugged Test Hole, P-1)	2/21/2020	N30 9 12.2	W98 0 32.2	3336192	595436
S-18	Manmade Feature in Bedrock (Plugged Test Hole, P-2)	2/20/2020	N30 9 6.04	W98 0 24.6	3336009	595644
S-19	Manmade Feature in Bedrock (Plugged Test Hole, P-3)	2/18/2020	N30 9 1.8	W98 0 26.8	3335878	595587
S-20	Manmade Feature in Bedrock (Plugged Test Hole, P-4)	2/18/2020	N30 9 0.1	W98 0 17.5	3335827	595837
S-21	Manmade Feature in Bedrock (Plugged Test Hole, P-5)	2/18/2020	N30 8 56.2	W98 0 26.6	3335705	595594

March 2, 2020 2


FEATURE POSITION TABLE

Dripping Springs Elementary School No. 5 Property
Dripping Springs, Hays County, Texas
RKI Project No. ASF20-019-00

Feature Designation	Feature Type	Date Collected	North Latitude	West Longitude	UTM Northing (meters)	UTM Easting (meters)
S-22	Manmade Feature in Bedrock (Plugged Test Hole, P-6)	2/18/2020	N30 8 55.3	W98 0 21.2	3335679	595738
S-23	Manmade Feature in Bedrock (Plugged Test Hole, B-1)	2/18/2020	N30 8 55.0	W98 0 25.7	3335669	595618
S-24	Manmade Feature in Bedrock (Plugged Test Hole, B-2)	2/18/2020	N30 8 54.5	W98 0 23.8	3335655	595670
S-25	Manmade Feature in Bedrock (Plugged Test Hole, B-3)	2/18/2020	N30 8 54.1	W98 0 22.4	3335641	595706
S-26	Manmade Feature in Bedrock (Plugged Test Hole, B-4)	2/18/2020	N30 8 55.0	W98 0 25.7	3335643	595747
S-27	Manmade Feature in Bedrock (Plugged Test Hole, B-5)	2/18/2020	N30 8 54.2	W98 0 24.8	3335643	595643
S-28	Manmade Feature in Bedrock (Plugged Test Hole, B-6)	2/18/2020	N30 8 53.6	W98 0 25.8	3335627	595616
S-29	Manmade Feature in Bedrock (Plugged Test Hole, B-7)	2/18/2020	N30 8 53.2	W98 0 24.1	3335615	595660
S-30	Manmade Feature in Bedrock (Plugged Test Hole, B-8)	2/18/2020	N30 8 52.9	W98 0 22.4	3335605	595707
S-31	Manmade Feature in Bedrock (Plugged Test Hole, B-9)	2/18/2020	N30 8 52.4	W98 0 20.8	3335590	595751
S-32	Manmade Feature in Bedrock (Plugged Test Hole, B-10)	2/18/2020	N30 8 51.9	W98 0 23.6	3335574	595674
S-33	Manmade Feature in Bedrock (Plugged Test Hole, B-11)	2/18/2020	N30 8 51.2	W98 0 21.9	3335552	595723
S-34	Manmade Feature in Bedrock (Plugged Test Hole, F-1)	2/18/2020	N30 8 51.8	W98 0 27.3	3335570	595577
S-35	Manmade Feature in Bedrock (Plugged Test Hole, F-1)	2/18/2020	N30 8 51.2	W98 0 24.7	3335553	595646

NOTES:

- 1) Geographic coordinates are presented Degrees, Minutes, Decimal Seconds
- 2) Reference Datum is NAD 83
- 3) Data were collected utilizing a Garmin GPS 60cx Global Positioning System
- 4) Horizontal Accuracy: RMS Value < 3 meter ground resolution
- 5) GPS data were collected by Chris Murrary and Kyle Gillespie (**RKI** Project Professionals).



ATTACHMENT D - Factors Affecting Surface Water Quality

Factors affecting water quality include oils, grease, and other substances typically associated with driving areas. Runoff will be treated as required by the TCEQ Environmental Regulations.

ATTACHMENT E – Volume and Character of Stormwater

The expected character of water generated from the site includes a mixture of water with sediment, hydrocarbons, and nutrients generally associated with vehicle traffic, landscaping and other urban improvements.

The 155.74-acre site has four main discharge points for stormwater. The combined 25-year peak flow under existing and developed conditions is 1,042 cfs and 997 cfs, respectively.

Developed conditions include two batch detention ponds with peak flow detention in accordance with TCEQ and City of Dripping Springs design criteria.

ATTACHMENT J – BMPs for Up Gradient Stormwater

Approximately 37 acres of off-site up-gradient stormwater flows onto the site from the north after crossing Darden Hill Road. The proposed project will divert this runoff around the site and discharge the flow near the southeast corner of the property. A 100-foot wide stream buffer centered on the diversion channel is required by the City of Dripping Springs development regulations to maintain the water quality of the downstream waterway.

ATTACHMENT K – BMPs for On-Site Stormwater

Permanent measures to capture and treat the required volumes of storm water runoff associated with the proposed school consist of a batch detention pond and vegetated filter strips designed in accordance with TCEQ's requirements including the Optional Enhanced Measures in RG-348 Appendix A.

ATTACHMENT L – BMPs for Surface Streams

As previously described, all site developed flows will be routed to the onsite BMPs prior to discharge into the existing intermittent drainageways on site. In accordance with the enhanced measures requirement, the peak 2-year release rate is less than 50% of the peak existing 2-year release rate. This helps to minimize streambank erosion of downstream surface streams.

ATTACHMENT M – Construction Plans

Construction plans are included with this application.

DRIPPING SPRINGS HIGH SCHOOL NO. 2

DRIPPING SPRINGS ISD DRIPPING SPRINGS, TEXAS

OWNER/DEVELOPER

DRIPPING SPRINGS ISD 300 SPORTSPLEX DRIVE DRIPPING SPRINGS, TX 78620 PH: (5120 382-3079 CONTACT: JAMES CONKLE

WALKER PARTNERS

ENGINEER:

6504 BRIDGE POINT PKWY, STE. 200 AUSTIN, TEXAS 78730-5091 PH: (512) 382-0021 CONTACT: DAVID P. SMITH, P.E., CFM

ARCHITECT

VLK ARCHITECTS, INC. 2700 VIA FORTUNA, STE. 230 AUSTIN, TEXAS 78746 PH: (512) 807-3145 CONTACT: BRIAN COTSWORTH, AIA

LANDSCAPE:

BLU FISH COLLABORATIVE P.O. BOX 40792 AUSTIN, TX 78704 PH: 512-388-4115 CONTACT: WHITNEY BLUNT, PLA, ASLA, LI

- 5.0 ACRES OF LOT 74, ONION CREEK RANCH SUBDIVISION (VOL. 8, PG 65 P.R.H.C.T. AND 150.74 ACRES OF DRIPPING SPRINGS (DOC. NO. 2010026988, O.P.R.) BEING OF THE FANNY A.D. DARDEN SURVEY ABSTRACT NO. 664 HAYS COUNTY, TEXAS.

WATERSHED:

- THIS PROJECT IS LOCATED WITHIN THE ONION CREEK WATERSHED.

FLOODPLAIN:

- NO PORTION OF THE SITE LIES WITHIN A DESIGNATED FLOODPLAIN. THE SITE LIES WITHIN 'ZONE X- AREA OF MINIMAL FLOOD HAZARD' ACCORDING TO FEMA FIRM PANEL NO. 48209C 0140G DATED JANUARY 17, 2025.

EDWARDS AQUIFER NOTE:

- ACCORDING TO TCEQ, THE PROPERTY IS WITHIN THE EDWARD'S AQUIFER CONTRIBUTING ZONE. STORM WATER QUALITY MEASURES (I.E. WATER QUALITY PONDS) ARE REQUIRED. THIS SITE IS UNDER THE MEMORANDUM OF UNDERSTANDING (M.O.U.) BETWEEN LCRA AND THE US FISH AND WILDLIFE SERVICES (USFWS). TO COMPLY WITH THE M.O.U., THE TCEQ'S OPTIONAL ENHANCED MEASURES WILL APPLY TO THE SITE AND TO THE DESIGN OF THE STORM WATER QUALITY MEASURES.

WATERS OF THE U.S.:

ZONING:

- THE PROPERTY IS IN THE CITY OF DRIPPING SPRINGS EXTRATERRITORIAL JURISDICTION (ETJ) AND IS NOT ZONED.

BENCHMARKS:

WATER & WASTEWATER:

- WATER SERVICE WILL BE PROVIDED BY THE WEST TRAVIS COUNTY PUBLIC UTILITY AGENCY - WASTEWATER TREATMENT AND DISPOSAL WILL BE PROVIDED BY AN ON-SITE TREATMENT

FACILITY AND ON-SITE LAND APPLICATION OF TREATED EFFLUENT (SEPARATE PERMIT).

ELECTRIC SERVICE:

- PEDERNALES ELECTRIC COOPERATIVE (PEC)

EASEMENT DOCUMENTS:

RELATED CASES:

- CYPRESS SPRINGS ELEMENTARY SCHOOL (SD 2020-1412) - WTCPUA PROJECT NUMBER 290-20-004

NOTES: 1. STORMWATER UTILITIES AND POND MAINTENANCE WILL BE PROVIDED BY OWNER.

2. THERE ARE NO PUBLIC STREETS PROPOSED WITHIN THE PROPERTY WITH THIS PERMIT. **WTCPUA NOTES:**

1. THE WEST TRAVIS COUNTY PUBLIC UTILITY AGENCY IS THE WATER PROVIDER. 2. ALL METERS FOR DOMESTIC PURPOSES ONLY.

3. WTCPUA DOES NOT GUARANTEE FIRE FLOW. 4. A WTCPUA REPRESENTATIVE MUST BE PRESENT AT THE TIME OF CONNECTION TO THE


EXISTING SYSTEM. 5. ALL WATER AND WASTEWATER INFRASTRUCTURE SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY OF AUSTIN WATER AND WASTEWATER CONSTRUCTION

SPECIFICATIONS AND WITH MATERIALS FROM THE CURRENT APPROVED CITY OF AUSTIN STANDARD PRODUCTS LIST (SPL).

!!! CAUTION !!! **EXISTING OVERHEAD UTILITIES IN VICINITY** CONTRACTOR SHALL EXERCISE EXTREME CAUTIO WHEN WORKING NEAR ELECTRIC FACILITIES

!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"



ORIGINAL SUBMITTAL DATE: #### DAVID P SMITH, P.E. 7/24/2025 **REVIEWED BY:** TORY CARPENTER CITY OF DRIPPING SPRINGS SITE DEVELOPMENT CHAD GILPIN CITY ENGINEER CITY OF DRIPPING SPRINGS SITE DEVELOPMENT PERMIT #SD2025-XXXX WTCPUA

HAYS COUNTY TRANSPORTATION DEPARTMENT

Sheet Number	Sheet Title
C0.0	COVER SHEET
C0.1	ABBREVIATIONS & LEGENDS
C0.2	CONSTRUCTION NOTES
C1.0	SHT_SURVEY - SURVEY (1 OF10)
C1.1	SHT_SURVEY - SURVEY (2 OF 10)
C1.2	SHT_SURVEY - SURVEY (3 OF 10)
C1.3	SHT_SURVEY - SURVEY (4 OF 10)
C1.4	SHT_SURVEY - SURVEY (5 OF 10)
C1.5	SHT_SURVEY - SURVEY (6 OF 10)
C1.6	SHT_SURVEY - SURVEY (7 OF 10)
C1.7	SHT_SURVEY - SURVEY (8 OF 10)
C1.8	SHT_SURVEY - SURVEY (9 OF 10)
C1.9	SHT_SURVEY - SURVEY (10 OF 10)
C2.0	EXISTING CONDITIONS AND DEMO PLAN
C3.0	EXISTING DRAINAGE AREA MAP
C3.1	PROPOSED DRAINAGE AREA MAP
C4.0	TEMP ESC PLAN - SECTION 1
C4.0	TEMP ESC PLAN - SECTION 1 TEMP ESC PLAN - SECTION 2
C4.1	TEMP ESC PLAN - SECTION 2 TEMP ESC PLAN - SECTION 3
C4.2	
C4.3	TEMP ESC PLAN - TREE LIST (1 OF 2) TEMP ESC PLAN - TREE LIST (2 OF 2)
	, ,
C5.0	OVERALL SITE PLAN
C5.1	SITE PLAN - SECTION 1
C5.2	SITE PLAN - SECTION 2
C5.3	SITE PLAN - SECTION 3
C5.4	SITE PLAN - SECTION 4
C5.5	SITE PLAN - SECTION 5
C5.6	SITE PLAN - SECTION 6
C5.7	SITE PLAN - SECTION 7
C5.8	SITE PLAN - SECTION 8
C5.9	SITE PLAN - SECTION 9
C5.10	PAVEMENT PLAN
C6.0	OVERALL GRADING PLAN
C6.1	GRADING PLAN - SECTION 1
C6.2	GRADING PLAN - SECTION 2
C6.3	GRADING PLAN - SECTION 3
C6.4	GRADING PLAN - SECTION 4
C6.5	GRADING PLAN - SECTION 5
C6.6	GRADING PLAN - SECTION 6
C6.7	GRADING PLAN - SECTION 7
C6.8	GRADING PLAN - SECTION 8
C6.9	GRADING PLAN - SECTION 9
C7.0	WATER PLAN - SECTION 1
C7.1	WATER PLAN - SECTION 2
C7.2	WATER PLAN - SECTION 3
C7.3	WATER PLAN - SECTION 4
C7.4	WATER PLAN - SECTION 5
C7.5	WATER PLAN - SECTION 6
C7.6	WATER PLAN - SECTION 7
C7.7	WATER PROFILE WL-A
C7.8	WATER PROFILE WL-B
C7.9	WATER PROFILE WL-C
C7.10	WATER PROFILE WL C1, C2 & C3
	,

Sheet List Table

|--|

ARCHITECT

2700 Via Fortuna, Suite 230

WASTEWATER PLAN - SECTION 1

WASTEWATER PLAN - SECTION 2

WASTEWATER PLAN - SECTION 3

STORM SEWER PLAN - SECTION 1

STORM SEWER PLAN - SECTION 2

STORM SEWER PLAN - SECTION 3

STORM SEWER PLAN - SECTION 4

STORM SEWER PLAN - SECTION 5

STORM SEWER PLAN - SECTION 6

STORM SEWER PLAN - SECTION 7

STORM SEWER PLAN - SECTION 8

POND 1 PLAN

POND 2 PLAN

POND DETAILS 1

POND DETAILS 2

CONSTRUCTION DETAILS (1 of 5)

CONSTRUCTION DETAILS (2 of 5)

CONSTRUCTION DETAILS (3 of 5)

CONSTRUCTION DETAILS (4 of 5)

CONSTRUCTION DETAILS (5 of 5)

C9.4

C9.7

Main Phone: 512.807.3145 www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Drawn By Quality Control Designer Designer

Checker PROJECT NO.

Proj. Arch.

23-134.00

COVER SHEET

SHEET NO.

SHTS IN CHANGE | SITE IMP. ADD (A) APPROVED **IMAGED** PLAN IPM. COVER IMP. NO. DESCRIPTION VOID (V) /DATE /DATE COVER SHEET NO.'S SET COVER



WTCPUA PROJECT NUMBER: 290-25-XXX

HAYS COUNTY TAX ID TRACT NUMBERS:

SAWYER RANCH WATER LINE) - 1420 HGL.

WTCPUA NOTE:

<u>10-0664-0047-00002-4</u> AND <u>11-6089-0000-07400-4</u>

WTCPUA 290 WATER SYSTEM GRID AT13, AU13 -- DARDEN HILL 16" WATER LINE IMPROVEMENTS (EXTENSION TO PROPOSED

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS

REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN

APPROVING THESE PLANS. THE CITY MUST RELY UPON THE

A WATER QUALITY BMP MAINTENANCE PLAN HAS BEEN

PREPARED FOR THIS DEVELOPMENT AND IS RECORDED IN DOCUMENT # _____, PUBLIC RECORDS OF HAYS COUNTY,

ADEQUACY OF WORK OF THE DESIGN ENGINEER.

ABBREVIATIONS

		1		,
ABS	ACRYLONITRILE-BU		(E)	EAST
	TADIENE-STYRENE		EP	EDGE OF PAVEMENT
ARV	AIR RELEASE VALVE		EA	EACH
ACP	ASBESTOS CEMENT		EF	EACH FACE
ALT	PIPE ALTERNATE		EIW	END INLET WING
			ELEC	ELECTRIC
AWG	AMERICAN WIRE		ELEV	ELEVATION
	GAGE		EJ	EXPANSION JOINT
BEG	BEGIN		ENG	ENGINEER
	_		R	LINGINELIX
BF	BLIND FLANGE		EQ	EQUAL
BFV	BUTTERFLY VALVE		ER	END RETURN
BIW	BEGIN INLET WING		ESM	EASEMENT
?	BASELINE		T	LAOLIVILIVI
BM	BENCH MARK		ETP	ELECTRIC
ВС	BACK OF CURB			TRANSFORMER PAS
BW	BOTTOM OF WALL		EW	EACH WAY
			EXC	EXCAVATE
CAT	CABLE TV		EX	EXISTING
V	 · ·			
СВ	CATCH BASIN		FDC	FIRE DEPARTMENT
C-C	CENTER TO CENTER			CONNECTION
CFS	CUBIC FEET PER		FEM	FEDERAL
_	SECOND		Α	EMERGENCY
CIP	CAST IRON PIPE			MANAGEMENT
CJ	CONTROL JOINT			AGENCY
?	CENTER LINE		FH	FIRE HYDRANT
CLR	CLEAR		FFE	FINISHED FLOOR
CO	CLEANOUT			ELEVATION
COE	CORPS OF		FG	FINISHED GRADE
COL	ENGINEERS		FL	FLOWLINE
CMP	CORRUGATED		FM	FORCE MAIN
	METAL PIPE		FOC	FIBER OPTIC CABLE
CON	CONCRETE		FC	FACE OF CURB
С			FG	FINISHED GRADE
CON	CONSTRUCTION		FT	FEET OR FOOT
ST			FH	FIRE HYDRANT
CON	CONTINUOUS			
CTB	CEMENT TREATED		G	GAS LINE
טוט	BASE		GA	GAUGE
CV	CHECK VALVE		GAL	GALVANIZED
CY	CUBIC YARD		V	GALVAINIZED
C&G	CURB AND GUTTER		GRN	GROUND
	COND AND OUT IEN		D	3.100115
Γ,			GV	GATE VALVE
DA	DRAINAGE AREA			
DRN	DRAINAGE		HDP	HIGH DENSITY
G DBL	DOUBLE		E	POLYETHYLENE
				PIPE
DET	DETAIL		HDW	HEADWALL
DIA	DIAMETER		L	
DI	DUCTILE IRON		HP	HIGH POINT OR
DIP	DUCTILE IRON PIPE		110:	HORSE POWER
DN	DOWN		HGL	HYDRAULIC GRADE
DRW	DRIVEWAY		ЦОП	LINE
Υ			HORI Z	HORIZONTAL
DWG	DRAWING		HW	HEAD WATER
			1177	TILAD VVATER

\sim	HOT MIXED
С	ASPHALTIC
	CONCRETE
ID	INCIDE DIAMETED
ID	INSIDE DIAMETER
IN	INCH
INCL	INCLUDE (D) (ING)
NSL	INSULATION OR
INV	INSULATED INVERT
IP	IRON PIPE OR IRON
11	PIN
JB	JUNCTION BOX
JT	JOINT
KV	KILOVOLT
L	LENGTH
LP	LOW POINT
LF	LINEAR FOOT
LG	LIP OF GUTTER
LSS	LIME-STABILIZED
LSS	SUBGRADE
LT	LEFT
MTL	MATERIAL
MAX	MAXIMUM
MBG	METAL BEAM
F	GAURD FENCE
MED	MEDIUM
MH	MANHOLE
MIN	MINIMUM
MISC	MISCELLANEOUS
M&M	MEET AND MATCH
МО	MOTOR OPERATED
MP	MIDPOINT
(N)	NORTH
NAD	NORTH AMERICAN
NAD 83	NORTH AMERICAN DATUM OF 1983
NAD 83 NAV	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN
NAD 83	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM
NAD 83 NAV	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN
NAD 83 NAV D 88	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED
NAD 83 NAV D 88 NC NFV	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED
NAD 83 NAV D 88 NC NFV NG	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND
NAD 83 NAV D 88 NC NFV NG NTS	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND NOT TO SCALE
NAD 83 NAV D 88 NC NFV NG NTS NIC	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND NOT TO SCALE NOT IN CONTRACT
NAD 83 NAV D 88 NC NFV NG NTS	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND NOT TO SCALE
NAD 83 NAV D 88 NC NFV NG NTS NIC	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND NOT TO SCALE NOT IN CONTRACT
NAD 83 NAV D 88 NC NFV NG NTS NIC NO	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND NOT TO SCALE NOT IN CONTRACT NORMALLY OPEN
NAD 83 NAV D 88 NC NFV NG NTS NIC NO	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND NOT TO SCALE NOT IN CONTRACT NORMALLY OPEN ON CENTER
NAD 83 NAV D 88 NC NFV NG NTS NIC NO	NORTH AMERICAN DATUM OF 1983 NORTH AMERICAN VERTICAL DATUM OF 1988 NORMALLY CLOSED NOT FIELD VERIFIED NATURAL GROUND NOT TO SCALE NOT IN CONTRACT NORMALLY OPEN ON CENTER OUTSIDE DIAMETER

OPP	OPPOSITE	(S)
		<u> </u>
OCE	ON CENTER EACH	SCH
W	WAY	SD
		SF
PC	POINT OF	SHT
	CURVATURE OR	
	PORTLAND CEMENT	SIM
PED	PEDESTRIAN	SPE
		C
PGL	PROPOSED GRADE	SQ
	LINE	STA
PI	POINT OF	
	INTERSECTION	STD
?	PROPERTY LINE	STR
POB	POINT OF	STR
_	BEGINNING	
POC	POINT OF	SW
1 00	COMMENCEMENT	
PP		SWE
	POWER POLE	T
PRC	POINT OF REVERSE	
	CURVATURE	SY
PRO	PROPOSED	SYM
Р		
PSI	POUNDS PER	SYS
	SQUARE INCH	
PT	POINT OF	TBA
1 1	TANGENCY	TBM
DLIE		
PUE	PUBLIC UTILITY	TE
	EASEMENT	TELE
PVC	POINT OF VERTICAL	
	CURVATURE OR	TEM
	POLYVINYL	Р
	CHLORIDE	THK
PVI	POINT OF VERTICAL	ТВ
	INTERSECTION	
PVM	PAVEMENT	TO
T		TC TC
PVT	POINT OF VERTICAL	TG
1 V I	TANGENCY	TN
DCC		TP
PCC	POINT OF	
	COMPOUND	TP&I
	CURVATURE	
		TxD
Q	FLOW RATE,	ОТ
	0 ,	
		TYP
R	RADIUS	TW
RCB	REINFORCED	1 7 7
	CONCRETE BOX	
RCP	REINFORCED	UE
	CONCRETE PIPE	
RD	ROAD	UNC
RE:	REFERENCE OR	
	REFER	
REIN	REINFORCE OR	
F	REINFORCED	VC
REQ	REQUIRED	VER
D		
REV	REVISION	
ROW		
- ₹ U J \/ \/	RIGHT-OF-WAY	(W)
	DIALIT	ı
RT	RIGHT	W
	RIGHT RADIUS POINT	<u> </u>
RT		W WB

(S)	SOUTH
SCH	SCHEDULE
SD	STORM DRAIN
SF	
	SQUARE FOOT
SHT	SHEET
SIM	SIMILAR
SPE	SPECIFICATION
С	
SQ	SQUARE
STA	STATION
STD	STANDARD
STR	STRUCTURAL
STR	STORM
M	
SW	SIDEWALK
SWB	SOUTHWESTERN
T	BELL TELEPHONE
	CO.
SY	SQUARE YARD
SYM	SYMMETRICAL
SYS	SYSTEM
TBA	TO BE ABANDONED
TBM	TEMPORARY
	BENCHMARK
TELE	TELECOMMUNICATI
COM	ONS
TEM P	TEMPORARY
THK	THICK
TB	TOP OF BANK
	(BERM)
TC	TOP OF CURB
TG	TOP OF GRATE
TN	TOP OF NUT
TP	TOP OF PAVEMENT
TP&L	TEXAS POWER AND
1	LIGHT
TxD	TEXAS
OT	DEPARTMENT OF
	TRANSPORTATION
TYP	TYPICAL
TW	TOP OF WALL
UE	UNDERGROUND
	ELECTRIC CABLE
UNO	UNLESS NOTED
	OTHERWISE
V	VELOCITY
VC	VERTICAL CURVE
VER T	VERTICAL
(W)	WEST
۱۸/	MATEDI INE


WATERLINE


WATER BIBB


W/O	WITHOUT
WM	WATER METER
WSE	WATER SURFACE
L	ELEVATION
WT	WEIGHT
WWF	WELDED WIRE
	FABRIC
WW	WASTEWATER


W/O	WITHOUT
WM	WATER METER
WSE	WATER SURFACE
L	ELEVATION
WT	WEIGHT
WWF	WELDED WIRE
	FABRIC
WW	WASTEWATER


UT	_
ETER	_
RFACE	_
ION	
НT	
WIRE	
IC	
'ATER	_












SURVEY CONTROL

	33/11/27/33/1
0	IRON ROD WITH CAP STAMPED "WALKER PARTNER
•	IRON ROD FOUND
	MONUMENT FOUND
	MONUMENT SET
0	IRON PIPE FOUND
Δ	NAIL FOUND
Ø	CUT "X" FOUND
•	BENCH MARK
À	CONTROL POINT

	CONTROL FOINT
	STORM DRAINAGE
⊞	STORM DRAIN GRATE
×	STORM ROOF DRAIN
(STORM DRAIN MANHOLE
—SD——SD—	STORM DRAIN LINE (< 12")
18" STRM	STORM DRAIN LINE (>12")



СО	SANITARY SEWERAGE
O	SANITARY SEWER (WW) CLEAN OUT
\mathbb{V}	SANITARY SEWER (WW) VENT
<u> </u>	SANITARY SEWER (WW) MANHOLE
− FM −− FM −	FORCE MAIN LINE
-wwww-	SANITARY SEWER (WW) LINE

	TELECOMN
FO	FIBER-OPTIC RISER
T	TELECOM RISER
TV	TELEVISION RISER
TCOM	TELECOM VAULT
\bigcirc	TELECOM MANHOLE
——FO——	FIBER OPTIC LINE
CTV	CABLE TELEVISION LINE

——OHT—— OVERHEAD TELECOM LINE

——UT—— UNDERGROUND TELECOM LINE

	ELEC
Α	AIR CONDITIONER UNIT
В	ELECTRIC BREAKER BOX
E	ELECTRIC METER
J	ELECTRIC JUNCTION BOX
E	ELECTRIC CABLE MARKER
EV	ELECTRIC VAULT
E	ELECTRIC MANHOLE
\leftarrow	GUY WIRE
- O-	UTILITY POLE
\Rightarrow	LIGHT POLE
0	YARD LAMP

- O-	UTILITY POLE	
ø	LIGHT POLE	
0	YARD LAMP	
—ОНЕ —	OVERHEAD ELECTRIC LINE	
— UE —	UNDERGROUND ELECTRIC	
		G
G	GAS METER	
G ⊠ G	GAS REGULATOR VALVE	
Ğ ♦	GAS PIPELINE MARKER	

GAS ANODE

G GAS MANHOLE

−G**−** GAS LINE

MATERIALS LEGEND



EARTH (COMPACTED) EARTH (UNDISTURBED) CONCRETE

SAND ASPHALT

MASONRY

GRATING CHECKERED PLATE

ALUMINUM

DRAWING NUMBER CONVENTION

FUTURE CONSTRUCTION

AUTOMATIC FLUSH VALVE

QUICK DISCONNECT COUPLER

CAPPED END OR PLUGGED END

AIR VACUUM AND AIR RELEASE ASSEMBLY

BLOW-OFF ASSEMBLY

CENTRIFUGAL OR TURBINE PUMP OR FAN

FIRE HYDRANT & VALVE

CLEANOUT TO GRADE

PROPOSED SPOT ELEVATION

MANHOLE

JUNCTION BOX

GATE VALVE

CHECK VALVE

PLUG VALVE

BLIND FLANGE


REDUCER OR INCREASER

BACKFLOW PREVENTOR

GRATE INLET

—— — BOUNDARY LINE

BUTTERFLY VALVE



RAWING TYPE	DESIGNATOR
ENERAL NOTES, LEGENDS, ABBREVIATIONS, MAPS, ETC.)	0
LANS; OVERALL PLANS; PLATS; ETC.	1
LAN & PROFILES; PROFILES; LARGE - SCALE VIEWS; ETC.	2
ECTIONS (SECTIONAL VIEWS, CROSS SECTIONS, ETC.); OR USER-DEFINED	3
ETAILS (PROJECT SPECIFIC)**	4
ETAILS (MUNICIPALITY STANDARDS)**	5
ETAILS (TxDOT STANDARD DETAILS)**	6
CHEDULES	7
SER DEFINED	8

DETAILS MAY BE IDENTIFIED BY AN "AREA CODE" OR A "DESIGNATOR"

ISSUED: July 28, 2025 REVISIONS Revision Date Revision No.

RING

Bid Package 2

Issue For Permitting,

Bidding and Construction

DAVID P SMITH

Director Drawn By Approver **Quality Control** Designer Designer Proj. Arch. Checker

> PROJECT NO. 23-134.00

SHEET TITLE **ABBREVIATIONS** & LEGENDS

COPYRIGHT © 2025 VLK ARCHITECTS, LLC

SHEET NO.



"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES

!!! WARNING !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR

SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE

AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

- AT THE TIME OF CONSTRUCTION. 2) WHERE PROPOSED FEATURES TIE TO EXISTING FEATURES, FIELD VERIFY EXISTING TOPOGRAPHY PRIOR TO
- EXVAVATION AND/OR CONSTRUCTION. CONSTRUCT (WALLS, WALKS, DRIVES, UTILITIES, ETC...) TO MATCH EXISTING LOCATION AND ELEVATION IN ACCORDANCE WITH INTENT OF DESIGN. CONTRACTOR TO NOTIFY ENGINEER IF
- DISCREPANCY EXISTS BETWEEN EXISTING FIELD VERIFIED TOPOGRAPHY AND TOPOGRAPHY SHOWN ON PLANS.

3) CONTRACTOR TO VERIFY LOCATION, DEPTH AND SIZE OF EXISTING UTILITIES PRIOR TO DEMOLITION AND

- CONSTRUCTION AND ENSURE CONTINUITY OF SERVICES AS NECESSARY. 4) ALL WORK IN PUBLIC EASEMENTS AND RIGHT-OF-WAYS SHALL BE PER APPLICABLE CITY, COUNTY, AND STATE
- STANDARD DETAILS AND SPECIFICATIONS. 5) ALL PUBLIC UTILITY CONSTRUCTION AND CONNECTIONS TO PUBLIC UTILITIES SHALL BE PER UTILITY OWNER'S
- STANDARD DETAILS AND SPECIFICATIONS. CONTACT UTILITY OWNER PRIOR TO START OF CONSTRUCTION AND COORDINATE TO ENSURE ACCEPTABLE PROCEDURES, DETAILS, AND SPECIFICATIONS ARE FOLLOWED
- 6) CONTRACTOR TO CONTACT THE CITY OF _____ UTILITY DEPARTMENT A MINIMUM OF 48 HOURS PRIOR TO WORK.
- CITY UTILITY DEPARTMENT MUST BE PRESENT DURING CONNECTION TO EXISTING WATER AND SEWER MAINS. 7) EXISTING LINE LOCATIONS ARE SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR BASED ON AVAILABLE
- INFORMATION, AND ARE NOT GUARANTEED TO BE CORRECT OR COMPLETE. 8) LOCATIONS OF EXISTING WATER, WASTEWATER, AND WASTEWATER FORCE MAIN ARE APPROXIMATE AND BASED ON
- DRAWINGS BY:_____ DATED:____ 9) WHERE FILL IS PROPOSED WITHIN 4 FEET ABOVE THE PROPOSED TOP OF UTILITY PIPE, COMPACTION OF FILL UP TO
- 4' ABOVE THE TOP OF PROPOSED PIPE IS REQUIRED PRIOR TO EXCAVATION AND INSTALLATION OF PIPE. 10) CONTRACTOR TO REPORT ANY DISCREPANCIES BETWEEN CIVIL AND M.E.P./ARCH/STRUCTURAL PLANS TO ENGINEERS
- AND ARCHITECT FOR RESOLUTION PRIOR TO THE INSTALLATION OF THE REPORTED ITEMS.

EXISTING CONDITIONS & DEMOLITION NOTES:

IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR BASED ON AVAILABLE INFORMATION. THIS INFORMATION IS NOT GUARANTEED TO BE CORRECT OR COMPLETE. LOCATIONS OF UNDERGROUND UTILITIES /STRUCTURES MAY VARY FROM LOCATIONS SHOWN HERE ON. ADDITIONAL BURIED UTILITIES/STRUCTURES, SUCH AS ELECTRICAL, TELEPHONE, CABLE, FIBER OPTICS, AND PIPE LINES, MIGHT BE ENCOUNTERED. NO EXCAVATIONS WERE MADE DURING THE PROGRESS OF THE SURVEY TO LOCATE BURIED UTILITIES/STRUCTURES. FOR INFORMATION REGARDING BURIED UTILITIES/STRUCTURES OR BEFORE ANY EXCAVATION IS BEGUN, PLEASE CONTACT THE APPROPRIATE

1) UTILITY INFORMATION SHOWN HEREON CONSTITUTES A FIELD RECOVERY OF OBSERVED EVIDENCE OF UTILITIES AND

- AGENCIES FOR VERIFICATION OF UTILITY TYPE AND FOR FIELD LOCATION. 2) CONTRACTOR TO VERIFY LOCATION AND DEPTH OF EXISTING UTILITIES PRIOR TO DEMOLITION AND CONSTRUCTION
- AND ENSURE CONTINUITY OF SERVICE AS NECESSARY. 3) TREES SHOWN ON THE TREE LIST AND ON THIS PLAN ARE THOSE REQUIRED TO BE LOCATED PER THE CURRENT ORDINANCE. OTHER TREES MAY EXIST ON SITE AND ARE TO BE REMOVED IF WITHIN THE LIMITS OF CONSTRUCTION, UNLESS OTHERWISE INDICATED ON THESE PLANS.

AND UTILITIES, AND/OR PROTECTION AND SUPPORT/RELOCATION OF EXISTING FEATURES AND UTILITIES.

- 4) PROPOSED CONSTRUCTION AND DEMOLITION MAY REQUIRE HAND DIGGING FOR INSTALLATIONS OF NEW FEATURES
- 5) REFER TO M.E.P. SITE DEMO PLANS FOR ALL ELECTRIC, TELEPHONE, AND GAS UTILITIES
- REMOVE AND RELOCATE ALL EXISTING SIGNAGE, FENCING, AND GATES AS NECESSARY.
- 7) PROVIDE AND MAINTAIN A.D.A. ACCESSIBILITY TO FACILITIES THAT ARE TO REMAIN IN USE DURING CONSTRUCTION. 8) CONTRACTOR TO MAINTAIN ALL EXISTING WATER AND WASTEWATER SERVICES WITHIN THE EXTENTS OF THIS PROJECT UNTIL EITHER FACILITIES (SUCH AS BUILDINGS, IRRIGATION SYSTEMS, HOSE BIBS, ETC.) SERVED BY THESE

SERVICES ARE REMOVED/VACATED, OR UNTIL NEW OR ALTERNATIVE SERVICES ARE PROVIDED. THE CONTRACTOR

SHALL COORDINATE WITH, AND NOTIFY THE OWNER AHEAD OF SERVICE INTERRUPTIONS SHOULD INTERRUPTIONS BE

NECESSARY. **EROSION-SEDIMENTATION CONTROL NOTES:**

- 1. UNLESS OTHERWISE INDICATED ON THE LANDSCAPE PLANS AND SPECIFICATIONS:
- i) ALL DISTURBED AREAS AND AREAS DESIGNATED AS "GRASS" AREAS SHALL RECEIVE A MINIMUM OF 4" OF TOP SOIL AND BE REVEGETATED BY SEED, HYDROMULCH, OR SOD. MAINTAIN AND WATER THESE AREAS AS NECESSARY TO ESTABLISH PERMANENT REVEGETATIVE GROWTH OF APPROXIMATELY TWO (2) INCHES OF HEIGHT OVER 70% OF AREA
- ii) TOPSOIL THAT HAS BEEN STRIPPED FROM THE SITE AND STOCKPILED MAY BE USED. REMOVE ALL BRUSH, TRASH, STUMPS, WOOD, CONCRETE AND OTHER DEBRIS OVER 1-1/2" IN SIZE PRIOR TO SPREADING.
- iii) IF SUFFICIENT QUANTITIES ARE NOT AVAILABLE, PROVIDE IMPORTED TOPSOIL CHARACTERISTIC OR THE AREA. PROVIDE IMPORTED LOAM TOPSOIL CONTAINING A MINIMUM ORGANIC MATTER CONTENT BY WEIGHT OF 5%. TOPSOIL SHALL NOT HAVE A MIXTURE SUBSOIL AND SHALL CONTAIN NO STONES, LUMPS OF SOIL, STICKS, ROOTS, TRASH OR OTHER EXTRANEOUS MATERIALS LARGER THAN 1-1/2 INCHES IN DIAMETER OR
- iv) . APPLY TOPSOIL TO ENSURE A MINIMUM OF 4" DEPTH IN ALL DISTURBED AREAS. TILL SOIL TO A DEPTH OF 2 INCHES. RAKE SOIL SMOOTH, FREE FROM VARIATIONS, BUMPS AND DEPRESSIONS TO FINISH GRADE (1" BELOW WALKS AND CURBS). ALL AREAS SHALL SLOPE TO DRAIN.
- 2) ALL PROPOSED STORM INLETS TO HAVE INLET PROTECTION.
- 3) ADDITIONAL ENVIRONMENTAL CONTROLS MAY BE REQUIRED BY THE CITY AND OR COUNTY INSPECTOR AS CONSTRUCTION PROGRESSES.
- 4) CONCRETE "WASHOUT" LOCATIONS TO BE DETERMINED IN THE FIELD IN COORDINATION WITH CITY/COUNTY INSPECTOR. WASHOUT LOCATIONS ARE TO BE NOTED IN THE SWPPP.
- 5) CONTRACTOR TO PUMP OUT WATER FROM DETENTION POND UNTIL POND CONSTRUCTION IS COMPLETE. PUMPED WATER MUST PASS THROUGH 2 ROWS OF SILT FENCE PRIOR TO BEING RELEASED DOWNSTREAM.

SPOILS MANAGEMENT AND DISPOSAL NOTES

EROSION / SEDIMENTATION CONTROL NOTES

STANDARD TREE PROTECTION NOTES

HOURS OF CONSTRUCTION

the case of an emergency.

shown on the Plans.

Erosion/Sedimentation Controlnotes, as appropriate.

Erosion/Sedimentation Control notes, as appropriate

on the plans.

governing authority.

6) ALL PRESERVED TREES SHALL BE FLAGGED WITH ORANGE FLUORESCENT VINYL TAPE TO BE WRAPPED AROUND THE MAIN TRUNK AT A HEIGHT OF FOUR (4) FEET OR MORE SO THAT THE TAPE IS VISIBLE TO WORKERS OPERATING CONSTRUCTION EQUIPMENT.

SITE PLAN NOTES: 1) ALL DIMENSIONS ARE FROM FACE OF CURB TO FACE OF CURB UNLESS OTHERWISE NOTED.

7) USE APPROVED SLOPE STABILIZATION MATTING SUCH AS PYRAMAT ON ALL SLOPES STEEPER THAN 3:1.

- 2) ALL CURB RETURNS SHALL BE 3' RADIUS UNLESS OTHERWISE NOTED.
- 3) FIRE LANE MARKINGS DESIGNATED HEREIN SHALL CONSIST OF A 6" WIDE RED STRIPE APPLIED EITHER ON THE FACE OF CURB OR THE PAVEMENT SURFACE AS APPROPRIATE. THE RED STRIPE SHALL BE MARKED WITH "FIRE LANE - NO PARKING - TOW AWAY ZONE" IN WHITE LETTERS AT LEAST 3" TALL AT A 30' MAXIMUM INTERVAL. UNLESS OTHERWISE SPECIFIED WITHIN THIS PLAN SET.
- 4) PAVEMENT STRIPING SHALL BE WHITE PAINT, 4" WIDE.
- 6) WHERE CONSTRUCTION IS PROPOSED ADJACENT TO EXISTING BUILDINGS, ENSURE THAT EXISTING WEEP HOLES ARE NOT COVERED. CONTACT ENGINEER AND ARCHITECT PRIOR TO CONSTRUCTION SHOULD SUCH A CONFLICT ARISE.

5) COORDINATE KNOX BOX REQUIREMENTS WITH THE APPROPRIATE CITY/COUNTY FIRE DEPARTMENT.

7) REFER TO STRUCTURAL PLANS FOR ALL WALL DETAILS. 8) AT NEW PAVEMENT TIE IN LOCATION, SAWCUT A MINIMUM OF 1' BEHIND AND ALONG THE EDGE OF EXISTING

PAVEMENT AS NECESSARY FOR A CLEAN, AND STRUCTURALLY SOUND TIE IN.

GRADING PLAN NOTES

- 1) ALL SIDEWALK AND CROSSWALK SLOPES SHALL NOT EXCEED THE FOLLOWING A.D.A. REQUIREMENTS:
- 1:20 LONGITUDINAL (ALONG THE WALK) MAX. ii) 1:50 TRANSVERSE (ACROSS THE WALK) MAX.
- 2) ALONG AN ACCESSIBLE ROUTE, CHANGES IN LEVEL UP TO 1/4" MAY BE VERTICAL AND WITHOUT EDGE TREATMENT, CHANGES IN LEVEL BETWEEN 1/4" AND 1/2" SHALL BE BEVELED WITH A SLOPE NO GREATER THAN 1:2, AND CHANGES IN LEVEL GREATER THAN 1/2" SHALL BE ACCOMPLISHED BY MEANS OF AN ACCESSIBLE RAMP.
- 3) ALL SIDEWALKS ALONG CURB TO SLOPE TOWARDS CURB (2% MAX) 4) ADJUST ALL CASTINGS TO PROPOSED GRADES.
- 5) SEE STORM SEWER PLANS FOR ALL TOP OF INLET ELEVATIONS.
- 6) COORDINATE WITH STRUCTURAL FOUNDATION PLANS AND DETAILS FOR EXTENTS AND GRADES AT ALL STRUCTURAL
- 7) SLOPES STEEPER THAN 3:1 SHALL BE STRUCTURALLY STABILIZED UNLESS OTHERWISE NOTED.
- 8) INSTALL EDGE PROTECTION PER TAS FOR ALL ACCESSIBLE ROUTES THAT ARE HIGHER THAN ADJACENT FINISHED 9) INSTALL SAFETY RAILING OR CHAINLINK FENCING, FOR ALL SIDEWALKS, RETAINING WALLS, POND WALLS WITH VERTICAL ELEVATION CHANGES OF MORE THAN 30-INCHES.

STORM SEWER PLAN NOTES:

- 1) COORDINATE WITH M.E.P. PLANS FOR EXISTING UTILITY DEMO PLANS.
- 2) COORDINATE WITH M.E.P. PLANS FOR ALL WATER, WASTEWATER, AND STORM CONNECTIONS AT BUILDINGS. 3) COORDINATE WITH M.E.P. PLANS AND INSTALL NECESSARY FITTINGS FOR CONNECTIONS OF STORM SYSTEM TO ROOF DRAINS AND DOWNSPOUTS.
- 4) T/INET = FINISHED GRADE FOR CURB INLETS AND GRATE INLETS.
- 5) STORM SEWER LINES 30" OR LARGER SHALL BE CLASS III RCP PIPE. ALL OTHER PIPES TO BE HDPE OR PVC SDR 35 UNLESS OTHERWISE NOTED.

6) ALL DOWNSPOUT LATERAL PIPES TO HAVE A MINIMUM SLOPE OF 1% UNLESS OTHERWISE SPECIFIED.

7) COORDIDNATE WITH ARCH/LANDSCAPE FOR PLANTER DRAIN LOCATIONS NOT SHOWN HEREON. THE PLANTER DRAINS TO DOWNSPOUT COLLECTOR LINES.

WATER & WASTEWATER PLAN NOTES:

- 1) CONTRACTOR TO CONTACT UTILITY OWNER FOR COORDINATION PRIOR TO INSTALLATION OF NEW, OR RELOCATION/REMOVAL OF EXISTING WATER METERS.
- 2) COORDINATE WITH M.E.P. PLANS FOR EXISTING UTILITY DEMO PLANS.
- 3) MUNICIPAL WATER LINES ARE TO BE CONSTRUCTED IN ACCORDANCE WITH THE "RULES AND REGULATIONS FOR PUBLIC WATER SYSTEMS", SECTION 290, AS ADOPTED BY THE T.C.E.Q.
- 4) SANITARY SEWER LINES ARE TO BE CONSTRUCTED IN ACCORDANCE WITH CHAPTER 217, "DESIGN CRITERIA FOR DOMESTIC WASTEWATER SYSTEMS" AS ADOPTED BY THE T.C.E.O. 5) WHERE WATER LINES AND NEW SEWER LINES ARE INSTALLED WITH A SEPARATION DISTANCE CLOSER THAN NINE FEET
- (I.E. WATER AND WASTEWATER LINES, OR WATER LINES NEXT TO MANHOLES) THE INSTALLATION MUST MEET THE REQUIREMENTS OF 30 TAC 217.53 OR 30 TAC 290.44(E) (WATER HYGIENE).
- 6) WATER LINES TO BE AWWA C900 DR 14 UNLESS OTHERWISE NOTED. 7) FIRE HYDRANT LEADS TO BE D.I. PIPE.
- 8) WASTEWATER LINES TO BE SDR 26 PVC GRAVITY SEWER PIPE, WITH A MINIMUM SLOPE OF 1.0% UNLESS OTHERWISE
- 9) ALL ON-SITE UTILITY MATERIALS AND WORK SHALL CONFORM TO THE CURRENT PLUMBING CODE. 10) COORDINATE WITH M.E.P. PLANS FOR ALL WATER, WASTEWATER, AND STORM SEWER CONNECTIONS AT BUILDING.

TCEQ WATER STORAGE TANK GENERAL **CONSTRUCTION NOTES**

- The water storage tank must be constructed in accordance with the current Texas Commission on Environmental Quality (TCEQ) Rules and Regulations for Public Water Systems 30 Texas Administrative Code (TAC) Chapter 290 Subchapter D. When conflicts are noted with local standards, the more stringent requirement shall be applied. At a minimum, construction for public water systems must always meet TCEQ's "Rules and Regulations for Public Water Systems."
- All facilities for potable water storage shall be covered and designed, fabricated, erected, tested and disinfected in strict accordance with current American Water Works Association (AWWA) standards and shall be provided with the minimum number, size and type of roof vents, man ways, drains, sample connections, access ladders, overflows, liquid level indicators on-site, and other appurtenances as specified in these rules.
- Disinfection of water storage facilities shall be in strict accordance with current AWWA Standard C652-11 or most recent
- Dechlorination of disinfecting water shall be in strict accordance with current AWWA Standard C655-09 or most recent.

Bolted tanks shall be designed, fabricated, erected and tested in strict accordance with

- current AWWA Standard D103. Welded tanks shall be designed, fabricated, erected and tested in strict accordance with current AWWA Standard D100. The roof of all metal tanks shall be designed and erected so that no water ponds at any point on the roof and, in addition, no area of the roof shall have a slope of less than 0.75 inch per foot Concrete tank roofs shall be constructed in strict compliance with their respective
- Roof vents shall be installed in strict accordance with current AWWA standards and shall be equipped with approved screens to prevent entry of animals, birds, insects and heavy air contaminants. Screens shall be fabricated of corrosion resistant material and shall be 16 mesh or finer. Screens shall be securely clamped in place with stainless or galvanized bands or wires and shall be designed to withstand winds of not less than tank design criteria (unless specified otherwise by the engineer).
- All roof openings shall be designed in accordance with current AWWA standards. If an alternate 30 inch diameter access opening is not provided in a storage tank, the primary roof access opening shall not be less than 30 inches in diameter. Other roof openings required only for ventilating purposes during cleaning, repairing or painting operation shall be not less than 24 inches in diameter or as specified by the licensed professional engineer. An existing tank without a 30-inch in diameter access opening must be modified to meet this requirement when major repair or maintenance is performed on the tank. Each access opening shall have a raised curbing at least four inches in height with a lockable cover that overlaps the curbing at least two inches in a downward direction. Where necessary, a gasket shall be used to make a positive seal when the hatch is closed. All hatches shall remain locked except during inspections and
- Overflows shall be designed in strict accordance with current AWWA standards and shall terminate with a gravity-hinged and weighted cover, an elastomeric duckbill valve, or other approved device to prevent the entrance of insects and other nuisances. The cover shall fit tightly with no gap over 1/16 inches. If the overflow terminates at any point other than the ground level, it shall be located near enough and at a position accessible from a ladder or the balcony for inspection purposes. The overflow(s) shall be sized to handle the maximum possible fill rate without exceeding the capacity of the overflow(s). The discharge opening of the overflow(s) shall be above the surface of the ground and shall not be subject to submergence.
- tank site. The indicator can be a float with a moving target, an ultrasonic level indicator or a pressure gauge calibrated in feet of water. If an elevated tank or standpipe has a float with moving target indicator, it must also have a pressure indicator located at ground level. Pressure gauges must not be less than three inches in diameter and calibrated at not more than two-foot intervals. Remote reading gauges at the owner's treatment plant or pumping station will not eliminate the requirement for a gauge at the tank site unless the tank is located at the plant or station.

All clearwells and water storage tanks shall have a liquid level indicator located at the

- Inlet and outlet connections shall be located so as to prevent short circuiting or stagnation of water. Clearwells used for disinfectant contact time shall be appropriately
- Clearwells and potable water storage tanks shall be thoroughly tight against leakage. shall be located above the ground water table and shall have no walls in common with any other plant units containing water in the process of treatment. All associated appurtenances including valves, pipes and fittings shall be tight against leakage.
- Each clearwell or potable water storage tank shall be provided with a means of removing accumulated silt and deposits at all low points in the bottom of the tank. Drains shall not be connected to any waste or sewage disposal system and shall be constructed so that they are not a potential agent in the contamination of the stored water.
- 13. All clear wells, ground storage tanks, standpipes, and elevated tanks shall be painted, disinfected, and maintained in strict accordance with current AWWA standards. However, no temporary coatings, wax grease coatings, or coating materials containing lead will be allowed. No other coatings will be allowed which are not approved for use (as a contact surface with potable water) by the United States Environmental Protection DA). All newly installed coatings must conform to ANSI/NSF International Standard 61 and must be certified by an organization accredited by ANSI.
- 4. No tanks or containers shall be used to store potable water that has previously been used for any non-potable purpose. Where a used tank is proposed for use, a letter from the previous owner or owners must be submitted to the Commission which states the
- Access manways in the riser pipe, shell area, access tube, bowl area or any other location opening directly into the water compartment shall be located in strict accordance with current AWWA standards. These openings shall not be less than 24 inches in diameter. However, in the case of a riser pipe or access tube of 36 inches in diameter or smaller, the access manway may be 18 inches times 24 inches with the vertical dimension not less than 24 inches. The primary access manway in the lower ring or section of a ground storage tank shall be not less than 30 inches in diameter. Where necessary, for any access manyay which allows direct access to the water compartment. a gasket shall be used to make a positive seal when the access manway is closed.
- 6. Service pump installation taking suction from storage tanks shall provide automatic low water level cutoff devices to prevent damage to the pumps. The service pump circuitry shall also resume pumping automatically once the minimum water level is reached in
- Pursuant to 30 TAC §290.44(b)(1), the maximum allowable lead content of pipes, pipe fittings, plumbing fittings, and fixtures is 0.25 percent.

Texas Commission on Environmental Quality Contributing Zone Plan General Construction Notes

Edwards Aguifer Protection Program Construction Notes - Legal Disclaimer

CITY OF DRIPPING SPRINGS

STANDARD WASTEWATER UTILITY CONSTRUCTION NOTES

All wastewater lines shall be constructed in accordance with City of Austin

Contractor shall guarantee the Work against defective workmanship and

materials for a period of two (2) years from the date of final acceptance of

i. Bedding for gravity wastewater lines, force mains, and treated effluent lines

shall be 3/4" to 1" rock with a 6 ounce nonwoven geotextile fabric, meeting

either TxDOT DMS 6200 or Type 1 COA 620S, placed over the bedding.

iv. When groundwater is encountered during construction, recommendations

on bedding and backfill shall be provided by a Geotechnical Engineer

before proceeding with construction. All recommendations shall be

vi. Gravity Wastewater lines shall be PVC SDR 26 ASTM D3034 if located

v. Contractor shall adhere to City of Austin standard 1100S-1 for wastewater

greater than 9 feet from a waterline. If less than 9 feet (outside of pipe to

outside of pipe) from any water line, pipe shall be PVC SDR 26 ASTM

vii. Force Mains shall be minimum PVC SDR 26 ASTM D2241 pressure rated

viii. Treated effluent lines shall be minimum PVC SDR 21 ASTM D2241 purple

ix. All wastewater manholes are to be coated with cementitious lining

shall be coated or recoated after connections are made.

inspector identified at the preconstruction meeting.

City of Dripping Springs prior to acceptance.

minimum first course of base is installed.

of 1.5 times working pressure for 24 hours.

manholes when connecting to existing facilities.

xvi. Gravity wastewater lines and services – low pressure air test.

regarding water line and water service line crossings.

(Sewpercoat® or approved equal) per City of Austin requirements.

Existing manholes where connections are made to the City Sewer System

Engineer and Contractor shall coordinate with the Dripping Springs WSC

xi. Contractor shall install bolted manhole lids on all manholes outside

xii. Wastewater manhole lids shall have "Sanitary Sewer" cast in the lid.

xiii. City of Dripping Springs' inspector shall observe installation of all taps onto

xiv. City of Dripping Springs' inspector shall be notified 48 hours prior to all

utility line testing by calling the City 512-858-4725 or the designated

xv. Contractor shall perform the following testing on all types of wastewater

xvii. Gravity wastewater lines – mandrel deflection testing after 30 days of final

xviii. Gravity wastewater lines – televised upon completion of construction

xix. Wastewater manholes – vacuum test @ 10 psi for 3 minutes. No vacuum

xx. Force mains and treated effluent lines – hydrostatically test to a minimum

xxi. Existing wastewater facilities – pretest and posttest existing lines and

and prior to paving. Contractor shall provide the videos of the pipes to the

testing will be accepted by the City of Dripping Springs until completion of

Contractor shall provide a minimum 5 gallon bucket sample of the

proposed bedding material for City of Dripping Springs approval.

FEBRUARY 2017

and TCEQ 30 TAC, Chapter 217 requirements.

the Work by the City of Dripping Springs.

approved by the City of Dripping Springs.

manhole ring adjustments in paved areas.

D2241 pressure rated pipe.

pipe in brown poly bag.

pressure rated pipe

wastewater lines.

improvements at his expense:

The following/listed "construction notes" are intended to be advisory in nature only and do not constitute an approval or conditional approval by the Executive Director (ED), nor do they constitute a comprehensive listing of rules or conditions to be followed during construction. Further actions may be required to achieve compliance with TCEQ regulations found in Title 30, Texas Administrative Code (TAC), Chapters 213 and 217, as well as local ordinances and regulations providing for the protection of water quality. Additionally, nothing contained in the following/listed "construction notes" restricts the powers of the ED, the commission or any other governmental entity to prevent, correct, or curtail activities that result or may result in pollution of the Edwards Aquifer or hydrologically connected surface waters. The holder of any Edwards Aquifer Protection Plan containing "construction notes" is still responsible for compliance with Title 30, TAC, Chapters 213 or any other applicable TCEQ regulation, as well as all conditions of an Edwards Aquifer Protection Plan through all phases of plan implementation. Failure to comply with any condition of the ED's approval, whether or not in contradiction of any "construction notes," is a violation of TCEQ regulations and any violation is subject to administrative rules, orders, and penalties as provided under Title 30, TAC § 213.10 (relating to Enforcement). Such violations may also be subject to civil penalties and injunction. The following/listed "construction notes" in no way represent an approved exception by the ED to any part of Title 30 TAC, Chapters 213 and 217, or any other TCEQ applicable regulation

- A written notice of construction must be submitted to the TCEQ regional office at least 48 hours prior to the start of any ground disturbance or construction activities. This notice must - the name of the approved project; the activity start date: and - the contact information of the prime contractor.
- All contractors conducting regulated activities associated with this project should be provided with complete copies of the approved Contributing Zone Plan (CZP) and the TCEQ letter indicating the specific conditions of its approval. During the course of these regulated activities, the contractor(s) should keep copies of the approved plan and approval letter on-
- No hazardous substance storage tank shall be installed within 150 feet of a water supply source, distribution system, well, or sensitive feature. Prior to beginning any construction activity, all temporary erosion and sedimentation (E&S)
- control measures must be properly installed and maintained in accordance with the manufacturers specifications. If inspections indicate a control has been used inappropriately. or incorrectly, the applicant must replace or modify the control for site situations. These controls must remain in place until the disturbed areas have been permanently stabilized.
- Any sediment that escapes the construction site must be collected and properly disposed of before the next rain event to ensure it is not washed into surface streams, sensitive features
- Sediment must be removed from the sediment traps or sedimentation basins when it occupies 50% of the basin's design capacity.
- Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from being discharged offsite.
- All excavated material that will be stored on-site must have proper E&S controls. If portions of the site will have a cease in construction activity lasting longer than 14 days, soil stabilization in those areas shall be initiated as soon as possible prior to the 14th day of inactivity. If activity will resume prior to the 21st day, stabilization measures are not required. If drought conditions or inclement weather prevent action by the 14th day, stabilization measures shall be initiated as soon as possible.
- The following records should be maintained and made available to the TCEQ upon request: the dates when major grading activities occur; - the dates when construction activities temporarily or permanently cease on a portion of the site: and the dates when stabilization measures are initiated
- 11. The holder of any approved CZP must notify the appropriate regional office in writing and obtain approval from the executive director prior to initiating any of the following:
- any physical or operational modification of any best management practices (BMPs) or structure(s), including but not limited to temporary or permanent ponds, dams, berms, silt fences, and diversionary structures;
- any change in the nature or character of the regulated activity from that which was
- any change that would significantly impact the ability to prevent pollution of the
- any development of land previously identified as undeveloped in the approved contributing zone plan.


Austin Regional Office San Antonio Regional Office 12100 Park 35 Circle, Building A 14250 Judson Road Austin, Texas 78753-1808 San Antonio, Texas 78233-4480 Phone (512) 339-2929 Phone (210) 490-3096 Fax (512) 339-3795

TCEQ WATER DISTRIBUTION SYSTEM **GENERAL CONSTRUCTION NOTES** (Revised February 2019 or latest version)

- 1. This water distribution system must be constructed in accordance with the current Texas Commission on Environmental Quality (TCEQ) Rules and Regulations for Public Water Systems 30 Texas Administrative Code (TAC) Chapter 290 Subchapter D. When conflicts are noted with local standards, the more stringent requirement shall be applied. At a minimum, construction for public water systems must always meet TCEQ's "Rules and Regulations for Public Water
- 2. All newly installed pipes and related products must conform to American National Standards Institute (ANSI)/NSF International Standard 61 and must be certified by an organization
- accredited by ANSI [§290.44(a)(1)]. 3. Plastic pipe for use in public water systems must bear the NSF International Seal of Approval
- (NSF-pw) and have an ASTM design pressure rating of at least 150 psi or a standard dimension ratio of 26 or less [§290.44(a)(2)].
- 4. No pipe which has been used for any purpose other than the conveyance of drinking water shall be accepted or relocated for use in any public drinking water supply [§290.44(a)(3)].
- All water line crossings of wastewater mains shall be perpendicular [§290.44(e)(4)(B)].
- 6. Water transmission and distribution lines shall be installed in accordance with the manufacturer's instructions. However, the top of the water line must be located below the frost line and in no case shall the top of the water line be less than 24 inches below ground surface [§290.44(a)(4)].
- 7. The maximum allowable lead content of pipes, pipe fittings, plumbing fittings, and fixtures is 0.25 percent [§290.44(b)].
- 8. The contractor shall install appropriate air release devices with vent openings to the atmosphere covered with 16-mesh or finer, corrosion resistant screening material or an acceptable equivalent [§290.44(d)(1)].
- 9. The contractor shall not place the pipe in water or where it can be flooded with water or sewage during its storage or installation [§290.44(f)(1)].

10. When waterlines are laid under any flowing or intermittent stream or semi-permanent body

- of water the waterline shall be installed in a separate watertight pipe encasement. Valves must be provided on each side of the crossing with facilities to allow the underwater portion of the system to be isolated and tested [§290.44(f)(2)].
- 11. Pursuant to 30 TAC §290.44(a)(5), the hydrostatic leakage rate shall not exceed the amount allowed or recommended by the most current AWWA formulas for PVC pipe, cast iron and ductile iron pipe. Include the formulas in the notes on the plans.
- The hydrostatic leakage rate for polyvinyl chloride (PVC) pipe and appurtenances shall not exceed the amount allowed or recommended by formulas in America Water Works Association (AWWA) C-605 as required in 30 TAC §290.44(a)(5). Please ensure that the formula



- Q = the quantity of makeup water in gallons per hour,
- L = the length of the pipe section being tested, in feet, D = the nominal diameter of the pipe in inches, and

for this calculation is correct and most current formula is in use;

- P = the average test pressure during the hydrostatic test in pounds per square inch (psi). o The hydrostatic leakage rate for ductile iron (DI) pipe and appurtenances shall not exceed the
- amount allowed or recommended by formulas in America Water Works Association (AWWA) C-600 as required in 30 TAC §290.44(a)(5). Please ensure that the formula for this calculation is correct and most current formula is in use:



- L = the quantity of makeup water in gallons per hour, S = the length of the pipe section being tested, in feet,
- D = the nominal diameter of the pipe in inches, and
- P = the average test pressure during the hydrostatic test in pounds per square inch (psi) 12. The contractor shall maintain a minimum separation distance in all directions of nine feet
- between the proposed waterline and wastewater collection facilities including manholes. If this distance cannot be maintained, the contractor must immediately notify the project engineer for further direction. Separation distances, installation methods, and materials utilized must meet §290.44(e)(1)-(4).
- 13. The separation distance from a potable waterline to a wastewater main or lateral manhole or cleanout shall be a minimum of nine feet. Where the nine-foot separation distance cannot be achieved, the potable waterline shall be encased in a joint of at least 150 psi pressure class pipe at least 18 feet long and two nominal sizes larger than the new conveyance. The space around the carrier pipe shall be supported at five-foot intervals with spacers or be filled to the springline with washed sand. The encasement pipe shall be centered on the crossing and both ends sealed with cement grout or manufactured sealant [§290.44(e)(5)].
- 4. Fire hydrants shall not be installed within nine feet vertically or horizontally of any wastewater line, wastewater lateral, or wastewater service line regardless of construction [§290.44(e)(6)].
- 15. Suction mains to pumping equipment shall not cross wastewater mains, wastewater laterals, or wastewater service lines. Raw water supply lines shall not be installed within five feet of any tile or concrete wastewater main, wastewater lateral, or wastewater service line [§290,44(e)(7)].
- 16. Waterlines shall not be installed closer than ten feet to septic tank drainfields [§290.44(e)(8)].
- 17. The contractor shall disinfect the new waterlines in accordance with AWWA Standard C-651-14 or most recent, then flush and sample the lines before being placed into service. Samples shall be collected for microbiological analysis to check the effectiveness of the disinfection procedure which shall be repeated if contamination persists. A minimum of one sample for each 1,000 feet of completed waterline will be required or at the next available sampling point beyond 1,000 feet as designated by the design engineer [§290.44(f)(3)].
- 18. Dechlorination of disinfecting water shall be in strict accordance with current AWWA

the current adopted version of all notes is included in the construction plans.

Standard C655-09 or most recent. OTHER NOTES – Engineer is responsible for including all applicable notes, including but not limited to County, City, TxDOT, State, Fire Department, OSHA, TCEQ (CZP, WPAP, Organized Sewage Collection System Notes, General Construction Notes). Engineer is responsible for ensuring

Bid Package 2 Issue For Permitting



REVISIONS Revision No. Revision Date

Drawn By Designer Quality Control Designer

> PROJECT NO. 23-134.00

SHEET TITLE CONSTRUCTION NOTES

SHEET NO.

ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

SPRINGS I

ISSUED: July 28, 2025

LIMITS OF CONSTRUCTION . The limits of construction shall be bounded by the right of way line or permanent /temporary casement limits shown on the Plans. Limits of construction may be further restricted by placement of silt fence, tree protection fencing, or other appurtenances as 15. Complete water quality ponds.

Holidays without the written permission of the WTCPUA in each case, except such work as may

Use latest City of Austin, City of Dripping Springs, City of Bee Cave, Travis County, Hays County

WEST TRAVIS COUNTY PUBLIC UTILITY AGENCY (WTCPUA) NOTES - to be placed on General Notes

- Limits of construction shall be clearly delineated by the Contractor by installing silt fence orange tensar fencing (4 - foot roll tied to 6-foot posts set at 10-foot intervals) or other barriers as approved by the Engineer. All temporary barriers shall be removed at the end of
- Any areas outside the limits of construction disturbed by the Contractor shall immediately be restored to preconstruction condition.

Provisions shall be made for necessary sanitary conveniences for the use of laborers on the work. The facilities must be properly secluded from public observation and shall be installed

SANITARY FACILITIES

and maintained by the contractor. PROTECTION OF BORE PITS

Install barrier fencing (Tensar orange fencing or chain link fencing) to surround the bore pits.

Barrier fencing shall remain in place at all times while the bore pit is open. Contractor shall be

- responsible for security and safety at the bore pits. HORIZONTAL CONTROLS
- All linework shall be staked prior to construction with sealed cut sheets provided to the WTCPUA inspector prior to construction.

and/or piping and appurtenances may be located within the limits of construction as shown

- No permanent spoils disposal shall be allowed on-site, unless approved by the owner and stockpiling, or other construction operations. All spoils materials shall be disposed of by the Contractor at an approved spoil disposal site.
- notify the Owner and/or Engineer at least forty-eight (48) hours prior to disposal of any spoil representative, and TCEQ representative, as applicable
- Install traffic control measures. Use latest City of Austin, City of Dripping Springs, City of Bee Cave, Travis County, Hays County 5. Contractor shall locate all existing utilities prior to initiating construction.
 - 8. Rough cut roads/site, as necessary.
- 1. No work shall be done between the hours of 8:00 P.M. and 6:00 A.M; nor on Sundays or Legal be necessary for the proper care, maintenance and protection of the work already done or in 11. Complete subgrade.
 - 12. Complete 1st course base.
 - 14. Lay pavement and/or complete any pavement repair.
 - 16. Complete permanent erosion control and site restoration. 17. Remove and dispose of temporary erosion controls.
 - 18. Complete any necessary final dress up of areas disturbed by construction operations. TRAFFIC CONTROL NOTES (include if applicable) 1. Plans shall indicate responsible agent for traffic control (Engineer or Contractor).
 - 2. Contractor shall maintain reasonable local vehicular traffic throughout construction Contractor shall provide signs, barricades, flaggers, and other measures as required to
 - allow for vehicular and pedestrian traffic to proceed safely with minimum 4. Signs, barricades, flaggers, and related work shall be in accordance with the Texas Manual on Uniform Traffic Control Devices and with the requirements of the governing city/county.

5. For any activity within TxDOT right-of-way, project must ha', e a TxDOT permit. A copy of the TxDOT permit shall be provided to the WTCPUA prior to construction.

This project is subject to the Texas Commission on Environmental Quality's (TCEQ) Texas Pollution Discharge Elimination System (TPDES) General Permit TXR150000 for Construction Activities. The General Permit requires the preparation of a Storm Water Pollution Prevention Plan (SWPPP), which has been provided by the OWNER for use by the CONTRACTOR. The OWNER shall provide the OWNER'S Notice of Intent (NOI) and Notice of Termination (NOT) to the TCEQ. The CONTRACTOR'S 15. Reinforcing steel shall be ASTM A 615M, Grade 60 unless otherwise noted. responsibilities are as follows:

1. Maintain a copy of the SWPPP and a set of construction plans with the temporary erosion and sediment control plan at the Work site at all times.

2. File a Notice of Intent (NOI) and applicable payment to the TCEQ at least 2 days prior to site

4. Sign the certification and obtain a signed certification statement from all Subcontractors

responsible for implementing the erosion and sediment control measures which indicates that

the CONTRACTOR and Subcontractor understands the permit requirements (forms are in the

3. Post a copy of the OWNER'S and CONTRACTOR'S NOI forms at the Work site.

CONSTRUCTION SEQUENCING (modify to fit project)

REFER TO PLAN SHEETS FOR ANY ADDITIONAL NOTES

- Temporary holding sites as necessary to stockpile excavated soils, embedment material, 1. 48 hours prior to beginning any work, call the One-Call Board of Texas at 811 or 1-800-545-6005 for utility locations and obtain street cut permit for any work within city, county, and/or state
 - Install temporary erosion controls and tree/natural area protection fencing prior to preconstruction meeting and prior to any site clearing, grubbing, excavation, material
- The Contractor shall be responsible for locating and securing a permit for the site; and shall Schedule and convene a preconstruction meeting including but not limited to the Owner's representative, Engineer, WTCPUA representative, Fire Department, City, County, TxDOT
 - 6. Rough cut water quality ponds and direct runoff to ponds to act as a sediment trap. 7. Remove and stockpile topsoil in areas as required.
 - 9. Install all underground utilities. Contractor shall be responsible for coordinating with the WTCPUA when switching service to the WTCPUA system. It shall be the contractor's
 - responsibility to provide materials/facilities to ensure service is maintained during 10. Complete all underground installations, including installation of sleeves.
 - 4. The Contractor shall be responsible for all coordination between himself and other Complete final course base. contractors and utilities in the vicinity of the project. This includes all water, wastewater, gas, electrical, telephone, cable television, and street and drainage work. Once the contractor becomes aware of a possible conflict, it is the contractor's responsibility to notify the engineer and WTCPUA inspector within twenty-four (24) hours.

and modifications.

374-0271.

been accepted by the owner.

WTCPUA WATER & WASTEWATER GENERAL CONSTRUCTION NOTES

the appropriate electric utility company.

submittal of the final payment.

1. All construction operations shall be accomplished in accordance with applicable state

statutes and U.S. Occupational Safety and Health Administration regulations (0.S.H.A.).

Copies of O.S.H.A. standards may be purchased from the U.S. Government printing office.

Information and related reference materials may be obtained from O.S.H.A. Austin Area

Office - La Costa Green Bldg 1033, La Posada Dr, Suite 375, Austin, Texas 78752-3832, 512-

and to the State Law, (Vernon's Annotated Texas Statutes, Article 1436 ©) and the need

for effective precautionary measures when operating in the vicinity of electrical lines. The

contractor is responsible for all safety requirements, and for coordination of all work with

3. The Contractor shall contact the One-Call Board of Texas at 811 or 1-800-545-6005 for

existing utility locations prior to any excavation. The location and type of utilities and

underground facilities shown on these plans are not guaranteed to be accurate or all-

inclusive. It is the Contractor's responsibility to locate and protect all existing utilities. The

Contractor shall verify all depths and locations of existing utilities prior to any

construction. In additional to normal precautions when excavating, use extra caution

when excavating within 25 feet of any utilities shown on the plans.

2. The attention of the contractor is directed to The City of Austin Standard Specifications

spoil site. The contractor shall be responsible for locating and securing a permit for the site. The contractor shall notify the WTCPUA inspector at least forty-eight (48) hours prior to disposal of the material. No spoils are to remain overnight in the floodplain. 10. Cleanup - upon completion and before making application for acceptance of the work, the contractor shall clean all streets and all ground occupied by him in connection with the work of all rubbish, excess materials, excess excavated materials, temporary structures and

5. The Contractor shall be responsible for disposing of all spoil material from the

construction site. All spoils material shall be disposed of by the contractor at an approved

11. The Contractor shall maintain access to businesses and residences at all times. The contractor shall coordinate with property owners to minimize disruption of deliveries, parking, and other

equipment. All parts of the work shall be left in a neat and presentable condition

satisfactory to the WTCPUA and other governmental bodies having jurisdiction prior to

basis for additional payment. 13. The minimum depth of cover from top of pipe to finished grade for all water lines shall be four feet. Install lines to avoid high points.

14. Concrete shall be Class 'A' with a minimum 28-day compressive strength of 3,000 psi, unless

12. Dewatering, if necessary, shall be considered incidental to the work and shall not constitute a

- 5. Follow and comply with all aspects of the TPDES General Permit No. TXR150000. This includes 16. All responsibility for the adequacy of these plans remains with the engineer who prepared but is not limited to field inspections and report, maintaining and repairing erosion controls them. In reviewing these plans, the WTCPUA must rely on the adequacy of the design and updating erosion controls and updating erosion control plan sheets based on field changes engineer. Approval of these plans by the WTCPUA does not release the design engineer of these responsibilities. 6. File a copy of the CONTRACTOR'S Notice of Termination (NOT) with the TCEQ once the WEST TRAVIS COUNTY PUA WATER AND WASTEWATER UTILITY NOTES work is completed in accordance with the TPDES general permit no TXR.150000 and has
 - facilities will be inspected up to, and including, the water meter and/or fire hydrants. The may result in serious damage to the existing waterline. contact number for WTCPUA is (512) 263-0100. The City of Austin standard specifications and standard details current at the time of service laterals and drain valve leads, with the hydrant valves closed and nozzle caps open construction shall govern materials and methods used to perform this work. City of Austin shall be included in the tests.

1. West Travis County PUA is the water and / or wastewater service provider for this project.

A pre-construction meeting with the WTCPUA shall be held prior to commencement of

- Specifications and Standard Details are available 16. Contractor shall submit a Disinfection and Flushing Plan in accordance with AWWA https://library.municode.com/tx/austin/codes/ . Contractor shall obtain all approvals and permits, including but not limited to street/driveway method of disposal of flush water shall be in accordance with the approved plan.
- construction within the right-of-way of a public street or alley. 4. The WTCPUA shall be contacted at (512) 263-0100 at least 48 hours before connecting to their existing water and/or wastewater facilities. 5. The Contractor shall contact the Austin Area "One Call" System at 811 or 1-800-545-6005 for

existing utility locations prior to any excavation. In advance of construction, the contractor

Where water lines and sewer line are installed with a separation distance closer than nine feet

Contract documents, which include a trench safety plan signed and sealed by a Texas

9. All material tests, including soil density tests and related soil analysis, shall be accomplished b

shall verify the location of all utilities to be extended, tied to, or altered, or subject to damage/inconvenience by the construction operations. 6. No other utility service/appurtenances shall be placed near the property line, or other assigned location designated for water and wastewater utility service that would interfere

with the water and/or wastewater services.

(i.e., water lines crossing wastewater lines, water lines paralleling wastewater lines, or water lines next to manholes) the installation must meet the requirements of 30 TAC §217.53(d) (Pipe 22. Test stations shall be installed where water and/or wastewater lines/appurtenances and Design) and 30 TAC §290.44(e) (Water Distribution). Any deviation these standards shall require wastewater manholes are installed offsite or outside pavement. a variance approved by TCEQ before submitting piping assignments to the WTCPUA. The City of Austin Specification item 509S will be required as a minimum trench safety measure.

State, County, and City requirements before beginning work on the project.

- an independent laboratory funded by the owner in accordance with City of Austin Standard 26. The downstream end of any force main shall be terminated in a sanitary sewer manhole Specification Item 1804S.4. 10. Connections to existing WTCPUA water lines shall be made by cut-in tees in accordance with City 27. Contractor shall have necessary Erosion and Sedimentation Controls in place prior to of Austin Standard Specification Item 510.3(24). Isolation valves shall be installed on the ends of commencing water/wastewater facility construction. the cut-in tee, as necessary. A shut-out valve plan shall be provided showing the location of existing owners. Contractor shall perform all work and shall furnish all materials, including draining and Record for verification and furnished to the WTCPUA upon completion of the project. cutting into existing piping and connecting a new pipeline or other extension into the existing pressure piping, forming an addition to the potable water transmission and distribution network and performing necessary shutoffs. Contractor shall schedule all such connections in advance and such schedule shall be approved by the WTCPUA before beginning the work. At least 72 hours-
- blocking behind and under the tap shall have a minimum of 24 hours curing time before the valve 32. Water services shall be installed using HDPE pipe. Copper is not allowed. Minimum service tap can be reopened for service from that tap.

by use of and approved full circle, gasketed cast iron or ductile iron tapping sleeve. Concrete

use of precast blocks may be used to hold the tap in its correction position prior to blocking. The

12. Fire hydrants shall be set in accordance with City of Standard Specification Item 51IS.3 E and shall be approved by the Fire Department or other appropriate party prior to installation. Fire hydrants on mains under construction shall be securely wrapped with a poly wrap bag and taped into place. The poly wrap will be removed when the mains are accepted and placed in service. Where Storz adaptors are required (Hays County), fire hydrants shall be manufactured with integral Storz adaptors.

13. Water line testing and sterilization shall be performed in accordance with City of Austin Standard Specification Item 510.3(29) and/or TCEQ rules.

back to and including the valve against which the pressure test shall be performed, has been installed to at least the specifications of this project. Failure to verify that thrust blocking construction to schedule inspection of installation of water/wastewater facilities. Water and/or thrust restraint in the existing line meets or exceeds the specifications of this project

Prior to pressure testing, contractor shall verify that thrust blocking and/or thrust restraint

14. Test pressure for 2-hour test shall be at 175 psi at the lowest point in the line.

15. Water lines shall be filled with water and all air expelled at least 24 hours before testing. All

standards to the WTCPUA for approval. Required flushing volumes, flushing schedule, and cut and utility cut permits from the appropriate governmental agency before beginning 17. Gate valves shall be resilient seated gate valves conforming to AWWAC509, with a minimum rated working pressure of 250 psig.

> 18. Force main testing shall be performed in accordance with the City of Austin Standard Specification Item 510.3(27) and/or TCEQ rules. 19. Gravity sanitary sewer main testing shall be performed in accordance with the City of Austin Standard Specification Items 510.3(26) and/or TCEQ rules. In addition, all gravity sanitary sewer mains shall be televised prior to acceptance by WTCPUA. Digital files (via CD-ROM) clearly

showing televised recording shall be submitted to the Engineer of Record following inspection.

20. Locator 'Finder' Wire - All non -metallic water lines shall have a finder wire located above the pipe. The wire shall be poly-insulated No. 10 solid copper and will terminate at each isolation valve such that it is accessible from the valve box. 21. Locator 'Finder' Wire - All non-metallic wastewater lines shall have a finder wire located above

the pipe. The wire shall be poly-insulated No. 10 solid copper and will terminate at readily

23. All valve risers shall have a 1'-6" square concrete box poured around them at finished grade.

24. All manholes shall be lined with a corrosion resistant lining approved by the WTCPUA.

accessible locations throughout the collection system.

in a manner to minimize turbulence.

Professional Engineer and a pay item for trench safety measures, in compliance with OSHA, 25. Bolted and gasketed covers shall be used for all manholes located in the 100-year floodplain. Where there are more than three gasketed manholes in a row, vents shall be provided on

gate valves in the vicinity of the connection. The shut-out plan shall identify all affected property 28. Record drawings, as stipulated by the WTCPUA, shall be submitted to the Engineer of

29. The WTCPUA will own and operate all water lines and appurtenances up to and including

the water meter. These improvements will be defined by a recorded easement or in public

notice shall be given to the WTCPUA prior to making the connection, and a representative from the 30. Any portions of wastewater lines including services that are located outside of a recorded WTCPUA shall be present when the connection is made. Pressure taps may be approved on a caseeasement or public right-of-way will be owned and maintained by the property owner, or by-case basis. "Size on Size" taps will NOT be permitted. When approved, any taps shall be made blocking shall be placed behind and under all tap sleeves prior to making the pressure tap and the 31. Where existing water and/or wastewater infrastructure is to be abandoned, the engineer shall

11. Thrust restraint shall be by metal thrust restraints in accordance with City of Austin Standard 33. For any storm sewer line crossing a water or wastewater line closer than 18", the storm sewer pipe shall be laid such that no storm sewer joints will be over the water pipe crossing.

submit an abandonment plan for approval by the WTCPUA.

Bidding and Construction

Director

Proj. Arch. Checker

AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION. "RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS

REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

!!! CAUTION !!!

EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION

WHEN WORKING NEAR ELECTRIC FACILITIES

!!! WARNING !!!

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY


OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR


SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL


EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE


COPYRIGHT © 2025 VLK ARCHITECTS, LLC

Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_COVER SHEET.dwg Plotted By: Brian Green Date: 7/23/2025 7:57:19 PM Layout: CONSTRUCTION NOTES Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:1
























1	l 5 l 6 l 7 l	8 9 10 11	12 13 14 15	l 16 l 17	
TREE TAG # TREE SIZE	TREE TAG # TREE SIZE TREE TYPE	5201 26" CEDAR 5202 22" CEDAR 5203 19" CEDAR 5204 23" CEDAR 5205 37" CEDAR 5206 22" CEDAR 5206 22" CEDAR 5207 8" OAK 5208 8" OAK 5209 13" OAK 5210 10" OAK 5211 8" OAK 5211 8" OAK 5212 15" OAK 5213 25" CEDAR 5214 11" OAK 5215 10" OAK 5216 10" OAK 5217 14" OAK 5218 10" OAK 5219 12" OAK 5210 11" OAK 5211 10" OAK 5211 10" OAK 5212 <	TREE TAG # TREE SIZE TREE TYPE 5401	TREE TAG # TREE SIZE TREE TYPE 5601 20" OAK 5602 9" OAK 5603 15" OAK 5604 56" CEDAR 5606 8" OAK 5607 17" HACKBERRY 5608 11" OAK 5609 23" HACKBERRY 5610 13.5" OAK 5611 12" OAK 5612 10" OAK 5613 12" OAK 5614 9" OAK 5615 23" CEDAR 5616 21" OAK 5617 15.5" OAK 5618 27" OAK 5619 20" CEDAR 5620 15" OAK 5621 11" OAK 5622 20" OAK 5624 9" OAK 5624 9" OAK 5625 14.5" OAK 5626 18" OAK 5627 15" OAK 5628 15.5" OAK 5629 12" OAK 5630 11.5" OAK 5631 9" OAK 5631 9" OAK	LEGEND H.C.C.D. **HAYES COUNTY CLERKS DOCUMENT OP FRANCE. **OFFICIAL PUBLIC RECORDS HAYES COUNTY, TEXAS \$\triangle \text{ "SURVEY CONTINC PONT}\$ \$\triangle \text{ "FIRST PROBAITY}\$ \$\triangle \text{ "WATER METER}\$ \$\triangle \text{ "LOUT FOLE}\$ \$\triangle \text{ "GLANT FOLE}\$ \$\triangle \text{ "GLANT FOLE}\$ \$\triangle \text{ "FRAFFIC SIGN}\$ \$\triangle \text{ "APPAUL TEDDE}\$ \$\triangle \text{ "MALBOX}\$ \$\triangle \text{ "GRAVEL}\$ \$\triangle \text{ "GRAVEL}\$ \$\triangle \text{ "CONCRETE}\$ \$\triangle \text{ "FRAFFIC SIGN}\$ \$\triangle \text{ "GRAVEL}\$ \$\triangle \text{ "CONCRETE}\$ \$\triangle \text{ "GRAVEL}\$ \$\triangle \text{ "CONCRETE}\$ \$\triangle \text{ "GRAVEL}\$ \$\triangle \text{ "CONCRETE}\$ \$\triangle "GRAVEL" "
1	5035 18" CEDAR 5135 24" CEDAR 5036 18" CEDAR 5136 18" CEDAR 5037 8" OAK 5137 20" CEDAR 5038 8" OAK 5139 10" OAK 5039 8" OAK 5139 10" OAK 5040 18" CEDAR 5140 9" OAK 5041 15" OAK 5141 18" CEDAR 5042 9" OAK 5142 32" CEDAR 5043 8" OAK 5143 13.5" OAK 5044 8" OAK 5144 19" CEDAR 5045 13" OAK 5144 19" CEDAR 5046 20" CEDAR 5146 26" CEDAR 5047 18" CEDAR 5149 21" OAK 5054 18" CEDAR 5150 19"	5235 9" OAK 5335 8.5" OAK 5236 8" OAK 5336 12" OAK 5237 8" OAK 5337 22" CEDAR 5238 18" CEDAR 5338 42" CEDAR 5240 28" CEDAR 5340 10" OAK 5241 21" CEDAR 5341 9" OAK 5242 11" OAK 5342 10.5" OAK 5243 25" CEDAR 5343 10" OAK 5244 25" CEDAR 5344 9" OAK 5245 28" CEDAR 5345 8" OAK 5245 28" CEDAR 5345 8" OAK 5246 19" CEDAR 5345 8" OAK 5247 22" CEDAR 5348 46" CEDAR 5249 25" CEDAR 5349 23" </td <td>5435 8" OAK 5535 9" OAK 5436 9" OAK 5536 11" OAK 5437 14" OAK 5537 9" OAK 5438 9" OAK 5538 10" OAK 5440 8.5" OAK 5540 8" OAK 5441 8" OAK 5540 8" OAK 5442 13" OAK 5542 11" OAK 5443 10" OAK 5543 18" CEDAR 5443 10" OAK 5544 18" CEDAR 5444 11" OAK 5544 18" CEDAR 5445 9.5" OAK 5545 22" CEDAR 5446 9" OAK 5546 18" CEDAR 5448 8.5" OAK 5548 24" CEDAR 5450 8.5" OAK 5550 18" <t< td=""><td>5636 9" OAK 5637 11.5" OAK 5638 17" OAK 5639 21" OAK 5640 17" OAK 5641 18" OAK 5642 8" OAK 5643 23" OAK 5644 20" OAK 5645 10.5" OAK 5646 11" OAK 5647 10" OAK 5648 16" OAK 5649 10" OAK 5650 11" OAK 5651 10.5" OAK 5652 8.5" OAK 5653 24" OAK 5654 17" OAK 5655 12.5" OAK 5656 22.5" OAK 5657 20" OAK 5659 19" OAK 5660 13" OAK 5661</td><td>3-00895 CONTROL LIST PONT</td></t<></td>	5435 8" OAK 5535 9" OAK 5436 9" OAK 5536 11" OAK 5437 14" OAK 5537 9" OAK 5438 9" OAK 5538 10" OAK 5440 8.5" OAK 5540 8" OAK 5441 8" OAK 5540 8" OAK 5442 13" OAK 5542 11" OAK 5443 10" OAK 5543 18" CEDAR 5443 10" OAK 5544 18" CEDAR 5444 11" OAK 5544 18" CEDAR 5445 9.5" OAK 5545 22" CEDAR 5446 9" OAK 5546 18" CEDAR 5448 8.5" OAK 5548 24" CEDAR 5450 8.5" OAK 5550 18" <t< td=""><td>5636 9" OAK 5637 11.5" OAK 5638 17" OAK 5639 21" OAK 5640 17" OAK 5641 18" OAK 5642 8" OAK 5643 23" OAK 5644 20" OAK 5645 10.5" OAK 5646 11" OAK 5647 10" OAK 5648 16" OAK 5649 10" OAK 5650 11" OAK 5651 10.5" OAK 5652 8.5" OAK 5653 24" OAK 5654 17" OAK 5655 12.5" OAK 5656 22.5" OAK 5657 20" OAK 5659 19" OAK 5660 13" OAK 5661</td><td>3-00895 CONTROL LIST PONT</td></t<>	5636 9" OAK 5637 11.5" OAK 5638 17" OAK 5639 21" OAK 5640 17" OAK 5641 18" OAK 5642 8" OAK 5643 23" OAK 5644 20" OAK 5645 10.5" OAK 5646 11" OAK 5647 10" OAK 5648 16" OAK 5649 10" OAK 5650 11" OAK 5651 10.5" OAK 5652 8.5" OAK 5653 24" OAK 5654 17" OAK 5655 12.5" OAK 5656 22.5" OAK 5657 20" OAK 5659 19" OAK 5660 13" OAK 5661	3-00895 CONTROL LIST PONT
4266 8" OAK 4366 10" OAK 4267 9" OAK 4368 11.5" OAK 4268 10" OAK 4368 11.5" OAK 4269 35" OAK 4370 8.5" OAK 4270 9" OAK 4371 18" OAK 4271 10" OAK 4371 18" OAK 4273 9" OAK 4372 12" OAK 4273 9" OAK 4373 9.5" OAK 4274 24.5" OAK 4375 32" OAK 4276 10" OAK 4376 13" OAK 4277 8" OAK 4277 8" OAK 4377 15" OAK 4278 10" OAK 4378 18" OAK 4279 20" OAK 4380 49.5" OAK 4280 9" OAK 4380 49.5" OAK 4281 8.5" OAK 4381 32" OAK 4282 9" OAK 4382 10.5" OAK 4283 9" OAK 4383 21" OAK 4284 10.5" OAK 4384 16" OAK 4286 8.5" OAK 4386 12" OAK 4287 14.5" OAK 4386 12" OAK 4287 14.5" OAK 4288 11.5" OAK 4288 11.5" OAK 4289 16.5" OAK 4289 16.5" OAK 4289 16.5" OAK 4289 12" OAK	5066 11" OAK 5166 9.5" OAK 5067 18.5" OAK 5167 12" OAK 5068 26" CEDAR 5168 24" CEDAR 5069 18" CEDAR 5169 22" CEDAR 5070 11" OAK 5170 9.5" OAK 5071 12" OAK 5171 15.5" OAK 5072 13" OAK 5172 18" OAK 5073 23" CEDAR 5173 8" HACK 5074 10" OAK 5174 9" OAK 5075 8.5" OAK 5175 10" OAK 5076 8" OAK 5176 12" OAK 5077 10" OAK 5177 15.5" OAK 5078 8.5" OAK 5178 16.5" OAK 5080 10" OAK 5181 19" <td>5267 26" CEDAR 5366 8" OAK 5268 33" CEDAR 5367 42" CEDAR 5269 22" CEDAR 5368 22" CEDAR 5270 19" CEDAR 5369 19.5" ELM 5271 18" CEDAR 5370 9" OAK 5272 22" CEDAR 5371 12" OAK 5273 20" CEDAR 5372 20" CEDAR 5274 18" CEDAR 5373 22" CEDAR 5275 25" CEDAR 5374 9" OAK 5276 12" OAK 5375 18" CEDAR 5277 30" CEDAR 5376 28" CEDAR 5279 22" CEDAR 5377 20" CEDAR 5280 28" CEDAR 5378 24" CEDAR 5281 25" CEDAR 5380<td>5467 10" OAK 5566 23" OAK 5468 9" OAK 5567 15" OAK 5469 10" OAK 5568 16" OAK 5470 8" OAK 5569 12" OAK 5471 8" OAK 5570 11" OAK 5472 9.5" OAK 5571 22" OAK 5473 9" OAK 5571 22" OAK 5474 10" OAK 5573 10" OAK 5475 8" OAK 5574 35" CEDAR 5476 13" OAK 5575 13" OAK 5478 19" CEDAR 5576 12" OAK 5479 8.5" OAK 5578 16" OAK 5481 9" OAK 5580 14" OAK 5482 8.5" OAK 5581 12" OAK<</td><td>5667 14" OAK 5668 11" OAK 5669 13" OAK 5670 20" OAK 5671 29" OAK 5672 21" OAK 5673 19" OAK 5674 9" OAK 5675 12" OAK 5676 10" OAK 5677 9" OAK 5678 8.5" OAK 5679 9" OAK 5680 10" OAK 5681 11" OAK 5682 11" OAK 5683 21" OAK 5684 15" OAK 5685 21" OAK 5686 23.5" OAK 5687 16" OAK 5689 10" OAK 5690 16" OAK 5691 16.5" OAK 5692 17"<td>SHEET 7 SHEET 8 0 20 40 80 GRAPHIC SCALE (FEET) 1. ADDITIONAL TREES 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 DRIPPING SPRINGS, HAYES COUNTY, TEXAS TOPOGRAPHIC SURVEY OF DRIPPING SPRINGS HIGH SCHOOL NO. 2 IHERBY STATE THAT TO THE BEST OF MY PROFESSIONAL KNOWLEDGE AND BELIEF THAT THIS PLAT AND THE SURVEY UPON WHICH IT IS BASED MEETS THE REQUIREMENTS FOR LAND SURVEYS IN THE STATE OF TEXAS. SURVEYED IN THE MONTH OF OCTOBER 2024. NOVEMBER 5, 2024 RELEASE DATE OFFECURE SMITH R.P.L.S. 6845</td></td></td>	5267 26" CEDAR 5366 8" OAK 5268 33" CEDAR 5367 42" CEDAR 5269 22" CEDAR 5368 22" CEDAR 5270 19" CEDAR 5369 19.5" ELM 5271 18" CEDAR 5370 9" OAK 5272 22" CEDAR 5371 12" OAK 5273 20" CEDAR 5372 20" CEDAR 5274 18" CEDAR 5373 22" CEDAR 5275 25" CEDAR 5374 9" OAK 5276 12" OAK 5375 18" CEDAR 5277 30" CEDAR 5376 28" CEDAR 5279 22" CEDAR 5377 20" CEDAR 5280 28" CEDAR 5378 24" CEDAR 5281 25" CEDAR 5380 <td>5467 10" OAK 5566 23" OAK 5468 9" OAK 5567 15" OAK 5469 10" OAK 5568 16" OAK 5470 8" OAK 5569 12" OAK 5471 8" OAK 5570 11" OAK 5472 9.5" OAK 5571 22" OAK 5473 9" OAK 5571 22" OAK 5474 10" OAK 5573 10" OAK 5475 8" OAK 5574 35" CEDAR 5476 13" OAK 5575 13" OAK 5478 19" CEDAR 5576 12" OAK 5479 8.5" OAK 5578 16" OAK 5481 9" OAK 5580 14" OAK 5482 8.5" OAK 5581 12" OAK<</td> <td>5667 14" OAK 5668 11" OAK 5669 13" OAK 5670 20" OAK 5671 29" OAK 5672 21" OAK 5673 19" OAK 5674 9" OAK 5675 12" OAK 5676 10" OAK 5677 9" OAK 5678 8.5" OAK 5679 9" OAK 5680 10" OAK 5681 11" OAK 5682 11" OAK 5683 21" OAK 5684 15" OAK 5685 21" OAK 5686 23.5" OAK 5687 16" OAK 5689 10" OAK 5690 16" OAK 5691 16.5" OAK 5692 17"<td>SHEET 7 SHEET 8 0 20 40 80 GRAPHIC SCALE (FEET) 1. ADDITIONAL TREES 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 DRIPPING SPRINGS, HAYES COUNTY, TEXAS TOPOGRAPHIC SURVEY OF DRIPPING SPRINGS HIGH SCHOOL NO. 2 IHERBY STATE THAT TO THE BEST OF MY PROFESSIONAL KNOWLEDGE AND BELIEF THAT THIS PLAT AND THE SURVEY UPON WHICH IT IS BASED MEETS THE REQUIREMENTS FOR LAND SURVEYS IN THE STATE OF TEXAS. SURVEYED IN THE MONTH OF OCTOBER 2024. NOVEMBER 5, 2024 RELEASE DATE OFFECURE SMITH R.P.L.S. 6845</td></td>	5467 10" OAK 5566 23" OAK 5468 9" OAK 5567 15" OAK 5469 10" OAK 5568 16" OAK 5470 8" OAK 5569 12" OAK 5471 8" OAK 5570 11" OAK 5472 9.5" OAK 5571 22" OAK 5473 9" OAK 5571 22" OAK 5474 10" OAK 5573 10" OAK 5475 8" OAK 5574 35" CEDAR 5476 13" OAK 5575 13" OAK 5478 19" CEDAR 5576 12" OAK 5479 8.5" OAK 5578 16" OAK 5481 9" OAK 5580 14" OAK 5482 8.5" OAK 5581 12" OAK<	5667 14" OAK 5668 11" OAK 5669 13" OAK 5670 20" OAK 5671 29" OAK 5672 21" OAK 5673 19" OAK 5674 9" OAK 5675 12" OAK 5676 10" OAK 5677 9" OAK 5678 8.5" OAK 5679 9" OAK 5680 10" OAK 5681 11" OAK 5682 11" OAK 5683 21" OAK 5684 15" OAK 5685 21" OAK 5686 23.5" OAK 5687 16" OAK 5689 10" OAK 5690 16" OAK 5691 16.5" OAK 5692 17" <td>SHEET 7 SHEET 8 0 20 40 80 GRAPHIC SCALE (FEET) 1. ADDITIONAL TREES 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 DRIPPING SPRINGS, HAYES COUNTY, TEXAS TOPOGRAPHIC SURVEY OF DRIPPING SPRINGS HIGH SCHOOL NO. 2 IHERBY STATE THAT TO THE BEST OF MY PROFESSIONAL KNOWLEDGE AND BELIEF THAT THIS PLAT AND THE SURVEY UPON WHICH IT IS BASED MEETS THE REQUIREMENTS FOR LAND SURVEYS IN THE STATE OF TEXAS. SURVEYED IN THE MONTH OF OCTOBER 2024. NOVEMBER 5, 2024 RELEASE DATE OFFECURE SMITH R.P.L.S. 6845</td>	SHEET 7 SHEET 8 0 20 40 80 GRAPHIC SCALE (FEET) 1. ADDITIONAL TREES 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 1/8/2025 DRIPPING SPRINGS, HAYES COUNTY, TEXAS TOPOGRAPHIC SURVEY OF DRIPPING SPRINGS HIGH SCHOOL NO. 2 IHERBY STATE THAT TO THE BEST OF MY PROFESSIONAL KNOWLEDGE AND BELIEF THAT THIS PLAT AND THE SURVEY UPON WHICH IT IS BASED MEETS THE REQUIREMENTS FOR LAND SURVEYS IN THE STATE OF TEXAS. SURVEYED IN THE MONTH OF OCTOBER 2024. NOVEMBER 5, 2024 RELEASE DATE OFFECURE SMITH R.P.L.S. 6845
A 4295 11" OAK	5095 9" OAK 5195 13" OAK 5096 21" CEDAR 5196 12.5" OAK 5097 8" OAK 5197 9.5" OAK 5098 " OAK 5198 11" OAK 5099 23" CEDAR 5199 23" OAK 5100 11" OAK 5200 9.5" OAK 5 6 7 7 7	5297 18" CEDAR 5395 26" CEDAR 5298 8" OAK 5396 25" CEDAR 5397 28" CEDAR 5398 12" OAK 5399 9.5" OAK 5400 9" OAK 5400 9" OAK	5496 8.5" OAK 5595 9" OAK 5497 20" CEDAR 5596 9" OAK 5498 8" OAK 5597 29" OAK 5499 31" CEDAR 5598 12" OAK 5500 9" OAK 5599 10" OAK 5600 21" OAK	5696 14.5" OAK 5697 22" OAK 5698 12" OAK 5699 14" OAK 5700 14" OAK	PLAT NUMBER PROJECT NUMBER 3-00895.00 DRAWN BY/CHECKED BY WRW/KLS FIELD NOTE NO. DRAWING NAME DRAFT DATE SURV SURV PLAT NUMBER 10/29/2024 SHEET NUMBER 10/29/2024 C1.8

1	l 5 l 6	l 7 l 8	l 9 l	10 l 11 l	12 l 13 l	14 l 15	l 16 l 17	
TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	3-00895.00 TREE TAG LIST TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE		LEGEND
P 319 5" OAK 320 3" OAK	1020 11" OAK 1021 10" OAK	1121 7" OAK 1122 8" OAK	1227 8" OAK 1228 8" OAK	1403 6" OAK 1404 6" OAK	2195 11" OAK 2196 6" OAK	5721 8" OAK 5722 6" OAK		H.C.C.D. = HAYES COUNTY CLERK'S DOCUMENT O.P.R.H.C.T. = OFFICIAL PUBLIC RECORDS HAYES COUNTY, TEXAS
321 4" OAK 322 12" OAK	1022 7" OAK 1023 7" OAK	1123 10" OAK 1124 6" OAK	1229 16" OAK 1230 19" OAK	1405 6" OAK 1406 6" OAK	2197 6" OAK 2198 6" OAK	5723 6" OAK 5724 6" OAK		
323 22" CEDAR 324 4" OAK	1024 7" OAK 1025 7" OAK	1125 8" OAK 1126 6" OAK	1231 8" OAK 1232 8" OAK	1407 6" OAK 1408 18" CEDAR	2199 8" OAK 2200 10" OAK	5725 8" OAK 5726 6" OAK		
325 4" OAK 0 326 15" OAK	1026 6" OAK 1027 6" OAK	1127 6" OAK 1128 7" OAK	1233 6" OAK 1234 10" OAK	1409 6" OAK 1410 9" OAK	2201 8" OAK	5727 6" OAK 5728 6" OAK		⇒ = WATER IRRIGATION CONTROL VALVE ARV ⇒ AIR RELEASE VALVE
327 5" OAK	1028 6" OAK	1129 7" OAK	1235 6" OAK	1411 6" OAK	2203 11" OAK	5729 18" CEDAR		→ = UTILITY POLE ← = GUY WIRE ☐ = ELECTRIC JUNCTION BOX
— 328 22 CEDAK 329 4" OAK	1030 6" OAK	1131 12" OAK	1237 8" OAK	1649 9" OAK	2204 8" OAK 2205 13" OAK	5731 10" OAK		
330 5" OAK 331 17" CEDAR	1031 6" ELM 1032 24" CEDAR	1132 6" OAK 1133 7" OAK	1238 6" OAK 1239 6" OAK	1650 9.5" OAK 1651 14" OAK	3531 8" OAK	5732 10 OAK 5733 6" OAK		— X — = FENCE → = TRAFFIC SIGN
N 332 6" OAK 333 4" OAK	1033 12" OAK 1034 12" OAK	1134 8" OAK 1135 6" OAK	1240 13" OAK 1241 15" OAK	1652 8.5" OAK 1653 12.5" OAK	3532 8" OAK 3533 5" OAK	5734 6" OAK 5735 8" OAK		= ASPHALT EDGE = MAILBOX
334 10" OAK 335 13" OAK	1035 7" OAK 1036 10" OAK	1136 9" OAK 1137 7" OAK	1242 6" OAK 1243 7" OAK	1654 6" OAK 1655 8.5" OAK	3534 10" OAK 3535 8" OAK	5736 6" OAK 5737 7" OAK		= GRAVEL = CONCRETE
336 8" OAK 337 10" OAK	1037 6" OAK 1038 12" OAK	1138 8" OAK 1139 7" OAK	1244 8" OAK 1245 6" OAK	1656 11" OAK 1657 18" CEDAR	3536 23" CEDAR 3537 18" CEDAR	5738 6" OAK 5739 6" OAK		= RIP RAP
M 338 18" CEDAR 339 4" OAK	1039 17" OAK 1040 11" OAK	1140 22" CEDAR 1141 7" OAK	1246 6" OAK 1247 9" OAK	1658 19" CEDAR 1659 5" OAK	3538 18" CEDAR 3539 19" CEDAR	5740 12" OAK 5741 6" OAK		= TREE
340 3" OAK 341 3" OAK	1041 11" OAK 1042 6" OAK	1142 10" OAK 1143 7" OAK	1248 9" OAK 1249 6" OAK	1660 4" OAK 1661 4" OAK	3540 24" CEDAR 3541 25" CEDAR	5801 6" OAK 5802 6" OAK		SURVEYOR'S NOTES
- 342 13" OAK 343 14" OAK	1043 8" OAK 1044 9" OAK	1144 7" OAK 1145 6" OAK	1250 6" OAK 1251 21" ELM	1662 3" OAK 1663 4" OAK	3542 10" OAK 3543 10" OAK	5803 6" OAK 5804 6" OAK		
344 11" OAK 345 11" OAK	1045 6" OAK 1046 22" CEDAR	1146 6" OAK 1147 6" OAK	1252 6" OAK 1253 7" OAK	1664 4" OAK 1665 27" CEDAR	3544 10" OAK 3545 22" CEDAR	5805 13" OAK 5806 6" OAK		SURVEY DATE: OCTOBER 11, 2024 THE SURVEYOR DID NOT ABSTRACT THE SUBJECT TRACT. THEREFORE THE SURVEYOR CERTIFIES THAT EASEMENTS THAT HE HAS BEEN
346 9" OAK 347 3" OAK	1047 20" CEDAR 1048 6" OAK	1148 7" OAK 1149 10" OAK	1254 7" OAK 1255 19" CEDAR	1666 4" OAK 1667 4.5" OAK	3546 18" CEDAR 3547 7" OAK	5807 7" OAK 5808 " OAK7		ADVISED OF HAVE BEEN ADDRESSED HEREON. HOWEVER, THE SURVEYOR DOES NOT GUARANTEE THAT ALL EASEMENTS, RESTRICTIONS OR ENCUMBRANCES (EITHER OF RECORD OR NOT OF RECORD) WHICH MAY AFFECT THE SUBJECT TRACT ARE SHOWN HEREON. FEDERAL EMERGENCY MANAGEMENT AGENCY (FEMA) NOTE: BY GRAPHIC PLOTTING ONLY THIS PROPERTY IS IN FEMA "OTHER AREAS"
348 3" OAK	1049 6" OAK	1150 20" OAK	1256 7" OAK	1668 4.5" OAK	3548 5" OAK	5809 7" OAK		ZONE X AS SHOWN ON THE FLOOD INSURANCE RATE MAP, COMMUNITY PANEL 48209C0120F AND 48209C0140F, HAVING AN EFFECTIVE DATE OF SEPTEMBER 2, 2005. THIS FLOOD STATEMENT DOES NOT IMPLY THAT THIS TRACT WILL, OR WILL NOT FLOOD, NOR DOES IT CREATE ANY LIABILITY IN SUCH EVENT ON THE PART OF THIS SURVEYOR OR COMPANY.
350 4" OAK	1050 8" OAK 1051 7" OAK	1151 9" OAK 1152 13" OAK	1258 7" OAK	1670 7" OAK	3549 4" OAK 3550 5" OAK	5810 7" OAK 5811 12" OAK		EXPLANATION OF FEMA ZONES: FEMA "OTHER AREAS" ZONE X = AREA OF MINIMAL FLOOD HAZARD TREES SHOWN HEREON WITHOUT TREE TAG NUMBERS ARE 8-17" CEDAR TREES.
K 351 24 CEDAK 352 5" OAK	1052 6" OAK 1053 6" OAK	1153 18" OAK 1154 10" OAK	1259 7" OAK 1260 7" OAK	1671 6" OAK 1672 8" OAK	3551 4" OAK 3552 3" OAK	5812 7" OAK 5813 24" CEDAR		THE COORDINATES AND ELEVATIONS ARE BASED UPON STATE PLANE COORDINATE SYSTEM, NAD 83, TEXAS SOUTH CENTRAL ZONE, NAVD 88 (USA GEOID 12B) ACQUIRED FROM GLOBAL POSITIONING SYSTEM OBSERVATIONS. THE COORDINATES SHOWN HEREON ARE SURFACE COORDINATES WITH A COMBINED ADJUSTED SCALE FACTOR (CAF) OF 1,00013. (SURF / CAF = GRID)
353 6" OAK 354 24" CEDAR	1054 6" OAK 1055 7" OAK	1155 18" CEDAR 1156 7" OAK	1261 24" CEDAR 1262 23" OAK	1673 6" OAK 1674 6" OAK	3553 4" OAK 3554 3" OAK	5814 7" OAK 5815 10" OAK		
- 355 7" OAK 356 6" OAK	1056 6" OAK 1057 7" OAK	1157 6" OAK 1158 6" OAK	1263 7" OAK 1264 7" OAK	1675 18" CEDAR 1676 11" OAK	3555 3" OAK 3557 6" OAK	5816 7" OAK 5817 12" OAK		
357 18" CEDAR 358 6" OAK	1058 6" OAK 1059 6" OAK	1159 7" OAK 1160 8" OAK	1265 6" OAK 1266 7" OAK	1677 7" OAK 1678 7" OAK	3558 19" CEDAR 3559 6" OAK	5818 6" OAK 5819 19" CEDAR		
359 8" OAK 360 6" OAK	1060 7" OAK 1061 6" OAK	1161 7" OAK 1162 7" OAK	1267 7" OAK 1268 6" OAK	1679 7" OAK 1680 7" OAK	3560 6" OAK 3561 6" OAK	5820 6" OAK 5821 6" OAK		
	1062 6" OAK 1063 10" OAK	1163 9" ELM 1164 6" OAK	1269 6" OAK 1270 6" OAK	1681 6" OAK 1682 7" OAK	3562 8" OAK 3563 9" OAK	5822 6" OAK 5823 7" OAK		
363 8" OAK 364 7" OAK	1064 16" OAK 1065 18" OAK	1165 6" OAK 1166 7" OAK	1271 6" OAK 1272 6" OAK	1683 7" OAK 1684 8" OAK	3564 7" OAK 3565 6" OAK	5824 8" OAK 5825 13" OAK		
365 12" OAK 366 7" OAK	1066 13" OAK 1067 16" OAK	1167 6" OAK 1168 6" OAK	1273 27" OAK 1274 7" OAK	1685 8" OAK 1686 9" OAK	3566 6" OAK 3567 6" OAK	5826 6" OAK 5827 6" OAK		3-00895 CONTROL LIST
- 367 7" OAK - 368 6" OAK	1068 24" OAK 1069 16" OAK	1169 19" CEDAR 1170 18" CEDAR	1275 6" OAK 1276 8" OAK	1687 7" OAK 1688 7" OAK	3568 20" CEDAR 3569 18" CEDAR	5901 8" OAK 5902 9" OAK		POINT NORTHING EASTING EASTING DESCRIPTION 1 13968548.32 2283176.63 1137.13 1/2" IRON ROD WITH CAP STAMPED "WALKER CONTROL"
369 6" OAK 370 9" OAK	1070 8" OAK 1071 8" OAK	1171 7" OAK 1172 6" OAK	1277 8" OAK 1278 6" OAK	1689 14" OAK 1690 7" OAK	3570 7" OAK 3571 22" CEDAR	5903 6" OAK 5904 7" OAK		2 13968568.26 2283154.69 1137.28 MAG NAIL WITH WASHER STAMPED "WALKER PARTNERS" 3 13970179.55 2282119.98 1122.06 CUT "X" IN CONCRETE
H 371 9" OAK 372 8" OAK	1072 7" OAK 1073 6" OAK	1173 19" CEDAR 1174 6" OAK	1279 6" OAK 1280 6" OAK	1691 10" OAK 1692 10" OAK	3572 20" CEDAR 3573 30" CEDAR	5905 8" OAK 5906 6" OAK		4 13970216.21 2285016.77 1146.70 COTTON SPINDLE WITH WASHER STAMPED "WALKER PARTNERS" 5 1396923.69 2283146.54 1135.27 CUT "X" IN CONCRETE 6 13970119.93 2283353.87 1148.71 1/2" IRON ROD WITH CAP STAMPED "WALKER CONTROL" 7 13967487.67 2283103.86 1114.86 1/2" IRON ROD WITH CAP STAMPED "WALKER CONTROL"
373 6" OAK 374 18" CEDAR	1074 18" CEDAR 1075 24" CEDAR	1175 6" OAK 1176 19" CEDAR	1281 9" OAK 1282 20" CEDAR	1693 6" OAK 1694 7" OAK	3574 35" CEDAR 3575 22" CEDAR	5907 6" OAK 5908 9" OAK		KEY MAP
375 22" CEDAR 376 21" CEDAR	1076 6" OAK 1077 8" OAK	1177 21" CEDAR 1178 7" OAK	1301 18" CEDAR	1695 7" OAK 1696 6" OAK	3576 24" CEDAR 3577 19" CEDAR	5909 17" OAK 5910 30" OAK		
377 20" CEDAR	1078 6" OAK	1179 19" CEDAR	1303 6" OAK	1697 7" OAK	3578 12" OAK	5911 9" OAK		SUEET 2 SUEET 4
378 24 CEDAK 379 7" OAK	1079 6" OAK 1080 6" OAK	1180 18" CEDAR 1181 7" OAK	1304 6" OAK 1305 8" OAK	1699 8" OAK	3579 6" OAK 3580 6" OAK	5912 10 OAK 5913 8" OAK		SHEET 2 SHEET 3 SHEET 4
- 380 6" OAK 381 28" CEDAR	1081 18" CEDAR 1082 6" OAK	1182 7" OAK 1183 18" CEDAR	1306 18" CEDAR 1307 13" OAK	1700 8" OAK 2156 9" OAK	3581 6" OAK 3582 6" OAK	5914 8" OAK 5915 9" OAK		
382 29" CEDAR 383 6" OAK	1083 6" OAK 1084 6" OAK	1184 8" OAK 1185 7" OAK	1308 10" OAK 1309 10" OAK	2157 7" OAK 2158 7" OAK	3583 6" OAK 3584 6" OAK	5916 10" OAK 5917 7" OAK		SHEET 5 SHEET 6
F 384 8" OAK 385 6" OAK	1085 6" OAK 1086 6" OAK	1186 9" OAK 1187 9" OAK	1310 10" OAK 1311 6" OAK	2159 6" OAK 2160 6" OAK	3585 19" CEDAR 3586 6" OAK	5918 8" OAK 5919 12" OAK		
	1087 6" OAK 1088 6" OAK	1188 9" OAK 1189 7" OAK	1312 6" OAK 1313 7" OAK	2161 6" OAK 2162 9" OAK	3587 7" OAK 3588 10" ELM	5920 6" OAK 5921 7" OAK		SHEET 7 SHEET 8
388 8" OAK 389 32" CEDAR	1089 8" OAK 1090 18" CEDAR	1190 8" OAK 1191 8" OAK	1314 7" OAK 1315 6" OAK	2163 7" OAK 2164 6" OAK	3589 6" OAK 3590 8" OAK	5922 6" OAK 5923 6" OAK		
B 390 27" CEDAR 391 30" CEDAR	1091 19" OAK 1092 19" OAK	1192 9" OAK 1193 10" OAK	1316 6" OAK 1317 6" OAK	2165 6" OAK 2166 21" CEDAR	3591 7" OAK 3592 7" OAK	5924 8" OAK 5925 8" OAK		0 20 40 80
392 6" OAK 393 18" CEDAR	1093 7" OAK 1094 8" OAK	1194 21" CEDAR 1195 7" OAK	1318 9" OAK 1319 10" OAK	2167 19" CEDAR 2168 6" OAK	3593 6" OAK 3594 7" OAK	5926 13" OAK 5927 11" OAK		GRAPHIC SCALE (FEET)
- 394 12" OAK 395 24" CEDAR	1095 6" OAK 1096 12" ELM	1196 8" OAK 1197 7" OAK	1320 16" OAK 1321 8" OAK	2169 6" OAK 2170 6" OAK	3595 13" OAK 3596 22" CEDAR	5928 6" OAK 5929 7" OAK		1. ADDITIONAL TREES 1/8/2025
D 396 8" OAK 397 6" OAK	1097 12" OAK 1098 20" OAK	1198 6" OAK 1199 7" OAK	1322 6" OAK 1323 6" OAK	2171 7" OAK 2172 7" OAK	3597 6" OAK 3598 7" OAK	5930 6" OAK 5931 6" OAK		
398 6" OAK 399 10" OAK	1099 7" OAK 1100 19" CEDAR	1200 6" OAK 1206 8" OAK	1324 6" OAK 1325 6" OAK	2173 6" OAK 2174 6" OAK	3599 9" OAK 3600 12" OAK	5932 10" OAK 5933 7" OAK		AWAII - ou Double out
	1101 9" OAK 1102 6" OAK	1207 6" OAK 1208 6" OAK	1326 6" OAK 1327 6" OAK	2175 6" OAK 2176 6" OAK	5701 7" OAK 5702 6" OAK	5934 6" OAK 5935 6" OAK		Walker Partners engineers * surveyors
1001 10 OAK 1002 10" OAK 1003 7" OAK	1102 0 OAK 1103 7" OAK 1104 6" OAK	1209 6" OAK 1210 6" OAK	1328 18" CEDAR 1329 6" OAK	2177 7" OAK 2178 20" OAK	5703 6" OAK 5704 7" OAK	J. J		823 Washington Ave. ● Waco, Texas 76701 Phone: 1-254-714-1402 ● T.B.P.E. Registration No. 8053 T.B.P.L.S. Registration No. 10032500
1003 7 OAK 1004 8" OAK 1005 7" OAK	1105 6" OAK 1106 6" OAK	1210 6" OAK 1211 6" OAK 1212 6" ELM	1330 6" OAK 1331 6" OAK	2178 20 OAK 2179 7" OAK 2180 8" OAK	5705 6" OAK 5706 11" OAK			DRIPPING SPRINGS, HAYES COUNTY, TEXAS
1005 7 OAK 1006 7" OAK 1007 8" OAK	1106 6 OAK 1107 21" CEDAR 1108 10" OAK	1212 6 ELIVI 1213 7" OAK 1214 7" OAK	1331 6 OAK 1332 12" OAK 1333 6" OAK	2180 8 OAK 2181 8" OAK 2182 10" OAK	5706 11 OAK 5707 11" OAK 5708 6" OAK			TOPOGRAPHIC SURVEY
1007 8 OAK 1008 8" OAK 1009 6" OAK	1109 8" OAK	1215 36" OAK	1334 6" OAK	2182 10 OAK 2183 9" OAK 2184 7" OAK	5709 7" OAK 5710 6" OAK			OF DRIPPING SPRINGS HIGH SCHOOL NO. 2
B 1010 9" OAK	1111 6" OAK	1216 18.5" OAK 1217 7" OAK	1336 6" OAK	2185 6" OAK	5711 7" OAK			I HEREBY STATE THAT TO THE BEST OF MY PROFESSIONAL KNOWLEDGE AND BELIEF THAT THIS PLAT AND THE SURVEY UPON WHICH IT IS BASED MEETS THE REQUIREMENTS FOR LAND SURVEYS IN THE STATE OF TEXAS. SURVEYED IN THE MONTH OF OCTOBER 2024.
1011 6" OAK 1012 30" CEDAR	1112 7" OAK 1113 6" OAK	1218 9" OAK 1219 9" OAK	1337 9" OAK 1338 7" OAK	2186 8" OAK 2187 6" OAK	5712 6" OAK 5713 6" OAK			NOVEMBER 5, 2024 RELEASE DATE KOREY LEE SMITH R P.L.S. 6645
	1114 9" OAK 1115 8" OAK	1220 6" OAK 1221 6" OAK	1339 6" OAK 1340 6" OAK	2188 8" OAK 2189 6" OAK	5714 22" OAK 5715 20" OAK			PLAT NUMBER E1-0074 PROJECT NUMBER 3-00895.00
1015 6" OAK 1016 6" OAK	1116 8" OAK 1117 22" CEDAR	1222 9" OAK 1223 8" OAK	1341 6" OAK 1342 28" OAK	2190 6" OAK 2191 6" OAK	5716 7" OAK 5717 6" OAK			DRAWN BY/CHECKED BY WRW/KLS FIELD NOTE NO. N/A DRAWING NAME 3-00895TOPO.DWG
1017 6" OAK 1018 6" OAK	1118 18" CEDAR 1119 6" OAK	1224 8" OAK 1225 12" OAK	1343 30" CEDAR 1401 7" OAK	2192 10" OAK 2193 27" OAK	5718 8" OAK 5719 6" OAK			DRAFT DATE 10/29/2024 SHEET NUMBER
1019 6" OAK 1 2 3 4	1120 9" OAK 6	1226 8" OAK 8	1402 18" CEDAR	10 6" OAK	12 13 13	14 15	16 17	L. L.
ı ı l		. 1	a 1	a d	a I	J	<u>A</u>	C1.9









SCALE =1:100

LEGEND ■ ■ ■ ■ ■ ■ ■ ■ DRAINAGE BOUNDARY LINE TC TIME OF CONCENTRATION LINE DRAINAGE FLOW ARROW


SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS



ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Designer Designer

Proj. Arch. Checker PROJECT NO.

23-134.00

SHEET TITLE EXISTING DRAINAGE

SHEET NO.

AREA MAP

C3.0

COPYRIGHT © 2025 VLK ARCHITECTS, LLC

!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES

!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL


EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.


"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS


SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"



Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_EXISTING DA MAP.dwg Plotted By: Brian Green Date: 7/23/2025 7:57:56 PM Layout: EXISTING DRAINAGE AREA MAP Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:200







SCALE =1:200

LEGEND ■ ■ ■ ■ ■ ■ ■ ■ DRAINAGE BOUNDARY LINE TC TIME OF CONCENTRATION LINE DRAINAGE FLOW ARROW

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS

ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145

www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Drawn By Director Designer Designer

Proj. Arch. Checker PROJECT NO.

23-134.00

SHEET TITLE

DRAINAGE AREA MAF

SHEET NO.

C3.1

COPYRIGHT © 2025 VLK ARCHITECTS, LLC




!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY


CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES


!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS

SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"








LEGEND

PROPOSED CURB & GUTTER



ARCHITECT

VLK 2700 Via Fortuna, Suite 230 Austin, Texas 78746

Main Phone: 512.807.3145 www.vlkarchitects.com

PROPOSED CONCRETE SIDEWALK SDWK (SEE PLAN FOR WIDTHS) ----- IP ------ INLET PROTECTION S.C.E. (TEMPORARY STABILIZED CONSTRUCTION VEGETATIVE FILTER STRIP 100 PROPOSED CONTOURS - - - 100- - PROPOSED CONTOURS - MAJOR PROPOSED CONTOURS - MINOR EXISTING UTILITIES: FIRE HYDRANTS WATER VALVE WATER VALVE MANHOLE (STORM) MANHOLE (STORM) MANHOLE (WW) MANHOLE (WW) INLET INLET INLET WASTEWATER STORM SEWER STORM SEWER PROPERTY LINE (ADJACENT) EXISTING EASEMENT EXISTING TREE (TO REMAIN) PROPOSED TREE

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS Revision Date

Drawn By Director **Quality Control** Designer Designer

Proj. Arch. Checker

PROJECT NO. 23-134.00

SHEET TITLE TEMP ESC PLAN - SECTION 1

SHEET NO.

C4.0

COPYRIGHT © 2025 VLK ARCHITECTS, LLC



!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES


!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY

OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL


EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS

SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"



Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_TEMP EROSION & SEDIMENTATION CONTROL PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:01:30 AM Layout: TEMP ESC PLAN - SECTION 2 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:50



TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	3-00895.00 TREE TAG LIST TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE
4201 16.5" OAK	4301 14.5" OAK	5001 4" OAK	* 5101 9" OAK	* 5201 26" CEDAR	5301 10" OAK	* 5401 18" CEDAR	5501 19" CEDAR	5601 20" OAK
4202 13.5" OAK	4302 12" OAK	5002 4.5" LIVE	5102 19" CEDAR	* 5202 22" CEDAR	5302 8.5" OAK	5402 9" OAK	5502 25" CEDAR	* 5602 9" OAK
4203 13" OAK	4303 16" OAK	5003 4" LIVE	5103 28" CEDAR	* 5203 19" CEDAR	5303 8.5" OAK	5403 9.5" OAK	* 5503 18" CEDAR	* 5603 15" OAK
4204 14" OAK 4205 18" CEDAR	4304 11.5" OAK 4305 15" OAK	5004 11" OAK 5005 9" OAK	5104 10" CEDAR	5204 23" CEDAR * 5205 37" CEDAR	5304 8" OAK 5305 10.5" OAK	5404 21.5" OAK 5405 22" OAK	5504 10" OAK 5505 21" CEDAR	* 5604 56" CEDAR 5606 8" OAK
4205 18" CEDAR 4206 18" CEDAR	4305 15" OAK 4306 9" OAK	5005 9" OAK 5006 9" OAK	5105 10" OAK 5106 19" CEDAR	* 5205 37" CEDAR * 5206 22" CEDAR	5305 10.5" OAK 5306 10" OAK	5405 22" OAK 5406 14.5" OAK	5506 26" CEDAR	* 5607 17" HACKBERRY
4207 16" OAK	4307 12" OAK	5007 4" LIVE	5107 19" CEDAR	* 5207 8" OAK	5307 11" OAK	5407 14" OAK	5507 18" CEDAR	* 5608 11" OAK
4208 11" OAK	4308 12.5" OAK	5008 4" LIVE	5108 " OAK	* 5208 8" OAK	5308 8.5" OAK	5408 16" OAK	5508 9" OAK	* 5609 23" HACKBERRY
4209 12" OAK	* 4309 8.5" OAK	5009 4" LIVE	5109 10" OAK	5209 13" OAK	5309 9" OAK	5409 10" OAK	5509 18" OAK	5610 13.5" OAK
4210 20" CEDAR 4211 11.5" OAK	* 4310 11" OAK * 4311 10.5" OAK	5010 4.5" LIVE 5011 4.5" LIVE	5110 15" OAK 5111 26" OAK	5210 10" OAK 5211 8" OAK	5310 18" CEDAR 5311 9" OAK	5410 11.5" OAK 5411 9.5" OAK	5510 10" OAK 5511 10" OAK	5611 12" OAK 5612 10" OAK
4212 12" OAK	* 4312 10" OAK	5012 24" OAK	5112 19" CEDAR	5212 15" OAK	5312 8" OAK	5412 9" OAK	5512 8" OAK	5613 12" OAK
4213 14" OAK	* 4313 10" OAK	5013 17" OAK	5113 8" OAK	5213 25" CEDAR	5313 8" OAK	5413 26" OAK	5513 8" OAK	5614 9" OAK
4214 9.5" OAK	* 4314 12.5" OAK	5014 8.5" OAK	5114 8.5" OAK	5214 11" OAK	5314 10" OAK	5414 10" OAK	5514 28" CEDAR	5615 23" CEDAR
4215 13" OAK 4216 17" OAK	* 4315 9" OAK * 4316 10" OAK	5015 4.5" LIVE 5016 4" LIVE	5115 9" OAK 5116 9.5" OAK	5215 10" OAK 5216 10" OAK	5315 10.5" OAK 5316 16" OAK	5415 19" CEDAR 5416 9" OAK	5515 8" OAK 5516 33" CEDAR	5616 21" OAK 5617 15.5" OAK
4217 12" OAK	* 4317 12.5" OAK	5017 20" CEDAR	5117 9.5" OAK	5217 14" OAK	5317 14" OAK	5417 9" OAK	5517 12" OAK	5618 27" OAK
4218 10.5" OAK	* 4318 8.5" OAK	5018 23" OAK	5118 10.5" OAK	5218 10" OAK	5318 21" CEDAR	* 5418 10" OAK	5518 24" CEDAR	5619 20" CEDAR
4219 9" OAK	* 4319 9" OAK	5019 21" OAK	5119 10" OAK	5219 12" OAK	5319 8" OAK	* 5419 9" OAK	5519 9" OAK	* 5620 15" OAK
4220 9" OAK 4221 18" CEDAR	* 4320 12" OAK * 4321 12" OAK	5020 14.5" OAK 5021 14.5" OAK	5120 26" CEDAR	5220 11" OAK 5221 11" OAK	5320 10" OAK 5321 10" OAK	* 5420 12" OAK * 5421 9" OAK	5520 14" OAK 5521 18" CEDAR	* 5621 11" OAK * 5622 20" OAK
4221 18" CEDAR 4222 8" OAK	* 4321 12" OAK * 4322 10.5" OAK	5021 14.5" OAK 5022 10" OAK	5121 11" OAK 5122 11" OAK	5221 11" OAK 5222 12" OAK	5321 10" OAK 5322 8.5" OAK	* 5421 9" OAK * 5422 14" OAK	5522 24" CEDAR	* 5623 8.5" OAK
4223 10" OAK	4323 13" OAK	5023 13" OAK	5123 19" CEDAR	5223 8" OAK	5323 9.5" OAK	5423 9.5" OAK	5523 26" CEDAR	* 5624 9" OAK
4224 9.5" OAK	4324 12.5" OAK	5024 19" OAK	5124 12" OAK	5224 8" OAK	5324 8" OAK	5424 13" OAK	5524 35" CEDAR	* 5625 14.5" OAK
4225 13" OAK	4325 8" OAK	5025 23" CEDAR	5125 20" CEDAR	5225 9" OAK	5325 8" OAK	5425 8.5" OAK	5525 22" CEDAR	* 5626 18" OAK
4226 9" OAK 4227 10" OAK	4326 8" OAK 4327 8" OAK	5026 26" CEDAR 5027 22" ELM	5126 18" CEDAR 5127 18" CEDAR	5226 11" OAK 5227 9" OAK	5326 19" OAK 5327 21" CEDAR	5426 10" OAK 5427 13" OAK	5526 35" CEDAR 5527 19" CEDAR	* 5627 15" OAK * 5628 15.5" OAK
4228 10" OAK	4328 11" OAK	5027 22 ELIVI 5028 11" OAK	5128 16" OAK	5228 8" OAK	5328 17" OAK	* 5428 8" OAK	5528 18" CEDAR	5629 12" OAK
4229 8" OAK	4329 8.5" OAK	5029 8" OAK	5129 18" CEDAR	5229 8" OAK	5329 10" OAK	* 5429 8" OAK	5529 22" CEDAR	5630 11.5" OAK
4230 10" OAK	4330 22" OAK	5030 10.5" OAK	5130 19" CEDAR	5230 8" OAK	5330 23" CEDAR	* 5430 9" OAK	5530 13" OAK	5631 9" OAK
4231 21.5" CEDAR 4232 15" OAK	4331 25" CEDAR 4332 12" OAK	5031 9" OAK 5032 18" CEDAR	5131 24" CEDAR 5132 19" CEDAR	5231 11" OAK 5232 26" CEDAR	5331 18" CEDAR 5332 18" CEDAR	* 5431 8" OAK * 5432 19" OAK	5531 12" OAK 5532 13" OAK	* 5632 8" OAK * 5633 11.5" OAK
4233 11.5" OAK	4333 14" OAK	5032 18 CEDAK 5033 8" OAK	5133 24" CEDAR	5233 15" OAK	5333 22" CEDAR	* 5433 8.5" OAK	5533 14" OAK	* 5634 9.5" OAK
4234 11" OAK	* 4334 8" OAK	5034 8" OAK	5134 14" OAK	5234 12" OAK	5334 10.5" OAK	* 5434 8" OAK	5534 11" OAK	* 5635 10" OAK
4235 22.5" OAK	* 4335 10" OAK	5035 18" CEDAR	5135 24" CEDAR	5235 9" OAK	5335 8.5" OAK	* 5435 8" OAK	5535 9" OAK	* 5636 9" OAK * 5637 11.5" OAK
4236 14.5" OAK 4237 14" OAK	* 4336 26" OAK * 4337 10" OAK	5036 18" CEDAR 5037 8" OAK	5136 18" CEDAR 5137 20" CEDAR	5236 8" OAK 5237 8" OAK	5336 12" OAK 5337 22" CEDAR	* 5436 9" OAK * 5437 14" OAK	5536 11" OAK 5537 9" OAK	* 5637 11.5" OAK * 5638 17" OAK
4238 8.5" OAK	* 4338 11" OAK	5037 8 OAK 5038 8" OAK	5138 25" CEDAR	* 5238 18" CEDAR	5338 42" CEDAR	5438 9" OAK	5538 10" OAK	* 5639 21" OAK
4239 24.5" OAK	* 4339 20" OAK	5039 8" OAK	5139 10" OAK	5239 18" CEDAR	5339 13.5" OAK	5439 11" OAK	5539 9" OAK	* 5640 17" OAK
4240 10" OAK	4340 22" OAK	5040 18" CEDAR	5140 9" OAK	5240 28" CEDAR	5340 10" OAK	5440 8.5" OAK	5540 8" OAK	* 5641 18" OAK
4241 11.5" OAK 4242 9.5" OAK	4341 27" OAK 4342 17" OAK	5041 15" OAK 5042 9" OAK	5141 18" CEDAR 5142 32" CEDAR	5241 21" CEDAR 5242 11" OAK	5341 9" OAK 5342 10.5" OAK	5441 8" OAK 5442 13" OAK	5541 8" OAK 5542 11" OAK	* 5642 8" OAK * 5643 23" OAK
4243 8" OAK	* 4343 17" OAK	5043 8" OAK	5143 13.5" OAK	5243 25" CEDAR	5343 10" OAK	* 5443 10" OAK	5543 18" CEDAR	* 5644 20" OAK
4244 9" OAK	* 4344 15" OAK	5044 8" OAK	5144 19" CEDAR	5244 25" CEDAR	5344 9" OAK	* 5444 11" OAK	5544 18" CEDAR	* 5645 10.5" OAK
4245 9.5" OAK	* 4345 15" OAK	5045 13" OAK	5145 18" CEDAR	5245 28" CEDAR	5345 8" OAK	* 5445 9.5" OAK	5545 22" CEDAR	* 5646 11" OAK
4246 17" OAK 4247 20.5" OAK	* 4346 12" OAK * 4347 14" OAK	5046 20" CEDAR 5047 18" CEDAR	5146 26" CEDAR 5147 9" OAK	5246 19" CEDAR 5247 22" CEDAR	5346 20" CEDAR 5347 20" CEDAR	* 5446 9" OAK * 5447 12" OAK	5546 18" CEDAR 5547 22" CEDAR	* 5647 10" OAK * 5648 16" OAK
4248 8" OAK	* 4348 19" OAK	5048 18" OAK	5148 21" CEDAR	5248 21" CEDAR	5348 46" CEDAR	* 5448 8.5" OAK	5548 24" CEDAR	* 5649 10" OAK
4249 9" OAK	* 4349 20" OAK	5049 18" CEDAR	5149 21" OAK	5249 25" CEDAR	5349 23" OAK	* 5449 9" OAK	5549 20" CEDAR	* 5650 11" OAK
4250 9.5" OAK	* 4350 19" OAK	5050 24" CEDAR	5150 19" CEDAR	5250 19" CEDAR	5350 9" OAK	* 5450 8.5" OAK	5550 18" CEDAR	* 5651 10.5" OAK
4251 14" OAK 4252 12.5" OAK	* 4351 19" OAK * 4352 18" OAK	5051 " OAK 5052 8" OAK	5151 24" CEDAR 5152 25" CEDAR	5252 22" CEDAR 5253 24" CEDAR	5351 8" OAK 5352 24" CEDAR	* 5451 12" OAK * 5452 9" OAK	5551 32" CEDAR 5552 18" CEDAR	* 5652 8.5" OAK * 5653 24" OAK
4253 11" OAK	* 4353 18" OAK	5052 8" OAK	5153 18" CEDAR	5254 20" CEDAR	5353 18" CEDAR	* 5453 8" OAK	5553 25" CEDAR	* 5654 17" OAK
4254 9.5" OAK	* 4354 14" OAK	5054 10" OAK	5154 20" OAK	5255 18" CEDAR	5354 20" CEDAR	* 5454 9" OAK	5554 18" CEDAR	* 5655 12.5" OAK
4255 11" OAK	* 4355 17.5" OAK	5055 8" OAK	5155 14" OAK	5256 20" CEDAR	5355 12.5" OAK	* 5455 8.5" OAK	5555 22" CEDAR	* 5656 22.5" OAK
4256 9" OAK 4257 13.5" OAK	* 4356 14" OAK * 4357 12" OAK	5056 20" OAK 5057 19" OAK	5156 11" OAK 5157 18" CEDAR	5257 8" OAK 5258 30" CEDAR	5356 12" OAK 5357 13.5" OAK	* 5456 8" OAK * 5457 28" CEDAR	5556 22" CEDAR 5557 18" CEDAR	* 5657 20" OAK * 5658 13.5" OAK
4258 10.5" OAK	* 4358 18" OAK	5057 15 CAK 5058 8" OAK	5158 23" CEDAR	5259 18" CEDAR	5358 15" OAK	* 5458 24" CEDAR	5558 20" CEDAR	* 5659 19" OAK
4259 17" OAK	* 4359 17.5" OAK	5059 11" OAK	5159 20" CEDAR	5260 18" CEDAR	5359 20" CEDAR	* 5459 15.5" OAK	5559 23" CEDAR	* 5660 13" OAK
4260 8.5" OAK	* 4360 11" OAK	5060 11" OAK	5160 31" CEDAR	5261 40" CEDAR	5360 20" CEDAR	* 5460 18" CEDAR	5560 22" OAK	* 5661 9" OAK
4261 " OAK 4262 11" OAK	* 4361 13.5" OAK * 4362 9" OAK	5061 20" CEDAR 5062 8" OAK	5161 8.5" OAK 5162 8" OAK	5262 18" CEDAR 5263 23" CEDAR	5361 21" OAK 5362 9.5" OAK	5461 8" OAK 5462 8" OAK	5561 22" OAK 5562 21" OAK	* 5662 13" OAK * 5663 21" OAK
4263 9" OAK	* 4363 15" OAK	5063 8" OAK	5163 27" CEDAR	5264 18" CEDAR	5363 29" CEDAR	5463 9" OAK	5563 25" OAK	* 5664 19" OAK
4264 11" OAK	* 4364 11.5" OAK	5064 22" CEDAR	5164 12" OAK	5265 22" CEDAR	5364 28" CEDAR	5464 8" OAK	* 5564 13" OAK	* 5665 14" OAK
4265 8" OAK	* 4365 11.5" OAK	5065 14" OAK	5165 9" OAK	5266 18" CEDAR	5365 9" OAK	5466 8" OAK	5565 8" OAK	* 5666 10" OAK
4266 8" OAK 4267 9" OAK	* 4366 10" OAK * 4367 27.5" OAK	5066 11" OAK 5067 18.5" OAK	5166 9.5" OAK 5167 12" OAK	5267 26" CEDAR 5268 33" CEDAR	5366 8" OAK 5367 42" CEDAR	5467 10" OAK 5468 9" OAK	5566 23" OAK 5567 15" OAK	* 5667 14" OAK * 5668 11" OAK
4268 10" OAK	* 4368 11.5" OAK	5068 26" CEDAR	* 5168 24" CEDAR	5269 22" CEDAR	5368 22" CEDAR	5469 10" OAK	5568 16" OAK	* 5669 13" OAK
4269 35" OAK	* 4369 17.5" OAK	5069 18" CEDAR	* 5169 22" CEDAR	5270 19" CEDAR	5369 19.5" ELM	5470 8" OAK	5569 12" OAK	* 5670 20" OAK
4270 9" OAK 4271 10" OAK	* 4370 8.5" OAK * 4371 18" OAK	5070 11" OAK 5071 12" OAK	* 5170 9.5" OAK * 5171 15.5" OAK	5271 18" CEDAR 5272 22" CEDAR	5370 9" OAK 5371 12" OAK	5471 8" OAK 5472 9.5" OAK	5570 11" OAK 5571 22" OAK	* 5671 29" OAK * 5672 21" OAK
4271 10 OAK 4272 8.5" OAK	* 4371 18 OAK * 4372 12" OAK	5071 12 OAK 5072 13" OAK	* 5171 15.5 OAK * 5172 18" OAK	5272 22 CEDAR 5273 20" CEDAR	5371 12 OAK 5372 20" CEDAR	5473 9" OAK	5572 17" OAK	* 5673 19" OAK
4273 9" OAK	* 4373 9.5" OAK	5073 23" CEDAR	* 5173 8" HACK	5274 18" CEDAR	5373 22" CEDAR	5474 10" OAK	5573 10" OAK	* 5674 9" OAK
4274 24.5" OAK	* 4374 32.5" OAK	5074 10" OAK	* 5174 9" OAK	5275 25" CEDAR	5374 9" OAK	5475 8" OAK	5574 35" CEDAR	* 5675 12" OAK
4275 9" OAK 4276 10" OAK	4375 32" OAK 4376 13" OAK	5075 8.5" OAK 5076 8" OAK	* 5175 10" OAK * 5176 12" OAK	5276 12" OAK 5277 30" CEDAR	5375 18" CEDAR 5376 28" CEDAR	5476 13" OAK 5477 18" CEDAR	5575 13" OAK 5576 12" OAK	* 5676 10" OAK * 5677 9" OAK
4277 8" OAK	4377 15" OAK	5077 10" OAK	* 5177 15.5" OAK	5277 30 CEDAR 5279 22" CEDAR	5377 20" CEDAR	5477 18 CEDAR 5478 19" CEDAR	5577 12" OAK	* 5678 8.5" OAK
4278 10" OAK	* 4378 18" OAK	5078 8.5" OAK	* 5178 16.5" OAK	5280 28" CEDAR	5378 24" CEDAR	5479 8.5" OAK	5578 16" OAK	* 5679 9" OAK
4279 20" OAK	* 4379 21" OAK	5079 11" OAK	* 5179 11" OAK	5281 25" CEDAR	5379 24" CEDAR	5480 10" OAK	5579 8" OAK	* 5680 10" OAK
4280 9" OAK 4281 8.5" OAK	* 4380 49.5" OAK * 4381 32" OAK	5080 10" OAK 5081 10" OAK	* 5180 16" OAK * 5181 19" OAK	5282 21" CEDAR 5283 18" CEDAR	5380 12" OAK 5381 8" OAK	5481 9" OAK 5482 8.5" OAK	5580 14" OAK 5581 12" OAK	* 5681 11" OAK * 5682 11" OAK
4281 8.5 OAK 4282 9" OAK	* 4381 32 OAK * 4382 10.5" OAK	5082 11" OAK	* 5182 10.5" OAK	5284 26" CEDAR	5382 17.5" OAK	5483 9" OAK	5582 16" OAK	* 5683 21" OAK
4283 9" OAK	* 4383 21" OAK	5083 9" OAK	* 5183 10.5" OAK	5285 35" CEDAR	5383 13.5" OAK	5484 22" OAK	5583 11" OAK	* 5684 15" OAK
4284 10.5" OAK	* 4384 16" OAK	5084 11" OAK	* 5184 18" CEDAR	5286 18" CEDAR	5384 18" OAK	5485 10.5" OAK	5584 10" OAK	* 5685 21" OAK
4285 9.5" OAK 4286 8.5" OAK	* 4385 14" OAK * 4386 12" OAK	5085 12" OAK 5086 9" OAK	* 5185 9.5" OAK * 5186 20.5" CEDAR	5287 18" CEDAR 5288 28" CEDAR	5385 18.5" OAK 5386 17" OAK	5486 9.5" OAK 5487 8" OAK	5585 12" OAK 5586 13" OAK	* 5686 23.5" OAK * 5687 16" OAK
4287 14.5" OAK	* 4387 9" OAK	5087 8" OAK	* 5187 11" OAK	5289 20" CEDAR	5387 18" OAK	5488 9" OAK	5587 11" OAK	* 5688 23" OAK
4288 11.5" OAK		5088 8" OAK	* 5188 11" OAK	5290 30" CEDAR	5388 30" CEDAR	5489 11" OAK	5588 10" OAK	* 5689 10" OAK
4289 16.5" OAK		5089 10" OAK	* 5189 9" OAK	5291 18" CEDAR	5389 9" OAK	5490 17" OAK	5589 16" OAK	* 5690 16" OAK
4290 18" OAK 4291 12.5" OAK		5090 12" OAK 5091 8" OAK	* 5190 9.5" OAK * 5191 8" OAK	5292 22" CEDAR 5293 10" OAK	5390 8" OAK 5391 11.5" OAK	5491 8.5" OAK 5492 11" OAK	5590 11" OAK 5591 10" OAK	* 5691 16.5" OAK * 5692 17" OAK
4291 12.3 OAK 4292 11" OAK		5092 9" OAK	5192 12" OAK	5294 9" OAK	5392 22" CEDAR	5493 24" CEDAR	5592 9" OAK	* 5693 16" OAK
4293 12" OAK		5093 8" OAK	* 5193 10" OAK	5295 18" CEDAR	5393 8" OAK	5494 8" OAK	5593 11" OAK	* 5694 18" OAK
4294 11" OAK		5094 47" CEDAR	5194 11" OAK	5296 24" CEDAR	5394 25" CEDAR	5495 9" OAK	5594 10" OAK	* 5695 16.5" OAK
4295 11" OAK 4296 8.5" OAK		5095 9" OAK 5096 21" CEDAR	5195 13" OAK 5196 12.5" OAK	5297 18" CEDAR 5298 8" OAK	5395 26" CEDAR 5396 25" CEDAR	5496 8.5" OAK 5497 20" CEDAR	5595 9" OAK 5596 9" OAK	* 5696 14.5" OAK * 5697 22" OAK
4297 17" OAK		5097 8" OAK	5197 9.5" OAK	5299 18" CEDAR	5397 28" CEDAR	5498 8" OAK	5597 29" OAK	* 5698 12" OAK
4298 12.5" OAK		5098 " OAK	5198 11" OAK	5300 18" CEDAR	5398 12" OAK	5499 31" CEDAR	5598 12" OAK	* 5699 14" OAK
4299 12.5" OAK 4300 8.5" OAK		5099 23" CEDAR	5199 23" OAK		5399 9.5" OAK	5500 9" OAK	5599 10" OAK	* 5700 14" OAK
· · · · · · · · · · · · · · · · · · ·		5100 11" OAK	5200 9.5" OAK	1	5400 9" OAK	ı	5600 21" OAK	I

Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_TEMP EROSION & SEDIMENTATION CONTROL PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:01:48 AM Layout: TEMP ESC PLAN - TREE LIST (1 OF 2) Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####

!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY CONTRACTOR SHALL EXERCISE EXTREME CAUTION
WHEN WORKING NEAR ELECTRIC FACILITIES

!!! Warning !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"







ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

Bid Package 2
Issue For Permitting,
Bidding and Construction

ISSUED: July 28, 2025

REVISIONS

Drawn By Designer Designer Proj. Arch. Checker **Quality Control**

PROJECT NO.

23-134.00

SHEET TITLE TEMP ESC PLAN -TREE LIST (1 OF 2)

SHEET NO.

COPYRIGHT © 2025 VLK ARCHITECTS, LLC

				2 00005 00 TREE TAC LIST			
TREE TAG # TREE SIZE	E TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	3-00895.00 TREE TAG LIST TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE	TREE TAG # TREE SIZE TREE TYPE
319 5"	OAK	1020 11" OAK	1121 7" OAK	1227 8" OAK	1403 6" OAK	2195 11" OAK	5721 8" OAK
320 3"	OAK	1021 10" OAK	1122 8" OAK	1228 8" OAK	1404 6" OAK	2196 6" OAK	5722 6" OAK
321 4"	OAK	1022 7" OAK	1123 10" OAK	1229 16" OAK	1405 6" OAK	2197 6" OAK	5723 6" OAK
322 12"	OAK	1023 7" OAK	1124 6" OAK	1230 19" OAK 1231 8" OAK	1406 6" OAK	2198 6" OAK 2199 8" OAK	5724 6" OAK
323 22" 324 4"	CEDAR OAK	1024 7" OAK 1025 7" OAK	1125 8" OAK 1126 6" OAK	1231 8" OAK 1232 8" OAK	1407 6" OAK 1408 18" CEDAR	2199 8" OAK 2200 10" OAK	5725 8" OAK 5726 6" OAK
325 4"	OAK	1026 6" OAK	1127 6" OAK	1233 6" OAK	1409 6" OAK	2201 8" OAK	5727 6" OAK
326 15"	OAK	1027 6" OAK	1128 7" OAK	1234 10" OAK	1410 9" OAK	2202 11" OAK	5728 6" OAK
327 5"	OAK	1028 6" OAK	1129 7" OAK	1235 6" OAK	1411 6" OAK	2203 11" OAK	5729 18" CEDAR
328 22"	CEDAR	1029 9" OAK	1130 10" OAK	1236 6" OAK	1412 7" OAK	2204 8" OAK	5730 25" CEDAR
329 4" 330 5"	OAK OAK	1030 6" OAK 1031 6" ELM	1131 12" OAK 1132 6" OAK	1237 8" OAK 1238 6" OAK	1649 9" OAK 1650 9.5" OAK	2205 13" OAK 3530 10" OAK	5731 10" OAK 5732 10" OAK
331 17"	CEDAR	1031 0 EEW 1032 24" CEDAR	1132 0 OAK	1239 6" OAK	1651 14" OAK	3531 8" OAK	5733 6" OAK
332 6"	OAK	1033 12" OAK	1134 8" OAK	1240 13" OAK	1652 8.5" OAK	3532 8" OAK	5734 6" OAK
333 4"	OAK	1034 12" OAK	1135 6" OAK	1241 15" OAK	1653 12.5" OAK	3533 5" OAK	5735 8" OAK
334 10"	OAK	1035 7" OAK	1136 9" OAK 1137 7" OAK	1242 6" OAK 1243 7" OAK	1654 6" OAK	3534 10" OAK	5736 6" OAK
335 13" 336 8"	OAK OAK	1036 10" OAK 1037 6" OAK	1137 7" OAK 1138 8" OAK	1243 7" OAK 1244 8" OAK	1655 8.5" OAK 1656 11" OAK	3535 8" OAK 3536 23" CEDAR	5737 7" OAK 5738 6" OAK
337 10"	OAK	1038 12" OAK	1139 7" OAK	1245 6" OAK	1657 18" CEDAR	3537 18" CEDAR	5739 6" OAK
338 18"	CEDAR	1039 17" OAK	1140 22" CEDAR	1246 6" OAK	1658 19" CEDAR	3538 18" CEDAR	5740 12" OAK
339 4"	OAK	1040 11" OAK	1141 7" OAK	1247 9" OAK	1659 5" OAK	3539 19" CEDAR	5741 6" OAK
340 3"	OAK	1041 11" OAK 1042 6" OAK	1142 10" OAK 1143 7" OAK	1248 9" OAK	1660 4" OAK	3540 24" CEDAR 3541 25" CEDAR	5801 6" OAK 5802 6" OAK
341 3" 342 13"	OAK OAK	1042 6" OAK 1043 8" OAK	1143 7" OAK 1144 7" OAK	1249 6" OAK 1250 6" OAK	1661 4" OAK 1662 3" OAK	3541 25" CEDAR 3542 10" OAK	5802 6" OAK 5803 6" OAK
343 14"	OAK	1044 9" OAK	1145 6" OAK	1251 21" ELM	1663 4" OAK	3543 10" OAK	5804 6" OAK
344 11"	OAK	1045 6" OAK	1146 6" OAK	1252 6" OAK	1664 4" OAK	3544 10" OAK	5805 13" OAK
345 11"	OAK	1046 22" CEDAR	1147 6" OAK	1253 7" OAK	1665 27" CEDAR	3545 22" CEDAR	5806 6" OAK
346 9" 347 3"	OAK OAK	1047 20" CEDAR 1048 6" OAK	1148 7" OAK 1149 10" OAK	1254 7" OAK 1255 19" CEDAR	1666 4" OAK 1667 4.5" OAK	3546 18" CEDAR 3547 7" OAK	5807 7" OAK 5808 " OAK7
347 3	OAK	1048 6 OAK OAK	1149 10 OAK 1150 20" OAK	1256 7" OAK	1667 4.5 OAK	3547 / OAK 3548 5" OAK	5808 OAK7 5809 7" OAK
349 2"	OAK	1050 8" OAK	1151 9" OAK	1257 7" OAK	1669 19" CEDAR	3549 4" OAK	5810 7" OAK
350 4"	OAK	1051 7" OAK	1152 13" OAK	1258 7" OAK	1670 7" OAK	3550 5" OAK	5811 12" OAK
351 24" 352 5"	CEDAR	1052 6" OAK 1053 6" OAK	1153 18" OAK	1259 7" OAK 1260 7" OAK	1671 6" OAK 1672 8" OAK	3551 4" OAK 3552 3" OAK	5812 7" OAK
352 5" 353 6"	OAK OAK	1053 6" OAK 1054 6" OAK	1154 10" OAK 1155 18" CEDAR	1260 7" OAK 1261 24" CEDAR	1672 8" OAK 1673 6" OAK	3552 3" OAK 3553 4" OAK	5813 24" CEDAR 5814 7" OAK
354 24"	CEDAR	1055 7" OAK	1156 7" OAK	1262 23" OAK	1674 6" OAK	3554 3" OAK	5815 10" OAK
355 7"	OAK	1056 6" OAK	1157 6" OAK	1263 7" OAK	1675 18" CEDAR	3555 3" OAK	5816 7" OAK
356 6" 357 18"	OAK CEDAR	1057 7" OAK 1058 6" OAK	1158 6" OAK 1159 7" OAK	1264 7" OAK 1265 6" OAK	1676 11" OAK 1677 7" OAK	3557 6" OAK 3558 19" CEDAR	5817 12" OAK 5818 6" OAK
358 6"	OAK	1058 6 OAK	1160 8" OAK	1265 6 OAK 1266 7" OAK	1677 7 OAK 1678 7" OAK	3558 19 CEDAK 3559 6" OAK	5818 6 OAK 5819 19" CEDAR
359 8"	OAK	1060 7" OAK	1161 7" OAK	1267 7" OAK	1679 7" OAK	3560 6" OAK	5820 6" OAK
360 6"	OAK	1061 6" OAK	1162 7" OAK	1268 6" OAK	1680 7" OAK	3561 6" OAK	5821 6" OAK
361 7" 362 6"	OAK OAK	1062 6" OAK 1063 10" OAK	1163 9" ELM 1164 6" OAK	1269 6" OAK 1270 6" OAK	1681 6" OAK 1682 7" OAK	3562 8" OAK 3563 9" OAK	5822 6" OAK 5823 7" OAK
363 8"	OAK	1064 16" OAK	1165 6" OAK	1270 6" OAK	1683 7" OAK	3564 7" OAK	5824 8" OAK
364 7"	OAK	1065 18" OAK	1166 7" OAK	1272 6" OAK	1684 8" OAK	3565 6" OAK	5825 13" OAK
365 12"	OAK	1066 13" OAK	1167 6" OAK	1273 27" OAK	1685 8" OAK	3566 6" OAK	5826 6" OAK
366 7" 367 7"	OAK	1067 16" OAK	1168 6" OAK 1169 19" CEDAR	1274 7" OAK 1275 6" OAK	1686 9" OAK	3567 6" OAK	5827 6" OAK
367 7" 368 6"	OAK OAK	1068 24" OAK 1069 16" OAK	1169 19" CEDAR 1170 18" CEDAR	1275 6" OAK 1276 8" OAK	1687 7" OAK 1688 7" OAK	3568 20" CEDAR 3569 18" CEDAR	5901 8" OAK 5902 9" OAK
369 6"	OAK	1070 8" OAK	1171 7" OAK	1277 8" OAK	1689 14" OAK	3570 7" OAK	5903 6" OAK
370 9"	OAK	1071 8" OAK	1172 6" OAK	1278 6" OAK	1690 7" OAK	3571 22" CEDAR	5904 7" OAK
371 9"	OAK	1072 7" OAK	1173 19" CEDAR	1279 6" OAK	1691 10" OAK	3572 20" CEDAR	5905 8" OAK
372 8" 373 6"	OAK OAK	1073 6" OAK 1074 18" CEDAR	1174 6" OAK 1175 6" OAK	1280 6" OAK 1281 9" OAK	1692 10" OAK 1693 6" OAK	3573 30" CEDAR 3574 35" CEDAR	5906 6" OAK 5907 6" OAK
374 18"	CEDAR	1075 24" CEDAR	1176 19" CEDAR	1282 20" CEDAR	1694 7" OAK	3575 22" CEDAR	5908 9" OAK
375 22"	CEDAR	1076 6" OAK	1177 21" CEDAR	1301 18" CEDAR	1695 7" OAK	3576 24" CEDAR	5909 17" OAK
376 21"	CEDAR	1077 8" OAK	1178 7" OAK	1302 18" CEDAR	1696 6" OAK	3577 19" CEDAR	5910 30" OAK
377 20" 378 24"	CEDAR CEDAR	1078 6" OAK 1079 6" OAK	1179 19" CEDAR 1180 18" CEDAR	1303 6" OAK 1304 6" OAK	1697 7" OAK 1698 11" OAK	3578 12" OAK 3579 6" OAK	5911 9" OAK 5912 10" OAK
379 7"	OAK	1075 6" OAK	1181 7" OAK	1305 8" OAK	1699 8" OAK	3580 6" OAK	5913 8" OAK
380 6"	OAK	1081 18" CEDAR	1182 7" OAK	1306 18" CEDAR	1700 8" OAK	3581 6" OAK	5914 8" OAK
381 28"	CEDAR	1082 6" OAK	1183 18" CEDAR	1307 13" OAK	2156 9" OAK	3582 6" OAK	5915 9" OAK
382 29"	CEDAR	1083 6" OAK	1184 8" OAK	1308 10" OAK	2157 7" OAK	3583 6" OAK	5916 10" OAK
8 383 6" 8 384 8"	OAK OAK	1084 6" OAK 1085 6" OAK	1185 7" OAK 1186 9" OAK	1309 10" OAK 1310 10" OAK	2158 7" OAK 2159 6" OAK	3584 6" OAK 3585 19" CEDAR	5917 7" OAK 5918 8" OAK
385 6"	OAK	1086 6" OAK	1187 9" OAK	1311 6" OAK	2160 6" OAK	3586 6" OAK	5919 12" OAK
386 6"	OAK	1087 6" OAK	1188 9" OAK	1312 6" OAK	2161 6" OAK	3587 7" OAK	5920 6" OAK
387 6"	OAK	1088 6" OAK	1189 7" OAK	1313 7" OAK	2162 9" OAK	3588 10" ELM	5921 7" OAK
8 388 8" 8 389 32"	OAK CEDAR	1089 8" OAK 1090 18" CEDAR	1190 8" OAK 1191 8" OAK	1314 7" OAK 1315 6" OAK	2163 7" OAK 2164 6" OAK	3589 6" OAK 3590 8" OAK	5922 6" OAK 5923 6" OAK
390 27"	CEDAR	1090 18 CLDAK 1091 19" OAK	1191 8 OAK 1192 9" OAK	1316 6" OAK	2165 6" OAK	3591 7" OAK	5924 8" OAK
391 30"	CEDAR	1092 19" OAK	1193 10" OAK	1317 6" OAK	2166 21" CEDAR	3592 7" OAK	5925 8" OAK
392 6"	OAK	1093 7" OAK	1194 21" CEDAR	1318 9" OAK	2167 19" CEDAR	3593 6" OAK	5926 13" OAK
393 18" 394 12"	CEDAR OAK	1094 8" OAK 1095 6" OAK	1195 7" OAK 1196 8" OAK	1319 10" OAK 1320 16" OAK	2168 6" OAK 2169 6" OAK	3594 7" OAK 3595 13" OAK	5927 11" OAK 5928 6" OAK
395 24"	CEDAR	1096 12" ELM	1197 7" OAK	1321 8" OAK	2170 6" OAK	3596 22" CEDAR	5929 7" OAK
396 8"	OAK	1097 12" OAK	1198 6" OAK	1322 6" OAK	2171 7" OAK	3597 6" OAK	5930 6" OAK
397 6"	OAK	1098 20" OAK	1199 7" OAK	1323 6" OAK	2172 7" OAK	3598 7" OAK	5931 6" OAK
8 398 6" 399 10"	OAK OAK	1099 7" OAK 1100 19" CEDAR	1200 6" OAK 1206 8" OAK	1324 6" OAK 1325 6" OAK	2173 6" OAK 2174 6" OAK	3599 9" OAK 3600 12" OAK	5932 10" OAK 5933 7" OAK
400 8"	OAK	1100 19 CEDAK 1101 9" OAK	1206 8 OAK 1207 6" OAK	1326 6" OAK	2175 6" OAK	5701 7" OAK	5934 6" OAK
1001 10"	OAK	1102 6" OAK	1208 6" OAK	1327 6" OAK	2176 6" OAK	5702 6" OAK	5935 6" OAK
1002 10"	OAK	1103 7" OAK	1209 6" OAK	1328 18" CEDAR	2177 7" OAK	5703 6" OAK	
1003 7" 1004 8"	OAK OAK	1104 6" OAK 1105 6" OAK	1210 6" OAK 1211 6" OAK	1329 6" OAK 1330 6" OAK	2178 20" OAK 2179 7" OAK	5704 7" OAK 5705 6" OAK	
1004 8"	OAK	1105 6" OAK 1106 6" OAK	1211 6" OAK 1212 6" ELM	1330 6" OAK 1331 6" OAK	2179 / OAK 2180 8" OAK	5705 6" OAK 5706 11" OAK	
1006 7"	OAK	1107 21" CEDAR	1213 7" OAK	1332 12" OAK	2181 8" OAK	5707 11" OAK	
1007 8"	OAK	1108 10" OAK	1214 7" OAK	1333 6" OAK	2182 10" OAK	5708 6" OAK	
* 1008 8" * 1009 6"	OAK OAK	1109 8" OAK 1110 8" OAK	1215 36" OAK 1216 18.5" OAK	1334 6" OAK 1335 6" OAK	2183 9" OAK 2184 7" OAK	5709 7" OAK 5710 6" OAK	
1010 9"	OAK	1110 8 OAK 1111 6" OAK	1216 18.5 OAK	1335 6" OAK 1336 6" OAK	2184 / OAK 2185 6" OAK	5710 6 OAK	
1011 6"	OAK	1112 7" OAK	1218 9" OAK	1337 9" OAK	2186 8" OAK	5712 6" OAK	
1012 30"	CEDAR	1113 6" OAK	1219 9" OAK	1338 7" OAK	2187 6" OAK	5713 6" OAK	
1013 30" 1014 6"	CEDAR	1114 9" OAK	1220 6" OAK	1339 6" OAK 1340 6" OAK	2188 8" OAK	5714 22" OAK	
1014 6" 1015 6"	OAK OAK	1115 8" OAK 1116 8" OAK	1221 6" OAK 1222 9" OAK	1340 6" OAK 1341 6" OAK	2189 6" OAK 2190 6" OAK	5715 20" OAK 5716 7" OAK	
1016 6"	OAK	1117 22" CEDAR	1223 8" OAK	1342 28" OAK	2191 6" OAK	5717 6" OAK	
1017 6"	OAK	1118 18" CEDAR	1224 8" OAK	1343 30" CEDAR	2192 10" OAK	5718 8" OAK	
1018 6"	OAK	1119 6" OAK	1225 12" OAK	1401 7" OAK	2193 27" OAK 2194 6" OAK	5719 6" OAK	
1019 6" ★ TREE TO REMOVE	OAK	1120 9" OAK	1226 8" OAK	1402	2194 6" OAK	5720 10" OAK	

* TREE TO REMOVE

Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_TEMP EROSION & SEDIMENTATION CONTROL PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:01:53 AM Layout: TEMP ESC PLAN - TREE LIST (2 OF 2) Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####

!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY CONTRACTOR SHALL EXERCISE EXTREME CAUTION
WHEN WORKING NEAR ELECTRIC FACILITIES

!!! Warning !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"





ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS


Designer Designer


Proj. Arch. Checker PROJECT NO.

23-134.00

SHEET TITLE TEMP ESC PLAN -TREE LIST (2 OF 2)

SHEET NO.






Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings\SHT_SITE PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:03:15 AM Layout: SITE PLAN - SECTION 1 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:30



ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Revision Date

Drawn By Director **Quality Control** Designer Designer

Proj. Arch.


PROJECT NO.


23-134.00 SHEET TITLE


SITE PLAN -SECTION 1


SHEET NO.


C5.1

























Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings\SHT_SITE PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 11:00:07 AM Layout: PAVEMENT PLAN Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:100





FIRE HYDRANTS

WATER VALVE

MANHOLE (WW)

INLET


WASTEWATER

MANHOLE (STORM)

ARCHITECT

2700 Via Fortuna, Suite 230 Main Phone: 512.807.3145 www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Drawn By Designer Designer


PROJECT NO.


23-134.00

SHEET TITLE OVERALL **GRADING PLAN**


SHEET NO.

C6.0





Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings\SHT_GRADING PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:06:03 AM Layout: GRADING PLAN - SECTION 2 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####






VLK
2700 Via Fortuna, Suite 230
Austin, Texas 78746
Main Phone: 512.807.3145

Main Phone: 512.807.3145
www.vlkarchitects.com

Bid Package 2
Issue For Permitting,
Bidding and Construction



ISSUED: July 28, 2025

REVISIONS
vision No. Revision Date

Director Drawn By
Approver Author
Designer Quality Control
Designer
Proj. Arch.

PROJECT NO.

Checker

23-134.00


SHEET TITLE

GRADING PLAN SECTION 3


SHEET NO.

C6.3





Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings\SHT_GRADING PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:06:38 AM Layout: GRADING PLAN - SECTION 5 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####



Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings\SHT_GRADING PLAN.dwg Plotted By: David Smith Date: 7/26/2025 2:26:06 PM Layout: GRADING PLAN - SECTION 6 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####

ARCHITECT

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS Revision Date


PROJECT NO.


23-134.00


GRADING PLAN -SECTION 6


SHEET NO.


C6.6














SCALE = 1:30

ARCHITECT

2700 Via Fortuna, Suite 230


Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

VLK

LEG	END		
	PROPOSED ACCESSIBLE ROUTE		
	PROPOSED CURB & GUTTER (UNLESS OTHERWISE NOTED PLANS)		
A A SDWK	PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR WIDTHS)		
	L.O.C. (LIMITS OF CONSTRUCTION)		
FIRE LANE	PROPOSED FIRE LANE (REFER TO PLAN FOR STRIPING NOTES)		
	FENCE (REF:ARCH)		
———— GR ————	PEDESTRIAN GUARDRAIL (REF:ARCH)		
0 0 0 0 0 0 0	VEHICLE GUARDRAILS		
	PROPOSED CONTOURS - MAJOR PROPOSED CONTOURS - MINOR		
PROPOSED UTILITIES:	EXISTING UTILITIES:		
FIRE HYDRANTS	FIRE HYDRANTS		
WV WATER VALVE MANHOLE (STORM) MANHOLE (WW) INLET INLET	WATER VALVE MANHOLE (STORM) MANHOLE (WW) INLET INLET		
— w — WATER — w →	— W — WATER		
— ww — wastewater ww —	- WW - WASTEWATER WW -		
— SD — SD — SD —	— SD — SD —		
PR	ROPERTY LINE ROPERTY LINE (ADJACENT) (ISTING EASEMENT		
EX	(ISTING TREE (TO REMAIN)		

WATER METER TABLE										
vleter umber	Meter Size (in.)	WSFU	Individual Demand (GPM)	Water Service Deliniation	Water Service					
1	3" Compound	1,384	255	WTR-SERV-B-1	4" Domestic Service					
2	2" Compound	643	150	WTR-SERV-C2-2	4" Domestic Service					
3	3" Compound	1,247	239	WTR-SERV-C2-1	4" Domestic Service					
4	1.5"	251	75	WTR-SERV-C-3	3" Domestic Service					
5	1.5"	261	77	WTR-SERV-C-1	3" Domestic Service					
6	5/8"	11	15	WTR-SERV-C-2	1.5" Domestic Service					
7	3/4"	28	23	WTR-SERV-C1-3	2" Domestic Service					
8	1.5"	251	75	WTR-SERV-C1-1	3" Domestic Service					
9	1.5"	251	75	WTR-SERV-C3-1	3" Domestic Service					
10	1.5"	251	75	WTR-SERV-C1-2	3" Domestic Service					
11	5/8"	12	16	WTR-SERV-C3-2	1.5" Domestic Service					
12	Future Meter			WTR-SERV-C-4	3" Domestic Service					

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Revision Date

Drawn By Director Quality Control Designer Designer Proj. Arch. Checker

PROJECT NO.

23-134.00 SHEET TITLE

WATER PLAN -SECTION 1

SHEET NO.

C7.0


COPYRIGHT © 2025 VLK ARCHITECTS, LLC





!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY


WHEN WORKING NEAR ELECTRIC FACILITIES


!!! **WARNING** !!!
















Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_WATER PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:09:42 AM Layout: WATER PLAN - SECTION 7 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####





!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES

!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.


"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"



ARCHITECT

2700 Via Fortuna, Suite 230 Main Phone: 512.807.3145 www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Revision Date

Drawn By **Quality Control** Designer Designer Proj. Arch. Checker


PROJECT NO.

23-134.00

SHEET TITLE WATER PROFILE WL-A

SHEET NO.

C7.7





2700 Via Fortuna, Suite 230 Main Phone: 512.807.3145

www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Revision Date

Drawn By Director

Quality Control Designer Designer Proj. Arch. Checker

PROJECT NO.

23-134.00 SHEET TITLE

WATER PROFILE WL-B

SHEET NO.

C7.8

COPYRIGHT © 2025 VLK ARCHITECTS, LLC

!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES


!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY

OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL

EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS

SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"






VLK

VLK
2700 Via Fortuna, Suite 230
Austin, Texas 78746
Main Phone: 512.807.3145
www.vlkarchitects.com

DRIPPIN

Bid Package 2
Issue For Permitting,
Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

o. Revision Da

Director Drawn By
Approver Author
Designer Quality Control
Designer


Proj. Arch. Checker PROJECT NO.

PROJECT NO. 23-134.00

WATER PROFILE

SHEET NO.


C7.9





2700 Via Fortuna, Suite 230 Main Phone: 512.807.3145 www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS

Revision Date

Drawn By Quality Control Designer Designer

Proj. Arch. Checker PROJECT NO.

23-134.00

SHEET TITLE WATER PROFILE WL C1, C2 & C3

SHEET NO.

C7.10

COPYRIGHT © 2025 VLK ARCHITECTS, LLC



!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES

!!! **WARNING** !!!

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY


OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR


EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.


SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL


"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS


SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

















LEG	END
	PROPOSED ACCESSIBLE ROUTE
4 4 SDWK	PROPOSED CURB & GUTTER (UNLESS OTHERWISE NOTED PLANS) PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR WIDTHS)
	L.O.C. (LIMITS OF CONSTRUCTION)
FIRE LANE	PROPOSED FIRE LANE (REFER TO PLAN FOR STRIPING NOTES)
	FENCE (REF:ARCH)
———— GR ————	PEDESTRIAN GUARDRAIL (REF:ARCH)
~ ~ ~ ~ ~ ~ ~	VEHICLE GUARDRAILS
	PROPOSED CONTOURS - MAJOR PROPOSED CONTOURS - MINOR
PROPOSED UTILITIES:	EXISTING UTILITIES:
FIRE HYDRANTS WV WATER VALVE MANHOLE (STORM) MANHOLE (WW) INLET INLET	FIRE HYDRANTS WATER VALVE MANHOLE (STORM) MANHOLE (WW) INLET INLET
WATER W — WASTEWATER WW — WASTEWATER WW — STORM SEWER SD —	W
PF	ROPERTY LINE ROPERTY LINE (ADJACENT) KISTING EASEMENT KISTING TREE (TO REMAIN)

Bid Package 2 Issue For Permitting, Bidding and Construction

ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

VLK



ISSUED: July 28, 2025

REVISIONS Revision Date

Director Drawn By Approver **Quality Control** Designer Designer Proj. Arch.


PROJECT NO.

23-134.00

SHEET TITLE STORM SEWER PLAN

SHEET NO.

C9.0



Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_STORM SEWER PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:13:35 AM Layout: STORM SEWER PLAN - SECTION 2 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####




ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

• • • • • • • • • • • • PROPOSED ACCESSIBLE ROUTE PROPOSED CURB & GUTTER (UNLESS OTHERWISE NOTED PLANS) PROPOSED CONCRETE SIDEWALK PROPOSED FIRE LANE (REFER TO PLAN FOR STRIPING NOTES) GR ———— PEDESTRIAN GUARDRAIL (REF:ARCH) - PROPOSED CONTOURS - MAJOR PROPOSED CONTOURS - MINOR FIRE HYDRANTS WATER VALVE MANHOLE (STORM) MANHOLE (WW) WASTEWATER STORM SEWER

> Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS Revision Date Revision No.

Director Drawn By **Quality Control** Designer Designer

Checker PROJECT NO.

Proj. Arch.


23-134.00

SHEET TITLE


STORM SEWER PLAN

SHEET NO.

C9.1



Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_STORM SEWER PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:13:51 AM Layout: STORM SEWER PLAN - SECTION 3 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####



ARCHITECT

2700 Via Fortuna, Suite 230

Main Phone: 512.807.3145 www.vlkarchitects.com

LEG	END
• • • • • • • • • • • •	PROPOSED ACCESSIBLE ROUTE
	PROPOSED CURB & GUTTER (UNLESS OTHERWISE NOTED PLANS)
A SDWK	PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR WIDTHS)
	L.O.C. (LIMITS OF CONSTRUCTION)
FIRE LANE	PROPOSED FIRE LANE (REFER TO PLAN FOR STRIPING NOTES)
	FENCE (REF:ARCH)
———— GR ————	PEDESTRIAN GUARDRAIL (REF:ARCH)
0 0 0 0 0 0 0	VEHICLE GUARDRAILS
	PROPOSED CONTOURS PROPOSED CONTOURS - MAJOR PROPOSED CONTOURS - MINOR
PROPOSED UTILITIES:	EXISTING UTILITIES:
FIRE HYDRANTS WATER VALVE MANHOLE (STORM) MANHOLE (WW) INLET INLET	FIRE HYDRANTS WATER VALVE MANHOLE (STORM) MANHOLE (WW) INLET INLET
WATER W — WASTEWATER WW — STORM SEWER SD —	WATER W WASTEWATER WW STORM SEWER SD SD SD
<u> — </u>	ROPERTY LINE ROPERTY LINE (ADJACENT) KISTING EASEMENT

Bid Package 2 Issue For Permitting,



ISSUED: July 28, 2025

REVISIONS

Drawn By

Designer Designer Proj. Arch. Checker


PROJECT NO.


23-134.00 SHEET TITLE

STORM SEWER PLAN - SECTION 3

SHEET NO.

C9.2






Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_STORM SEWER PLAN.dwg Plotted By: Brian Green Date: 7/24/2025 10:14:24 AM Layout: STORM SEWER PLAN - SECTION 5 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), ####

ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS Revision No.

Revision Date

Director Drawn By Approver **Quality Control** Designer Designer


PROJECT NO.

23-134.00

SHEET TITLE STORM SEWER PLAN

SHEET NO.

C9.4





ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145

www.vlkarchitects.com

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS Revision Date

Drawn By Director **Quality Control** Designer Designer Proj. Arch.

Checker PROJECT NO.


23-134.00


SHEET TITLE


STORM SEWER PLAN

SHEET NO.


C9.5








Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_POND PLAN.dwg Plotted By: Brian Green Date: 7/23/2025 8:12:15 PM Layout: POND 1 PLAN Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:30





Main Phone: 512.807.3145 www.vlkarchitects.com

PROPOSED CONTOURS PROPOSED SPOT GRADES EXISTING SPOT GRADES PROPOSED CONTOURS - MAJOR PROPOSED CONTOURS - MINOR --> ---> ---> ----> PROPOSED FLOW DIRECTION L.O.C. (LIMITS OF CONSTRUCTION)

FENCE (REF:ARCH) — PROPERTY LINE (ADJACENT) - 100 - - - - EXISTING EASEMENT

EXISTING TREE (TO REMAIN) ---- 50 'STREAM BUFFERS • • 200' STREAM BUFFERS 400' STREAM BUFFERS

> !!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES

!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR

SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS


SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS

ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746

Bid Package 2 Issue For Permitting,



ISSUED: July 28, 2025

REVISIONS

Revision Date

Director Drawn By Designer **Quality Control** Designer Proj. Arch. Checker

PROJECT NO.


23-134.00

SHEET TITLE POND 1 PLAN


SHEET NO.


C10.0





Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings_Production Drawings\SHT_POND PLAN.dwg Plotted By: Brian Green Date: 7/23/2025 8:12:31 PM Layout: POND 2 PLAN Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:30





2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com SCALE = 1:30

ARCHITECT

DRIPPING SPRINGS ISD DRIPPING SPRINGS, TEXAS

PROPOSED CONTOURS PROPOSED SPOT GRADES EXISTING SPOT GRADES PROPOSED CONTOURS - MAJOR PROPOSED CONTOURS - MINOR L.O.C. (LIMITS OF CONSTRUCTION)

PROPERTY LINE — PROPERTY LINE (ADJACENT) - 100 (•) EXISTING EASEMENT EXISTING TREE (TO REMAIN) ---- 50 ' STREAM BUFFERS 100 ' STREAM BUFFERS • • • 200' STREAM BUFFERS 400' STREAM BUFFERS

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS

Bid Package 2 Issue For Permitting, Bidding and Construction



ISSUED: July 28, 2025

REVISIONS Revision Date

Drawn By **Quality Control** Designer Designer Proj. Arch. Checker

PROJECT NO.

23-134.00

SHEET TITLE POND 2 PLAN

SHEET NO.

C10.1

!!! CAUTION !!! EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES

!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR

SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS

SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

BASIN	AREA	AREA	AREA	RUNOFF	IMPERVOUS	PERVIOUS	T _c	2-YR	10-YR	25-YR	100-YR
NAME	(FT ⁺)	Acres	(MI ²)	CURVE NO.	(%)	(%)	(min)	Q (FT*/S)	Q (FT*/S)	Q (FT ² /S)	Q (FT²/S)
E1	3,880,127	89.08	0.1391804	72	5%	95%	20.2	146.7	323.8	453.0	675.1
OS	1,603,415	36.81	0.0575146	74	2%	98%	16.5	70.3	151.7	210.5	310.8
E1 + OS	5,483,542	125.88	0.1966950		ĺ			214.9	471.8	658.5	978.3

	SCS TYPE B, C & D SOILS, GRASSLAND, GOOD CONDITION
	SCS CURVE NUMBER RANGE: 72-77
	SCS UNIT HYDROGRAPH METHOD
el.	HEC-HMS FREQUENCY STORM RAINFALL DISTRIBUTION

DEPTH DURATION FREQUENCY RAINFALL									
Year	5-MIN	15-MIN	60-MIN	2-HR	3-HR	6-HR	12-HR	24-HR	
2	0.52	1.04	1.93	2.39	2.66	3.13	3.59	4.08	
10	0.80	1.59	2.95	3.76	4.27	5.13	5.94	6.76	
25	0.98	1.95	3.64	4.76	5.50	6.72	7.80	8.87	
100	1.29	2.56	4.78	6.59	7.84	9.86	11.50	13.00	

	HEC-HMS OUTPUT - OPTIONAL ENHANCED METHODS (OEM)									
BASIN	AREA	AREA	AREA	IMPERVOUS	PERVIOUS	T _c	2-YR	10-YR	25-YR	100-YR
NAME	(FT²)	Acres	(MI ²)	(%)	(%)	(min)	Q (FT°/S)	Q (FT°/S)	Q (FT°/S)	Q (FT°/S)
OEM-1	2,628,598	60.34	0.0942880	5%	95%	20.2	99.4	219.4	306.9	457.3
OEM-2	1,460,369	33.53	0.05238353	0%	100%	16.5	86.1	171.6	230.9	330.3

			H	IEC-HMS OUT	PUT - PROPOS	ED					
BASIN OR JUNCTION	AREA	AREA	AREA	RUNOFF	IMPERVOUS	PERVIOUS	Tc	2-YR	10-YR	25-YR	100-YR
NAME	(FT [*])	Acres	(MI ²)	CURVE NO.	(%)	(%)	(min)	Q (FT ² /S)	Q (FT'/S)	Q (FT*/S)	Q (FT'/S
P1-1	2,628,598	60.34	0.0942880	72	65%	35%	10.8	225.8	377.1	480.8	657.1
POND OUTFLOW		į.		M.	St. 118	···		45.4	203.9	335.4	520.9
POND PEAK STORAGE (A	CRE-FEET)							13.2	15.9	17.1	18.7
POND PEAK ELEVATION	(FT MSL)							1,102.1	1,102.7	1,103.0	1,103.4
OS	1,603,415	36.81	0.0575146	74	2%	98%	16,5	70.3	151.7	210.5	310.8
P1-2	729,034	16.74	0.0261505		3%	97%	13.3	32.2	71.7	100.7	150.6
P1 OUTFALL	4,961,047	113.89	0.1779531					134.9	400.4	632.9	972.5
P2-1	1,460,369	33.53	0.0523835	76	42%	58%	8.7	121.4	214.8	279.1	387.9
POND OUTFLOW				•				42.8	99.0	141.2	212.6
POND PEAK STORAGE (A	CRE-FEET)							4.7	6.3	7.3	8.9
POND PEAK ELEVATION	(FT MSL)							1,114.7	1,115.6	1,116.2	1,117.0
P2-2	59,872	1.37	0.0021476	75	0%	100%	7.8	3.5	7.6	10.4	15.3
P2 OUTFALL	1,520,241	34.90	0.0545311		**	W 43=0	-	44.1	102.4	146.2	220.5

SCS TYPE B, C & D SOILS, GRASSLAND, GOOD CONDITION
SCS CURVE NUMBER RANGE: 72-76
SCS UNIT HYDROGRAPH METHOD
HEC-HMS FREQUENCY STORM RAINFALL DISTRIBUTION

	50.	DEPTH	DURATION FRE	QUENCY RAIN	NFALL	2-1-1		1
Year	5-MIN	15-MIN	60-MIN	2-HR	3-HR	6-HR	12-HR	24-HR
2	0.52	1.04	1.93	2.39	2.66	3.13	3.59	4.08
10	0.80	1,59	2.95	3,76	4.27	5.13	5.94	6.76
25	0.98	1.95	3.64	4.76	5.50	6.72	7.80	8.87
100	1.29	2.56	4.78	6.59	7.84	9.86	11.50	13.00

HEC-HMS OUTPUT - STORM EVENT DELTA									
JUNCTION	2-YR ∆	10-YR ∆	25-YR ∆	100-YR ∆					
NAME	Q (FT³/S)	Q (FT'/S)	Q (FT³/S)	Q (FT ³ /S)					
P1 OUTFALL vs. E1+OS	-80.0	-71.4	-25.6	-5.8					
P2 OUTFALL vs. E2	-13.6	-13.5	-10.3	-4.8					

		1	HEC-HMS OUTP	UT - OPTIONA	L ENHANCED I	METHODS (OE	M)				
BASIN	AREA (FT ^z)	AREA	AREA	RUNOFF CURVE NO.	IMPERVOUS (%)	PERVIOUS (%)	Tc	2-YR Q (FT³/S)	10-YR Q (FT³/S)	25-YR Q (FT ³ /S)	100-YR Q (FT³/S)
NAME		Acres (MI ²)	(MI ²)				(min)				
OEM-1	2,628,598	60.34	0.0942880	72	5%	95%	20.2	99.4	219.4	306.9	457.3
OEM-2	1,460,369	33.53	0.05238353	76	0%	100%	16.5	86.1	171.6	230.9	330.3

DRIPPING SPRINGS HIGH SCHOOL #2

Drainage Area Control (DA)

Water Quality Control Calculations:

Water Quality Volume:

Water Quality Elevation

Elevation of Overflow

Batch Detention Pond:

Elev Depth

1097.0

1098.0

1099.7

Cd = 0.6

g = 32.2

h2 = 0.00

h1 = 4.10

Pipe Size =

t = 151200 sec

ft

Load Removal (L_M) for this basin

Total WQV

On-site Water Quality Volume

Area (sf)

sf sf

96,292 71,701

130,930 113,611

48-Hour Drawdown (Falling Head Orifice Equation)

ft/s^2

A = 130930 sq. ft. (WQE surface area)

Area Avg Area Inc. Vol

5,889

(Orifice Coefficient)

(Gravitational Acceleration)

(WQE - Orifice Elevation)

0.73 sq. ft. =

(42hr Drawdown Time in Seconds)

47,110 29,444 29,444

Storage for Sediment

Drainage Area Impervious Cover

Batch Detention Pond #1

Drainage Area Data

HEC-HMS OUTPUT	- STORM EVEN	T DELTA
JUNCTION	2-YR ∆	2-YR △
NAME	Q (FT³/S)	PCT.
POND 1 vs. OEM-1	-54.0	46%
POND 2 vs OFM-2	.42.2	50%

DRIPPING SPRINGS HS #2 POND 1

WSEL	AREA	AREA	STORAGE	STORAGE	DISCHARGE	NOTES
(FT)	(SF)	(AC)	(CF)	(AF)	(CFS)	
1,096.0	823	27	0	0,0	0	
1,097.0	11,777	0.27036	5,889	0.1	0	1. 0.0
1,098.0	47,110	1.08150	35,332	0.8	0	
1,099.0	96,292	2.21056	107,033	2.5	0	
1,099.7	130,930	3.00574	186,561	4.3	0	WQE
1,100.0	145,775	3.34653	228,067	5.2	0	
1,101.0	172,954	3.97048	387,431	8.9	14	
1,102.0	179,643	4.12404	563,730	12.9	43	1.
1,102.1	180,051	4.13339	574,520	13.2	45	2-YR
1,102.7	184,310	4.23117	688,747	15.8	204	10-YR
1,103.0	186,436	4.27998	746,769	17.1	338	25-YR
1,103.4	188,916	4.33692	814,332	18.7	521	100-YR
1,104.0	193,326	4.43815	936,650	21.5	913	TOP OF BER

Weir # 1 @ 1100.10 - 5.5' long Weir # 2 @ 1102.10 - 100' long

DRIPPING SPRINGS HS #2 POND 2

WSEL	AREA	AREA	STORAGE	STORAGE	DISCHARGE	NOTES
(FT)	(SF)	(AC)	(CF)	(AF)	(CFS)	
1,110.0	9 4 9	===	H	0.0	0	
1,111.0	14,885	0.34171	7,443	0.2	0	0.00
1,112.0	46,416	1.06556	38,093	0.9	0	
1,112.9	61,065	1.40187	86,460	2.0	0	WQE
1,113.0	62,693	1.43923	92,648	2.1	0	
1,114.0	67,566	1.55110	157,777	3.6	17	
1,114.7	71,103	1.63230	206,311	4.7	43	2-YR
1,115.0	72,619	1.66710	227,924	5.2	59	
1,115.6	75,992	1.74453	275,479	6.3	99	10-YR
1,116.0	77,889	1.78809	303,178	7.0	125	
1,116.2	78,993	1.81343	318,866	7.3	141	25-YR
1,117.0	83,410	1.91483	383,827	8.8	209	
1,117.0	83,641	1.92013	387,168	8.9	213	100-YR
1,118.0	89,183	2.04736	470,124	10.8	306	TOP OF BE

Weir # 1 @ 1112.90 - 5' long Weir # 2 @ 1114.20 - 6' long



Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348. Characters shown in red are data entry fields. Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet. 1. The Required Load Reduction for the total project: Calculations from RG-348 Pages 3-27 to 3-30 Page 3-29 Equation 3.3: L_M = 27.7(A_N x P) L_{M.TOTAL PROJECT} = Required TSS removal resulting from the proposed development = 80% of increased load

P = Average annual precipitation, inches Site Data: Determine Required Load Removal Based on the Entire Project County = Hays
Total project area included in plan *= 110.61 acres Predevelopment impervious area within the limits of the plan = 4.40 acres

Total post-development impervious area within the limits of the plan = 53.77 acres

Total post-development impervious cover fraction = 0.49

P = 33 inches L_{M TOTAL PROJECT} = 45129 lbs. * The values entered in these fields should be for the total project area. Number of drainage basins / outfalls areas leaving the plan area = 3

2. Drainage Basin Parameters (This information should be provided for each basin): Drainage Basin/Outfall Area No. = 1 Total drainage basin/outfall area = 60.34 acres Predevelopment impervious area within drainage basin/outfall area = 3.02 acres
Post-development impervious area within drainage basin/outfall area = 39.22 acres

Post-development impervious fraction within drainage basin/outfall area = 0.65 L_{M THIS BASIN} = 33094 lbs. 3. Indicate the proposed BMP Code for this basin.

Proposed BMP = Wet Bacin Batch Detention 4. Calculate Maximum TSS Load Removed (L_B) for this Drainage Basin by the selected BMP Type. RG-348 Page 3-33 Equation 3.7: L_R = (BMP efficiency) x P x (A₁ x 34.6 + A₂ x 0.54) A_C = Total On-Site drainage area in the BMP catchment area A_t = Impervious area proposed in the BMP catchment area A_P = Pervious area remaining in the BMP catchment area L_R = TSS Load removed from this catchment area by the proposed BMP

A_C = 60.34 acres A₁ = 39.22 acres Ap = 21.12 acres L_R = 41095 lbs 5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

Desired L_{M THIS BASIN} = 33094 lbs. F = 0.81 6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area, Calculations from RG-348 Pages 3-34 to 3-36 Rainfall Depth = 1.12 inches Post Development Runoff Coefficient = 0.60 On-site Water Quality Volume = 147804 cubic feet

Calculations from RG-348 Pages 3-36 to 3-37 Off-site area draining to BMP = 0.00 acres Off-site Impervious cover draining to BMP = 0.00 acres
Impervious fraction of off-site area = 0 Off-site Water Quality Volume = 0 cubic feet Storage for Sediment = 29561 Total Capture Volume (required water quality volume(s) x 1.20) = 177365 cubic feet The following sections are used to calculate the required water quality volume(s) for the selected BMP The values for BMP Types not selected in cell C45 will show NA.

Texas Commission on Environmental Quality TSS Removal Calculations 04-20-2009

Project Name: Dripping Springs HS 2

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348. Characters shown in red are data entry fields. Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet. 1. The Required Load Reduction for the total project Calculations from RG-348 Pages 3-27 to 3-30

Page 3-29 Equation 3.3; L_M = 27.7(A_N x P) L_{M TOTAL PROJECT} = Required TSS removal resulting from the proposed development = 80% of increased load A_N = Net increase in impervious area for the project P = Average annual precipitation, inches Site Data: Determine Required Load Removal Based on the Entire Project Predevelopment impervious area within the limits of the plan" = 4.40 acres

fotal post-development impervious area within the limits of the plan" = 53.77 acres

1. Acres to the plan" = 6.49 acres

1. Acres to the plan" = 6.49 acres

1. Acres to the plan" = 6.49 acres to the plan" acres to the pl County = Hays
Total project area included in plan *= 110.61 acres Total post-development impervious area within the limits of the plar* = L_{M TOTAL PROJECT} = 45129 lbs. * The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = 3 2. Drainage Basin Parameters (This information should be provided for each basin) Drainage Basin/Outfall Area No. = 2 Total drainage basin/outfall area = 33.53 acres Predevelopment impervious area within drainage basin/outfall area = 0.00 acres

Post-development impervious area within drainage basin/outfall area = 14.08 acres Post-development impervious fraction within drainage basin/outfall area = 0.42 L_{M THIS BASIN} = 12873 lbs. 3. Indicate the proposed BMP Code for this basin

Proposed BMP = Wet Basin Batch Detention Removal efficiency = 91 percent 4. Calculate Maximum TSS Load Removed (Le) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7: L_R = (BMP efficiency) x P x (A_c x 34.6 + A_P x 0.54) A_C = Total On-Site drainage area in the BMP catchment area A = Impervious area proposed in the BMP catchment area A_P = Pervious area remaining in the BMP catchment area L_R = TSS Load removed from this catchment area by the proposed BMP A_C = 33.53 acres A_t = 14.08 acres A_o = 19.45 acres

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall are Desired L_{M THIS BASIN} = 12873 lbs. F = 0.86

6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area Calculations from RG-348 Pages 3-34 to 3-36 Post Development Runoff Coefficient = 0.41

L_R = 14948 lbs

On-site Water Quality Volume = 68362 cubic feet Calculations from RG-348 Pages 3-36 to 3-37 Off-site area draining to BMP = 0.00 acres Off-site Impervious cover draining to BMP = 0.00 acres Impervious fraction of off-site area = 0 Off-site Runoff Coefficient = 0.00 Off-site Water Quality Volume = 0 cubic feet Storage for Sediment = 13672

Total Capture Volume (required water quality volume(s) x 1.20) = 82034 cubic feet

The following sections are used to calculate the required water quality volume(s) for the selected BMF The values for BMP Types not selected in cell C45 will show NA

Pre-Developed Tc Calculations (SCS Unit Hydrograph Model)

PROJECT NAME: DSISD High School No. 2 PROJECT NO. 3-00895

			Sheet Fl	ow			Shallow (Concentrat	ed Flow			Shallow C	concentra	ated Flow	/	Į.		Open Cha	nnel Fk	wc		Total T _c	(minimum 5 min)	
AREA No.	L (ft)	n	s (ft/ft)	P _{2 (in)}	t _{sheet min}	L (ft)	Surface	s (ft/ft)	V (fps)	t _{shallow min}	L (ft)	Surface	s (ft/ft)	V (fps)	t _{shallow} min	L (ft)	n	s (ft/ft)	R	V (fps)	t _{channel min}	min	hrs	Tlag
E1	100	0.15	0.0100	4.14	11.37	1212	Unpaved	0.0350	3.02	6.69						874	0.04	0.0330	1.00	6.75	2.16	20.2	0.34	12.1
os	100	0.40	0.0900	4.14	10.34	1128	Unpaved	0.0363	3.08	6.11												16.5	0.27	9.9
E2	100	0.15	0.0400	4.14	6.53	1943	Unpaved	0.0211	2.34	13.82]	Ĭ_						20.3	0.34	12.2

P₂ = 2-year, 24-hour rainfall depth (in) =

Wetted perimeter, Pw

T_c = t_{sheet} + t_{shellow} + t_{channel} EQUATIONS USED: where: $t_{sheet} = 0.007(nL)^{0.08} / (P_2)^{0.5}S^{0.4}$ t_{shallow} = L/V_{shallow}

V_{shallow} = 16.1345 x Unpaved V_{shallow} = 20.3282 x Paved $V_{channel} = 1.49R^{2/3}S^{1/2} / n$ t_{channel} = L/V_{channel} where: *R = Hydraulic radius = A / Pw Cross sectional flow area, A 4.14 FOR AUSTIN AREA - ZONE 1

Tc = t_{sheet} + t_{shellow} + t_{channel} EQUATIONS USED: where: $t_{\text{sheet}} = 0.007 (nL)^{0.08} / (P_2)^{0.5} S^{0.4}$ t_{shallow} = L/V_{shallow} t_{channel} = L/V_{channel}

P₂ = 2-year, 24-hour rainfall depth (in) = V_{shallow} = 16.1345 x Unpaved V_{shallow} = 20.3282 x Paved V_{channel} = 1.49R^{2/3}S^{1/2} / n *R = Hydraulic radius = A / Pw Cross sectional flow area,A

Wetted perimeter, Pw

DRIPPING SPRINGS HIGH SCHOOL #2 Batch Detention Pond #2

Pipe Size =

Drainage Area Data Drainage Area Control (DA) Drainage Area Impervious Cover Water Quality Control Calculations : Load Removal (L_M) for this basin Water Quality Volume: 68,362 CF On-site Water Quality Volume 13,672 CF Storage for Sediment 82,034 CF Total WQV 1,112.90 FT Water Quality Elevation Elevation of Overflow 1,112.90 FT

Batch Detention Pond: Stage (ft)* Area (sf) Area Avg Area Inc. Vol Total Vol ac-ft sf cf ft 7,443 86,459

48-Hour Drawdown (Falling Head Orifice Equation) A = 61065 sq. ft. (WQE surface area) Cd = 0.6(Orifice Coefficient) (36hr Drawdown Time in Seconds) t = 129600 sec g = 32.2ft/s^2 (Gravitational Acceleration) h2 = 0.00h1 = 2.90(WQE - Orifice Elevation)

0.33 sg. ft. =

Falling head orifice equation: $\frac{-2A}{\sqrt{2}} * \left[\sqrt{h_2} - \sqrt{2} \right]$ $= \frac{1}{C_d * t * \sqrt{2g}}$

Post-Developed Tc Calculations (SCS Unit Hydrograph Model)

PROJECT NAME PROJECT NO.	ž.		3-00895	gh Schoo	l No. 2								Date:	7/6/	2025									
	Sheet Flow					Shallow Concentrated Flow					Shallow Concentrated Flow				Open Channel Flow						Total T _{c (minimum 5 min)}		I	
AREA No.	L (ft)	n	s (ft/ft)	P _{2 (in)}	t _{sheet min}	L (ft)	Surface	s (ft/ft)	V (fps)	t _{shallow min}	L (ft)	Surface	s (ft/ft)	V (fps)	t _{shalkow} min	L (ft)	n	s (ft/ft)	R	V (fps)	¹ channel min	min	hrs	Tlag
P1-1	100	0.15	0.0400	4.14	6.53	65	Unpaved	0.0538	3.74	0.29					Ī	2250	0.013	0.0109	0.70	9.43	3.98	10.8	0.18	6.5
P1-2	12	0.016	0.0150	4.14	0.30	58	Unpaved	0.0776	4.49	0.22			-			2450	0.045	0.0167	1.34	5.21	7.84			
	88	0.15	0.0625	4.14	4.93																	13.3	0.22	8.0
os	100	0.40	0.0900	4.14	10.34	1128	Unpaved	0.0363	3.08	6,11												16.5	0.27	9.9
		56			-27	2 2			56			*	era e					A 10			101			
P2-1	100	0.15	0.0450	4.14	6.23	407	Unpaved	0.0688	4.23	1.60	180	Paved	0.0278	3.39	0.89							8.7	0.15	5.2
P2-2	100	0.15	0.0350	4.14	6.89	165	Unpaved	0.0364	3.08	0.89												7.8	0.13	4.7

33,094 LB

147,804 CF

177,365 CF

1.099.70 FT

Storage (cf)

186,561

Total Vol

ac-ft

29,561

33,094 LB


186,561 CF

1,100.10 FT

Falling head orifice equation:

 $A_o = \frac{-2A}{C_d * t * \sqrt{2g}} * \left[\sqrt{h_2} - \sqrt{h_1} \right].$

4.14 FOR AUSTIN AREA - ZONE 1



!!! WARNING !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

C10.2

Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings\SHT_POND PLAN.dwg Plotted By: Brian Green Date: 7/23/2025 8:12:31 PM Layout: POND DETAILS 1 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:30

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

ARCHITECT

Bid Package 2 Issue For Permitting,

Bidding and Constructior 安 DAVID P SMITH Z 56239

ISSUED: July 28, 2025

REVISIONS Revision Date Revision No.

Z

Director Drawn By Author


Approver **Quality Control** Designer Designer Proj. Arch. Checker


PROJECT NO. 23-134.00


SHEET TITLE


POND DETAILS 1


SHEET NO.












CONTROLLER CIRCUIT DIAGRAM

LOGIC CONTROLLER CYCLE OVERVIEW:

CONTROLLER WILL OPEN THE VALVE ONCE A WEEK FOR THE TWO HOURS TO DRAIN.

- 1. CASE 1: A SINGLE RAIN EVENT FILLS THE BATCH DETENTION BASIN. THE BASIN HOLDS THE DIVERTED STORM WATER FOR THE DETENTION TIME (12 HOURS) AND THEN RELEASES THE WATER. ONCE THE BATCH DETENTION BASIN IS EMPTY, A DELAY OF 2 HOURS IS STARTED TO ALLOW THE BASIN TO COMPLETELY DRAIN, AND THEN A CLOSE SIGNAL IS SENT TO THE ACTUATOR TO CLOSE THE VALVE.
- 2. CASE 2: A SINGLE RAIN EVENT OCCURS, BUT DOES NOT COMPLETELY FILL THE BATCH DETENTION BASIN. THE BASIN HOLDS THE WATER FOR THE DETENTION PERIOD (12 HOURS), AND THEN RELEASES IT. ONCE THE BATCH DETENTION BASIN IS EMPTY, A DELAY OF 2 HOURS IS STARTED TO ALLOW THE BASIN TO COMPLETELY DRAIN, AND THEN A CLOSE SIGNAL IS SENT TO THE ACTUATOR TO CLOSE THE VALVE. 3. CASE 3: A SINGLE RAIN EVENT FILLS THE BATCH DETENTION BASIN UNDER THE TRIP POINT OF THE LEVEL SENSOR. THE LEVEL SENSOR DOES NOT TRIP. THE CAPTURED WATER IS HELD UNTIL IT INFILTRATES / EVAPORATES OR IS JOINED BY STORM WATER FROM A SUBSEQUENT STORM.
- . CASE 4: BEGINS THE SAME AS CASE 1. DURING THE DRAWDOWN PERIOD, ONE OR MORE ADDITIONAL RAIN EVENTS OCCUR CAUSING ADDITIONAL WATER TO ENTER THE BATCH DETENTION BASIN. THE VALVE REMAINS OPEN AND ADDITIONAL WATER VOLUME IS DRAINED. ONCE THE BATCH DETENTION BASIN IS EMPTY, A DELAY OF 2 HOURS IS STARTED TO ALLOW THE BASIN TO COMPLETELY DRAIN, AND THEN A CLOSE SIGNAL IS SENT TO THE ACTUATOR TO CLOSE THE VALVE. 5. CASE 5: BEGINS THE SAME AS CASE 2. DURING THE DRAWDOWN PERIOD, ONE OR MORE OF THE ADDITIONAL RAIN EVENTS CAN OCCUR CAUSING ADDITIONAL WATER TO IS STARTED TO ALLOW THE BASIN TO COMPLETELY DRAIN, AND THEN A CLOSE SIGNAL IS SENT TO THE ACTUATOR TO CLOSE THE VALVE. 6. CASE 6: INTERMITTENT NUISANCE WATER LESS THAN THE FLOAT ON ELEVATION. TO ALLEVIATE SMALL FLOWS DUE TO IRRIGATION OUTSIDE OF STORM EVENTS, THE

BATCH DETENTION POND CONTROLLER INFORMATION									
COMPONENT	DESCRIPTION	VOLTAGE							
	SOLAR CHARGED 12 VDC BATTERY (MODEL MK POWERED 8GU1) (OR APPROVED								
POWER SYSTEM	EQUAL)								
LOGIC CONTROLLER	IDEC FL1C-H12RCE (OR APPROVED EQUAL)	12							
	SOUTHWEST PHOTOVOLTAIC MODEL BBG-1 (15.75" WIDE x 9.75" DEEP x 11.75"								
PARTS ENCLOSURE	TALL) (OR APPROVED EQUAL)								
NATURE OF EVENT SENSING	ANCHOR SCIENTIFIC FLOAT SWITCH (OR APPROVED EQUAL)								
	KEYSTONE 4" BUTTERFLY VALVE WITH OVER TORQUE SENSORS AND MECHANICAL								
	HAND CRANK FOR PHYSICAL OVERRIDE IF NECESSARY. ABLE TO WITHSTAND 100								
VALVE TYPE	psi MINIMUM. (OR APPROVED EQUAL)								
ACTUATOR	EPI-6 12 VDC. ABLE TO WITHSTAND 100 psi MINIMUM. (OR APPROVED EQUAL)	12							
POWER CONSUMPTION (ACTUATOR,	242.58 W, 46.5 W-HOURS								
CONTROLLER, RELAY, PLC)									



ATTACHMENT N:

Inspection, Maintenance, Repair and Retrofit Plan

PROJECT NAME: Dripping Springs High School No. 2

Batch Detention Pond:

Inspections, Inspections should be conducted a minimum of twice a year. One inspection should take place during wet weather to determine if the basin is meeting the target detention time of 12 hours and a drawdown time of no more than 48 hours. The remaining inspections should occur between storm events so that manual operation of the valve and controller can be verified. The level sensor in the basin should be inspected and any debris or sediment in the area should be removed. The outlet structure and the trash screen should be inspected for signs of clogging. Debris and sediment should be removed from the orifice and outlet(s) as described below. Debris obstructing the valve should be removed. During each inspection, erosion areas inside and downstream of this BMP should be identified and repaired/revegetated immediately.

Mowing: The basin, basin side-slopes, and embankment of the basin must be mowed to prevent woody growth and control weeds. A mulching mower should be used, or the grass clippings should be caught and removed. Mowing should take place at least twice a year, or more frequently if vegetation exceeds 18 inches in height. More frequent mowing to maintain aesthetic appeal may be necessary in landscaped areas.

Litter and Debris Removal: Litter and debris removal should take place at least twice a year, as part of the periodic mowing operations and inspections. Debris and litter should be removed from the surface of the basin. Particular attention should be paid to floatable debris around the outlet structure. The outlet should be checked for possible clogging or obstructions and any debris removed.

Erosion Control: The basin side slopes and embankment all may periodically suffer from slumping and erosion. To correct these problems, corrective action, such as regarding and revegetation, may be necessary. Correction of erosion control should take place whenever required based on the periodic

Nuisance Control: Standing water or soggy conditions may occur in the basin. Some standing water may occur after a storm event since the valve may close with 2 to 3 inches of water in the basin. Some flow into the basin may also occur between storms due to spring flow and residential water use that enters the storm sewer system. Twice a year, the facility should be evaluated in terms of nuisance control (insects, weeds, odors, algae, etc.).

Structural Repairs and Replacement: With each inspection, any damage to structural elements of the basin (pipes, concrete drainage structures, retaining walls, etc.) should be identified and repaired immediately. An example of this type of repair can include patching of cracked concrete, sealing of voids, removal of revegetation from cracks and joints. The various inlet/outlet structures in a basin will eventually deteriorate and must be

Sediment Removal: A properly designed batch detention basin will accumulate quantities of sediment over time. The accumulated sediment can detract from the appearance of the facility and reduce the pollutant removal performance of the facility. The sediment also tends to accumulate near the outlet structure and can interfere with the level sensor operation. Sediment shall be removed from the basin at least every 5 years, when sediment depth exceeds 6 inches, when the sediment interferes with the level sensor or when the basin does not drain within 48 hours. Care should be taken not to compromise the basin lining during

Page 1 of 3

Logic Controller. The Logic Controller should be inspected as part of the twice-yearly investigations. Verify that the external indicators (active, cycle in progress) are operating properly by turning the controller off and on, and by initiating a cycle by triggering the level sensor in the basin. The valve should be manually opened and closed using the open/close switch to verify valve operation and to assist in inspecting the valve for debris. The solar panel should be inspected and any dust or debris on the panel should be carefully removed. The controller and all other circuitry and wiring should be inspected for signs of corrosion, damage from insects, water leaks, or other damage. At the end of the inspection, the controller should be reset.

Once a vegetated area is well established, little additional maintenance is generally necessary. The key to establishing a viable vegetated feature is the care and maintenance it receives in the first few months after it is plant ed. Once established, all vegetated BMPs require some basic maintenance to insure the health of the

Seasonal Mowing and Lawn Care: If the filter strip is made up of turf grass, it should be mowed as needed to limit vegetation height to 18 inches, using a mulching mower (or removal of clippings). If native grasses are used, the filter may require less frequent mowing, but a minimum of twice annually. Grass clippings and brush debris should not be deposited on vegetated filter strip areas. Regular mowing should also include weed control practices, however herbicide use should be kept to a minimum (Urbonas et al., 1992). Healthy grass can be maintained without using fertilizers because runoff usually contains sufficient nutrients. Irrigation of the site can help assure a dense and healthy vegetative cover.

Inspection: Inspect filter strips at least twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable. The strip should be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance needs. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish

Debris and Litter Removal: Trash tends to accumulate in vegetated areas, particularly along highways. Any filter strip structures (i.e. level spreaders) should be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but should be performed no less than 4 times per year.

Sediment Removal: Sediment removal is not normally required in filter strips, since the vegetation normally grows through it and binds it to the soil. However, sediment may accumulate along the upstream boundary of the strip preventing uniform overland flow. Excess sediment should be removed by hand or with flat-

Grass Reseeding and Mulching: A healthy dense grass should be maintained on the filter strip. If areas are eroded, they should be filled, compacted, and reseeded so that the final grade is level. Grass damaged during the sediment removal process should be promptly replaced using the same seed mix used during filter strip establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Corrective maintenance, such as weeding or replanting should be done more frequently in the first two to three years after installation to ensure stabilization. Dense vegetation may require irrigation immediately after planting, and during particularly dry periods, particularly as the vegetation is initially

Page 2 of 3

Page 3 of 3

!!! CAUTION !!!

EXISTING OVERHEAD UTILITIES IN VICINITY

CONTRACTOR SHALL EXERCISE EXTREME CAUTION

WHEN WORKING NEAR ELECTRIC FACILITIES

!!! WARNING !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY

OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR


VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS

SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY

RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY

OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS

REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"



Issue For Permitting, Bidding and Constructior



Bid Package 2

ARCHITECT

SPRINGS INGS, TEX

2700 Via Fortuna, Suite 230

Main Phone: 512.807.3145

Austin, Texas 78746

www.vlkarchitects.com

ISSUED: July 28, 2025

REVISIONS Revision No.

Director Drawn By

Approver Designer Designer Proj. Arch. Checker

PROJECT NO.

SHEET TITLE

SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING LITH ITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION. "RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A

SHEET NO.

C10.3


Drawing Path: G:\Projects\3-00895\2 Engineering\2.0 CAD_Production Drawings\SHT_POND PLAN.dwg Plotted By: David Smith Date: 7/26/2025 2:30:51 PM Layout: POND DETAILS 2 Page Size: ARCH full bleed E1 (30.00 x 42.00 Inches), 1:30


Revision Date


Quality Control


23-134.00


POND DETAILS 2

















1. STEEL OR WOOD POSTS WHICH SUPPORT THE SILT FENCE SHALL BE INSTALLED ON A SLIGHT ANGLE TOWARD THE ANTICIPATED RUNOFF SOURCE. POST MUST BE EMBEDDED A MINIMUM OF 300 mm (12 INCHES). IF WOOD POSTS CANNOT ACHIEVE 300 mm (12 inches) DEPTH, USE STEEL POSTS. 2. THE TOE OF THE SILT FENCE SHALL BE TRENCHED IN WITH A SPADE OR MECHANICAL TRENCHER, SO THAT THE DOWNSLOPE FACE OF THE TRENCH IS FLAT AND PERPENDICULAR TO THE LINE OF FLOW. 3. THE TRENCH MUST BE A MINIMUM OF 150 mm (6 Inches) DEEP AND 150 mm (6 Inches) WIDE TO ALLOW FOR THE SILT FENCE FABRIC TO BE LAID IN THE GROUND AND BACKFILLED WITH COMPACTED 4. SILT FENCE FABRIC SHOULD BE SECURELY FASTENED TO EACH STEEL OR WOOD SUPPORT POST OR TO WOVEN WIRE, WHICH IS IN TURN ATTACHED TO THE STEEL OR WOOD FENCE POST. 5. INSPECTION SHALL BE MADE WEEKLY OR AFTER EACH RAINFALL EVENT AND REPAIR OR


6. SILT FENCE SHALL BE REMOVED WHEN THE SITE IS COMPLETELY STABILIZED SO AS NOT TO BLOCK OR 7. ACCUMULATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF 150 mm (6 inches). THE SILT TO ADDITIONAL SILTATION.

CITY OF AUSTIN ATERSHED PROTEOTION DEPARTMENT	SILT FENCE	
my 1. Ry 9/1/2011	THE ARCHITECT/ENGINEER ASSUMES RESPONSEILITY FOR APPROPRIATE USE OF THIS STANDARD.	standard no. 642S-1









1. DAILY INSPECTION SHALL BE MADE BY THE CONTRACTOR AND SILT ACCUMULATION MUST BE REMOVED WHEN DEPTH REACHES 2". 2. CONTRACTOR SHALL MONITOR THE PERFORMANCE OF INLET PROTECTION DURING EACH RAINFALL EVENT AND IMMEDIATELY CLEAN THE INLET PROTECTION

AREA INLET PROTECTION DETAIL

IF EXCESSIVE PONDING OCCURS. 3. INLET PROTECTIONS SHALL BE REMOVED AS SOON AS THE SOURCE OF SEDIMENT IS STABILIZED.

> Bid Package 2 Issue For Permitting, **Bidding and Construction**


ARCHITECT

2700 Via Fortuna, Suite 230

Main Phone: 512.807.3145

Austin, Texas 78746

www.vlkarchitects.com



RING

Z

Author **Quality Control** Designer Proj. Arch.

SHEET TITLE

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS

!!! CAUTION !!! **EXISTING OVERHEAD UTILITIES IN VICINITY**

CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES

!!! **WARNING** !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY

OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICE

AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

C11.0

COPYRIGHT © 2025 VLK ARCHITECTS, LLC

Z

ISSUED: July 28, 2025

REVISIONS Revision Date Revision No.


Director Drawn By Approver Designer

PROJECT NO.

23-134.00

CONSTRUCTION DETAILS (1 OF 5)


SHEET NO.



COPYRIGHT © 2025 VLK ARCHITECTS, LLC

Z

RING



PROPERTY

RECESSED

OPTION 2

(4") OR (6")

LIFTING EYES

AWU

TOTAL (INCHES)

BYPASS LINE

FLANGED 90° ELBOW

16 FLANGED 90° ELBOW

TOTAL (INCHES)

AUSTIN WATER UTILITY

7 OF BYPASS LINE

CLEARANCE FROM INSIDE WALL TO TEE

BYPASS GATE VALVE WITH HAND WHEEL

14+15 X FLANGE DI PIPE + (15) DISMANTLING JOINT (DJ)

1 CLEARANCE FROM VALVE WALL TO TEE

CLEARANCE FROM INSIDE WALL TO CENTER

(14) FLANGED X PLAIN END DI PIPE + (15) RESTRAINED

RESPONSIBILITY OWNER'S

6' x 9' PRECAST

METER VAULT

H20 LOADING

CONNECTION (4") OR (6") MJ TEE

OPTION 1

7" MIN. - 9" MAX. * CLEAR

ADJUSTABLE PIPE SADDLE SUPPORT PER SPL

MJ x MJ ADAPTOR (4") OR (6")
RESTRAINT PER SPL WW-27B MJ x MJ GATE VALVE

3", 4" AND 6" COMPOUND & TURBINE METER

INSTALLATIONS

RESPONSIBILITY FOR APPROPRIATE USE 520-AW-06

THE ARCHITECT/ENGINEER ASSUMES

36" x 36" HATCH INCLUDING SAFETY -

SPRINGS AND ALL REQUIREMENTS OF

4.5' MIN. - 5.5' MAX. CLEAR

PIPE BEDDING STONE PER

SPECIFICATION 510.2(2)(a)

(4") OR (6") FLG TEE -

(4") OR (6") FLG x MJ-/

CITY OF AUSTIN


Lathi & flowers 11/19/2015

AUSTIN WATER UTILIT

SPL NO. WW-614 CENTERED ON VAULT LID

REMOVABLE TOP

GRATING, COMPRESSION-ASSIST



108.0" 108.0" 108.0" 108.0" 108.0" 108.0"

8" 8" 12" 12" 6" 6

6 1/2" 6 1/2" 6 1/2" 8" 8

6 1/2" 6 1/2" 6 1/2" 6 1/2" 8"

9" 9" 9" 10 1/2" 10 1/2"

6 1/2" 6 1/2" 6 1/2" 6 1/2" 8" 8 6 1/2" 6 1/2" 6 1/2" 6 1/2" 8" 8"

8" 8" 12" 12" 6" 6"

3", 4" AND 6" COMPOUND & TURBINE METER

INSTALLATIONS


23" 23" 23" 20" 20"


FLANGE COUPLING ADAPTOR (RFCA) OR (14) FLANGE 57" 57" 49" 49" 53 1/2" 53 1/2"


METER VAULT MUST BE PLACED AT THE PROPERTY LINE WITHIN PUBLIC RIGHT-OF-WAY OR WITHIN A DEDICATED WATER METER EASEMENT. METER SHALL NOT BE PLACED IN THE PATH OF VEHICULAR TRAFFIC INCLUDING ROADWAYS, DRIVEWAYS AND PARKING LOTS. METERS MAY NOT BE PLACED IN SIDEWALKS UNLESS SPECIFICALLY APPROVED BY AUSTIN WATER. METERS MUST BE ACCESSIBLE TO SERVICE VEHICLES AND SHALL NOT BE ENCLOSED WITHIN PROPERTY FENCES.


2. ALL PIPE AND FITTINGS FROM MAIN TO CUSTOMER VALVE SHALL BE RESTRAINED.

3. FACTORY NOTCHES WHERE PIPING GOES THROUGH VAULT WALL SHALL BE FILLED WITH NON-SHRINK GROUT PER SPL NO. WW-704A.









CITY OF AUSTIN

STANDARD PRODUCTS LIST

METER VAULTS


SPL No. WW-298





ARCHITECT

2700 Via Fortuna, Suite 230 Austin, Texas 78746 Main Phone: 512.807.3145 www.vlkarchitects.com

	TOP VIEW NOTES: 1. MATERIAL SHALL BE GRAY CAST IRO 2. THE MANUFACTURER'S IDENTIFICAT AND THE COUNTRY WHERE CAST, ONTO EACH LID, FRAME, COLLAR ANI 3. DRAFT AND SHRINKAGE ALLOWANC WITH NORMAL FOUNDRY PRACTICE. 4. CASTING FINISH BY MANUFACTURER FINS AND FLASHING, AND PAINT WITH	N, ASTM A FION AND SHALL E D BASE. E SHALL SHALL IF	VALVE B A48, GRAI D CASTIN BE IN AC NCLUDE F	DE 30B. IG NUM NCTLY C	BER, C7 REC C6 REC NCE C5	FRAME: I CLAIMED BASE: 78 ETTERING	SS LID: 15 LBS 23 LBS	FINAL GRADE. CONNECT THE TWO PIECES OF RISER PIPE WITH A 6" COLLAR MIN. 12" LENGTH APPROXIMATELY CENTERED ON THE JOINT WITH THE TOP OF SLEEVE LOCATED ½" - 18" BELOW SUB-GRADE. THE INSIDE "LIP" OF COLLAR TO BE PAINTED WITH FLUORESCENT WHITE PAINT OR COVERED WITH FLUORESCENT WHITE TAPE. ALTERNATE: FOR OPTIONAL SINGLE PIECE RISER INSTALLATION SEE SHEET 4 OF 4. 3. CLEAN VALVE BOX OF ALL DEBRIS DOWN TO THE NUT OF THE VALVE; NUT SHALL OPERATE WITH NO OBSTRUCTION. 4. WHERE CASTINGS TO BE REMOVED REQUIRE EXCAVATION GREATER THAN 20" DEEP, CONTRACTOR MAY ELECT TO FILL EXCAVATION WITH CONTROLLED LOW STRENGTH MATERIAL (SPEC. ITEM 402S) TO THE UNDERSIDE OF THE CONCRETE. PAVEMENT PATCH IN LIEU OF COMPACTED BACKFILL. 5. REINFORCING STEEL SHALL MEET SPEC. ITEM 406S.7. 6. NO MORE THAN 2 SECTIONS OF PIPE SHALL BE USED FROM VALVE TO FINAL GRADE. 7. BELL AND SPIGOT IS ACCEPTABLE FOR DEPTH OVER 18'. PLAN VIEW	
	CITY OF AUSTIN AUSTIN WATER			TYPIC	AL GATI	E VALVI	≣ 4" - 16"	CITY OF AUSTIN TYPICAL GATE VALVE 4" -	16"
	Kathi L. Flowers 05/18/	2016	RESPONSI	BILITY F	IGINEER A OR APPRO STANDAR	PRIATE	STANDARD NO. 511-AW-01 2 OF 4	(THE ANOTHE ENGINEER MODOWILD)	ANDA! 1 1-A ! 3 OF
	GE METER INSTALLATIONS ENSIONS IN INCHES	3" TURBINE	3° COMPOUND	4° TURBINE	4" COMPOUND	6° TURBINE	6" COMPOUND	NOTES: 1. TEST STATION SHALL BE HANDLEY	
١o.	METER LINE	4" BYPASS	4" BYPASS	4" BYPASS	4" BYPASS	6* BYPASS	6* BYPASS	B B INDUSTRIES INC 2 INCH CATHODIC TEST STATIONS OR APPROVED EQUAL.	
1	CLEARANCE FROM VALVE WALL TO TEE	8"	8"	12"	12"	6"	6"	2. THE 15" ABS PLASTIC BOX SHALL BE A FLANGED TOP FOR INSTALLATION AT	
2	FLANGED TEE	13"	13"	13"	13"	16"	16"	GROUND LEVEL. 3. ALL TERMINALS ARE TO BE MADE OF SOLID	
3	COA GATE VALVE SQUARE NUT	9"	9"	9"	9"	10 1/2"	10 1/2"	24"x24"x6" STD. CONC. COLLAR BRASS. 4. PLASTIC LIDS SHALL BE COLOR BLUE AND	
4	3" X 4" FLANGED REDUCER (3" METER ONLY)	7"	7"	-	_	-	-	MARKED "WATER". 5. TEST TERMINALS ARE TO BE	
5	METER	17"	19"	20"	23"	24"	27"	INCORPORATED WITH HANDLEY VALVE BOXES.	
6	3" X 4" FLANGED REDUCER (3" METER ONLY)	7"	7"		_	-	-	6. BURY SPLICE SHALL BE 3M DIRECT BURY SPLICE (DBR) OR APPROVED EQUAL.	
r+8	(†) FLANGED X PLAIN END DI PIPE + (8) RESTRAINED FLANGE COUPLING ADAPTER (RFCA) OR (7) FLANGE X DI PIPE + (8) DISMANTLING JOINT (DJ)	17"	15"	20"	17"	19"	16"	7. TEST STATIONS SHALL BE INSTALLED AT EACH FIRE HYDRANT LOCATION AND END OF LINE.	ŀ
9	COA GATE VALVE SQUARE NUT	9"	9"	9"	9"	10 1/2"	10 1/2"		
10	FLANGED TEE	13"	13"	13"	13"	16"	16"	SPLICE TRACER WIRE 2" CATHODIC TEST STATION	
11	CLEARANCE FROM INSIDE WALL TO TEE	8"	8"	12"	12"	6"	6"	18" 2" CATHODIC TEST STATION (SEE NOTE 1)	
								~ 4 ~	







-NTS-

SPL No. WW-298

APPROVAL

CITY OF AUSTIN

STANDARD PRODUCTS LIST

METER VAULTS

USING DEPARTMENT: Austin Water ISSUED: 10/01/97 REVIEWED: 10/01/16 REVISED: 10/01/16

Meter Vault, rectangular, for 3", 4" or 6" compound meters and fire demand meters, with 8"

removable reinforced concrete top having valve openings and aluminum access hatch (with stainless steel hardware) as listed in SPL WW-614. Vault, including removable top and access

hatch, to be designed for H-20 loading. (Not to be installed in areas of high density traffic).

Precast plant must be NPCA certified. Concrete used for pre-cast vaults shall conform to TxDOT

PRODUCT

IDENTIFICATION/COMMEN

9' Compound Meter Vault as

designed by Stuart D. Gorka on 9/7/16

ire Demand Meter Vaults as designed

Christopher Wickham on 7/11/06

designed by Ronald Berg on 7/22/1

ire Demand Meter Vaults as designed

Gary Munkelt & Assoc.

8' x 12' Fire Demand Meter Vault

10' x 12' Fire Demand Meter Vau

10' x 15' Fire Demand Meter Vaul

10' x 12' Fire Demand Meter Vault

0' x 15' Fire Demand Meter Vault

Fire Demand Meter Vaults as designed by Gary Munkelt & Associates on 9/7/1

x 12' Fire Demand Meter Vault 10' x 12' Fire Demand Meter Vault 10' x 15' Fire Demand Meter Vault

PREPARED BY: Bill Flynn, P.E.

Item 421, 2004 Edition.

MANUFACTURER

CAPITAL CONCRETE PRODUC

6905 S. Old Bastrop Highway

San Marcos, TX 78666

8491 U.S. Hwy 87 East

NOTE: 1. See shop drawings for approval of knockout and opening locations.

San Antonio, TX 78263


5264 Hwy. 71 East Del Valle, TX 78617


04/01/10 CAPITAL PRECAST


07/01/11 PARK ENVIRONMENTAL


DESCRIPTION:


LISTING

















- R.O.W. OR ESMT. LINE

R.O.W. OR ESMT. LINE

1" PVC MALE


5/4" METER = 7 3/4"

- ¾" METER = 9" +-1" METER = 11"

RECORD COPY SIGNED

CITY OF AUSTIN

AUSTIN WATER



METER SIZES TO BE SHOWN ON PLANS.
METER BOX CUT OUTS SHALL NOT EXCEED TWO TIMES THE PIPE DIAMETER.

TO BALL VALVE "D".

SECTION OF TUBING.

WATER MAIN -

WATER SERVICE & METER INSTALLATION -

1" & SMALLER METERS

1" & SMALLER METERS

THE ENGINEER/ARCHITECT ASSUMES
RESPONSIBILITY FOR APPROPRIATE USE
OF THIS STANDARD MODIFICATIONS TO
THIS STANDARD MODIFICATIONS TO
1.05 2

1.05 2

THIS STANDARD ARE PROHIBITED.

WATER SERVICE TAP PROFILE VIEW

OMPRESSION FITTING USED.

CAST INTO THEM, SPL WW-145A.

AUSTIN WATER

RECORD COPY SIGNED

JEFF A. KYLE

INSTALL METALLIC TRACER TAPE, SPL WW-597, MINIMUM 1' ABOVE TUBING FROM SERVICE CLAMP "A"

TUBING SHALL BE PLACED IN A STRAIGHT ALIGNMENT AND ALLOWED TO RELAX AND "SNAKE"

LOOSELY IN THE TRENCH. TUBING BEHIND CURB AND GUTTER SHALL BE INSTALLED WITH A MINIMUM 2' DEPTH OF COVER.

1" TUBING, WHEN BENT, SHALL HAVE A RADIUS NO SMALLER THAN 3'. 2" TUBING, WHEN BENT, SHALL

HAVE A RADIUS NO SMALLER THAN 5'. BRASS FITTINGS SHALL NOT BE CONNECTED TO A BENT

SOLID, TUBULAR STAINLESS STEEL INSERT STIFFENERS FOR HDPE TUBING SHALL BE USED AT ALL

FOR RECLAIMED WATER SERVICES AND METERS. ALL RECLAIMED TUBING SHALL BE MANUFACTURED

SOLID PURPLE, SPL WW-65A. ALL APPURTENANCES SHALL BE MANUFACTURED PURPLE IF AVAILABLE. ALL FITTINGS THAT ARE NOT AVAILABLE FROM THE MANUFACTURER IN PURPLE SHALL BE PAINTED PURPLE PER SPL WW-3C. ALL METER BOX LIDS SHALL BE PURPLE AND HAVE "RECLAIMED WATER"

WATER SERVICE & METER INSTALLATION -

1" & SMALLER METERS

THE ENGINEER/ARCHITECT ASSUMES STANDARD NO.


08/16/2019

RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD, MODIFICATIONS TO


STANDARD NO.


\$120-AW-01B


COMPRESSION FITTINGS. INSERT STIFFENERS SHALL BE FROM THE SAME MANUFACTURER AS THE











RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

SHEET NO. C11.2

Director

Approver

Designer

Designer

Proj. Arch.

COPYRIGHT © 2025 VLK ARCHITECTS, LLC

Bid Package 2

Issue For Permitting,

Bidding and Construction

X

DAVID P SMITH

56239

ISSUED: July 28, 2025

REVISIONS

Revision Date

Drawn By

Author

PROJECT NO.

23-134.00

SHEET TITLE


CONSTRUCTION


DETAILS (3 OF 5)


Quality Control


Z


<u>~</u>
































Bid Package 2 Issue For Permitting, **Bidding and Construction**



ISSUED: July 28, 2025

Z

RING

DRIP

REVISIONS

Revision Date

Drawn By Director Author Approver Quality Control Designer Designer

PROJECT NO.

Proj. Arch.

23-134.00

SHEET TITLE CONSTRUCTION DETAILS (4 OF 5)

SHEET NO.

C11.3

!!! CAUTION !!!

EXISTING OVERHEAD UTILITIES IN VICINITY

!!! WARNING !!! THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY


OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL


EXISTING UTILITIES BY CALLING THE 'ONE CALL" LOCATOR SERVICI AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.


"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS


SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"


CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES











MATURAL GROUND

- COMPACTED BACKFILL ITEM 510, SECTION 510.2(6)

BEDDING ENVELOPE ITEM 510, SECTION 510.3(14)

--- CENTER PIPE IN TRENCH

... UNDISTURBED EARTH

CROSSING DETAIL


STORM SEWER & WATERLINE **CROSSING DETAIL**


N.T.S


265 mm -k >k >l 225 mm (SYMMETRICAL ABOUT C.L.) 460 mm (10 1/2 ") (9") A7 B7 PERM. CONSTRUCTION JOINT-3 m 1/2LENGTH OF INLET 3 m (10'-0") STANDARD CONSTRUCTION JOINT L /2LENGTH OF INLET


150 mm —

CITY OF AUSTIN
DEPARTMENT OF PUBLIC WORKS











- NEW PAVEMENT DEPTH (SEE NOTE 6)

THIS DETAIL FOR USE ONLY ON CITY OF AUSTIN C.I.P. PROJECTS.

NEW PAVING SURFACE -ITEM 340

NEW BASE -





"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"

A=GREATER OF 36" MINIMUM

B=GREATER OF 15" MINIMUM

OR .5D

TYPICAL CONCRETE

RIP-RAP AT PIPE



DRIP

Z

Bid Package 2

Issue For Permitting,

Bidding and Construction

X

DAVID P SMITH

56239

REVISIONS

Author

PROJECT NO.

SHEET TITLE

CONSTRUCTION

DETAILS (5 OF 5)

SHEET NO.

Director

Approver

Designer

Designer Proj. Arch.

ARCHITECT

2700 Via Fortuna, Suite 230


Main Phone: 512.807.3145

Austin, Texas 78746

www.vlkarchitects.com

C11.4

COPYRIGHT © 2025 VLK ARCHITECTS, LLC



RETAINING WALL

DETAIL NO. 8040 SPECIFICATION SECTION: 32 32 2

FULL SIZE = 3/4"=1'-0" - HALF SIZE = 3/8"=1'-0"

ATTACHMENT N:

Inspection, Maintenance, Repair and Retrofit Plan

PROJECT NAME: Dripping Springs High School No. 2

Batch Detention Pond:

Inspections. Inspections should be conducted a minimum of twice a year. One inspection should take place during wet weather to determine if the basin is meeting the target detention time of 12 hours and a drawdown time of no more than 48 hours. The remaining inspections should occur between storm events so that manual operation of the valve and controller can be verified. The level sensor in the basin should be inspected and any debris or sediment in the area should be removed. The outlet structure and the trash screen should be inspected for signs of clogging. Debris and sediment should be removed from the orifice and outlet(s) as described below. Debris obstructing the valve should be removed. During each inspection, erosion areas inside and downstream of this BMP should be identified and repaired/revegetated immediately.

Mowing: The basin, basin side-slopes, and embankment of the basin must be mowed to prevent woody growth and control weeds. A mulching mower should be used, or the grass clippings should be caught and removed. Mowing should take place at least twice a year, or more frequently if vegetation exceeds 18 inches in height. More frequent mowing to maintain aesthetic appeal may be necessary in landscaped areas.

Litter and Debris Removal: Litter and debris removal should take place at least twice a year, as part of the periodic mowing operations and inspections. Debris and litter should be removed from the surface of the basin. Particular attention should be paid to floatable debris around the outlet structure. The outlet should be checked for possible clogging or obstructions and any debris removed.

Erosion Control: The basin side slopes and embankment all may periodically suffer from slumping and erosion. To correct these problems, corrective action, such as regarding and revegetation, may be necessary. Correction of erosion control should take place whenever required based on the periodic inspections.

Nuisance Control: Standing water or soggy conditions may occur in the basin. Some standing water may occur after a storm event since the valve may close with 2 to 3 inches of water in the basin. Some flow into the basin may also occur between storms due to spring flow and residential water use that enters the storm sewer system. Twice a year, the facility should be evaluated in terms of nuisance control (insects, weeds, odors, algae, etc.).

Structural Repairs and Replacement: With each inspection, any damage to structural elements of the basin (pipes, concrete drainage structures, retaining walls, etc.) should be identified and repaired immediately. An example of this type of repair can include patching of cracked concrete, sealing of voids, removal of revegetation from cracks and joints. The various inlet/outlet structures in a basin will eventually deteriorate and must be replaced.

Sediment Removal: A properly designed batch detention basin will accumulate quantities of sediment over time. The accumulated sediment can detract from the appearance of the facility and reduce the pollutant removal performance of the facility. The sediment also tends to accumulate near the outlet structure and can interfere with the level sensor operation. Sediment shall be removed from the basin at least every 5 years, when sediment depth exceeds 6 inches, when the sediment interferes with the level sensor or when the basin does not drain within 48 hours. Care should be taken not to compromise the basin lining during maintenance.

Logic Controller. The Logic Controller should be inspected as part of the twice-yearly investigations. Verify that the external indicators (active, cycle in progress) are operating properly by turning the controller off and on, and by initiating a cycle by triggering the level sensor in the basin. The valve should be manually opened and closed using the open/close switch to verify valve operation and to assist in inspecting the valve for debris. The solar panel should be inspected and any dust or debris on the panel should be carefully removed. The controller and all other circuitry and wiring should be inspected for signs of corrosion, damage from insects, water leaks, or other damage. At the end of the inspection, the controller should be reset.

Vegetated Filter Strips:

Once a vegetated area is well established, little additional maintenance is generally necessary. The key to establishing a viable vegetated feature is the care and maintenance it receives in the first few months after it is plant ed. Once established, all vegetated BMPs require some basic maintenance to insure the health of the plants including:

Seasonal Mowing and Lawn Care: If the filter strip is made up of turf grass, it should be mowed as needed to limit vegetation height to 18 inches, using a mulching mower (or removal of clippings). If native grasses are used, the filter may require less frequent mowing, but a minimum of twice annually. Grass clippings and brush debris should not be deposited on vegetated filter strip areas. Regular mowing should also include weed control practices, however herbicide use should be kept to a minimum (Urbonas et al., 1992). Healthy grass can be maintained without using fertilizers because runoff usually contains sufficient nutrients. Irrigation of the site can help assure a dense and healthy vegetative cover.

Inspection: Inspect filter strips at least twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable. The strip should be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance

needs. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish shallow overland flow.

Debris and Litter Removal: Trash tends to accumulate in vegetated areas, particularly along highways. Any filter strip structures (i.e. level spreaders) should be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but should be performed no less than 4 times per year.

Sediment Removal: Sediment removal is not normally required in filter strips, since the vegetation normally grows through it and binds it to the soil. However, sediment may accumulate along the upstream boundary of the strip preventing uniform overland flow. Excess sediment should be removed by hand or with flat-bottomed shovels.

Grass Reseeding and Mulching: A healthy dense grass should be maintained on the filter strip. If areas are eroded, they should be filled, compacted, and reseeded so that the final grade is level. Grass damaged during the sediment removal process should be promptly replaced using the same seed mix used during filter strip establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Corrective maintenance, such as weeding or replanting should be done more frequently in the first two to three years after installation to ensure stabilization. Dense vegetation may require irrigation immediately after planting, and during particularly dry periods, particularly as the vegetation is initially established.

Responsible Party: Elaine Coburn (Name Printed)	
Entity: _DRIPPING SPRINGS ISD	
Mailing Address: 300 Sportsplex Drive, Dripping Springs, Texas 78620	
City, State: DRIPPING SPRINGS, TX Zip Code:78620	
Telephone:512-858-3000	
Signature of Responsible Party	P7. 22.3035 Date

ATTACHMENT P – Measures for Minimizing Surface Stream Contamination

In order to avoid or minimize surface stream contamination, storm water runoff from the site will be routed through the proposed water quality pond and vegetated filter strips prior to any discharge to the existing intermittent drainageways on site. The improvements are not expected to change the way water enters surface streams.

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: DAVID P SMITH, P.E.

Date: 6/2/2025

Signature of Customer/Agent:

Regulated Entity Name: DRIPPING SPRINGS HIGH SCHOOL #2

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1.	construction:
	X The following fuels and/or hazardous substances will be stored on the site: NONE
	These fuels and/or hazardous substances will be stored in:
	Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year. Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- X Fuels and hazardous substances will not be stored on the site.
- 2. X Attachment A Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. | X | Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. X Attachment B Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

- 5. | X | Attachment C Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
 - | X | For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
 - × For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6. | X | Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: ONION CREEK

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

7. | X | Attachment D – Temporary Best Management Practices and Measures. TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

		 A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site. A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site. A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer. A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the
8.	X	geologic assessment, TCEQ inspections, or during excavation, blasting, or construction. The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active
		construction should be avoided.
		Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature. X There will be no temporary sealing of naturally-occurring sensitive features on the
		site.
9.	X	Attachment F - Structural Practices . A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10.	X	Attachment G - Drainage Area Map . A drainage area map supporting the following requirements is attached:
		 For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided. For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
		For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
		There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used. 11. | X | Attachment H - Temporary Sediment Pond(s) Plans and Calculations. Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached. N/A 12. X Attachment I - Inspection and Maintenance for BMPs. A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP. 13. | X | All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations. 14. X If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). 15. | X | Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume. 16. X Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening

Soil Stabilization Practices

outfalls, picked up daily).

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. X Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices. A schedule of the interim and permanent soil stabilization practices for the site is attached.

- 18. X Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 19. X Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

- 20. X All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. X If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. X Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

ATTACHMENT A

CONTRACTOR IS RESPONSIBLE FOR ADEQUATE CLEANUP OF ANY SPILLS DURING CONSTRUCTION.

CONTRACTOR SHALL HAVE PERSONNEL ONSITE WHO ARE KNOWLEDGEABLE AND TRAINED TO PERFORM THE SPILL RESPONSE ACTIONS.

SMALL SPILL RESPONSE

BELOW ARE GENERAL STEPS AND MATERIALS TO BE USED FOR CLEANUP.

- 1) IDENTIFYING THE SUBSTANCE & DETERMINING THE RISK BASED ON THE MATERIAL SAFETY DATA SHEETS
- 2) ISOLATING THE AREA OF THE SPILL
- 3) PROTECTING PERSONNEL AND CLEANUP PERSONNEL (Personal Protective Equipment as necessary, goggles, gloves)
- 4) STOPPING THE SPILL AT THE SOURCE
- 5) CONTAINING THE SPILL: Utilizing the correct sorbents to dam or divert the spill for clean up.
- 6) CLEANING UP THE SPILL: Utilizing the proper containers, bags, shovels and other tools, sawdust, sorbent pads, socks, and pillows as needed.

SPILL RESPONSE ACTIONS

Responsibility for adequate cleanup of any chemical spills during construction will be placed on the contractor. The contractor will notify TCEQ of any chemical spills as required at (512) 339-2929.

Reportable quantities as defined by 30 TAC Chapter 327 are as follows:

- (a) Hazardous substances. The reportable quantities for hazardous substances shall be:
 - (1) for spills or discharges onto land--the quantity designated as the Final Reportable Quantity (RQ) in Table 302.4 in 40 CFR §302.4; or

- (2) for spills or discharges into waters in the state--the quantity designated as the Final RQ in Table 302.4 in 40 CFR §302.4, except where the Final RQ is greater than 100 pounds in which case the RQ shall be 100 pounds.
- (b) Oil, petroleum product, and used oil.
 - (1) The RQ for crude oil and oil other than that defined as petroleum product or used oil shall be:
 - (A) for spills or discharges onto land--210 gallons (five barrels); or
 - (B) for spills or discharges directly into water in the state--quantity sufficient to create a sheen.
 - (2) The RQ for petroleum product and used oil shall be:
 - (A) except as noted in subparagraph (B) of this paragraph, for spills or discharges onto land--25 gallons;
 - (B) for spills or discharges to land from PST exempted facilities--210 gallons (five barrels); or
 - (C) for spills or discharges directly into water in the state--quantity sufficient to create a sheen.
- (c) Industrial solid waste or other substances. The RQ for spills or discharges into water in the state shall be 100 pounds.

ATTACHMENT B – POTENTIAL SOURCES OF CONTAMINATION

Some potential sources of contamination are as follows: construction vehicles tracking onto public roads, existing solid waste, and other vehicle contaminants (i.e., fuel, oil, lubricants, etc.). Refer to Attachment A for Spill Response Actions.

ATTACHMENT C - SEQUENCE OF MAJOR ACTIVITIES

- 1. Install erosion controls
- 2. Start excavation of two temporary sediment ponds (4 acres and 2 acres, respectively)
- 3. Start rough grading of access roads and site (94 acres)
- 4. Start underground utility installation (within disturbed 94 acres)
- 5. Start construction of building, drives, and parking lot (within disturbed 94 acres)
- 6. Finalize construction of pond and vegetated filter strips (within disturbed 94 acres)
- 7. Restore disturbed areas, place topsoil, install permanent vegetation (within disturbed 94 acres outside building and pavement improvements)

ATTACHMENT D – TEMPORARY BEST MANAGEMENT PRACTICES AND MEASURES

The disturbed areas will drain to one of the existing drainageways on site.

Stabilized construction entrance/exit, concrete clean out area, silt fence, rock berm and inlet protection will be installed to protect these drainageways. During construction, these BMPs are to be inspected weekly and after any rainfall.

Thee TBMPs will provide temporary runoff detention, velocity reduction, and settlement of sediment.

Silt fence and rock berms will prevent pollutants from entering existing surface streams.

There are no naturally-occurring sensitive features identified onsite.

ATTACHMENT F - STRUCTURAL PRACTICES

Structural practices consist of the use of silt fence, rock berms, and inlet protection as previously described.

ATTACHMENT G - DRAINAGE AREA MAP

Drainage area map showing the proposed work is included.

ATTACHMENT H – TEMPORARY SEDIMENT POND(S) PLANS AND CALCULATIONS

Two water quality ponds with batch detention will be used as a temporary sediment basin during construction. Per RG-348A, the capture volume for Hays County is 8,000 cf/ac. This equates to 483,000 c.f. and 268,000 c.f. for the pond drainage areas of 60.3 acres (P1-1) and 36.8 acres (P2-1). See the enclosed Pond Plan and Pond Details sheets for additional information.

NAN	ME OF PROJECT		Date:		
			Storm Event:		Inches:
One	erator Inspection Fo	rm	Storm Evenu		
Opt	crator inspection re	<i>7</i> 1111			
Projec	ct Name:				
Inspec					_
Quali	fications:				
Are I	RMPs in place and maintaine	d in accordance for site? I	f not describe la	ocation	of failures or inadequacies, and
	ns required.	a in accordance for site. I	i not, deserioe ic	cution	of fundies of madequaties, and
	_	I (CE 1 /I	1 ' / A . '	ъ	. 1/0
Used		Location of Failures/ In	adequactes/Action	ns Req	juired/Comments
	Interceptor Swale				
	Diversion Dike				
	Pipe Slope Drain				
_	Vegetation	=			
_	Mulching				
	Erosion Control Mats				
	Silt Fence				
	Straw Bale Dike				
	Tri-Sediment Filter				
	Inlet Protection				
	Sediment Trap Sediment Basin	-			
	Check Dams/Gabions				
	Temp. Sed. Tank				
	Stab. Const. Entry				
	Sandbag Berms				
_	Vegetation				
_	Waste Management				
_	Material Management				
_	Non Storm Water Runoff				
	Other Controls				
Inspe	ector:		Da	ate:	
- F -	-		_		

ATTACHMENT J – SCHEDULE OF INTERIM AND PERMANENT SOIL STABILIZATION PRACTICES

- 1. From September 15 to March 1, seeding shall be with cool season cover crops (wheat at 0.5 pounds per 1000 sf, oats at 0.5 pounds per 1000 sf, cereal rye grain at 0.5 pounds per 1000 sf) with a total rate of 1.5 pounds per 1000 sf. Cool season cover crops are not permanent erosion control.
- 2. From March 2 to September 14, seeding shall be with hulled bermuda at a rate of 1 pounds per 1000 sf.
 - a. Fertilizer shall be water soluble with an analysis of 15-15-15 to be applied once at planting and once during the period of establishment at a rate of 1/2 pound per 1000 sf.
 - b. Hydromulch shall comply with table below.
 - c. Temporary erosion control shall be acceptable when the grass has grown at least 1 1/2 inches high with 95% coverage, provided no bare spots larger than 16 square feet exist.
 - d. When required, native grass seeding shall comply with requirements of the City of Austin Environmental Criteria Manual (as adopted by the City of Dripping Springs).

Material	Description	Longevity	Typical Applications	Application Rate
100% or any blend of wood, cellulose, straw, and/or cotton plant material (except no mulch shall exceed 30% paper).	71% or greater woods/straw 30% or less paper or natural fibers.	0-3 months	Moderate slopes; from flat to 3:1.	1500 to 2000 lbs per acre.

If portions of the site will have a temporary or permanent cease in construction activity lasting longer than 14 days, soil stabilization in those areas shall be initiated as soon as possible prior to the 14th day of inactivity. If activity will resume prior to the 21st day, stabilization measures are not required. If drought conditions or inclement weather prevent action by the 14th day, stabilization measures shall be initiated as soon as possible.

Summary of Authorization

CR Query

TCEQ Home

Water Quality General Permit Search

Summary of Application: NOTICE OF INTENT

Authorization Number TXR1571QQ

Application Type: NOTICE OF INTENT

Application Status: APPROVED **Received Date:** 04/23/2024 **Final Action Date:** 04/23/2024

Submission Type: ELECTRONIC SUBMITTAL

Administrative Review

Admin Reviewer: STORMWATER PROCESSING TEAM

Admin Review Began: 04/23/2024 **Admin Review Complete:** 04/23/2024

Site Help | Disclaimer | Web Policies | Accessibility | Our Compact with Texans | TCEQ Homeland Security | Contact Us Statewide Links: Texas.gov | Texas Homeland Security | TRAIL Statewide Archive | Texas Veterans Portal

© 2002-2025 Texas Commission on Environmental Quality

Agent Authorization Form

For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

- Elaine	Cogburn Print Name
	Superintendent Title - Owner/President/Other
of	Dripping Springs Independent School District
	Corporation/Partnership/Entity Name
have authorized	David P. Smith, P.E.
·	Print Name of Agent/Engineer
of	Walker Partners, LLC
	Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

- 1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
- 2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
- 3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
- 4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
- 5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

Ela	me Co	1
Applicant's	Signature	0

07.08.2025

THE STATE OF __TEXAS_§

County of HAYS §

BEFORE ME, the undersigned authority, on this day personally appeared <u>Elaine Cogburn</u> known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this the day of ______, 2025_

Katrina C Walker y Commission Expires

My Commission Expires 10/6/2027 Notary 1D 131748741 NOTARY PUBLIC

Katrina C. Walker
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 10 6 2027

Application Fee Form

Texas Commission on Environmental Quality									
Name of Proposed Regulated Entity: DRIPPING SPRINGS HIGH SCHOOL #2									
Regulated Entity Location: 10400 BLOCK, DARDEN HILL RD, DRIFTWOOD, TX 78619									
Name of Customer: DRIPPING SPRINGS ISD									
Contact Person: JAMES CONKLE Phone: 512-858-3079									
Customer Reference Number (if issu									
Regulated Entity Reference Number (if issued):RN									
Austin Regional Office (3373)									
X Hays	☐ Travis	□w	illiamson						
San Antonio Regional Office (3362)									
Bexar	Medina	Пυν	<i>r</i> alde						
Comal	Kinney								
Application fees must be paid by che		or money order, pavab	le to the Texas						
Commission on Environmental Qua		15 0.16 51							
form must be submitted with your	•	•	• 8						
Austin Regional Office		an Antonio Regional O							
X Mailed to: TCEQ - Cashier		Overnight Delivery to: 7							
Revenues Section		.2100 Park 35 Circle	rela casilier						
Mail Code 214									
P.O. Box 13088		Building A, 3rd Floor							
		Austin, TX 78753							
Austin, TX 78711-3088		512)239-0357							
Site Location (Check All That Apply)	<u>:</u>	_							
Recharge Zone	Contributing Zone	Transi	tion Zone						
Type of Plan		Size	Fee Due						
Water Pollution Abatement Plan, Co	ntributing Zone								
Plan: One Single Family Residential [Owelling	Acres	\$						
Water Pollution Abatement Plan, Co	ntributing Zone								
Plan: Multiple Single Family Residen	tial and Parks	Acres	\$						
Water Pollution Abatement Plan, Co	ntributing Zone								
Plan: Non-residential	155.74 Acres	\$ 10,000							
Sewage Collection System	L.F.	\$							
Lift Stations without sewer lines	Acres	\$							
Underground or Aboveground Stora	Tanks	\$							
Piping System(s)(only)		Each	\$						
Exception		Each	\$						
Extension of Time		Each	\$						

Signature: Date: 6-4-2025

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

	Project Area in	_
Project	Acres	Fee
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional,	< 1	\$3,000
multi-family residential, schools, and other sites	1 < 5	\$4,000
where regulated activities will occur)	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

Project	Cost per Linear Foot	Minimum Fee- Maximum Fee
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

Project	Cost per Tank or Piping System	Minimum Fee- Maximum Fee
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

Project	Fee
Exception Request	\$500

Extension of Time Requests

Project	Fee
Extension of Time Request	\$150



TCEQ Core Data Form

For detailed instructions on completing this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)

New Perr	mit, Registration	or Authorization	(Core Data Form	n should be s	submitted	d with th	he prog	ram application.)			
Renewal	Renewal (Core Data Form should be submitted with the renewal form)						Other				
2. Customer Reference Number (if issued) Eollow this link to some for CN or RN number CN 601259435 Ecentral Registry					N number	rs in					issued)
	N II: Cu	<u>istomer</u>			_	Inform	nation	Updates (mm/dd/	(1000)		06-02-2025
4. General Co	istomer inform					11110111	iiatioii	opuates (mm/uu/	уууу)		00-02-2023
	egal Name (Verif	fiable with the Te		State or Tex	kas Comp	troller o	of Public		•		
		tted here may of Public Accou	-	ıtomaticalı	lly based	d on wh	hat is c	urrent and active	with th	ie Texas Seci	retary of State
6. Customer	Legal Name (If	an individual, pr	int last name firs	st: eg: Doe, J	John)			<u>If new Customer,</u>	enter pre	evious Custom	er below:
Dripping Spring	gs ISD										
			8. TX State T	TX State Tax ID (11 digits)				9. Federal Tax ID (9 digits) 74-60030996 10. DUNS N applicable)		Number (if	
11. Type of C	ustomer:	☐ Corpora	tion				Individual Partnership:		rship: 🔲 Gen	neral 🗌 Limited	
Government: [City Coun	ty 🗌 Federal 🗌	Local State	◯ Other] Sole P	roprietorship	Ot	ner:	
12. Number	of Employees					ı		13. Independe	ntly Ow	ned and Ope	erated?
0-20	21-100 🗌 10	1-250 🔲 251-	-500 🛚 501 a	and higher				⊠ Yes	□ No		
14. Custome	r Role (Propose	d or Actual) – as	it relates to the I	Regulated Er	ntity liste	d on thi	is form.	Please check one o	the follo	wing	
Owner Occupation		Operator Responsible Pa		ner & Opera /CP/BSA App				☐ Other:			
15. Mailing											
Address:	300 Sportsple					1		I			I
	City Dri	ipping Springs		State	TX		ZIP	78620		ZIP + 4	
16. Country I	Mailing Inform	nation (if outside	USA)	•		17. E-I	Mail A	ddress (if applicabl	le)		
					james.conkle@dsisdtx.us						

TCEQ-10400 (11/22) Page 1 of 3

(512) 858-3000						()	-		
ECTION III:	Regula	ated Ent	ity Infori	mation					
21. General Regulated Er	ntity Informa	ation (If 'New Reg	gulated Entity" is sele	ected, a new p	ermit applica	ition is also re	quired.)		
New Regulated Entity	Update to	Regulated Entity	Name	to Regulated	Entity Inform	ation			
The Regulated Entity Na	me submitte	d may be upda	ted, in order to m	eet TCEQ Cor	e Data Sta	ndards (rem	oval of or	rganizatio	nal endings such
as Inc, LP, or LLC).									
22. Regulated Entity Nan	ne (Enter nam	e of the site wher	re the regulated action	on is taking plo	ice.)				
Dripping Springs High Schoo	l No. 2								
23. Street Address of									
the Regulated Entity:									
(No PO Boxes)	City		State		ZIP			ZIP + 4	
24. County		l			1				
		If no Stre	et Address is prov	ided, fields 2	5-28 are re	quired.			
25. Description to									
Physical Location:	SE OF DARD	EN HILL RD AND	SAWYER RANCH RD						
26. Nearest City	l					State		Nea	rest ZIP Code
Oripping Springs						TX		786	19
Latitude/Longitude are r	-	-	-		ata Stando	ırds. (Geoco	ding of th	ne Physical	Address may be
used to supply coordinat		ne have been p	rovided or to gain					_	
27. Latitude (N) In Decim	nal:	30.1525		28. L	ongitude (V	V) In Decim	al:	98.0033	
Degrees	Minutes		Seconds	Degre	es	Mir	nutes		Seconds
30		09	09		98		00		12
29. Primary SIC Code	30.	Secondary SIC	Code	31. Prima	y NAICS Co	ode	32. Seco	ndary NAI	CS Code
4 digits)	(4 d	igits)		(5 or 6 digi	ts)		(5 or 6 dig	gits)	
3211				611110					
33. What is the Primary I	Business of t	:his entity? (D	o not repeat the SIC	or NAICS descr	iption.)				
Secondary Education									
34. Mailing									
-					<u> </u>			·	
Address:	City		State		ZIP			ZIP + 4	
35. E-Mail Address:									
36. Telephone Number			37. Extension or	r Code	38. F	ax Number	(if applicab	ole)	
() -					() -			
. <i>1</i>					١,	,			

19. Extension or Code

20. Fax Number (if applicable)

18. Telephone Number

TCEQ-10400 (11/22) Page 2 of 3

form. See the Core D	Data Form instr	uctions for additional រ្	guidance.				
☐ Dam Safety		☐ Districts ☐ Edwards Aquifer			Emissions	Inventory Air	☐ Industrial Hazardous Waste
Municipal Sol	id Waste	ste		Petroleum Storage Tank		☐ PWS	
Sludge		Storm Water	☐ Title V Air		Tires		☐ Used Oil
☐ Voluntary Cle	anup	☐ Wastewater	☐ Wastewater Agricul	Iture	Water Righ	nts	Other:
SECTION	IV: Pr	<u>eparer Inf</u>	<u>formation</u>				
40. Name:	David P. Smith,	P.E.		41. Title:	Client Ma	inager	
42. Telephone N	umber	43. Ext./Code	44. Fax Number	45. E-Mail	Address		
(512)382-0021			() -	dsmith@wa	lkerpartners	s.com	
SECTION	V: Au	thorized S	<u>Signature</u>	•			
			owledge, that the information	•		•	e, and that I have signature authority entified in field 39.
Company:	Walker Pa	artners, LLC		Job Title:	Client M	1anager	
Name (In Print):	David P. S	mith, P.E.			L	Phone:	(512)382-21
Signature:	Da	vilf Sn	ith	Date: 6/2/2025			
			•				

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this