



**Water Pollution Abatement Plan (WPAP) &  
Organized Sewage Collection System (SCS) Plan  
for  
SOUTHWESTERN UNIVERSITY  
560 DEVELOPMENT PHASE 1  
Georgetown, TX 78626**

**CV Project #A799**

**Prepared By:**

**CIVILITUDE  
503 Kenniston Drive,  
Austin, TX-78752  
Phone: (512) 761-6161  
Fax: (512) 761-6167  
[www.civilitude.com](http://www.civilitude.com)**

**Firm Reg. # 12469**

# Texas Commission on Environmental Quality

## Edwards Aquifer Application Cover Page

---

### Our Review of Your Application

**The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).**

### Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains “possibly sensitive” features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

### Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

**Mid-Review Modifications**

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a “Mid-Review Modification”. Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ’s Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ’s San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

<b>1. Regulated Entity Name:</b> Southwestern University 560 Development Phase 1				<b>2. Regulated Entity No.:</b>					
<b>3. Customer Name:</b> Southwestern University				<b>4. Customer No.:</b> CN600787329					
<b>5. Project Type:</b> (Please circle/check one)	<input checked="" type="radio"/> New	<input type="radio"/> Modification		<input type="radio"/> Extension		<input type="radio"/> Exception			
<b>6. Plan Type:</b> (Please circle/check one)	<input checked="" type="radio"/> WPAP	<input type="radio"/> CZP	<input checked="" type="radio"/> SCS	<input type="radio"/> UST	<input type="radio"/> AST	<input type="radio"/> EXP	<input type="radio"/> EXT	<input type="radio"/> Technical Clarification	<input type="radio"/> Optional Enhanced Measures
<b>7. Land Use:</b> (Please circle/check one)	<input type="radio"/> Residential		<input checked="" type="radio"/> Non-residential			<b>8. Site (acres):</b>		68.77	
<b>9. Application Fee:</b>	8,000 (WPAP) \$1,548.50 (SCS)		<b>10. Permanent BMP(s):</b>			Contech Jellyfish			
<b>11. SCS (Linear Ft.):</b>	3,097		<b>12. AST/UST (No. Tanks):</b>			N/A			
<b>13. County:</b>	Williamson		<b>14. Watershed:</b>			Smith Branch – San Gabriel River			

# Application Distribution


Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the “Texas Groundwater Conservation Districts within the EAPP Boundaries” map found at:

[http://www.tceq.texas.gov/assets/public/compliance/field\\_ops/eapp/EAPP%20GWCD%20map.pdf](http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf)

For more detailed boundaries, please contact the conservation district directly.

<b>Austin Region</b>			
<b>County:</b>	<b>Hays</b>	<b>Travis</b>	<b>Williamson</b>
Original (1 req.)	N/A	N/A	X
Region (1 req.)	N/A	N/A	X
County(ies)	N/A	N/A	X
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Barton Springs/ Edwards Aquifer <input type="checkbox"/> Hays Trinity <input type="checkbox"/> Plum Creek	<input type="checkbox"/> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<input type="checkbox"/> Austin <input type="checkbox"/> Buda <input type="checkbox"/> Dripping Springs <input type="checkbox"/> Kyle <input type="checkbox"/> Mountain City <input type="checkbox"/> San Marcos <input type="checkbox"/> Wimberley <input type="checkbox"/> Woodcreek	<input type="checkbox"/> Austin <input type="checkbox"/> Bee Cave <input type="checkbox"/> Pflugerville <input type="checkbox"/> Rollingwood <input type="checkbox"/> Round Rock <input type="checkbox"/> Sunset Valley <input type="checkbox"/> West Lake Hills	<input type="checkbox"/> Austin <input type="checkbox"/> Cedar Park <input type="checkbox"/> Florence <input checked="" type="checkbox"/> Georgetown <input type="checkbox"/> Jerrell <input type="checkbox"/> Leander <input type="checkbox"/> Liberty Hill <input type="checkbox"/> Pflugerville <input type="checkbox"/> Round Rock

<b>San Antonio Region</b>					
<b>County:</b>	<b>Bexar</b>	<b>Comal</b>	<b>Kinney</b>	<b>Medina</b>	<b>Uvalde</b>
Original (1 req.)	N/A	N/A	N/A	N/A	N/A
Region (1 req.)	N/A	N/A	N/A	N/A	N/A
County(ies)	N/A	N/A	N/A	N/A	N/A
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Trinity-Glen Rose	<input type="checkbox"/> Edwards Aquifer Authority	<input type="checkbox"/> Kinney	<input type="checkbox"/> EAA <input type="checkbox"/> Medina	<input type="checkbox"/> EAA <input type="checkbox"/> Uvalde
City(ies) Jurisdiction	<input type="checkbox"/> Castle Hills <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Helotes <input type="checkbox"/> Hill Country Village <input type="checkbox"/> Hollywood Park <input type="checkbox"/> San Antonio (SAWS) <input type="checkbox"/> Shavano Park	<input type="checkbox"/> Bulverde <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Garden Ridge <input type="checkbox"/> New Braunfels <input type="checkbox"/> Schertz	NA	<input type="checkbox"/> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.	
Jordan Miller (Civiltude)	
Print Name of Customer/Authorized Agent	
	10/3/2025
Signature of Customer/Authorized Agent	Date

<b>**FOR TCEQ INTERNAL USE ONLY**</b>			
Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

# General Information Form

## Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

**To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.**

**Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.**

## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **General Information Form** is hereby submitted for TCEQ review. The application was prepared by:

Print Name of Customer/Agent: Jordan Miller, P.E.

Date: 08/12/2025

Signature of Customer/Agent:

  
\_\_\_\_\_

## Project Information

1. Regulated Entity Name: Southwestern University 560 Development Phase 1

2. County: Williamson

3. Stream Basin: Smith Branch - San Gabriel River

4. Groundwater Conservation District (If applicable): N/A

5. Edwards Aquifer Zone:

- Recharge Zone  
 Transition Zone

6. Plan Type:

- |                                          |                                            |
|------------------------------------------|--------------------------------------------|
| <input checked="" type="checkbox"/> WPAP | <input type="checkbox"/> AST               |
| <input checked="" type="checkbox"/> SCS  | <input type="checkbox"/> UST               |
| <input type="checkbox"/> Modification    | <input type="checkbox"/> Exception Request |

7. Customer (Applicant):

Contact Person: Richard Madonna

Entity: Southwestern University

Mailing Address: 1001 E University Avenue

City, State: Georgetown, TX

Zip: 78626

Telephone: \_\_\_\_\_

FAX: \_\_\_\_\_

Email Address: \_\_\_\_\_

8. Agent/Representative (If any):

Contact Person: Jordan Miller, P.E.

Entity: Civiltude, LLC

Mailing Address: 503 Kenniston Dr, Unit #5

City, State: Austin, TX

Zip: 78752

Telephone: (512) 761-6161

FAX: \_\_\_\_\_

Email Address: Jordan@civiltude.com

9. Project Location:

The project site is located inside the city limits of Georgetown.

The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of \_\_\_\_\_.

The project site is not located within any city's limits or ETJ.

10.  The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

Site is located at the intersection of E University Ave and Smith Creek Rd in Georgetown Texas, 78626 near the Southwestern University Campus.

11.  **Attachment A – Road Map.** A road map showing directions to and the location of the project site is attached. The project location and site boundaries are clearly shown on the map.

12.  **Attachment B - USGS / Edwards Recharge Zone Map.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached. The map(s) clearly show:

Project site boundaries.

USGS Quadrangle Name(s).

Boundaries of the Recharge Zone (and Transition Zone, if applicable).

Drainage path from the project site to the boundary of the Recharge Zone.

13.  **The TCEQ must be able to inspect the project site or the application will be returned.** Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment.

Survey staking will be completed by this date: 06/01/2026

14.  **Attachment C – Project Description.** Attached at the end of this form is a detailed narrative description of the proposed project. The project description is consistent throughout the application and contains, at a minimum, the following details:

- Area of the site
- Offsite areas
- Impervious cover
- Permanent BMP(s)
- Proposed site use
- Site history
- Previous development
- Area(s) to be demolished

15. Existing project site conditions are noted below:

- Existing commercial site
- Existing industrial site
- Existing residential site
- Existing paved and/or unpaved roads
- Undeveloped (Cleared)
- Undeveloped (Undisturbed/Uncleared)
- Other: \_\_\_\_\_

### ***Prohibited Activities***

16.  I am aware that the following activities are prohibited on the Recharge Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
- (2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
- (3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
- (4) The use of sewage holding tanks as parts of organized collection systems; and
- (5) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
- (6) New municipal and industrial wastewater discharges into or adjacent to water in the state that would create additional pollutant loading.

17.  I am aware that the following activities are prohibited on the Transition Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);

- (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
- (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

### ***Administrative Information***

18. The fee for the plan(s) is based on:

- For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur.
- For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines.
- For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems.
- A request for an exception to any substantive portion of the regulations related to the protection of water quality.
- A request for an extension to a previously approved plan.


19.  Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

- TCEQ cashier
- Austin Regional Office (for projects in Hays, Travis, and Williamson Counties)
- San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

20.  Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.


21.  No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.

# Attachment A - Road Map




8/12/2025, 6:41:15 PM



-  Parcels
-  County Boundary



County of Williamson, Esri, HERE, Garmin, INCREMENT P, NGA, USGS



Produced by the United States Geological Survey  
Control by USGS and NOS/NOAA  
Compiled from aerial photographs taken 1974. Field checked 1975  
Map edited 1982  
North American Datum of 1927 (NAD 27). Projection and  
10 000-foot ticks. Texas Coordinate System, central zone  
(Lambert Conformal Conic)  
Blue 1000-meter Universal Transverse Mercator ticks, zone 14  
North American Datum of 1983 (NAD 83) is shown by dashed  
corner ticks. The values of the shift between NAD 27 and NAD 83  
for 7.5-minute intersections are obtainable from National Geographic  
Survey NADCON software  
Red tint indicates areas in which only landmark buildings are shown  
Fine red dashed lines indicate selected fence lines  
Areas covered by dashed light-blue pattern are subject to  
controlled inundation



THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION

Primary highway, hard surface	Light-duty road, hard or improved surface
Secondary highway, hard surface	Unimproved road
Interstate Route	U.S. Route
	State Route



GEORGETOWN, TX  
30097-6-1F-024  
1982  
DMA 6445 II NW-SERIES V882



## Regulatory Zones

### 30 TAC Chapter 213- Edwards Aquifer Effective March 1990

This map was produced by the Groundwater Planning and Assessment Team of the Texas Commission on Environmental Quality to detail the boundaries of the regulatory zones of the Edwards Aquifer Protection Program, as described in Texas Administrative Code Title 30, Part 1, §213.3. No other claims are made to the accuracy or completeness of the data or to its suitability for a particular use. For more information about the Edwards Aquifer Protection Program, please contact the TCEQ Regional Offices in San Antonio or Austin. Printed June 2006.

## **General Information Form [TCEQ 0587]**

### **Attachment C**

#### **Project Description**

Southwestern University 560 Development Phase I is a Planned Unit Development located within the city limits of Georgetown at 1001 E University Ave. The site is also located in Williamson County and within the boundaries of the Edward's Aquifer Recharge Zone. The 68.6 acre property is currently underdeveloped (has never been developed) and bounded by TX-29, Smith Creek Co Rd 188 (Smith Creek Rd), and Smith Branch Creek. The proposed development will consist of the planning and construction of roadways, parking lots, and all required onsite wet and dry utilities to service this walkable mixed-use district. Also included in the plans are new Contech Jellyfish storm water treatment systems and detention ponds to fully account for pollutant removal and detention of the storm run-off produced by the development. The maximum allowable amount of impervious cover for the entirety of the PUD is 60%.

This property is located within Smith Creek-San Gabriel Watershed Basin Sub-Watershed which is a part of the Granger Lake-San Gabriel River Watershed. A portion of the site is located within a 100-year FEMA designated floodplain, as shown on FEMA Panel No. 48491C0294F, effective date December 20, 2019 .


**GEOLOGIC ASSESSMENT  
SOUTHWESTERN UNIVERSITY – PHASE 1  
EAST UNIVERSITY AVENUE  
GEORGETOWN, WILLIAMSON COUNTY, TEXAS  
HJN 24206 GA**

**PREPARED FOR:**

**CIVILITUDE, LLC  
AUSTIN, TEXAS**

**PREPARED BY:**

**HORIZON ENVIRONMENTAL SERVICES  
A BRANCH OF LJA ENVIRONMENTAL SERVICES, LLC  
TBPG FIRM REGISTRATION NO. 50679**



**SEPTEMBER 2024**

**TABLE OF CONTENTS**

- I. GEOLOGIC ASSESSMENT FORM (TCEQ-0585)**
- II. ATTACHMENTS:**
  - A GEOLOGIC ASSESSMENT TABLE
  - B STRATIGRAPHIC COLUMN
  - C DESCRIPTION OF SITE GEOLOGY
  - D SITE GEOLOGIC MAP
  - E SUPPORTING INFORMATION
  - F ADDITIONAL SITE MAPS
  - G SITE PHOTOGRAPHS

# Geologic Assessment

## Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

**To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.**

**Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.**

## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: James Killian


Telephone: 512-328-2430

Date: 18 September 2024

Fax: 512-328-1804

Representing: Horizon Environmental Services and TBPG Form Registration No. 50679 (Name of Company and TBPG or TBPE registration number)

Signature of Geologist:



**Regulated Entity Name:** Southwestern University - Phase I; East University Avenue, Georgetown, Williamson County, Texas

## Project Information

1. Date(s) Geologic Assessment was performed: 20 to 21 August and 9 September 2024

2. Type of Project:

WPAP

AST

SCS

UST

3. Location of Project:

Recharge Zone

Transition Zone

Contributing Zone within the Transition Zone

4.  **Attachment A - Geologic Assessment Table.** Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
5.  Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups\* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

**Table 1 - Soil Units, Infiltration Characteristics and Thickness**

Soil Name	Group*	Thickness(feet)
Branyon clay, 1 to 3% slopes (BrB)	C	0.3 to 6.3
Eckrant cobbly clay, 1 to 8% slopes (EaD)	D	up to 1.2
Heiden clay, 5 to 8% slopes, eroded (HeiD3)	D	0.5 to 4.0
Houston Black clay, 3 to 5% slopes, moderately eroded (HoC2)	D	1.0 to 4.0

Soil Name	Group*	Thickness(feet)
Oakalla silty clay loam, 0 to 2% slopes, frequently flooded (OkA)	B	up to 4.0

*\* Soil Group Definitions (Abbreviated)*

- A. Soils having a high infiltration rate when thoroughly wetted.
- B. Soils having a moderate infiltration rate when thoroughly wetted.
- C. Soils having a slow infiltration rate when thoroughly wetted.
- D. Soils having a very slow infiltration rate when thoroughly wetted.

6.  **Attachment B – Stratigraphic Column.** A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.
7.  **Attachment C – Site Geology.** A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
8.  **Attachment D – Site Geologic Map(s).** The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1": 400'

Applicant's Site Plan Scale: 1" = 400'

Site Geologic Map Scale: 1" = 400'

Site Soils Map Scale (if more than 1 soil type): 1" = 400'

9. Method of collecting positional data:

- Global Positioning System (GPS) technology.  
 Other method(s). Please describe method of data collection: \_\_\_\_\_

10.  The project site and boundaries are clearly shown and labeled on the Site Geologic Map.

11.  Surface geologic units are shown and labeled on the Site Geologic Map.

12.  Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.

Geologic or manmade features were not discovered on the project site during the field investigation.

13.  The Recharge Zone boundary is shown and labeled, if appropriate.

14. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section.

There are \_\_\_\_\_ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)

The wells are not in use and have been properly abandoned.

The wells are not in use and will be properly abandoned.

The wells are in use and comply with 16 TAC Chapter 76.

There are no wells or test holes of any kind known to exist on the project site.

### ***Administrative Information***

15.  Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

**Table 1 – Soil Units, Infiltration Characteristics and Thickness  
(Continued)**

Soil Name	Group*	Thickness (feet)
Sunev silty clay loam, 1 to 3% slopes (SvB)	B	0 to 5.0
Queeney clay loam, 1 to 5% slopes (QuC)	D	up to 2.0

\* Soil Group Definitions (Abbreviated)

- A. Soils having a high infiltration rate when thoroughly wetted.
- B. Soils having a moderate infiltration rate when thoroughly wetted.
- C. Soils having a slow infiltration rate when thoroughly wetted.
- D. Soils having a very slow infiltration rate when thoroughly wetted.

**ATTACHMENT A**  
**GEOLOGIC ASSESSMENT TABLE**


GEOLOGIC ASSESSMENT TABLE					PROJECT NAME: Southwestern University - Phase I, Georgetown, Williamson Co., Texas															
LOCATION			FEATURE CHARACTERISTICS										EVALUATION		PHYSICAL SETTING					
1A	1B*	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10	11		12	
FEATURE ID	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DIP (DEGREES)	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY	CATCHMENT AREA (ACRES)		TOPOGRAPHY	
						X	Y	Z		10						<40	≥40	<1.6	≥1.6	
F-1	30.638921	-97.655175	SC	20	Qal	2	2	2	--	--	--	--	C,F,O	12	32	X		X		Hillside
M-1	30.638573	-97.651477	MB	30	Kdr	100	75	5	--	--	--	--	C,F,O	8	38	X		X		Drainage
M-2	30.637163	-97.652745	MB	30	Qta+Qu	2	2	--	--	--	--	--	C,F,O	5	35	X		X		Hillside
M-3	30.640247	-97.65667	MB	30	Qal	2	2	--	--	--	--	--	C,F,O	5	35	X		X		Hillside
M-4	30.639154	-97.656446	MB	30	Qal	2	2	--	--	--	--	--	C,F,O	5	35	X		X		Hillside
M-5	30.638572	-97.656614	MB	30	Qal	2	2	--	--	--	--	--	C,F,O	5	35	X		X		Hillside
M-6	30.637783	-97.656376	MB	30	Qal	2	2	--	--	--	--	--	C,F,O	5	35	X		X		Hillside
M-7	30.637059	-97.655914	MB	30	Qal	2	2	--	--	--	--	--	C,F,O	5	35	X		X		Hillside
M-8	30.636573	-97.655461	MB	30	Qal	2	2	--	--	--	--	--	C,F,O	5	35	X		X		Hillside
S-1	30.640665	-97.657442	O	5	Kgt	--	--	--	--	--	--	--	N	7	12	X		X		Streambed
S-2	30.639789	-97.656984	O	5	Kgt	--	--	--	--	--	--	--	N	7	12	X		X		Streambed
S-3	30.638586	-97.657135	O	5	Kgt	--	--	--	--	--	--	--	N	7	12	X		X		Streambed
S-4	30.637764	-97.656928	O	5	Qal	--	--	--	--	--	--	--	N	7	12	X		X		Streambed
S-5	30.63665	-97.655861	O	5	Qal	--	--	--	--	--	--	--	N	7	12	X		X		Streambed

\* DATUM:

2A TYP	TYPE	2B POINTS
C	Cave	30
SC	Solution cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Man-made feature in bedrock	30
SW	Swallow hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30

8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials: concrete and/or casing

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed



I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

*James P. Killian*

Date: 18 September 2024

Sheet 1 of 1

**ATTACHMENT B**  
**STRATIGRAPHIC COLUMN**

Geologic Unit	Hydrologic Unit	Approx. Thickness at Project Site (ft)	Elevation (ft msl)	Depth (ft)
			744	0
Alluvium (Qal)	Edwards Aquifer	10		
Older Alluvium and Terrace (QTa+Qu)		15	734	10
Del Rio Formation (Kdr)		65	719	25
Georgetown Limestone (Kgt)		80	654	90
Edwards Formation (Ked)		150	574	170
				424

**Note: Unit elevation and thickness given with respect to a ground surface elevation of 744 ft in the southeastern portion of the subject site.**



Date: 08/27/2024  
 Drawn: KRW  
 HJN NO: 24206.001 GA

**Attachment B**  
 Stratigraphic Column  
 Southwestern University  
 Phase I Development  
 Georgetown, Williamson County, Texas



**ATTACHMENT C**  
**DESCRIPTION OF SITE GEOLOGY**

Geologic information for the subject site obtained via literature review is provided in Attachment E, Supporting Information.


A geologic assessment of approximately 83 acres located off East University Avenue (Texas State Highway 29) in Georgetown, Williamson County, Texas, was conducted pursuant to Texas rules for regulated activities in the Edwards Aquifer Recharge Zone (EARZ) (30 TAC 213). The subject site consists of vacant, partially wooded agricultural land. The surrounding area is primarily characterized by fragmented rangeland and residential development. Assessment findings were used to develop recommendations for site construction measures intended to be protective of water resources at the subject site and adjacent areas.

Most of the subject site is located within the EARZ, as defined by the Texas Commission on Environmental Quality (TCEQ). The EARZ occurs where surface water enters the subsurface through exposed limestone bedrock containing faults, fractures, sinkholes, and caves. The south-central portion of the site is located within the Edwards Aquifer Transition Zone, as defined by the TCEQ. The Transition Zone occurs where geologic formations crop out in proximity to and south and southeast of the Recharge Zone and where faults, fractures, and other geologic features present a possible avenue for recharge of surface water to the Edwards Aquifer, including portions of the Del Rio Clay, Buda Limestone, Eagle Ford Group, Austin Chalk, Pecan Gap Chalk, and Anacacho Limestone.

The subject site is underlain by alluvium (Qal); older alluvium and terrace deposits, drainageway, and slope-wash alluvium, undivided (QTa+Qu); the Del Rio Formation (Kdr); and Georgetown Limestone (Kgt), with estimated maximum thicknesses of 10, 15, 65, and 80 feet, respectively.

A total of 1 geologic feature (F-1) and 8 man-made features (M-1 to M-8) were identified at the subject site. Further information pertaining to the geologic and man-made features is presented in the following Attachments D, E, and F. Photographs of the subject site and the geologic and man-made features are presented in Attachment G.

**ATTACHMENT D**  
**SITE GEOLOGIC MAP**




**Legend**

-  Man-Made Feature
-  Non-Sensitive Geologic Feature
-  Spring/Seep
-  Subject Site
-  Alluvium (Qal)
-  Older Alluvium and Terrace (QTa+Qu)
-  Del Rio Formation (Kdr)
-  Georgetown Formation (Kgt)



Date:	08/19/2024
Drawn:	KRW
HJN NO:	24206.001 GA
Source:	Nearmap, 2024; TWSC, 2014

**Attachment D**  
 Site Geologic Map  
 Southwestern University  
 Phase I Development  
 Georgetown, Williamson County, Texas



**ATTACHMENT E**  
**SUPPORTING INFORMATION**

## **1.0 INTRODUCTION AND METHODOLOGY**

This report and any proposed abatement measures are intended to fulfill Texas Commission on Environmental Quality (TCEQ) reporting requirements (TCEQ, 2005). This geologic assessment includes a review of the subject site for potential aquifer recharge and documentation of general geologic characteristics for the subject site. Horizon Environmental Services (Horizon) conducted the necessary field and literature studies according to TCEQ *Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zones* (TCEQ, 2004).

Horizon walked transects spaced 50 feet apart, mapped the locations of features using a sub-foot accurate Trimble Geo HX handheld GPS, and posted processed data utilizing GPS Pathfinder Office software, topographic maps, and aerial photographs. Horizon also searched the area around any potential recharge features encountered to look for additional features. When necessary, Horizon removed loose rocks and soil (by hand) to preliminarily assess each feature's subsurface extent while walking transects. However, labor-intensive excavation was not conducted during this assessment. Features that did not meet the TCEQ definition of a potential recharge feature (per TCEQ, 2004), such as surface weathering, karren, or animal burrows, were evaluated in the field and omitted from this report.

The results of this survey do not preclude the possibility of encountering subsurface voids or abandoned test or water wells during the clearing or construction phases of the proposed project. If a subsurface void is encountered during any phase of the project, work should be halted until the TCEQ (or appropriate agency) is contacted and a geologist can investigate the feature.

## **2.0 ENVIRONMENTAL SETTING**

### **2.1 LOCATION AND GENERAL DESCRIPTION**

The subject site consists of approximately 83 acres of undeveloped farmland and woodlands located along the northwest of the intersection of East University Avenue (Texas State Highway 29) and Smith Creek Road in Georgetown, Williamson County, Texas (Appendix F, Figure 1).

### **2.2 LAND USE**

Portions of the subject site are reportedly used for hay production and an ecological educational study area. Surrounding lands are generally used for educational facilities and residences.

### **2.3 TOPOGRAPHY AND SURFACE WATER**

The subject site is situated on gently to moderately sloping terrain within the Smith Branch watershed (Appendix F, Figures 2 and 3). Surface elevations on the subject site vary from a minimum of approximately 680 feet above mean sea level (amsl) within Smith Branch in the northwestern property corner to a maximum of approximately 744 feet amsl near the southeastern

portion of the site (USGS, 1982). Drainage on the site occurs primarily by overland sheet flow in multiple directions depending on proximity to Smith Branch (on the western portion of the site) and/or an unnamed tributary of Smith Branch (along the eastern side of the site).

## 2.4 EDWARDS AQUIFER ZONE

Most of the subject site is found within the Edwards Aquifer Recharge Zone (TCEQ, 2024) (Attachment F, Figure 2). The southeastern portion of the site is found within the Edwards Aquifer Transition Zone (TCEQ, 2024).

## 2.5 SURFACE SOILS

Seven soil units are mapped within the subject site (NRCS, 2024) (Appendix F, Figure 4). Generally, the soil series are similar in their physical, chemical, and engineering properties, with the principal exception being rock fragment content and thickness. The soil units are described in further detail below.

Branyon clay (BrB) occurs on smooth, high ancient terraces. Typically, this soil has a dark gray clay upper layer about 50 inches thick. The layer below that, which extends to a depth of about 62 inches, is gray clay. The underlying layer to 80 inches is very pale brown silty clay that has yellow mottles. The soil is calcareous and moderately alkaline throughout. This soil is moderately well-drained. When dry, the soil has cracks 2 to 5 feet deep and permeability is very slow. Runoff is medium. The available water capacity is high.

Eckrant cobbly clay (EaD) is on undulating uplands. Typically, the surface layer is about 13 inches thick. The upper part is dark grayish-brown cobbly clay. The lower part is dark brown cobbly clay. The underlying material is coarsely fractured indurated limestone. This soil is calcareous and moderately alkaline. The surface has about a 50% cover of fragments of limestone that are mostly 4 to 8 inches across. This soil is well-drained. Permeability is moderately slow, and runoff is rapid. The available water capacity is very low. The rooting zone is very shallow to shallow.

Houston Black clay, moderately eroded (HoC2) is a gently sloping soil on uplands. Typically, the upper layer is dark grayish-brown clay about 16 inches thick. The next layer, which extends down to about 42 inches, is olive clay. The underlying layer to 60 inches is mottled, pale olive clay. The soil is calcareous and moderately alkaline throughout. This soil is well-drained. Permeability is very slow. Runoff is rapid. When this soil is dry, deep cracks form; when wet, the soil swells and the cracks close. The available water capacity is high. Fertility is low in many places. Erosion is a severe hazard.

Heiden clay, eroded (HeiD3) is an undulating soil on uplands. The surface layer has been thinned by soil removal; the thinnest areas are near gullies. Generally, one-fourth to one-half of the original surface layer has been removed. Most gullies are crossable with regular farm equipment. The areas of this soil that are used for crops have a striped appearance because of the alternating darker inter-gully areas and the lighter area where the lower soil layers have been exposed by gully erosion. Typically, this soil has a dark grayish-brown clay upper layer about 22

inches thick. The next layer, to about 44 inches, is grayish-brown clay. The underlying layer to 60 inches is pale olive shaly clay. This soil is calcareous and moderately alkaliine throughout. This soil is well-drained. When the soil is dry, deep cracks form; when the soil is wet, it swells and the cracks close. Permeability is very slow. Runoff is rapid. The available water capacity is high. Fertility is low in many places. Erosion is a severe hazard.

Oakalla silty clay loam, 0 to 2% slopes, frequently flooded (OkA) is a nearly level soil found on long, narrow bottomlands that are flooded several times after heavy rain events. Oakalla soil tends to become sandier with depth. This soil is well-drained with moderate permeability. The available water capacity is high. This soil is typically used for pastures and rangeland. The soil is not suitable for urban uses due to the frequent flooding. Roads and bridges are sometimes damaged by brush and trees being swept downstream (Werchan and Coker, 1983).

Queeny clay loam (QuC) is a gently sloping soil along the edge of ancient stream terraces. The areas are generally long and narrow; however, some areas are irregular in shape. Typically, the surface layer is calcareous, moderately alkaline clay loam about 13 inches thick that is dark grayish brown in the upper part and brown in the lower part. The underlying layer from 13 to 32 inches is bedded gravel, sand, and fine earth. The upper part of the gravel layer is strongly cemented by caliche. This soil is well-drained. Permeability is moderate. The rooting depth is very shallow to shallow. This soil has a very low available water capacity and is droughty.

Sunev silty clay loam, 1 to 3% slopes (SuB) is a gently sloping soil located on stream terraces. The soil is calcareous and moderately alkaline throughout. Sunev silty clay loam has a moderate permeability with a medium surface runoff and is known to be well-drained. The available water capacity of this soil is moderate. This soil is typically used for crops, pastures, or as rangeland. Some limitations associated with this soil include corrosion of underground steel pipes and poor functioning of septic systems, but both limitations can be easily controlled if designed properly (Werchan and Coker, 1983).

## 2.6 WATER WELLS

A review of TCEQ and Texas Water Development Board (TWDB) records revealed 1 water well (ID No. 5819909) on the subject site and approximately 6 wells within 0.5 miles of the subject site (TCEQ, 2024; TWDB, 2024). According to the TWDB records, the on-site well was drilled in 1986 to approximately 126 feet deep and was completed within the Edwards Aquifer. All the off-site wells are reportedly completed within the Edwards Aquifer at total depths ranging from 100 to 200 feet below surface. Horizon observed no water wells on the subject site. The well indicated on the subject site in the TWDB records (ID No. 5819909) was not found during the site visit.

If the on-site is not intended for future use, it should be capped or properly abandoned according to the Administrative Rules of the Texas Department of Licensing and Regulation (TDLR), 16 Texas Administrative Code (TAC), Chapter 76. TCEQ publication RG-347, "Landowner's Guide to Plugging Abandoned Water Wells," provides specific guidance. If a well is intended for use, it must comply with 16 TAC §76.

The results of this assessment do not preclude the existence of additional undocumented/abandoned wells on the site. If a water well or casing is encountered during construction, work should be halted near the feature until the TCEQ is contacted.

## 2.7 GEOLOGY

### Literature Review

The subject site is underlain by alluvium (Qal); older alluvium and terrace deposits, drainageway, and slope-wash alluvium, undivided (QTa+Qu); the Del Rio Formation (Kdr); and Georgetown Limestone (Kgt), with estimated maximum thicknesses of 10, 15, 65, and 80 feet, respectively.

Alluvium (Qal) consists of gravel, sand, silt, and clay along streams and rivers; it is inundated regularly. The gravel is mostly limestone and chert. Along minor drainages, it includes undivided low terrace deposits. It also includes some local bedrock outcrops that are undivided.

Older alluvium (QTa) consists of gravel, sand, clay, well-rounded pebble-to-cobble-sized gravel, and few boulders. It is mostly chert and limestone, with some quartz and igneous and metamorphic rock detritus. Some deposits comprise mostly sand and clay. Deposits typically cap topographically high areas. Its precise age is unknown; deposits are probably of different ages.

Undivided alluvium (Qu) consists of sand, silt, clay, and some gravel. It includes terrace alluvium, local drainageway alluvium, and slope-wash alluvium.

The Del Rio Formation (Kdr) consists of clay that is calcareous, fossiliferous, poorly indurated, plastic, and dark gray to olive brown. It contains *Ilymatogyra ariertiina* (formerly *Exogyra arietina*). It is slope forming or underhanging where slumped below overlying Buda Limestone. The formation weathers light gray to yellowish gray. As it forms highly expansive soil, water tanks for livestock are commonly excavated on outcrops. Thickness is up to 65 feet.

The Georgetown Formation (Kgt) consists of limestone and marl that are nodular and very fossiliferous. Diagnostic marine megafossils include *Waconelt wacoensis* (formerly *Kingena wacoensis*) and *Gryphaea washitaensis*. The formation is located in the uppermost Edwards Aquifer strata. Thickness increases northward from 65 to 110 feet (UT-BEG, 1995).

The site Stratigraphic Column is provided as Attachment B, and the Site Geologic Map is Attachment D.

The subject site is located within the Balcones Fault Zone. Available geologic reports indicate the nearest mapped fault occurs about 2 miles east of the site, trending from southwest to northeast (TWSC, 2014).

## Field Assessment

One geologic feature (F-1) and 8 man-made features (M-1 to M-8) were identified at the subject site. Man-made feature M-1 is an existing stock pond and M-2 to M-8 are City of Georgetown sanitary sewer manholes that appeared to be properly constructed and in good working condition. In addition, approximately 5 springs/seeps (S-1 to S-5) were found along portions of Smith Branch, which is located along the western portion of the subject site.

Geologic feature F-1 is a small solution cavity measuring approximately 0.5 feet in diameter by 0.3 feet wide by 1 foot deep. During the initial site investigation, the feature was noted to have very slight air flow conductivity. Horizon staff excavated the feature (4 feet long by 2.5 feet wide by 3.5 feet deep) on 9 September 2024 using hand tools only. After excavation, Horizon probed the floor of the feature with a steel rod; however, no portals and/or voids were discovered in the floor or walls of the feature. This feature has a very low infiltration rate and a surface runoff catchment of less than 0.1 acre.

The Site Geologic Map is provided as Attachment D. The Geologic Assessment Table (Attachment A) describes those features observed on the subject site that meet the TCEQ definition of a potential recharge feature.

### **3.0 CONCLUSIONS AND RECOMMENDATIONS**



No geologic or man-made features were identified at the subject site that would require protection or mitigation pursuant to TCEQ rules for protection of the Edwards Aquifer (30 TAC 213). The site generally appears well-suited to development prospectuses. It should be noted that soil and drainage erosion would increase with ground disturbance. Native grasses and the cobbly content of the soil aid to prevent erosion. Soil and sedimentation fencing should be placed in all appropriate areas prior to any site disturbing activities.

Because most of the subject site is located over the Edwards Aquifer Recharge Zone, it is possible that subsurface voids underlie the site. If any subsurface voids are encountered during site development, work should halt immediately so that a geologist may assess the potential for the void(s) to provide meaningful contribution to the Edwards Aquifer.

#### 4.0 REFERENCES

- (CAPCOG) Capital Area Council of Governments. 2-foot contours, CAPCOG Center for Regional Development, Austin, Texas. 2015
- (Nearmap) Nearmap US, Inc. Nearmap Vertical™ digital orthographic photograph, <<https://go.nearmap.com>>. Imagery date 30 April 2023.
- (NRCS) US Department of Agriculture, Natural Resources Conservation Service. Web Soil Survey, <<http://websoilsurvey.sc.egov.usda.gov/App/HomePage.htm>>. Soil map data layer updated 12 September 2019. Accessed 4 August 2023.
- (OSM) OpenStreetMap contributors. OpenStreetMap, <<http://www.openstreetmap.org>>. Available under the Open Database License ([www.opendatacommons.org/licenses/odbl](http://www.opendatacommons.org/licenses/odbl)). Accessed 14 August 2023.
- (TCEQ) Texas Commission on Environmental Quality. Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zones. Revised October 2004.
- \_\_\_\_\_. RG-348, Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices. Revised July 2005.
- \_\_\_\_\_. Optional Enhanced Measures for the Protection of Water Quality in the Edwards Aquifer (Revised). Appendix A to RG-348, Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices. September 2007.
- \_\_\_\_\_. Edwards Aquifer Protection Program. Edwards Aquifer Viewer, <<http://www.tceq.state.tx.us/field/eapp/viewer.html>>. Accessed 4 August 2023.
- (TWDB) Texas Water Development Board. Water Information Integration and Dissemination System. TWDB Groundwater Database, <<https://www3.twdb.texas.gov/apps/water/datainteractive/groundwaterdataviewer>>. Accessed 11 August 2023.
- (TWSC) United States Geological Survey, Texas Water Science Center. Geologic Database of Texas, <<https://txpub.usgs.gov/txgeology/>>. Updated 1 February 2014; Accessed 7 August 2023.
- (UT-BEG) University of Texas Bureau of Economic Geology, Geologic Atlas of Texas Austin Sheet, Francis Luther Whitney Memorial Edition. C.V. Proctor, Jr., T.E. Brown, J.H. McGowen, and N.B. Waechter. 1974. Reprinted 1995.
- Werchan, L. E., and J. L. Coker. Soil survey of Williamson County, Texas. US Department of Agriculture, Natural Resources Conservation Service (formerly Soil Conservation Service), in cooperation with the Texas Agricultural Experiment Station. 1983.
- (USGS) US Geological Survey. 7.5-minute series topographic maps, Georgetown, Texas, quadrangle. 1982.

**ATTACHMENT F**  
**ADDITIONAL SITE MAPS**



Subject Site  
 Lat: 30.639296 N  
 Long: -97.653933 W


**Legend**


 Subject Site



Date: 08/19/2024  
 Drawn: KRW  
 HJN NO: 24206.001 GA  
 Source: OSM, 2024

**Attachment F, Figure 1**  
 Vicinity Map  
 Southwestern University  
 Phase I Development  
 Georgetown, Williamson County, Texas





**Legend**

- SDRDB Well Location
- Subject Site
- GWDB Water Well
- Edwards Aquifer Recharge Zone
- 0.5-Mile Subject Site Buffer
- Edwards Aquifer Transition Zone



Date:	08/19/2024
Drawn:	KRW
HJN NO:	24206.001 GA
Source:	TCEQ, 2024; TWDB, 2024; USGS, 1982

**Attachment F, Figure 2**  
 Topography and Hydrogeology Map  
 Southwestern University  
 Phase I Development  
 Georgetown, Williamson County, Texas

0      550      1,100  
Feet




**Legend**


-  2-Foot Contour
-  Subject Site



Date:	08/19/2024
Drawn:	KRW
HJN NO:	24206.001 GA
Source:	CAPCOG 2015; Nearmap, 2024

**Attachment F, Figure 3**  
 Site Topography Map  
 Southwestern University  
 Phase I Development  
 Georgetown, Williamson County, Texas






**Legend**

- Subject Site
- Soil Unit Boundary



Date:	08/19/2024
Drawn:	KRW
HJN NO:	24206.001 GA
Source:	Nearmap, 2024; NRCS, 2022

**Attachment F, Figure 4**  
 Site Soil Map  
 Southwestern University  
 Phase I Development  
 Georgetown, Williamson County, Texas



**ATTACHMENT G**  
**SITE PHOTOGRAPHS**



**PHOTO 1**  
View of geologic feature F-1 (solution cavity), facing down



**PHOTO 2**  
View of F-1 after hand excavation, facing north



**PHOTO 3**  
Man-made feature M-1 (stock pond), facing south



**PHOTO 4**  
Man-made feature M-2 (sanitary sewer manhole)



**PHOTO 5**  
Man-made feature M-3 (sanitary sewer manhole)



**PHOTO 6**  
Man-made feature M-4 (sanitary sewer manhole)



**PHOTO 7**  
Man-made feature M-5 (sanitary sewer manhole)



**PHOTO 8**  
Man-made feature M-6 (sanitary sewer manhole)



**PHOTO 9**  
Man-made feature M-7 (sanitary sewer manhole)



**PHOTO 10**  
Man-made feature M-8 (sanitary sewer manhole)



**PHOTO 11**  
Geologic feature S-1 (spring/seep pool) along Smith Branch,  
facing south




**PHOTO 12**  
Geologic feature S-2 (spring/seep pool) along Smith Branch,  
facing south



**PHOTO 13**  
Geologic feature S-3 (spring/seep pool), facing north



**PHOTO 14**  
Geologic feature S-4 (spring/seep pool) facing north



**PHOTO 15**  
Geologic feature S-5 (spring/seep pool), facing north

# Water Pollution Abatement Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b), Effective June 1, 1999

*To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.*

*Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.*


## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Water Pollution Abatement Plan Application Form** is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Print Name of Customer/Agent: Jordan Miller, P.E.

Date: 08/13/2025

Signature of Customer/Agent:



Regulated Entity Name: Southwestern University 560 Development Phase 1

## Regulated Entity Information

1. The type of project is:

- Residential: Number of Lots: \_\_\_\_\_
- Residential: Number of Living Unit Equivalents: \_\_\_\_\_
- Commercial
- Industrial
- Other: Non-Residential

2. Total site acreage (size of property): 68.6

3. Estimated projected population: \_\_\_\_\_

4. The amount and type of impervious cover expected after construction are shown below:

**Table 1 - Impervious Cover Table**

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	36,000	÷ 43,560 =	0.82
Parking	303,175	÷ 43,560 =	6.96
Other paved surfaces	292,050	÷ 43,560 =	6.70
Total Impervious Cover	631,225	÷ 43,560 =	14.49

**Total Impervious Cover 14.48 ÷ Total Acreage 68.6 X 100 = 21.1% Impervious Cover**

5.  **Attachment A - Factors Affecting Surface Water Quality.** A detailed description of all factors that could affect surface water and groundwater quality that addresses ultimate land use is attached.
6.  Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

***For Road Projects Only***

**Complete questions 7 - 12 if this application is exclusively for a road project.**

7. Type of project:

- TXDOT road project.
- County road or roads built to county specifications.
- City thoroughfare or roads to be dedicated to a municipality.
- Street or road providing access to private driveways.

8. Type of pavement or road surface to be used:

- Concrete
- Asphaltic concrete pavement
- Other: \_\_\_\_\_

9. Length of Right of Way (R.O.W.): \_\_\_\_\_ feet.

Width of R.O.W.: \_\_\_\_\_ feet.

L x W = \_\_\_\_\_ Ft<sup>2</sup> ÷ 43,560 Ft<sup>2</sup>/Acre = \_\_\_\_\_ acres.

10. Length of pavement area: \_\_\_\_\_ feet.

Width of pavement area: \_\_\_\_\_ feet.

L x W = \_\_\_\_\_ Ft<sup>2</sup> ÷ 43,560 Ft<sup>2</sup>/Acre = \_\_\_\_\_ acres.

Pavement area \_\_\_\_\_ acres ÷ R.O.W. area \_\_\_\_\_ acres x 100 = \_\_\_\_\_% impervious cover.

11.  A rest stop will be included in this project.
- A rest stop will not be included in this project.

12.  Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

### ***Stormwater to be generated by the Proposed Project***

13.  **Attachment B - Volume and Character of Stormwater.** A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on the area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

### ***Wastewater to be generated by the Proposed Project***

14. The character and volume of wastewater is shown below:

<u>100%</u> Domestic	<u>640,000</u> Gallons/day
<u>      </u> % Industrial	<u>      </u> Gallons/day
<u>      </u> % Commingled	<u>      </u> Gallons/day
TOTAL gallons/day <u>640,000</u>	

15. Wastewater will be disposed of by:

On-Site Sewage Facility (OSSF/Septic Tank):

**Attachment C - Suitability Letter from Authorized Agent.** An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

Sewage Collection System (Sewer Lines):

Private service laterals from the wastewater generating facilities will be connected to an existing SCS.

Private service laterals from the wastewater generating facilities will be connected to a proposed SCS.

The SCS was previously submitted on \_\_\_\_\_.

The SCS was submitted with this application.

The SCS will be submitted at a later date. The owner is aware that the SCS may not be installed prior to Executive Director approval.

The sewage collection system will convey the wastewater to the San Gabriel Wastewater (name) Treatment Plant. The treatment facility is:

Existing.

Proposed.

16.  All private service laterals will be inspected as required in 30 TAC §213.5.

## **Site Plan Requirements**

**Items 17 – 28 must be included on the Site Plan.**

17.  The Site Plan must have a minimum scale of 1" = 400'.

Site Plan Scale: 1" = 100'.

18. 100-year floodplain boundaries:

Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.

No part of the project site is located within the 100-year floodplain.

The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): \_\_\_\_\_

19.  The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, open space, etc. are shown on the plan.

The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, open space, etc. are shown on the site plan.

20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):

There are 0 (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)

The wells are not in use and have been properly abandoned.

The wells are not in use and will be properly abandoned.

The wells are in use and comply with 16 TAC §76.

There are no wells or test holes of any kind known to exist on the project site.

21. Geologic or manmade features which are on the site:

All sensitive geologic or manmade features identified in the Geologic Assessment are shown and labeled.

No sensitive geologic or manmade features were identified in the Geologic Assessment.

**Attachment D - Exception to the Required Geologic Assessment.** A request and justification for an exception to a portion of the Geologic Assessment is attached.

- 22.  The drainage patterns and approximate slopes anticipated after major grading activities.
- 23.  Areas of soil disturbance and areas which will not be disturbed.
- 24.  Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
- 25.  Locations where soil stabilization practices are expected to occur.
- 26.  Surface waters (including wetlands).  
 N/A
- 27.  Locations where stormwater discharges to surface water or sensitive features are to occur.  
 There will be no discharges to surface water or sensitive features.
- 28.  Legal boundaries of the site are shown.

### ***Administrative Information***

- 29.  Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
- 30.  Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

**Water Pollution Abatement Plan Application Form [TCEQ-0584]  
Attachment A**

**Factors Affecting Water Quality**

Urbanization will affect water quality by increasing sediment loading and introducing nutrients, pathogens, oxygen-demanding matter and toxic pollutants to receiving waters.

Factors affecting water quality for the proposed development include the following:

- (1) Proposed roads and vehicular traffic,
- (2) Human litter and pet waste,

Multiple Contech Jellyfish storm water treatment systems will help mitigate the pollutants from the factors listed above.

**Water Pollution Abatement Plan Application Form [TCEQ-0584]  
Attachment B**

**Volume and Character of Stormwater**

A hydrologic and hydraulic analysis was performed for this property to estimate the volume and character of stormwater runoff expected under the proposed conditions. For this WPAP, Phase 1 of this project proposes to construct the public roadways to make future developments possible, parking lots on Lot 2, and the City of Georgetown office building development located on Lot 3. All runoff generated by these additions of impervious cover has been designed to be conveyed via a storm pipe network to the two new detention ponds located in the northern corner of the site.

For water quality treatment, Contech Jellyfish Filters have been selected as the permanent Best Management Practice (BMP) for the development. These filters provide membrane filtration to capture fine sediment, nutrients hydrocarbons, and heavy metals. The units are sized to treat and remove approximately 85% of the increase in total suspended solids (TSS) load associated with development. Each filter is located upstream of its corresponding detention pond to provide treatment prior to discharge into the pond basin.

In summary, the proposed stormwater management system provides detention capacity sufficient to offset increased runoff values and peak flows, while integrating permanent water quality treatment through Jellyfish filters to meet TSS reduction requirements.

Project Name: **560 Development**  
Date Prepared: 8/11/2025

1. The Required Load Reduction for the total project:

Calculations from RG-348 Page 3-29 Equation 3.3:  $L_M = 28.9(A_N \times P)$   
Pages 3-27 to 3-30

$L_{M \text{ TOTAL PROJECT}}$  = Required TSS removal resulting from the proposed development = 85% of increased load  
 $A_N$  = Net increase in impervious area for the project  
P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	<b>Williamson</b>	
Total project area included in plan * =	<b>10.00</b>	acres
Predevelopment impervious area within the limits of the plan * =	<b>0.00</b>	acres
Total post-development impervious area within the limits of the plan* =	<b>8.00</b>	acres
Total post-development impervious cover fraction * =	<b>0.80</b>	
P =	<b>32</b>	inches
$L_{M \text{ TOTAL PROJECT}}$ =	<b>7398</b>	lbs.

Number of drainage basins / outfalls areas leaving the plan area = **1**

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	<b>P-2A</b>	
Total drainage basin/outfall area =	<b>10.00</b>	acres
Predevelopment impervious area within drainage basin/outfall area =	<b>0.00</b>	acres
Post-development impervious area within drainage basin/outfall area =	<b>8.00</b>	acres
Post-development impervious fraction within drainage basin/outfall area =	<b>0.80</b>	
$L_{M \text{ THIS BASIN}}$ =	<b>7398</b>	lbs.

3. Indicate the proposed BMP Code for this basin.

Proposed BMP =	<b>JF</b>	abbreviation
Removal efficiency =	<b>86</b>	percent

4. Calculate Maximum TSS Load Removed ( $L_R$ ) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7:  
 $L_R = (\text{BMP efficiency}) \times P \times (A_i \times 34.6 + A_p \times 0.54)$

$A_C$  = Total On-Site drainage area in the BMP catchment area  
 $A_i$  = Impervious area proposed in the BMP catchment area  
 $A_p$  = Pervious area remaining in the BMP catchment area  
 $L_R$  = TSS Load removed from this catchment area by the proposed BMP

$A_C$ =	<b>10.00</b>	acres
$A_i$ =	<b>8.00</b>	acres
$A_p$ =	<b>2.00</b>	acres
$L_R$ =	<b>7647</b>	lbs.

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

Desired $L_{M \text{ THIS BASIN}}$ =	<b>7398</b>	lbs.
F =	<b>0.97</b>	

6. Calculate Treated Flow required by the BMP Type for this drainage basin / outfall area.

Offsite area draining to BMP =	<b>0.00</b>	acres
Offsite impervious cover draining to BMP =	<b>0.00</b>	acres

Calculations from RG-348  
Pages Section 3.2.22

Rainfall Intensity =	<b>2.00</b>	inches per hour
Effective Area =	<b>7.26</b>	acres
Cartridge Length =	<b>54</b>	inches


Peak Treatment Flow Required =	<b>14.64</b>	cubic feet per second
--------------------------------	--------------	-----------------------

7. Jellyfish


Designed as Required in RG-348  
Section 3.2.22

Flow Through Jellyfish Size	Vault
<p>Jellyfish Size for Flow-Based Configuration = <b>2ea JFPD0816-38-8</b></p> <p>Jellyfish Treatment Flow Rate = <b>14.97</b> cfs</p>	

I:\COMMON\CAD\TREATMENT\13 JELLYFISH FILTER\40 STANDARD DRAWINGS\JFPD0816-DTL NEW.DWG 1/29/2018 11:11 AM



**PLAN VIEW**  
(TOP SLAB NOT SHOWN FOR CLARITY)



**ELEVATION VIEW**

**Jellyfish Filter**


THIS PRODUCT MAY BE PROTECTED BY ONE OR MORE OF THE FOLLOWING: U.S. PATENT NO. 8,287,726; 8,221,618; US 8,123,935; OTHER INTERNATIONAL PATENTS PENDING

**JELLYFISH DESIGN NOTES**


JELLYFISH TREATMENT CAPACITY IS A FUNCTION OF THE CARTRIDGE LENGTH AND THE NUMBER OF CARTRIDGES. THE STANDARD PEAK DIVERSION STYLE WITH PRECAST TOP SLAB IS SHOWN. ALTERNATE OFFLINE VAULT AND/OR SHALLOW ORIENTATIONS ARE AVAILABLE. PEAK CONVEYANCE CAPACITY TO BE DETERMINED BY ENGINEER OF RECORD

**CARTRIDGE SELECTION**

CARTRIDGE LENGTH	54"	40"	27"	15"
OUTLET INVERT TO STRUCTURE INVERT (A)	6'-6"	5'-4"	4'-3"	3'-3"
FLOW RATE HI-FLO / DRAINDOWN (CFS) (PER CART)	0.178 / 0.089	0.133 / 0.067	0.089 / 0.045	0.049 / 0.025
MAX. TREATMENT (CFS)	7.84	5.88	3.92	2.16
DECK TO INSIDE TOP (MIN) (B)	5.00	4.00	4.00	4.00



**FRAME AND COVER**  
(DIAMETER VARIES)  
N.T.S.



**24" TRENCH COVER**  
(LENGTH VARIES)  
N.T.S.

SITE SPECIFIC DATA REQUIREMENTS					
STRUCTURE ID					*
WATER QUALITY FLOW RATE (cfs)					*
PEAK FLOW RATE (cfs)					*
RETURN PERIOD OF PEAK FLOW (yrs)					*
# OF CARTRIDGES REQUIRED (HF / DD)					*
CARTRIDGE LENGTH					*
PIPE DATA:	I.E.	MAT'L	DIA	SLOPE %	HGL
INLET #1	*	*	*	*	*
INLET #2	*	*	*	*	*
OUTLET	*	*	*	*	*
SEE GENERAL NOTES 6-7 FOR INLET AND OUTLET HYDRAULIC AND SIZING REQUIREMENTS.					
RIM ELEVATION					*
ANTI-FLOTATION BALLAST		WIDTH	HEIGHT		
		*	*		
NOTES/SPECIAL REQUIREMENTS:					
* PER ENGINEER OF RECORD					

**GENERAL NOTES:**

- CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
- FOR SITE SPECIFIC DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHT, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS REPRESENTATIVE. [www.ContechES.com](http://www.ContechES.com)
- JELLYFISH WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
- STRUCTURE SHALL MEET AASHTO HS-20 OR PER APPROVING JURISDICTION REQUIREMENTS, WHICHEVER IS MORE STRINGENT, ASSUMING EARTH COVER OF 0' - 10', AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 LOAD RATING AND BE CAST WITH THE CONTECH LOGO.
- STRUCTURE SHALL BE PRECAST CONCRETE CONFORMING TO ASTM C-857, ASTM C-918, AND AASHTO LOAD FACTOR DESIGN METHOD.
- OUTLET PIPE INVERT IS EQUAL TO THE CARTRIDGE DECK ELEVATION.
- THE OUTLET PIPE DIAMETER FOR NEW INSTALLATIONS IS RECOMMENDED TO BE ONE PIPE SIZE LARGER THAN THE INLET PIPE AT EQUAL OR GREATER SLOPE.
- NO PRODUCT SUBSTITUTIONS SHALL BE ACCEPTED UNLESS SUBMITTED 10 DAYS PRIOR TO PROJECT BID DATE, OR AS DIRECTED BY THE ENGINEER OF RECORD.

**INSTALLATION NOTES**

- ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
- CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STRUCTURE.
- CONTRACTOR WILL INSTALL AND LEVEL THE STRUCTURE, SEALING THE JOINTS, LINE ENTRY AND EXIT POINTS (NON-SHRINK GROUT WITH APPROVED WATERSTOP OR FLEXIBLE BOOT).
- CARTRIDGE INSTALLATION, BY CONTECH, SHALL OCCUR ONLY AFTER SITE HAS BEEN STABILIZED AND THE JELLYFISH UNIT IS CLEAN AND FREE OF DEBRIS. CONTACT CONTECH TO COORDINATE CARTRIDGE INSTALLATION WITH SITE STABILIZATION.

**CONTECH**  
ENGINEERED SOLUTIONS LLC

[www.ContechES.com](http://www.ContechES.com)  
9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069  
800-338-1122 513-645-7000 513-645-7993 FAX

JELLYFISH JFPD0816  
STANDARD DETAIL  
PEAK DIVERSION CONFIGURATION

Project Name: 560 Development  
Date Prepared: 8/11/2025

1. The Required Load Reduction for the total project:

Calculations from RG-348 Page 3-29 Equation 3.3:  $L_M = 28.9(A_N \times P)$   
Pages 3-27 to 3-30

$L_{M \text{ TOTAL PROJECT}}$  = Required TSS removal resulting from the proposed development = 85% of increased load  
 $A_N$  = Net increase in impervious area for the project  
P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Williamson	
Total project area included in plan * =	8.00	acres
Predevelopment impervious area within the limits of the plan * =	0.00	acres
Total post-development impervious area within the limits of the plan* =	6.40	acres
Total post-development impervious cover fraction * =	0.80	
P =	32	inches
$L_{M \text{ TOTAL PROJECT}}$ =	5919	lbs.

Number of drainage basins / outfalls areas leaving the plan area = 1

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	P-2B	
Total drainage basin/outfall area =	8.00	acres
Predevelopment impervious area within drainage basin/outfall area =	0.00	acres
Post-development impervious area within drainage basin/outfall area =	6.40	acres
Post-development impervious fraction within drainage basin/outfall area =	0.80	
$L_{M \text{ THIS BASIN}}$ =	5919	lbs.

3. Indicate the proposed BMP Code for this basin.

Proposed BMP =	JF	abbreviation
Removal efficiency =	86	percent

4. Calculate Maximum TSS Load Removed ( $L_R$ ) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7:  
 $LR = (BMP \text{ efficiency}) \times P \times (A_i \times 34.6 + A_p \times 0.54)$

$A_C$  = Total On-Site drainage area in the BMP catchment area  
 $A_i$  = Impervious area proposed in the BMP catchment area  
 $A_p$  = Pervious area remaining in the BMP catchment area  
 $L_R$  = TSS Load removed from this catchment area by the proposed BMP

$A_C$ =	8.00	acres
$A_i$ =	6.40	acres
$A_p$ =	1.60	acres
$L_R$ =	6118	lbs.

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

Desired $L_{M \text{ THIS BASIN}}$ =	5919	lbs.
F =	0.97	

6. Calculate Treated Flow required by the BMP Type for this drainage basin / outfall area.

Offsite area draining to BMP =	0.00	acres
Offsite impervious cover draining to BMP =	0.00	acres

Calculations from RG-348  
Pages Section 3.2.22

Rainfall Intensity =	2.00	inches per hour
Effective Area =	5.81	acres
Cartridge Length =	54	inches


Peak Treatment Flow Required =	11.71	cubic feet per second
--------------------------------	-------	-----------------------

7. Jellyfish


Designed as Required in RG-348  
Section 3.2.22

Flow Through Jellyfish Size	Vault
Jellyfish Size for Flow-Based Configuration =	2ea JFPD0812-30-6
Jellyfish Treatment Flow Rate =	11.76 cfs

I:\COMMON\CAD\TREATMENT\13 JELLYFISH FILTER\40 STANDARD DRAWINGS\JFPD0812-DTL.DWG 4/15/2020 8:19 AM



**PLAN VIEW**  
TOP SLAB NOT SHOWN




**ELEVATION VIEW**


**JELLYFISH DESIGN NOTES**

JELLYFISH TREATMENT CAPACITY IS A FUNCTION OF THE CARTRIDGE SIZE, TYPE AND QUANTITY. THE STANDARD PEAK DIVERSION VAULT STYLE WITH PRECAST TOP SLAB IS SHOWN. THE 8' x 12' [2438 x 3658] JELLYFISH PEAK TREATMENT CAPACITY IS 5.88 CFS [166.50 L/s]. MAXIMUM BYPASS CAPACITY IS DETERMINED BY CONTECH ENGINEERED SOLUTIONS. IF THE SITE CONDITIONS EXCEED THE TOTAL BYPASS CAPACITY OF THE SYSTEM, AN UPSTREAM DIVERSION STRUCTURE IS REQUIRED.

CARTRIDGE SIZE	54	40	27	15
FLOW RATE HIGH-FLO / DRAINDOWN (cfs [L/s])	0.178/0.089 [5.10/2.55]	0.133/0.065 [3.68/1.84]	0.089/0.045 [2.55/1.28]	0.049/0.025 [1.42/0.71]
MAXIMUM CARTRIDGE QUANTITY, HI-FLO / DRAINDOWN	30/6			
MAXIMUM TREATMENT	5.88 [166.50]	4.41 [124.88]	2.94 [83.25]	1.62 [45.87]
OUTLET INVERT TO STRUCTURE INVERT (A) (ft. [mm])	6.50 [1981]	5.33 [1625]	4.25 [1295]	3.25 [991]
FINISHED GRADE TO OUTLET INVERT (SHALLOW) (B)	DETERMINED BY CONTECH			
FINISHED GRADE TO OUTLET INVERT (STANDARD) (B) (ft. [mm])	5.67 [1727]	4.58 [1396]		



**FRAME AND COVER**  
STANDARD TOP  
SLAB CONFIGURATION  
(DIAMETER VARIES)  
NOT TO SCALE



**24\"/>**

SITE SPECIFIC DATA REQUIREMENTS					
STRUCTURE ID					
WATER QUALITY FLOW RATE (cfs [L/s])					
PEAK FLOW RATE (cfs [L/s])					
RETURN PERIOD OF PEAK FLOW (yrs)					
NUMBER OF CARTRIDGES REQUIRED (HF / DD)					
CARTRIDGE SIZE (54, 40, 27, 15)					
RIM ELEVATION					
PIPE DATA:	INVERT	MAT'L	DIA	SLOPE %	HGL
INLET PIPE 1					
INLET PIPE 2					
OUTLET PIPE					
SEE GENERAL NOTES 7-8 FOR INLET AND OUTLET HYDRAULIC AND SIZING REQUIREMENTS.					
NOTES / SPECIAL REQUIREMENTS:					

**GENERAL NOTES:**

- CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
- FOR SITE SPECIFIC DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHT, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS REPRESENTATIVE. [www.ContechES.com](http://www.ContechES.com)
- ALTERNATE UNITS ARE IN MILLIMETERS [mm] UNLESS NOTED OTHERWISE.
- JELLYFISH WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
- STRUCTURE SHALL MEET AASHTO HS-20 OR PER APPROVING JURISDICTION REQUIREMENTS, WHICHEVER IS MORE STRINGENT, ASSUMING EARTH COVER OF 0' - 10' [3048], AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 LOAD RATING AND BE CAST WITH THE CONTECH LOGO.
- STRUCTURE SHALL BE PRECAST CONCRETE CONFORMING TO ASTM C-857, ASTM C-918, AND AASHTO LOAD FACTOR DESIGN METHOD.
- OUTLET PIPE INVERT IS EQUAL TO THE CARTRIDGE DECK ELEVATION.
- THE OUTLET PIPE DIAMETER FOR NEW INSTALLATIONS IS RECOMMENDED TO BE ONE PIPE SIZE LARGER THAN THE INLET PIPE AT EQUAL OR GREATER SLOPE.
- NO PRODUCT SUBSTITUTIONS SHALL BE ACCEPTED UNLESS SUBMITTED 10 DAYS PRIOR TO PROJECT BID DATE, OR AS DIRECTED BY THE ENGINEER OF RECORD.

**INSTALLATION NOTES**

- ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
- CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STRUCTURE.
- CONTRACTOR WILL INSTALL AND LEVEL THE STRUCTURE, SEALING THE JOINTS, LINE ENTRY AND EXIT POINTS (NON-SHRINK GROUT WITH APPROVED WATERSTOP OR FLEXIBLE BOOT).
- CARTRIDGE INSTALLATION, BY CONTECH, SHALL OCCUR ONLY AFTER SITE HAS BEEN STABILIZED AND THE JELLYFISH UNIT IS CLEAN AND FREE OF DEBRIS. CONTACT CONTECH TO COORDINATE CARTRIDGE INSTALLATION WITH SITE STABILIZATION.

**Jellyfish Filter**

THIS PRODUCT MAY BE PROTECTED BY ONE OR MORE OF THE FOLLOWING: U.S. PATENT NO. 8,287,726; 8,221,618; US 8,123,935; OTHER INTERNATIONAL PATENTS PENDING

**CONTECH**  
ENGINEERED SOLUTIONS LLC

[www.ContechES.com](http://www.ContechES.com)  
9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069  
800-338-1122 513-645-7000 513-645-7993 FAX

JELLYFISH JFPD0812  
PEAK DIVERSION CONFIGURATION  
STANDARD DETAIL



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Water Pollution Abatement Plan Application Form [TCEQ-0584]  
Attachment C**

**Suitability Letter from Authorized Agent**

There is no proposed on-site sewage facility (OSSF) proposed with this project.

# Organized Sewage Collection System Application

## Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(c), Effective June 1, 1999

***To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.***

***Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.***

**Regulated Entity Name:** Southwestern University 560 Development Phase 1

1.  **Attachment A – SCS Engineering Design Report.** This Engineering Design Report is provided to fulfill the requirements of 30 TAC Chapter 217, including 217.10 of Subchapter A, §§217.51 – 217.70 of Subchapter C, and Subchapter D as applicable, and is required to be submitted with this SCS Application Form.

## Customer Information

2. The entity and contact person responsible for providing the required engineering certification of testing for this sewage collection system upon completion (including private service connections) and every five years thereafter to the appropriate TCEQ region office pursuant to 30 TAC §213.5(c) is:

Contact Person: Richard Madonna

Entity: Southwestern University

Mailing Address: 1001 E University Avenue

City, State: Georgetwon, TX

Zip: 78626

Telephone: \_\_\_\_\_

Fax: \_\_\_\_\_

Email Address: \_\_\_\_\_

***The appropriate regional office must be informed of any changes in this information within 30 days of the change.***

3. The engineer responsible for the design of this sewage collection system is:

Contact Person: Jordan Miller

Texas Licensed Professional Engineer's Number: 124884

Entity: Civiltude, LLC

Mailing Address: 503 Kenniston Dr, Unit 5

City, State: Austin, TX

Zip: 78752

Telephone: (512) 761-6161

Fax: \_\_\_\_\_

Email Address: Jordan@civiltude.com

## Project Information

4. Anticipated type of development to be served (estimated future population to be served, plus adequate allowance for institutional and commercial flows):

- Residential: Number of single-family lots: \_\_\_\_\_  
 Multi-family: Number of residential units: 752  
 Commercial  
 Industrial  
 Off-site system (not associated with any development)  
 Other: \_\_\_\_\_

5. The character and volume of wastewater is shown below:

100% Domestic 640,000 gallons/day  
0% Industrial \_\_\_\_\_ gallons/day  
0% Commingled \_\_\_\_\_ gallons/day  
 Total gallons/day: 640,000

6. Existing and anticipated infiltration/inflow is 41,000 gallons/day. This will be addressed by: The Sanitary Sewer Collection System has been designed to accommodate inflow & infiltration from the site.

7. A Water Pollution Abatement Plan (WPAP) is required for construction of any associated commercial, industrial or residential project located on the Recharge Zone.

- The WPAP application for this development was approved by letter dated \_\_\_\_\_. A copy of the approval letter is attached.  
 The WPAP application for this development was submitted to the TCEQ on 09/17/2025, but has not been approved.  
 A WPAP application is required for an associated project, but it has not been submitted.  
 There is no associated project requiring a WPAP application.

8. Pipe description:

**Table 1 - Pipe Description**

<i>Pipe Diameter(Inches)</i>	<i>Linear Feet (1)</i>	<i>Pipe Material (2)</i>	<i>Specifications (3)</i>
12	3,097	SDR-26 PVC	ASTM D3034

**Total Linear Feet: 3,097**

(1) Linear feet - Include stub-outs and double service connections. Do not include private service laterals.

(2) Pipe Material - If PVC, state SDR value.

(3) Specifications - ASTM / ANSI / AWWA specification and class numbers should be included.

9. The sewage collection system will convey the wastewater to the San Gabriel Wastewater (name) Treatment Plant. The treatment facility is:

- Existing
- Proposed

10. All components of this sewage collection system will comply with:

- The City of Georgetown standard specifications.
- Other. Specifications are attached.

11.  No force main(s) and/or lift station(s) are associated with this sewage collection system.  
 A force main(s) and/or lift station(s) is associated with this sewage collection system and the **Lift Station/Force Main System Application** form (TCEQ-0624) is included with this application.

***Alignment***

12.  There are no deviations from uniform grade in this sewage collection system without manholes and with open cut construction.

13.  There are no deviations from straight alignment in this sewage collection system without manholes.

**Attachment B - Justification and Calculations for Deviation in Straight Alignment without Manholes.** A justification for deviations from straight alignment in this sewage collection system without manholes with documentation from pipe manufacturer allowing pipe curvature is attached.

For curved sewer lines, all curved sewer line notes (TCEQ-0596) are included on the construction plans for the wastewater collection system.

***Manholes and Cleanouts***

14.  Manholes or clean-outs exist at the end of each sewer line(s). These locations are listed below: (Please attach additional sheet if necessary)

**Table 2 - Manholes and Cleanouts**

<i>Line</i>	<i>Shown on Sheet</i>	<i>Station</i>	<i>Manhole or Clean-out?</i>
A	44 Of 67	1+00.00	MH
A	44 Of 67	3+19.51	MH
A	44 Of 67	4+26.31	MH
A	44 Of 67	5+88.02	MH
A	44 Of 67	9+44.92	MH
B	45 Of 67	1+44.88	MH

<i>Line</i>	<i>Shown on Sheet</i>	<i>Station</i>	<i>Manhole or Clean-out?</i>
B	45 Of 67	5+61.09	MH
B	46 Of 67	7+46.35	MH
B	46 Of 67	9+34.22	MH
See MH Locations PDF for a complete List of MH/CO Locations	Of		

15.  Manholes are installed at all Points of Curvature and Points of Termination of a sewer line.
16.  The maximum spacing between manholes on this project for each pipe diameter is no greater than:

<b>Pipe Diameter (inches)</b>	<b>Max. Manhole Spacing (feet)</b>
6 - 15	500
16 - 30	800
36 - 48	1000
≥54	2000

- Attachment C – Justification for Variance from Maximum Manhole Spacing.** The maximum spacing between manholes on this project (for each pipe diameter used) is greater than listed in the table above. A justification for any variance from the maximum spacing is attached, and must include a letter from the entity which will operate and maintain the system stating that it has the capability to maintain lines with manhole spacing greater than the allowed spacing.
17.  All manholes will be monolithic, cast-in-place concrete.
- The use of pre-cast manholes is requested for this project. The manufacturer's specifications and construction drawings, showing the method of sealing the joints, are attached.

## **Site Plan Requirements**

**Items 18 - 25 must be included on the Site Plan.**

18.  The Site Plan must have a minimum scale of 1" = 400'.  
Site Plan Scale: 1" = 100'.
19.  The Site Plan must include the sewage collection system general layout, including manholes with station numbers, and sewer pipe stub outs (if any). Site plan must be overlain by topographic contour lines, using a contour interval of not greater than ten feet and showing the area within both the five-year floodplain and the 100-year floodplain of any drainage way.
20. Lateral stub-outs:

- The location of all lateral stub-outs are shown and labeled.
- No lateral stub-outs will be installed during the construction of this sewer collection system.

21. Location of existing and proposed water lines:

- The entire water distribution system for this project is shown and labeled.
- If not shown on the Site Plan, a Utility Plan is provided showing the entire water and sewer systems.
- There will be no water lines associated with this project.

22. 100-year floodplain:

- After construction is complete, no part of this project will be in or cross a 100-year floodplain, either naturally occurring or manmade. (Do not include streets or concrete-lined channels constructed above of sewer lines.)
- After construction is complete, all sections located within the 100-year floodplain will have water-tight manholes. These locations are listed in the table below and are shown and labeled on the Site Plan. (Do not include streets or concrete-lined channels constructed above sewer lines.)

**Table 3 - 100-Year Floodplain**

<i>Line</i>	<i>Sheet</i>	<i>Station</i>
C	47 of 67	1+00.00 to 4+14.17
	of	to
	of	to
	of	to

23. 5-year floodplain:

- After construction is complete, no part of this project will be in or cross a 5-year floodplain, either naturally occurring or man-made. (Do not include streets or concrete-lined channels constructed above sewer lines.)
- After construction is complete, all sections located within the 5-year floodplain will be encased in concrete or capped with concrete. These locations are listed in the table below and are shown and labeled on the Site Plan. (Do not include streets or concrete-lined channels constructed above sewer lines.)

**Table 4 - 5-Year Floodplain**

<i>Line</i>	<i>Sheet</i>	<i>Station</i>
	of	to

- 24.  Legal boundaries of the site are shown.

25.  The **final plans and technical specifications** are submitted for the TCEQ's review. Each sheet of the construction plans and specifications are dated, signed, and sealed by the Texas Licensed Professional Engineer responsible for the design on each sheet.

**Items 26 - 33 must be included on the Plan and Profile sheets.**

26.  All existing or proposed water line crossings and any parallel water lines within 9 feet of sewer lines are listed in the table below. These lines must have the type of pressure rated pipe to be installed shown on the plan and profile sheets. Any request for a variance from the required pressure rated piping at crossings must include a variance approval from 30 TAC Chapter 290.

There will be no water line crossings.

There will be no water lines within 9 feet of proposed sewer lines.

**Table 5 - Water Line Crossings**

<i>Line</i>	<i>Station or Closest Point</i>	<i>Crossing or Parallel</i>	<i>Horizontal Separation Distance</i>	<i>Vertical Separation Distance</i>
B	1+32.06	Crossing		14.05'
C	7+20.18	Crossing		18.59'
C	11+20.27	Crossing		21.35'

27. Vented Manholes:

**No part** of this sewer line is within the 100-year floodplain and vented manholes are not required by 30 TAC Chapter 217.

**A portion** of this sewer line is within the 100-year floodplain and vented manholes will be provided at less than 1500 foot intervals. These water-tight manholes are listed in the table below and labeled on the appropriate profile sheets.

**A portion** of this sewer line is within the 100-year floodplain and an alternative means of venting shall be provided at less than 1500 feet intervals. A description of the alternative means is described on the following page.

**A portion** of this sewer line is within the 100-year floodplain; however, there is no interval longer than 1500 feet located within. No vented manholes will be used.

**Table 6 - Vented Manholes**

<i>Line</i>	<i>Manhole</i>	<i>Station</i>	<i>Sheet</i>
C	1	1+00.00	47 OF 67
C	2	2+66.28	

<i>Line</i>	<i>Manhole</i>	<i>Station</i>	<i>Sheet</i>

28. Drop manholes:

- There are no drop manholes associated with this project.
- Sewer lines which enter new or existing manholes or "manhole structures" higher than 24 inches above the manhole invert are listed in the table below and labeled on the appropriate profile sheets. These lines meet the requirements of 30 TAC §217.55(l)(2)(H).

**Table 7 - Drop Manholes**

<i>Line</i>	<i>Manhole</i>	<i>Station</i>	<i>Sheet</i>
C	1	1+00.00	47

29. Sewer line stub-outs (For proposed extensions):

- The placement and markings of all sewer line stub-outs are shown and labeled.
- No sewer line stub-outs are to be installed during the construction of this sewage collection system.

30. Lateral stub-outs (For proposed private service connections):

- The placement and markings of all lateral stub-outs are shown and labeled.
- No lateral stub-outs are to be installed during the construction of this sewage collection system.

31. Minimum flow velocity (From Appendix A)

- Assuming pipes are flowing full; all slopes are designed to produce flows equal to or greater than 2.0 feet per second for this system/line.

32. Maximum flow velocity/slopes (From Appendix A)

- Assuming pipes are flowing full, all slopes are designed to produce maximum flows of less than or equal to 10 feet per second for this system/line.
- Attachment D – Calculations for Slopes for Flows Greater Than 10.0 Feet per Second.** Assuming pipes are flowing full, some slopes produce flows which are greater than 10 feet per second. These locations are listed in the table below. Calculations are attached.

**Table 8 - Flows Greater Than 10 Feet per Second**

<i>Line</i>	<i>Profile Sheet</i>	<i>Station to Station</i>	<i>FPS</i>	<i>% Slope</i>	<i>Erosion/Shock Protection</i>

33. Assuming pipes are flowing full, where flows are  $\geq 10$  feet per second, the provisions noted below have been made to protect against pipe displacement by erosion and/or shock under 30 TAC §217.53(l)(2)(B).

- Concrete encasement shown on appropriate Plan and Profile sheets for the locations listed in the table above.
- Steel-reinforced, anchored concrete baffles/retards placed every 50 feet shown on appropriate Plan and Profile sheets for the locations listed in the table above.
- N/A

**Administrative Information**

- 34.  The final plans and technical specifications are submitted for TCEQ review. Each sheet of the construction plans and specifications are dated, signed, and sealed by the Texas Licensed Professional Engineer responsible for the design on each sheet.
- 35.  Standard details are shown on the detail sheets, which are dated, signed, and sealed by the Texas Licensed Professional Engineer, as listed in the table below:

**Table 9 - Standard Details**

<b>Standard Details</b>	<b>Shown on Sheet</b>
Lateral stub-out marking <b>[Required]</b>	65 of 67
Manhole, showing inverts comply with 30 TAC §217.55(l)(2) <b>[Required]</b>	65 of 67
Alternate method of joining lateral to existing SCS line for potential future connections <b>[Required]</b>	of
Typical trench cross-sections <b>[Required]</b>	65 of 67
Bolted manholes <b>[Required]</b>	65 of 67
Sewer Service lateral standard details <b>[Required]</b>	65 of 67
Clean-out at end of line <b>[Required, if used]</b>	65 of 67
Baffles or concrete encasement for shock/erosion protection <b>[Required, if flow velocity of any section of pipe &gt;10 fps]</b>	of
Detail showing Wastewater Line/Water Line Crossing <b>[Required, if crossings are proposed]</b>	64 of 67
Mandrel detail or specifications showing compliance with 30 TAC §217.57(b) and (c) <b>[Required, if Flexible Pipe is used]</b>	65 of 67

<i>Standard Details</i>	<i>Shown on Sheet</i>
Drop manholes [Required, if a pipe entering a manhole is more than 24 inches above manhole invert]	65 of 67

36.  All organized sewage collection system general construction notes (TCEQ-0596) are included on the construction plans for this sewage collection system.
37.  All proposed sewer lines will be sufficiently surveyed/staked to allow an assessment prior to TCEQ executive director approval. If the alignments of the proposed sewer lines are not walkable on that date, the application will be deemed incomplete and returned.
- Survey staking was completed on this date: \_\_\_\_\_
38.  Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
39.  Any modification of this SCS application will require TCEQ approval, prior to construction, and may require submission of a revised application, with appropriate fees.


## **Signature**

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Organized Sewage Collection System Application** is hereby submitted for TCEQ review and executive director approval. The system was designed in accordance with the requirements of 30 TAC §213.5(c) and 30 TAC §217 and prepared by:

Print Name of Licensed Professional Engineer: Jordan Miller

Date: 10/6/2025

Place engineer's seal here:



Signature of Licensed Professional Engineer:

*Jordan L. Miller*

---

## Appendix A-Flow Velocity Table

**Flow Velocity (Flowing Full)** All gravity sewer lines on the Edwards Aquifer Recharge Zone shall be designed and constructed with hydraulic slopes sufficient to give a velocity when flowing full of not less than 2.0 feet per second, and not greater than 10 feet per second. The grades shown in the following table are based on Manning's formula and an n factor of 0.013 and shall be the minimum and maximum acceptable slopes unless provisions are made otherwise.

**Table 10 - Slope Velocity**

Pipe Diameter(Inches)	% Slope required for minimum flow velocity of 2.0 fps	% Slope which produces flow velocity of 10.0 fps
6	0.50	12.35
8	0.33	8.40
10	0.25	6.23
12	0.20	4.88
15	0.15	3.62
18	0.11	2.83
21	0.09	2.30
24	0.08	1.93
27	0.06	1.65
30	0.055	1.43
33	0.05	1.26
36	0.045	1.12
39	0.04	1.01
>39	*	*

\*For lines larger than 39 inches in diameter, the slope may be determined by Manning's formula (as shown below) to maintain a minimum velocity greater than 2.0 feet per second when flowing full and a maximum velocity less than 10 feet per second when flowing full.

$$v = \frac{1.49}{n} \times R_h^{0.67} \times \sqrt{S}$$

**Figure 1 - Manning's Formula**

Where:

v = velocity (ft/sec)  
n = Manning's roughness coefficient (0.013)  
Rh = hydraulic radius (ft)  
S = slope (ft/ft)

The following SCS Engineering Design Report is provided to fulfill the requirements of 30 TAC Chapter 217, including 217.10 of Subchapter A, 217.51-217.70 of Subchapter C, and Subchapter D as applicable. The contents of this report are based off of 30 TAC Chapter 217, Subchapter A 217.10, section E.

### 1. SERVICE AREA MAP

Please reference the Overall Utility Plans and Profile Sheets in the included plan set.

### 2. TOPOGRAPHIC FEATURES OF THE SERVICE AREA

Please reference the Overall Utility Plans and Profile Sheets in the included plan set.

### 3. DESIGN FLOW DETERMINATION

- a) Type of development to be served: Residential (Multifamily)
- b) Peak factor used for design: 4.00

### 4. MINIMUM AND MAXIMUM GRADES

All sewer pipes are designed with slopes that will provide a velocity of at least 2 fps flowing full, as calculated using Manning's Equation with a Roughness Coefficient (n) of 0.011. Sewer pipes are also designed with slopes that will provide a velocity less than 10 fps.

Pipe Diameter	Pipe Type	Minimum Slope	Maximum Slope
12"	SDR-26	1.00%	1.00%

### 5. MINIMUM AND MAXIMUM VELOCITIES AND FLOWS

All sewer pipes are designed with slopes that will provide a velocity of at least 2 fps flowing full, as calculated using Manning's Equation with a Roughness Coefficient (n) of 0.011. Sewer pipes are also designed with slopes that will provide a velocity less than 10 fps.

Pipe Diameter	Pipe Type	Minimum Velocity/Wet Flow	Maximum Velocity/Wet Flow
12"	SDR-26	2.15 fps @ 1.00% / 60.2 GPM	4.15 fps @ 1.00% / 471.7 GPM

Pipe Diameter	Pipe Type	Slope	Maximum Capacity
12"	SDR-26	1.00 %	1,893 GPM

### 6. EFFECT ON EXISTING SYSTEM'S CAPACITY

Per discussions with the City of Georgetown, the existing system has capacity to handle the sewer flow generated from the subject site.

## 7. INFLOW AND INFILTRATION

The anticipated inflow and infiltration flows are calculated below.

- **VOLUME OF WASTEWATER PRODUCED:**  
LUE's = 745.90  
 $745.90 \text{ LUE'S} * 245 \text{ GPD/LUE} = \underline{182,746 \text{ GPD}} \text{ (126.91 GPM)}$
- **ANTICIPATED INFLOW AND INFILTRATION:**  
Area = 54.61 Acres  
Infiltration = 750 GPD/Acre  
 $54.61 \text{ Acres} * 750 \text{ GPD/Acre} = \underline{40,958 \text{ GPD}} \text{ (28.44 GPM)}$
- **PEAK DRY WEATHER FLOW:**  
Per Austin Water Utility Living Unit Equivalent (LUE) Guidance Document:  
 $\text{Peak Flow Factor} = \frac{18 + \sqrt{(0.0206 * F)}}{4 + \sqrt{(0.0206 * F)}} = 3.49$ , where  $F = 126.91 \text{ GPM}$   
 $\text{Peak Dry Weather Flow} = 3.49 * 182,746 \text{ GPD} = \underline{637,783 \text{ GPD}} \text{ (443.22 GPM)}$
- **PEAK WET WEATHER FLOW:**  
 $\text{Peak Dry Weather Flow} + \text{Inflow and Infiltration} = \underline{678,741 \text{ GPD}} \text{ (471.66 GPM)}$
- **TOTAL REQUIRED CAPACITY FOR PIPE DESIGN = 678,741 GPD (471.66 GPM)**

The following testing measures shall take place upon completion to minimize the inflow and infiltration rates:

a) Leakage Test:

A LOW PRESSURE AIR TEST will be performed on all the lines according to 30 TAC Chapter 217, Subchapter C, Rule 217.57, Section (a) (1).

b) Manholes:

Manholes will be tested with a vacuum test.

Each manhole will be tested immediately after assembly and prior to backfilling. Manholes which have been backfilled shall either be excavated to expose the entire exterior prior to vacuum testing or the manhole will be tested for leakage by means of a hydrostatic test.

Stub outs, manhole boots, and pipe lugs shall be secured to prevent movement while the vacuum is drawn.

A minimum of 60-inch/lb torque wrench will be used to tighten the external clamps that secure the test cover to the top of the manhole.

The test head will be placed at the inside of the top of the cone section and the seal inflated in accordance with the manufacturer's recommendation.

A vacuum of 10 inches of mercury will be drawn and the vacuum pump must be shut off. With the valves closed, the time will be measured for the vacuum to drop to 9 inches of mercury. The manhole will pass if the time is greater than 2 minutes. If the manhole fails a second time, repairs will again be made and the manhole will be tested by means of a hydrostatic test which complies with Rule 217.58(b) (1) of Title 30 of the TAC, Chapter 217, Subchapter C. If any manhole fails the hydrostatic test, after failing the vacuum test twice, the contractor shall consider replacing that manhole. If the contractor chooses to attempt to repair that manhole, the manhole must be retested by means of the hydrostatic test outlined in Rule 217.58(b) (1) of Title 30 of the TAC, Chapter 217, Subchapter C, until it passes.

c) Deflection Test:

All flexible pipe gravity lines will be tested for deflection by pulling a rigid mandrel through the installed pipe. The test will be conducted at least 30 days after placement and compaction of final backfill. No pipe will exceed a deflection of 5 %. A rigid mandrel will be used to measure deflection. The test will be performed without mechanical pulling devices. The mandrel's minimum outside diameter will be 95% of the pipes inside diameter. The mandrel will have an odd number of runners, totaling nine or more. The barrel section of the mandrel must have a length at least 75% of the pipe inside diameter.

**8. EXISTING AND PROPOSED TRUNK AND INTERCEPTOR WASTEWATER COLLECTION**

Per discussions with the City of Georgetown, the existing system has capacity to handle the sewer flow generated from the subject site.

**9. RECEIVING TREATMENT FACILITY CAPACITY**

Per discussions with the City of Georgetown, the existing system has capacity to handle the sewer flow generated from the subject site.

## 10. ENGINEERING ANALYSIS OF STRUCTURAL DESIGN

General Structural Components  
 Materials Used and ASTM Standards Adhered to: 30 TAC 217.53(b) (1)

LINE	FROM	TO	PIPE DIAMETER	LINEAR FEET	PIPE MATERIAL	NATIONAL SPECIFICATION PIPE MATERIAL	NATIONAL SPECIFICATION PIPE JOINTS
A	1+00	3+19.5	12"	219.5	SDR-26	ASTM D-2241	ASTM D-3139
A	3+19.5	4+26.3	12"	106.81	SDR-26	ASTM D-2241	ASTM D-3139
A	4+26.3	5+88.0	12"	161.71	SDR-26	ASTM D-2241	ASTM D-3139
A	5+88.0	9+44.9	12"	356.90	SDR-26	ASTM D-2241	ASTM D-3139
B	1+00	1+44.9	12"	44.88	SDR-26	ASTM D-2241	ASTM D-3139
B	1+44.9	5+61.1	12"	416.21	SDR-26	ASTM D-2241	ASTM D-3139
B	5+61.1	7+46.4	12"	185.3	SDR-26	ASTM D-2241	ASTM D-3139
B	7+46.4	9+34.2	12"	187.9	SDR-26	ASTM D-2241	ASTM D-3139
C	1+00	2+66.3	12"	166.3	SDR-26	ASTM D-2241	ASTM D-3139
C	2+66.3	7+27.6	12"	461.4	SDR-26	ASTM D-2241	ASTM D-3139
C	7+27.6	11+39.3	12"	411.64	SDR-26	ASTM D-2241	ASTM D-3139
C	11+39.3	11+79.3	12"	40.05	SDR-26	ASTM D-2241	ASTM D-3139
C	11+79.3	11+94.9	12"	15.56	SDR-26	ASTM D-2241	ASTM D-3139
C	11+94.9	15+17.5	12"	225	SDR-26	ASTM D-2241	ASTM D-3139

Watertight, size on size resilient connectors conforming to ASTM C-923 will be specified for connecting pipe to manholes.

Bedding for placement of flexible pipe must comply with ASTM D2321-11 Class IA, IB, II, or III for materials and densification. A minimum of 6 inches of bedding is required for all pipes.

Pipe Diameter: 12"      Pipe Material: PVC      Bedding Class: IA  
 Manholes shall be pre-cast reinforced concrete, ASTM C-478.

## 11. CORROSION PREVENTION

There are NO components within the proposed collection system that will be susceptible to deterioration through the corrosive effects of an anaerobic sewage environment.

## 12. MANHOLES – GENERAL

Manholes are provided at all changes in size, grade, or alignment of the wastewater pipe. Manholes or cleanouts are provided at the end of all lines.

Pipe Diameter	Max. Proposed Spacing	Max. Spacing Allowed by TCEQ
12"	461.4 LF	500 LF

### **13. MANHOLES – VENTILATION**

Vented Manholes are required. A Portion of the site is within the 100-year flood plain. The proposed manholes shall be watertight and are proposed to be vented.

### **14. MANHOLES – MINIMIZING TURBULENCE**

The number of drop manholes within this system has been kept to a minimum. There is only one sewer lines that enter the manholes higher than 42 inches above the manhole invert. This is the manhole that will replace the existing one at the tie in point into the existing 30" wastewater line.

### **15. MANHOLE CONNECTION**

The connection to the replacement manhole in the existing wastewater line shall use watertight size on size resilient connectors that allow differential settlement and conform to ASTM C-923 (30TAC 217.55(n)).

### **16. INVERTED SIPHONS**

This project does not include any sag pipes.

### **17. TRENCHLESS TECHNOLOGY**

This project does not propose any trenchless installation of pipe

### **18. VERTICAL CURVATURE**

This project has been designed without vertically curved gravity collection piping between manholes.

### **19. HORIZONTAL CURVATURE**

The sewer lines have been designed to be laid in straight alignment with uniform grade between manholes.

### **20. RIGID PIPE DESIGN**

NOT APPLICABLE

## 21. FLEXIBLE PIPE DESIGN

The following computations are for a 12-inch diameter PVC SDR-26 pipe. A summary of results table may be found at the end of this section.

The 12" PVC pipe will be used for the gravity sewer system and will range in depth from 3 to 8.5 ft. There is no concrete encasement being proposed for the pipe.

Pipe Diameter	Average Depth of Cover	Pipe Wall Thickness [t]	Mean Pipe Diameter [D] (O.D. - t)	Modulus of Elasticity [E]	Pipe Stiffness
12"	15.0'	0.481"	12.019"	400,000 psi	115 psi

### Live Load Analysis:

The live load on the pipe ( $W_L$ ) for calculations purposes is zero, as the proposed sewer pipe will not be subjected to live loads during or after construction that affect pipe design. Additionally, "...the influence of pipe loads on the performance of PVC pipe is only significant in shallow depths, usually 4 ft..." (page 191 *Uni-Bell Handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*).

### Buckling Analysis:

#### A. Allowable Buckling Pressure

- 1) Calculate Moment of Inertia,  $I$ , where  $t$  = pipe wall thickness (in.)

$$I = (t^3/12) \text{ in units of inches}^4/\text{linear inch (Equation 4 TCEQ-10243, page 21)}$$

$$I = 0.481^3/12 = \mathbf{0.00927372 \text{ in}^4/\text{in}}$$

- 2) Calculate  $B'$ , an empirical coefficient of elastic support. The max cover height of 28 feet (H) is the worst case and will be used in the buckling calculation.

The equation used below is from *Equation 3 TCEQ-10243, page 21*.

$$B' = \frac{1}{1 + 4 * e^{-0.065(H)}} = \frac{1}{1 + 4 * e^{-0.065(28)}}$$

$$B' = \mathbf{0.607}$$

- 3) Calculate  $R_w$ , the water buoyancy factor. The worst case occurs when groundwater height above the pipe equals the height of cover. This is the case that is calculated.

$h_w$  = height of water surface above top of pipe in inches (in)

$h$  = height of soil surface above top of pipe in inches (in)

$R_w$  = water buoyancy factor

$$R_w = 1 - 0.33 * (h_w/h); 0 \leq h_w \leq h \text{ (Equation 2 TCEQ-10243, page 20)}$$

$$R_w = 1 - 0.33 * (0) = \mathbf{1.0}$$

- 4) Calculate  $q_a$ , allowable buckling pressure. (Equation 1 TCEQ-10243, page 20)

$$q_a = (DF) * \sqrt{\frac{32R_w B' E' EI}{D_{avg}^3}}$$

where:

$q_a$  = allowable buckling pressure (psi)

$E'$  = Modulus of soil reaction for the bedding material (psi)

$E' = 3000$  psi (Class 1A bedding w/ slight compaction, +/-85%)(Table 7.3, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993)

DF = Design factor, 0.40

E=Modulus of Elasticity of pipe material = 400,000psi

D =  $D_{average}$  = mean pipe diameter (O.D. -  $t_{min}$ ) = 12.019 in.

$$q_a = (0.40) * \sqrt{\frac{32 * 1.0 * 0.607 * 3000 * 400,000 * 0.00927372}{12.019^3}}$$

**$q_a = 141.11$  psi**

**B. Calculate pressure applied to pipe under installed conditions.**

- 1) Calculate  $W_c$ , vertical soil load on pipe per unit length (lb/in). (Equation 6 TCEQ-10243, page 21)

$$W_c = \gamma_s * H * \frac{D_{avg} + t}{144}$$

where:

$\gamma_s$  = specific weight of soil = 125 pcf

H = Depth of burial = 28 feet

$D_{avg}$  = mean pipe diameter (O.D. -  $t_{min}$ ) = 12.019 in.

t = pipe structural wall thickness = 0.481 in

$$W_c = 125 * 28 * \frac{12.019 + 0.481}{144} = 304 \text{ lb/in}$$

- 2) Calculate  $q_p$ , pressure applied to pipe under installed conditions. (Equation 5 TCEQ-10243, page 21).

$$q_p = \gamma_w * h_w + R_w * \frac{W_c}{D_{avg}} + W_L$$

where:

$\gamma_w = 0.0361$  lb/in<sup>3</sup> = specific weight of water in pounds per cubic inch

$h_w = 0.0$  in. - height of groundwater surface above top of pipe (inches)

h = 336.0 in. - height of ground surface above top of pipe (inches)

$R_w$  = water buoyancy factor, calculated as  $R_w = 1 - .33 (h_w/h)$ ;  $0 \leq h_w \leq h$   
 $W_c$  = 163 lb/in - vertical soil load on pipe per unit length (lb/in)  
 $W_L$  = 0 - Live load on pipe  
 $D_{avg}$  = mean pipe diameter (O.D. -  $t_{min}$ ) = 12.019 in.

$$q_p = 0.0361 * 0.0 + 1.00 * \frac{304}{12.019} + 0 = 26.33 \text{ psi}$$

**3)** If  $q_a > q_p$ , specified pipe is acceptable for the proposed installation. (TCEQ-10243)

$q_a = 141 \text{ psi}$   
 $q_p = 26.33 \text{ psi}$

**141 psi > 26.33psi**

**Therefore, buckling requirements are met**  
**Pipe Diameter = 12" Pipe Material = PVC SDR-26**

### Wall Crushing:

The following computations are for 12-inch diameter PVC SDR-26 pipe. The following formula is used to calculate the maximum depth that the pipe can be buried before wall crushing (or failure by ring compression) will occur.

**1) Calculate Wall Thrust (lb/in) and Vertical Soil Pressure (psi)**

$$T = P_y * \frac{D_o}{2} \quad (\text{Eq. 7.21, Uni-Bell Handbook, 3}^{\text{rd}} \text{ Edition, Second Printing, 1993})$$

$$\sigma_c = \frac{T}{A} \quad (\text{Eq. 7.22, Uni-Bell Handbook, 3}^{\text{rd}} \text{ Edition, Second Printing, 1993})$$

where:

T = wall thrust (lb/in)  
 $P_y$  = Vertical Soil Pressure (psi)  
 $D_o$  = Outside Wall Diameter = 12.5 in  
 $\sigma_c$  = Compressive Stress = 4,000 psi (Ch VII, page 227 Uni-Bell Handbook, 3<sup>rd</sup> Edition, Second Printing, 1993)  
A = area of pipe wall (in<sup>2</sup>/in) = 0.481 in<sup>2</sup>/in (Plastic Pipe Design Manual)

$$P_y = \sigma_c * \frac{2A}{D_o} = 4,000 \text{ psi} * \frac{2 * 0.481}{12.5}$$

**$P_y = 307.84 \text{ ft}$**

## 2) Calculate Maximum Allowable Depth, H (ft)

$$P_y = w * H \quad (\text{Ch VII, pg. 227 Uni-Bell Handbook, 3}^{rd} \text{ Edition, Second Printing, 1993})$$

where:

$P_y$ =Vertical Soil Pressure, psi

$w$ =soil unit weight = 120 pcf (Ch VII, Uni-Bell Handbook, 3<sup>rd</sup> Edition, Second Printing, 1993)

$$H = \frac{P_y}{w} = \frac{307.84 \text{ psi}}{120 \text{ pcf}} * 144 \frac{\text{in}^2}{\text{ft}^2}$$

**H= 369.541 ft**

**Design does not exceed allowable depth for PVC pipe**

### Installation Temperature Effects:

The PVC pipe will be installed using recommended installation practices. Following recommended installation practices will ensure adequate installation for normal installation temperatures.

### Tensile Strength:

Pipe Material: PVC, Tensile Strength = 7,000 psi, Cell Class (PVC only) 12454

### Strain:

$$\varepsilon = \varepsilon_f + \varepsilon_h \quad (\text{Eq. 7.27, Uni-Bell Handbook, 3}^{rd} \text{ Edition, Second Printing, 1993})$$

$$\varepsilon_f = \frac{1}{DR} * \left( \frac{3 * \frac{\Delta Y}{D}}{1 - 2 * \frac{\Delta Y}{D}} \right) \quad (\text{Eq. 7.26, Uni-Bell Handbook, 3}^{rd} \text{ Edition, Second Printing, 1993})$$

$$\varepsilon_h = \frac{PD}{2tE} \quad (\text{Eq. 7.24, Uni-Bell Handbook, 3}^{rd} \text{ Edition, Second Printing, 1993})$$

where:

$\varepsilon$  = Maximum combined strain in pipe wall, in/in

$\varepsilon_f$  = Max. Strain on pipe wall due to ring deflection (in/in)

$\varepsilon_h$  = Max. Strain on pipe wall due to hoop stress (in/in)

$P$  = pressure on pipe (psi) = 28 ft\*120pcf/144 in<sup>2</sup>/ft<sup>2</sup>=23.33 psi

$E$  = Modulus of elasticity of pipe material = 400,000 psi

$t$  = pipe wall thickness = 0.481 in

$D$ =mean pipe diameter= 12.019 in.

$DY$ =vertical decrease in diameter

$DY/D=0.0127$ , Max

$DR$ =dimension ratio = 26

$$\varepsilon_f = \frac{1}{26} * \left( \frac{3 * 0.0127}{1 - 2 * 0.0127} \right) = 0.0014982 \frac{in}{in}$$

$$\varepsilon_h = \frac{23.33 * 12.019}{2 * 0.481 * 400,000} = 0.000728699 \frac{in}{in}$$

$$\varepsilon = 0.0014982 + 0.000728699 = 0.0022269 \frac{in}{in}$$

### Deflection Analysis:

$E_b = E_2$  = Modulus of soil reaction of bedding = 3000 psi (Class 1A bedding w/ slight compaction, +/-85%) (Table 7.3, *Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

$E_n = E_3$  = Modulus of soil reaction for the in-situ soil = 3,000 psi (Table 7.3 Ch. VI, *Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

Zeta = correction factor

b = trench width (ft)

$d_a$  = pipe diameter (ft)

The ratio of bedding modulus to soil modulus:

$$E_b/E_n = E_2/E_3 = 3000/3,000 = 1$$

$$Zeta = \frac{1.44}{f + (1.44 - f) \frac{E_2}{E_3}} \quad (\text{Eq. 7.37, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993})$$

Where:

$$f = \frac{\frac{b}{d_a} - 1}{1.154 + 0.444 * \left( \frac{b}{d_a} - 1 \right)} \quad (\text{Eq. 7.37, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993})$$

$$f = \frac{\frac{4.67'}{1'} - 1}{1.154 + 0.444 * \left( \frac{4.67'}{1'} - 1 \right)} = 1.32$$

$$Zeta = \frac{1.44}{1.32 + (1.44 - 1.32) * 1} = 1.0$$

Pipe Diameter = 12"

Trench Width = 4.67'

Zeta = 1.0

Pipe stiffness ( $P_s$ ) in psi.

The pipe stiffness for PVC is determined by the parallel plate test.  
(Table 7.1, *Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

Outside Pipe Diameter	Pipe Material	Modulus of Elasticity, E	$P_s$
12.5"	PVC SDR-26	400,000 psi	115 psi

Deflection Calculation:

*Ch. VI and VII Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

$$\frac{\Delta Y}{D} = \frac{D_L * K * P * 100}{\left(\frac{2E}{3(DR - 1)^3}\right) + 0.061 * Zeta * E'} \quad (\text{Eq. 7.37, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993})$$

Where:

$\Delta Y/D$ =Vertical Deflection, %

$D_L$ =Deflection Lag Factor = 1.0 (*Equation 7.12, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

K = Bedding Constant = 0.1 (*Table 7.2, Ch. VII, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

E= Modulus of Elasticity of pipe (psi) (*Ch. VII, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

DR=outside diameter to thickness ratio= 26

$E'$ - Modulus of Soil Reaction = 3,000 psi (*Table 7.3 Ch. VI, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

P=Prism Load Pressure=23.33 psi (28 ft) (*Table 6.3 of Ch. VI, Uni-Bell handbook, 3<sup>rd</sup> Edition, Second Printing, 1993*)

w= unit weight of soil = 120 pcf

H=Depth or bury, 27.9 ft max

Zeta=correction factor

15 Feet of Cover:

$$\frac{\Delta Y}{D} = \frac{1.0 * 0.10 * 23.33 * 100}{\left(\frac{2 * 400,000}{3(26 - 1)^3}\right) + 0.061 * 1.0 * 3,000} = 1.27\% \text{ for 28 feet of cover}$$

All pipes proposed for this project have a maximum deflection of less than 5.00%

**Summary of Flexible Pipe Results**

Pipe Size	12"
Outside Pipe Diameter	12.5"
Type of Material	PVC SDR-26
Pipe Stiffness ( $P_s$ )	115 psi
Zeta Factor	1.0
Modulus of Pipe Bedding Material ( $E_b$ )	3,000 psi
Strain ( $\epsilon$ )	0.0022269 in/in
Max Deflection	1.27%

**22. SPECIAL PROVISIONS FOR FUTURE EXPANSION**

There are no anticipated future extensions.

**23. OPERATING CHARACTERISTICS OF LIFT STATION**

Not Applicable. There is not a proposed lift station associated with this development.

**24. SAFETY CONSIDERATIONS**

**Occupational Safety, Public Health, and Environmental Protection:**

The project plans and specifications will ensure that the pipe installation will adhere to the minimum separation distances allowed by rule 217.13 of the TAC Title 30. Additionally, the project plans or specifications will include an exact reproduction of the separation distance wording detailed by rule 217.13 of the TAC Title 30, which ensures that the separation distance between any unknown water lines which are discovered during the installation phase of the project and the gravity sanitary sewer pipe which will be installed, will be sufficient to comply with the minimum separation distances allowed by the reference stated above.

Provisions to control erosion or sedimentation due to runoff during construction of the project are:

Silt Fence – SEE ATTACHED section with Pollution Prevention Plan.

This site does not contain any water wells, springs, surface water sources of potable water or potable water storage facilities.

**Occupational Safety:**

All manhole base sections will be at least 48 inches in diameter.

All manhole covers will be at least 30 inches nominal diameter.

Portable ladders will be used for access to manholes for maintenance purposes.

The GENERAL CONTRACTOR will be responsible for ensuring that personal gas detectors will be provided to the appropriate personnel that are entering enclosed spaces.

**Testing, Inspection, and Certification**

**Criteria for laying Pipe:** Pipe embedment, compaction, and envelope size shall comply with TAC Title 30 §217.54 and AWU requirements.

**Manholes and Related Structures:** All manhole covers will be at least 30 inches nominal diameter. Manhole connections shall comply with by rule 217.55(n) of the TAC Title 30.


**Testing Requirements for Installation of Gravity Collection System Pipes:** Infiltration and exfiltration test or low air pressure test shall conform to TAC Title 30 §217.57 note 16(a)(1) and 16(a)(2).

**Testing Requirements for Manholes:** All manholes shall be subjected to a leakage test and shall conform to TAC Title 30 §217.58.

***The professional engineer signing and sealing this document is responsible for the completion of this Engineering Design Report and will certify that all the information provided in this document and in the accompanying set of plans and specifications show full compliance with the requirements of Chapter 217 of the TAC Title 30 (TCEQ's rules).***

Signature, Seal, and Date of the Texas Professional engineer who is certifying this document.

10-06-2025



Jordan L. Miller

## MANHOLES AND CLEANOUTS

<b>LINE</b>	<b>SHOWN ON SHEET</b>	<b>STATION</b>	<b>MANHOLE OR CLEANOUT?</b>
A	44 OF 67	1+00.00	MANHOLE
A	44 OF 67	3+19.51	MANHOLE
A	44 OF 67	4+26.31	MANHOLE
A	44 OF 67	5+88.02	MANHOLE
A	44 OF 67	9+44.92	MANHOLE
B	45 OF 67	1+44.92	MANHOLE
B	45 OF 67	5+61.09	MANHOLE
B	46 OF 67	7+46.35	MANHOLE
B	46 OF 67	9+34.22	MANHOLE
C	47 OF 67	1+00.00	MANHOLE
C	47 OF 67	2+66.28	MANHOLE
C	47 OF 67	7+27.63	MANHOLE
C	48 OF 67	11+79.32	MANHOLE
C	48 OF 67	11+94.88	MANHOLE
C	48 OF 67	15+17.47	MANHOLE

# Temporary Stormwater Section

## Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

**To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.**

**Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.**


## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Jordan Miller, P.E.

Date: 08/14/2025

Signature of Customer/Agent:



Regulated Entity Name: Southwestern University 560 Development Phase 1

## Project Information

### Potential Sources of Contamination

*Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.*

1. Fuels for construction equipment and hazardous substances which will be used during construction:

The following fuels and/or hazardous substances will be stored on the site: \_\_\_\_\_

These fuels and/or hazardous substances will be stored in:

- Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
- Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- Fuels and hazardous substances will not be stored on the site.
- 2.  **Attachment A - Spill Response Actions.** A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3.  Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4.  **Attachment B - Potential Sources of Contamination.** A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

### ***Sequence of Construction***

- 5.  **Attachment C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
  - For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
  - For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6.  Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Smith Branch Creek

### ***Temporary Best Management Practices (TBMPs)***

*Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.*

- 7.  **Attachment D – Temporary Best Management Practices and Measures.** TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

- A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
  - A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
  - A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
  - A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8.  The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- Attachment E - Request to Temporarily Seal a Feature.** A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
  - There will be no temporary sealing of naturally-occurring sensitive features on the site.
9.  **Attachment F - Structural Practices.** A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10.  **Attachment G - Drainage Area Map.** A drainage area map supporting the following requirements is attached:
- For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
  - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
  - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
  - There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.

11.  **Attachment H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
- N/A
12.  **Attachment I - Inspection and Maintenance for BMPs.** A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13.  All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14.  If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15.  Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16.  Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

### ***Soil Stabilization Practices***

*Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.*

17.  **Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices.** A schedule of the interim and permanent soil stabilization practices for the site is attached.

18.  Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19.  Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

### ***Administrative Information***

20.  All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21.  If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22.  Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

**Temporary Stormwater Section (TCEQ-0602)  
Attachment A**

**Spill Response Actions**

Spills will be reported to the City of Georgetown (via 911 in emergencies). Hydrocarbons or hazardous substances spilled during construction will be cleaned up immediately upon detection. Waterways will be broomed and vacuumed as required. Contaminated soil will be excavated and removed to a TCEQ approved disposal site. The TCEQ will be notified immediately upon detection.

The objective of this section is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees.

The following steps will help reduce the stormwater impacts of leaks and spills:

**Education**

1. Be aware that different materials pollute in different amounts. Make sure that each employee knows what a “significant spill” is for each material they use, and what is the appropriate response for “significant” and “insignificant” spills. Employees should also be aware of when spill must be reported to the TCEQ. Information available in 30 TAC 327.4 and 40 CFR 302.4.
2. Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
3. Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
4. Establish a continuing education program to indoctrinate new employees.
5. Have contractor’s superintendent or representative oversee and enforce proper spill prevention and control measures.

### **General Measures**

1. To the extent that the work can be accomplished safely, spills of oil, petroleum products, substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
2. Store hazardous materials and wastes in covered containers and protect from vandalism.
3. Place a stockpile of spill cleanup materials where it will be readily accessible.
4. Train employees in spill prevention and cleanup.
5. Designate responsible individuals to oversee and enforce control measures.
6. Spills should be covered and protected from stormwater runoff during rainfall to the extent that it doesn't compromise clean-up activities.
7. Do not bury or wash spills with water.
8. Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.
9. Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.
10. Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.
11. Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.
12. Keep waste storage areas clean, well-organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

### **Cleanup**

1. Clean up leaks and spills immediately.
2. Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.
3. Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

### **Minor Spills**

1. Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.
2. Use absorbent materials on small spills rather than hosing down or burying the spill.
3. Absorbent materials should be promptly removed and disposed of properly.
4. Follow the practice below for a minor spill:
5. Contain the spread of the spill.
6. Recover spilled materials.
7. Clean the contaminated area and properly dispose of contaminated materials. 1-120

### **Semi-Significant Spills**

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities. Spills should be cleaned up immediately:

1. Contain spread of the spill.
2. Notify the project foreman immediately.

3. If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
4. If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
5. If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

### **Significant/Hazardous Spills**

For significant or hazardous spills that are in reportable quantities:

1. Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
2. For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110,119, and 302, the contractor should notify the National Response Center at (800) 424-8802.
3. Notification should first be made by telephone and followed up with a written report.
4. The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.
5. Other agencies which may need to be consulted include, but are not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc. More information on spill rules and appropriate responses is available on the TCEQ website at:

<https://www.tceq.texas.gov/response/spills>

**Temporary Stormwater Section (TCEQ-0602)**  
**Attachment B**

**Potential Sources of Contamination**

Potential sources of contamination at the site include:

1. Construction vehicles tracking mud onto the roadway.
2. Fueling of construction vehicles.
3. Short-term storage and use of fertilizers for use in establishing vegetation.
4. Possible littering around the construction site.

All activities will be conducted in a manner to minimize the potential for impact to the environment.

**Temporary Stormwater Section (TCEQ-0602)**  
**Attachment C**

**Sequence of Major Activities**

Sequence of major activities:

1. Install temporary erosion controls and tree protection fencing. (perimeter of 68.77-acre limits of construction)
2. Clearing and grubbing. (68.77-acres)
3. Rough grade site and construct ponds. (68.77-acres)
4. Construct utilities. (3.25-acres)
5. Construct and pave roadway. (11.98-acres)
6. Complete final grading. (68.77-acres)
7. Construct Buildings. (6.28-acres)
8. Complete permanent erosion control and restoration of site vegetation. (46.65-acres)
9. Remove temporary erosion controls. (perimeter of 68.77-acre limits of construction)

**Temporary Stormwater Section (TCEQ-0602)  
Attachment D**

**Temporary Best Management Practices and Measures**

Temporary Erosion and Sediment Control Best Management Practices (BMPs) shall be designed and placed in accordance with the City of Georgetown and TCEQ requirements. The temporary BMPs shall be installed prior to any site preparation work (clearing, grubbing, or excavation).

**Silt Fence**

Silt fence shall be installed immediately down gradient of areas of soil disturbance. See City of Georgetown Standard Detail on the Construction Plans for details on construction and installation.

**Tree Protection**

If applicable, tree protection shall be installed around trees to prevent tree damage and potential damage or disturbance of the tree's root zone. See the City of Georgetown Standard Detail on the Construction Plans for details on construction of and installation.

**Dust Control**

Dust control can prevent blowing and movement of dust from exposed soil surfaces, reduce on-site and off-site damage, and improve traffic safety. Dust control will be implemented at the site during all phases of construction.

Dust control during construction shall be done with mulch, irrigation, or an alternative method described in the City of Georgetown Environmental Protection section of the Georgetown Unified Development Code.

**Disturbed Area Minimization**

An effective way to minimize potential impact from storm water runoff from construction sites is to minimize the area of soil disturbance. The site will be developed in such a manner as to limit the necessary construction to as small an area as practical, thereby reducing the amount of run-off generated by a storm event.

### **Stabilized Construction Entrance**

Anti-tracking pads consisting of stone will be installed at the entrance as identified on the site plan to prevent the off-site transport of sediment by construction vehicles. Crushed stone will be placed over a layer of geotextile filter fabric to reduce the mitigation of sediment from the underlying soil. The stabilization entrance will be installed prior to construction beginning on the site. The stone will remain in place until the sub grade of pavement is installed at the site.

### **Rock Berm**

Rock berms will be utilized throughout the site to protect trees and other environmentally sensitive areas from erosion. Temporary erosion and sedimentation controls are to be installed prior to any site grading activities. The contractor is required to inspect the controls and fences at weekly intervals and after significant rainfall events to ensure that they are functioning properly.

### **Inlet Protection**

Inlet filter inserts will be installed as the storm sewer system is constructed onsite. The catch basin filter inserts will be inspected weekly and immediately after storm events. If the basin insert becomes clogged with sediment, the insert will be removed and cleaned or replaced per the manufacturer's recommendations.

### **Concrete Washout**

A designated temporary, above-grade concrete washout area will be constructed. The temporary concrete washout area will be constructed with sufficient quantity and volume to contain all liquid and concrete waste generated by washout operations. Concrete mixer trucks and chutes will be washed during or before an anticipated storm event in the designated area and any concrete waste will be properly disposed of off-site.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Temporary Stormwater Section (TCEQ-0602)  
Attachment E**

**Request to Temporarily Seal a Feature**

We are not requesting to seal any sensitive features on site.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Temporary Stormwater Section (TCEQ-0602)  
Attachment F**

**Structural Practices**

The site will be graded to allow storm water runoff to flow to the proposed storm inlets in the new roadways. The captured storm runoff will then go through the proposed storm drains and eventually reach the proposed Contech Jellyfish Stormwater Treatment Filters where sediment and pollutants will be filtered out. The treated runoff will then be held in the on-site detention ponds and finally released into the nearby creek.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Temporary Stormwater Section (TCEQ-0602)  
Attachment G**

**Drainage Area Map**

A drainage area map has been included in the construction documents that accompany this WPAP submittal.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Temporary Stormwater Section (TCEQ-0602)  
Attachment H**

**Temporary Sediment Pond(s) Plans and Calculations**

There are no temporary sediment ponds associated with this development; however, the permanent detention ponds will function as the temporary sediment traps for this project until the Contech Jellyfish Storm Water Treatment Filters are installed.

**Temporary Stormwater Section (TCEQ-0602)  
Attachment I**

**Inspection and Maintenance for BMP's**

The following is a schedule for inspection and maintenance for Temporary BMPs:

Silt Fence:	Inspect daily and after every rain event any repairs must be done within 24 hours of failure.
Temporary Inlet Protection:	Inspect weekly and after every rain event any repairs must be done within 24 hours of failure.
Tree Protection:	Inspect weekly.
Stabilized Construction Entrance:	Inspect weekly and after every rain event any repairs must be done within 24 hours of failure.
Concrete Washout Area:	Inspect weekly, after every rain event, and at the end of any day when concrete has been poured. Any overflowing of the washout facilities onto the ground must be cleaned up and removed within 24 hours of discovery. Break up hardened solids prior to removal and either reuse material on-site (as in the case for roadbeds) or haul away for recycling. Inspect structure for signs of weakening or damage after removal of materials and make any necessary repairs including re-lining with plastic that is free of holes or tears.
Rock Berms:	Inspect weekly and after every rain event to make repairs and clean out as necessary. Sediment accumulated upstream of rock berm shall be removed when the sediment depth upstream of filter is within 5 inches of the crest. If rock berms are removed any disturbed area shall be stabilized in a manner approved by the City.
Dewatering:	Install, operate, and maintain pressurized filtration systems by following manufacturer recommendations. Sediment must be frequently removed from devices and properly disposed of to



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

#### Temporary Sedimentation Basin:

maintain effectiveness.

Inspection should be made weekly and after each rainfall. Check the embankment, spillways, and outlet for erosion damage, and inspect the embankment for piping and settlement. Repair should be made promptly as needed by the contractor. Trash and other debris should be removed after each rainfall to prevent clogging of the outlet structure. Accumulated silt should be removed and the basin should be regraded to its original dimensions at such point that the capacity of the impoundment has been reduced to 75% of its original storage capacity. The removed sediment should be stockpiled or redistributed in areas that are protected from erosion.

**Temporary Stormwater Section (TCEQ-0602)  
Attachment J**

**Schedule of Interim and Permanent Soil Stabilization Practices**

The following is a schedule of interim and permanent soil stabilization practices:

<b>Prior to site disturbance:</b>	Install all temporary vegetation features.
<b>During construction:</b>	Maintain all temporary vegetation features and install soil stabilization matting on slopes greater than 3:1 as described in the Edwards Aquifer Technical Guidance Manual Section 1.3. Inspect all temporary features on a weekly basis and after all rain events.
<b>After completion of construction:</b>	Install all permanent vegetation and geotextile features.
<b>After completion of permanent Erosion and sedimentation:</b>	Remove all temporary vegetation and soil stabilization matting features.
<b>If construction is temporarily stopped unexpectedly:</b>	If disturbed area is not to be worked on for more than 14 days, disturbed area needs to be stabilized by re-vegetation, mulch, tarp, or re-vegetation matting. If construction is permanently stopped, install all permanent vegetation and geotextile features and remove all temporary vegetation and soil stabilization matting features.

# Permanent Stormwater Section

## Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(C), (D)(li), (E), and (5), Effective June 1, 1999

*To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.*

*Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.*

### Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Permanent Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Jordan Miller, P.E.

Date: 08/19/2025

Signature of Customer/Agent

  
\_\_\_\_\_

Regulated Entity Name: Southwestern University 560 Development Phase 1

### Permanent Best Management Practices (BMPs)

*Permanent best management practices and measures that will be used during and after construction is completed.*

- 1.  Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.  
 N/A
- 2.  These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.  
 The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.

A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: \_\_\_\_\_

N/A

3.  Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.

N/A

4. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

The site will be used for low density single-family residential development and has 20% or less impervious cover.

The site will be used for low density single-family residential development but has more than 20% impervious cover.

The site will not be used for low density single-family residential development.

5. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

**Attachment A - 20% or Less Impervious Cover Waiver.** The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.

The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.

The site will not be used for multi-family residential developments, schools, or small business sites.

6.  **Attachment B - BMPs for Upgradient Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
  - No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
  - Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
7.  **Attachment C - BMPs for On-site Stormwater.**
- A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
  - Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
8.  **Attachment D - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is attached. Each feature identified in the Geologic Assessment as sensitive has been addressed.
- N/A
9.  The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.
- The permanent sealing of or diversion of flow from a naturally-occurring sensitive feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed.
  - Attachment E - Request to Seal Features.** A request to seal a naturally-occurring sensitive feature, that includes, for each feature, a justification as to why no reasonable and practicable alternative exists, is attached.
10.  **Attachment F - Construction Plans.** All construction plans and design calculations for the proposed permanent BMP(s) and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. The plans are attached and, if applicable include:
- Design calculations (TSS removal calculations)
  - TCEQ construction notes
  - All geologic features
  - All proposed structural BMP(s) plans and specifications
- N/A

11.  **Attachment G - Inspection, Maintenance, Repair and Retrofit Plan.** A plan for the inspection, maintenance, repairs, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan includes all of the following:
- Prepared and certified by the engineer designing the permanent BMPs and measures
  - Signed by the owner or responsible party
  - Procedures for documenting inspections, maintenance, repairs, and, if necessary retrofit
  - A discussion of record keeping procedures
- N/A
12.  **Attachment H - Pilot-Scale Field Testing Plan.** Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
- N/A
13.  **Attachment I -Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that results in water quality degradation.
- N/A

### ***Responsibility for Maintenance of Permanent BMP(s)***

***Responsibility for maintenance of best management practices and measures after construction is complete.***

14.  The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
- N/A
15.  A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.
- N/A



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Permanent Stormwater Section (TCEQ-0600)  
Attachment A**

**20% or Less Impervious Cover Waiver**

This waiver is not applicable for this site.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Permanent Stormwater Section (TCEQ-0600)  
Attachment B**

**BMP for Upgradient Water**

Storm water runoff from upgradient areas is treated separately on each individual site. Any off-site storm water draining to this site that is located within the drainage areas shown on the proposed drainage area map included in the plan set will be accounted for by the BMPs detailed in Attachment C.

**Permanent Stormwater Section (TCEQ-0600)  
Attachment C**

**Permanent BMP's for On-Site Stormwater**

Implementation of Contech Jellyfish Filters have been selected as the permanent Best Management Practice (BMP) for on-site stormwater quality treatment for this development. The Jellyfish Filters are designed to provide water quality for the proposed site and to reduce the increase in total suspended solids (TSS) load associated with the overall site development. These Jellyfish structures have been designed in conjunction with on-site detention ponds. The ponds have been designed per the City of Georgetown's Drainage Criteria Manual and the Texas Commission on Environmental Qualities Technical Guidance Manual. The TSS removal calculations show that the Contech Jellyfish Stormwater Treatment Filters are sufficiently sized to treat a total of 14.40-acres of on-site impervious cover (80%). Additionally, the two on-site detention ponds have been designed to detain a total of 16.87 acres; resulting in a decrease in the amount of stormwater being discharged to their respective points of analysis. The calculations demonstrate that the Contech Jellyfish Filters will sufficiently remove 86% of the increased TSS load.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Permanent Stormwater Section (TCEQ-0600)  
Attachment D**

**Permanent BMP's for Surface Streams**

There are no surface streams on the regulated site.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Permanent Stormwater Section (TCEQ-0600)  
Attachment E**

**Request to Temporarily Seal Features**

There are no sensitive environmental features on the regulated entity that are proposed to be sealed.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Permanent Stormwater Section (TCEQ-0600)  
Attachment F**

**Construction Plans**

Construction plans for this project have been prepared and submitted along with this WPAP Application.

## **Permanent Stormwater Section [TCEQ-0600]**

### **Attachment G**

#### **Inspection, Maintenance, Repair and Retrofit Plan**

##### **CONTECH JELLYFISH FILTERS**

The primary purpose of the Jellyfish® Filter is to capture and remove pollutants from stormwater runoff. As with any filtration system, these pollutants must be removed to maintain the filter's maximum treatment performance. Regular inspection and maintenance are required to insure proper functioning of the system.

Maintenance frequencies and requirements are site specific and vary depending on pollutant loading. Additional maintenance activities may be required in the event of non-storm event runoff, such as base-flow or seasonal flow, an upstream chemical spill or due to excessive sediment loading from site erosion or extreme runoff events. It is a good practice to inspect the system after major storm events.

Inspection activities are typically conducted from surface observations and include:

- Observe if standing water is present
- Observe if there is any physical damage to the deck or cartridge lids
- Observe the amount of debris in the Maintenance Access Wall (MAW)

Maintenance activities typically include:

- Removal of oil, floatable trash and debris
- Removal of collected sediments
- Rinsing and re-installing the filter cartridges
- Replace filter cartridge tentacles, as needed



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civilitude.com | civilitude.com

## **Inspection:**

### **Inspection Timing**

Inspection of the Jellyfish Filter is key in determining the maintenance requirements for, and to develop a history of the site's pollutant loading characteristics. In general, inspections should be performed at the times indicated below; or per the approved project stormwater quality documents (if applicable), whichever is more frequent.

1. Post-construction inspection is required prior to putting the Jellyfish Filter into service. All construction debris or construction-related sediment within the device must be removed, and any damage to system components repaired, before installing the filter cartridges.
2. A minimum of two inspections during the first year of operation to assess the sediment and floatable pollutant accumulation, and to ensure proper functioning of the system.
3. Inspection frequency in subsequent years is based on the inspection and maintenance plan developed in the first year of operation. Minimum frequency should be once per year.
4. Inspection is recommended after each major storm event.
5. Inspection is required immediately after an upstream oil, fuel or other chemical spill.

### **Inspection Procedure**

The following procedure is recommended when performing inspections:

1. Provide traffic control measures as necessary.
2. Inspect the MAW for floatable pollutants such as trash, debris, and oil sheen.
3. Measure oil and sediment depth in several locations, by lowering a sediment probe through the MAW opening until contact is made with the floor of the structure. Record sediment depth, and presences of any oil layers.
4. Inspect cartridge lids. Missing or damaged cartridge lids to be replaced.
5. Inspect the MAW, cartridge deck, and backwash pool weir, for cracks or broken components. If damaged, repair is required.

### **Dry Weather Inspections**

- Inspect the cartridge deck for standing water, and/or sediment on the deck.
- No standing water under normal operating conditions.
- Standing water inside the backwash pool, but not outside the backwash pool indicates that the filter cartridges need to be rinsed.
- Standing water outside the backwash pool may indicate a backwater condition caused by high water elevation in the receiving water body, or possibly a blockage in downstream infrastructure.
- Any appreciable sediment ( $\geq 1/16''$ ) accumulated on the deck surface should be removed.

### **Wet Weather Inspections**

- Observe the rate and movement of water in the unit. Note the depth of water above deck elevation within the MAW.
- Less than 6 inches, flow should be exiting the cartridge lids of each of the draindown cartridges (i.e. cartridges located outside the backwash pool).
- Greater than 6 inches, flow should be exiting the cartridge lids of each of the draindown cartridges and each of the hi-flo cartridges (i.e. cartridges located inside the backwash pool), and water should be overflowing the backwash pool weir.
- 18 inches or greater and relatively little flow is exiting the cartridge lids and outlet pipe, this condition indicates that the filter cartridges are occluded with sediment and need to be rinsed.

### **Maintenance:**

#### **Maintenance Requirements**

Required maintenance for the Jellyfish Filter is based upon results of the most recent inspection, historical maintenance records, or the site specific water quality management plan; whichever is more frequent. In general, maintenance requires some combination of the following:

1. Sediment removal for depths reaching 12 inches or greater, or within 3 years of the most recent sediment cleaning, whichever occurs sooner.
2. Floatable trash, debris, and oil removal.
3. Deck cleaned and free from sediment.
4. Filter cartridges rinsed and re-installed as required by the most recent inspection results, or within 12 months of the most recent filter rinsing, whichever occurs sooner.
5. Replace tentacles if rinsing does not restore adequate hydraulic capacity, remove accumulated sediment, or if damaged or missing. It is recommended that tentacles should remain in service no longer than 5 years before replacement.
6. Damaged or missing cartridge deck components must be repaired or replaced as indicated by results of the most recent inspection.
7. The unit must be cleaned out and filter cartridges inspected immediately after an upstream oil, fuel, or chemical spill. Filter cartridge tentacles should be replaced if damaged or compromised by the spill.

### **Maintenance Procedure**

The following procedures are recommended when maintaining the Jellyfish Filter:

1. Provide traffic control measures as necessary.
2. Open all covers and hatches. Use ventilation equipment as required, according to confined space entry procedures.
3. Caution: Dropping objects onto the cartridge deck may cause damage.
4. Perform Inspection Procedure prior to maintenance activity.
5. To access the cartridge deck for filter cartridge service, descend the ladder and step directly onto the deck. Caution: Do not step onto the maintenance access wall (MAW) or backwash pool weir, as damage may result. Note that the cartridge deck may be slippery.

6. Maximum weight of maintenance crew and equipment on the cartridge deck not to exceed 450 lbs.

### **Filter Cartridge Removal**

1. Remove a cartridge lid.
2. Remove cartridges from the deck using the lifting loops in the cartridge head plate. Rope or a lifting device (available from Contech) should be used. Caution: Should a snag occur, do not force the cartridge upward as damage to the tentacles may result. Wet cartridges typically weigh between 100 and 125 lbs.
3. Replace and secure the cartridge lid on the exposed empty receptacle as a safety precaution. Contech does not recommend exposing more than one empty cartridge receptacle at a time.

### **Filter Cartridge Rinsing**

1. Remove all 11 tentacles from the cartridge head plate. Take care not to damage or break the plastic threaded nut or connector.
2. Position tentacles in a container (or over the MAW), with the threaded connector (open end) facing down, so rinse water is flushed through the membrane and captured in the container.
3. Using the Jellyfish rinse tool (available from Contech) or a low-pressure garden hose sprayer, direct water spray onto the tentacle membrane, sweeping from top to bottom along the length of the tentacle. Rinse until all sediment is removed from the membrane. Caution: Do not use a high pressure sprayer or focused stream of water on the membrane. Excessive water pressure may damage the membrane.
4. Collected rinse water is typically removed by vacuum hose.
5. Reattach tentacles to cartridge head plate. Reuse O-rings and nuts, ensuring proper placement on each tentacle.

### **Cleaning Procedure**

1. Perform vacuum cleaning of the Jellyfish Filter only after filter cartridges have been removed from the system. Access the lower chamber for vacuum cleaning only through the maintenance access wall (MAW) opening, being careful not to damage the flexible plastic separator skirt that is attached to the underside of the deck. The separator skirt surrounds the filter cartridge zone, and could be torn if contacted by the wand. Do not lower the vacuum wand through a cartridge receptacle, as damage to the receptacle will result.
2. Vacuum floatable trash, debris, and oil, from the MAW opening. Alternatively, floatable solids may be removed by a net or skimmer.
3. Pressure wash cartridge deck and receptacles to remove all sediment and debris. Sediment should be rinsed into the sump area. Take care not to flush rinse water into the outlet pipe.
4. Remove water from the sump area. Vacuum or pump equipment should only be introduced through the MAW.
5. Remove the sediment from the bottom of the unit through the MAW opening.
6. For larger diameter Jellyfish Filter manholes ( $\geq 8$ -ft) and vaults without an MAW opening, complete sediment removal may be facilitated by removing a cartridge lid from an empty receptacle and inserting a jetting wand (not a vacuum wand) through the receptacle. Use the sprayer to rinse loosened sediment toward the vacuum hose in the MAW opening, being careful not to damage the receptacle.
7. After the unit is clean, re-fill the lower chamber with water if required by the local jurisdiction, and re-install filter cartridges.
8. Dispose of sediment, floatable trash and debris, oil, spent tentacles, and water according to local regulatory requirements.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

### **Chemical Spills**

Caution: If a chemical spill has been captured, do not attempt maintenance. Immediately contact the local hazard response agency and contact Contech.

### **Related Maintenance Activities**

Jellyfish units are often just one of many structures in a more comprehensive stormwater drainage and treatment system.

In order for maintenance of the Jellyfish filter to be successful, it is imperative that all other components be properly maintained. The maintenance and repair of upstream facilities should be carried out prior to Jellyfish maintenance activities.

In addition to considering upstream facilities, it is also important to correct any problems identified in the drainage area. Drainage area concerns may include: erosion problems, heavy oil loading, and discharges of inappropriate materials.

### **Material Disposal**

The accumulated sediment found in stormwater treatment and conveyance systems must be handled and disposed of in accordance with regulatory protocols. It is possible for sediments to contain measurable concentrations of heavy metals and organic chemicals (such as pesticides and petroleum products). Areas with the greatest potential for high pollutant loading include industrial areas and heavily traveled roads. Sediments and water must be disposed of in accordance with all applicable waste disposal regulations. When scheduling maintenance, consideration must be made for the disposal of solid and liquid wastes. This typically requires coordination with a local landfill for solid waste disposal. For liquid waste disposal a number of options are available including a municipal vacuum truck decant facility, local waste water treatment plant or on-site treatment and discharge.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

## **Repair:**

### **Filter Cartridge Replacement**

1. Cartridges should be installed after the deck has been cleaned. It is important that the receptacle surfaces be free from grit and debris.
2. If rinsing is ineffective in removing sediment from the tentacles, or if tentacles are damaged, provisions must be made to replace the spent or damaged tentacles with new tentacles. Contact Contech to order replacement tentacles.
3. Lower filter cartridge to the cartridge deck. Remove cartridge lid from deck and carefully lower the filter cartridge into the receptacle until head plate gasket is seated squarely in receptacle. Caution: Should a snag occur when lowering the cartridge into the receptacle, do not force the cartridge downward; damage may occur.
4. Replace the cartridge lid and check fit before completing rotation to a firm hand-tight attachment.

### **If necessary, Retrofit:**

Not necessary.

### **Record Keeping Procedures:**

Project superintendent shall have a log for entering site inspections. Results of inspections, including damage and any recommended remedial action, shall be noted along with inspection personnel data and date of completion of any action.



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

10-06-2025



*Jordan L. Miller*

Jordan Miller  
PE #124884

Engineer who designed the permanent BMPs and measures: \_\_\_\_\_

An amended copy of this document will be provided to TCEQ within thirty (30) days of any changes in the following information:

Owner or responsible party: Laura Skandera Trombley

Address: 1001 E. University Ave., Georgetown, TX 78626

Telephone: 512.863.1454

Signature of Responsible Party: \_\_\_\_\_



Texas P.E. Firm Registration 12469  
503 Kenniston Dr, Unit 5 Austin, TX 78752  
Phone 512.761.6161 | Fax 512.761.6167  
info@civiltitude.com | civiltitude.com

**Permanent Stormwater Section (TCEQ-0600)  
Attachment H**

**Pilot Scale Field Testing Plan**

The TCEQ Technical Guidance Manual (TGM) was used to design the ponds for the regulated entity, therefore a Pilot Scale Field Testing Plan has not been provided.

**Permanent Stormwater Section (TCEQ-0600)  
Attachment I**

**Measures for Minimizing Surface Stream Contamination**

Drainage facilities have been designed to capture storm water runoff from proposed developments and direct the flows to one of two on-site storm water detention ponds. These ponds have been design to reduce peak flow rates discharging downstream. Reduced peak flow rates will result in lower velocities for storm water entering surface streams, thereby reducing the potential for erosion. These ponds will receive and detain treated storm water from the Contech Jellyfish Storm Water Treatment Filters directly upstream.

**Agent Authorization Form**  
For Required Signature  
Edwards Aquifer Protection Program  
Relating to 30 TAC Chapter 213  
Effective June 1, 1999

I Laura Skandera Trombley  
Print Name

President  
Title - Owner/President/Other

of Southwestern University  
Corporation/Partnership/Entity Name

have authorized Civiltude, LLC, C/O Gerardo Martinez  
Print Name of Agent/Engineer

of Civiltude, LLC  
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

Laura Tombley  
Applicant's Signature

9-16-2025  
Date

THE STATE OF Texas §

County of Williamson §


BEFORE ME, the undersigned authority, on this day personally appeared Laura Tombley known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 16th day of Sept., 2025.

Latoya E. Jenkins  
NOTARY PUBLIC

Latoya E. Jenkins  
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 11-26-2026



# Application Fee Form

## Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: Southwestern University 560 Development Phase 1

Regulated Entity Location: 1001 E University Ave, Georgetown, TX 78626

Name of Customer: Richard Madonna

Contact Person: Jordan Miller, P.E.

Phone: (512) 761-6161

Customer Reference Number (if issued): CN 600787329

Regulated Entity Reference Number (if issued): RN \_\_\_\_\_

### Austin Regional Office (3373)

Hays

Travis

Williamson

### San Antonio Regional Office (3362)

Bexar

Medina

Uvalde

Comal

Kinney

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to:

Austin Regional Office

San Antonio Regional Office

Mailed to: TCEQ - Cashier

Overnight Delivery to: TCEQ - Cashier

Revenues Section

12100 Park 35 Circle

Mail Code 214

Building A, 3rd Floor

P.O. Box 13088

Austin, TX 78753

Austin, TX 78711-3088

(512)239-0357


### Site Location (Check All That Apply):

Recharge Zone

Contributing Zone

Transition Zone

<i>Type of Plan</i>	<i>Size</i>	<i>Fee Due</i>
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	68.77 Acres	\$ 8,000
Sewage Collection System	3,097 L.F.	\$ 1,548.50
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: 

Date: 08/20/2025

# Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

## ***Water Pollution Abatement Plans and Modifications***

### ***Contributing Zone Plans and Modifications***

<b><i>Project</i></b>	<b><i>Project Area in Acres</i></b>	<b><i>Fee</i></b>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

### ***Organized Sewage Collection Systems and Modifications***

<b><i>Project</i></b>	<b><i>Cost per Linear Foot</i></b>	<b><i>Minimum Fee- Maximum Fee</i></b>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

### ***Underground and Aboveground Storage Tank System Facility Plans and Modifications***

<b><i>Project</i></b>	<b><i>Cost per Tank or Piping System</i></b>	<b><i>Minimum Fee- Maximum Fee</i></b>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

### ***Exception Requests***

<b><i>Project</i></b>	<b><i>Fee</i></b>
Exception Request	\$500

### ***Extension of Time Requests***

<b><i>Project</i></b>	<b><i>Fee</i></b>
Extension of Time Request	\$150



# TCEQ Core Data Form

For detailed instructions on completing this form, please read the Core Data Form Instructions or call 512-239-5175.

## SECTION I: General Information

<b>1. Reason for Submission</b> (If other is checked please describe in space provided.)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input type="checkbox"/> Other	
<b>2. Customer Reference Number</b> (if issued)	<a href="#">Follow this link to search for CN or RN numbers in Central Registry**</a>	<b>3. Regulated Entity Reference Number</b> (if issued)
CN 600787329		RN

## SECTION II: Customer Information

<b>4. General Customer Information</b>		<b>5. Effective Date for Customer Information Updates</b> (mm/dd/yyyy)		10/1/2025	
<input type="checkbox"/> New Customer		<input checked="" type="checkbox"/> Update to Customer Information		<input type="checkbox"/> Change in Regulated Entity Ownership	
<input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)					
<i>The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).</i>					
<b>6. Customer Legal Name</b> (If an individual, print last name first: eg: Doe, John)			<i>If new Customer, enter previous Customer below:</i>		
Southwestern University					
<b>7. TX SOS/CPA Filing Number</b>		<b>8. TX State Tax ID</b> (11 digits)		<b>9. Federal Tax ID</b>	<b>10. DUNS Number</b> (if applicable)
0033266101		17412337960		(9 digits)	
<b>11. Type of Customer:</b>		<input checked="" type="checkbox"/> Corporation		<input type="checkbox"/> Individual	
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> Local <input type="checkbox"/> State <input type="checkbox"/> Other		<input type="checkbox"/> Sole Proprietorship		Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited	
<b>12. Number of Employees</b>				<b>13. Independently Owned and Operated?</b>	
<input type="checkbox"/> 0-20 <input type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input checked="" type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher				<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
<b>14. Customer Role</b> (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following					
<input checked="" type="checkbox"/> Owner		<input type="checkbox"/> Operator		<input checked="" type="checkbox"/> Owner & Operator	
<input type="checkbox"/> Occupational Licensee		<input type="checkbox"/> Responsible Party		<input type="checkbox"/> VCP/BSA Applicant	
<input type="checkbox"/> Other:					
<b>15. Mailing Address:</b>	1001 E University Avenue				
City	Georgetown	State	TX	ZIP	78626
ZIP + 4					
<b>16. Country Mailing Information</b> (if outside USA)			<b>17. E-Mail Address</b> (if applicable)		

<b>18. Telephone Number</b>	<b>19. Extension or Code</b>	<b>20. Fax Number (if applicable)</b>
( ) -		( ) -

### **SECTION III: Regulated Entity Information**

<b>21. General Regulated Entity Information</b> (If 'New Regulated Entity' is selected, a new permit application is also required.)								
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information								
<i>The Regulated Entity Name submitted may be updated, in order to meet TCEQ Core Data Standards (removal of organizational endings such as Inc, LP, or LLC).</i>								
<b>22. Regulated Entity Name</b> (Enter name of the site where the regulated action is taking place.)								
Southwestern University 560 Development Phase 1								
<b>23. Street Address of the Regulated Entity:</b>  (No PO Boxes)	1001 E University Avenue							
	<b>City</b>	Georgetown	<b>State</b>	TX	<b>ZIP</b>	78626	<b>ZIP + 4</b>	
<b>24. County</b>	Williamson							

If no Street Address is provided, fields 25-28 are required.

<b>25. Description to Physical Location:</b>	Williamson County parcel ID: R393536										
<b>26. Nearest City</b>					<b>State</b>				<b>Nearest ZIP Code</b>		
<i>Latitude/Longitude are required and may be added/updated to meet TCEQ Core Data Standards. (Geocoding of the Physical Address may be used to supply coordinates where none have been provided or to gain accuracy).</i>											
<b>27. Latitude (N) In Decimal:</b>						<b>28. Longitude (W) In Decimal:</b>					
Degrees	Minutes		Seconds		Degrees	Minutes		Seconds			
<b>29. Primary SIC Code</b>	<b>30. Secondary SIC Code</b>		<b>31. Primary NAICS Code</b>			<b>32. Secondary NAICS Code</b>					
(4 digits)	(4 digits)		(5 or 6 digits)			(5 or 6 digits)					
8221											
<b>33. What is the Primary Business of this entity?</b> (Do not repeat the SIC or NAICS description.)											
Subdivision Infrastructure											
<b>34. Mailing Address:</b>	1001 E University Avenue										
	<b>City</b>	Geogetown	<b>State</b>	TX	<b>ZIP</b>	78626	<b>ZIP + 4</b>				
<b>35. E-Mail Address:</b>											
<b>36. Telephone Number</b>	<b>37. Extension or Code</b>			<b>38. Fax Number (if applicable)</b>							
( ) -				( ) -							

**39. TCEQ Programs and ID Numbers** Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.


<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input checked="" type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Wastewater	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

**SECTION IV: Preparer Information**

<b>40. Name:</b>	Ali Al-Zoubi, E.I.T	<b>41. Title:</b>	Graduate Engineer
<b>42. Telephone Number</b>	<b>43. Ext./Code</b>	<b>44. Fax Number</b>	<b>45. E-Mail Address</b>
( 737 ) 351-2013		( ) -	ali@civiltitude.com

**SECTION V: Authorized Signature**

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

<b>Company:</b>	Civiltitude LLC	<b>Job Title:</b>	Lead Engineer
<b>Name (In Print):</b>	Jordan Miller	<b>Phone:</b>	( 512 ) 761- 6161
<b>Signature:</b>		<b>Date:</b>	10/03/2025










LINE #	DIRECTION	LENGTH
L1	N21°04'29"W	75.00'
L2	S68°55'31"W	100.00'
L3	N51°30'23"W	85.84'
L4	N42°32'02"W	124.49'
L5	N32°15'06"W	173.82'
L6	N02°35'22"W	105.98'
L7	N11°16'53"E	51.97'
L8	N13°38'23"E	73.47'
L9	N03°04'37"E	51.24'
L10	N13°19'40"W	72.10'
L11	N31°00'39"W	135.95'
L12	N44°16'00"W	85.61'
L13	N53°22'14"W	78.62'
L14	N61°06'26"E	47.21'
L15	N79°51'53"E	54.83'
L16	S61°06'26"W	60.69'
L17	S79°58'41"W	67.96'
L18	N61°05'15"E	105.87'
L19	S21°04'29"E	75.00'

- NOTES:
- EXISTING CONDITIONS SURVEY PREPARED BY STEGER BIZZELL - ISSUED 10-14-2024.
  - WHERE TREE PROTECTION FENCING CANNOT BE INSTALLED AROUND THE FULL CRZ, PLACE FENCING AT THE 1/2 CRZ AND ADD 8" OF HARDWOOD MULCH FROM THE 1/2 CRZ TO THE FULL CRZ.
  - THE SIZE AND LOCATION OF UTILITY STRUCTURES, (IF SHOWN), MAY BE EXAGGERATED FOR GRAPHICAL CLARITY. THE SURVEY SHOWS FIELD MEASURED SIZES AND DEPTHS AS OBSERVED FROM GROUND LEVEL OPENINGS.
  - THIS PLAN WAS PREPARED WITHOUT THE BENEFIT OF A DESIGN SURVEY. UTILITIES SHOWN WERE LOCATED USING CITY MAPS. LOCATIONS OF EXISTING UTILITIES, SOME OF WHICH MAY NOT BE SHOWN, COULD IMPACT CONSTRUCTION MEANS AND METHODS.
  - GAS MAIN SIZE TO BE VERIFIED WITH ATMOS ENERGIY

**LEGEND**

- BOUNDARY / RIGHT OF WAY
- EASEMENT / SETBACK
- EXISTING CONTOUR LINE
- CURB / EDGE OF PAVEMENT
- EXISTING BUILDING
- STORM DRAIN LINE
- WATER LINE
- WASTEWATER LINE
- OVERHEAD ELECTRIC
- GAS LINE
- FORCEMAIN LINE
- FLOODPLAIN
- FEMA FLOODPLAIN-100-YR
- FEMA FLOODPLAIN-500-YR
- ATLAS 14 FLOODPLAIN-100-YR
- CREEK CENTERLINE
- WATER METER
- WATER VALVE
- FIRE HYDRANT
- WASTEWATER MANHOLE
- WASTEWATER CLEANOUT
- BACKFLOW PREVENTER
- STORM DRAIN MANHOLE
- STORM DRAIN CURB INLET
- STORM DRAIN AREA INLET
- TRANSFORMER
- AIR CONDITIONER UNIT
- GAS METER
- ELECTRIC MANHOLE
- ELECTRIC BOX
- UTILITY POLE
- GUY WIRE
- SIGN
- SURVEY ROD/NAIL
- BENCHMARK
- TAG# TREE W/ TAG
- TAG# TREE - REMOVE
- TAG# HERITAGE TREE W/TAG
- TAG# PROTECTED TREE W/TAG
- SPRING BUFFER
- DEMOLITION AREA



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 75626

**OVERALL EXISTING CONDITIONS  
& DEMOLITION PLAN**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
**004**  
OF 069

Plot Date: September 19, 2025 @ 3:36 PM



**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	BENCHMARK
	SURVEY ROD/NAIL
	TAG#
	TREE W/ TAG
	TAG#
	TREE - REMOVE
	TREE PROTECTION FENCE
	MULCH SOCK
	LIMIT OF CONSTRUCTION
	SILT FENCE
	FILTER DIKE
	FLOODPLAIN
	FEMA FLOODPLAIN-100-YR
	FEMA FLOODPLAIN-500-YR
	ATLAS 14 FLOODPLAIN-100-YR
	CREEK CENTERLINE
	ROCK BERM
	POND SKIMMER
	STABILIZED CONSTRUCTION ENTRANCE
	PUBLIC OPEN SPACE

- NOTES:**
- LIMITS OF CONSTRUCTION: ±40 ACRES
  - IF DISTURBED AREA IS NOT TO BE WORKED ON FOR MORE THAN 14 DAYS, DISTURBED AREA NEEDS TO BE STABILIZED BY REVEGETATION, MULCH, TARP OR REVEGETATION MATTING.
  - ENVIRONMENTAL INSPECTOR HAS THE AUTHORITY TO ADD AND/OR MODIFY EROSION/SEDIMENTATION CONTROLS ON SITE TO KEEP PROJECT IN COMPLIANCE WITH THE CITY OF AUSTIN RULES AND REGULATIONS
  - CONTRACTOR SHALL UTILIZE DUST CONTROL MEASURES DURING SITE CONSTRUCTION SUCH AS IRRIGATION TRUCKS AND MULCHING AS PER ECM 1.4.5(A), OR AS DIRECTED BY THE ENVIRONMENTAL INSPECTOR.
  - THE CONTRACTOR WILL CLEAN UP SPOILS THAT MIGRATE ONTO THE ROADS A MINIMUM OF ONCE DAILY.
  - WHERE TREE PROTECTION FENCING CANNOT BE INSTALLED AROUND THE FULL CRZ, PLACE FENCING AT THE 1/2 CRZ AND ADD 8" OF HARDWOOD MULCH FROM THE 1/2 CRZ TO THE FULL CRZ.
  - SEE EXISTING CONDITIONS SHEET FOR TREE SURVEY.
  - CONTRACTOR MUST PICK UP AND DISPOSE OF ALL SEDIMENT CONTROLS, INCLUDING SILT FENCE, ONCE PERMANENT EROSION CONTROLS MEASURES ARE ESTABLISHED.



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**OVERALL EROSION CONTROL & TREE PRESERVATION PLAN**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR

**SHEET NO. 005**  
OF 069

Plot Date: September 19, 2025 @ 3:37 PM

TREE LIST	
TAG #	Description
2001	10in CEDAR ELM
2002	9in CEDAR ELM
2003	9in CEDAR ELM
2004	9in CEDAR ELM
2005	12in (P) CEDAR ELM
2006	9in CEDAR ELM
2007	12in (P) CEDAR ELM
2008	10in CEDAR ELM
2009	10in CEDAR ELM
2010	10in CEDAR ELM
2011	12in (P) CEDAR ELM
2012	9in (M) CEDAR ELM
2013	8in CEDAR ELM
2014	10in CEDAR ELM
2015	10in (M) CEDAR ELM
2016	8in CEDAR ELM
2017	8in (M) CEDAR ELM
2018	11in (M) CEDAR ELM
2019	8in CEDAR ELM
2020	11in (M) CEDAR ELM
2021	11in (M) CEDAR ELM
2022	8in CEDAR ELM
2023	10in (M) CEDAR ELM
2024	9in (M) CEDAR ELM
2025	10in (M) CEDAR ELM
2026	8in CEDAR ELM
2027	10in (M) CEDAR ELM
2028	9in CEDAR ELM
2029	9in CEDAR ELM
2030	11in (M) CEDAR ELM
2031	9in CEDAR ELM
2032	11in CEDAR ELM
2033	9in CEDAR ELM
2034	8in CEDAR ELM
2035	8in CEDAR ELM
2036	8in CEDAR ELM
2037	10in CEDAR ELM
2038	14in (M)(P) CEDAR ELM
2039	10in CEDAR ELM
2040	12in (P) CEDAR ELM
2041	14in (P) MESQUITE
2042	20in (P) CEDAR ELM
2043	14in (P) CEDAR ELM
2044	10in CEDAR ELM
2045	9in CEDAR ELM
2046	12in (P) CEDAR ELM
2047	13in (P) CEDAR ELM
2048	19in (M)(P) CEDAR ELM
2049	17in (M)(P) CEDAR ELM
2050	16in (M)(P) CEDAR ELM
2051	12in (M)(P) CEDAR ELM
2052	13in (M)(P) CEDAR ELM
2053	10in (M) CEDAR ELM
2054	12in (M)(P) CEDAR ELM
2055	9in (M) CEDAR ELM
2056	13in (M)(P) CEDAR ELM
2057	8in CEDAR ELM
2058	12in (P) CEDAR ELM
2059	9in CEDAR ELM
2060	9in CEDAR ELM

TREE LIST	
TAG #	Description
2061	12in (P) CEDAR ELM
2062	21in (M)(P) CEDAR ELM
2063	9in CEDAR ELM
2064	9in CEDAR ELM
2065	19in (P) CEDAR ELM
2066	15in (P) CEDAR ELM
2067	11in CEDAR ELM
2068	13in (M)(P) CEDAR ELM
2069	11in (M) CEDAR ELM
2070	8in (M) CEDAR ELM
2071	9in CEDAR ELM
2072	8in CEDAR ELM
2073	12in (P) CEDAR ELM
2074	9in CEDAR ELM
2075	12in (P) CEDAR ELM
2076	13in (P) CEDAR ELM
2077	10in (M) CEDAR ELM
2078	12in (M)(P) CEDAR ELM
2079	10in CEDAR ELM
2080	9in CEDAR ELM
2081	76in (M)(H) CEDAR ELM
2082	9in CEDAR ELM
2083	10in CEDAR ELM
2084	17in (M)(P) CEDAR ELM
2085	12in (P) CEDAR ELM
2086	9in CEDAR ELM
2087	10in CEDAR ELM
2088	12in (P) CEDAR ELM
2089	10in CEDAR ELM
2090	13in (M)(P) CEDAR ELM
2091	9in CEDAR ELM
2092	16in (M)(P) CEDAR ELM
2093	8in CEDAR ELM
2094	22in (M)(P) CEDAR ELM
2095	8in CEDAR ELM
2096	8in CEDAR ELM
2097	8in CEDAR ELM
2098	8in CEDAR ELM
2099	10in CEDAR ELM
2100	9in (M) CEDAR ELM
2101	11in CEDAR ELM
2102	12in (P) CEDAR ELM
2103	13in (P) CEDAR ELM
2104	13in (P) LIVE OAK
2105	9in (M) CEDAR ELM
2106	10in CEDAR ELM
2107	10in CEDAR ELM
2108	13in (P) CEDAR ELM
2109	27in (H) CEDAR ELM DISTRESSED
2110	10in CEDAR ELM
2111	10in (M) CEDAR ELM
2112	13in (M)(P) CEDAR ELM
2113	9in CEDAR ELM
2114	10in (M) CEDAR ELM
2115	15in (M)(P) CEDAR ELM
2116	13in (P) CEDAR ELM
2117	16in (P) CEDAR ELM
2118	22in (P) CEDAR ELM DISTRESSED
2119	21in (P) CEDAR ELM
2120	10in CEDAR ELM

TREE LIST	
TAG #	Description
2121	12in (P) CEDAR ELM
2122	12in (P) CEDAR ELM
2123	12in (P) CEDAR ELM
2124	11in CEDAR ELM
2125	11in CEDAR ELM
2126	11in (M) CEDAR ELM
2127	9in CEDAR ELM
2128	9in CEDAR ELM
2129	14in (M)(P) CEDAR ELM
2130	15in (M)(P) CEDAR ELM
2131	36in (M)(H) CEDAR ELM
2132	11in (M) CEDAR ELM
2133	14in (P) CEDAR ELM
2134	9in CEDAR ELM
2135	11in (M) CEDAR ELM
2136	15in (P) CEDAR ELM
2137	8in CEDAR ELM
2138	11in CEDAR ELM
2139	10in (M) CEDAR ELM
2140	10in (M) CEDAR ELM
2141	10in CEDAR ELM
2142	10in CEDAR ELM
2143	9in CEDAR ELM
2144	13in (P) CEDAR ELM
2145	13in (P) CEDAR ELM
2146	9in (M) CEDAR ELM
2147	8in CEDAR ELM
2148	11in CEDAR ELM
2149	18in (M)(P) CEDAR ELM
2150	13in (P) CEDAR ELM
2151	12in (M)(P) CEDAR ELM
2152	13in (P) CEDAR ELM
2153	15in (P) CEDAR ELM
2154	9in (M) CEDAR ELM
2155	8in CEDAR ELM
2156	18in (M)(P) CEDAR ELM
2157	11in (M) CEDAR ELM
2158	8in CEDAR ELM
2159	16in (M)(P) CEDAR ELM
2160	17in (P) CEDAR ELM
2161	9in CEDAR ELM
2162	8in (M) CEDAR ELM
2163	8in MESQUITE
2164	10in CEDAR ELM
2165	11in (M) CEDAR ELM
2166	13in (P) CEDAR ELM
2167	11in (M) CEDAR ELM
2168	13in (M)(P) CEDAR ELM
2169	18in (M)(P) CEDAR ELM
2170	8in CEDAR ELM
2171	8in CEDAR ELM
2172	8in CEDAR ELM
2173	9in CEDAR ELM
2174	8in CEDAR ELM
2175	12in CEDAR ELM
2176	12in (M)(P) CEDAR ELM
2177	12in (M)(P) CEDAR ELM
2178	8in CEDAR ELM
2179	10in CEDAR ELM
2180	11in (M) CEDAR ELM

TREE LIST	
TAG #	Description
2181	8in CEDAR ELM
2182	10in GUM BUMELIA
2183	10in (P) CEDAR ELM
2184	13in (P) CEDAR ELM
2185	8in CEDAR ELM
2186	15in (M)(P) MESQUITE
2187	9in CEDAR ELM
2188	10in LIVE OAK
2189	9in CEDAR ELM
2190	11in (M) CEDAR ELM
2191	11in LIVE OAK
2192	9in CEDAR ELM
2193	8in CEDAR ELM
2194	11in CEDAR ELM
2195	11in CEDAR ELM
2196	11in (M) CEDAR ELM
2197	9in CEDAR ELM
2198	9in LIVE OAK
2199	9in CEDAR ELM
2200	12in (M)(P) CEDAR ELM
2201	19in (M)(P) CEDAR ELM
2202	8in CEDAR ELM
2203	15in (P) LIVE OAK
2204	9in (M) CEDAR ELM
2205	9in CEDAR ELM
2206	8in CEDAR ELM
2207	9in CEDAR ELM
2208	10in GUM BUMELIA
2209	8in CEDAR ELM
2210	8in CEDAR ELM
2211	11in CEDAR ELM
2212	10in CEDAR ELM
2213	16in (M)(P) GUM BUMELIA
2214	9in (M) CEDAR ELM
2215	12in (M)(P) GUM BUMELIA
2216	10in CEDAR ELM
2217	8in CEDAR ELM
2218	11in (M) CEDAR ELM
2219	9in CEDAR ELM
2220	16in (P) CEDAR ELM
2221	9in CEDAR ELM
2222	8in CEDAR ELM
2223	10in CEDAR ELM
2224	8in CEDAR ELM
2225	8in AMERICAN ELM
2226	10in AMERICAN ELM
2227	8in AMERICAN ELM
2228	11in AMERICAN ELM
2229	8in (M) AMERICAN ELM
2230	10in (M) AMERICAN ELM
2231	9in (M) LIVE OAK
2232	9in LIVE OAK
2233	14in (M)(P) CEDAR ELM
2234	8in LIVE OAK
2235	9in LIVE OAK
2236	9in CEDAR ELM
2237	12in (P) CEDAR ELM
2238	10in CEDAR ELM
2239	10in CEDAR ELM
2240	9in CEDAR ELM

TREE LIST	
TAG #	Description
2241	11in CEDAR ELM
2242	10in CEDAR ELM
2243	8in CEDAR ELM
2244	13in (P) CEDAR ELM
2245	14in (M) (P) CEDAR ELM
2246	12in (P) CEDAR ELM
2247	8in CEDAR ELM
2248	9in (M) CEDAR ELM
2249	10in (M) CEDAR ELM
2250	9in CEDAR ELM
2251	12in (M)(P) CEDAR ELM
2252	9in CEDAR ELM
2253	10in GUM BUMELIA
2254	10in (M) GUM BUMELIA
2255	8in GUM BUMELIA
2256	9in (M) GUM BUMELIA
2257	12in (P) CEDAR ELM
2258	8in CEDAR ELM
2259	12in (P) CEDAR ELM
2260	13in (P) GUM BUMELIA
2261	12in (P) CEDAR ELM
2262	9in CEDAR ELM
2263	9in CEDAR ELM
2264	9in (M) CEDAR ELM
2265	9in CEDAR ELM
2266	12in (P) CEDAR ELM
2267	16in (P) CEDAR ELM
2268	11in CEDAR ELM
2269	14in (M)(P) CEDAR ELM
2270	10in CEDAR ELM
2271	11in CEDAR ELM
2272	11in CEDAR ELM
2273	11in (M) CEDAR ELM
2274	12in (M)(P) CEDAR ELM
2275	11in CEDAR ELM
2276	9in CEDAR ELM
2277	12in (P) CEDAR ELM
2278	9in CEDAR ELM
2279	8in CEDAR ELM
2280	9in CEDAR ELM
2281	10in CEDAR ELM
2282	13in (P) CEDAR ELM
2283	8in CEDAR ELM
2284	9in CEDAR ELM
2285	23in (M)(P) CEDAR ELM
2286	13in (P) CEDAR ELM
2287	8in CEDAR ELM
2288	10in (M) CEDAR ELM
2289	15in (M)(P) CEDAR ELM
2290	8in (M) CEDAR ELM
2291	12in (P) CEDAR ELM
2292	9in (M) CEDAR ELM
2293	9in CEDAR ELM
2294	8in GUM BUMELIA
2295	8in CEDAR ELM
2296	9in GUM BUMELIA
2297	9in CEDAR ELM
2298	9in CEDAR ELM
2299	8in CEDAR ELM
2300	10in CEDAR ELM

TREE LIST	
TAG #	Description
2301	10in CEDAR ELM
2302	10in CEDAR ELM
2303	11in CEDAR ELM
2304	8in CEDAR ELM
2305	11in CEDAR ELM
2306	9in CEDAR ELM
2307	15in (P) CEDAR ELM
2308	9in (M) CEDAR ELM
2309	12in (P) CEDAR ELM
2310	10in CEDAR ELM
2311	11in GUM BUMELIA
2312	12in (P) GUM BUMELIA
2313	9in GUM BUMELIA
2314	52in (H) LIVE OAK
2315	8in CEDAR ELM
2316	10in GUM BUMELIA
2317	43in (H) LIVE OAK
2318	17in (P) CEDAR ELM
2319	8in CEDAR ELM
2320	37in (M) (H) LIVE OAK
2321	12in (P) LIVE OAK
2322	8in GUM BUMELIA
2323	9in CEDAR ELM
2324	8in CEDAR ELM
2325	9in CEDAR ELM
2326	28in (H) LIVE OAK DISTRESSED
2327	9in TEXAS ASH
2328	9in CEDAR ELM DISTRESSED
2329	9in (M) CEDAR ELM DISTRESSED
2330	8in (M) CEDAR ELM
2331	15in (P) CEDAR ELM
2332	10in CEDAR ELM
2333	8in TEXAS ASH
2334	10in CEDAR ELM
2335	8in CEDAR ELM
2336	8in CEDAR ELM
2337	10in CEDAR ELM
2338	9in CEDAR ELM
2339	9in (M) CEDAR ELM
2340	18in (M)(P) TEXAS ASH
2341	9in CEDAR ELM
2342	9in (M) CEDAR ELM
2343	10in (M) CEDAR ELM
2344	15in (P) CEDAR ELM
2345	15in (P) CEDAR ELM
2346	16in (M)(P) CEDAR ELM
2347	11in CEDAR ELM
2348	9in CEDAR ELM
2349	9in CEDAR ELM
2350	8in CEDAR ELM
2351	8in CEDAR ELM
2352	8in CEDAR ELM DISTRESSED
2353	11in CEDAR ELM
2354	13in (P) CEDAR ELM
2355	11in CEDAR ELM
2356	8in TEXAS ASH
2357	10in (M) CEDAR ELM
2358	8in (M) CEDAR ELM
2359	9in (M) MESQUITE
2360	10in (M) MESQUITE

TREE LIST	
TAG #	Description
2361	13in (M)(P) MESQUITE
2362	20in (M)(P) CEDAR ELM
2363	9in (M) GUM BUMELIA
2364	8in (M) GUM BUMELIA
2365	11in (M) GUM BUMELIA
2366	6in CEDAR ELM
2367	13in (M)(P) CEDAR ELM
2368	8in (M) CEDAR ELM
2369	9in (M) CEDAR ELM
2370	8in (M) CEDAR ELM
2371	9in (M) MESQUITE
2372	9in (M) CEDAR ELM
2373	9in (M) CEDAR ELM
2374	20in (M)(P) MESQUITE
2375	12in (M)(P) MESQUITE
2376	13in (M)(P) MESQUITE
2377	14in (M)(P) MESQUITE
2378	12in (M)(P) GUM BUMELIA
2379	11in CEDAR ELM
2380	12in (M)(P) CEDAR ELM
2381	16in (M)(P) CEDAR ELM
2382	13in (M)(P) CEDAR ELM
2383	21in (M)(P) CEDAR ELM
2384	8in CEDAR ELM
2385	16in (P) CEDAR ELM
2386	9in (M) CEDAR ELM
2387	12in (M)(P) CEDAR ELM
2388	9in (M) CEDAR ELM
2389	14in (M)(P) AMERICAN ELM
2390	9in LIVE OAK
2391	8in LIVE OAK
2392	8in CEDAR ELM
2393	8in AMERICAN ELM
2394	10in AMERICAN ELM
2395	16in (P) AMERICAN ELM
2396	10in CEDAR ELM
2397	8in CEDAR ELM
2398	11in CEDAR ELM
2399	14in (M)(P) CEDAR ELM
2400	10in CEDAR ELM
2401	9in CEDAR ELM
2402	9in (M) CEDAR ELM
2403	8in (M) CEDAR ELM
2404	8in (M) CEDAR ELM
2405	8in (M) CEDAR ELM
2406	9in CEDAR ELM
2407	13in (M)(P) CEDAR ELM
2408	9in CEDAR ELM
2409	9in (M) CEDAR ELM
2410	26in (H) CEDAR ELM
2411	9in (M) CEDAR ELM
2412	12in (P) CEDAR ELM
2413	14in (P) CEDAR ELM
2414	21in (M)(P) WILLOW
2415	11in (M) WILLOW
2416	9in (M) WILLOW
2417	20in (M)(P) WILLOW
2418	12in (P) WILLOW
2419	18in (M)(P) WILLOW
2420	10in WILLOW

TREE LIST	
TAG #	Description
2421	24in (M)(P) WILLOW
2422	18in (M)(P) WILLOW
2423	14in (M)(P) TEXAS ASH
2424	8in CEDAR ELM
2425	17in (M



**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	CURB / EDGE OF PAVEMENT
	ACCESSIBLE ROUTE (ADA)
	FIRE LANE STRIPING
	RETAINING / SCREENING WALL
	BUILDING PAD AREA
	PAVEMENT / ASPHALT
	PAVEMENT / CONCRETE
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	FORCE MAIN LINE
	FLOODPLAIN
	FEMA FLOODPLAIN-100-YR
	FEMA FLOODPLAIN-500-YR
	ATLAS 14 FLOODPLAIN-100-YR
	CREEK CENTERLINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	STORM DRAIN AREA INLET
	TRANSFORMER
	AIR CONDITIONER UNIT
	UTILITY POLE
	GUY WIRE
	DUMPSTER
	SIGN
	BICYCLE RACK
	PARKING BUMPER
	ACCESSIBLE PARKING (ADA)
	CROSSWALK
	SPRING BUFFER




NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626 <b>OVERALL ROADWAY &amp; PAVEMENT PLAN</b>			
<b>CIVILTUDE</b> ENGINEERS & PLANNERS			
503 KENNISTON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	
		FIRM REG # F12469 INFO@CIVILTUDE.COM	
9-19-2025			
JOB NO:	A799		
DN BY:	WS		
DWN BY:	MD,TML		
RV BY:	MVR		
			SHEET NO. <b>007</b> OF 069


Plot Date: September 19, 2025 @ 12:18 PM

LEGEND


-  BOUNDARY / RIGHT OF WAY
-  EASEMENT / SETBACK
-  CURB / EDGE OF PAVEMENT
-  RETAINING / SCREENING WALL
-  PROPOSED BUILDING PAD AREA
-  EXISTING CONTOUR LINE
-  PROPOSED CONTOUR LINE
-  STORM DRAIN LINE
-  OVERHEAD ELECTRIC
-  BARRICADE
-  STORM DRAIN MANHOLE
-  STORM DRAIN CURB INLET
-  STORM DRAIN GRATE INLET
-  WATER METER
-  WATER VALVE
-  FIRE HYDRANT
-  WASTEWATER MANHOLE
-  WASTEWATER CLEANOUT
-  TRANSFORMER
-  UTILITY POLE
-  GUY WIRE
-  TAG# TREE W/ TAG
-  TAG# TREE - REMOVE



PAIDEIA WAY SIGN & STRIPING STA. 1+00 TO 9+00  
SCALE: 1" = 30'




PAIDEIA WAY SIGN & STRIPING STA. 9+00 TO END  
SCALE: 1" = 30'




NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626			
<b>PAIDEIA WAY SIGN &amp; STRIPING PLAN</b>			
 <b>CIVILTUDE</b> ENGINEERS & PLANNERS		503 KENNISTON DR #4    AUSTIN, TX 78752    FIRM REG # F12469 PHONE 512 761 6161    FAX 512 761 6167    INFO@CIVILTUDE.COM	
JOB NO: A799 DGN BY: WS DWN BY: MD,TML RVW BY: MVR		9-19-2025  JORDAN L. MILLER 124884 LICENSED PROFESSIONAL ENGINEER	
SHEET NO. <b>008</b> OF 069			

Plot Date: September 19, 2025 @ 12:20 PM





GOLDEN POPPY DR. SIGN & STRIPING STA. 1+00 TO 7+50  
SCALE: 1" = 30'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - EASEMENT / SETBACK
  - CURB / EDGE OF PAVEMENT
  - RETAINING / SCREENING WALL
  - PROPOSED BUILDING PAD AREA
  - EXISTING CONTOUR LINE
  - PROPOSED CONTOUR LINE
  - STORM DRAIN LINE
  - OVERHEAD ELECTRIC
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - STORM DRAIN GRATE INLET
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - TRANSFORMER
  - UTILITY POLE
  - GUY WIRE
  - TAG# TREE W/ TAG
  - TAG# TREE - REMOVE




GOLDEN POPPY DR. SIGN & STRIPING STA. 7+50 TO END  
SCALE: 1" = 30'




NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  <b>GOLDEN POPPY RD SIGN &amp; STRIPING PLAN</b>			
<b>CIVILITUDE</b> ENGINEERS & PLANNERS			
503 KENNISTON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	
		FIRM REG # F12469 INFO@CIVILITUDE.COM	
JOB NO: A799 DGN BY: WS DWN BY: MD,TML RVW BY: MVR		9-19-2025 	
			SHEET NO. <b>009</b> OF 069


Plot Date: September 19, 2025 @ 12:21 PM





STORY TREE LANE SIGN & STRIPING STA. 1+00 TO 5+50  
SCALE: 1" = 30'



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - EASEMENT / SETBACK
  - CURB / EDGE OF PAVEMENT
  - RETAINING / SCREENING WALL
  - PROPOSED BUILDING PAD AREA
  - EXISTING CONTOUR LINE
  - PROPOSED CONTOUR LINE
  - STORM DRAIN LINE
  - OVERHEAD ELECTRIC
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - STORM DRAIN GRATE INLET
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - TRANSFORMER
  - UTILITY POLE
  - GUY WIRE
  - TAG# TREE W/ TAG
  - TAG# TREE - REMOVE



STORY TREE LANE SIGN & STRIPING STA. 5+50 TO END  
SCALE: 1" = 30'



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**STORY TREE LANE SIGN & STRIPING PLAN**


**CIVILITUDE**  
ENGINEERS & PLANNERS  
503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER


SHEET NO.  
**010**  
OF 069

Plot Date: September 19, 2025 @ 12:22 PM




PAIDEIA WAY STA. 1+00 TO 8+00 - PLAN VIEW  
SCALE: 1" = 30'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - CURB / EDGE OF PAVEMENT
  - RETAINING / SCREENING WALL
  - ▭ PROPOSED BUILDING PAD AREA
  - - - 512 EXISTING CONTOUR LINE
  - - - 512 PROPOSED CONTOUR LINE
  - SD --- SD STORM DRAIN LINE
  - OH --- OVERHEAD ELECTRIC
  - BARRICADE
  - ⊙ STORM DRAIN MANHOLE
  - ⊙ STORM DRAIN CURB INLET
  - ⊙ STORM DRAIN GRATE INLET
  - ⊙ WATER METER
  - ⊙ WATER VALVE
  - ⊙ FIRE HYDRANT
  - ⊙ WASTEWATER MANHOLE
  - ⊙ WASTEWATER CLEANOUT
  - ⊙ CO
  - ⊙ TRANSFORMER
  - ⊙ UTILITY POLE
  - ⊙ GUY WIRE
  - TAG#
  - TREE W/ TAG
  - TAG#
  - TREE - REMOVE



PAIDEIA WAY STA. 1+00 TO 8+00 - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 30' VERTICAL SCALE: 1" = 3'




NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**PAIDEIA WAY PLAN & PROFILE**  
STA. 1+00 TO 8+00

**CIVILITUDE**  
ENGINEERS & PLANNERS  
503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025  
JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR  
  
SHEET NO. **011**  
OF 069





Plot Date: September 19, 2025 @ 12:26 PM



PAIDEIA WAY STA. 8+00 TO END - PLAN VIEW  
SCALE: 1" = 30'

**LEGEND**

- BOUNDARY / RIGHT OF WAY
- EASEMENT / SETBACK
- CURB / EDGE OF PAVEMENT
- RETAINING / SCREENING WALL
- PROPOSED BUILDING PAD AREA
- EXISTING CONTOUR LINE
- PROPOSED CONTOUR LINE
- STORM DRAIN LINE
- OVERHEAD ELECTRIC
- STORM DRAIN MANHOLE
- STORM DRAIN CURB INLET
- STORM DRAIN GRATE INLET
- WATER METER
- WATER VALVE
- FIRE HYDRANT
- WASTEWATER MANHOLE
- WASTEWATER CLEANOUT
- TRANSFORMER
- UTILITY POLE
- GUY WIRE
- TREE W/ TAG
- TREE - REMOVE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**PAIDEIA WAY PLAN & PROFILE**  
STA. 8+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4    AUSTIN, TX 78752    FIRM REG # F12469  
PHONE 512 761 6161    FAX 512 761 6167    INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR


SHEET NO.  
**012**  
OF 069

Plot Date: September 19, 2025 @ 12:26 PM





GOLDEN POPPY DR. STA. 1+00 TO 8+00 - PLAN VIEW  
SCALE: 1" = 30'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - CURB / EDGE OF PAVEMENT
  - - - RETAINING / SCREENING WALL
  - ▭ PROPOSED BUILDING PAD AREA
  - - - S12 EXISTING CONTOUR LINE
  - - - S12 PROPOSED CONTOUR LINE
  - SD --- STORM DRAIN LINE
  - OH --- OVERHEAD ELECTRIC
  - ⊙ STORM DRAIN MANHOLE
  - ⊙ STORM DRAIN CURB INLET
  - ⊙ STORM DRAIN GRATE INLET
  - ⊙ WATER METER
  - ⊙ WATER VALVE
  - ⊙ FIRE HYDRANT
  - ⊙ WASTEWATER MANHOLE
  - ⊙ WASTEWATER CLEANOUT
  - ⊙ TRANSFORMER
  - ⊙ UTILITY POLE
  - ⊙ GUY WIRE
  - ⊙ TAG# TREE W/ TAG
  - ⊙ TAG# TREE - REMOVE



GOLDEN POPPY DR. STA. 1+00 TO 8+00 - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 30' VERTICAL SCALE: 1" = 3'



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**GOLDEN POPPY RD PLAN & PROFILE STA. 1+00 TO 8+00**

**CIVILITUDE**  
ENGINEERS & PLANNERS


503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
DN BY: WS  
DN BY: MD,TML  
RVW BY: MVR

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER


SHEET NO. 013 OF 069

Plot Date: September 19, 2025 @ 12:27 PM






GOLDEN POPPY DR. STA. 8+00 TO END - PLAN VIEW  
SCALE: 1" = 30'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - EASEMENT / SETBACK
  - CURB / EDGE OF PAVEMENT
  - RETAINING / SCREENING WALL
  - PROPOSED BUILDING PAD AREA
  - EXISTING CONTOUR LINE
  - PROPOSED CONTOUR LINE
  - STORM DRAIN LINE
  - OVERHEAD ELECTRIC
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - STORM DRAIN GRATE INLET
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - TRANSFORMER
  - UTILITY POLE
  - GUY WIRE
  - TREE W/ TAG
  - TREE - REMOVE




GOLDEN POPPY DR. STA. 8+00 TO END - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 30' VERTICAL SCALE: 1" = 3'




NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626 <b>GOLDEN POPPY RD PLAN &amp; PROFILE STA. 8+00 TO END</b>			
503 KENNISTON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	
		FIRM REG # F12469 INFO@CIVILITUDE.COM	
JOB NO: A799 DGN BY: WS DWN BY: MD,TML RVW BY: MVR		9-19-2025 	
			SHEET NO. <b>014</b> OF 069

Plot Date: September 19, 2025 @ 12:28 PM





STORY TREE LANE STA. 1+00 TO END - PLAN VIEW  
SCALE: 1" = 30'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - CURB / EDGE OF PAVEMENT
  - - - RETAINING / SCREENING WALL
  - ▭ PROPOSED BUILDING PAD AREA
  - - -512- EXISTING CONTOUR LINE
  - - -512- PROPOSED CONTOUR LINE
  - - - SD - - - STORM DRAIN LINE
  - OH - - - OVERHEAD ELECTRIC
  - ⊙ STORM DRAIN MANHOLE
  - ⊙ STORM DRAIN CURB INLET
  - ⊙ STORM DRAIN GRATE INLET
  - ⊙ WATER METER
  - ⊙ WATER VALVE
  - ⊙ FIRE HYDRANT
  - ⊙ WASTEWATER MANHOLE
  - ⊙ WASTEWATER CLEANOUT
  - ⊙ TRANSFORMER
  - ⊙ UTILITY POLE
  - ⊙ GUY WIRE
  - ⊙ TAG# TREE W/ TAG
  - ⊙ TAG# TREE - REMOVE



STORY TREE LANE STA. 1+00 TO END - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 30' VERTICAL SCALE: 1" = 3'



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET


SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**STORY TREE LANE PLAN & PROFILE**  
STA. 1+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS  
503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM


JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER


SHEET NO.  
**015**  
OF 069



Plot Date: September 19, 2025 @ 12:29 PM



**84' ROW STREET CROSS-SECTIONS**  
SCALE: 1"=5'



**64' ROW STREET CROSS-SECTIONS**  
SCALE: 1"=5'

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE, GEORGETOWN, TX 78626

**TYPICAL STREET SECTIONS**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER





Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
**016**  
OF 069

Plot Date: September 19, 2025 @ 12:29 PM

LEGEND	
	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	CURB / EDGE OF PAVEMENT
	RETAINING / SCREENING WALL
	PROPOSED ASPHALT WIDENING
	STORM DRAIN LINE
	OVERHEAD ELECTRIC
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	STORM DRAIN GRATE INLET
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	TRANSFORMER
	UTILITY POLE
	GUY WIRE
	TREE W/ TAG
	TREE - REMOVE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE, GEORGETOWN, TX 78626

DECEL LANE PLAN

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
 DN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR

9-19-2025

JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

SHEET NO. 017 OF 069

Plot Date: September 19, 2025 @ 12:30 PM



LEGEND	
	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	PROPOSED BUILDING PAD AREA
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	STORM DRAIN AREA INLET
	TRANSFORMER
	AIR CONDITIONER UNIT
	GAS METER
	ELECTRIC MANHOLE
	ELECTRIC BOX
	UTILITY POLE
	GUY WIRE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 75626

**OVERALL GRADING PLAN**

**CIVILITUDE**  
 ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
 124884  
 LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller


JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR

SHEET NO.  
**018**  
 OF 069

Plot Date: September 19, 2025 @ 12:31 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - CEF SETBACK
  - - - EASEMENT / SETBACK
  - - - CURB / EDGE OF PAVEMENT
  - - - RETAINING / SCREENING WALL
  - - - EXISTING CONTOUR LINE
  - S12 --- STORM DRAIN LINE
  - ⊙ STORM DRAIN MANHOLE
  - ⊕ STORM DRAIN CURB INLET
  - ⊖ STORM DRAIN GRATE INLET
  - DRAINAGE SWALE FLOW LINE
  - DRAINAGE AREA
  - CREEK CENTERLINE
  - FEMA FLOODWAY
  - FEMA FLOODPLAIN-100-YR
  - FEMA FLOODPLAIN-500-YR
  - ATLAS 14 FLOODPLAIN-100-YR
  - ⊙ DRAINAGE AREA NAME  
AREA/IC %
  - FLOW DIRECTION



Sub Basin	Downstream	Area (ac)	Impervious Cover (%)	HEC-HMS Outputs			
				Q2 (cfs)	Q10 (cfs)	Q25 (cfs)	Q100 (cfs)
EX-1	EX-POA-1	45.8	0.0%	75.3	174.1	233.0	327.6
EX-2	EX-POA-2	23.0	0.0%	38.2	88.3	118.1	166.1
OS-1	EX-POA-2	14.2	0.0%	26.0	60.0	80.2	112.7
OS-2	EX-POA-2	20.2	50.0%	76.3	130.3	160.8	209.7
OS-3	EX-POA-3	60.3	50.0%	185.7	317.4	391.7	511.2
<b>Point of Analysis 1</b>				75.3	174.1	233.0	327.6
<b>Point of Analysis 2</b>				312.0	572.6	722.1	962.7

Sub Basin	Total Reach (ft)	Curve Number	Total Tc (min)	Sheet Flow $T_c = 0.42 * ((nL)^{0.8}) / (P_s^{0.5}) * (s^{0.4})$				Shallow Concentrated Flow $Unpaved T_c = L / (60 * 16.1345 * (s^{0.5}))$		
				Reach (L) (ft)	Manning's (n)	Slope (s) (ft/ft)	Tc (min)	Reach (L) (ft)	Slope (s) (ft/ft)	Tc (min)
EX-1	2300	80	22.3	100	0.2	0.08	6.3	2200	0.02	16.1
EX-2	2125	80	21.9	100	0.2	0.06	7.1	2025	0.02	14.8
OS-1	2437	80	17.8	100	0.011	0.05	0.7	2337	0.02	17.1
OS-2	1637	94	12.0	100	0.011	0.05	0.7	1537	0.02	11.2
OS-3	2682	94	19.6	100	0.011	0.05	0.7	2582	0.02	18.9

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE, GEORGETOWN, TX 78626 <b>EXISTING DRAINAGE AREA MAP</b>			
503 KENNISTON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	FIRM REG # F12469 INFO@CIVILITUDE.COM
JOB NO: A799		9-19-2025	
DGN BY: WS			
DWN BY: MD,TML			
RVW BY: MVR			
			SHEET NO. <b>019</b> OF 069

Plot Date: September 19, 2025 @ 12:31 PM



**LEGEND**

- BOUNDARY / RIGHT OF WAY
- - - - - CEF SETBACK
- - - - - EASEMENT / SETBACK
- ==== CURB / EDGE OF PAVEMENT
- RETAINING / SCREENING WALL
- - - - - EXISTING CONTOUR LINE
- S12 --- STORM DRAIN LINE
- ⊙ STORM DRAIN MANHOLE
- ⊙ STORM DRAIN CURB INLET
- ⊙ STORM DRAIN GRATE INLET
- DRAINAGE SWALE FLOW LINE
- █ DRAINAGE AREA
- CREEK CENTERLINE
- FLOODWAY
- FEMA FLOODWAY
- 100YR FEMA FLOODPLAIN-100-YR
- 500YR FEMA FLOODPLAIN-500-YR
- ATLAS 14 ATLAS 14 FLOODPLAIN-100-YR
- ⊙ DRAINAGE AREA NAME
- ⊙ AREA/IC %
- FLOW DIRECTION




Sub Basin	Downstream	Area (ac)	Impervious Cover (%)	HEC-HMS Outputs			
				Q2 (cfs)	Q10 (cfs)	Q25 (cfs)	Q100 (cfs)
P-A1	PR-POA-2	4.9	75.31%	22.5	38.0	46.8	60.8
P-A2	PR-POA-2	5.0	80.00%	24.3	41.0	50.4	65.5
P-B1	PR-POA-2	1.8	80.00%	9.5	16.0	19.7	25.6
P-B2	PR-POA-2	6.3	80.00%	31.2	52.4	64.6	83.9
P-C1	PR-POA-2	4.9	0.00%	8.8	20.3	27.1	38.0
P-C2	PR-POA-2	7.9	0.00%	12.2	28.2	37.8	53.2
P-D1	PR-POA-1	1.9	19.51%	4.3	9.1	11.9	16.4
P-D2	PR-POA-1	5.1	0.00%	9.7	22.4	30.0	42.1
P-D3	FR-POA-1	1.6	0.00%	3.1	7.1	9.4	13.2
P-D4	PR-POA-1	12.0	0.00%	21.0	48.5	65.0	91.3
P-D5	FR-POA-1	17.3	0.00%	30.7	70.9	94.8	133.1
OS-1	PR-POA-2	14.2	0.00%	26.0	60.0	80.2	112.7
OS-2	PR-POA-2	20.2	50.00%	76.3	130.3	160.8	209.7
OS-3	PR-POA-2	60.3	50.00%	185.7	317.4	391.7	511.2
<b>Point of Analysis 1</b>				68.3	156.8	209.5	294.4
<b>Point of Analysis 2</b>				309.1	560.6	706.6	944.2
<b>WEST POND</b>				8.3	18.4	25.8	39.4
<b>EAST POND</b>				6.7	11.0	13.8	18.9
<b>Δ Flow at POA 1 (CFS)</b>				-7.0	-17.3	-23.5	-33.2
<b>Δ Flow at POA 2 (CFS)</b>				-2.9	-12.0	-15.5	-18.5

Sub Basin	Total Reach (ft)	Curve Number	Total Tc (min)	Sheet flow			Shallow Concentrated Flow			Channel Flow/Pipe			
				Tc = 0.42 * ((nL)^0.8) / (P2^0.5) * (s^0.4)				Unpaved TC = L / (60 * 16.1345 * (s^0.5))					
				Reach (L) (ft)	Manning's (n)	Slope (s) (ft/ft)	Tc (min)	Reach (L) (ft)	Slope (s) (ft/ft)	Tc (min)	Length (ft)	Avg. Velocity (ft/s)	Tc (min)
P-A1	1411	94	6.9	100	0.011	0.01	1.4	0	0.02	0.0	1,311	4.0	5.5
P-A2	693	94	5.3	100	0.011	0.015	1.2	279	0.01	2.8	314	4.0	1.3
P-B1	220	94	2.8	100	0.011	0.010	1.4	120	0.01	1.4	0	4.0	0.0
P-B2	610	94	5.1	100	0.011	0.010	1.4	200	0.01	2.4	310	4.0	1.3
P-C1	500	80	18.4	300	0.2	0.010	14.2	300	0.01	3.8	100	4.0	0.4
P-C2	2000	80	25.2	100	0.2	0.020	10.8	1900	0.02	14.5	0	4.0	0.0
P-D1	192	80	14.8	100	0.2	0.010	14.2	92	0.02	0.6	0	4.0	0.0
P-D2	498	80	16.4	100	0.2	0.010	14.2	129	0.02	1.1	269	4.0	1.1
P-D3	357	80	16.1	100	0.2	0.010	14.2	257	0.02	1.9	0	4.0	0.0
P-D4	630	80	19.7	100	0.2	0.010	14.2	530	0.01	5.5	0	4.0	0.0
P-D5	943	80	19.0	100	0.2	0.010	14.2	407	0.02	3.0	436	4.0	1.8
OS-1	2437	80	17.8	100	0.011	0.05	0.7	2337	0.02	17.1	0	4.0	0.0
OS-2	1637	94	12.0	100	0.011	0.05	0.7	1537	0.02	11.2	0	4.0	0.0
OS-3	2682	94	19.6	100	0.011	0.05	0.7	2582	0.02	18.9	0	4.0	0.0

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626 <b>PROPOSED DRAINAGE AREA MAP</b>			
503 KENNISTON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	
		FIRM REG # F12469 INFO@CIVILITUDE.COM	
9-19-2025			
JOB NO:	A799		
DN BY:	WS		
DWN BY:	MD,TML		
RVW BY:	MVR		
			SHEET NO. <b>020</b> OF 069

Plot Date: September 19, 2025 @ 12:32 PM



**LEGEND**

- BOUNDARY / RIGHT OF WAY
- EASEMENT / SETBACK
- CURB / EDGE OF PAVEMENT
- RETAINING / SCREENING WALL
- EXISTING CONTOUR LINE
- PROPOSED CONTOUR LINE
- STORM DRAIN LINE
- STORM DRAIN MANHOLE
- STORM DRAIN CURB INLET
- STORM DRAIN GRATE INLET
- DRAINAGE SWALE FLOW LINE
- DRAINAGE AREA
- DRAINAGE AREA NAME AREA/IC %
- FLOW DIRECTION

DA NAME	AREA (sf)	AREA (Ac)	Q - 100YR (cfs)
1	6,529.0	0.150	1.73
2	6,776.7	0.156	1.79
3	7,582.5	0.174	2.01
4	9,467.3	0.217	2.50
5	17,680.0	0.410	4.73
6	13,892.1	0.319	3.68
7	10,665.0	0.245	0.94
8	8,352.9	0.192	0.73
9	5,687.0	0.131	1.50
10	3,650.8	0.084	0.97
11	9,593.1	0.220	2.54
12	14,307.8	0.328	3.79
13	9,629.3	0.221	2.55
14	11,465.7	0.263	3.03
15	10,508.0	0.241	2.78
16	10,168.6	0.233	2.69
17	9,987.4	0.229	2.64
18	14,936.5	0.343	3.95
19	8,909.5	0.205	2.36
20	12,869.4	0.295	3.40
21	9,342.7	0.214	2.47
22	12,157.1	0.279	3.22
23	7,237.1	0.166	1.91
24	7,555.0	0.173	2.00



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**INLET DRAINAGE AREA MAP**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

JORDAN L. MILLER  
124884

Jordan L. Miller

JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR


SHEET NO.  
**021**  
OF 069

Plot Date: September 19, 2025 @ 12:25 PM



**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	UTILITY POLE
	GUY WIRE
	PUBLIC OPEN SPACE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**OVERALL STORM PLAN**

503 KENNISTON DR #4    AUSTIN, TX 78752    FIRM REG # F12469  
 PHONE 512 761 6161    FAX 512 761 6167    INFO@CIVILITUDE.COM

9-19-2025


Jordan L. Miller

JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR

SHEET NO.  
**022**  
 OF 069




Plot Date: September 19, 2025 @ 12:26 PM





- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - 512 EXISTING CONTOUR LINE
  - - - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - ==== STORM DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - OH OVERHEAD ELECTRIC
  - GAS GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - D STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**STORM LINE A PLAN & PROFILE**  
STA. 7+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM

9-19-2025

JOB NO: A799


DN BY: WS

DWN BY: MD,TML

RVW BY: MVR




SHEET NO.  
**024**  
OF 069

Plot Date: September 19, 2025 @ 3:42 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - 512 EXISTING CONTOUR LINE
  - - - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - S DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - OH OVERHEAD ELECTRIC
  - GAS GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - W WASTEWATER MANHOLE
  - CO WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - S DRAIN MANHOLE
  - S DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**STORM LINE B PLAN & PROFILE**  
STA. 1+00 TO 5+50

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM



JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR


SHEET NO.  
**025**  
OF 099

Plot Date: September 19, 2025 @ 3:44 PM











**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	UE/UC LINE
	OVERHEAD ELECTRIC GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	UTILITY POLE
	GUY WIRE
	PUBLIC OPEN SPACE


**PROFILE LEGEND**

	PROP. GRADE
	EXISTING GRADE






NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626 <b>STORM LINE D PLAN &amp; PROFILE</b> STA. 1+00 TO END			
		<b>CIVILITUDE</b> ENGINEERS & PLANNERS	
503 KENNISTON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	
FIRM REG # F12469 INFO@CIVILITUDE.COM		9-19-2025 	
JOB NO:	A799	DGN BY:	WS
DWN BY:	MD,TML	RVW BY:	MVR
			<b>SHEET NO.</b> 029 OF 069

Plot Date: September 19, 2025 @ 3:50 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - 512 EXISTING CONTOUR LINE
  - - - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - ==== STORM DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - OH OVERHEAD ELECTRIC
  - GAS GAS LINE
  - ▲ WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - CO ● WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - ← GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE @ 6



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**DRIVEWAY B CULVERT  
PLAN & PROFILE**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM

9-19-2025

JOB NO: A799



DGN BY: WS

DWN BY: MD,TML

RVW BY: MVR

SHEET NO.  
**030**  
OF 069

Plot Date: September 19, 2025 @ 12:38 PM




ELEVATION VIEW

**JELLYFISH DESIGN NOTES**

JELLYFISH TREATMENT CAPACITY IS A FUNCTION OF THE CARTRIDGE SIZE, TYPE AND QUANTITY. THE STANDARD PEAK DIVERSION VAULT STYLE WITH PRECAST TOP SLAB IS SHOWN. THE 8' x 12' [2438 x 3658] JELLYFISH PEAK TREATMENT CAPACITY IS 3.88 CFS [166.50 L/s]. MAXIMUM BYPASS CAPACITY IS DETERMINED BY CONTECH ENGINEERED SOLUTIONS. IF THE SITE CONDITIONS EXCEED THE TOTAL BYPASS CAPACITY OF THE SYSTEM, AN UPSTREAM DIVERSION STRUCTURE IS REQUIRED.

CARTRIDGE SIZE	64	40	27	15
FLOW RATE HIGH-FLO / DRAINDOWN (cfs [L/s])	0.179/0.089 [5.102/2.55]	0.133/0.065 [3.68/1.84]	0.089/0.045 [2.55/1.28]	0.049/0.025 [1.42/0.71]
MAXIMUM CARTRIDGE QUANTITY, HI-FLO / DRAINDOWN	5.98 [166.50]	4.41 [124.88]	3.06	1.62 [45.87]
MAXIMUM TREATMENT	6.50 [198.1]	5.33 [1625]	4.25 [1209]	3.25 [991]
OUTLET INVERT TO STRUCTURE INVERT (A) (ft. [mm])	5.33 [1625]	5.33 [1625]	4.25 [1209]	3.25 [991]
FINISHED GRADE TO OUTLET INVERT (SHALLOW) (B)	DETERMINED BY CONTECH			
FINISHED GRADE TO OUTLET INVERT (STANDARD) (B) (ft. [mm])	5.67 [1727]			4.58 [1396]



**FRAME AND COVER**  
STANDARD TOP  
SLAB CONFIGURATION  
(DIAMETER VARIES)  
NOT TO SCALE

**24" TRENCH COVER**  
SHALLOW TOP  
SLAB CONFIGURATION  
(LENGTH VARIES)  
NOT TO SCALE

**SITE SPECIFIC DATA REQUIREMENTS**

STRUCTURE ID	
WATER QUALITY FLOW RATE (cfs [L/s])	
PEAK FLOW RATE (cfs [L/s])	
RETURN PERIOD OF PEAK FLOW (yr)	
NUMBER OF CARTRIDGES REQUIRED (HF / DD)	
CARTRIDGE SIZE (64, 40, 27, 15)	
RIM ELEVATION	
PIPE DATA:	
INLET PIPE 1	
INLET PIPE 2	
OUTLET PIPE	



SEE GENERAL NOTES 7-8 FOR INLET AND OUTLET HYDRAULIC AND SIZING REQUIREMENTS.

NOTES / SPECIAL REQUIREMENTS:

- GENERAL NOTES:**
- CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
  - FOR SITE SPECIFIC DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHT, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS REPRESENTATIVE. [www.ContechES.com](http://www.ContechES.com)
  - JELLYFISH WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
  - STRUCTURE SHALL MEET AASHTO HS-20 OR PER APPROVING JURISDICTION REQUIREMENTS, WHICHEVER IS MORE STRINGENT, ASSUMING EARTH COVER OF 7' - 10' (2048), AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 LOAD RATING AND BE CAST WITH THE CONTECH LOGO.
  - STRUCTURE SHALL BE PRECAST CONCRETE CONFORMING TO ASTM C-857, ASTM C-918, AND AASHTO LOAD FACTOR DESIGN METHOD.
  - OUTLET PIPE INVERT IS EQUAL TO THE CARTRIDGE DECK ELEVATION.
  - THE OUTLET PIPE DIAMETER FOR NEW INSTALLATIONS IS RECOMMENDED TO BE ONE PIPE SIZE LARGER THAN THE INLET PIPE AT EQUAL OR GREATER SLOPE.
  - NO PRODUCT SUBSTITUTIONS SHALL BE ACCEPTED UNLESS SUBMITTED 10 DAYS PRIOR TO PROJECT BID DATE, OR AS DIRECTED BY THE ENGINEER OF RECORD.
- INSTALLATION NOTES:**
- ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
  - CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STRUCTURE.
  - CONTRACTOR WILL INSTALL AND LEVEL THE STRUCTURE, SEALING THE JOINTS, LINE ENTRY AND EXIT POINTS (NON-SHRINK GROUT WITH APPROVED WATERTIGHT OR FLEXIBLE BOOT).
  - CARTRIDGE INSTALLATION, BY CONTECH, SHALL OCCUR ONLY AFTER SITE HAS BEEN STABILIZED AND THE JELLYFISH UNIT IS CLEAN AND FREE OF DEBRIS. CONTACT CONTECH TO COORDINATE CARTRIDGE INSTALLATION WITH SITE STABILIZATION.

**CONTECH ENGINEERED SOLUTIONS LLC**  
www.ContechES.com  
9028 Centre Pointe Dr., Suite 400, West Chester, OH 45390  
930-338-1122 930-338-7000 930-338-7993 FAX

JELLYFISH JFPD0812  
PEAK DIVERSION CONFIGURATION  
STANDARD DETAIL




ELEVATION VIEW

**JELLYFISH DESIGN NOTES**

JELLYFISH TREATMENT CAPACITY IS A FUNCTION OF THE CARTRIDGE LENGTH AND THE NUMBER OF CARTRIDGES. THE STANDARD PEAK DIVERSION STYLE WITH PRECAST TOP SLAB IS SHOWN. ALTERNATE OFFLINE VAULT AND/OR SHALLOW ORIENTATIONS ARE AVAILABLE. PEAK CONVEYANCE CAPACITY TO BE DETERMINED BY ENGINEER OF RECORD.

CARTRIDGE SELECTION	54"	40"	27"	15"
CARTRIDGE LENGTH	6'-6"	5'-4"	4'-3"	3'-3"
OUTLET INVERT TO STRUCTURE INVERT (A)	6'-6"	5'-4"	4'-3"	3'-3"
FLOW RATE HI-FLO / DRAINDOWN (CFS) (PER CART)	0.178 / 0.089	0.133 / 0.067	0.089 / 0.045	0.049 / 0.025
MAX TREATMENT (CFS)	7.84	5.86	3.92	2.16
DECK TO INSIDE TOP (MIN) (B)	5.00	4.00	4.00	4.00



**FRAME AND COVER**  
(DIAMETER VARIES)  
N.T.S.

**24" TRENCH COVER**  
(LENGTH VARIES)  
N.T.S.

**SITE SPECIFIC DATA REQUIREMENTS**

STRUCTURE ID	
WATER QUALITY FLOW RATE (cfs)	
PEAK FLOW RATE (cfs)	
RETURN PERIOD OF PEAK FLOW (yr)	
# OF CARTRIDGES REQUIRED (HF / DD)	
CARTRIDGE LENGTH	
PIPE DATA:	
INLET #1	
INLET #2	
OUTLET	

SEE GENERAL NOTES 6-7 FOR INLET AND OUTLET HYDRAULIC AND SIZING REQUIREMENTS.

RIM ELEVATION	
ANTI-FLOTATION BALLAST	
WIDTH	
HEIGHT	

NOTES/SPECIAL REQUIREMENTS:  
\* PER ENGINEER OF RECORD

- GENERAL NOTES:**
- CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
  - FOR SITE SPECIFIC DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHT, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS REPRESENTATIVE. [www.ContechES.com](http://www.ContechES.com)
  - JELLYFISH WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
  - STRUCTURE SHALL MEET AASHTO HS-20 OR PER APPROVING JURISDICTION REQUIREMENTS, WHICHEVER IS MORE STRINGENT, ASSUMING EARTH COVER OF 7' - 10' AND GROUNDWATER ELEVATION AT, OR BELOW, THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 LOAD RATING AND BE CAST WITH THE CONTECH LOGO.
  - STRUCTURE SHALL BE PRECAST CONCRETE CONFORMING TO ASTM C-857, ASTM C-918, AND AASHTO LOAD FACTOR DESIGN METHOD.
  - OUTLET PIPE INVERT IS EQUAL TO THE CARTRIDGE DECK ELEVATION.
  - THE OUTLET PIPE DIAMETER FOR NEW INSTALLATIONS IS RECOMMENDED TO BE ONE PIPE SIZE LARGER THAN THE INLET PIPE AT EQUAL OR GREATER SLOPE.
  - NO PRODUCT SUBSTITUTIONS SHALL BE ACCEPTED UNLESS SUBMITTED 10 DAYS PRIOR TO PROJECT BID DATE, OR AS DIRECTED BY THE ENGINEER OF RECORD.
- INSTALLATION NOTES:**
- ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
  - CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STRUCTURE.
  - CONTRACTOR WILL INSTALL AND LEVEL THE STRUCTURE, SEALING THE JOINTS, LINE ENTRY AND EXIT POINTS (NON-SHRINK GROUT WITH APPROVED WATERTIGHT OR FLEXIBLE BOOT).
  - CARTRIDGE INSTALLATION, BY CONTECH, SHALL OCCUR ONLY AFTER SITE HAS BEEN STABILIZED AND THE JELLYFISH UNIT IS CLEAN AND FREE OF DEBRIS. CONTACT CONTECH TO COORDINATE CARTRIDGE INSTALLATION WITH SITE STABILIZATION.

**CONTECH ENGINEERED SOLUTIONS LLC**  
www.ContechES.com  
9028 Centre Pointe Dr., Suite 400, West Chester, OH 45390  
930-338-1122 930-338-7000 930-338-7993 FAX

JELLYFISH JFPD0816  
STANDARD DETAIL  
PEAK DIVERSION CONFIGURATION

Plot Date: September 19, 2025 @ 12:40 PM

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**JELLYFISH WATER QUALITY DETAILS**

**CIVILITUDE ENGINEERS & PLANNERS**  
503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO. 031 OF 069

**Contech Engineered Solutions Calculations for Texas Commission on Environmental Quality  
TSS Removal Calculations**

Project Name: **560 Development**  
Date Prepared: **8/11/2025**

**1. The Required Load Reduction for the total project:**

Calculations from RG-348 Page 3-29 Equation 3.3:  $L_M = 28.9(A_N \times P)$   
Pages 3-27 to 3-30

$L_{M\ TOTAL\ PROJECT}$  = Required TSS removal resulting from the proposed development = 85% of increased load  
 $A_N$  = Net increase in impervious area for the project  
P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County = **Williamson**  
Total project area included in plan \* = **10.00** acres  
Predevelopment impervious area within the limits of the plan \* = **0.00** acres  
Total post-development impervious area within the limits of the plan \* = **8.00** acres  
Total post-development impervious cover fraction \* = **0.80**  
P = **32** inches  
 $L_{M\ TOTAL\ PROJECT}$  = **7398** lbs.

Number of drainage basins / outfalls areas leaving the plan area = **1**

**2. Drainage Basin Parameters (This information should be provided for each basin):**

Drainage Basin/Outfall Area No. = **P-2A**

Total drainage basin/outfall area = **10.00** acres  
Predevelopment impervious area within drainage basin/outfall area = **0.00** acres  
Post-development impervious area within drainage basin/outfall area = **8.00** acres  
Post-development impervious fraction within drainage basin/outfall area = **0.80**  
 $L_{M\ THIS\ BASIN}$  = **7398** lbs.

**3. Indicate the proposed BMP Code for this basin.**

Proposed BMP = **JF** abbreviation  
Removal efficiency = **86** percent

**4. Calculate Maximum TSS Load Removed ( $L_R$ ) for this Drainage Basin by the selected BMP Type.**

RG-348 Page 3-33 Equation 3.7:  
 $LR = (BMP\ efficiency) \times P \times (A_I \times 34.6 + A_P \times 0.54)$

$A_C$  = Total On-Site drainage area in the BMP catchment area  
 $A_I$  = Impervious area proposed in the BMP catchment area  
 $A_P$  = Pervious area remaining in the BMP catchment area  
 $L_R$  = TSS Load removed from this catchment area by the proposed BMP

$A_C$  = **10.00** acres  
 $A_I$  = **8.00** acres  
 $A_P$  = **2.00** acres  
 $L_R$  = **7647** lbs.

**5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area**

Desired  $L_{M\ THIS\ BASIN}$  = **7398** lbs.  
F = **0.97**

**6. Calculate Treated Flow required by the BMP Type for this drainage basin / outfall area.**

Offsite area draining to BMP = **0.00** acres  
Offsite impervious cover draining to BMP = **0.00** acres

Calculations from RG-348  
Pages Section 3.2.22

Rainfall Intensity = **2.00** inches per hour  
Effective Area = **7.26** acres  
Cartridge Length = **54** inches

Peak Treatment Flow Required = **14.64** cubic feet per second

**7. Jellyfish**  
Designed as Required in RG-348  
Section 3.2.22

**Flow Through Jellyfish Size Vault**  
Jellyfish Size for Flow-Based Configuration = **2ea JFPDo816-38-8**  
Jellyfish Treatment Flow Rate = **14.97** cfs

**Contech Engineered Solutions Calculations for Texas Commission on Environmental Quality  
TSS Removal Calculations**

Project Name: **560 Development**  
Date Prepared: **8/11/2025**

**1. The Required Load Reduction for the total project:**

Calculations from RG-348 Page 3-29 Equation 3.3:  $L_M = 28.9(A_N \times P)$   
Pages 3-27 to 3-30

$L_{M\ TOTAL\ PROJECT}$  = Required TSS removal resulting from the proposed development = 85% of increased load  
 $A_N$  = Net increase in impervious area for the project  
P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County = **Williamson**  
Total project area included in plan \* = **8.00** acres  
Predevelopment impervious area within the limits of the plan \* = **0.00** acres  
Total post-development impervious area within the limits of the plan \* = **6.40** acres  
Total post-development impervious cover fraction \* = **0.80**  
P = **32** inches  
 $L_{M\ TOTAL\ PROJECT}$  = **5919** lbs.

Number of drainage basins / outfalls areas leaving the plan area = **1**

**2. Drainage Basin Parameters (This information should be provided for each basin):**

Drainage Basin/Outfall Area No. = **P-2B**

Total drainage basin/outfall area = **8.00** acres  
Predevelopment impervious area within drainage basin/outfall area = **0.00** acres  
Post-development impervious area within drainage basin/outfall area = **6.40** acres  
Post-development impervious fraction within drainage basin/outfall area = **0.80**  
 $L_{M\ THIS\ BASIN}$  = **5919** lbs.

**3. Indicate the proposed BMP Code for this basin.**

Proposed BMP = **JF** abbreviation  
Removal efficiency = **86** percent

**4. Calculate Maximum TSS Load Removed ( $L_R$ ) for this Drainage Basin by the selected BMP Type.**

RG-348 Page 3-33 Equation 3.7:  
 $LR = (BMP\ efficiency) \times P \times (A_I \times 34.6 + A_P \times 0.54)$

$A_C$  = Total On-Site drainage area in the BMP catchment area  
 $A_I$  = Impervious area proposed in the BMP catchment area  
 $A_P$  = Pervious area remaining in the BMP catchment area  
 $L_R$  = TSS Load removed from this catchment area by the proposed BMP

$A_C$  = **8.00** acres  
 $A_I$  = **6.40** acres  
 $A_P$  = **1.60** acres  
 $L_R$  = **6118** lbs.

**5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area**

Desired  $L_{M\ THIS\ BASIN}$  = **5919** lbs.  
F = **0.97**

**6. Calculate Treated Flow required by the BMP Type for this drainage basin / outfall area.**

Offsite area draining to BMP = **0.00** acres  
Offsite impervious cover draining to BMP = **0.00** acres

Calculations from RG-348  
Pages Section 3.2.22

Rainfall Intensity = **2.00** inches per hour  
Effective Area = **5.81** acres  
Cartridge Length = **54** inches

Peak Treatment Flow Required = **11.71** cubic feet per second

**7. Jellyfish**  
Designed as Required in RG-348  
Section 3.2.22

**Flow Through Jellyfish Size Vault**  
Jellyfish Size for Flow-Based Configuration = **2ea JFPDo812-30-6**  
Jellyfish Treatment Flow Rate = **11.76** cfs

Plot Date: September 19, 2025 @ 12:40 PM


NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**TCEQ WATER QUALITY  
CALCULATIONS**


**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM


9-19-2025  
JOB NO: A799  
DN BY: WS  
DN BY: MD,TML  
RVW BY: MVR  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER  
STATE OF TEXAS  
SHEET NO.  
032  
OF 069



WEST POND PLAN VIEW  
SCALE: 1" = 20'



WEST POND SECTION B-B  
HORIZONTAL SCALE: 1" = 20' VERTICAL SCALE: 1" = 2'



WEST POND SECTION A-A  
HORIZONTAL SCALE: 1" = 20' VERTICAL SCALE: 1" = 2'

WEST POND VOLUME CALCULATIONS					
Elevation (ft)	Area		Total Volume		100-Year Outflow
	(sf)	(ac)	(cf)	(ac-ft)	(cfs)
697	1	0.000019	-	0.00	
698	7,372	0.169238	3,686.4	0.08	1.60
699	24,405	0.560262	19,574.9	0.45	4.40
700	31,885	0.731979	47,719.9	1.10	8.50
701	33,730	0.774334	80,527.4	1.85	18.40
702	34,868	0.800459	114,826.4	2.64	31.00
703	36,014	0.810000	150,267.4	3.45	47.80
704	36,015	0.826768	186,281.9	4.28	64.30

West Pond Elevations		
Storm Event	Peak Elev. (ft)	Peak Discharge (cfs)
100-year	703.9	64.3
25-year	702.8	43.6
10-year	702	31.6
2-year	700.6	13.9

West Pond Outlet Controls		
	Elevation	Length (ft)
Spillway 1	0	0.5
Spillway 2	2.8	1.50

- LEGEND
- BOUNDARY / RIGHT OF WAY
  - EASEMENT / SETBACK
  - CURB / EDGE OF PAVEMENT
  - RETAINING / SCREENING WALL
  - 512- EXISTING CONTOUR LINE
  - 512- PROPOSED CONTOUR LINE
  - SD SD STORM DRAIN LINE
  - (D) STORM DRAIN MANHOLE
  - STORM DRAIN GRATE INLET
- PROFILE LEGEND
- FINISHED GRADE
  - EXISTING GRADE

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

## WEST POND PLAN & SECTIONS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
LICENSED PROFESSIONAL ENGINEER  
124884

Jordan L. Miller


JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO. 033 OF 069


Plot Date: September 19, 2025 @ 12:41 PM



EAST POND PLAN VIEW  
SCALE: 1" = 20'



EAST POND SECTION B-B  
HORIZONTAL SCALE: 1" = 20' VERTICAL SCALE: 1" = 2'



EAST POND SECTION A-A  
HORIZONTAL SCALE: 1" = 20' VERTICAL SCALE: 1" = 2'

EAST POND VOLUME CALCULATIONS					
Elevation (ft)	Area		Total Volume		100-Year Outflow
	(sf)	(ac)	(cf)	(ac-ft)	(cfs)
698	1	0.000016	-	0.00	-
699	8,781	0.201584	4,390.9	0.10	1.60
700	23,242	0.533563	20,402.4	0.47	4.40
701	30,077	0.690473	47,061.9	1.08	8.00
702	31,583	0.725046	77,891.9	1.79	12.20
703	32,789	0.752732	110,077.9	2.53	16.90
704	34,011	0.780785	143,477.9	3.29	-

East Pond Elevations		
Storm Event	Peak Elev. (ft)	Peak Discharge (cfs)
100-year	703.4	18.9
25-year	702.4	13.8
10-year	701.8	11.0
2-year	700.7	6.7

East Pond Outlet Controls		
	Elevation	Length (ft)
Spillway 1	0	0.5

- LEGEND
- BOUNDARY / RIGHT OF WAY
  - EASEMENT / SETBACK
  - CURB / EDGE OF PAVEMENT
  - RETAINING / SCREENING WALL
  - - - -512- - - EXISTING CONTOUR LINE
  - - -512- - - PROPOSED CONTOUR LINE
  - S0 --- S0 --- STORM DRAIN LINE
  - (D) STORM DRAIN MANHOLE
  - (G) STORM DRAIN GRATE INLET
- PROFILE LEGEND
- FINISHED GRADE
  - EXISTING GRADE

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

## EAST POND PLAN & SECTIONS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM




9-19-2025

JORDAN L. MILLER  
LICENSED PROFESSIONAL ENGINEER  
124884

Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO. 034 OF 069



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

DETENTION POND DETAILS

503 KENNISTON DR #4      AUSTIN, TX 78752      FIRM REG # F12469  
PHONE 512 761 6161      FAX 512 761 6167      INFO@CIVILITUDE.COM

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR


9-19-2025

SHEET NO.  
035  
OF 069

Plot Date: September 19, 2025 @ 12:44 PM



LEGEND	
	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	PROPOSED BUILDING PAD AREA
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	STORM DRAIN AREA INLET
	TRANSFORMER
	AIR CONDITIONER UNIT
	GAS METER
	ELECTRIC MANHOLE
	ELECTRIC BOX
	UTILITY POLE
	GUY WIRE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 75626

OVERALL UTILITY PLAN



503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
036  
OF 069

GRID N: 10206737.02  
GRID E: 3137807.18


GRID N: 10207243.05  
GRID E: 3139545.14

Plot Date: September 19, 2025 @ 12:45 PM



**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	UTILITY POLE
	GUY WIRE
	PUBLIC OPEN SPACE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**OVERALL WATER LINE DISTRIBUTION PLAN**

**CIVILITUDE**  
ENGINEERS & PLANNERS


503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

Jordan L. Miller




PROJECT NUMBER: 2025-\_\_\_-CON

Plot Date: September 19, 2025 @ 12:46 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - - - EASEMENT / SETBACK
  - - - - - EXISTING CONTOUR LINE
  - 512 — PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - ==== STORM DRAIN LINE
  - W — WATER LINE
  - WW — WASTEWATER LINE
  - UUC — UE/UC LINE
  - OH — OVERHEAD ELECTRIC
  - GAS — GAS LINE
  - ◻ WATER METER
  - ◻ WATER VALVE
  - ◻ FIRE HYDRANT
  - ◻ WASTEWATER MANHOLE
  - ◻ WASTEWATER CLEANOUT
  - ◻ BFP — BACKFLOW PREVENTER
  - ◻ D — STORM DRAIN MANHOLE
  - ◻ S — STORM DRAIN CURB INLET
  - ◻ U — UTILITY POLE
  - ◻ GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - - - EXISTING GRADE



Plot Date: September 19, 2025 @ 3:52 PM

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WATER LINE A PLAN &  
PROFILE STA. 1+00 TO 7+00**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM

9-19-2025


JOB NO: A799

DGN BY: WS


DWN BY: MD,TML

RVW BY: MVR

SHEET NO.  
**038**  
OF 069





WATER LINE A STA. 7+00 TO END - PLAN VIEW  
SCALE: 1" = 40'



WATER LINE A STA. 7+00 TO END - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 40' VERTICAL SCALE: 1" = 4'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - 512 EXISTING CONTOUR LINE
  - - - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - WATER LINE
  - WASTEWATER LINE
  - UE/UC LINE
  - OVERHEAD ELECTRIC
  - GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WATER LINE A PLAN & PROFILE STA. 7+00 TO END**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM


9-19-2025  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR


SHEET NO.  
**039**  
OF 069

Plot Date: September 19, 2025 @ 12:48 PM





WATER LINE B STA. 1+00 TO 9+00 - PLAN VIEW  
SCALE: 1" = 40'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - - EASEMENT / SETBACK
  - - - - EXISTING CONTOUR LINE
  - - - - PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - ==== STORM DRAIN LINE
  - ==== WATER LINE
  - ==== WASTEWATER LINE
  - ==== UE/C LINE
  - ==== OVERHEAD ELECTRIC
  - ==== GAS LINE
  - ◻ WATER METER
  - ◻ WATER VALVE
  - ◻ FIRE HYDRANT
  - ◻ WASTEWATER MANHOLE
  - ◻ WASTEWATER CLEANOUT
  - ◻ BACKFLOW PREVENTER
  - ◻ STORM DRAIN MANHOLE
  - ◻ STORM DRAIN CURB INLET
  - ◻ UTILITY POLE
  - ◻ GUY WIRE
  - ◻ PUBLIC OPEN SPACE
- PROFILE LEGEND**
- PROP. GRADE
  - - - - EXISTING GRADE



WATER LINE B STA. 1+00 TO 9+00 - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 40' VERTICAL SCALE: 1" = 4'



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WATER LINE B PLAN &  
PROFILE STA. 1+00 TO 9+00**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
**040**  
OF 069


Plot Date: September 19, 2025 @ 3:54 PM





- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - ▭ 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - W WATER LINE
  - WASTEWATER LINE
  - UE/UC LINE
  - OH OVERHEAD ELECTRIC
  - GAS LINE
  - ◻ WATER METER
  - ◻ WATER VALVE
  - ◻ FIRE HYDRANT
  - ◻ WASTEWATER MANHOLE
  - ◻ CO WASTEWATER CLEANOUT
  - ◻ BFP BACKFLOW PREVENTER
  - ◻ STORM DRAIN MANHOLE
  - ◻ STORM DRAIN CURB INLET
  - ◻ UTILITY POLE
  - ◻ GUY WIRE
  - █ PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE

WATER LINE B STA. 9+00 TO END - PLAN VIEW  
SCALE: 1" = 40'



WATER LINE B STA. 9+00 TO END - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 40' VERTICAL SCALE: 1" = 4'



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WATER LINE B PLAN & PROFILE STA. 9+00 TO END**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
**041**  
OF 069


Plot Date: September 19, 2025 @ 12:45 PM

**LEGEND**


- BOUNDARY / RIGHT OF WAY
- - - EASEMENT / SETBACK
- - - S12 EXISTING CONTOUR LINE
- - - 512 PROPOSED CONTOUR LINE
- ==== CURB / EDGE OF PAVEMENT
- S12 STORM DRAIN LINE
- W WATER LINE
- WW WASTEWATER LINE
- OH OVERHEAD ELECTRIC
- GAS LINE
- WATER METER
- WATER VALVE
- FIRE HYDRANT
- WASTEWATER MANHOLE
- CO WASTEWATER CLEANOUT
- BFP BACKFLOW PREVENTER
- D STORM DRAIN MANHOLE
- STORM DRAIN CURB INLET
- UTILITY POLE
- GUY WIRE
- Public Open Space

**PROFILE LEGEND**



- PROP. GRADE
- - - EXISTING GRADE



WATER LINE C STA. 1+00 TO END - PLAN VIEW  
SCALE: 1" = 40'



WATER LINE C STA. 1+00 TO END - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 40' VERTICAL SCALE: 1" = 4'



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WATER LINE C PLAN &  
PROFILE STA. 1+00 TO END**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025

JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR


SHEET NO.  
**042**  
OF 069

Plot Date: September 19, 2025 @ 12:48 PM



**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	UTILITY POLE
	GUY WIRE
	PUBLIC OPEN SPACE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**OVERALL WASTEWATER PLAN**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
124884

Jordan L. Miller

JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR




SHEET NO.  
**043**  
OF 069

Plot Date: September 19, 2025 @ 12:48 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - SDR-26 STORM DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - UE/UC LINE
  - OH OVERHEAD ELECTRIC
  - GAS GAS LINE
  - ◻ WATER METER
  - ◻ WATER VALVE
  - ◻ FIRE HYDRANT
  - ◻ WWMH WASTEWATER MANHOLE
  - ◻ WWC WASTEWATER CLEANOUT
  - ◻ BFP BACKFLOW PREVENTER
  - ◻ SDM STORM DRAIN MANHOLE
  - ◻ SDI STORM DRAIN CURB INLET
  - ◻ UP UTILITY POLE
  - ◻ GW GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WASTEWATER LINE A PLAN & PROFILE STA. 1+00 TO END**

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM

JOB NO: A799

DN BY: WS


DWN BY: MD,TML

RVW BY: MVR

9-19-2025




**SHEET NO.**  
**044**  
**OF 069**

Plot Date: September 19, 2025 @ 12:47 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - 512 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - SDR-26 STORM DRAIN LINE
  - WATER LINE
  - WASTEWATER LINE
  - UE/UC LINE
  - OVERHEAD ELECTRIC
  - GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WASTEWATER LINE B PLAN &  
PROFILE STA. 1+00 TO 6+00**

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM


9-19-2025

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

**JORDAN L. MILLER**  
124884  
LICENSED PROFESSIONAL ENGINEER




SHEET NO.  
**045**  
OF 069

Plot Date: September 19, 2025 @ 12:49 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - 512 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - W WATER LINE
  - WASTEWATER LINE
  - UE/UC LINE
  - OVERHEAD ELECTRIC
  - GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY - 560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WASTEWATER LINE B PLAN & PROFILE STA. 6+00 TO END**


**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM


JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR



SHEET NO.  
**046**  
OF 069





WASTEWATER LINE C STA. 1+00 TO 7+50 - PLAN VIEW  
SCALE: 1" = 40'



WASTEWATER LINE C STA. 1+00 TO 7+50 - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 40' VERTICAL SCALE: 1" = 4'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - WATER LINE
  - W W W W WASTEWATER LINE
  - U U U U U U UC LINE
  - O H O H O H OVERHEAD ELECTRIC
  - G A S GAS LINE
  - ◻ WATER METER
  - ◉ WATER VALVE
  - ◉ FIRE HYDRANT
  - ◉ W W W W WASTEWATER MANHOLE
  - ◉ WASTEWATER CLEANOUT
  - ◉ BFP BACKFLOW PREVENTER
  - ◉ S D M S D M STORM DRAIN MANHOLE
  - ◉ S D M S D M STORM DRAIN CURB INLET
  - ◉ UTILITY POLE
  - ◉ GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**WASTEWATER LINE C PLAN &  
PROFILE STA. 1+00 TO 7+50**

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167


FIRM REG # F12469  
INFO@CIVILITUDE.COM

9-19-2025

JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
**047**  
OF 069


Plot Date: September 19, 2025 @ 12:46 PM




WASTEWATER LINE C STA. 7+50 TO END - PLAN VIEW  
SCALE: 1" = 40'

- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - - EASEMENT / SETBACK
  - - - - EXISTING CONTOUR LINE
  - - - - PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - S DRAIN LINE
  - WATER LINE
  - W W WASTEWATER LINE
  - U E / U C LINE
  - OH OVERHEAD ELECTRIC
  - GAS LINE
  - ◻ WATER METER
  - ◉ WATER VALVE
  - ◉ FIRE HYDRANT
  - ◉ W W WASTEWATER MANHOLE
  - ◉ W W WASTEWATER CLEANOUT
  - ◉ BFP BACKFLOW PREVENTER
  - ◉ S DRAIN MANHOLE
  - ◉ S DRAIN CURB INLET
  - ◉ UTILITY POLE
  - ◉ GUY WIRE
  - PUBLIC OPEN SPACE


- PROFILE LEGEND**
- PROP. GRADE
  - - - - EXISTING GRADE



WASTEWATER LINE C STA. 7+50 TO END - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 40' VERTICAL SCALE: 1" = 4'



SCALE: NTS KEY MAP



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY - 560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 75626  
**WASTEWATER LINE C PLAN & PROFILE STA. 7+50 TO END**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

SHEET NO. **048**  
OF 069



LEGEND	
	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	PROPOSED BUILDING PAD AREA
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	EXISTING OVERHEAD ELECTRIC
	UE/UC DUCTBANK
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	STORM DRAIN AREA INLET
	TRANSFORMER
	AIR CONDITIONER UNIT
	GAS METER
	ELECTRIC MANHOLE
	ELECTRIC BOX
	UTILITY POLE
	GUY WIRE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 75626

**OVERALL U.G. ELECTRIC  
 & TELECOM PLAN**

**CIVILITUDE**  
 ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR


9-19-2025  
**JORDAN L. MILLER**  
 124884

SHEET NO.  
**049**  
 OF 069

GRID N: 10206737.02  
 GRID E: 3137807.18




GRID N: 10207243.05  
 GRID E: 3139545.14

Plot Date: September 19, 2025 @ 12:47 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - WATER LINE
  - WASTEWATER LINE
  - UE/UC LINE
  - OVERHEAD ELECTRIC
  - GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**UE-UC LINE A1 PLAN & PROFILE STA. 1+00 TO 7+00**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
**050**  
OF 050


Plot Date: September 19, 2025 @ 12:49 PM





- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - WATER LINE
  - WASTEWATER LINE
  - UE/UC LINE
  - OVERHEAD ELECTRIC
  - GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE

UE-UC LINE A1 STA. 7+00 TO END - PLAN VIEW  
SCALE: 1" = 40'



UE-UC LINE A1 STA. 7+00 TO END - PROFILE VIEW  
HORIZONTAL SCALE: 1" = 40' VERTICAL SCALE: 1" = 4'



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**UE-UC LINE A1 PLAN & PROFILE**  
STA. 7+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS


503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025  
JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER




SHEET NO.  
**051**  
OF 069

Plot Date: September 19, 2025 @ 12:46 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - UE/UC LINE
  - OH OVERHEAD ELECTRIC
  - GAS LINE
  - Water Meter Symbol WATER METER
  - Water Valve Symbol WATER VALVE
  - Fire Hydrant Symbol FIRE HYDRANT
  - WWM WASTEWATER MANHOLE
  - CO WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - SDM STORM DRAIN MANHOLE
  - SDCI STORM DRAIN CURB INLET
  - UP UTILITY POLE
  - GW GUY WIRE
  - Public Open Space Symbol PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**UE-UC LINE A2 PLAN & PROFILE**  
STA. 1+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025






JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

SHEET NO.  
**052**  
OF 069

Plot Date: September 19, 2025 @ 12:50 PM



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**UE-UC LINE B PLAN & PROFILE**  
STA. 1+00 TO 10+00

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR



SHEET NO.  
**053**  
OF 069

Plot Date: September 19, 2025 @ 12:48 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - 512 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - UE/UC LINE
  - OH OVERHEAD ELECTRIC
  - GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**UE-UC LINE B PLAN & PROFILE**  
STA. 10+00 TO 14+00

**CIVILITUDE**  
ENGINEERS & PLANNERS


503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

SHEET NO.  
**054**  
OF 069

Plot Date: September 19, 2025 @ 12:48 PM





**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	UE/UC LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	UTILITY POLE
	GUY WIRE
	PUBLIC OPEN SPACE

**PROFILE LEGEND**

	PROP. GRADE
	EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 75626  
**UE-UC LINE B PLAN & PROFILE**  
STA. 14+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS


503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER




SHEET NO.  
**055**  
OF 069

Plot Date: September 19, 2025 @ 12:47 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - S12 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - UE/UC LINE
  - OH OVERHEAD ELECTRIC
  - GAS GAS LINE
  - ◻ WATER METER
  - ◻ WATER VALVE
  - ◻ FIRE HYDRANT
  - ◻ WASTEWATER MANHOLE
  - ◻ WASTEWATER CLEANOUT
  - ◻ BFP BACKFLOW PREVENTER
  - ◻ D STORM DRAIN MANHOLE
  - ◻ O STORM DRAIN CURB INLET
  - ◻ UTILITY POLE
  - ◻ GUY WIRE
  - ◻ PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**UE-UC LINE C1 PLAN & PROFILE**  
STA. 1+00 TO 6+00

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025


JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR




SHEET NO.  
**056**  
OF 069

Plot Date: September 19, 2025 @ 12:46 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - - - S12 PROPOSED CONTOUR LINE
  - ==== CURB / EDGE OF PAVEMENT
  - S12 STORM DRAIN LINE
  - W WATER LINE
  - WW WASTEWATER LINE
  - UE/UC LINE
  - OH OVERHEAD ELECTRIC
  - GAS GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WW WASTEWATER MANHOLE
  - CO WASTEWATER CLEANOUT
  - BFP BACKFLOW PREVENTER
  - S12 STORM DRAIN MANHOLE
  - S12 STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**UE-UC LINE C1 PLAN & PROFILE**  
STA. 6+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM


JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

9-19-2025

**Jordan L. Miller**  
124884

SHEET NO.  
**057**  
OF 069

Plot Date: September 19, 2025 @ 12:46 PM






**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	UE/UC LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	UTILITY POLE
	GUY WIRE
	PUBLIC OPEN SPACE

**PROFILE LEGEND**

	PROP. GRADE
	EXISTING GRADE




NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**UE-UC LINE C2 PLAN & PROFILE**  
 STA. 1+00 TO 7+00

**CIVILITUDE**  
 ENGINEERS & PLANNERS  
 503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM




9-19-2025  
 JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR  
  
 SHEET NO. **058**  
 OF 069

Plot Date: September 19, 2025 @ 12:47 PM



- LEGEND**
- BOUNDARY / RIGHT OF WAY
  - - - EASEMENT / SETBACK
  - - - S12 EXISTING CONTOUR LINE
  - 512 PROPOSED CONTOUR LINE
  - CURB / EDGE OF PAVEMENT
  - STORM DRAIN LINE
  - WATER LINE
  - WASTEWATER LINE
  - UE/UC LINE
  - OVERHEAD ELECTRIC
  - GAS LINE
  - WATER METER
  - WATER VALVE
  - FIRE HYDRANT
  - WASTEWATER MANHOLE
  - WASTEWATER CLEANOUT
  - BACKFLOW PREVENTER
  - STORM DRAIN MANHOLE
  - STORM DRAIN CURB INLET
  - UTILITY POLE
  - GUY WIRE
  - PUBLIC OPEN SPACE

- PROFILE LEGEND**
- PROP. GRADE
  - - - EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626  
**UE-UC LINE C2 PLAN & PROFILE**  
STA. 7+00 TO END

**CIVILITUDE**  
ENGINEERS & PLANNERS



503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

JOB NO: A799  
DGN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR

9-19-2025  
STATE OF TEXAS  
JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

SHEET NO.  
**059**  
OF 069

Plot Date: September 19, 2025 @ 12:49 PM





**LEGEND**

	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	UE/UC LINE
	OVERHEAD ELECTRIC GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	UTILITY POLE
	GUY WIRE
	PUBLIC OPEN SPACE

**PROFILE LEGEND**

	PROP. GRADE
	EXISTING GRADE



NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY—560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**UE-UC LINE D PLAN & PROFILE**  
 STA. 1+00 TO END

**CIVILITUDE**  
 ENGINEERS & PLANNERS

503 KENNISTON DR #4    AUSTIN, TX 78752    FIRM REG # F12469  
 PHONE 512 761 6161    FAX 512 761 6167    INFO@CIVILITUDE.COM

JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR


9-19-2025

SHEET NO.  
**060**  
 OF 069

Plot Date: September 19, 2025 @ 12:47 PM



LEGEND	
	BOUNDARY / RIGHT OF WAY
	EASEMENT / SETBACK
	EXISTING CONTOUR LINE
	PROPOSED CONTOUR LINE
	CURB / EDGE OF PAVEMENT
	PROPOSED BUILDING PAD AREA
	STORM DRAIN LINE
	WATER LINE
	WASTEWATER LINE
	OVERHEAD ELECTRIC
	GAS LINE
	WATER METER
	WATER VALVE
	FIRE HYDRANT
	WASTEWATER MANHOLE
	WASTEWATER CLEANOUT
	BACKFLOW PREVENTER
	STORM DRAIN MANHOLE
	STORM DRAIN CURB INLET
	STORM DRAIN AREA INLET
	TRANSFORMER
	AIR CONDITIONER UNIT
	GAS METER
	ELECTRIC MANHOLE
	ELECTRIC BOX
	UTILITY POLE
	GUY WIRE



NO.	DATE	REVISION / CORRECTION / ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
 1001 E UNIVERSITY AVE., GEORGETOWN, TX 75626

**OVERALL GAS DISTRIBUTION PLAN**

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
 PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM














JOB NO: A799  
 DGN BY: WS  
 DWN BY: MD,TML  
 RVW BY: MVR

9-19-2025

SHEET NO.  
**061**  
 OF 069

Plot Date: September 19, 2025 @ 12:47 PM





NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**PAVING & DRAINAGE DETAILS-1**

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM

9-19-2025
















JORDAN L. MILLER  
124884  
LICENSED PROFESSIONAL ENGINEER

Jordan L. Miller

JOB NO: A799  
DN BY: WS  
DWN BY: MD,TML  
RVW BY: MVR









SHEET NO.  
063  
OF 069

Plot Date: September 19, 2025 @ 12:50 PM



Plot Date: September 19, 2025 @ 12:50 PM

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626			
PAVING & DRAINAGE DETAILS-2			
503 KENNISON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	
		FIRM REG # F12469 INFO@CIVILITUDE.COM	
9-19-2025			
JOB NO: A799	DGN BY: WS	DWN BY: MD,TML	RJV BY: MVR
			SHEET NO. 064 OF 069



**SAFETY END TREATMENT FOR 12" DIA TO 72" DIA PIPE CULVERTS TYPE II - PARALLEL DRAINAGE SETP-PD**

NO. DATE REVISION/CORRECTION/ADDENDUM SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**PAVING & DRAINAGE DETAILS-3**

**CIVILITUDE ENGINEERS & PLANNERS**

503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

















9-19-2025

JORDAN L. MILLER  
124884

SHEET NO. 065 OF 069

PROJECT NUMBER: 2025-\_\_\_CON

Plot Date: September 19, 2025 @ 12:48 PM




NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET
SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT 1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626			
<b>UTILITY DETAILS-1</b>			
<b>CIVILITUDE ENGINEERS &amp; PLANNERS</b>			
503 KENNISON DR #4 PHONE 512 761 6161		AUSTIN, TX 78752 FAX 512 761 6167	
JOB NO: A799		FIRM REG # F12469 INFO@CIVILITUDE.COM	
DGN BY: WS		9-19-2025	
DWN BY: MD,TML			
RW BY: MVR		SHEET NO. 066 OF 069	

Plot Date: September 19, 2025 @ 1:43 PM




Plot Date: September 19, 2025 @ 12:50 PM



PERPENDICULAR OR ANGLED ACCESSIBLE PARKING SPACE DIMENSIONS

**GENERAL NOTES:**

- All paved accessible parking space limit lines shall be 4" solid white lines.
- Paved accessible parking spaces must include a white International Symbol of Accessibility applied conspicuously on the surface in a color that contrasts the pavement. A blue background with white border may supplement the symbol for additional contrast.
- The words "NO PARKING" must be applied on any access aisle adjacent to the parking space. The words must be white, applied:
  - in all capital letters,
  - centered within each access aisle adjacent to the parking space.
- RESERVED PARKING (R7-8T) sign including the International Symbol of Accessibility:
  - shall be REQUIRED for each accessible parking space.
  - shall NOT be placed between two accessible parking spaces.
  - shall NOT be placed in a location that restricts movement of wheelchairs within the adjacent sidewalk.
  - shall have a mounting height of 7 feet to the bottom of the sign.
- A sign identifying the consequences of parking illegally in a paved accessible parking space. Must:
  - at a minimum state "VIOLATORS SUBJECT TO FINE AND TOWING" (Plate) (R7-8aPT).
  - be mounted on a pole, post, wall or freestanding board.
  - be no more than eight inches (8") below sign R7-8T a sign required by the Texas Accessibility Standards, 502.6.
  - be installed so that the bottom edge of the sign is no lower than 48 inches and no higher than 80 inches above the ground level.
- Signs identifying van parking spaces shall contain the designation "VAN ACCESSIBLE" (R7-8V) Signs shall be 60 inches minimum above the ground level measured to the bottom of the sign.
- Perpendicular or angled parking spaces shall be 8 feet wide minimum with an access aisle 8 feet minimum wide (van accessible). Two parking spaces are permitted to share a common access aisle.
- Access aisles shall be at street level, extend the full length of the parking space they serve, follow ADA surface requirements, and marked to discourage parking in the access aisle. Curb ramps shall connect the access aisle to the adjacent pedestrian access route. Curb ramps shall not be located within the access aisle.
- International Symbol of Accessibility Parking Space Marking and sign details can be found in the Standard Highway Sign Designs for Texas (SHSD) at the following website: <http://www.txdot.gov/>



Detail A


ALUMINUM SIGN BLANKS THICKNESS	
Source Feet	Minimum Thickness
Less than 7.5	0.080
7.5 to 15	0.100
Greater than 15	0.125

DEPARTMENTAL MATERIAL SPECIFICATIONS	
ALUMINUM SIGN BLANKS	DMS-7110
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
SIGN FACE MATERIALS	DMS-8300


**PAVEMENT MARKINGS AND SIGNING FOR ACCESSIBLE PARKING**

**PM (AP) - 21**


FILE NO.	DATE	BY	CHKD	APPD	JOB	REVISION
11-18-01	7/20/01	JM	MS	MS	SD21	1




EDGE LINE AND LANE LINES ONE-WAY ROADWAY WITH OR WITHOUT SHOULDERS




TYPICAL TWO-LANE, TWO-WAY PAVEMENT MARKINGS THROUGH INTERSECTIONS




CENTERLINE AND LANE LINES FOUR LANE TWO-WAY ROADWAY WITH OR WITHOUT SHOULDERS




TYPICAL MULTI-LANE, TWO-WAY PAVEMENT MARKINGS THROUGH INTERSECTIONS



TWO LANE TWO-WAY ROADWAY WITH OR WITHOUT SHOULDERS



YIELD LINES



FOUR LANE DIVIDED ROADWAY CROSSOVERS

**NOTES**


- Where divided highways are separated by median widths of 30 feet or more, median openings shall be signed as two separate intersections. Each median opening has two width measurements, with one measurement for each approach. The narrow median width will be the controlling width to determine if signs are required. Yield signs are the typical intersection control. Stop signs and stop bars are optional as determined by the Engineer.
- Install median striping (double yellow centerlines and stop lines/yield lines) when a 50' or greater median centerline can be placed. Stop lines shall only be used with stop signs. Yield lines shall only be used with yield signs.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.

**GENERAL NOTES**

- Edge line striping shall be as shown in the plans or as directed by the Engineer. The edge line should not be placed less than 6 inches from the edge of pavement. This distance may vary due to pavement leveling or other conditions. Edge lines are not required in curb and gutter sections of roadways.
- The traveled way includes only that portion of the roadway used for vehicular travel. It does not include the parking lanes, sidewalks, berms and shoulders. The traveled ways shall be measured from the center of edge line to the center of edge line of a two lane roadway.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.




GUIDE FOR PLACEMENT OF STOP LINES, EDGE LINE & CENTERLINE

**TYPICAL STANDARD PAVEMENT MARKINGS**

**PM (1) - 22**

FILE NO.	DATE	BY	CHKD	APPD	JOB	REVISION
11-18-01	7/20/01	JM	MS	MS	SD22	1



FRONT VIEW

**GENERAL NOTES FOR THIN WALL TUBE TYPE SIGN SUPPORT:**

- THE BASE SOCKET IS FORMED FROM 2 7/8" O.D. X 12 GAUGE GALVANIZED PIPE.
- THE WEDGE IS FORMED FROM 11 GAUGE STEEL GALVANIZED PER ASTM A525.
- THE SIGN POST IS 2.375" O.D. X 0.095" THIN WALL STEEL TUBING.
- STEEL SUPPORTS SHALL BE MADE FROM NEW MATERIAL AND SHALL BE CORROSION RESISTANT. STEEL SUPPORTS SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM DESIGNATIONS A123 OR A525 (G-90 OR BETTER).
- SUPPORTS SHALL BE STRAIGHT WITHIN 1/4" PER 5 FEET OF LENGTH AND SHALL HAVE A SMOOTH, UNIFORM FINISH FREE FROM DEFECTS AFFECTING STRENGTH OR APPEARANCE. ANY BOLT HOLES AND SHEARED ENDS SHALL BE FREE FROM BURRS. BASES OF MULTISECTION SUPPORTS SHALL NOT EXTEND MORE THAN 5 INCHES ABOVE GROUND WHEN INSTALLED.
- BOLTS, NUTS, SCREWS, WASHERS AND OTHER MISCELLANEOUS HARDWARE SHALL BE GALVANIZED IN ACCORDANCE TO ASTM DESIGNATION: A153 CLASS C OR D, OR 306SS CLASS 50.
- BARRICADE SUPPORTS SYSTEMS USED ON THIS SHEET MAY BE SUITABLE FOR ONLY CERTAIN SOIL TYPES. THE CONTRACTOR IS RESPONSIBLE FOR SELECTING THE APPROPRIATE SUPPORT SYSTEM FOR SOIL CONDITIONS ON EACH PROJECT.
- ALL BARRICADES TO BE IN CONFORMANCE WITH THE CURRENT EDITION OF THE TEXAS MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD).
- RAIL-HIGH DENSITY POLYETHYLENE OR HOLLOW PROFILE PLASTIC LUMBER AND SHEETING SHALL BE RETROREFLECTIVE, INCLUDING SPLICE BLOCKS.


The Architect/Engineer assumes responsibility for appropriate use of this standard.

**CITY OF GEORGETOWN CONSTRUCTION STANDARDS AND DETAILS**

**PERMANENT END-OF-ROAD BARRICADE**

ADOPTED 6/21/2006

SD21



PROFILE

**VIEW F-F**

\* FRP PIPE OR 0.095" THIN WALL TUBING.

\*\* FOOTING SHALL BE REMOVED AND BACKFILLED WHEN BARRICADE IS REMOVED.


The Architect/Engineer assumes responsibility for appropriate use of this standard.

**CITY OF GEORGETOWN CONSTRUCTION STANDARDS AND DETAILS**

**UNIVERSAL ANCHOR SYSTEM**

ADOPTED 6/21/2006

SD23



TYPICAL ASSEMBLY

**VIEW G-G**

\* PLASTIC INSERT MUST BE USED WITH 1/16" THIN WALL TUBING.


The Architect/Engineer assumes responsibility for appropriate use of this standard.

**CITY OF GEORGETOWN CONSTRUCTION STANDARDS AND DETAILS**

**POX-LOC (BREAKAWAY FOUNDATION)**

ADOPTED 6/21/2006

SD24



**NOTES:**

- 7-FOOT MIN. HEIGHT FROM GROUND TO BOTTOM OF SIGN.
- ALL SIGNS TO BE IN CONFORMANCE WITH THE CURRENT EDITION OF THE TEXAS MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD).
- ALL SIGNAGE SHEETINGS SHALL BE HIGH-INTENSITY "3M" SHEETING.

The Architect/Engineer assumes responsibility for appropriate use of this standard.

**CITY OF GEORGETOWN CONSTRUCTION STANDARDS AND DETAILS**

**STANDARD STREET SIGN DETAIL**

REVISED 1/14/2014 WRB

ADOPTED 6/21/2006 TRB

SD25

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

**SIGN & STRIPING DETAILS-1**

**CIVILITUDE ENGINEERS & PLANNERS**




503 KENNISTON DR #4 AUSTIN, TX 78752 FIRM REG # F12469  
PHONE 512 761 6161 FAX 512 761 6167 INFO@CIVILITUDE.COM

9-19-2025



JORDAN L. MILLER  
124884

SHEET NO. 068 OF 069

DISCLAIMER: This drawing is prepared by the engineer and is not to be used for any purpose other than that for which it is intended. The engineer assumes no responsibility for any damage resulting from the use of this drawing for any purpose other than that for which it is intended.



DISCLAIMER: This drawing is prepared by the engineer and is not to be used for any purpose other than that for which it is intended. The engineer assumes no responsibility for any damage resulting from the use of this drawing for any purpose other than that for which it is intended.



DISCLAIMER: This drawing is prepared by the engineer and is not to be used for any purpose other than that for which it is intended. The engineer assumes no responsibility for any damage resulting from the use of this drawing for any purpose other than that for which it is intended.

Plot Date: September 19, 2025 @ 12:50 PM

NO.	DATE	REVISION/CORRECTION/ADDENDUM	SHEET

SOUTHWESTERN UNIVERSITY-560 DEVELOPMENT  
1001 E UNIVERSITY AVE., GEORGETOWN, TX 78626

## SIGN & STRIPING DETAILS-2

**CIVILITUDE**  
ENGINEERS & PLANNERS

503 KENNISTON DR #4  
PHONE 512 761 6161

AUSTIN, TX 78752  
FAX 512 761 6167

FIRM REG # F12469  
INFO@CIVILITUDE.COM

9-19-2025

JOB NO: A799

DGN BY: WS

DWN BY: MD,TML

RVW BY: MVR

SHEET NO.  
**069**  
OF 069