8570 River Road

A project by: 8570 River Road, LLC

Water Pollution Abatement Plan Report



New Braunfels, Texas February 2023



Prepared by:

410 N. Seguin Ave. New Braunfels, TX 78130 HMTNB.COM 830.625.8555 • FAX: 830.625.8556 TBPE FIRM F-10961



Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with 30 TAC 213.

Administrative Review

- 1. <u>Edwards Aquifer applications</u> must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.
 - To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: http://www.tceq.texas.gov/field/eapp.
- 2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
- 3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
- 4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.
 - An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.
- 5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
- 6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the Instructions to Geologists (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.

- 2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.
- 3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or if not withdrawn the application will be denied and the application fee will be forfeited.
- 4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available to you:

- You can withdraw your application, and your fees will be refunded or credited for a resubmittal.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the effected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: 8570 River Road				2. Regulated Entity No.:				
3. Customer Name: 8570 River Road, LLC				4. Customer No:				
5. Project Type: (Please circle/check one)	New	Modif	icatior	1	Exter	nsion	Exception	
6. Plan Type: (Please circle/check one)	WPAP CZP	SCS	UST	AST	T EXP EX		Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Residential (Non-residential			8. Sit	e (acres):	0.7380	
9. Application Fee:	\$3,000	10. Pe	ermar	nent E	3MP(s):	Vegetative Filte	er Strip
11. SCS (Linear Ft.):	N/A	12. AST/UST (No			o. Tar	. Tanks): N/A		
13. County:	Comal	14. Watershed:					Guadalupe Rive	er

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceg.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region				
County:	Hays	Travis	Williamson	
Original (1 req.)	_	_	_	
Region (1 req.)	_	_	_	
County(ies)		_		
Groundwater Conservation District(s)	Edwards Aquifer AuthorityBarton Springs/ Edwards AquiferHays TrinityPlum Creek	Barton Springs/ Edwards Aquifer	NA	
City(ies) Jurisdiction	AustinBudaDripping SpringsKyleMountain CitySan MarcosWimberleyWoodcreek	AustinBee CavePflugervilleRollingwoodRound RockSunset ValleyWest Lake Hills	AustinCedar ParkFlorenceGeorgetownJerrellLeanderLiberty HillPflugervilleRound Rock	

	Sa	an Antonio Region			
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)		_X_			
Region (1 req.)		_X_			
County(ies)		_X_			
Groundwater Conservation District(s)	Edwards Aquifer Authority Trinity-Glen Rose	_X_Edwards Aquifer Authority	Kinney	EAA Medina	EAA Uvalde
City(ies) Jurisdiction	Castle HillsFair Oaks RanchHelotesHill Country VillageHollywood ParkSan Antonio (SAWS)Shavano Park	BulverdeFair Oaks RanchGarden Ridge _X_New BraunfelsSchertz	NA	San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is hereby submitted to TCEQ for admi	ne application is complete and accurate. This ministrative review and technical review.
Jessica Calhoun, P.E., CFM	
Print Name of Customer/Authorized Agent	
Signature of Customer/Authorized Agent	02/24/2023
Signature of Customer/Authorized Agent	Date

Date(s)Reviewed:	Date Administratively Complete:		
Received From:	Correct Number of Copies:		
Received By:	Distribu	tion Date:	
EAPP File Number:	Complex	C:	
Admin. Review(s) (No.):	No. AR Rounds:		
Delinquent Fees (Y/N):	Review Time Spent:		
Lat./Long. Verified:	SOS Customer Verification:		
Agent Authorization Complete/Notarized (Y/N):	Fee	Payable to TCEQ (Y/N):	
Core Data Form Complete (Y/N):	Check: Signed (Y/N): Less than 90 days old (Y/N):		
Core Data Form Incomplete Nos.:			

General Information Form

Print Name of Customer/Agent: Jessica Calhoun, P.E., CFM

Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **General Information Form** is hereby submitted for TCEQ review. The application was prepared by:

Date: 02/24/2023 Signature of Customer/Agent: posice Calhour **Project Information** Regulated Entity Name: 8570 River Road 2. County: Comal 3. Stream Basin: Guadalupe River 4. Groundwater Conservation District (If applicable): Edwards Aquifer Authority 5. Edwards Aquifer Zone: X Recharge Zone Transition Zone 6. Plan Type: AST **WPAP** UST SCS Modification **Exception Request**

7.	Customer (Applicant):	
	Contact Person: Kellie Jenks Entity: 8570 River Road Mailing Address: 1001 McKinney Street, Suite 525 City, State: Houston, Texas Telephone: 713-876-1372 Email Address: kjenks@trccapitalpartners.com	Zip: <u>77002</u> FAX:
8.	Agent/Representative (If any):	
	Contact Person: Jessica Calhoun, P.E., CFM Entity: HMT Engineering & Surveying Mailing Address: 290 S. Castell Avenue, Ste 100 City, State: New Braunfels, Texas Telephone: 210-255-7873 Email Address: jessica.calhoun@hmtnb.com	Zip: <u>78132</u> FAX: <u>830-625-8556</u>
9.	Project Location:	
	 ☐ The project site is located inside the city limits of the project site is located outside the city limits jurisdiction) of New Braunfels. ☐ The project site is not located within any city's 	s but inside the ETJ (extra-territorial
10.	The location of the project site is described belonged and clarity so that the TCEQ's Regional st boundaries for a field investigation.	
	Beginning at TCEQ San Antonio regional office, Road, turn right onto Wenzel Road, turn lef on FM 3009 N. Follow Nacogdoches for 2.4 Road N for 5.0 miles before turning right or Valley Road, left onto TX-46 W, right onto F onto River Road and the site will be on the	t onto Topperwein Road, then turn right miles then turn right onto Schoenthal ato FM 1863 E. Turn left on Mission Hueco Springs Loop Road, and then left
11.	Attachment A – Road Map. A road map showing project site is attached. The project location and the map.	S .
12.	Attachment B - USGS / Edwards Recharge Zone USGS Quadrangle Map (Scale: 1" = 2000') of the The map(s) clearly show:	
	 ☑ Project site boundaries. ☑ USGS Quadrangle Name(s). ☑ Boundaries of the Recharge Zone (and Tran ☑ Drainage path from the project site to the boundaries. 	

	The TCEQ must be able to inspect the project site or the application will be returned. Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment.
	Survey staking will be completed by this date:
	Attachment C – Project Description. Attached at the end of this form is a detailed narrative description of the proposed project. The project description is consistent throughout the application and contains, at a minimum, the following details:
	 ✓ Area of the site ✓ Offsite areas ✓ Impervious cover ✓ Permanent BMP(s) ✓ Proposed site use ✓ Site history ✓ Previous development ✓ Area(s) to be demolished
15. Exis	ting project site conditions are noted below:
	 □ Existing commercial site □ Existing industrial site □ Existing residential site □ Existing paved and/or unpaved roads □ Undeveloped (Cleared) □ Undeveloped (Undisturbed/Uncleared) □ Other:
Proh	ibited Activities
	I am aware that the following activities are prohibited on the Recharge Zone and are not proposed for this project:
	(1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
	(2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
	(3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
	(4) The use of sewage holding tanks as parts of organized collection systems; and
	(5) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
	(6) New municipal and industrial wastewater discharges into or adjacent to water in the


state that would create additional pollutant loading.

- 17. 🖂 I am aware that the following activities are prohibited on the Transition Zone and are not proposed for this project:
 - (1) Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);
 - (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
 - (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

Standards which are defined in §330.41 (b), (c), and (d) or this title.
Administrative Information
18. The fee for the plan(s) is based on:
 For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur. For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines. For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems. A request for an exception to any substantive portion of the regulations related to the protection of water quality. A request for an extension to a previously approved plan.
19. Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:
 ☐ TCEQ cashier ☐ Austin Regional Office (for projects in Hays, Travis, and Williamson Counties) ☐ San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)
20. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
21. No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.



Texas Commission-Environmental, 14250 Judson Drive 27.3 miles, 44 min Rd, San Antonio, TX 78233 to 8570 River Rd, New Braunfels, TX 78132



200 ft **■** Map data ©2023 Google

Texas Commission-Environmental 14250 Judson Rd, San Antonio, TX 78233

Continue to Judson Rd


Cont	inue	e to Juason Ka	
1	1.	Head southeast toward Judson Rd	16 sec (200 ft)
\rightarrow	2.	Turn right toward Judson Rd	115 ft
	_		85 ft
		cogdoches Rd and Schoenthal Rd N to d in Comal County	Mission 25 min (16.6 mi)
\rightarrow	3.	Turn right onto Judson Rd	23 111111 (10.0 1111)
·	_	Pass by AutoZone Auto Parts (on the	right in 0.6
			0.6 mi
\hookrightarrow	4.	Turn right onto Nacogdoches Rd	
	0	Pass by Wendy's (on the left in 1.5 mi)	
←	5.	Turn left onto FM3009 N	6.0 mi

2.4 mi

\rightarrow	6.	Turn right onto Schoenthal Rd N	
\rightarrow	7.	Turn right onto FM1863 E	5.0 mi
ᠳ	8.	Turn left onto Mission Valley Rd	2.6 mi 3 min (1.7 mi)
Follo	w H	ueco Springs Loop Rd and River Rd	17 in (0.0 i)
←	9.	Turn left onto TX-46 W	17 min (8.9 mi)
\rightarrow	10.	Turn right onto Hueco Springs Loop	0.3 mi Rd
←	11.	Turn left onto River Rd	3.3 mi
			5.3 mi
ightharpoons	A	Turn right Restricted usage road Destination will be on the left	
			8 sec (102 ft)

8570 River Rd

New Braunfels TX 78132



USGS MAP - SATTLER QUAD

8570 RIVER ROAD

NEW BRAUNFELS, TEXAS





290 S. Castell Avenue, Ste. 100 New Braunfels, TX 78130 (830) 625-8555 TBPE-FIRM F-10961 TBPLS FIRM 10153600

GENERAL INFORMATION FORM ATTACHMENT C Project Description

The proposed 8570 River Road project is located 8570 River Road, in New Braunfels, Texas. The site is located within the City of New Braunfels Extraterritorial Jurisdiction (ETJ). The site is currently a 0.7380-acre residential site with 5,113 square feet (0.117 acres) of impervious cover created by a main residential home and asphalt driveway, these improvements were built in 1938 before TCEQ Edwards Aquifer Program. Additionally, there are currently 1,104 square feet (0.025 acres) of additional rooftop, 1,680 square feet (0.039 acres) of concrete, and 1,859 square feet (0.043 acres) of decking that have not previously been permitted. A Water Pollution Abatement Plan has not previously been recorded for this property. The proposed conditions increase the impervious cover by 400 square feet to 5,043 square feet (0.116 acres) or 15.7% at full development.

The proposed 8570 River Road project is a commercial cabin rental site with amenities located near the Guadalupe River. The proposed site improvements include the construction of two elevated tiny home structures that will cover 200 square feet each. The existing wood and metal sheds shown on the survey will be demolished. The tiny homes will be elevated on pier and beam approximately one foot above the ground. When completed there will be 1,504 square feet (0.035 acres) of rooftops. No offsite area flows to the site, the site is south of River Road which intercepts the flow. Therefore, these areas are not used in our water quality calculations. The flow onsite sheet flows towards the Guadalupe River. A 50 feet natural vegetative filter strip is the proposed Best Management Practice.

The construction will be completed in one phase with 8570 River Road being the permitted entity that will operate the proposed site.

Geologic Assessment

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: Matt Anding	Telephone: <u>832-641-8143</u>
Date: <u>09/16/2022</u>	Fax:
Representing: <u>Anding Environmental Consulting, LL</u> registration number)	(Name of Company and TBPG or TBPE
Regulated Entity Name: TRC Capital Partners	MATTHEW ANDING: GEOLOGY 11654 CENSE ONAL & GEO
Project Information	will do
1. Date(s) Geologic Assessment was performed: <u>Se</u>	ptember 10, 2022
2. Type of Project:	
WPAP SCS Location of Project:	☐ AST ☐ UST
Recharge Zone Transition Zone Contributing Zone within the Transition Zone	

4. Attachment A - Geologic Assessment Table. Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached. 5. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map. Table 1 - Soil Units, Infiltration * Soil Group Definitions (Abbreviated) **Characteristics and Thickness** A. Soils having a high infiltration rate when thoroughly wetted. Soil Name Group* Thickness(feet) B. Soils having a moderate В 5' BoB infiltration rate when thoroughly wetted. C. Soils having a slow infiltration rate when thoroughly wetted. D. Soils having a very slow infiltration rate when thoroughly wetted. 6. Attachment B – Stratigraphic Column. A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column. 7. Attachment C – Site Geology. A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached. 8. Attachment D – Site Geologic Map(s). The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1": 400' Applicant's Site Plan Scale: 1" = 100' Site Geologic Map Scale: 1" = 100' Site Soils Map Scale (if more than 1 soil type): 1" = 100' 9. Method of collecting positional data: Global Positioning System (GPS) technology. Other method(s). Please describe method of data collection: 10. The project site and boundaries are clearly shown and labeled on the Site Geologic Map. 11. Surface geologic units are shown and labeled on the Site Geologic Map.

12. 🔼	investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
	Geologic or manmade features were not discovered on the project site during the field investigation.
13. 🖂	The Recharge Zone boundary is shown and labeled, if appropriate.
	known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If olicable, the information must agree with Item No. 20 of the WPAP Application Section.
	There are 1 (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.) The wells are not in use and have been properly abandoned. The wells are not in use and will be properly abandoned. The wells are in use and comply with 16 TAC Chapter 76. There are no wells or test holes of any kind known to exist on the project site.
	There are no wens or test noies or any kind known to exist on the project site.

Administrative Information

15. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

GEOLOGIC ASSESSMENT ATTACHMENT A - GEOLOGIC ASSESSMENT TABLE

LOCATION				FEATURE CHARACTERISTICS										TEVALUATION		PHYSICAL SETTIN				
36	18.1	101	2A	28	3		4		- 5	5A	6	7	BA.	88	9		10		11	12
TARRETO	ENTRINE	CONGRIDE	FEATURE I'M	Ponts	FORMATION	Descri	SIONS	reet)	file (see E.S.)	8	DEMSITY	APERTURE (FEET)	WO.	RELATIVE REPLEMATION PATE	TOTAL	3000	strytty	CATOHIN	ENT AREK REID	Torocatere
						X	Y	ż		10						<40	≥40	<1.6	≥1.6	
MB1	29.799627	-98.147789	MB	30	Qt	6	6	?	12	-	1.5	+	1400	5	35	1		1		Hillside
MB2	29.799303	-98.147507	MB	30	Qt	8	8	?		×	*	+:	-	5	35	1		1		Hillside

* DAT	UM: NAD_1963_StatePlane_Texas_South_Central_I	IPS 4204
2A TY	PE TYPE	2B POINTS
C	Cave	30
SC	Solution cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
0	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30

	BA INFILLING
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
0	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field.

My signification of the My significant of the My significa

Date: 09/16/2022

TCEQ-0585-Table (Rev. 10-01-04)

GEOLOGIC ASSESSMENT ATTACHMENT B - STRATIGRAPHIC COLUMN

SITE STRATIGRAPHY (Edwards Aquifer)


Group, Hydro-Thickness Field Cavern Porosity/ Hydrogeologic Lithology formation, logic identification development permeability type subdivision (feet) or member function CU 50 - 60Blue-green to Fossiliferous; None None/primary upper Del Rio Clay yellow-brown clay llymatogyra arietina confining unit Boxwork vugs; light tan, Laterally extensive; Mudstone to Many caves; Cyclic and 0 - 70AQ packstone; miliolid both fabric and not marine massive: some Toucasia. might be fabric/water-yielding; grainstone; chert Caprinid, and associated members, with earlier one of the most porous Chondrodonta undivided and permeable; karst (4) essentially absent in development Travis County Formation Crystalline limestone; Light-gray, bioturbated iron-Extensive Majority not fabric/ 30 - 80Leached and AO III stained beds separated by one of the most porous collapsed mudstone to wackelateral Person members, stone to miliolid massive limestone beds; development; and permeable grainstone; chert; Toucasia, Chondrodonta large rooms undivided collapsed breccia Light-tan, dense, Wispy iron-oxide stains; Not fabric/ IV Regional CU 20 - 30None; only low permeability; argillaceous Pleuromya knowltoni, vertical dense Edwards aquifer Edwards Group vertical barrier mudstone Ceratostreon texanum fracture member enlargement (3) Not fabric/ Light-gray, miliolid White crossbedded Few caves V Grainstone AQ 45 - 60grainstone; grainstone; Toucasia, recrystallization member reduces permeability Turritella, and mudstone to (2) Chondrodonta wackestone: chert Probably Majority fabric/ Boxwork voids, with AQ 65 - 75Light-gray, crystalline VI Kirschberg limestone; chalky neospar and travertine extensive one of the most porous evaporite frame; Cladophyllia and and permeable mudstone; chert cave member development Turritella (1) Massively bedded, light Mostly not fabric; some Caves related VII Dolomitic AQ 110 - 150Mudstone to gray, Toucasia to structure or bedding-plane fabric/ grainstone; member water-yielding; locally crystalline abundant; Dictvoconus bedding (1) walnutensis, Caprinid permeable limestone; chert planes Shaly, fossiliferous, Massive, nodular and Fewlcaves Fabric/low permeability VIII Basal nodular Karst 45 - 60nodular limestone; mottled; Ceratostreon AQ: member texanum, Dictvoconus not karst mudstone: miliolid grainstone CU walnutensis, and Texigryphaea Upper member of the Yellowish-tan, thinly Stair-step topography; Some water production CU: 350 - 500Some surface Lower at evaporite beds/ confining Glen Rose Limestone evaporite bedded limestone alternating limestone cave beds and marl and marl development relatively impermeable unit

AO

STRATIGRAPHIC COLUMN

GEOLOGIC ASSESSMENT ATTACHMENT C - SITE GEOLOGY





Geologic Assessment

8570 River Road New Braunfels, Comal County, Texas

Prepared for:

8570 River Road, LLC & TRC Capital Partners 1001 McKinney St Suite 525 Houston, TX 77002

Prepared by:



Anding Environmental Consulting, LLC. 925 Lauren Street New Braunfels, TX 78130

September 2022




Table of Contents

1.0	INTRODUCTION AND PURPOSE									
	1.1	INTRODUCTION								
	1.2	PROJECT DESCRIPTION								
2.0	METHODOLOGY									
	2.1	RESEARCH INFORMATION								
	2.2	FIELD SURVEY								
	2.3	DATA GAPS								
	2.4	LIMITATIONS OF ASSESSMENT								
3.0	NARRATIVE DESCRIPTION OF SITE GEOLOGY									
2.0	3.1 SITE CHARACTERIZATION									
	3.2	SITE GEOLOGY								
	3.3	SITE SOILS								
	3.4	SITE ASSESSMENT								
4.0	SUM	MARY6								
5.0	REFE	REFERENCES								
List o	of Tab	les								
Table	3-1	Site Soils								
Attac	chmen	ts								
Attach	ment A	Geologic Assessment Table								
Attach	ment B	Stratigraphic Column								
Attach	ment C	Site Geology and Geologic Assessment								
Attach	ment D	Site Geologic Maps								
Attach	ment E	Photo Log								

Acronyms

BMP Best Management Practices

EAPP Edwards Aquifer Protection Plan

FEMA Federal Emergency Management Administration

GPS Global Positioning System

TCEQ Texas Commission on Environmental Quality

USDA United States Department of Agriculture

USGS United States Geological Survey

1.0 INTRODUCTION AND PURPOSE

1.1 Introduction

This Geologic Assessment was prepared in general accordance with to 30 TAC §213.5(b)(3), effective September 01, 2003, Texas Commission on Environmental Quality (TCEQ) requirements for regulated developments within the Edwards Aquifer Recharge Zone, and the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04). Per TCEQ guidance, a proposed project on the Site for future development requires a Geologic Assessment to identify all potential pathways for contaminant movement to the Edwards Aquifer and provide sufficient geologic information so that the appropriate Best Management Practices (BMPs) can be proposed in the Edwards Aquifer Protection Plan (EAPP). This Geologic Assessment has been prepared by a Texas Board of Professional Geoscientists licensed geologist, Mr. Matt Anding, P.G.

1.2 Project Description

The Site is located at 8570 River Road, New Braunfels, TX 78132. The center of the Site is located at 29°47'58.44"N Latitude and 98° 8'52.13"W Longitude (WGS 84), and the Site is ~1.06 acres in size. The Site is currently developed with a residential home, multiple vacation rental cabins, and a river-front concession stand and bar. The property location is depicted on **Figure D-1**. A proposed project plans to modify existing vacation rental cabins.

2.0 METHODOLOGY

2.1 Research Information

The Geologic Assessment was performed by Matt Anding, P.G., with Anding Environmental Consulting, LLC (Anding Environmental) on September 10, 2022. Anding Environmental first conducted a desktop analysis of the geology of the area surrounding the Site. The research included, but was not limited to, the Geologic Atlas of Texas, Federal Emergency Management Agency (FEMA) maps, Edwards Aquifer Recharge Zone Maps, USGS 7.5 Minute Quadrangle Maps, Bureau of Economic Geology online digital data, historic aerials and topographic maps, and the United States Department of Agriculture (USDA) Soil Survey of Comal County, Texas.

2.2 Field Survey

After reviewing the available information, a field investigation was performed to identify any geologic or man-made potential recharge features. A transect spacing of approximately 25-50 feet, or less depending on Site vegetation, was used to inspect the Site. A 2021 aerial photograph, in conjunction with a handheld sub-meter Trimble GeoXH Global Positioning System (GPS), was used to navigate on the property and search for potential recharge features, as recommended in the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04). The Geologic Assessment Form, Stratigraphic Column, and the Geologic Assessment Table have been filled with the appropriate information for this Site and are included in this report. Special attention was given to the mapped faults, bedrock outcroppings, and other structural features mapped in the area.

2.3 Data Gaps

No data gaps were incurred during the desktop analysis or field reconnaissance.

2.4 Limitations of Assessment

No Geologic Assessment can wholly eliminate uncertainty regarding potential pathways for contaminant movement to the Edwards Aquifer in connection with a property. Performance of a Geologic Assessment in accordance with TCEQ-0585 instructions is intended to reduce, but cannot eliminate, uncertainty regarding the potential for surficial points of infiltration in connection with a property, and the TCEQ recognizes reasonable limits of time and cost.

Anding Environmental assumes no responsibility for the discovery of any surficial or subsurface points of infiltration, caves, solution cavities or enlarged fractures/faults, sinkholes, or any other karst features not observed during this Geologic Assessment. Anding Environmental does not have any responsibility with regard to the Client's compliance with or fulfillment of its obligation under any law, ordinance, or regulation prevailing at any of the observed locations.

3.0 NARRATIVE DESCRIPTION OF SITE GEOLOGY

3.1 Site Characterization

The Site is a long narrow parcel located along the Guadalupe River valley and is currently developed with a residential home, multiple vacation rental cabins, and a river-front concession stand and bar. The northern portion of the Site rests on the edge of a stream terrace, which then slopes down to another relatively gently sloping terrace, before sloping down the river at the southern portion of the property. The entirety of the Site is developed with either structures or maintained lawn and driveway/walkways.

The Site extends from River Road at the northern property boundary down to the Guadalupe River at the southern property boundary. The Site is bordered by residential/vacation rental properties to the east and west.

The Site is located within the Guadalupe River valley and is positioned along stream terrace topography. Site topography consists of a relatively flat terrace at the top by River Road, a middle bench terrace in the center of the Site, then an additional slope down to the river. The highest elevation is approximately 724 ft amsl at the northern Site corner. The lowest elevation is approximately 680 ft amsl at the southern Site boundary. Surface water tends to sheetflow to the southeast towards the Guadalupe River.

The Site vegetation consists of maintained lawns along with pecan trees and bald cypress trees along the river banks.

3.2 Site Geology

Per the TCEQ Edwards Aquifer Program GIS dataset, the entire Site is located within the Edwards Aquifer Recharge Zone. A map of the Site and Edwards Aquifer Zones is presented as **Figure D-3**.

The following resources were most utilized in mapping the Site geology:

- Digital Geologic Map Database for the State of Texas (USGS)
- 1982 Geologic Atlas of Texas, San Antonio Sheet (Bureau of Economic Geology)
- 1992 Geologic Map of Texas (Bureau of Economic Geology)
- 2007 Geology of the New Braunfels Area (Bureau of Economic Geology, Texas Water Development Board, and USGS)
- 1991 Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Outcrop, Comal County, Texas (USGS)
- 2016 Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Outcrop, Comal County, Texas (USGS)
- Geologic Map of the Edwards Aquifer Recharge Zone, South-Central Texas (USGS)

High resolution geologic mapping in the Site area was best found in the 2016 Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas (Clark et al). The Site is located within the Guadalupe River valley where the river has cut through the Edwards Formation into the Glen Rose Formation. The majority of the Site is

mapped as Terrace Deposits (Qt) from the Guadalupe River, and the northern portion of the Site is mapped as the Upper Glen Rose (Kgru).

Terrace Alluvium Deposits (Quaternary) – Surficial mapping efforts in the area display the Site area along the Guadalupe River as Terrace Alluvium/Fluviatile Terrace Deposits (Qt). These unconsolidated gravels, sands, silts, and clays are normally found around rivers and streams such as the Guadalupe river and associated drainages and are inundated regularly (2005 Blome et al).

Upper Glen Rose Formation (Kgru) (Lower Cretaceous) – The Upper Glen Rose Formation is a yellowish tan, thinly bedded limestone and marl, identifiable in the region by the star-step topography is creates capping limestone and marl features. Upper Glen Rose Formation in the area, likely Cavernous (Kgrc) and Camp Bullis (Kgrcb) units at the Site, consists of evaporates, wackestones, grainstones, and argillacuous limestones. This formation is the lower confining unit of the Edwards Aquifer, though the formation does have some permeability and water production. The Cavernous (Kgrc) member in the area is known to have karst features and caverns. (Small and Hanson, 1995; Collins, 2000, Clark et al 2016). Thickness 120-230 ft.

No Edwards limestone outcroppings were observed at the Site. Based on literature research and field reconnaissance, the Site has no known or inferred faults on the Site or immediate surrounding area. Anding Environmental observed no fault structures on the Site during the field reconnaissance. No evidence of fault structures were observed on historic aerial imagery. Mapped normal faults are located 0.5 miles to the north and 0.5 miles to the south of the Site.

A geologic map of the Site is presented as **Figure D-6**. **Attachment E, Photo Log**, displays photographs of typical outcroppings of the mapped geologic unit on Site.

3.3 Site Soils

The northern portion of the Site is covered with Eckrant-Rock (ErG) soils, and the southern portion of the Site is covered with Boerne fine sandy loams (BoB). **Table 3-1** displays soils mapped on the Site and **Figure D-5** illustrates the soils in relation to the Site.

Table 3-1 – Site Soils

BoB - Boerne fine sandy loam, 1% to 3 % slopes, rarely flooded

BoB - Boerne fine sandy loam – The entirety of the Site is mapped as Boerne fine sandy loams. These soils can be found on convex slopes along stream terraces near rivers and large creeks in the area. The surface layer is typically 17" if grayish brown fine sandy loams, and subsoil consists of 41" of pale brown sandy loams. The soil is well drained with slow surface runoff and moderately rapid permeability. BoB soils on the Site were observed to be very shallow. (USDA/NRCS, 2022).

3.4 Site Assessment

No rock outcroppings were observed on the southern stream terrace portion of the Site as the Site is covered in thick soils and stream terrace deposits. No Edwards limestone outcroppings were observed on the Site.

Anding Environmental observed no geologic features or potential recharge features during the Site reconnaissance.

- MB-1 Manmade Feature in Bedrock Water Well: A drinking water well exists in the center of the Site, next to one of the vacation rentals. The wellhead is which would not allow surface water to flow into the well head. Therefore, this would not be considered a potential sensitive feature.
- MB-2 Manmade Feature in Bedrock Septic System: A septic system exists in the southern portion of the Site behind the bathhouse. The septic system is covered in thick soils with no voids or other mechanisms for rapid infiltration into the subsurface. Therefore, this would not be considered a potential sensitive feature.

4.0 SUMMARY

Anding Environmental has conducted a Geologic Assessment for the referenced Site in accordance with 30 TAC §213.5(b)(3), TCEQ requirements for regulated developments within the Edwards Aquifer Recharge Zone, and the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04). Two (2) geologic or potentially sensitive features were observed on the Site.

No geologic features or potentially sensitive recharge features were observed on the Site. Therefore, it is Anding Environmental's professional judgement that the Site has low potential for rapid surface water movement to the Edwards Aquifer via direct infiltration.

Please note that other karst features may exist on Site, either buried or obscured from view, which may have potential for openings to the subsurface. If any additional potentially karst features are discovered during future Site activities, please do not hesitate to contact Anding Environmental for support.

5.0 REFERENCES

Bureau of Economic Geology, 1992, Geologic Map of Texas: University of Texas at Austin, Virgil E. Barnes, project supervisor, Hartmann, B.M. and Scranton, D.F., cartography, scale 1: 500,000

Clark et. al., 2016, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers Within Northern Bexar and Comal Counties, Texas. U.S. Geological Survey.

Collins, E.W., 2000, Geologic map of the New Braunfels, Texas, 30 x 60 minute quadrangle—Geologic framework of an urban-growth corridor along the Edwards aquifer, south-central Texas: University of Texas, Bureau of Economic Geology Miscellaneous Map 39, 28 p., 1 sheet, scale 1: 100,000.

Comal County Appraisal District. Property Search. http://www.comalad.org/

Federal Emergency Management Agency. Floodplain Maps. https://msc.fema.gov/portal

Hanson, J.A., and Small, T.A., 1995, Geologic framework and hydrogeologic characteristics of the Edwards aquifer outcrop, Hays County, Texas: U.S. Geological Survey Water-Resources Investigations Report 95–4265, 10 p., 1 sheet, scale 1: 75,000.

Stein, W.G., and Ozuna, G.B., 1995, Geologic framework and hydrogeologic characteristics of the Edwards aquifer recharge zone, Bexar County, Texas: U.S. Geological Survey Water-Resources Investigations Report 95–4030, 8 p., 1 sheet, scale 1:75,000.

Stoeser, D.B., Shock, Nancy, Green, G.N., Dumonceaux, G. M., and Heran, W.D., in press, A Digital Geologic Map Database for the State of Texas: U.S. Geological Survey Data Series.


Texas Commission on Environmental Quality. Regulatory Databases. http://www.tceq.state.tx.us/

United States Department of Agriculture (USDA), 2022. NRCS Web Soil Survey. Custom Soil Report for Comal County, Texas. Accessed September 2022.

U.S. Geological Survey. Topographic Maps. https://ngmdb.usgs.gov/maps/topoview/viewer

U.S. Geological Survey. Texas Geology. http://mrdata.usgs.gov/sgmc/tx.html

GEOLOGIC ASSESSMENT ATTACHMENT D - SITE GEOLOGIC MAPS









8570 River Road New Braunfels, Comal County, Texas

Site Aerial


Geologic Asessment 8570 River Road, New Braunfels, TX



100

925 Lauren St. New Braunfels, TX 78130

TC NO.	DATE	DRAWN BY	MAP NO.	FIGURE
22-014	9/13/2022	ANDING	002	D-2





Elevation Contours 5' Intervals



Site

Site Topography

Geologic Asessment 8570 River Road, New Braunfels, TX





925 Lauren St. New Braunfels, TX 78130


TC NO. DATE DRAWN BY
22-014 9/13/2022 ANDING

MAP NO. FIGURE

004 D-4











925 Lauren St. ew Braunfels TX 78130

			vew braumer	3, 17, 70130
TC NO.	DATE	DRAWN BY	MAP NO.	FIGURE
22-014	9/13/2022	ANDING	005	D-5





GEOLOGIC ASSESSMENT ATTACHMENT E - PHOTO LOG

Attachment E - Photo Log Site Investigation Photos



Site Entrance and Northern Site Boundary Vacation House



Slope Down From Top of Site Western Site Boundary



Center of Site Vacation Rentals



Center of Site Vacation Rentals



Vacation Rentals



Southern Portion of Site Concession Stand and Bar Above River



River Landing Area



Concession Stand and River Landing Area





Guadalupe River-Front Southern Site Boundary

Septic System

Water Pollution Abatement Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Water Pollution Abatement Plan Application Form** is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Print Name of Customer/Agent: Jessica Calhoun, P.E., CFM

Date: 02/24/2023

Signature of Customer/Agent:

Regulated Entity Name: 8570 River Road

Regulated Entity Information

1. The type of project is:

Residential: Number of Lots:

Residential: Number of Living Unit Equivalents:

- 2. Total site acreage (size of property):0.7380
- 3. Estimated projected population: 0

Commercial Industrial Other:

4. The amount and type of impervious cover expected after construction are shown below:

Table 1 - Impervious Cover Table

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	1,504	÷ 43,560 =	0.035
Parking	1,680	÷ 43,560 =	0.039
Other paved surfaces	1,859	÷ 43,560 =	0.043
Total Impervious Cover	5,043	÷ 43,560 =	0.116

Total Impervious Cover <u>0.116</u> ÷ Total Acreage <u>0.738</u> X 100 = <u>15.7</u>% Impervious Cover

- 5. Attachment A Factors Affecting Surface Water Quality. A detailed description of all factors that could affect surface water and groundwater quality that addresses ultimate land use is attached.
- 6. Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

For Road Projects Only

Complete questions 7 - 12 if this application is exclusively for a road project.

7.	Type of project:
	 ☐TXDOT road project. ☐ County road or roads built to county specifications. ☐ City thoroughfare or roads to be dedicated to a municipality. ☐ Street or road providing access to private driveways.
8.	Type of pavement or road surface to be used:
	Concrete Asphaltic concrete pavement Other:
9.	Length of Right of Way (R.O.W.): feet.
	Width of R.O.W.: feet. L x W = $Ft^2 \div 43,560 Ft^2/Acre = acres.$
10.	Length of pavement area: feet.
	Width of pavement area: feet. L x W = $Ft^2 \div 43,560 Ft^2/Acre = acres$. Pavement area acres \div R.O.W. area acres x $100 = _$ % impervious cover.
11.	A rest stop will be included in this project.
	A rest stop will not be included in this project.

TCEQ Executive Director. Modification	roadways that do not require approval from the ons to existing roadways such as widening re than one-half (1/2) the width of one (1) existing a TCEQ.
Stormwater to be generate	ed by the Proposed Project
volume (quantity) and character (qu occur from the proposed project is a quality and quantity are based on th	ter of Stormwater. A detailed description of the fality) of the stormwater runoff which is expected to extrached. The estimates of stormwater runoff he area and type of impervious cover. Include the pre-construction and post-construction conditions.
Wastewater to be generate	ed by the Proposed Project
14. The character and volume of wastewate	er is shown below:
100% Domestic% Industrial% Commingled TOTAL gallons/day 1,000	<u>1,000</u> Gallons/day Gallons/day Gallons/day
15. Wastewater will be disposed of by:	
On-Site Sewage Facility (OSSF/Seption	: Tank):
will be used to treat and dispose licensing authority's (authorized the land is suitable for the use of the requirements for on-site sew relating to On-site Sewage Facili Each lot in this project/developm size. The system will be designe	r from Authorized Agent. An on-site sewage facility of the wastewater from this site. The appropriate agent) written approval is attached. It states that f private sewage facilities and will meet or exceed vage facilities as specified under 30 TAC Chapter 285 ties. nent is at least one (1) acre (43,560 square feet) in d by a licensed professional engineer or registered nsed installer in compliance with 30 TAC Chapter
Sewage Collection System (Sewer Lin	nes):
to an existing SCS.	wastewater generating facilities will be connected wastewater generating facilities will be connected
The SCS was previously submittedThe SCS was submitted with thisThe SCS will be submitted at a la be installed prior to Executive Di	application. ter date. The owner is aware that the SCS may not

☐ The sewage collection system will convey the wastewater to the (name) Treatment Plant. The treatment facility is:	
Existing. Proposed.	
16. All private service laterals will be inspected as required in 30 TAC §213.5.	
Site Plan Requirements	
Items 17 – 28 must be included on the Site Plan.	
17. 🔀 The Site Plan must have a minimum scale of 1" = 400'.	
Site Plan Scale: 1" = <u>100</u> '.	
18. 100-year floodplain boundaries:	
 Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled. No part of the project site is located within the 100-year floodplain. The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FIRM 48091C0270F (effective September 2, 2009) 	n
19. The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, open space, etc. are shown on the plan.	
The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, open space, etc. are shown on the site plan.	
20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):	
\boxtimes There are <u>1</u> (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)	
 ☐ The wells are not in use and have been properly abandoned. ☐ The wells are not in use and will be properly abandoned. ☐ The wells are in use and comply with 16 TAC §76. 	
☐ There are no wells or test holes of any kind known to exist on the project site.	
21. Geologic or manmade features which are on the site:	
 ☐ All sensitive geologic or manmade features identified in the Geologic Assessment ar shown and labeled. ☑ No sensitive geologic or manmade features were identified in the Geologic 	е
Assessment. Attachment D - Exception to the Required Geologic Assessment. A request and justification for an exception to a portion of the Geologic Assessment is attached.	

22. 🔀	The drainage patterns and approximate slopes anticipated after major grading activities
23. 🖂	Areas of soil disturbance and areas which will not be disturbed.
24. 🔀	Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
25. 🔀	Locations where soil stabilization practices are expected to occur.
26. 🗌	Surface waters (including wetlands).
\boxtimes	N/A
27. 🔀	Locations where stormwater discharges to surface water or sensitive features are to occur.
	There will be no discharges to surface water or sensitive features.
28. 🔀	Legal boundaries of the site are shown.
Adm	ninistrative Information
29. 🔀	Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
30. 🔀	Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

WATER POLLUTION ABATEMENT PLAN ATTACHMENT A Factors Affecting Water Quality

The proposed 8570 River Road site includes the construction of two elevated tiny homes covering 400 square feet (0.009 acres). In existing conditions, there are 1,104 square feet (0.025 acres) of rooftops, 1,680 square feet (0.039 acres) of roadway and parking area, and 1,859 square feet (0.043 acres) of decks. The factor affecting water quality is runoff sediment transport from the construction being performed. However, temporary BMP measures were taken to ensure water quality is not impaired by construction.

WATER POLLUTION ABATEMENT PLAN ATTACHMENT B

Volume and Character of Stormwater

The River Road Cottages site covers 0.7380 acres. The Drainage Area Map (with the corresponding flow calculations) can be found in Exhibit A -8570 River Road Drainage Map. There is no proposed grading onsite.

The site is currently a 0.7380-acre residential site with 5,113 square feet (0.117 acres) of impervious cover created by a main residential home and asphalt driveway, these improvements were built in 1938 before TCEQ Edwards Aquifer Program. Additionally, there are currently 1,104 square feet (0.025 acres) of additional rooftop, 1,680 square feet (0.039 acres) of concrete, and 1,859 square feet (0.043 acres) of decking that have not previously been permitted. A Water Pollution Abatement Plan has not previously been recorded for this property. The proposed conditions increase the impervious cover by 400 square feet to 5,043 square feet (0.116 acres) or 15.7% at full development. 8570 River Road, LLC is proposing a natural vegetative filter strip for the Permanent Stormwater BMP.

The existing runoff from the site was determined using the Rational Method. The existing runoff coefficient is a weighted average of impervious cover (concrete/asphalt), 0.25-0.53 based on the undeveloped range over multiple slopes. The proposed conditions runoff coefficient is also a weighted average of impervious cover (concrete/asphalt), 0.25-0.53 based on the undeveloped range over multiple slopes. These values were derived from the most current revision of the City of New Braunfels Drainage and Erosion Control Design Manual. Tables showing the drainage areas and resulting flows are on the Drainage Area Map referenced above.



February 24, 2023

Jessica Calhoun, P.E.
HMT Engineering & Surveying
via e-mail: Jessica.calhoun@hmtnb.com

Re: 8570 River Road WPAP On-Site Sewage Facility Suitability Letter, within Comal County,

Texas

Dear Ms. Calhoun:

In accordance with TAC §213.5(b)(4)(F)(ii), Comal County has found that the entire referenced site is suitable for the use of private sewage facilities and will meet the special requirements for on-site sewage facilities located on the Edwards Aquifer recharge zone as specified in TAC §285.40-42 based on the following information submitted to our office on February 23, 2023:

- The Geologic Assessment, prepared by Anding Environmental Consulting, LLC
- The Water Pollution Abatement Plan, prepared by HMT Engineering & Surveying

According to TAC §285.42(a), if any recharge feature is discovered during construction of an OSSF, all regulated activities near the feature shall be suspended immediately. The owner shall immediately notify the TCEQ San Antonio office of the discovery of the feature. All activities regulated under TAC §213 shall not proceed near the feature until Comal County, in conjunction with the TCEQ San Antonio office, has reviewed and approved a plan proposed to protect the feature, the structural integrity of the OSSF, and the water quality of the aquifer. The plan shall be sealed, signed, and dated by a professional engineer.

If you have any questions or need additional information, please do not hesitate to contact our office.

sincerely,

Robert Boyd, P.E.

Comal County Assistant Engineer

cc: Donna Eccleston, Comal County Commissioner Precinct No. 1

Douglas R. Dowlearn D.A.D. Services, Inc. PO BOX 212, BULVERDE, TX 78163 (210)240-2101

txseptic@gmail.com

February 16th, 2023

Attn:

Comal County Engineers Office Environmental Health Department 195 David Jonas Drive New Braunfels, Texas 78132

RE: On-Site Sewage Facility (OSSF) Suitability Evaluation for 8570 River Rd

To Whom It May Concern:

I have completed a site evaluation of the above referenced proposed site to determine the suitability of the site for the use of an on-site sewage facility (OSSF).

The site consists of the following type of soil(see SOILS MAP for soil sample locations):

SOIL TYPE	SOIL TEXTURE
Boerne fine sandy loam(Bob)	0" - 8" fine sandy loam 8" - 60" loam 1% - 3% Slope

The proposed lot will be served by a well. Proper OSSF setbacks found in CH285.91 Table X. Minimum Required Separation Distances for On-Site Sewage Facilities shall be maintained from the well, along with any neighboring wells.

The proposed lot is well drained primarily with sheet flow, but with small areas of concentrated flow. Seasonal groundwater (seeps) may occur.

A portion of the lot does lie within both the 100 year floodplain, and the floodway - see 8570 RIVER ROAD SURVEY for locations. If a new OSSF system is installed in either the floodplain or floodway, special planning requirements shall be implemented to prevent damage to the OSSF in the event of a flood.

The Guadalupe River is directly behind this property. A 75' setback shall be maintained from the river's edge with soil absorption and drip irrigation drainfields. A 50' setback shall be maintained from the river's edge with the drainfield if an LPD system with

secondary treatment disinfection is utilized, if a drip system with secondary treatment and disinfection is utilized, or if surface application is utilized.

The OSSFs most likely to be used on the proposed lot are aerobic treatment with drip disposal, OSSFs with septic tanks utilizing conventional drain fields or low pressure pipe. Aerobic spray disposal may also be an option.

There is an existing OSSF system(permit #92071) on the property - see 8570 RIVER ROAD SURVEY for location. The system appears to be functioning properly. There is also an existing septic tank and existing drainfield with no county record on the property - see 8570 RIVER ROAD SURVEY for location. Upon investigation, it appears this existing system(with no county record) is no longer in use. Proper measures shall be taken to ensure that the tank has been abandoned in accordance to CH285.36(b)(1) & (2).

Final permitting will be by Comal County when the OSSF permits are applied for.


I have reviewed the proposed site and determined that there is sufficient area and suitability on site for at least one of the OSSFs listed in Texas Wastewater Code 285.90-285.91, Table IX.

If you have any questions or concerns with reference to this report, I may be contacted by phone at 210.240.2101 or by email at txseptic@gmail.com.


Respectfully,


Douglas R. Dowlearn, R.S.


2 Attachments: 8570 RIVER ROAD SURVEY SOILS MAP



8570 RIVER ROAD SURVEY










er

479.002

SEQUENCE OF CONSTRUCTION

- 1. CALL PEDERNALES ELECTRIC COOPERATIVE (PEC) AND TCEQ 48 HOURS PRIOR TO BEGINNING ANY WORK. CALL DIG TESS FOR UTILITIES LOCATIONS.
- 2. INSTALL TEMPORARY EROSION CONTROLS PRIOR TO ANY CLEARING AND GRUBBING.
- 3. INSPECT EROSION CONTROLS AT WEEKLY INTERVALS, BEFORE AND AFTER SIGNIFICANT RAINFALL EVENTS TO ENSURE THEY ARE FUNCTIONING PROPERLY.
- 4. BEGIN SITE CLEARING. (0.009 ACRES)
- 5. COMPLETE ALL CONSTRUCTION PER APPROVED PLANS AND STABILIZE ALL DISTURBED AREAS.
- 6. COMPLETE FINAL SITE INSPECTION.
- 7. COMPLETE ANY NECESSARY FINAL DRESS UP OF AREAS THAT WERE DISTURBED.
- 8. REMOVE AND DISPOSE OF TEMPORARY EROSION CONTROLS AFTER SITE RE-VEGETATION HAS OCCURRED.


NO AREAS GREATER THAN 10 ACRES WILL BE DISTURBED AT ONE TIME.



NOTE:

PER TPDES REQUIREMENTS, DISTURBED AREAS ON WHICH CONSTRUCTION ACTIVITIES HAVE CEASED (TEMPORARILY OR PERMANENT) SHALL BE STABILIZED WITHIN 14 DAYS UNLESS ACTIVITY RESUMES WITHIN 21 DAYS. SEEDING DOES NOT CONSTITUTE AS STABILIZATION.

SILT FENCE AT PROPERTY LINE MAY BE SHOWN GRAPHICALLY OFFSET FROM PROPERTY LINE TO AVOID OVERLAP OF LINEWORK. CONTRACTOR SHALL NOT INSTALL EROSION CONTROL MEASURES BEYOND LIMITS OF CONSTRUCTION REGARDLESS OF GRAPHIC REPRESENTATION.



DRAINAGE FLOW DIRECTION — SF — SF — SILT FENCE — LOC — LOC — LIMIT OF CONSTRUCTION STABILIZED CONSTRUCTION ENTRANCE ---- FEMA EFFECTIVE 100-YR FLOODPLAIN FEMA EFFECTIVE 500-YR FLOODPLAIN ---- FEMA EFFECTIVE FLOODWAY

<u>LEGEND</u>

BUILDING SETBACK LINE

---- GUADALUPE RIVER CENTERLINE

UTILITY EASEMENT

DRAINAGE EASEMENT

JESSICA L. CALHOUN

Jessica Calhoun 03/02/2023

EROSION

间 日 RIVER F AUNFEL


DATE: MARCH 2023

DRAWN BY: WC DESIGNED BY: JC

REVIEWED BY: JC HMT PROJECT NO.:


479.002

SHEET



THE LOCATION OF ALL EXISTING UNDERGROUND UTILITIES ARE SHOWN IN APPROXIMATE LOCATIONS ONLY. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK. THE CONTRACTOR WILL AGREE TO BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT BE INCURRED BY THEIR FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL

UNDERGROUND UTILITIES, STRUCTURES OR FACILITIES. CONTRACTOR SHALL NOTIFY ENGINEER OF ANY DISCREPANCIES 24-HOURS PRIOR TO COMMENCING CONSTRUCTION.



JESSICA L. CALHOUN Jessica Calhoun

02/22/2023

ROAD LS, TEXAS

DATE: **FEBRUARY 2023**

REVIEWED BY: JC HMT PROJECT NO .:

479.002

THE PURPOSE OF CONCRETE WASHOUT AREAS IS TO PREVENT OR REDUCE THE DISCHARGE OF POLLUTANTS TO STORMWATER FROM CONCRETE WASTE BY CONDUCTING WASHOUT OFFSITE, PERFORMING ONSITE WASHOUT IN A DESIGNATED AREA, AND TRAINING EMPLOYEES AND SUBCONTRACTORS.

THE FOLLOWING STEPS WILL HELP REDUCE STORMWATER POLLUTION FROM CONCRETE WASTES:


- INCORPORATE REQUIREMENTS FOR CONCRETE WASTE MANAGEMENT INTO MATERIAL SUPPLIER AND SUBCONTRACTOR AGREEMENTS.
- AVOID MIXING EXCESS AMOUNTS OF FRESH CONCRETE. PERFORM WASHOUT OF CONCRETE TRUCKS IN DESIGNATED AREAS ONLY.
- DO NOT WASH OUT CONCRETE TRUCKS INTO STORM DRAINS, OPEN DITCHES,
- DO NOT ALLOW EXCESS CONCRETE TO BE DUMPED ONSITE, EXCEPT IN DESIGNATED AREAS.

FOR ONSITE WASHOUT:


- LOCATE WASHOUT AREA AT LEAST 50 FEET FROM SENSITIVE FEATURES, STORM DRAINS, OPEN DITCHES, OR WATER BODIES. DO NOT ALLOW RUNOFF FROM THIS AREA BY CONSTRUCTING A TEMPORARY PIT OR BERMED AREA LARGE ENOUGH
- FOR LIQUID AND SOLID WASTE. WASH OUT WASTES INTO THE TEMPORARY PIT WHERE THE CONCRETE CAN SET, BE BROKEN UP, AND THEN DISPOSED PROPERLY.

BELOW GRADE CONCRETE WASHOUT FACILITIES ARE TYPICAL. THESE CONSIST OF A LINED EXCAVATION SUFFICIENTLY LARGE TO HOLD EXPECTED VOLUME OF WASHOUT MATERIAL. ABOVE GRADE FACILITIES ARE USED IF EXCAVATION IS NOT PRACTICAL. TEMPORARY CONCRETE WASHOUT FACILITY (TYPE ABOVE GRADE) SHOULD BE CONSTRUCTED AS SHOWN ON THE DETAILS AT THE END OF THIS SECTION, WITH SUFFICIENT QUANTITY AND VOLUME TO CONTAIN ALL LIQUID AND CONCRETE WASTE GENERATED BY WASHOUT OPERATIONS. PLASTIC LINING MATERIAL SHOULD BE A MINIMUM OF 10 MIL IN POLYETHYLENE SHEETING AND SHOULD BE FREE OF HOLES, TEARS, OR OTHER DEFECTS THAT COMPROMISE THE IMPERMEABILITY OF THE MATERIAL.

WHEN TEMPORARY CONCRETE WASHOUT FACILITIES ARE NO LONGER REQUIRED FOR THE WORK, THE HARDENED CONCRETE SHOULD BE REMOVED AND DISPOSED OF, MATERIALS USED TO CONSTRUCT TEMPORARY CONCRETE WASHOUT FACILITIES SHOULD BE REMOVED FROM THE SITE OF THE WORK AND DISPOSED OF HOLES, DEPRESSIONS OR OTHER GROUND DISTURBANCE CAUSED BY THE REMOVAL OF THE TEMPORARY CONCRETE WASHOUT FACILITIES SHOULD BE BACKFILLED AND REPAIRED.



CONCRETE WASHOUT PIT DETAIL TYPE "ABOVE GRADE" NOT TO SCALE





02/22/2023

ONTRO

C

ШÌ 8570 F NEW BRAI

EROSION

DATE: **FEBRUARY 2023** DRAWN BY: WRC

DESIGNED BY: JC

REVIEWED BY: JC HMT PROJECT NO .: 479.002

SHEET

C1.1

ATCH DETENTION BASINS MAY HAVE SOMEWHAT HIGHER MAINTENANCE REQUIREMENTS THAN AN EXTENDED DETENTION BASIN SINCE THEY ARE ACTIVE STORMWATER CONTROLS. THE ACTIVITIES ARE IDENTICAL TO THOSE OF EXTENDED DETENTION BASINS WITH THE ADDITION OF MAINTENANCE AND INSPECTIONS OF THE AUTOMATIC CONTROLLER AND THE VALVE AT THE

INSPECTIONS: INSPECTIONS SHOULD TAKE PLACE A MINIMUM OF TWICE A YEAR. ONE INSPECTION SHOULD TAKE PLACE DURING WET WEATHER TO DETERMINE IF THE BASIN IS MEETING THE TARGET DETENTION TIME OF 12 HOURS AND A DRAWDOWN TIME OF NO MORE THAN 48 HOURS. THE REMAINING INSPECTIONS SHOULD OCCUR BETWEEN STORM EVENTS SO THAT MANUAL OPERATION OF THE VALVE AND CONTROLLER CAN BE VERIFIED. THE LEVEL SENSOR IN THE BASIN SHOULD BE INSPECTED AND ANY DEBRIS OR SEDIMENT IN THE AREA SHOULD BE REMOVED. THE OUTLET STRUCTURE AND THE TRASH SCREEN SHOULD BE INSPECTED FOR SIGNS OF CLOGGING, DEBRIS AND SEDIMENT SHOULD BE REMOVED FROM THE ORIFICE AND OUTLET(S) AS DESCRIBED IN PREVIOUS SECTIONS. DEBRIS OBSTRUCTING THE VALVE SHOULD BE REMOVED. DURING EACH INSPECTION, EROSION AREAS INSIDE AND DOWNSTREAM OF THIS BMP SHOULD BE IDENTIFIED AND REPAIRED/REVEGETATED IMMEDIATELY.

MOWING. THE BASIN: BASIN SIDE—SLOPES, AND EMBANKMENT OF THE BASIN MUST BE MOWED TO PREVENT WOODY GROWTH AND CONTROL WEEDS. A MULCHING MOWER SHOULD BE USED, OR THE GRASS CLIPPINGS SHOULD BE CAUGHT AND REMOVED. MOWING SHOULD TAKE PLACE AT LEAST TWICE A YEAR, OR MORE FREQUENTLY IF VEGETATION EXCEEDS 18 INCHES IN HEIGHT. MORE FREQUENT MOWING TO MAINTAIN AESTHETIC APPEAL MAY BE NECESSARY IN LANDSCAPED AREAS.

<u>Litter and debris removal:</u> Litter and debris removal should take place at least TWICE A YEAR, AS PART OF THE PERIODIC MOWING OPERATIONS AND INSPECTIONS. DEBRIS AND LITTER SHOULD BE REMOVED FROM THE SURFACE OF THE BASIN. PARTICULAR ATTENTION SHOULD BE PAID TO FLOATABLE DEBRIS AROUND THE OUTLET STRUCTURE. THE OUTLET SHOULD BE CHECKED FOR POSSIBLE CLOGGING OR OBSTRUCTIONS AND ANY DEBRIS REMOVED.

EROSION CONTROL: THE BASIN SIDE SLOPES AND EMBANKMENT ALL MAY PERIODICALLY SUFFER FROM SLUMPING AND EROSION. TO CORRECT THESE PROBLEMS, CORRECTIVE ACTION, SUCH AS REGRADING AND REVEGETATION, MAY BE NECESSARY. CORRECTION OF EROSION CONTROL SHOULD TAKE PLACE WHENEVER REQUIRED BASED ON THE PERIODIC INSPECTIONS.

NUISANCE CONTROL: STANDING WATER OR SOGGY CONDITIONS MAY OCCUR IN THE BASIN. SOME STANDING WATER MAY OCCUR AFTER A STORM EVENT SINCE THE VALVE MAY CLOSE WITH 2 TO 3 INCHES OF WATER IN THE BASIN. SOME FLOW INTO THE BASIN MAY ALSO OCCUR BETWEEN STORMS DUE TO SPRING FLOW AND RESIDENTIAL WATER USE THAT ENTERS THE STORM SEWER SYSTEM. TWICE A YEAR, THE FACILITY SHOULD BE EVALUATED IN TERMS OF NUISANCE CONTROL (INSECTS, WEEDS, ODORS, ALGAE, ETC.).

STRUCTURAL REPAIRS AND REPLACEMENT: WITH EACH INSPECTION, ANY DAMAGE TO STRUCTURAL ELEMENTS OF THE BASIN (PIPES, CONCRETE DRAINAGE STRUCTURES, RETAINING WALLS, FTC.) SHOULD BE IDENTIFIED AND REPAIRED IMMEDIATELY, AN EXAMPLE OF THIS TYPE OF REPAIR CAN INCLUDE PATCHING OF CRACKED CONCRETE, SEALING OF VOIDS, REMOVAL OF VEGETATION FROM CRACKS AND JOINTS. THE VARIOUS INLET/OUTLET STRUCTURES IN A BASIN WILL EVENTUALLY DETERIORATE AND MUST BE REPLACED.

SEDIMENT REMOVAL: A PROPERLY DESIGNED BATCH DETENTION BASIN WILL ACCUMULATE QUANTITIES OF SEDIMENT OVER TIME. THE ACCUMULATED SEDIMENT CAN DETRACT FROM THE APPEARANCE OF THE FACILITY AND REDUCE THE POLLUTANT REMOVAL PERFORMANCE OF THE FACILITY. THE SEDIMENT ALSO TENDS TO ACCUMULATE NEAR THE OUTLET STRUCTURE AND CAN INTERFERE WITH THE LEVEL SENSOR OPERATION. SEDIMENT SHALL BE REMOVED FROM THE BASIN AT LEAST EVERY 5 YEARS, WHEN SEDIMENT DEPTH EXCEEDS 6 INCHES, WHEN THE SEDIMENT INTERFERES WITH THE LEVEL SENSOR OR WHEN THE BASIN DOES NOT DRAIN WITHIN 48 HOURS. CARE SHOULD BE TAKEN NOT TO COMPROMISE THE BASIN LINING DURING

LOGIC CONTROLLER: THE LOGIC CONTROLLER SHOULD BE INSPECTED AS PART OF THE TWICE YEARLY INVESTIGATIONS. VERIFY THAT THE EXTERNAL INDICATORS (ACTIVE, CYCLE IN OPERATING PROPERLY BY TURNING THE CONTROLLER OFF AND ON, AND BY INITIATING A CYCLE BY TRIGGERING THE LEVEL SENSOR IN THE BASIN. THE VALVE SHOULD BE MANUALLY OPENED AND CLOSED USING THE OPEN/CLOSE SWITCH TO VERIFY VALVE OPERATION AND TO ASSIST IN INSPECTING THE VALVE FOR DEBRIS. THE SOLAR PANEL SHOULD BE INSPECTED AND ANY DUST OR DEBRIS ON THE PANEL SHOULD BE CAREFULLY REMOVED. THE CONTROLLER AND ALL OTHER CIRCUITRY AND WIRING SHOULD BE INSPECTED FOR SIGNS OF CORROSION, DAMAGE FROM INSECTS, WATER LEAKS, OR OTHER DAMAGE. AT THE END OF THE INSPECTION, THE CONTROLLER SHOULD BE RESET.

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY TSS REMOVAL CALCULATIONS CALCULATIONS FROM RG-348

1. REQUIRED LOAD REDUCTION FROM THE TOTAL PROJECT: PAGE 3-29 EQUATION 3.3: $L_{M} = 27.2 (A_{N} \times P)$

 L_{M} = REQUIRED TSS REMOVAL $A_N = NET INCREASE IN IMPERVIOUS AREA FOR PROJECT$

P = AVERAGE ANNUAL PRECIPITATION, INCHES

SITE DATA: DETERMINE REQUIRED LOAD REMOVAL BASED ON THE ENTIRE PROJECT

TOTAL PROJECT ARE INCLUDED IN PLAN = 0.74 ACRES PREDEVELOPMENT IMPERVIOUS AREA WITHIN THE LIMITS OF THE PLAN = 0.12 ACRES TOTAL POST-DEVELOPMENT IMPERVIOUS AREA WITHIN THE LIMITS OF THE PLAN = 0.23 ACRES TOTAL POST-DEVELOPMENT IMPERVIOUS COVER FRACTION = 0.32 P = 33 INCHES

TOTAL L_M REQUIRED FOR THIS PLAN = 104 lbs

2. DRAINAGE BASIN PARAMETERS (PROVIDED FOR EACH BASIN) DRAINAGE BASIN/OUTFALL AREA NO. = 1

TOTAL DRAINAGE BASIN / OUTFALL AREA = 0.74 ACRES PREDEVELOPMENT IMPERVIOUS AREA WITHIN DRAINAGE BASIN / OUTFALL AREA = 0.12 ACRES POST-DEVELOPMENT IMPERVIOUS AREA WITHIN DRAINAGE BASIN / OUTFALL AREA = 0.23 ACRES POST-DEVELOPMENT IMPERVIOUS FRACTION WITHIN DRAINAGE BASIN / OUTFALL AREA = 0.31

3. INDICATE THE PROPOSED BMP CODE FOR THIS BASIN

REMOVAL EFFICIENCY = 85 PERCENT

4. CALCULATE MAXIMUM TSS LOAD REMOVED (LR) FOR THIS DRAINAGE BASIN BY THE SELECTED BMP TYPE:

- RG 348 PAGE 3-33 EQUATION 3.7: $L_R = (BMP EFFICIENCY) \times P \times (A_I \times 34.6 + A_P \times 0.54)$ A_C = TOTAL ON-SITE DRAINAGE AREA IN THE BMP CATCHMENT AREA
 - AI = IMPERVIOUS AREA PROPOSED IN THE BMP CATCHMENT A_P = PERVIOUS AREA REMAINING IN THE BMP CATCHMENT L_R = TSS LOAD REMOVED BY THE PROPOSED BMP $A_{C} = 0.74$ ACRES

PROPOSED BMP = VEGETATED FILTER STRIPS

 $A_1 = 0.12$ ACRES $A_P = 0.51$ ACRES $L_R = 234$ lbs 5. CALCULATE FRACTION OF ANNUAL RUNOFF

DESIRED $L_{M THIS BASIN} = 200$ lbs F = 0.86

TO TREAT THE DRAINAGE BASIN / OUTFALL AREA

6. CALCULATE CAPTURE VOLUME REQUIRED BY THE BMP TYPE FOR THIS DRAINAGE BASIN / OUTFALL AREA.

> RAINFALL DEPTH = 1.38 INCHES POST-DEVELOPMENT RUNOFF COEFFICIENT = 0.27 ON-SITE WATER QUALITY VOLUME = 984 CUBIC FEET

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY WATER POLLUTION ABATEMENT PLAN GENERAL CONSTRUCTION NOTES

- 1. A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS PRIOR TO THE START OF ANY REGULATED ACTIVITIES. THIS NOTICE MUST INCLUDE: - THE NAME OF THE APPROVED PROJECT:
 - THE ACTIVITY START DATE; AND - THE CONTACT INFORMATION OF THE PRIME CONTRACTOR.
- 2. ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT MUST BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED WATER POLLUTION ABATEMENT PLAN (WPAP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTORS ARE REQUIRED TO KEEP ON-SITE COPIES OF THE APPROVED PLAN AND APPROVAL LETTER.
- 3. IF ANY SENSITIVE FEATURE(S) (CAVES, SOLUTION CAVITY, SINK HOLE, ETC.) IS DISCOVERED DURING CONSTRUCTION, ALL REGULATED ACTIVITIES NEAR THE SENSITIVE FEATURE MUST BE SUSPENDED IMMEDIATELY. THE APPROPRIATE TCEQ REGIONAL OFFICE MUST BE IMMEDIATELY NOTIFIED OF ANY SENSITIVE FEATURES ENCOUNTERED DURING CONSTRUCTION. CONSTRUCTION ACTIVITIES MAY NOT BE RESUMED UNTIL THE TCEQ HAS REVIEWED AND APPROVED THE APPROPRIATE PROTECTIVE MEASURES IN ORDER TO PROTECT ANY SENSITIVE FEATURE AND THE EDWARDS AQUIFER FROM POTENTIALLY ADVERSE IMPACTS TO WATER QUALITY.
- 4. NO TEMPORARY OR PERMANENT HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.
- 5. PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE APPROVED PLANS AND MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORRECTLY, THE APPLICANT MUST REPLACE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THESE CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED.
- 6. ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES,
- 7. SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS NOT LATER THAN WHEN IT OCCUPIES 50% OF THE
- 8. LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE.
- 9. ALL SPOILS (EXCAVATED MATERIAL) GENERATED FROM THE PROJECT SITE MUST BE STÒRED ON-SITE WITH PROPER E&S CONTROLS. FOR STORAGE OR DISPOSAL OF SPOILS AT ANOTHER SITE ON THE EDWARDS AQUIFER RECHARGE ZONE, THE OWNER OF THE SITE MUST RECEIVE APPROVAL OF A WATER POLLUTION ABATEMENT PLAN FOR THE PLACEMENT OF FILL MATERIAL OR MASS GRADING PRIOR TO THE PLACEMENT OF SPOILS AT THE
- 10. IF PORTIONS OF THE SITE WILL HAVE A TEMPORARY OR PERMANENT CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS PÓSSIBLE PRIOR TO THE 14TH/ DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE 21ST/ DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE 14TH/ DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS
- 11. THE FOLLOWING RECORDS SHALL BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST: - THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR; - THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; - THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.
- 12. THE HOLDER OF ANY APPROVED EDWARD AQUIFER PROTECTION PLAN MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:
- A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY WATER POLLUTION ABATEMENT STRUCTURE(S), INCLUDING BUT NOT LIMITED TO PONDS, DAMS, BERMS, SEWAGE TREATMENT PLANTS, AND DIVERSIONARY
- B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED OR A CHANGE WHICH WOULD SIGNIFICANTLY IMPACT THE ABILITY OF THE PLAN TO PREVENT POLLUTION OF THE EDWARDS AQUIFER;

THE ORIGINAL WATER POLLUTION ABATEMENT PLAN AUSTIN REGIONAL OFFICE 12100 PARK 35 CIRCLE, BUILDING A 14250 JUDSON ROAD AUSTIN, TEXAS 78753-1808 PHONE (512) 339-2929 PHONE (210) 490-3096 FAX (512) 339-3795

SAN ANTONIO, TEXAS 78233-4480 FAX (210) 545-4329

1. THE CONSTRUCTION ACTIVITIES ASSOCIATED WITH THIS PROJECT MUST MEET ALL APPLICABLE CRITERIA OF THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY SET FORTH IN 30 TEXAS ADMINISTRATIVE CODE (TAC) 213.5(B) — WATER POLLUTION ABATEMENT PLAN FOR REGULATED ACTIVITIES UNDERTAKEN

ON THE RECHARGE ZONE OF THE EDWARDS AQUIFER. 2. TEMPORARY EROSION AND SEDIMENTATION CONTROLS ARE REQUIRED DURING CONSTRUCTION. THE CONTROLS MUST REMAIN IN PLACE UNTIL DISTURBED AREAS ARE REVEGETATED AND THE AREAS HAVE BECOME PERMANENTLY STABILIZED. THE TEMPORARY EROSION AND SEDIMENTATION CONTROLS MUST BE INSPECTED PERIODICALLY FOR DAMAGE CAUSED BY CONSTRUCTION ACTIVITIES AND FOLLOWING EVERY RAINFALL. DAMAGED OR OBSTRUCTED CONTROLS MUST BE REPAIRED OR REPLACED AS NECESSARY TO MAINTAIN PROPER OPERATION.

3. IF ANY SENSITIVE FEATURE IS DISCOVERED DURING CONSTRUCTION, REGULATED ACTIVITIES NEAR THE SENSITIVE FEATURE MUST BE SUSPENDED IMMEDIATELY. THE OWNER MUST IMMEDIATELY NOTIFY THE APPROPRIATE REGIONAL OFFICE OF THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY OF THE SENSITIVE FEATURE DISCOVERED. THE REGULATED ACTIVITIES NEAR THE SENSITIVE FEATURE MAY NOT PROCEED UNTIL THE EXECUTIVE DIRECTOR HAS REVIEWED AND APPROVED THE METHODS PROPOSED TO PROTECT THE SENSITIVE FEATURE AND THE EDWARDS AQUIFER FROM ANY POTENTIALLY ADVERSE IMPACTS TO WATER QUALITY WHILE MAINTAINING THE STRUCTURAL

INTEGRITY OF THE LINE. 4. ANY MODIFICATION TO THE APPROVED WATER POLLUTION ABATEMENT PLAN MUST BE SUBMITTED TO THE APPROPRIATE REGIONAL OFFICE FOR APPROVAL BY THE EXECUTIVE DIRECTOR OF THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY BEFORE CONSTRUCTION OF THE PROPOSED MODIFICATION MAY

5. ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT MUST BE PROVIDED WITH COPIES OF THE APPROVED WATER POLLUTION ABATEMENT PLAN AND THE TOEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTORS ARE REQUIRED TO KEEP ON-SITE COPIES OF THE APPROVED PLAN AND APPROVAL LETTER.

S. CASTELL , BRAUNFELS E FIRM F-109 S FIRM 1053 290 S. NEW F TBPE TBPLS



02/22/2023

ENT S 570 F BRA A MANEI 85 NEW I C

DATE: **FEBRUARY 2023**

DRAWN BY: WRC

DESIGNED BY: JC

REVIEWED BY: JC HMT PROJECT NO .: 479.002

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

Date: 02/24/2023

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: <u>Jessica Calhoun, P.E., CFM</u>

Signature of Customer/Agent:

Cessice Colhour
Regulated Entity Name: River Road Cottages

Project Information

Potential Sources of Contamination


Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

Fuels for construction equipment and hazardous substances which will be used during construction:
The following fuels and/or hazardous substances will be stored on the site:
These fuels and/or hazardous substances will be stored in:
Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

	 Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year. Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
	□ Fuels and hazardous substances will not be stored on the site.
2.	Attachment A - Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
3.	☐ Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
4.	Attachment B - Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.
S	equence of Construction
5.	Attachment C - Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
	 For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given. For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
6.	Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Guadalupe River
Τe	emporary Best Management Practices (TBMPs)
sta co ba	osion control examples: tree protection, interceptor swales, level spreaders, outlet abilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized instruction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment isins. Please refer to the Technical Guidance Manual for guidelines and specifications. All ructural BMPs must be shown on the site plan.
7.	Attachment D – Temporary Best Management Practices and Measures. TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to

retain sediment on site to the extent practicable. The following information is attached:

	A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
	A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
	A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
	A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. 🔀	The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
	Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
	There will be no temporary sealing of naturally-occurring sensitive features on the site.
9.	Attachment F - Structural Practices. A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10.	Attachment G - Drainage Area Map. A drainage area map supporting the following requirements is attached:
	For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
	For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
	For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
	There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.



- 18. Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 19. Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

- 20. All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. All regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

TEMPORARY STORMWATER SECTION ATTACHMENT A Spill Response Actions

Contractor to notify all appropriate authorities if more than 25 gallons of hydrocarbons are spilled. The construction plans include the required notes regarding appropriate spill response actions as directed by TCEQ. There will be no temporary storage vessels of fuel or hydrocarbons to be stored on site.

If spills of any hydrocarbons occur, construction must contain spills by immediate action. Earthen materials must be kept readily available to provide a Dike. Sand should be used to help soak fuels. Property disposal of any materials used will be required.

Contractor must promote job site awareness to all employees involved. All employees must be made aware of the provisions in this report.

Spill Prevention and Control

The objective of this section is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees.

The following steps will help reduce the stormwater impacts of leaks and spills:

Education

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a "significant spill" is for each material they use, and what is the appropriate response for "significant" and "insignificant" spills. Employees should also be aware of when spill must be reported to the TCEQ. Information available in 30 TAC 327.4 and 40 CFR 302.4
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor's superintendent or representative oversee and enforce proper spill prevention and control measures.

General Measures

- (l) To the extent that the work can be accomplished safely, spills of oil, petroleum products, substances listed under 40 CFR parts 110, 117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.
- (6) Spills should be covered and protected from stormwater runoff during rainfall to the extent that it doesn't compromise cleanup activities.
- (7) Do not bury or wash spills with water.
- (8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.
- (9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.
- (10) Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.
- (11) Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.
- (12) Keep waste storage areas clean, well-organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function

Clean up

- (1) Clean up leaks and spills immediately.
- (2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.

(3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMP's in this section for specific information.

Minor Spills

- (1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.
- (2) Use absorbent materials on small spills rather than hosing down or burying the spill.
- (3) Absorbent materials should be promptly removed and disposed of properly.
- (4) Follow the practice below for a minor spill:
 - (a) Contain the spread of the spill.
 - (b) Recover spilled materials.
 - (c) Clean the contaminated area and properly dispose of contaminated materials.

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman immediately.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with the absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities (25 gallons):

(1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact

- the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
- (2) For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110, 119 and 302, the contractor should notify the National Response Center at (800) 424-8802.
- (3) Notification should first be made by telephone and followed up with a written report.
- (4) The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.
- Other agencies which may need to be consulted include, but are not limited to, the City of Police Department, County Sheriff Office, Fire Departments, etc.

More information on spill rules and appropriate responses is available on the TCEQ website at: https://www.tceq.texas.gov/response/spills

Vehicle and Equipment Maintenance

- (1) If maintenance must occur onsite, use a designated area and a secondary containment, located away from drainage courses, to prevent the runon of stormwater and the runoff of spills.
- (2) Regularly inspect onsite vehicles and equipment for leaks and repair immediately.
- (3) Check incoming vehicles and equipment (including delivery trucks, and employee and subcontractor vehicles) for leaking oil and fluids. Do not allows leaking vehicles or equipment onsite.
- (4) Always use secondary containment, such as a drain pan or drop cloth, to catch spills or leaks when removing or changing fluids.
- (5) Place drip pans or absorbent materials under paving equipment when not in use.
- (6) Use absorbent materials on small spills rather than hosing down or burying the spill. Remove the absorbent materials promptly and dispose of properly.
- (7) Promptly transfer used fluids to the proper waste or recycling drums. Don't leave full drip pans or other open containers lying around.
- (8) Oil filters disposed of in trashcans or dumpsters can leak oil and pollute stormwater. Place the oil filter in a funnel over a waste oil-recycling drum to drain excess oil before disposal. Oil filters can also be recycled. Ask the oil supplier or recycler about recycling oil filters.

(9) Store cracked batteries in a non-leaking secondary container. Do this with all cracked batteries even if you think all the acid has drained out. If you drop a battery, treat it as if it is cracked. Put it into the containment area until you are not sure it is not leaking.

Vehicle and Equipment Fueling

- (1) If fueling must occur on site, use designated areas, located away from drainage courses, to prevent the runon of storrnwater and the runoff of spills.
- (2) Discourage "topping off" of fuel tanks.
- (3) Always use secondary containment, such as a drain pan, when fueling to catch spills/leaks.

TEMPORARY STORMWATER SECTION ATTACHMENT B

Potential Sources of Contamination

The proposed 8570 River Road site includes the construction of two elevated tiny homes covering 400 square feet (0.009 acres). The possible sources of contamination include sediment transport from runoff and fuel spills by the Contractor while refueling equipment. Other small quantities of solvent for construction may be present. Contractor shall keep all fuel transfers and any other contaminants used secure. Silt fences will aid in the removal of transported sediment from the runoff.

Please see Attachment "A" for response actions.

TEMPORARY STORMWATER SECTION ATTACHMENT C

Sequence of Major Activities

Construction sequencing- The construction will be performed in one phase.

- 1. Call Pedernales Electric Cooperative (PEC) and TCEQ 48 hours prior to beginning any work. Call Dig TESS for utilities locations.
- 2. Install temporary erosion controls prior to any clearing and grubbing.
- 3. Inspect erosion controls at weekly intervals, before and after significant rainfall events to ensure they are functioning properly.
- 4. Begin site clearing. (0.009 acres)
- 5. Complete all construction per approved plans and stabilize all disturbed areas.
- 6. Complete final site inspection.
- 7. Complete any necessary final dress up of areas that were disturbed.
- 8. Remove and dispose of temporary erosion controls after site re-vegetation has occurred.

No areas greater than 10 acres will be disturbed at one time.

TEMPORARY STORMWATER SECTION ATTACHMENT D

Temporary Best Management Practices and Measures

Temporary erosion controls are proposed for this project to include silt fence and a concrete wash out area. Please see C1.1 8750 River Road Erosion Control Plan for all temporary erosion control details.

Temporary sediment basins are not required because there are no drainage areas greater than 10 acres disturbed on site.

Approximately 336 linear feet of silt fence will be used during construction. This will be placed down gradient of all proposed construction.

From the TECQ RG 348 dated July 2005, silt fences provide protection. In addition, the contractor has been directed to minimize disturbance to a reasonable working space.

TEMPORARY STORMWATER SECTION ATTACHMENT F Structural Practices

During construction, silt fences will be used until construction is complete and vegetation and paving has been established. Additionally, the contractor will pile the spoils from excavation on the uphill side of the excavation, with a minimum of one foot between the excavation and the pile, in order to prevent storm water from entering the trenched area.

In addition, the contractor will be directed to minimize site disturbance and avoid having equipment in areas that are not necessary for the construction. Natural vegetation shall be left undisturbed and will help remove sediment if any bypass at silt fences or other structural measures occurs.

TEMPORARY STORMWATER SECTION ATTACHMENT G Drainage Area Map

The Drainage Area Map (with the corresponding flow calculations) can be found in Exhibit A 8570 River Road Drainage Map. The drainage area does not change between existing and proposed conditions.

TEMPORARY STORMWATER SECTION ATTACHMENT I

Inspection and Maintenance of BMPs

The Contractor will be directed to inspect and maintain all temporary BMPs. The design engineer will also make regular visits to the project and will provide visual inspections as well. Any deficiency noted must be corrected immediately by the contractor.

Maintenance:

- 1. Inspect all silt fences and concrete wash out areas weekly and directly after any rainfalls greater than 1 inch.
- 2. Remove sediment when buildup reaches 6 inches on silt fence or install a second line of silt fence parallel.
- 3. Replace any torn fabric in the silt fence.
- 4. Replace or repair any sections crushed or collapsed in the course of construction.
- 5. See stormwater pollution plan details as shown in the construction plans for proper size and installation.
- 6. Contractor to maintain a daily log and note any deficiencies to temporary BMPs and corrective action taken. Rainfall events shall also be noted.

BMP Inspection Report Attachment I

Operator:	_		Date:	
Job Name:	_	Recei	iving Waters:	
Location:			Map Grid:	
Inspector:		Inspector Q	ualifications:	
Is this site over the Aquifer recharge or contributing zone	_	If this site is	in compliand	e with the SWPPP and Permit
Visual Inspection of the Site	Υ	N	N/A	Comments
NOI Posted?				
Site Notice Posted?				
Was a copy of the NOI sent to the Reporting agency?				
SWPPP Plan in Box?				
Copy of WPAP in the box? (If applies)				
SWPPP Information updates				
Material list updated?				
Project Milestone current with intended dates?				
All current locations of BMP's Identified on plans?				
Areas under operators control clearly Identified on site map?				
Trash Containers and Restrooms noted?				
Stabilized areas updated or noted on plans?				
Site Conditions				
Entrance and exits free from off site tracking?				
Trash and Debri being contained on site?				
Material storage area effectively controlling pollutants?				
Wash out pit working order?				
Are all pollutants contained on site?				
Erosion Control devices in working order?				
Are all BMP's Adequate for this site at this times				
Hazardous Waste				
Is there materials being exposed to storm water runoff?				
Any signs of major leaks or spills?				
Any leaks or spills of reputable Quanitiv need to be reported?				

BMP Inspection Report Attachment I

Job Name:			Date:	
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
		_		
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
		_		
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
Evaluated the information submitted. B	Based on my inquiry of the person or persons wh	o manage the system? Or those person	cordance with a system designed to assure that qualified pe ns directly responsible for gathering the information, the info lse information, including the possibility of fine and imprisor	ormation submitted is, too the
		Qualified BM	1P Inspector:	

BMP Inspection Report Attachment I

ne:		Date:
ction Activities and location		
Block/Lot or Address	Work being done	Date
2100.0 201 01 7100.000		

Permanent Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(C), (D)(Ii), (E), and (5), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Permanent Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

executive director approval. The application was prepared by:

Print Name of Customer/Agent: <u>Jessica Calhoun, P.E., CFM</u>

Signature of Customer/Agent

Date: 02/24/2023

Regulated Entity Name: 8570 River Road

Permanent Best Management Practices (BMPs)

Permanent best management practices and measures that will be used during and after construction is completed.

1.	Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
	□ N/A
2.	These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
	The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.

	A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is:
	□ N/A
3.	Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
	□ N/A
4.	Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
	 □ The site will be used for low density single-family residential development and has 20% or less impervious cover. □ The site will be used for low density single-family residential development but has more than 20% impervious cover. □ The site will not be used for low density single-family residential development.
5.	The executive director may waive the requirement for other permanent BMPs for multifamily residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
	 Attachment A - 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached. The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover. The site will not be used for multi-family residential developments, schools, or small business sites.
6.	

		 A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached. No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached. Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
7.	\boxtimes	Attachment C - BMPs for On-site Stormwater.
		 A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached. Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
8.		Attachment D - BMPs for Surface Streams. A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is attached. Each feature identified in the Geologic Assessment as sensitive has been addressed.
	\boxtimes	N/A
9.		The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.
		 The permanent sealing of or diversion of flow from a naturally-occurring sensitive feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed. Attachment E - Request to Seal Features. A request to seal a naturally-occurring sensitive feature, that includes, for each feature, a justification as to why no reasonable and practicable alternative exists, is attached.
10.		Attachment F - Construction Plans. All construction plans and design calculations for the proposed permanent BMP(s) and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. The plans are attached and, if applicable include:
		 ☑ Design calculations (TSS removal calculations) ☑ TCEQ construction notes ☑ All geologic features ☑ All proposed structural BMP(s) plans and specifications
		N/A

11. Attachment G - Inspection, Maintenance, Repair and Retrofit Plan. A plan for the inspection, maintenance, repairs, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan includes all of the following:
Prepared and certified by the engineer designing the permanent BMPs and measures
 Signed by the owner or responsible party Procedures for documenting inspections, maintenance, repairs, and, if necessary retrofit
 ☑ A discussion of record keeping procedures ☑ N/A
12. Attachment H - Pilot-Scale Field Testing Plan. Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
⊠ N/A
13. Attachment I -Measures for Minimizing Surface Stream Contamination. A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that results in water quality degradation.
□ N/A
Responsibility for Maintenance of Permanent BMP(s)
Responsibility for maintenance of best management practices and measures after construction is complete.
14. The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
□ N/A
15. A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.
□ N/A

PERMANENT STORMWATER SECTION ATTACHMENT B BMPs for Upgradient Stormwater

There are no permanent BMPs for upgradient stormwater for the 8570 River Road site because the offsite area consists of undeveloped woods that are intercepted away by River Road.

PERMANENT STORMWATER SECTION ATTACHMENT C BMPs for On-Site Stormwater

There is one proposed Permanent BMP for the on-site stormwater for the 8570 River Road site that will remove 85% of the incremental increase in the annual mass loading of total suspended solids (TSS) as per TCEQ standards. The BMP is a natural vegetative filter strip that will be maintained to TCEQ standards. The design plans and details can be found on Sheet C1.2 8570 River Road Storage Permanent Stormwater BMPs.

PERMANENT STORMWATER SECTION ATTACHMENT D BMPs for Surface Streams

The on-site flow will be treated using natural vegetative filter strips. The natural vegetative filter strips will reduce the velocity of the runoff therefore reducing the chance of erosion from the site and filter out runoff sediment meeting TCEQ standards.

PERMANENT STORMWATER SECTION ATTACHMENT F Construction Plans

A natural vegetative filter strip is the proposed Permanent BMPs for the on-site stormwater for the 8570 River Road site. The permanent BMP will be constructed to TCEQ standards and the natural vegetative filter strips can be found on sheets C1.2 of the 8570 River Road Construction Plans.

PERMANENT STORMWATER SECTION ATTACHMENT G

Inspection, Maintenance, Repair and Retrofit Plan

The contractor will be directed to inspect and maintain all permanent BMPs during construction. After construction is complete the permanent BMPs will be turned over to 8570 River Road, LLC. Any deficiency noted must be corrected immediately by 8570 River Road, LLC. The maintenance guidelines were pulled from the TCEQ Document "Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices" and its addendum sheet, the documents can be referenced for a more in-depth explanation of maintenance guidelines.

Maintenance and Inspection:

- (1) Specification of routine and non-routine maintenance activities to be performed;
 - a. Natural Vegetative Filter Strips
 - Pest Management An Integrated Pest Management (IPM) Plan should be developed for vegetated areas. This plan should specify how problem insects and weeds will be controlled with minimal or no use of insecticides and herbicides.
 - ii. Seasonal Mowing- Should be mowed to limit the vegetation height to 18 inches, but a minimum of twice annually. When mowing is performed, a mulching mower should be used, or grass clippings should be caught and removed.
 - iii. Inspection Inspect vegetative filter strips at least twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable.
 - iv. Debris and Litter Removal The need for this practice is determined through periodic inspection, but should be performed no less than four times per year.
 - v. Sediment Removal Sediment should be removed when it has accumulated to 3 inches at any spot, or cover vegetation. Excess sediment should be removed by hand or with flat-bottomed shovel.
 - vi. Grass Reseeding and Mulching A healthy dense grass should be maintained in the channel and side slopes. Grass damaged during sediment removal should be promptly replaced using the same seed mix used during vegetation establishment.
- (2) A schedule for maintenance activities;
 - a. Inspection and maintenance will be held quarterly and after rainfall events of more than one inch
- (3) The natural vegetative filter strips can be accessed by foot or small equipment via the site;
- (4) The 8570 River Road, LLC will be in charge of the oversight and scheduling of inspections and maintenance. Kellie Jenks, Manager of General Partner, for 8570 River Road, LLC will establish the inspection and maintenance plans for the Organization; and

(5) Inspection records will be maintained at 8570 River Road, LLC offices.

Responsible for Maintenance

 $\frac{2-23-23}{\text{Date}}$

-

BMP Inspection Report Attachment G

Operator:	_		Date:	
Job Name:		Rece	iving Waters:	
Location:	Map Grid:			
Inspector:	_	Inspector C	Qualifications:	
Is this site over the Aquifer recharge or contributing zone	-	If this site is	in compliance	e with the SWPPP and Permit
Visual Inspection of the Site	Υ	N	N/A	Comments
NOI Posted?				
Site Notice Posted?				
Was a copy of the NOI sent to the Reporting agency?				
SWPPP Plan in Box?				
Copy of WPAP in the box? (If applies)				
SWPPP Information updates				
Material list updated?				
Project Milestone current with intended dates?				
All current locations of BMP's Identified on plans?				
Areas under operators control clearly Identified on site map?				
Trash Containers and Restrooms noted?				
Stabilized areas updated or noted on plans?				
Site Conditions				
Entrance and exits free from off site tracking?				
Trash and Debri being contained on site?				
Material storage area effectively controlling pollutants?				
Wash out pit working order?				
Are all pollutants contained on site?				
Erosion Control devices in working order?				
Are all BMP's Adequate for this site at this times				
Hazardous Waste				
Is there materials being exposed to storm water runoff?				
Any signs of major leaks or spills?				
Any leaks or spills of reputable Quanitiy need to be reported?				

BMP Inspection Report Attachment G

Job Name:			Date:	
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
		_		
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
Location	What Failed and Amount	Reason	Modification to be made	Correction Date
Evaluated the information sul	bmitted. Based on my inquiry of the person or persons wh	o manage the system? Or those persons nificant penalties for Submitting false inf	ordance with a system designed to assure that qualified per s directly responsible for gathering the information, the information, including the possibility of fine and imprisonment	mation submitted is, too the best
		Qualified BM	ทิก เมองคราย	

BMP Inspection Report Attachment G

lame:		Date:	
ruction Activities and location			
Block/Lot or Address	Work being done		Date
ES :			

PERMANENT STORMWATER SECTION ATTACHMENT I

Measures for Minimizing Surface Stream Contamination

The runoff from the site will travel over an undisturbed natural vegetative filter strip to provide natural filtration before entering the Guadalupe River. The vegetation will filter out runoff sediment from the proposed improvements and will reduce the velocity of the runoff therefore reducing the chance of erosion from the site. The storm water from the proposed site will enter into the surface stream system as sheet flow, thereby further reducing the likelihood of erosion.

Agent Authorization Form

For Required Signature Edwards Aquifer Protection Program Relating to 30 TAC Chapter 213 Effective June 1, 1999

	Kellie Jenks	
	Print Name	
	Manager of General Partner	
	Title - Owner/President/Other	
of	8570 River Road, LLC	
	Corporation/Partnership/Entity Name	
have authorized	Jessica Calhoun, P.E., CFM Print Name of Agent/Engineer	
	Fill Name of Agent Engineer	
of	HMT Engineering & Surveying	
-	Print Name of Firm	

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

- 1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
- 2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
- 3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
- 4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
- 5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

Applicant's Signature 2-23-23

Date

THE STATE OF WXOS §
County of Horris §

BEFORE ME, the undersigned authority, on this day personally appeared known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 23rd day of February, 2023

NOTARY PUBLIC

Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 03.29.2026

LIZZY CALKINS

Notary Public, State of Texas

Comm. Expires 03-29-2026

Notary ID 133673817

Application Fee Form

Texas Commission on Environmental Quality						
Name of Proposed Regulated Entity: <u>8570 River Road</u>						
Regulated Entity Location: <u>857</u>		<u>ls, Texas 78132</u>				
Name of Customer: <u>8570 River</u>	Road, LLC					
Contact Person: <u>Kellie Jenks</u>		e: <u>713-876-1372</u>				
Customer Reference Number (· ——					
Regulated Entity Reference Nu	ımber (if issued):RN					
Austin Regional Office (3373)						
☐ Hays	☐ Travis	☐ Wil	liamson			
San Antonio Regional Office (3	3362)					
Bexar		Uva	alde			
Comal	Kinney					
Application fees must be paid		r money order, payabl	e to the Texas			
Commission on Environmenta	-					
form must be submitted with	-	-	•			
Austin Regional Office		ın Antonio Regional Of				
Mailed to: TCEQ - Cashier	_	vernight Delivery to: TCEQ - Cashier				
Revenues Section	2100 Park 35 Circle					
Mail Code 214	uilding A, 3rd Floor					
P.O. Box 13088	ustin, TX 78753					
Austin, TX 78711-3088	12)239-0357					
Site Location (Check All That A	•	,				
🔀 Recharge Zone	Contributing Zone	☐ Transit	ion Zone			
Type of	Plan	Size	Fee Due			
Water Pollution Abatement P						
Plan: One Single Family Resid	o o	Acres	\$			
Water Pollution Abatement P						
Plan: Multiple Single Family R		Acres	\$			
Water Pollution Abatement P	Plan, Contributing Zone					
Plan: Non-residential	•	0.738 Acres	\$ 3,000			
Sewage Collection System		L.F.	\$			
Lift Stations without sewer lir	nes	Acres	\$			
Underground or Aboveground	Tanks	\$				
Piping System(s)(only)		Each	\$			
Exception		Each	\$			
Extension of Time		Each	\$			

Signature:

Date: 02/24/2023

Application Fee Schedule

Texas Commission on Environmental Quality Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

	Project Area in	
Project	Acres	Fee
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial,	< 1	\$3,000
institutional, multi-family residential, schools, and	1 < 5	\$4,000
other sites where regulated activities will occur)	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

	Cost per Linear	Minimum Fee-
Project	Foot	Maximum Fee
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

	Cost per Tank or	Minimum Fee-
Project	Piping System	Maximum Fee
Underground and Aboveground Storage Tank		
Facility	\$650	\$650 - \$6,500

Exception Requests

Project	Fee
Exception Request	\$500



TCEQ Use Only

TCEQ Core Data Form

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)											
New Per New Per	mit, Regis	tration or Authori	zation (Core D	ata Form sh	ould be	submi	tted wi	th the p	rogram applicatio	n.)	
☐ Renewal (Core Data Form should be submitted with the renewal form) ☐ Other											
2. Customer Reference Number (if issued) Follow this link to search 3. Regulated Entity Reference Number (if issued)					f issued)						
CN	CN For CN or RN numbers in Central Registry** RN										
SECTION	II: Cu	stomer Info	<u>rmation</u>								
4. General C	ustomer l	nformation	5. Effective I	Date for Cu	stomer	r Inforn	nation	Update	es (mm/dd/yyyy)	2/24/2	2023
New Cust				pdate to Cu						Regulated E	Entity Ownership
									Public Accounts)		
			-	•			-			rrent and	active with the
		f State (SOS)		-		iblic i		•			
6. Customer	Legal Nai	ne (If an individua	l, print last name	first: eg: Doe	, John)		<u>If .</u>	new Cus	stomer, enter previ	ous Custome	<u>er below:</u>
8570 Rive	r Road										
7. TX SOS/CI	PA Filing	Number	8. TX State 1	Γax ID (11 digi	its)		9.	Federa	I Tax ID (9 digits)	10. DUNS	S Number (if applicable)
804645403	3		32085408	3774			88	8-313	6576		
11. Type of C	11. Type of Customer: Corporation Individual Partnership: General Limited										
Government:	☐ City ☐ (County 🔲 Federal 🗀	State Other		Sole P	ropriet	orship		Other: Limited I	Liability Co	ompany
12. Number			□ 054 500	□ 501 es	ما اما ام				endently Owned	and Opera	ted?
☑ 0-20 ☐ 21-100 ☐ 101-250 ☐ 251-500 ☐ 501 and higher ☑ Yes ☐ No											
14. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following											
⊠Owner □Occupation	nal Licens	☐ Operat ee ☐ Respo	or nsible Party		wner & oluntary			plicant	Other:		
	1001 N	AcKinney St	reet								
15. Mailing Address:	Suite 5	525									
Address.	City	Houston		State	TX		ZIP	7700)2	ZIP + 4	6451
16. Country I	Mailing In	formation (if outsi	de USA)	•		17. E	-Mail <i>A</i>	Address	if applicable)		
n/a kjenks@trccapitalpartners.com											
18. Telephon	e Numbe	Ť		19. Extensi	on or (Code			20. Fax Numbe	r (if applicat	ole)
(713)87	(713) 876-1372										
SECTION III: Regulated Entity Information											
21. General Regulated Entity Information (If 'New Regulated Entity" is selected below this form should be accompanied by a permit application)											
 ☑ New Regulated Entity ☐ Update to Regulated Entity Information 											
The Regulated Entity Name submitted may be updated in order to meet TCEQ Agency Data Standards (removal											
of organizational endings such as Inc, LP, or LLC).											
22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)											
8570 Rive	r Road										

TCEQ-10400 (02/21) Page 1 of 3

	8570 Ri	ver Road									
23. Street Address of											
the Regulated Entity: (No PO Boxes)	City	New Braunfels	State	TX	ZIP	78132	ZIP + 4	3127			
24. County	Comal					•	•				
	E	nter Physical	Location Description	on if no str	eet address	s is provided.					
25. Description to Physical Location:											
26. Nearest City	1					State	Nea	rest ZIP Code			
New Braunfels		1				TX	781	132			
27. Latitude (N) In Decir	mal:	29.799857	7			V) In Decimal:	-98.14796	653			
Degrees	Minutes		Seconds	Degree		Minutes		Seconds			
29		47	59.4846		98		8	52.6734			
29. Primary SIC Code (4	digits) 30.	Secondary SI	C Code (4 digits)	31. Prima	ry NAICS C	ode 32. S (5 or 6	econdary NAI digits)	CS Code			
7011	70	32		531190		531	120				
33. What is the Primary		f this entity?	(Do not repeat the SIC	or NAICS desc	cription.)						
Vacation Rental Ca	abins										
34. Mailing		1001 McKinney Street									
Address:		Suite 525									
	City	Houston	State	TX	ZIP	77002	ZIP + 4	6451			
35. E-Mail Address:			kjenks@trccapitalpartners.com								
•	36. Telephone Number 3			37. Extension or Code 38. Fax Nu			mber (if appli	cable)			
· · · · ·	876-1372					() -				
9. TCEQ Programs and II rm. See the Core Data Form				mits/registra	tion numbers	that will be affected	by the updates	submitted on this			
☐ Dam Safety	☐ Distric	ts		fer	☐ Emission	ons Inventory Air	☐ Industrial	Hazardous Waste			
	<u> </u>		WPAP								
☐ Municipal Solid Waste	☐ New S	ource Review Air	OSSF 🗆		☐ Petrole	um Storage Tank	☐ PWS				
Sludge	Storm	Motor	☐ Title V Air		☐ Tires		☐ Used Oil				
☐ Siddye	Stollii	vvalei	Title v All		☐ Illes		☐ Osed Oil				
☐ Voluntary Cleanup	☐ Waste Water ☐ Wastewater Ag			griculture	riculture			Other:			
_ , ,			_	<u> </u>							
ECTION IV: Pro	eparer II	nformation	1								
40			-	41. Title:	Proje	ct Engineer					
I Laccica L'alh	oun, P.E.	, 01 111									
Name: Jessica Calh 42. Telephone Number	<u> </u>		ax Number	45. E-M	ail Address						
Name: Jessica Cain 42. Telephone Number	<u> </u>	de 44. F	ax Number 0) 625-8556			@hmtnb.com	<u> </u>				
Name: Jessica Cain	43. Ext./Co	de 44. Fa	0)625-8556				<u> </u>				

signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	HMT Engineering & Surveying	Job Title:	Project Engineer		
Name (In Print):	Jessica Calhoun			Phone:	(210) 255- 7873

TCEQ-10400 (02/21) Page 2 of 3 Signature: Joseph Calhaun Date: 2/24/23

TCEQ-10400 (02/21) Page 3 of 3