

# MODIFICATION OF AN APPROVED WATER POLLUTION ABATEMENT PLAN

## FOR TEXAS TITO'S

PREPARED FOR  
**Texas Commission on Environmental Quality**

Region 13 – San Antonio  
14250 Judson Road  
San Antonio, Texas 78233  
210-490-3096 (office)  
210-545-4329 (fax)

PREPARED BY



F-13351

James Ingalls, P.E.  
2021 SH 46W, Ste 105  
New Braunfels, TX 78132

Prepared  
October 20, 2023



<b>TCEQ Application Cover Page</b>	<b>Page 4</b>
<b>General Information Form</b>	<b>Page 8</b>
<b>A. Attachment A - Location Map</b>	<b>Page 12</b>
<b>B. Attachment B - USGS East &amp; West Map</b>	<b>Page 13</b>
<b>C. Attachment C – Project Description</b>	<b>Page 14</b>
<b>Geologic Assessment</b>	<b>Page 15</b>
<b>A. Attachment A - Geologic Assessment Table</b>	<b>Page 17</b>
<b>B. Attachment B – Stratigraphic Column</b>	<b>Page 19</b>
<b>C. Attachment C – Site Geology</b>	<b>Page 20</b>
<b>D. Attachment D – Site Geologic Map(s)</b>	<b>Page 22</b>
<b>Modification of a Previously Approved Water Pollution Abatement Plan</b>	<b>Page 23</b>
<b>A. Attachment A – Original Approved Letter</b>	<b>Page 26</b>
<b>B. Attachment B – Narrative of Proposed Modification</b>	<b>Page 30</b>
<b>C. Attachment C – Current Site Plan of Approved Project</b>	<b>Page 31</b>
<b>Water Pollution Abatement Plan Application Form</b>	<b>Page 32</b>
<b>D. Attachment A – Factors Affecting Surface Water Quality</b>	<b>Page 37</b>
<b>E. Attachment B – Volume and Character of Stormwater</b>	<b>Page 37</b>
<b>F. Attachment C – Suitability Letter</b>	<b>N/A</b>
<b>G. Exception to the Required Geologic Assessment</b>	<b>N/A</b>
<b>H. Site Plan</b>	<b>Page 38</b>
<b>Temporary Stormwater Section</b>	<b>Page 39</b>
<b>A. Attachment A – Spill Response Actions</b>	<b>Page 44</b>
<b>B. Attachment B – Potential Sources of Contamination</b>	<b>Page 48</b>
<b>C. Attachment C – Sequence of Major Construction</b>	<b>Page 48</b>
<b>D. Attachment D – Temporary BMP and Measures</b>	<b>Page 48</b>
<b>E. Attachment E – Request to Temporarily Seal a Feature</b>	<b>N/A</b>
<b>F. Attachment F – Structural Practices</b>	<b>Page 49</b>
<b>G. Attachment G – Drainage Area Map</b>	<b>Page 54</b>
<b>H. Attachment H – Temporary Sediment Pond Plan &amp; Calculation</b>	<b>N/A</b>
<b>I. Attachment I – Inspection and Maintenance for BMPs</b>	<b>Page 49</b>
<b>J. Attachment J – Schedule of Interim &amp; Permanent         Soil Stabilization Practices</b>	<b>Page 49</b>
<b>Permanent Stormwater Section</b>	<b>Page 55</b>
<b>A. Attachment A – 20% or Less Impervious Cover Waiver</b>	<b>N/A</b>
<b>B. Attachment B – BMPs for Upgradient Stormwater</b>	<b>Page 55</b>
<b>C. Attachment C – BMPs for On-Site Stormwater</b>	<b>Page 55</b>
<b>D. Attachment D – BMPs for Surface Streams</b>	<b>Page 55</b>
<b>E. Attachment E – Request to Seal Feature</b>	<b>N/A</b>

<b>F. Attachment F – Construction Plans TSS Removal Calculations/BMP Design</b>	<b>Page 63-65 Page 66-70</b>
<b>G. Attachment G – Inspection, Maintenance, Repair &amp; Retrofit Plan</b>	<b>Page 61</b>
<b>H. Attachment H – Pilot-Scale Field Testing Plan</b>	<b>N/A</b>
<b>I. Attachment I – Measures for Minimizing Surface Stream Contamination</b>	<b>Page 62</b>
<b>Agent Authorization Form</b>	<b>Page 73</b>
<b>Application Fee Form</b>	<b>Page 75</b>
<b>Core Data Form</b>	<b>Page 76</b>

# Texas Commission on Environmental Quality

## Edwards Aquifer Application Cover Page

---

### Our Review of Your Application

**The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).**

### Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains “possibly sensitive” features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

### Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited.**
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

**Mid-Review Modifications**

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a “Mid-Review Modification”. Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ’s Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ’s San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

<b>1. Regulated Entity Name:</b> Texas Tito’s					<b>2. Regulated Entity No.:</b> 111481024				
<b>3. Customer Name:</b> Blieders Creek, LLC					<b>4. Customer No.:</b> 606009058				
<b>5. Project Type:</b> (Please circle/check one)	New	Modification			Extension	Exception			
<b>6. Plan Type:</b> (Please circle/check one)	WPAP	CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
<b>7. Land Use:</b> (Please circle/check one)	Residential	Non-residential			<b>8. Site (acres):</b>			5.129	
<b>9. Application Fee:</b>	\$5,000		<b>10. Permanent BMP(s):</b>			(2) Partial sedimentation filtration basins			
<b>11. SCS (Linear Ft.):</b>	N/A		<b>12. AST/UST (No. Tanks):</b>			N/A			
<b>13. County:</b>	Comal		<b>14. Watershed:</b>			Blieders Creek			

# Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the “Texas Groundwater Conservation Districts within the EAPP Boundaries” map found at:

[http://www.tceq.texas.gov/assets/public/compliance/field\\_ops/eapp/EAPP%20GWCD%20map.pdf](http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf)

For more detailed boundaries, please contact the conservation district directly.

<b>Austin Region</b>			
<b>County:</b>	<b>Hays</b>	<b>Travis</b>	<b>Williamson</b>
Original (1 req.)	—	—	—
Region (1 req.)	—	—	—
County(ies)	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Barton Springs/ Edwards Aquifer <input type="checkbox"/> Hays Trinity <input type="checkbox"/> Plum Creek	<input type="checkbox"/> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<input type="checkbox"/> Austin <input type="checkbox"/> Buda <input type="checkbox"/> Dripping Springs <input type="checkbox"/> Kyle <input type="checkbox"/> Mountain City <input type="checkbox"/> San Marcos <input type="checkbox"/> Wimberley <input type="checkbox"/> Woodcreek	<input type="checkbox"/> Austin <input type="checkbox"/> Bee Cave <input type="checkbox"/> Pflugerville <input type="checkbox"/> Rollingwood <input type="checkbox"/> Round Rock <input type="checkbox"/> Sunset Valley <input type="checkbox"/> West Lake Hills	<input type="checkbox"/> Austin <input type="checkbox"/> Cedar Park <input type="checkbox"/> Florence <input type="checkbox"/> Georgetown <input type="checkbox"/> Jerrell <input type="checkbox"/> Leander <input type="checkbox"/> Liberty Hill <input type="checkbox"/> Pflugerville <input type="checkbox"/> Round Rock

<b>San Antonio Region</b>					
<b>County:</b>	<b>Bexar</b>	<b>Comal</b>	<b>Kinney</b>	<b>Medina</b>	<b>Uvalde</b>
Original (1 req.)	—	<u>X</u>	—	—	—
Region (1 req.)	—	<u>X</u>	—	—	—
County(ies)	—	<u>X</u>	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Trinity-Glen Rose	<input checked="" type="checkbox"/> Edwards Aquifer Authority	<input type="checkbox"/> Kinney	<input type="checkbox"/> EAA <input type="checkbox"/> Medina	<input type="checkbox"/> EAA <input type="checkbox"/> Uvalde
City(ies) Jurisdiction	<input type="checkbox"/> Castle Hills <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Helotes <input type="checkbox"/> Hill Country Village <input type="checkbox"/> Hollywood Park <input type="checkbox"/> San Antonio (SAWS) <input type="checkbox"/> Shavano Park	<input type="checkbox"/> Bulverde <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Garden Ridge <input checked="" type="checkbox"/> New Braunfels <input type="checkbox"/> Schertz	NA	<input type="checkbox"/> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

James Ingalls, P.E.

Print Name of Customer/ Authorized Agent

Signature of Customer/Authorized Agent

Date 10-20-23

**FOR TCEQ INTERNAL USE ONLY**			
Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

# General Information Form

## Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

*To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.*

*Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.*


## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **General Information Form** is hereby submitted for TCEQ review. The application was prepared by:

Print Name of Customer/Agent: James Ingalls, P.E.

Date: 10-20-23

Signature of Customer/Agent:



## Project Information

1. Regulated Entity Name: Texas Tito's
2. County: Comal
3. Stream Basin: Blieders Creek
4. Groundwater Conservation District (If applicable): Comal Trinity GCD, Edwards Aquifer Authority
5. Edwards Aquifer Zone:
  - Recharge Zone
  - Transition Zone
6. Plan Type:
  - WPAP
  - SCS
  - Modification
  - AST

UST

Exception Request

7. Customer (Applicant):

Contact Person: Chris Snider

Entity: Blieders Creek, LLC

Mailing Address: 422 Saddle Tree

City, State: New Braunfels, TX

Telephone: \_\_\_\_\_

Email Address: chris@texastitos.com

Zip: 78130

FAX: \_\_\_\_\_

8. Agent/Representative (If any):

Contact Person: James Ingalls, P.E.

Entity: INK Civil

Mailing Address: 2021 SH 46W, Ste 105

City, State: New Braunfels, TX

Telephone: (830) 358-7127

Email Address: jamesingalls@ink-civil.com

Zip: 78132

FAX: (830) 515-5611

9. Project Location:

The project site is located inside the city limits of New Braunfels.

The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of \_\_\_\_\_.

The project site is not located within any city's limits or ETJ.

10.  The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

Approxiamtly 0.10 miles southeast of Loop 337 and River Road intersection.

11.  **Attachment A – Road Map.** A road map showing directions to and the location of the project site is attached. The project location and site boundaries are clearly shown on the map.

12.  **Attachment B - USGS / Edwards Recharge Zone Map.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached. The map(s) clearly show:

Project site boundaries.

USGS Quadrangle Name(s).

Boundaries of the Recharge Zone (and Transition Zone, if applicable).

Drainage path from the project site to the boundary of the Recharge Zone.

13.  **The TCEQ must be able to inspect the project site or the application will be returned.** Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment.

Survey staking will be completed by this date: 5/10/2022

14.  **Attachment C – Project Description.** Attached at the end of this form is a detailed narrative description of the proposed project. The project description is consistent throughout the application and contains, at a minimum, the following details:

- Area of the site
- Offsite areas
- Impervious cover
- Permanent BMP(s)
- Proposed site use
- Site history
- Previous development
- Area(s) to be demolished

15. Existing project site conditions are noted below:

- Existing commercial site
- Existing industrial site
- Existing residential site
- Existing paved and/or unpaved roads
- Undeveloped (Cleared)
- Undeveloped (Undisturbed/Uncleared)
- Other: \_\_\_\_\_

### ***Prohibited Activities***

16.  I am aware that the following activities are prohibited on the Recharge Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
- (2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
- (3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
- (4) The use of sewage holding tanks as parts of organized collection systems; and
- (5) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
- (6) New municipal and industrial wastewater discharges into or adjacent to water in the state that would create additional pollutant loading.

17.  I am aware that the following activities are prohibited on the Transition Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);

- (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
- (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

### ***Administrative Information***

18. The fee for the plan(s) is based on:

- For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur.
- For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines.
- For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems.
- A request for an exception to any substantive portion of the regulations related to the protection of water quality.
- A request for an extension to a previously approved plan.

19.  Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

- TCEQ cashier
- Austin Regional Office (for projects in Hays, Travis, and Williamson Counties)
- San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

20.  Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.


21.  No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.



**CITY LIMITS**


**PROJECT SITE**

TEXAS TITO'S  
NEW BRAUNFELS, TX





1 inch = 500 feet

Legend  
Cadastral



Produced by the United States Geological Survey in cooperation with the Defense Mapping Agency Control by USGS and NOS/NOAA and USCE  
Compiled from aerial photographs taken 1966. Revisions in purple and woodland compiled from aerial photographs taken 1986 and other sources and has been field checked. Map edited 1994.  
Conflicts may exist between some updated features and previously mapped contours  
North American Datum of 1927 (NAD 27). Projection and 10,000-foot ticks: Texas Coordinate System, south central zone (Lambert Conformal Conic)  
Blue 1000-meter Universal Transverse Mercator ticks, zone 14  
North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are obtainable from National Geodetic Survey NADCON software



ROAD CLASSIFICATION

Primary highway, hard surface	Light-duty road, hard or improved surface
Secondary highway, hard surface	Unimproved road
Interstate Route	U.S. Route
	State Route



THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

NEW BRAUNFELS EAST, TEX.  
29098-F1-1F-024  
1968  
REVISED 1994  
DMA 6343 II NE-SERIES V882

2998-414

**ATTACHMENT "C"**  
**Project Description**

The proposed site is 5.13 acres. The entire site will be disturbed with 3.53 acres of impervious cover (68.8%). The lot is located within the New Braunfels city limits at the intersection of Loop 337 and River Road. The site is served by New Braunfels Utilities for electric, water, and wastewater. The site is currently established with a large mound of fill material. There are currently no above ground improvements.

The proposed use for the project is a 35,280 square foot manufacturing building with a 12,600 warehouse expansion, and a secondary 12,645 square foot office building totaling 60,525 sf. No other planned uses are proposed for this site. A more detailed breakdown of the impervious areas can be found in the WPAP Application Table 1.

The proposed construction will include minor grading for the parking areas and building pad, a sand filtration pond, utility service lines and building infrastructure.

According to the Flood Insurance Rate Map No. 48091C0455F, a portion of the site is inside the special flood hazard zone A and AE. The entire site drains to Blieders Creek. The sites runoff will be captured by storm drains and parking lot that will drain to a sand filtration ponds on the northeast and south sides of the site. The sand filtration ponds will ensure the quality of water exiting without adversely affecting the downstream drainage patterns.

**Modification Description**

The modification to the approved WPAP is regarding the design specifications of the BMPs. In the approved plans, the sedimentation chamber was specified to be concrete bottom. It is in the interest of the owner to amend the plans to have earthen bottoms for the sedimentation chamber portion of the BMP. No further revisions to the plans are proposed.

**Geologic Assessment**  
 For Regulated Activities  
 on The Edwards Aquifer Recharge/transition Zones  
 and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

REGULATED ENTITY NAME: Blieders Creek Commercial – 10.7 Acre Site New Braunfels

TYPE OF PROJECT:  WPAP     AST     SCS     UST

LOCATION OF PROJECT:  Recharge Zone     Transition Zone     Contributing Zone within the Transition Zone

PROJECT INFORMATION

1.  Geologic or manmade features are described and evaluated using the attached **GEOLOGIC ASSESSMENT TABLE**.
2. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups\* (*Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986*). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Soil Units, Infiltration Characteristics & Thickness			* Soil Group Definitions (Abbreviated)  A. Soils having a <u>high infiltration</u> rate when thoroughly wetted.  B. Soils having a <u>moderate infiltration</u> rate when thoroughly wetted.  C. Soils having a <u>slow infiltration</u> rate when thoroughly wetted.  D. Soils having a <u>very slow infiltration</u> rate when thoroughly wetted.
Soil Name	Group*	Thickness (feet)	
CrD	C	0 – 1'	
LeB	D	0 – 5'	
Or	D	0 – 2'	

3.  A **STRATIGRAPHIC COLUMN** is attached at the end of this form that shows formations, members, and thicknesses. The outcropping unit should be at the top of the stratigraphic column.
4.  A **NARRATIVE DESCRIPTION OF SITE SPECIFIC GEOLOGY** is attached at the end of this form. The description must include a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure, and karst characteristics of the site.
5.  Appropriate **SITE GEOLOGIC MAP(S)** are attached:

The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1" : 400'

Applicant's Site Plan Scale	1" = <u>50</u> '
Site Geologic Map Scale	1" = <u>50</u> '
Site Soils Map Scale (if more than 1 soil type)	1" = <u>50</u> '

6. Method of collecting positional data:  
 Global Positioning System (GPS) technology.

Other method(s).

- 7.   X   The project site is shown and labeled on the Site Geologic Map.
- 8.    Surface geologic units are shown and labeled on the Site Geologic Map.
- 9.   X   Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.  
   Geologic or manmade features were not discovered on the project site during the field investigation.
- 10.    The Recharge Zone boundary is shown and labeled, if appropriate.
- 11. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.):  
  X   There are   2   (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)  
   The wells are not in use and have been properly abandoned.  
  1   The wells are not in use and will be properly abandoned.  
  1   The wells are in use and comply with 16 TAC Chapter 76.  
   There are no wells or test holes of any kind known to exist on the project site.

ADMINISTRATIVE INFORMATION


- 12.   X   Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

Date(s) Geologic Assessment was performed:   August 1, 2013    
Date(s)

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Thomas Owen Mathews II  
Print Name of Geologist

830-249-8284  
Telephone



830-249-0221  
Fax

*Thomas Owen Mathews II*  
Signature of Geologist   765321  

  4/10/14    
Date

Representing:   Westward Environmental, Inc.    
(Name of Company)

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282.

**GEOLOGIC ASSESSMENT TABLE** PROJECT NAME: **Bladders Creek Commercial - 10.7 Acres - New Braunfels**

LOCATION		FEATURE CHARACTERISTICS										EVALUATION			PHYSICAL SETTING	
1A	1B*	1C*	2A	2B	3	4	5	6	7	8A	8B	9	10	11	12	
FEATURE ID	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)	TREND (DEGREES)	DENSITY (G/CM <sup>3</sup> )	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY	CATCHMENT AREA (ACRES)	TOPOGRAPHY	
						X Y Z							<40	<1.6		
S-1	N29° 43.6144818	N98° 7.4471598'	MM	30	Ked	6 7 10		10		C		35	X	X	Floodplain	
S-2	N29° 43.6666338	N98° 7.5040854'	MM	30	Ked	Unknown				X		10	X	X	Hillside	
S-3	N29° 43.6339212	N98° 7.405575'	MM	30	Ked	~1,100' long				C/O		9	X	X	Floodplain	

\* DATUM: NAD 83

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30

8A INFILLING
N None, exposed bedrock
C Coarse - cobbles, breakdown, sand, gravel
O Loose or soft mud or soil, organics, leaves, sticks, dark colors
F Fines, compacted clay-rich sediment, soil profile, gray or red colors
V Vegetation. Give details in narrative description
FS Flowstone, cements, cave deposits
X Other materials

12 TOPOGRAPHY  
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understand, and I have followed the Texas Commission on Environmental Quality's instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

*Thomas Mathews*  
PG5324

4-10-14



## Soils Narrative

**Geologic Site Review  
Blieiders Creek Commercial  
10.7 Acres  
New Braunfels, Comal County, Texas  
WEI Proj.: 10749-003**

In accordance with the United States department of Agriculture (USDA) Web Soil Survey, There are three different native surficial soils mapped at the site. The primary unit mapped is the Lewisville silty clay (LeB) followed by the Orif soils (Or), and the Comfort-Rock outcrop complex (CrD).

- LeB: The Lewisville silty clay has slopes that range from 1% - 3% and is moderately drained. LeB has a maximum calcium carbonate content of 40% and a typical profile is mapped as silty clay from 0 – 61”.
- Or: The Orif soils are a frequently flooded soil with 0% to 1% slopes and is moderately drained. Or has a maximum calcium carbonate content of 90%. This soil type has a typical profile of 0 – 20” of gravelly loamy sand followed by 20 – 40” of extremely gravelly sand before reaching 40 – 80” of coarse sand.
- CrD: The Comfort-Rock outcrop complex soil unit has slopes that range from 1% - 8% and is moderately drained. With a maximum calcium carbonate content of 20% this soil type has a typical profile of 0 – 13” extremely stony clay followed by bedrock from 13 – 20”.

Attachment C  
Stratigraphic Column

Blieders Creek Commercial  
10.7 acre New Braunfels Tract  
Stratigraphic Column

System	Series	Group	Formation	Member	Thickness (feet)	Lithology	Field ID
	Comanchean	Fredricksburg (Edwards)	Person	Leached & Collapsed Members undivided	70-90	Crystalline limestone; mudstone to grainstone; chert; collapsed breccia	Bioturbated iron- stained beds separated by massive limestone beds; stromatolitic limestone

## Geologic Narrative

### **Geologic Assessment Blieders Creek Commercial New Braunfels, Comal County, Texas WEI Proj.: 10749-003**

#### Introduction

A Geologic Assessment (GA) was performed for the above-referenced site on August 1, 2013 by a Westward Environmental, Inc. (Westward) field crew led by Thomas O. Mathews II, P.G. #5321 of Westward. The GA was performed at the ~10.7 acre site in accordance with the Texas Commission on Environmental Quality (TCEQ) *Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zones, TCEQ-0585-Instructions (Rev. 10-01-04)*. During the field reconnaissance, three potential recharge features, as defined by the TCEQ-0585, were observed on the surface of the site at the time of this assessment.

#### Background

The proposed project area is a section of partially developed land located at 1246 River Road, New Braunfels, Texas and is located within an area of rural land and commercial/industrial businesses. The project area is approximate 10.7 acres in size and encompasses various types of geographical settings; with flat to gently sloping surfaces in the northwestern portion, to floodplain in the southeastern portion. According to the United States Geological Survey (USGS) 7.5 Minute Series Topographic Maps, the site has an approximate elevation of 635 feet above mean sea level. General surface drainage appears to flow to the east towards Blieders Creek.

The subject site has been utilized for a trucking yard. The facility currently contains an office/shop, entry/exit road, and employee parking. The buildings receive their electricity from New Braunfels Utilities and the sewer service from the City of New Braunfels Utilities. Water is supplied by an on-site well.

#### Stratigraphy & Structure

According to the *Texas Bureau of Economic Geology, Geologic Atlas of Texas San Antonio Sheet (1983)*, the geology at the subject property is Leached and Collapsed Member of the Edwards Group (Ked) Limestones. No structure was observed at the subject property.

#### Features Discussion

##### Caves

No caves were observed during field reconnaissance.

##### Closed Depressions

No closed depressions were observed during field reconnaissance.

### **Faults**

No faults were observed during field reconnaissance.

### **MB – Man-Made Feature(s) in Bedrock**

#### **S-1, S-2: Sensitive**

S-1 is a man-made feature consisting of a hand dug well in the flood plain. The well is partially filled with sediment. The well is approximately 6-7 feet in diameter and 10 feet deep. The feature is located in the floodplain and therefore has a high probability of rapid infiltration, Due to these factors the feature is considered sensitive. The well is not in use, does not meet the standards of 16 TAC 76 and the owner intends to plug the well.

S-2 is a man-made feature consisting of an in-use water well. The well is located within a storage building at the site. The slab around the well is cracked and needs to be repaired in order to bring the well into full compliance. The probability of rapid infiltration is low and the well is considered marginally sensitive with a score of 40. Upon repair of the slab the probability of rapid infiltration will be reduced to less than >10 and the feature will then be considered not sensitive.

**S-3 Not Sensitive** S-3 is a man-made feature consisting of a sewer line located within Blieders Creek that runs the length of the eastern portion of the subject site. The sewer line appears to have been backfilled with the materials that were excavated during its construction. Given that any features encountered during sewer line construction were required to be sealed in accordance with 30 TAC 213 requirements, the probability of rapid infiltration is considered to be low and the feature is considered not sensitive.

### **Sinkholes**

Sinkholes were not observed during this assessment.

### **Solution Enlarged Fractures**

Solution Enlarged Fractures were not observed during this assessment.

### **Solution Caviities**

Solution Cavities were not observed during this assessment.

### **Swallow Holes**

Swallow Holes were not observed during this assessment.

### **Other Features**

No other features were observed during this assessment.

IMAGE:  
 NEW BRAUNFELS WEST 2012  
 ISSUE DATE: 03/03/2014  
 DRAWN BY: LJS  
 CHECKED BY: LJS  
 SCALE: 1" = 50'  
 JOB #: 10749-003

SHEET #:  
**01**  
 OF 01

**WESTWARD**  
 Environmental, Engineering, Natural Resources,  
 P.O. Box 2205 Boerne, Texas 78006  
 (830) 249-5284 Fax: (830) 249-0221  
 TBPE REG. NO.: F-4524  
 TBPG REG. NO.: 50112

REV.	DESCRIPTION	BY	DATE



**GA SENSITIVE FEATURES MAP**  
 GEOLOGIC ASSESSMENT  
 BEACH FAMILY LIMITED PARTNERSHIP  
 NEW BRAUNFELS, COMAL COUNTY, TX



N

SCALE: 1" = 50'

--- APPROXIMATE PROPERTY BOUNDARY

— SEWER LINE

⊕ SENSITIVE FEATURE

▨ FEMA 100 YEAR FLOODPLAIN

**SOILS**

Cd: COMFORT-ROCK OUTCROP COMPLEX, 1%–8% SLOPES

Ls: LEWISVILLE SILTY CLAY, 0%–1% SLOPES

Le: LEWISVILLE SILTY CLAY, 1%–3% SLOPES

Or: ORF SOILS, 0%–1% SLOPES, FREQUENTLY FLOODED

Pl: PITS

Pvc: PURVES CLAY, 1%–5% SLOPES

# Modification of a Previously Approved Plan

## Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Transition Zone and Relating to 30 TAC 213.4(j), Effective June 1, 1999

*To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.*

*Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.*

## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This request for a **Modification of a Previously Approved Plan** is hereby submitted for TCEQ review and executive director approval. The request was prepared by:

Print Name of Customer/Agent: James Ingalls, PE

Date: 10-20-23

Signature of Customer/Agent:



## Project Information

1. Current Regulated Entity Name: Texas Tito's  
Original Regulated Entity Name: Texas Tito's  
Regulated Entity Number(s) (RN): 111484024  
Edwards Aquifer Protection Program ID Number(s): 13001528  
 The applicant has not changed and the Customer Number (CN) is: 606009058  
 The applicant or Regulated Entity has changed. A new Core Data Form has been provided.
2.  **Attachment A: Original Approval Letter and Approved Modification Letters.** A copy of the original approval letter and copies of any modification approval letters are attached.

3. A modification of a previously approved plan is requested for (check all that apply):
- Physical or operational modification of any water pollution abatement structure(s) including but not limited to ponds, dams, berms, sewage treatment plants, and diversionary structures;
  - Change in the nature or character of the regulated activity from that which was originally approved or a change which would significantly impact the ability of the plan to prevent pollution of the Edwards Aquifer;
  - Development of land previously identified as undeveloped in the original water pollution abatement plan;
  - Physical modification of the approved organized sewage collection system;
  - Physical modification of the approved underground storage tank system;
  - Physical modification of the approved aboveground storage tank system.
4.  Summary of Proposed Modifications (select plan type being modified). If the approved plan has been modified more than once, copy the appropriate table below, as necessary, and complete the information for each additional modification.

<b><i>WPAP Modification</i></b>	<b><i>Approved Project</i></b>	<b><i>Proposed Modification</i></b>
<b><i>Summary</i></b>		
Acres	<u>5.13</u>	<u>5.13</u>
Type of Development	<u>Commercial</u>	<u>Commercial</u>
Number of Residential Lots	_____	_____
Impervious Cover (acres)	<u>3.53</u>	<u>3.53</u>
Impervious Cover (%)	<u>68.8</u>	<u>68.8</u>
Permanent BMPs	2 - partial <u>sedimentation basins</u>	2 - partial <u>sedimentation basins</u>
Other	_____	_____

<b><i>SCS Modification</i></b>	<b><i>Approved Project</i></b>	<b><i>Proposed Modification</i></b>
<b><i>Summary</i></b>		
Linear Feet	_____	_____
Pipe Diameter	_____	_____
Other	_____	_____

<b>AST Modification</b>	<b>Approved Project</b>	<b>Proposed Modification</b>
<b>Summary</b>		
Number of ASTs	_____	_____
Volume of ASTs	_____	_____
Other	_____	_____

<b>UST Modification</b>	<b>Approved Project</b>	<b>Proposed Modification</b>
<b>Summary</b>		
Number of USTs	_____	_____
Volume of USTs	_____	_____
Other	_____	_____

5.  **Attachment B: Narrative of Proposed Modification.** A detailed narrative description of the nature of the proposed modification is attached. It discusses what was approved, including any previous modifications, and how this proposed modification will change the approved plan.
  
6.  **Attachment C: Current Site Plan of the Approved Project.** A current site plan showing the existing site development (i.e., current site layout) at the time this application for modification is attached. A site plan detailing the changes proposed in the submitted modification is required elsewhere.
  - The approved construction has not commenced. The original approval letter and any subsequent modification approval letters are included as Attachment A to document that the approval has not expired.
  - The approved construction has commenced and has been completed. Attachment C illustrates that the site was constructed as approved.
  - The approved construction has commenced and has been completed. Attachment C illustrates that the site was **not** constructed as approved.
  - The approved construction has commenced and has **not** been completed. Attachment C illustrates that, thus far, the site was constructed as approved.
  - The approved construction has commenced and has **not** been completed. Attachment C illustrates that, thus far, the site was **not** constructed as approved.
  
7.  The acreage of the approved plan has increased. A Geologic Assessment has been provided for the new acreage.
  - Acreage has not been added to or removed from the approved plan.
  
8.  Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

Jon Niermann, *Chairman*  
Emily Lindley, *Commissioner*  
Bobby Janecka, *Commissioner*  
Toby Baker, *Executive Director*



## TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

*Protecting Texas by Reducing and Preventing Pollution*

July 8, 2022

Mr. Chris Snider  
Blieders Creek, LLC  
422 Saddle Tree  
New Braunfels, Texas 78130

Re: Edwards Aquifer, Comal County

NAME OF PROJECT: Texas Titos; Located approximately 10 miles southeast of Loop 337 and River Rd intersection; New Braunfels, Texas

TYPE OF PLAN: Request for Approval of a Water Pollution Abatement Plan (WPAP); 30 Texas Administrative Code (TAC) Chapter 213 Edwards Aquifer

Regulated Entity No. RN111481024; Additional ID No. 13001528

Dear Mr. Snider:

The Texas Commission on Environmental Quality (TCEQ) has completed its review of the WPAP application for the above-referenced project submitted to the San Antonio Regional Office by Ink Civil on behalf of Blieders Creek, LLC on April 25, 2022. Final review of the WPAP was completed after additional material was received on July 5, 2022. As presented to the TCEQ, the Temporary and Permanent Best Management Practices (BMPs) were selected and construction plans were prepared by a Texas Licensed Professional Engineer to be in general compliance with the requirements of 30 TAC Chapter 213. These planning materials were sealed, signed, and dated by a Texas Licensed Professional Engineer. Therefore, based on the engineer's concurrence of compliance, the planning materials for construction of the proposed project and pollution abatement measures are hereby approved subject to applicable state rules and the conditions in this letter. The applicant or a person affected may file with the chief clerk a motion for reconsideration of the executive director's final action on this Edwards Aquifer Protection Plan. A motion for reconsideration must be filed no later than 23 days after the date of this approval letter. *This approval expires two (2) years from the date of this letter unless, prior to the expiration date, more than 10 percent of the construction has commenced on the project or an extension of time has been requested.*

### PROJECT DESCRIPTION

The proposed commercial project will have an area of approximately 5.13 acres. It will include one building with associated parking, drives, and utilities. The impervious cover will be 3.53 acres (68.8 percent). Project wastewater will be disposed of by conveyance to the existing Gruene Road Water Reclamation Facility owned by New Braunfels Utilities.

### PERMANENT POLLUTION ABATEMENT MEASURES

To prevent the pollution of stormwater runoff originating on-site or upgradient of the site and potentially flowing across and off the site after construction, two partial sedimentation/filtration basins, designed using the TCEQ technical guidance document, Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices (2005), will be constructed to treat stormwater runoff. The required total suspended solids (TSS) treatment for this project is 3,169 pounds of TSS generated from the 3.53 acres of impervious cover. The approved measures meet the required 80 percent removal of the increased load in TSS caused by the project.

### GEOLOGY

According to the geologic assessment included with the application, the site lies on the leached and collapsed members of the Person Formation. Three man-made features in bedrock, one rated non-sensitive and two rated sensitive, were identified in the geologic assessment. The site assessment conducted on June 13, 2022, revealed the site was generally as described in the geologic assessment.

### SPECIAL CONDITIONS

- I. All permanent pollution abatement measures shall be operational prior to first occupancy of the facilities within their respective drainage areas.
- II. All sediment and/or media removed from the water quality basins during maintenance activities shall be properly disposed of according to 30 TAC 330 or 30 TAC 335, as applicable.

### STANDARD CONDITIONS

1. Pursuant to Chapter 7 Subchapter C of the Texas Water Code, any violations of the requirements in 30 TAC Chapter 213 may result in administrative penalties.
2. The holder of the approved Edwards Aquifer protection plan must comply with all provisions of 30 TAC Chapter 213 and all best management practices and measures contained in the approved plan. Additional and separate approvals, permits, registrations and/or authorizations from other TCEQ Programs (i.e., Stormwater, Water Rights, UIC) can be required depending on the specifics of the plan.
3. In addition to the rules of the Commission, the applicant may also be required to comply with state and local ordinances and regulations providing for the protection of water quality.

### Prior to Commencement of Construction:

4. Within 60 days of receiving written approval of an Edwards Aquifer Protection Plan, the applicant must submit to the San Antonio Regional Office, proof of recordation of notice in the county deed records, with the volume and page number(s) of the county deed records of the county in which the property is located. A description of the property boundaries shall be included in the deed recordation in the county deed records. A suggested form (Deed Recordation Affidavit, TCEQ-0625) that you may use to deed record the approved WPAP is enclosed.
5. All contractors conducting regulated activities at the referenced project location shall be provided a copy of this notice of approval. At least one complete copy of the approved WPAP and this notice of approval shall be maintained at the project location until all regulated activities are completed.
6. Modification to the activities described in the referenced WPAP application following the date of approval may require the submittal of a plan to modify this approval, including the payment of appropriate fees and all information necessary for its review and approval prior to initiating construction of the modifications.

7. The applicant must provide written notification of intent to commence construction, replacement, or rehabilitation of the referenced project. Notification must be submitted to the San Antonio Regional Office no later than 48 hours prior to commencement of the regulated activity. Written notification must include the date on which the regulated activity will commence, the name of the approved plan and program ID number for the regulated activity, and the name of the prime contractor with the name and telephone number of the contact person. The executive director will use the notification to determine if the approved plan is eligible for an extension.
8. Temporary erosion and sedimentation (E&S) controls, i.e., silt fences, rock berms, stabilized construction entrances, or other controls described in the approved WPAP, must be installed prior to construction, and maintained during construction. Temporary E&S controls may be removed when vegetation is established and the construction area is stabilized. If a water quality pond is proposed, it shall be used as a sedimentation basin during construction. The TCEQ may monitor stormwater discharges from the site to evaluate the adequacy of temporary E&S control measures. Additional controls may be necessary if excessive solids are being discharged from the site.
9. All borings with depths greater than or equal to 20 feet must be plugged with non-shrink grout from the bottom of the hole to within three (3) feet of the surface. The remainder of the hole must be backfilled with cuttings from the boring. All borings less than 20 feet must be backfilled with cuttings from the boring. All borings must be backfilled or plugged within four (4) days of completion of the drilling operation. Voids may be filled with gravel.

During Construction:

10. During the course of regulated activities related to this project, the applicant or agent shall comply with all applicable provisions of 30 TAC Chapter 213, Edwards Aquifer. The applicant shall remain responsible for the provisions and conditions of this approval until such responsibility is legally transferred to another person or entity.
11. This approval does not authorize the installation of temporary aboveground storage tanks on this project. If the contractor desires to install a temporary aboveground storage tank for use during construction, an application to modify this approval must be submitted and approved prior to installation. The application must include information related to tank location and spill containment. Refer to Standard Condition No. 6, above.
12. If any sensitive feature (caves, solution cavities, sink holes, etc.) is discovered during construction, all regulated activities near the feature must be suspended immediately. The applicant or his agent must immediately notify the San Antonio Regional Office of the discovery of the feature. Regulated activities near the feature may not proceed until the executive director has reviewed and approved the methods proposed to protect the feature and the aquifer from potentially adverse impacts to water quality. The plan must be sealed, signed, and dated by a Texas Licensed Professional Engineer.
13. Two wells exist on site. All water wells, including injection, dewatering, and monitoring wells must be in compliance with the requirements of the Texas Department of Licensing and Regulation under Title 16 TAC Chapter 76 (relating to Water Well Drillers and Pump Installers) and all other locally applicable rules, as appropriate.
14. If sediment escapes the construction site, the sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50 percent. Litter, construction debris, and construction chemicals shall be prevented from becoming stormwater discharge pollutants.
15. Intentional discharges of sediment laden water are not allowed. If dewatering becomes necessary, the discharge will be filtered through appropriately selected best management practices. These may include vegetated filter strips, sediment traps, rock berms, silt fence rings, etc.
16. The following records shall be maintained and made available to the executive director upon request: the dates when major grading activities occur, the dates when construction

activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.


17. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, and construction activities will not resume within 21 days. When the initiation of stabilization measures by the 14th day is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable.

After Completion of Construction:

18. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the San Antonio Regional Office within 30 days of site completion.
19. The applicant shall be responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. The regulated entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred. A copy of the transfer of responsibility must be filed with the executive director through San Antonio Regional Office within 30 days of the transfer. A copy of the transfer form (TCEQ-10263) is enclosed.
20. Upon legal transfer of this property, the new owner(s) is required to comply with all terms of the approved Edwards Aquifer protection plan. If the new owner intends to commence any new regulated activity on the site, a new Edwards Aquifer protection plan that specifically addresses the new activity must be submitted to the executive director. Approval of the plan for the new regulated activity by the executive director is required prior to commencement of the new regulated activity.
21. An Edwards Aquifer protection plan approval or extension will expire and no extension will be granted if more than 50 percent of the total construction has not been completed within ten years from the initial approval of a plan. A new Edwards Aquifer protection plan must be submitted to the San Antonio Regional Office with the appropriate fees for review and approval by the executive director prior to commencing any additional regulated activities.
22. At project locations where construction is initiated and abandoned, or not completed, the site shall be returned to a condition such that the aquifer is protected from potential contamination.

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality. If you have any questions or require additional information, please contact Mr. Joshua Vacek of the Edwards Aquifer Protection Program of the San Antonio Regional Office at 210-403-4028.

Sincerely,



Lillian Butler, Section Manager  
Edwards Aquifer Protection Program  
Texas Commission on Environmental Quality

LIB/jv


Enclosures: Deed Recordation Affidavit, Form TCEQ-0625  
Change in Responsibility for Maintenance of Permanent BMPs, Form TCEQ-10263

cc: Mr. Shane Klar, P.E., INK Civil

**ATTACHMENT "B"**  
**Modification Description**

The modification to the approved WPAP is regarding the design specifications of the BMPs. In the approved plans, the sedimentation chamber was specified to be concrete bottom. It is in the interest of the owner to amend the plans to have earthen bottoms with an impermeable liner for the sedimentation chamber portion of the BMP. No further revisions to the plans are proposed.

Project Control Points				
Point #	Row Description	Elevation	Northing	Easting
19	CP MAG	656.82	13813270.6850	2246277.3320
20	CP 60D	650.79	13813343.3960	2246518.4510
21	CP 60D	653.54	13813222.8800	2246576.2560
22	CP 60D	639.35	13813084.1575	2246497.0331
23	CP 60D	638.35	13812951.5990	2246472.8080
24	CP 60D	637.11	13812738.1060	2246425.5820



LEGEND	
	SILT FENCE
	LIMITS OF CONSTRUCTION
	EXISTING CONTOURS
	PROPOSED CONTOURS
	FLOW ARROWS
	STABILIZED CONSTRUCTION ENTRANCE/EXIT
	TRUCK WASH OUT PIT
	CONSTRUCTION STAGING AREA
	LIMITS OF CONSTRUCTION

**SILT FENCE**

- Materials:
- (1) Silt fence material should be polypropylene, polyethylene or polyamide woven or non-woven fabric. The fabric width should be 36 inches, with a minimum unit weight of 4.5 oz/yd, mullen burst strength exceeding 190 lb/in<sup>2</sup>, ultraviolet stability exceeding 70%, and minimum apparent opening size of U.S. Sieve No. 30.
  - (2) Fence posts should be made of hot rolled steel, at least 4 feet long with Tee or Ybar cross section, surface painted or galvanized, minimum nominal weight 1.25 lb/ft<sup>2</sup>, and Brinell hardness exceeding 140.
  - (3) Woven wire backing to support the fabric should be galvanized 2" x 4" welded wire, 12 gauge minimum.

Installation:

- (1) Steel posts, which support the silt fence, should be installed on a slight angle toward the anticipated runoff source. Post must be embedded a minimum of 1-foot deep and spaced not more than 8 feet on center. Where water concentrates, the maximum spacing should be 6 feet.
- (2) Lay out fencing down-slope of disturbed area, following the contour as closely as possible. The fence should be sited so that the maximum drainage area is 1/4 acre/100 feet of fence.
- (3) The toe of the silt fence should be trenched in with a spade or mechanical trencher, so that the down-slope face of the trench is flat and perpendicular to the line of flow. Where fence cannot be trenched in (e.g., pavement or rock outcrop), weight fabric flap with 3 inches of pea gravel on uphill side to prevent flow from seeping under fence.
- (4) The trench must be a minimum of 6 inches deep and 6 inches wide to allow for the silt fence fabric to be laid in the ground and backfilled with compacted material.
- (5) Silt fence should be securely fastened to each steel support post or to woven wire, which is in turn attached to the steel fence post. There should be a 3-foot overlap, securely fastened where ends of fabric meet.
- (6) Silt fence should be removed when the site is completely stabilized so as not to block or impede storm flow or drainage.

Inspection and Maintenance Guidelines:

- (1) Inspect all fencing weekly, and after any rainfall.
- (2) Remove sediment when buildup reaches 6 inches.
- (3) Replace any torn fabric or install a second line of fencing parallel to the torn section.
- (4) Replace or repair any sections crushed or collapsed in the course of construction activity. If a section of fence is obstructing vehicular access, consider relocating it to a spot where it will provide equal protection, but will not obstruct vehicles. A triangular filter dike may be preferable to a silt fence at common vehicle access points.
- (5) When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.

**HYDRAULIC MULCH**

MATERIALS:

**HYDRAULIC MULCHES:** WOOD FIBER MULCH CAN BE APPLIED ALONE OR AS A COMPONENT OF HYDRAULIC MATRICES. WOOD FIBER MULCH IS TYPICALLY APPLIED AT THE RATE OF 2,000 TO 4,000 LB/ACRE. WOOD FIBER MULCH IS MANUFACTURED FROM WOOD OR WOOD WASTE FROM LUMBER MILLS OR FROM URBAN SOURCES.

**HYDRAULIC MATRICES:** HYDRAULIC MATRICES INCLUDE A MIXTURE OF WOOD FIBER AND ACRYLIC POLYMER OR OTHER TACKIFIER AS BINDER. APPLY AS A LIQUID SLURRY USING A HYDRAULIC APPLICATION MACHINE (I.E., HYDRO SEEDER) AT THE FOLLOWING MINIMUM RATES, OR AS SPECIFIED BY THE MANUFACTURER TO ACHIEVE COMPLETE COVERAGE OF THE TARGET AREA: 2,000 TO 4,000 LB/ACRE WOOD FIBER MULCH, AND 5 TO 10% (BY WEIGHT) OF TACKIFIER (ACRYLIC COPOLYMER, GUAR, PSTILLUM, ETC.)



**BONDED FIBER MATRIX:** BONDED FIBER MATRIX (BFM) IS A HYDRAULICALLY APPLIED SYSTEM OF FIBERS AND ADHESIVES THAT UPON DRYING FORMS AN EROSION RESISTANT BLANKET THAT PROMOTES VEGETATION, AND PREVENTS SOIL EROSION. BFMS ARE TYPICALLY APPLIED AT RATES FROM 3,000 LB/ACRE TO 4,000 LB/ACRE BASED ON THE MANUFACTURER'S RECOMMENDATION. A BIODEGRADABLE BFM IS COMPOSED OF MATERIALS THAT ARE 100% BIODEGRADABLE. THE BINDER IN THE BFM SHOULD ALSO BE BIODEGRADABLE AND SHOULD NOT DISSOLVE OR DISPERSE UPON RE-WETTING. TYPICALLY, BIODEGRADABLE BFMS SHOULD NOT BE APPLIED IMMEDIATELY BEFORE, DURING OR IMMEDIATELY AFTER RAINFALL IF THE SOIL IS SATURATED. DEPENDING ON THE PRODUCT, BFMS TYPICALLY REQUIRE 12 TO 24 HOURS TO DRY AND BECOME EFFECTIVE.

INSTALLATION:



1. PRIOR TO APPLICATION, ROUGHEN EMBANKMENT AND FILL AREAS BY ROLLING WITH A CRUMPING OR PUNCHING TYPE ROLLER OR BY TRACK WALKING. TRACK WALKING SHALL ONLY BE USED WHERE OTHER METHODS ARE IMPRACTICAL.
2. TO BE EFFECTIVE, HYDRAULIC MATRICES REQUIRE 24 HOURS TO DRY BEFORE RAINFALL OCCURS.
3. AVOID MULCH OVER SPRAY ONTO ROADS, SIDEWALKS, DRAINAGE CHANNELS, EXISTING VEGETATION, ETC.
4. 4" OF TOP SOIL SHALL BE PLACED.

INSPECTION AND MAINTENANCE GUIDELINES:


1. MULCHED AREAS SHOULD BE INSPECTED WEEKLY AND AFTER EACH RAIN EVENT TO LOCATE AND REPAIR ANY DAMAGE.
2. AREAS DAMAGED BY STORMS OR NORMAL CONSTRUCTION ACTIVITIES SHOULD BE REGRADED AND HYDRAULIC MULCH REAPPLIED AS SOON AS PRACTICAL.



**TYPICAL CONCRETE TRUCK WASHOUT PIT**



**STABILIZED CONSTRUCTION ENTRANCE / EXIT**



**TYPICAL CONSTRUCTION STAGING AREA**

**SOIL STABILIZATION NOTE**

PER TPDES REQUIREMENTS, DISTURBED AREAS ON WHICH CONSTRUCTION ACTIVITIES HAVE CEASED (TEMPORARILY OR PERMANENTLY) SHALL BE STABILIZED WITHIN 14 DAYS UNLESS ACTIVITY RESUMES WITHIN 21 DAYS. SEEDING DOES NOT CONSTITUTE AS STABILIZATION.

SUBSTANTIAL GRADING IS PROPOSED WITH THIS UNIT. PER THE NEW BRAUNFELS DRAINAGE AND EROSION CONTROL DESIGN MANUAL SEC. 13.2(N), STRIPPING OF VEGETATION FROM PROJECT SITES SHALL BE PHASED SO AS TO EXPOSE THE MINIMUM AMOUNT OF AREA TO SOIL EROSION FOR THE SHORTEST POSSIBLE TIME.

EROSION CONTROL NOTES:

1. LIMITS OF CONSTRUCTION AND OTHER EROSION CONTROL IMPROVEMENTS SHOWN OUTSIDE THE PROPERTY ARE SHOWN FOR GRAPHICAL PURPOSE ONLY. IF NEAR PROPERTY LINE, THE INTENT IS TO BE PLACED NEAR THE PROPERTY LINE, NOT ON THE ADJACENT PROPERTY.
2. DO NOT DISTURB VEGETATED AREAS (TREES, GRASS, WEEDS, BRUSH, ETC.) ANY MORE THAN NECESSARY FOR CONSTRUCTION.
3. CONSTRUCTION ENTRANCE/EXIT LOCATION, CONCRETE WASH-OUT PIT, AND CONSTRUCTION EQUIPMENT AND MATERIAL STORAGE YARD TO BE DETERMINED IN THE FIELD.
4. STORM WATER POLLUTION PREVENTION CONTROLS MAY NEED TO BE MODIFIED IN THE FIELD TO ACCOMPLISH THE DESIRED EFFECT. ALL MODIFICATIONS ARE TO BE NOTED IN THE SWPPP DOCUMENTS AND SIGNED AND DATED BY THE RESPONSIBLE PARTY.
5. RESTRICT ENTRY/EXIT TO THE PROJECT SITE TO DESIGNATED LOCATIONS BY USE OF ADEQUATE FENCING, IF NECESSARY.
6. ALL STORM WATER POLLUTION PREVENTION CONTROLS ARE TO BE MAINTAINED AND IN WORKING CONDITIONS AT ALL TIMES.
7. STORM WATER POLLUTION PREVENTION STRUCTURES SHOULD BE CONSTRUCTED WITHIN THE SITE BOUNDARIES. SOME OF THESE FEATURES MAY BE SHOWN OUTSIDE THE SITE BOUNDARIES ON THIS PLAN FOR VISUAL CLARITY.
8. AS SOON AS PRACTICAL, ALL DISTURBED SOIL THAT WILL NOT BE COVERED BY IMPERVIOUS COVER SUCH AS PARKWAY AREAS, EASEMENT AREAS, EMBANKMENT SLOPES, ETC. WILL BE STABILIZED PER APPLICABLE PROJECT SPECIFICATIONS.
9. BEST MANAGEMENT PRACTICES MAY BE INSTALLED IN STAGES TO COINCIDE WITH THE DISTURBANCE OF UP-GRADE AREAS.
10. BEST MANAGEMENT PRACTICES MAY BE REMOVED IN STAGES ONCE THE WATERSHED FOR THAT PORTION CONTROLLED BY THE BEST MANAGEMENT PRACTICES HAS BEEN STABILIZED IN ACCORDANCE WITH TPDES REQUIREMENTS.
11. UPON COMPLETION OF THE PROJECT, INCLUDING SITE STABILIZATION, AND BEFORE FINAL PAYMENT IS ISSUED, CONTRACTOR SHALL REMOVE ALL SEDIMENT AND EROSION CONTROL MEASURES, PAYING SPECIAL ATTENTION TO ROCK BERMS IN DRAINAGE FEATURES.
12. STRIPPING OF VEGETATION FROM PROJECT SITES SHALL BE PHASED SO AS TO EXPOSE THE MINIMUM AMOUNT OF AREA TO SOIL EROSION FOR THE SHORTEST POSSIBLE PERIOD OF TIME PER THE NEW BRAUNFELS DRAINAGE AND EROSION CONTROL DESIGN MANUAL SEC. 12.2(N).



**KINGHAM DALTON WILSON, LTD**  
5858 WESTHEIMER, STE. 150  
HOUSTON, TX 77057

**TEXAS TITOS**  
1282 RIVER ROAD  
NEW BRAUNFELS, TX 78130

**WPAP SITE PLAN**

SHEET **2** OF **20**

NO	DATE	ISSUES AND REVISIONS
Δ	4/25/2022	UPDATED LABELING & DETAILS
Δ	6/30/2022	UPDATED PER CONB & TEO COMMENTS



2021 W SH46, STE 105  
NEW BRAUNFELS, TX. 78132  
PH: 830-358-7127 ink-civil.com  
TBPE FIRM F-13351

# Water Pollution Abatement Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b), Effective June 1, 1999

*To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.*

*Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.*


## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Water Pollution Abatement Plan Application Form** is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Print Name of Customer/Agent: James Ingalls, P.E.

Date: 10-20-23

Signature of Customer/Agent:



Regulated Entity Name: Texas Tito's

## Regulated Entity Information

1. The type of project is:

- Residential: Number of Lots: \_\_\_\_\_
- Residential: Number of Living Unit Equivalentents: \_\_\_\_\_
- Commercial
- Industrial
- Other: \_\_\_\_\_

2. Total site acreage (size of property): 5.13

3. Estimated projected population: 0

4. The amount and type of impervious cover expected after construction are shown below:

**Table 1 - Impervious Cover Table**

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	60,525	÷ 43,560 =	1.39
Parking	74,395	÷ 43,560 =	1.71
Other paved surfaces	18,847	÷ 43,560 =	0.43
Total Impervious Cover	153,767	÷ 43,560 =	3.53

**Total Impervious Cover 3.53 ÷ Total Acreage 5.13 X 100 = 68.8% Impervious Cover**

5.  **Attachment A - Factors Affecting Surface Water Quality.** A detailed description of all factors that could affect surface water and groundwater quality that addresses ultimate land use is attached.
6.  Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

***For Road Projects Only***

**Complete questions 7 - 12 if this application is exclusively for a road project.**

7. Type of project:

- TXDOT road project.
- County road or roads built to county specifications.
- City thoroughfare or roads to be dedicated to a municipality.
- Street or road providing access to private driveways.

8. Type of pavement or road surface to be used:

- Concrete
- Asphaltic concrete pavement
- Other: \_\_\_\_\_

9. Length of Right of Way (R.O.W.): \_\_\_\_\_ feet.

Width of R.O.W.: \_\_\_\_\_ feet.

L x W = \_\_\_\_\_ Ft<sup>2</sup> ÷ 43,560 Ft<sup>2</sup>/Acre = \_\_\_\_\_ acres.

10. Length of pavement area: \_\_\_\_\_ feet.

Width of pavement area: \_\_\_\_\_ feet.

L x W = \_\_\_\_\_ Ft<sup>2</sup> ÷ 43,560 Ft<sup>2</sup>/Acre = \_\_\_\_\_ acres.

Pavement area \_\_\_\_\_ acres ÷ R.O.W. area \_\_\_\_\_ acres x 100 = \_\_\_\_\_% impervious cover.

11.  A rest stop will be included in this project.
- A rest stop will not be included in this project.

12.  Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

### ***Stormwater to be generated by the Proposed Project***

13.  **Attachment B - Volume and Character of Stormwater.** A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on the area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

### ***Wastewater to be generated by the Proposed Project***

14. The character and volume of wastewater is shown below:

<u>100</u> % Domestic	<u>315</u> Gallons/day
<u>      </u> % Industrial	<u>      </u> Gallons/day
<u>      </u> % Commingled	<u>      </u> Gallons/day
TOTAL gallons/day <u>315</u>	

15. Wastewater will be disposed of by:

On-Site Sewage Facility (OSSF/Septic Tank):

**Attachment C - Suitability Letter from Authorized Agent.** An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

Sewage Collection System (Sewer Lines):

Private service laterals from the wastewater generating facilities will be connected to an existing SCS.

Private service laterals from the wastewater generating facilities will be connected to a proposed SCS.

The SCS was previously submitted on \_\_\_\_\_.

The SCS was submitted with this application.

The SCS will be submitted at a later date. The owner is aware that the SCS may not be installed prior to Executive Director approval.

The sewage collection system will convey the wastewater to the Gruene Water Reclaim Facility (name) Treatment Plant. The treatment facility is:

Existing.

Proposed.

16.  All private service laterals will be inspected as required in 30 TAC §213.5.

## **Site Plan Requirements**

**Items 17 – 28 must be included on the Site Plan.**

17.  The Site Plan must have a minimum scale of 1" = 400'.

Site Plan Scale: 1" = 50'.

18. 100-year floodplain boundaries:

Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.

No part of the project site is located within the 100-year floodplain.

The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FEMA Panel No. 48091C0455F eff. date 09/02/2009

19.  The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, open space, etc. are shown on the plan.

The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, open space, etc. are shown on the site plan.

20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):

There are 1 (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)

The wells are not in use and have been properly abandoned.

The wells are not in use and will be properly abandoned.

The wells are in use and comply with 16 TAC §76.

There are no wells or test holes of any kind known to exist on the project site.

21. Geologic or manmade features which are on the site:

All sensitive geologic or manmade features identified in the Geologic Assessment are shown and labeled.

No sensitive geologic or manmade features were identified in the Geologic Assessment.

**Attachment D - Exception to the Required Geologic Assessment.** A request and justification for an exception to a portion of the Geologic Assessment is attached.

- 22.  The drainage patterns and approximate slopes anticipated after major grading activities.
- 23.  Areas of soil disturbance and areas which will not be disturbed.
- 24.  Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
- 25.  Locations where soil stabilization practices are expected to occur.
- 26.  Surface waters (including wetlands).
  - N/A
- 27.  Locations where stormwater discharges to surface water or sensitive features are to occur.
  - There will be no discharges to surface water or sensitive features.
- 28.  Legal boundaries of the site are shown.

### ***Administrative Information***

- 29.  Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
- 30.  Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

**ATTACHMENT "A"**  
**Factors Affecting Water Quality**

The development will consist of a proposed building with an attached warehouse expansion, and a secondary building. These structures total approximately 60,525 sf, plus associated parking and miscellaneous infrastructure including brine storage tanks, and a covered canopy. To minimize pollution from the site, two sand filtration ponds will be implemented. Some pollution may occur due to automobile wastes and cleaning chemicals, which may have an effect on surface water by sediments leaving the site after a rainfall event.

**ATTACHMENT "B"**  
**Volume and Character of Stormwater**

The development of this site will result in increase in stormwater run-off. As a result of this increase, no downstream impact has been established within the receiving creek. Onsite stormwater will be conveyed to two proposed sand filtration ponds by means of parking lot/driveway grading. Drainage patterns for the site will remain relatively unchanged.

The volume of stormwater runoff from the site for the 100-year storm event totals 34,613 cubic feet. The quality of the water will be to TCEQ's standards as the required TSS removal will be met at the sand filtration ponds. The proposed post-development impervious cover fraction is 0.69 for the site.


**ATTACHMENT "C"**  
**Suitability Letter from Authorized Agent**

There is no proposed OSSF.

**ATTACHMENT "D"**  
**Exception to the Required Geologic Assessment**

No exception will be requested.

Project Control Points				
Point #	Row Description	Elevation	Northing	Easting
19	CP MAG	656.82	13813270.6850	2246277.3320
20	CP 60D	650.79	13813343.3960	2246518.4510
21	CP 60D	653.54	13813222.8800	2246576.2560
22	CP 60D	639.35	13813084.1575	2246497.0331
23	CP 60D	638.35	13812951.5990	2246472.8080
24	CP 60D	637.11	13812738.1060	2246425.5820



LEGEND	
	SILT FENCE
	LIMITS OF CONSTRUCTION
	EXISTING CONTOURS
	PROPOSED CONTOURS
	FLOW ARROWS
	STABILIZED CONSTRUCTION ENTRANCE/EXIT
	TRUCK WASH OUT PIT
	CONSTRUCTION STAGING AREA
	LIMITS OF CONSTRUCTION

### SILT FENCE

- Materials:
- Silt fence material should be polypropylene, polyethylene or polyamide woven or non-woven fabric. The fabric width should be 36 inches, with a minimum unit weight of 4.5 oz/yd, mullen burst strength exceeding 190 lb/in<sup>2</sup>, ultraviolet stability exceeding 70%, and minimum apparent opening size of U.S. Sieve No. 30.
  - Fence posts should be made of hot rolled steel, at least 4 feet long with Tee or Ybar cross section, surface painted or galvanized, minimum nominal weight 1.25 lb/ft<sup>2</sup>, and Brindell hardness exceeding 140.
  - Woven wire backing to support the fabric should be galvanized 2" x 4" welded wire, 12 gauge minimum.

### Installation:

- Steel posts, which support the silt fence, should be installed on a slight angle toward the anticipated runoff source. Post must be embedded a minimum of 1-foot deep and spaced not more than 8 feet on center. Where water concentrates, the maximum spacing should be 6 feet.
- Lay out fencing down-slope of disturbed area, following the contour as closely as possible. The fence should be sited so that the maximum drainage area is 1/4 acre/100 feet of fence.
- The toe of the silt fence should be trenched in with a spade or mechanical trencher, so that the down-slope face of the trench is flat and perpendicular to the line of flow. Where fence cannot be trenched in (e.g., pavement or rock outcrop), weight fabric flap with 3 inches of pea gravel on uphill side to prevent flow from seeping under fence.
- The trench must be a minimum of 6 inches deep and 6 inches wide to allow for the silt fence fabric to be laid in the ground and backfilled with compacted material.
- Silt fence should be securely fastened to each steel support post or to woven wire, which is in turn attached to the steel fence post. There should be a 3-foot overlap, securely fastened where ends of fabric meet.
- Silt fence should be removed when the site is completely stabilized so as not to block or impede storm flow or drainage.

### Inspection and Maintenance Guidelines:

- Inspect all fencing weekly, and after any rainfall.
- Remove sediment when buildup reaches 6 inches.
- Replace any torn fabric or install a second line of fencing parallel to the torn section.
- Replace or repair any sections crushed or collapsed in the course of construction activity. If a section of fence is obstructing vehicular access, consider relocating it to a spot where it will provide equal protection, but will not obstruct vehicles. A triangular filter dike may be preferable to a silt fence at common vehicle access points.
- When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.

### HYDRAULIC MULCH

MATERIALS:

HYDRAULIC MULCHES: WOOD FIBER MULCH CAN BE APPLIED ALONE OR AS A COMPONENT OF HYDRAULIC MATRICES. WOOD FIBER APPLIED ALONE IS TYPICALLY APPLIED AT THE RATE OF 2,000 TO 4,000 LB/ACRE. WOOD FIBER MULCH IS MANUFACTURED FROM WOOD OR WOOD WASTE FROM LUMBER MILLS OR FROM URBAN SOURCES.

HYDRAULIC MATRICES: HYDRAULIC MATRICES INCLUDE A MIXTURE OF WOOD FIBER AND ACRYLIC POLYMER OR OTHER TACKIFIER AS BINDER. APPLY AS A LIQUID SLURRY USING A HYDRAULIC APPLICATION MACHINE (I.E., HYDRO SEEDER) AT THE FOLLOWING MINIMUM RATES, OR AS SPECIFIED BY THE MANUFACTURER TO ACHIEVE COMPLETE COVERAGE OF THE TARGET AREA: 2,000 TO 4,000 LB/ACRE WOOD FIBER MULCH, AND 5 TO 10% (BY WEIGHT) OF TACKIFIER (ACRYLIC COPOLYMER, GUAR, PSYLLIUM, ETC.)



BONDED FIBER MATRIX: BONDED FIBER MATRIX (BFM) IS A HYDRAULICALLY APPLIED SYSTEM OF FIBERS AND ADHESIVES THAT UPON DRYING FORMS AN EROSION RESISTANT BLANKET THAT PROMOTES VEGETATION, AND PREVENTS SOIL EROSION. BFMS ARE TYPICALLY APPLIED AT RATES FROM 3,000 LB/ACRE TO 4,000 LB/ACRE BASED ON THE MANUFACTURER'S RECOMMENDATION. A BIODEGRADABLE BFM IS COMPOSED OF MATERIALS THAT ARE 100% BIODEGRADABLE. THE BINDER IN THE BFM SHOULD ALSO BE BIODEGRADABLE AND SHOULD NOT DISSOLVE OR DISPERSE UPON RE-WETTING. TYPICALLY, BIODEGRADABLE BFMS SHOULD NOT BE APPLIED IMMEDIATELY BEFORE, DURING OR IMMEDIATELY AFTER RAINFALL IF THE SOIL IS SATURATED. DEPENDING ON THE PRODUCT, BFMS TYPICALLY REQUIRE 12 TO 24 HOURS TO DRY AND BECOME EFFECTIVE.

### INSTALLATION:



- PRIOR TO APPLICATION, ROUGH EMBANKMENT AND FILL AREAS BY ROLLING WITH A CRIMPING OR PUNCHING TYPE ROLLER OR BY TRACK WALKING. TRACK WALKING SHALL ONLY BE USED WHERE OTHER METHODS ARE IMPRACTICAL.
- TO BE EFFECTIVE, HYDRAULIC MATRICES REQUIRE 24 HOURS TO DRY BEFORE RAINFALL OCCURS.
- AVOID MULCH OVER SPRAY ON ROADS, SIDEWALKS, DRAINAGE CHANNELS, EXISTING VEGETATION, ETC.
- 4" OF TOP SOIL SHALL BE PLACED.

### INSPECTION AND MAINTENANCE GUIDELINES:


- MULCHED AREAS SHOULD BE INSPECTED WEEKLY AND AFTER EACH RAIN EVENT TO LOCATE AND REPAIR ANY DAMAGE.
- AREAS DAMAGED BY STORMS OR NORMAL CONSTRUCTION ACTIVITIES SHOULD BE REGRADED AND HYDRAULIC MULCH REAPPLIED AS SOON AS PRACTICAL.



TYPICAL CONCRETE TRUCK WASHOUT PIT



STABILIZED CONSTRUCTION ENTRANCE / EXIT



TYPICAL CONSTRUCTION STAGING AREA

**SOIL STABILIZATION NOTE**

PER TPDES REQUIREMENTS, DISTURBED AREAS ON WHICH CONSTRUCTION ACTIVITIES HAVE CEASED (TEMPORARILY OR PERMANENTLY) SHALL BE STABILIZED WITHIN 14 DAYS UNLESS ACTIVITY RESUMES WITHIN 21 DAYS. SEEDING DOES NOT CONSTITUTE AS STABILIZATION.

SUBSTANTIAL GRADING IS PROPOSED WITH THIS UNIT. PER THE NEW BRAUNFELS DRAINAGE AND EROSION CONTROL DESIGN MANUAL SEC. 13.2(N), STRIPPING OF VEGETATION FROM PROJECT SITES SHALL BE PHASED SO AS TO EXPOSE THE MINIMUM AMOUNT OF AREA TO SOIL EROSION FOR THE SHORTEST POSSIBLE TIME.

### EROSION CONTROL NOTES:

- LIMITS OF CONSTRUCTION AND OTHER EROSION CONTROL IMPROVEMENTS SHOWN OUTSIDE THE PROPERTY ARE SHOWN FOR GRAPHICAL PURPOSE ONLY. IF NEAR PROPERTY LINE, THE INTENT IS TO BE PLACED NEAR THE PROPERTY LINE, NOT ON THE ADJACENT PROPERTY.
- DO NOT DISTURB VEGETATED AREAS (TREES, GRASS, WEEDS, BRUSH, ETC.) ANY MORE THAN NECESSARY FOR CONSTRUCTION.
- CONSTRUCTION ENTRANCE/EXIT LOCATION, CONCRETE WASH-OUT PIT, AND CONSTRUCTION EQUIPMENT AND MATERIAL STORAGE YARD TO BE DETERMINED IN THE FIELD.
- STORM WATER POLLUTION PREVENTION CONTROLS MAY NEED TO BE MODIFIED IN THE FIELD TO ACCOMPLISH THE DESIRED EFFECT. ALL MODIFICATIONS ARE TO BE NOTED IN THE SWPPP DOCUMENTS AND SIGNED AND DATED BY THE RESPONSIBLE PARTY.
- RESTRICT ENTRY/EXIT TO THE PROJECT SITE TO DESIGNATED LOCATIONS BY USE OF ADEQUATE FENCING, IF NECESSARY.
- ALL STORM WATER POLLUTION PREVENTION CONTROLS ARE TO BE MAINTAINED AND IN WORKING CONDITIONS AT ALL TIMES.
- STORM WATER POLLUTION PREVENTION STRUCTURES SHOULD BE CONSTRUCTED WITHIN THE SITE BOUNDARIES. SOME OF THESE FEATURES MAY BE SHOWN OUTSIDE THE SITE BOUNDARIES ON THIS PLAN FOR VISUAL CLARITY.
- AS SOON AS PRACTICAL, ALL DISTURBED SOIL THAT WILL NOT BE COVERED BY IMPERVIOUS COVER SUCH AS PARKWAY AREAS, EASEMENT AREAS, EMBANKMENT SLOPES, ETC. WILL BE STABILIZED PER APPLICABLE PROJECT SPECIFICATIONS.
- BEST MANAGEMENT PRACTICES MAY BE INSTALLED IN STAGES TO COINCIDE WITH THE DISTURBANCE OF UP-GRADE AREAS.
- BEST MANAGEMENT PRACTICES MAY BE REMOVED IN STAGES ONCE THE WATERSHED FOR THAT PORTION CONTROLLED BY THE BEST MANAGEMENT PRACTICES HAS BEEN STABILIZED IN ACCORDANCE WITH TPDES REQUIREMENTS.
- UPON COMPLETION OF THE PROJECT, INCLUDING SITE STABILIZATION, AND BEFORE FINAL PAYMENT IS ISSUED, CONTRACTOR SHALL REMOVE ALL SEDIMENT AND EROSION CONTROL MEASURES, PAYING SPECIAL ATTENTION TO ROCK BERMS IN DRAINAGE FEATURES.
- STRIPPING OF VEGETATION FROM PROJECT SITES SHALL BE PHASED SO AS TO EXPOSE THE MINIMUM AMOUNT OF AREA TO SOIL EROSION FOR THE SHORTEST POSSIBLE PERIOD OF TIME PER THE NEW BRAUNFELS DRAINAGE AND EROSION CONTROL DESIGN MANUAL SEC. 12.2(N).

**KINGHAM DALTON WILSON, LTD**  
5858 WESTHEIMER, STE. 150  
HOUSTON, TX 77057

**TEXAS TITOS**  
1282 RIVER ROAD  
NEW BRAUNFELS, TX 78130

**WPAP SITE PLAN**

SHEET **2** OF **20**

NO	DATE	ISSUES AND REVISIONS
1	4/25/2022	UPDATED LABELING & DETAILS
2	6/30/2022	UPDATED PER CONB & TCO COMMENTS
3	6/20/2023	REVISED GRADING NEAR FLOODWAY



2021 W SH46, STE 105  
NEW BRAUNFELS, TX. 78132  
PH: 830-358-7127 ink-civil.com  
TBPE FIRM F-13351

# Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

*To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.*

*Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.*


## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: James Ingalls, P.E.

Date: 10-20-23

Signature of Customer/Agent:



---

Regulated Entity Name: Texas Tito's

## Project Information

### Potential Sources of Contamination

*Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.*

1. Fuels for construction equipment and hazardous substances which will be used during construction:

The following fuels and/or hazardous substances will be stored on the site: \_\_\_\_\_

These fuels and/or hazardous substances will be stored in:

- Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
- Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- Fuels and hazardous substances will not be stored on the site.
- 2.  **Attachment A - Spill Response Actions.** A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3.  Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4.  **Attachment B - Potential Sources of Contamination.** A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

### ***Sequence of Construction***

- 5.  **Attachment C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
  - For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
  - For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6.  Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Blieders Creek

### ***Temporary Best Management Practices (TBMPs)***

*Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.*

- 7.  **Attachment D – Temporary Best Management Practices and Measures.** TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

- A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
  - A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
  - A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
  - A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8.  The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- Attachment E - Request to Temporarily Seal a Feature.** A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
  - There will be no temporary sealing of naturally-occurring sensitive features on the site.
9.  **Attachment F - Structural Practices.** A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10.  **Attachment G - Drainage Area Map.** A drainage area map supporting the following requirements is attached:
- For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
  - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
  - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
  - There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

- There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11.  **Attachment H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
- N/A
12.  **Attachment I - Inspection and Maintenance for BMPs.** A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13.  All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14.  If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15.  Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16.  Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

### ***Soil Stabilization Practices***

*Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.*

17.  **Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices.** A schedule of the interim and permanent soil stabilization practices for the site is attached.

18.  Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19.  Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

### ***Administrative Information***

20.  All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21.  If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22.  Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

**ATTACHMENT "A"**  
**Spill Response Actions**

Spill Prevention and Control

The objective of this section is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees.

The following steps will help reduce the stormwater impacts of leaks and spills:

***Education***

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a "significant spill" is for each material they use, and what is the appropriate response for "significant" and "insignificant" spills. Employees should also be aware of when spills must be reported to the TCEQ. Information available in 30 TAC 327.4 and 40 CFR 302.4.
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor's superintendent or representative oversee and enforce proper spill prevention and control measures.

***General Measures***

- (1) To the extent that the work can be accomplished safely, spills of oil, petroleum products, and substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.

(6) Spills should be covered and protected from stormwater runoff during rainfall to the extent that it doesn't compromise clean up activities.

(7) Do not bury or wash spills with water.

(8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMP's.

(9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.

(10) Contain water overflow or minor water spillage, and do not allow it to discharge into drainage facilities or watercourses.

(11) Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.

(12) Keep waste storage areas clean, well organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

### ***Cleanup***

(1) Clean up leaks and spills immediately.

(2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.

(3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMP's in this section for specific information.

### ***Minor Spills***

(1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.

(2) Use absorbent materials on small spills rather than hosing down or burying the spill.

(3) Absorbent materials should be promptly removed and disposed of properly.

- (4) Follow the practice below for a minor spill:
- (5) Contain the spread of the spill.
- (6) Recover spilled materials.
- (7) Clean the contaminated area and properly dispose of contaminated materials.

### ***Semi-Significant Spills***

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman immediately.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

### ***Significant/Hazardous Spills***

For significant or hazardous spills that are in reportable quantities:

- (1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
- (2) For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110,119, and 302, the contractor should notify the National Response Center at (800) 424-8802.
- (3) Notification should first be made by telephone and followed up with a written report.

(4) The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.

(5) Other agencies which may need to be consulted include, but are not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc.

More information on spill rules and appropriate responses is available on the TCEQ website at: [http://www.tnrcc.state.tx.us/enforcement/emergency\\_response.html](http://www.tnrcc.state.tx.us/enforcement/emergency_response.html)

### ***Vehicle and Equipment Maintenance***

(1) If maintenance must occur onsite, use a designated area and a secondary containment, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.

(2) Regularly inspect onsite vehicles and equipment for leaks and repair immediately

(3) Check incoming vehicles and equipment (including delivery trucks, and employee and subcontractor vehicles) for leaking oil and fluids. Do not allow leaking vehicles or equipment onsite.

(4) Always use secondary containment, such as a drain pan or drop cloth, to catch spills or leaks when removing or changing fluids.

(5) Place drip pans or absorbent materials under paving equipment when not in use.

(6) Use absorbent materials on small spills rather than hosing down or burying the spill. Remove the absorbent materials promptly and dispose of properly.

(7) Promptly transfer used fluids to the proper waste or recycling drums. Don't leave full drip pans or other open containers lying around.

(8) Oil filters disposed of in trashcans or dumpsters can leak oil and pollute stormwater. Place the oil filter in a funnel over a waste oil-recycling drum to drain excess oil before disposal. Oil filters can also be recycled. Ask the oil supplier or recycler about recycling oil filters.

(9) Store cracked batteries in a non-leaking secondary container. Do this with all cracked batteries even if you think all the acid has drained out. If you drop a battery, treat it as if it is cracked. Put it into the containment area until you are sure it is not leaking.

### ***Vehicle and Equipment Fueling***

(1) If fueling must occur on site, use designated areas, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.

(2) Discourage "topping off" of fuel tanks.

(3) Always use secondary containment, such as a drain pan, when fueling to catch spills/ leaks.

**ATTACHMENT "B"**  
**Potential Sources of Contamination**

The only potential sources of contamination are construction equipment leaks, re-fueling spills, port-o-lets, and the total suspended solids (TSS) due to the construction activities on-site. There are no other anticipated potential sources of contamination.

**ATTACHMENT "C"**  
**Sequence of Major Activities**

Stages of Construction:

1. Installation of temporary BMP's.
2. Minor site grading: This includes the removal of organic material and other debris within the proposed parking and building site. Approximate total disturbed area = 5.2 acres.
3. Grading: Cutting and filling of the proposed site to prepare the site for parking and foundation construction. Approximate total disturbed area = 5.2 acres.
4. Utility installation: All primary utility mains have already been installed and are available at the site. Sewer, water, gas, and electrical services will be installed at this time.
5. Finished grading: Final landscaping, Parking and building infrastructure are installed. Approximate total disturbed area = 3.53 acres.

**ATTACHMENT "D"**  
**Temporary BMP's and Measures**

The following sequence will be followed for installing temporary BMP's:

1. Silt fence will be constructed on the downgradient side of proposed site.
2. A stabilized construction exit will be installed prior to any site work.

A. Silt Fence will be installed on the most downgradient side of the site and will reduce potential pollution from any stormwater that originates onsite or offsite. A stabilized construction exit will be constructed at the entrance of the site; this will reduce the amount of contaminants leaving the site.

B. Silt fence will be placed on the downgradient side of each proposed improvement to contain pollutants generated from onsite runoff. Disturbed areas will be seeded to replace destroyed vegetation. The existing vegetation located downgradient of each proposed improvement will work in conjunction with the silt fence and stabilized construction entrance to prevent pollution of water originating onsite and/or flowing offsite.

C. The proposed silt fences, and stabilized construction entrance constructed upgradient of the existing streams will prevent pollutants from entering them, as well as the aquifer. According to the Geologic Assessment, there are no sensitive features with the project boundary.

D. There were no sensitive features identified in the Geologic Assessment.

**ATTACHMENT “E”**  
**Request to Temporarily Seal a Feature**

There will be no request to temporarily seal a feature.

**ATTACHMENT “F”**  
**Structural Practices**

Stabilized Construction Entrance/Exit, rock gabions, and silt fence will be used to protect disturbed soils and to prevent contamination from leaving the project site.

**ATTACHMENT “G”**  
**Drainage Area Map**

See Drainage Area Map at the end of this section.

**ATTACHMENT “H”**  
**Temporary Sediment Pond Plans and Calculations**

There will not be more than 10 acres of disturbed soil in one common drainage area that will occur at one time. Silt fence will be used for small drainage areas. No sediment ponds will be constructed due to the minimal amount of soil disturbance.

**ATTACHMENT “I”**  
**Inspection and Maintenance for BMP's**

Inspection and Maintenance Plan

The contractor is required to inspect the control and fences at weekly intervals and after any rainfall events to ensure that they are functioning properly. The contractor is required to document any changes on the Site Plan, documentation must include person performing task, task performed, and date. The contractor must also document if proper inspection measures have been taken while making changes. The person(s) responsible for maintenance controls and fences shall immediately make any necessary repairs to damaged areas.

Temporary Construction Entrance/Exit: The entrance should be maintained in a condition, which will prevent tracking or flowing of sediment onto public rights-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment. All sediment spilled, dropped, washed or tracked onto public rights-of-way should be removed immediately by contractor. When necessary, wheels should be cleaned to remove sediment prior to entrance onto public right-of-way. When washing is required, it should be done on an area stabilized with crushed stone that drains into an

approved sediment trap or sediment basin. All sediment should be prevented from entering any storm drain, ditch or water course by using approved methods.

Silt Fence: Remove sediment when buildup reaches 6 inches. Replace any torn fabric or install a second line of fencing parallel to the torn section. Replace or repair any sections crushed or collapsed in the course of construction activity. If a section of fence is obstructing vehicular access, consider relocating it to a spot where it will provide equal protection, but will not obstruct vehicles. A triangular filter dike may be preferable to a silt fence at common vehicle access points. When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.

TCEQ staff will be allowed full access to the property during construction of the project for inspecting controls and fences and to verify that the accepted plan is being utilized in the field. TCEQ staff has the right to speak with the contractor to verify plan changes and modifications.

Documentation: All scheduled inspection and maintenance measures made to the temporary BMPs must be documented clearly on the WPAP Site Plan showing inspection/maintenance measures performed, date, and person responsible for inspection and maintenance. Any changes made to the location or type of controls shown on the accepted plans, due to onsite conditions, shall be documented on the site plan that is part of this Water Pollution Abatement Plan. No other changes shall be made unless approved by TCEQ and the Design Engineer. Documentation shall clearly show changes made, date, person responsible for the change, and the reason for the change.

**Owner's Information:**

Owner: BLIEDERS CREEK, LLC  
Contact: Chris Snider  
Address: 422 Saddle Tree Dr  
New Braunfels, Texas 78130

**Design Engineer:**

Company: INK Civil  
Contact: Shane Klar, P.E.  
Phone: (830) 358-7127  
Address: 2021 SH 46W, Ste. 105  
New Braunfels, Texas 78132

**Person or Firm Responsible for Erosion/Sedimentation Control Maintenance:**

Company: \_\_\_\_\_

Contact: \_\_\_\_\_

Phone: \_\_\_\_\_

Address: \_\_\_\_\_

Signature of Responsible Party: \_\_\_\_\_

**This portion of the form shall be filled out and signed by the responsible party prior to construction.**

**ATTACHMENT “J”**  
**Schedule of Interim and Permanent Soil Stabilization Practices**

Areas which are disturbed by construction staging and storage areas will be hydro mulched with the appropriate seed mixture. Areas between the edge of pavement and property line will also be hydro mulched. There will be no fill slopes exceeding a 3:1 slope, and all fill slopes will be hydro mulched. Installation and acceptable mixtures of hydro mulch are as follows:

**Materials:**

Hydraulic Mulches: Wood fiber mulch can be applied alone or as a component of hydraulic matrices. Wood fiber applied alone is typically applied at the rate of 2,000 to 4,000 lb/acre. Wood fiber mulch is manufactured from wood or wood waste from lumber mills or from urban sources.

Hydraulic Matrices: Hydraulic matrices include a mixture of wood fiber and acrylic polymer or other tackifier as binder. Apply as a liquid slurry using a hydraulic application machine (i.e., hydro seeder) at the following minimum rates, or as specified by the manufacturer to achieve complete coverage of the target area: 2,000 to 4,000 lb/acre wood fiber mulch, and 5 to 10% (by weight) of tackifier (acrylic copolymer, guar, psyllium, etc.)

Bonded Fiber Matrix: Bonded fiber matrix (BFM) is a hydraulically applied system of fibers and adhesives that upon drying forms an erosion resistant blanket that promotes vegetation, and prevents soil erosion. BFMs are typically applied at rates from 3,000 lb/acre to 4,000 lb/acre based on the manufacturer's recommendation. A biodegradable BFM is composed of materials that are 100% biodegradable. The binder in the BFM should also be biodegradable and should not dissolve or disperse upon re-wetting. Typically, biodegradable BFMs should not be applied immediately before, during or immediately after rainfall if the soil is saturated. Depending on the product, BFMs typically require 12 to 24 hours to dry and become effective.

Seed Mixtures:

<b>Dates</b>	<b>Climate</b>	<b>Species</b>	<b>(lb/ac.)</b>
Sept. 1 to Nov. 30	Temporary Cool Season	Tall Fescue	4.0
		Oats	21.0
		Wheats	30.0
		<b>Total</b>	<b>55.0</b>
Sept. 1 to Nov. 30	Cool Season Legume	Hairy Vetch	8.0
May 1 to Aug. 31	Temporary Warm Season	Foxtail Millet	30.0



Fertilizer: Fertilizer should be applied at the rate of 40 pounds of nitrogen and 40 pounds of phosphorus per acre, which is equivalent to about 1.0 pounds of nitrogen and phosphorus per 1000 square feet.

**Installation:**

- (1) Prior to application, roughen embankment and fill areas by rolling with a crimping or punching type roller or by track walking. Track walking shall only be used where other methods are impractical.
- (2) To be effective, hydraulic matrices require 24 hours to dry before rainfall occurs.
- (3) Avoid mulch over spray onto roads, sidewalks, drainage channels, existing vegetation, etc.

**Texas Tito's - Proposed Conditions Rational Hydrology Calculations**

Point	AREA ID	Area (ac)	C <sub>2</sub>	C <sub>5</sub>	C <sub>10</sub>	C <sub>25</sub>	C <sub>50</sub>	C <sub>100</sub>	T <sub>c</sub> (min)	I <sub>2</sub> (in/hr)	I <sub>5</sub> (in/hr)	I <sub>10</sub> (in/hr)	I <sub>25</sub> (in/hr)	I <sub>50</sub> (in/hr)	I <sub>100</sub> (in/hr)	Q <sub>2</sub> (cfs)	Q <sub>5</sub> (cfs)	Q <sub>10</sub> (cfs)	Q <sub>25</sub> (cfs)	Q <sub>50</sub> (cfs)	Q <sub>100</sub> (cfs)	Location
A1	A1	0.90	0.63	0.67	0.71	0.76	0.79	0.84	10	5.05	6.36	7.50	9.12	10.38	11.70	2.87	3.84	4.78	6.20	7.41	8.86	Storm Drain Line A1
A2	A2	4.30	0.64	0.68	0.72	0.77	0.80	0.85	10	5.05	6.36	7.50	9.12	10.38	11.70	13.94	18.60	23.16	30.04	35.89	42.86	Water Quality Basin 1
A3	A3	1.20	0.59	0.63	0.66	0.71	0.75	0.79	12	4.70	5.92	6.97	8.45	9.61	10.83	3.33	4.46	5.56	7.21	8.63	10.33	Water Quality Basin 2




**LEGEND**

- LIMITS OF DRAINAGE AREA
- TC
- EXISTING CONTOURS
- PROPOSED CONTOURS
- FLOW ARROWS
- A  
9.0 DRAINAGE BASIN LABEL
- A1  
2.0 SUB-DRAINAGE AREA LABEL
- A1 INLET LABEL
- A1 ANALYSIS POINT LABEL

NOTE: THIS MAP IS FOR INTERNAL SIZING ONLY USING THE RATIONAL METHOD. THIS PROJECT IS PROPOSING A FEE-IN-LIEU OF DETENTION. PLEASE SEE THE DRAINAGE REPORT FOR CALCULATIONS SHOWING NO DOWNSTREAM IMPACT. THE SAME COMPARISON TABLE INCLUDED IN THAT ANALYSIS HAS BEEN ADDED BELOW FOR REFERENCE TO SHOW NO IMPACT 3,000-FT DOWNSTREAM.

**Texas Tito's Downstream Flow Comparison Summary (See Drainage Report)**

Location	Existing 100-yr Q (cfs)	Proposed 100-yr Q (cfs)
3,000-ft downstream - Blieders Creek	30669.25	30668.95
Low downstream - Blieders Creek	86.02	104.65



**KINGHAM DALTON WILSON, LTD**  
5858 WESTHEIMER, STE. 150  
HOUSTON, TX 77057

**TEXAS TITOS**  
1282 RIVER ROAD  
NEW BRAUNFELS, TX 78130

**DRAINAGE AREA MAP - PROPOSED**

SHEET **10** OF **20**

NO	DATE	ISSUES AND REVISIONS
1	6/30/2022	UPDATED PER CONB & TGEQ COMMENTS
2	8/31/2022	UPDATED PER CONB & NBQ COMMENTS
3	6/20/2023	REVISED GRADING NEAR FLOODWAY



2021 W SH46, STE 105  
NEW BRAUNFELS, TX. 78132  
PH: 830-358-7127 ink-civil.com  
TBPE FIRM F-13351

# Permanent Stormwater Section

## Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(C), (D)(li), (E), and (5), Effective June 1, 1999

*To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.*

*Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.*


## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Permanent Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: James Ingalls, P.E.

Date: 10-20-23

Signature of Customer/Agent



A handwritten signature in blue ink, appearing to read "James Ingalls", is written over a horizontal line. The signature is stylized and cursive.

Regulated Entity Name: Texas Tito's

## Permanent Best Management Practices (BMPs)

*Permanent best management practices and measures that will be used during and after construction is completed.*

- Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.  
 N/A
- These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.  
 The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.

A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: \_\_\_\_\_

N/A

3.  Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.

N/A

4. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

The site will be used for low density single-family residential development and has 20% or less impervious cover.

The site will be used for low density single-family residential development but has more than 20% impervious cover.

The site will not be used for low density single-family residential development.

5. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

**Attachment A - 20% or Less Impervious Cover Waiver.** The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.

The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.

The site will not be used for multi-family residential developments, schools, or small business sites.

6.  **Attachment B - BMPs for Upgradient Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
  - No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
  - Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
7.  **Attachment C - BMPs for On-site Stormwater.**
- A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
  - Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
8.  **Attachment D - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is attached. Each feature identified in the Geologic Assessment as sensitive has been addressed.
- N/A
9.  The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.
- The permanent sealing of or diversion of flow from a naturally-occurring sensitive feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed.
  - Attachment E - Request to Seal Features.** A request to seal a naturally-occurring sensitive feature, that includes, for each feature, a justification as to why no reasonable and practicable alternative exists, is attached.
10.  **Attachment F - Construction Plans.** All construction plans and design calculations for the proposed permanent BMP(s) and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. The plans are attached and, if applicable include:
- Design calculations (TSS removal calculations)
  - TCEQ construction notes
  - All geologic features
  - All proposed structural BMP(s) plans and specifications
- N/A

11.  **Attachment G - Inspection, Maintenance, Repair and Retrofit Plan.** A plan for the inspection, maintenance, repairs, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan includes all of the following:
- Prepared and certified by the engineer designing the permanent BMPs and measures
  - Signed by the owner or responsible party
  - Procedures for documenting inspections, maintenance, repairs, and, if necessary retrofit
  - A discussion of record keeping procedures
- N/A
12.  **Attachment H - Pilot-Scale Field Testing Plan.** Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
- N/A
13.  **Attachment I -Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that results in water quality degradation.
- N/A

### ***Responsibility for Maintenance of Permanent BMP(s)***

***Responsibility for maintenance of best management practices and measures after construction is complete.***

14.  The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
- N/A
15.  A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.
- N/A

**ATTACHMENT "A"**  
**20% or Less Impervious Cover Waiver**

The proposed development mixed use commercial and the 20% Impervious Cover Waiver does not apply. Permanent BMP's will be designed in accordance with TCEQ requirements for the removal of TSS generated by the proposed development.

**ATTACHMENT "B"**  
**BMP's for Upgradient Stormwater**

The off-site stormwater that comes across the site will be routed to Water Quality Basin 1. The offsite area's impervious cover is associated with increased runoff which was taken into account when sizing the basin.

**ATTACHMENT "C"**  
**BMP's for On-Site Stormwater**

The permanent BMP used to treat on-site stormwater runoff will be sand filtration ponds. Please refer to the Drainage Area Map in the Temporary Stormwater Section for areas of treatment and BMP structure used.

**ATTACHMENT "D"**  
**BMP's for Surface Streams**

The Sand Filtration Ponds will be used to filter out contaminants before it leaves the property and reaches any surface water or the aquifer. There were no sensitive features identified by the Geological assessment.

## **ATTACHMENT "G"**

### **Inspection, Maintenance, Repair, and Retrofit Plan**

#### **Sand Filter Systems Maintenance and Monitoring Procedures**

- *Inspections.* BMP facilities must be inspected at least twice a year (once during or immediately following wet weather) to evaluate facility operation. During each inspection, erosion areas inside and downstream of the BMP must be identified and repaired or revegetated immediately. With each inspection, any damage to the structural elements of the system (pipes, concrete drainage structures, retaining walls, etc.) must be identified and repaired immediately. Cracks, voids and undermining should be patched/filled to prevent additional structural damage. Trees and root systems should be removed to prevent growth in cracks and joints that can cause structural damage.
- *Sediment Removal.* Remove sediment from the inlet structure and sedimentation chamber when sediment buildup reaches a depth of 6 inches or when the proper functioning of inlet and outlet structures is impaired. Sediment should be cleared from the inlet structure at least every year and from the sedimentation basin at least every 5 years.
- *Media Replacement.* Maintenance of the filter media is necessary when the drawdown time exceeds 48 hours. When this occurs, the upper layer of sand should be removed and replaced with new material meeting the original specifications. Any discolored sand should also be removed and replaced. In filters that have been regularly maintained, this should be limited to the top 2 to 3 inches.
- *Debris and Litter Removal.* Debris and litter will accumulate near the sedimentation basin outlet device and should be removed during regular mowing operations and inspections. Particular attention should be paid to floating debris that can eventually clog the control device or riser.
- *Filter Underdrain.* Clean underdrain piping network to remove any sediment buildup as needed to maintain design drawdown time.
- *Mowing.* Grass areas in and around sand filters must be mowed at least twice annually to limit vegetation height to 18 inches. More frequent mowing to maintain aesthetic appeal may be necessary in landscaped areas. Vegetation on the pond embankments should be mowed as appropriate to prevent the establishment of woody vegetation.

**Attachment "G"**

**Maintenance Plan for Sand Filtration Pond**

Sand Filtration Pond: The Sand Filtration Ponds will be located on the Northeast and Southeast corners of the site adjacent to the proposed parking lot.

Owner: BLIEDERS CREEK, LLC  
422 Saddle Tree Dr  
New Braunfels, Texas 78130

Sand Filtration Pond Maintenance and Monitoring Procedures will be implemented to ensure that the proposed BMP functions as designed.



Chris Snider  
BLIEDERS CREEK, LLC

3/18/2022

Date

I have reviewed the attached maintenance and monitoring procedures and to the best of my knowledge certify that, if they are followed as outlined, the storm filter will function as designed.




Shane Klar, P.E.

**ATTACHMENT "I"**


**Measures for Minimizing Surface Stream Contamination**

All surface streams will be protected from erosion by not allowing runoff to exceed existing velocities. The storm water runoff for the property will be directed into the Sand Filtration Ponds where the pollutants will be removed.



**GABION BASKET DETAIL**  
SCALE: NTS


- STONE**  
STONE FILL MATERIAL SHALL CONSIST OF HARD, DURABLE, CLEAN STONE OF THE SIZE INDICATED, 6 TO 9 INCHES IN SIZE OR AS APPROVED BY THE ENGINEER AND RESISTANT TO THE ACTION OF AIR AND WATER AND SUITABLE IN ALL RESPECTS FOR THE PURPOSE INTENDED.
- WIRE CONTAINERS**  
WIRE MESH SHALL CONSIST OF PLASTIC COATED (P.V.C.) GALVANIZED WIRE 0.120 INCH IN DIAMETER MINIMUM AND SHALL EQUAL OR EXCEED FEDERAL SPECIFICATION QQ-W-481G, CLASS 3 UNLESS OTHERWISE INDICATED. OPENING OF THE MESH SHALL NOT EXCEED APPROXIMATELY 4 INCHES IN THE LONGEST DIMENSION. THE WIRE MESH IS TO BE FABRICATED IN SUCH MANNER AS TO BE NONRIVETING, TIE AND CONNECTING WIRE SHALL BE OF THE SAME TYPE AND SIZE AS THE BASKETS AND SHALL BE SUPPLIED IN SUFFICIENT QUANTITY FOR SECURELY FASTENING ALL EDGES OF THE GABION AND DIAPHRAGMS.
- FILTER FABRIC**  
FILTER FABRIC SHALL BE NON-BIODEGRADABLE ULTRAVIOLET STABILIZED, INERT TO MOST SOIL CHEMICALS, UNAFFECTED BY MOISTURE WHICH ALLOWS WATER TO PASS THROUGH WHILE RETAINING SOIL PARTICLES AND SHALL CONFORM TO ITEM NO. 820, "FILTER FABRIC".



**LEGEND**


- SF SILT FENCE
- LOC LIMITS OF CONSTRUCTION
- 900 EXISTING CONTOURS
- 900 PROPOSED CONTOURS
- FLOW ARROWS
- STABILIZED CONSTRUCTION ENTRANCE/EXIT
- TRUCK WASH OUT PIT
- CONSTRUCTION STAGING AREA
- ROCK BERM
- GRAVEL FILTER BAGS
- LOC LIMITS OF CONSTRUCTION

- DRAINAGE INFRASTRUCTURE MAINTENANCE AND MONITORING GUIDELINES**
- ACCESS - DRIVE OVER TOP OF CURB FOR MOWING AND MAINTENANCE OF SAND POND. A RAMP WILL BE PROVIDED AS SHOWN.
  - INSPECTIONS, BMP FACILITIES MUST BE INSPECTED AT LEAST TWICE A YEAR (ONCE DURING OR IMMEDIATELY FOLLOWING WET WEATHER) TO EVALUATE FACILITY OPERATION. DURING EACH INSPECTION, EROSION AREAS INSIDE AND DOWNSTREAM OF THE BMP MUST BE IDENTIFIED AND REPAIRED OR REVEGETATED IMMEDIATELY. WITH EACH INSPECTION, FLOW OF WATER THROUGH THE STRUCTURAL ELEMENTS OF THE SYSTEM (PIPES, CONCRETE DRAINAGE STRUCTURES, RETAINING WALLS, ETC.) MUST BE IDENTIFIED AND REPAIRED IMMEDIATELY. CRACKS, VOIDS AND UNDERMINING SHOULD BE PATCHED/FILLED TO PREVENT ADDITIONAL STRUCTURAL DAMAGE. TREES AND ROOT SYSTEMS SHOULD BE REMOVED TO PREVENT GROWTH IN CRACKS AND JOINTS THAT CAN CAUSE STRUCTURAL DAMAGE.
  - SEDIMENT REMOVAL, REMOVE SEDIMENT FROM THE INLET STRUCTURE AND SEDIMENTATION CHAMBER WHEN SEDIMENT BUILDUP REACHES A DEPTH OF 6 INCHES OR WHEN THE PROPER FUNCTIONING OF INLET AND OUTLET STRUCTURES IS IMPAIRED. SEDIMENT SHOULD BE CLEARED FROM THE INLET STRUCTURE AT LEAST EVERY YEAR AND FROM THE SEDIMENTATION BASIN AT LEAST EVERY 5 YEARS.
  - MEDIA REPLACEMENT, MAINTENANCE OF THE FILTER MEDIA IS NECESSARY WHEN THE DRAINDOWN TIME EXCEEDS 48 HOURS. WHEN THIS OCCURS, THE UPPER LAYER OF SAND SHOULD BE REMOVED AND REPLACED WITH NEW MATERIAL MEETING THE ORIGINAL SPECIFICATIONS. ANY DISCOLORED SAND SHOULD ALSO BE REMOVED AND REPLACED. IN FILTERS THAT HAVE BEEN REGULARLY MAINTAINED, THIS SHOULD BE LIMITED TO THE TOP 2 TO 3 INCHES.
  - DEBRIS AND LITTER REMOVAL, DEBRIS AND LITTER WILL ACCUMULATE NEAR THE SEDIMENTATION BASIN, OUTLET DEVICE AND SHOULD BE REMOVED DURING REGULAR MOWING OPERATIONS AND INSPECTIONS. PARTICULAR ATTENTION SHOULD BE PAID TO FLOATING DEBRIS THAT CAN EVENTUALLY CLOG THE CONTROL DEVICE OR RISER.
  - FILTER UNDERDRAIN, CLEAN UNDERDRAIN PIPING NETWORK TO REMOVE ANY SEDIMENT BUILDUP AS NEEDED TO MAINTAIN DESIGN DRAINDOWN TIME.
  - MOWING, GRASS AREAS IN AND AROUND SAND FILTERS MUST BE MOWED AT LEAST TWICE ANNUALLY TO LIMIT VEGETATION HEIGHT TO 18 INCHES. MORE FREQUENT MOWING TO MAINTAIN AESTHETIC APPEAL MAY BE NECESSARY IN LANDSCAPED AREAS. VEGETATION ON THE POND EMBANKMENTS SHOULD BE MOWED AS APPROPRIATE TO PREVENT THE ESTABLISHMENT OF WOODY VEGETATION.




**SEDIMENT DEPTH MARKER**

SEE STRUCTURAL PLANS FOR CONCRETE WALL THICKNESS AND REINFORCEMENT.




- Specifications:**
- Concrete has a 28 day strength of 5,000 psi
  - Steel reinforcement is ASTM A615 grade 60
  - All edges chamfered 3/4"
- Notes:**
- Consult manufacturer before handling


<b>CAPITAL PRECAST, INC.</b>		FOR <b>12" Headwall</b>	
0969 SOUTH OLD BASTROP HWY	0969 SOUTH OLD BASTROP HWY	JOB NO.	
SAN MARCOS, TEXAS 78666	SAN MARCOS, TEXAS 78666	DATE	12/12/2015
PH: (830) 696-6200	PH: (830) 696-6200	REV.	
		FILE	catlogheadwall12 Headwall
			1 of 1




**SECTION A-A**  
NOT TO SCALE



**SECTION B-B**



**SECTION C-C**



**SAND BED DETAIL**

**KINGHAM DALTON WILSON, LTD**  
5858 WESTHEIMER, STE. 150  
HOUSTON, TX 77057

**TEXAS TITOS**  
1282 RIVER ROAD  
NEW BRAUNFELS, TX 78130


**WATER QUALITY BASIN 1**

SHEET **11** OF **20**

NO	DATE	ISSUES AND REVISIONS
1	6/30/2022	UPDATED PER CONB & TCEQ COMMENTS
2	3/14/2023	UPDATED PER CONB COMMENTS
3	6/20/2023	REVISED GRADING NEAR FLOODWAY




2021 W SH46, STE 105  
NEW BRAUNFELS, TX. 78132  
PH: 830-358-7127 ink-civil.com  
TBPE FIRM F-13351



**GABION BASKET DETAIL**  
SCALE: NTS


- STONE**  
STONE FILL MATERIAL SHALL CONSIST OF HARD, DURABLE, CLEAN STONE OF THE SIZE INDICATED, 6 TO 9 INCHES IN SIZE OR AS APPROVED BY THE ENGINEER AND RESISTANT TO THE ACTION OF AIR AND WATER AND SUITABLE IN ALL RESPECTS FOR THE PURPOSE INTENDED.
- WIRE CONTAINERS**  
WIRE MESH SHALL CONSIST OF PLASTIC COATED (P.V.C.) GALVANIZED WIRE 0.120 INCH IN DIAMETER MINIMUM AND SHALL EQUAL OR EXCEED FEDERAL SPECIFICATION QQ-W-481G, CLASS 3 UNLESS OTHERWISE INDICATED. OPENING OF THE MESH SHALL NOT EXCEED APPROXIMATELY 4 INCHES IN THE LONGEST DIMENSION. THE WIRE MESH IS TO BE FABRICATED IN SUCH MANNER AS TO BE NONRAVELING. TIE AND CONNECTING WIRE SHALL BE OF THE SAME TYPE AND SIZE AS THE BASKETS AND SHALL BE SUPPLIED IN SUFFICIENT QUANTITY FOR SECURELY FASTENING ALL EDGES OF THE GABION AND DIAPHRAGMS.
- FILTER FABRIC**  
FILTER FABRIC SHALL BE NON-BIODEGRADABLE ULTRAVIOLET STABILIZED, WERT TO MOST SOIL CHEMICALS, UNAFFECTED BY MOISTURE WHICH ALLOWS WATER TO PASS THROUGH WHILE RETAINING SOIL PARTICLES AND SHALL CONFORM TO ITEM NO. 820, "FILTER FABRIC".

12" or 15" dia. Headwall  
(with dissipators)



- Specifications:
- Concrete has a 28 day strength of 5,000 psi
  - Steel reinforcement is ASTM A615 grade 60
  - All edges chamfered 3/4"
- Notes:
- Consult manufacturer before handling

<b>Capital Precast</b>	<b>CAPITAL PRECAST, INC.</b>	FOR <b>12" Headwall</b>
	696 SOUTH OLD BASTROP HWY SACRAMENTO, TEXAS 75666 PH: (830) 656-6200	JOB NO. _____ DRAWN BY _____ DATE 12/12/2015 REV. NO. _____ FILE c:\ink\civ\basin\2\wg




**LEGEND**


- SF SILT FENCE
- LOC LIMITS OF CONSTRUCTION
- EXISTING CONTOURS
- PROPOSED CONTOURS
- FLOW ARROWS
- STABILIZED CONSTRUCTION ENTRANCE/EXIT
- TRUCK WASH OUT PIT
- CONSTRUCTION STAGING AREA
- ROCK BERM
- GRAVEL FILTER BAGS
- LOC LIMITS OF CONSTRUCTION

**DRAINAGE INFRASTRUCTURE MAINTENANCE AND MONITORING GUIDELINES**


- ACCESS - DRIVE OVER TOP OF CURB FOR MOWING AND MAINTENANCE OF SAND POND. A RAMP WILL BE PROVIDED AS SHOWN.
- SAND FILTER SYSTEMS MAINTENANCE AND MONITORING PROCEDURES
- INSPECTIONS. BMP FACILITIES MUST BE INSPECTED AT LEAST TWICE A YEAR (ONCE DURING OR IMMEDIATELY FOLLOWING WET WEATHER) TO EVALUATE FACILITY OPERATION. DURING EACH INSPECTION, EROSION AREAS INSIDE AND DOWNSTREAM OF THE BMP MUST BE IDENTIFIED AND REPAIRED OR REVEGETATED IMMEDIATELY. WITH EACH INSPECTION, ANY DAMAGE TO THE STRUCTURAL ELEMENTS OF THE SYSTEM (PIPES, CONCRETE DRAINAGE STRUCTURES, RETAINING WALLS, ETC.) MUST BE IDENTIFIED AND REPAIRED IMMEDIATELY. CRACKS, VOIDS AND UNDERMINING SHOULD BE PATCHED/FILLED TO PREVENT ADDITIONAL STRUCTURAL DAMAGE. TREES AND ROOT SYSTEMS SHOULD BE REMOVED TO PREVENT GROWTH IN CRACKS AND JOINTS THAT CAN CAUSE STRUCTURAL DAMAGE.
- SEDIMENT REMOVAL. REMOVE SEDIMENT FROM THE INLET STRUCTURE AND SEDIMENTATION CHAMBER WHEN SEDIMENT BUILDUP REACHES A DEPTH OF 6 INCHES OR WHEN THE PROPER FUNCTIONING OF INLET AND OUTLET STRUCTURES IS IMPAIRED. SEDIMENT SHOULD BE CLEARED FROM THE INLET STRUCTURE AT LEAST EVERY YEAR AND FROM THE SEDIMENTATION BASIN AT LEAST EVERY 5 YEARS.
- MEDIA REPLACEMENT. MAINTENANCE OF THE FILTER MEDIA IS NECESSARY WHEN THE DRAWDOWN TIME EXCEEDS 48 HOURS. WHEN THIS OCCURS, THE UPPER LAYER OF SAND SHOULD BE REMOVED AND REPLACED WITH NEW MATERIAL MEETING THE ORIGINAL SPECIFICATIONS. ANY DISCOLORED SAND SHOULD ALSO BE REMOVED AND REPLACED. IN FILTERS THAT HAVE BEEN REGULARLY MAINTAINED, THIS SHOULD BE LIMITED TO THE TOP 2 TO 3 INCHES.
- DEBRIS AND LITTER REMOVAL. DEBRIS AND LITTER WILL ACCUMULATE NEAR THE SEDIMENTATION BASIN. OUTLET DEVICE AND SHOULD BE REMOVED DURING REGULAR MOWING OPERATIONS AND INSPECTIONS. PARTICULAR ATTENTION SHOULD BE PAID TO FLOATING DEBRIS THAT CAN EVENTUALLY CLOG THE CONTROL DEVICE OR RISER.
- FILTER UNDERDRAIN. CLEAN UNDERDRAIN PIPING NETWORK TO REMOVE ANY SEDIMENT BUILDUP AS NEEDED TO MAINTAIN DESIGN DRAWDOWN TIME.
- MOWING. GRASS AREAS IN AND AROUND SAND FILTERS MUST BE MOWED AT LEAST TWICE ANNUALLY TO LIMIT VEGETATION HEIGHT TO 18 INCHES. MORE FREQUENT MOWING TO MAINTAIN AESTHETIC APPEAL MAY BE NECESSARY IN LANDSCAPED AREAS. VEGETATION ON THE POND EMBANKMENTS SHOULD BE MOWED AS APPROPRIATE TO PREVENT THE ESTABLISHMENT OF WOODY VEGETATION.



**SECTION A-A**  
NOT TO SCALE



**SECTION B-B**



**SECTION C-C**



**KINGHAM DALTON WILSON, LTD**  
5858 WESTHEIMER, STE. 150  
HOUSTON, TX 77057

**TEXAS TITOS**  
1282 RIVER ROAD  
NEW BRAUNFELS, TX 78130

**WATER QUALITY BASIN 2**


SHEET **12** OF **20**

NO	DATE	ISSUES AND REVISIONS
6/30/2022		UPDATED PER CONB & TCEQ COMMENTS
3/14/2023		UPDATED PER CONB COMMENTS



2021 W SH46, STE 105  
NEW BRAUNFELS, TX. 78132  
PH: 830-358-7127 ink-civil.com  
TBPE FIRM F-13351

### 3' x 3' x var 4-Way Inlet



**Bottom Section**  
36" dia thinwall knockouts all four sides


**Specifications:**  
- Concrete has a 28 day strength of 5,000 psi  
- Steel reinforcement is ASTM A615 grade 60  
- Load design is H-20

**Notes:**  
- Consult manufacturer before handling

	<b>CAPITAL PRECAST, INC.</b> 6905 SOUTH OLD BASTROP HWY SAN MARCOS, TEXAS 78665 PH: (830) 696-6200	FOR	3' x 3' x var 4-Way Inlet		
		JOB			
		DRAWN	RW	DATE	12/1/2015
		FILE	catalog/area/inlet/3x3 area inlet		
		SHEET	1 of 1		

### LEGEND

- NEW SANITARY SEWER
- NEW MANHOLE
- NEW SEWER LATERAL
- NEW WATER SERVICE
- NEW DOUBLE METERED DUAL WATER SERVICE
- NEW FIRE HYDRANT
- 100-YR HGL
- 25-YR HGL
- 2-YR HGL






### STORM DRAIN MAINTENANCE

INSPECT INLETS, JUNCTION STRUCTURES, OUTLETS AND CHANNELS THROUGH PERIODIC INSPECTION BUT NO LESS THAN EVERY 6 MONTHS TO CLEAR STRUCTURES OF OBSTRUCTIONS, DEBRIS AND STRUCTURAL INTEGRITY.

ALL RCP TO BE CLASS IV RCP AND IS RATED FOR DIRECT TRAFFIC LOADING

### STORM DRAIN LINE A1 PIPE SUMMARY


Name	Size	Q <sub>2</sub>	V <sub>2</sub>	Q <sub>25</sub>	V <sub>25</sub>	Q <sub>100</sub>	V <sub>100</sub>
SD A1	24"	2.87	0.91	6.20	1.97	8.86	2.82
SD A2	24"	2.87	0.91	6.20	1.97	8.86	2.82
SD A3	24"	2.87	0.91	6.20	1.97	8.86	2.82



### STORM DRAIN LINE TO WATER QUALITY BASIN CONNECTION DETAIL



### 3' x 3' x var Junction Box



**Bottom Section**  
6" walls and floor  
36" dia. thinwall knockouts all four sides


**Specifications:**  
- Concrete has a 28 day strength of 5,000 psi  
- Steel reinforcement is ASTM A615 grade 60  
- Load design is H-20

Approximate weight of base: 4,100 lbs

**Notes:**  
- Consult manufacturer before handling

	<b>CAPITAL PRECAST, INC.</b> 6905 SOUTH OLD BASTROP HWY SAN MARCOS, TEXAS 78665 PH: (830) 696-6200	FOR	3' x 3' x var Junction Box		
		JOB			
		DRAWN	RW	DATE	12/1/2015
		FILE	catalog/junction boxes/3x3JB		
		SHEET	1 of 1		

### STORM DRAIN LINE A1



SCALE:  
HORIZONTAL 1" = 50'  
VERTICAL 1" = 5'

**KINGHAM DALTON WILSON, LTD**  
5858 WESTHEIMER, STE. 150  
HOUSTON, TX 77057

**TEXAS TITOS**  
1282 RIVER ROAD  
NEW BRAUNFELS, TX 78130

### STORM DRAIN LINE A1

SHEET 13 OF 20

NO	DATE	ISSUES AND REVISIONS
1	6/30/2022	UPDATED PER CONB & TCEQ COMMENTS



2021 W SH46, STE 105  
NEW BRAUNFELS, TX. 78132  
PH: 830-358-7127 ink-civil.com  
TBPE FIRM F-13351

**TSS REMOVAL CALCULATIONS/PERMANENT BMP  
DESIGN**

**FOR**

**Texas Tito's**

PREPARED FOR  
**Texas Commission on Environmental Quality**

Region 13 – San Antonio  
14250 Judson Road  
San Antonio, Texas 78233  
210-490-3096 (office)  
210-545-4329 (fa)

PREPARED BY



F-13351

Shane Klar, P.E.  
2021 SH 46W, Ste 105  
New Braunfels, TX 78132

Prepared  
April 19, 2022



*Shane Klar* 4-22-22

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet

**1. The Required Load Reduction for the total project:**

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3:  $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$  = Required TSS removal resulting from the proposed development = 80% of increased load

$A_N$  = Net increase in impervious area for the project

$P$  = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	<b>Comal</b>	
Total project area included in plan *	<b>5.13</b>	acres
Predevelopment impervious area within the limits of the plan *	<b>0.00</b>	acres
Total post-development impervious area within the limits of the plan *	<b>3.53</b>	acres
Total post-development impervious cover fraction *	<b>0.69</b>	
P =	<b>33</b>	inches

$L_{M \text{ TOTAL PROJECT}} = 3169$  lbs.

\* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = **3**

**2. Drainage Basin Parameters (This information should be provided for each basin):**

Drainage Basin/Outfall Area No. =	<b>1</b>	
Total drainage basin/outfall area =	<b>3.04</b>	acres
Predevelopment impervious area within drainage basin/outfall area =	<b>0.00</b>	acres
Post-development impervious area within drainage basin/outfall area =	<b>2.43</b>	acres
Post-development impervious fraction within drainage basin/outfall area =	<b>0.80</b>	
$L_{M \text{ THIS BASIN}}$ =	<b>2181</b>	lbs.

**3. Indicate the proposed BMP Code for this basin.**

Proposed BMP = **Sand Filter**  
Removal efficiency = **89** percent

- Aqualogic Cartridge Filter
- Bioretention
- Contech StormFilter
- Constructed Wetland
- Extended Detention
- Grassy Swale
- Retention / Irrigation
- Sand Filter
- Stormceptor
- Vegetated Filter Strips
- Vortechs
- Wet Basin
- Wet Vault

**4. Calculate Maximum TSS Load Removed ( $L_R$ ) for this Drainage Basin by the selected BMP Type.**

RG-348 Page 3-33 Equation 3.7:  $L_R = (\text{BMP efficiency}) \times P \times (A_i \times 34.6 + A_p \times 0.54)$

where:

$A_C$  = Total On-Site drainage area in the BMP catchment area

$A_i$  = Impervious area proposed in the BMP catchment area

$A_p$  = Pervious area remaining in the BMP catchment area

$L_R$  = TSS Load removed from this catchment area by the proposed BMP

$A_C$  = **3.04** acres

$A_i$  = **2.45** acres

$A_p$  = **0.59** acres

$L_R$  = **2499** lbs

**5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area**

Desired  $L_{M \text{ THIS BASIN}}$  = **2410** lbs.

F = **0.96**

**6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area.**

Calculations from RG-348

Pages 3-34 to 3-36

Rainfall Depth = **2.80** inches  
Post Development Runoff Coefficient = **0.63**  
On-site Water Quality Volume = **19531** cubic feet

Calculations from RG-348 Pages 3-36 to 3-37

Off-site area draining to BMP = **0.76** acres  
Off-site Impervious cover draining to BMP = **0.39** acres  
Impervious fraction of off-site area = **0.51**  
Off-site Runoff Coefficient = **0.36**  
Off-site Water Quality Volume = **2818** cubic feet

Storage for Sediment = **4470**

**Total Capture Volume (required water quality volume(s) x 1.20) = 26819** cubic feet

The following sections are used to calculate the required water quality volume(s) for the selected BMP.  
The values for BMP Types not selected in cell C45 will show NA.

**9. Filter area for Sand Filters**

Designed as Required in RG-348

Pages 3-58 to 3-63

**9A. Full Sedimentation and Filtration System**

Water Quality Volume for sedimentation basin = **26819** cubic feet

Minimum filter basin area = **1085** square feet

Maximum sedimentation basin area = **9765** square feet **For minimum water depth of 2 feet**

Minimum sedimentation basin area = **2441** square feet **For maximum water depth of 8 feet**

**9B. Partial Sedimentation and Filtration System**

Water Quality Volume for combined basins = **26819** cubic feet

Minimum filter basin area = **1953** square feet

Maximum sedimentation basin area = **7812** square feet **For minimum water depth of 2 feet**

Minimum sedimentation basin area = **488** square feet **For maximum water depth of 8 feet**

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

**1. The Required Load Reduction for the total project:**

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3:  $L_M = 27.2(A_N \times P)$

where:

$L_{M \text{ TOTAL PROJECT}}$  = Required TSS removal resulting from the proposed development = 80% of increased load  
 $A_N$  = Net increase in impervious area for the project  
 $P$  = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	<b>Comal</b>	
Total project area included in plan *	<b>5.13</b>	acres
Predevelopment impervious area within the limits of the plan *	<b>0.00</b>	acres
Total post-development impervious area within the limits of the plan *	<b>3.53</b>	acres
Total post-development impervious cover fraction *	<b>0.69</b>	
P =	<b>33</b>	inches

$L_{M \text{ TOTAL PROJECT}} = 3169$  lbs.

\* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = **3**

**2. Drainage Basin Parameters (This information should be provided for each basin):**

Drainage Basin/Outfall Area No. =	<b>2</b>	
Total drainage basin/outfall area =	<b>1.11</b>	acres
Predevelopment impervious area within drainage basin/outfall area =	<b>0.00</b>	acres
Post-development impervious area within drainage basin/outfall area =	<b>0.77</b>	acres
Post-development impervious fraction within drainage basin/outfall area =	<b>0.69</b>	
$L_{M \text{ THIS BASIN}} =$	<b>691</b>	lbs.

**3. Indicate the proposed BMP Code for this basin.**

Proposed BMP = **Sand Filter**  
 Removal efficiency = **89** percent

- Aqualogic Cartridge Filter
- Bioretention
- Contech StormFilter
- Constructed Wetland
- Extended Detention
- Grassy Swale
- Retention / Irrigation
- Sand Filter
- Stormceptor
- Vegetated Filter Strips
- Vortechs
- Wet Basin
- Wet Vault

**4. Calculate Maximum TSS Load Removed ( $L_R$ ) for this Drainage Basin by the selected BMP Type.**

RG-348 Page 3-33 Equation 3.7:  $L_R = (\text{BMP efficiency}) \times P \times (A_i \times 34.6 + A_p \times 0.54)$

where:

$A_C$  = Total On-Site drainage area in the BMP catchment area  
 $A_i$  = Impervious area proposed in the BMP catchment area  
 $A_p$  = Pervious area remaining in the BMP catchment area  
 $L_R$  = TSS Load removed from this catchment area by the proposed BMP

$A_C =$	<b>1.11</b>	acres
$A_i =$	<b>0.77</b>	acres
$A_p =$	<b>0.34</b>	acres
$L_R =$	<b>788</b>	lbs

**5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area**

Desired  $L_{M \text{ THIS BASIN}}$  = **760** lbs.

F = **0.96**

**6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area.**

Calculations from RG-348

Pages 3-34 to 3-36

Rainfall Depth = **2.80** inches  
Post Development Runoff Coefficient = **0.50**  
On-site Water Quality Volume = **5634** cubic feet

Calculations from RG-348 Pages 3-36 to 3-37

Off-site area draining to BMP = **0.00** acres  
Off-site Impervious cover draining to BMP = **0.00** acres  
Impervious fraction of off-site area = **0**  
Off-site Runoff Coefficient = **0.00**  
Off-site Water Quality Volume = **0** cubic feet

Storage for Sediment = **1127**

**Total Capture Volume (required water quality volume(s) x 1.20) = 6761** cubic feet

The following sections are used to calculate the required water quality volume(s) for the selected BMP.  
The values for BMP Types not selected in cell C45 will show NA.

**7. Retention/Irrigation System**

Designed as Required in RG-348

Pages 3-42 to 3-46

Required Water Quality Volume for retention basin = **NA** cubic feet

Irrigation Area Calculations:

Soil infiltration/permeability rate = **0.1** in/hr **Enter determined permeability rate or assumed value of 0.1**  
Irrigation area = **NA** square feet  
**NA** acres

**9. Filter area for Sand Filters**

Designed as Required in RG-348

Pages 3-58 to 3-63

**9A. Full Sedimentation and Filtration System**

Water Quality Volume for sedimentation basin = **6761** cubic feet

Minimum filter basin area = **313** square feet

Maximum sedimentation basin area = **2817** square feet **For minimum water depth of 2 feet**

Minimum sedimentation basin area = **704** square feet **For maximum water depth of 8 feet**

**9B. Partial Sedimentation and Filtration System**

Water Quality Volume for combined basins = **6761** cubic feet

Minimum filter basin area = **563** square feet

Maximum sedimentation basin area = **2254** square feet **For minimum water depth of 2 feet**

Minimum sedimentation basin area = **141** square feet **For maximum water depth of 8 feet**

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

**1. The Required Load Reduction for the total project:**

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3:  $L_M = 27.2(A_N \times P)$

where:  $L_{M \text{ TOTAL PROJECT}}$  = Required TSS removal resulting from the proposed development = 80% of increased load  
 $A_N$  = Net increase in impervious area for the project  
 P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project  
 County = **Comal**  
 Total project area included in plan = **5.13** acres  
 Predevelopment impervious area within the limits of the plan = **0.00** acres  
 Total post-development impervious area within the limits of the plan = **3.53** acres  
 Total post-development impervious cover fraction = **0.69**  
 P = **33** inches

$L_{M \text{ TOTAL PROJECT}}$  = **3169** lbs.

\* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area = **3**

**2. Drainage Basin Parameters (This information should be provided for each basin):**

Drainage Basin/Outfall Area No. = **3**  
 Total drainage basin/outfall area = **0.72** acres  
 Predevelopment impervious area within drainage basin/outfall area = **0.00** acres  
 Post-development impervious area within drainage basin/outfall area = **0.33** acres  
 Post-development impervious fraction within drainage basin/outfall area = **0.46**  
 $L_{M \text{ THIS BASIN}}$  = **296** lbs.

**3. Indicate the proposed BMP Code for this basin.**

Proposed BMP = **Sand Filter**  
 Removal efficiency = **89** percent

- Aqualogic Cartridge Filter
- Bioretention
- Contech StormFilter
- Constructed Wetland
- Extended Detention
- Grassy Swale
- Retention / Irrigation
- Sand Filter
- Stormceptor
- Vegetated Filter Strips
- Vortechs
- Wet Basin
- Wet Vault

**4. Calculate Maximum TSS Load Removed ( $L_R$ ) for this Drainage Basin by the selected BMP Type.**

RG-348 Page 3-33 Equation 3.7:  $L_R = (\text{BMP efficiency}) \times P \times (A_i \times 34.6 + A_p \times 0.54)$

where:  $A_C$  = Total On-Site drainage area in the BMP catchment area  
 $A_i$  = Impervious area proposed in the BMP catchment area  
 $A_p$  = Pervious area remaining in the BMP catchment area  
 $L_R$  = TSS Load removed from this catchment area by the proposed BMP

$A_C$  = **1.34** acres  
 $A_i$  = **0.19** acres  
 $A_p$  = **1.15** acres  
 $L_R$  = **208** lbs

**5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area**

Desired  $L_{M \text{ THIS BASIN}}$  = **168** lbs.

F = **0.81**

**6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area.**

Calculations from RG-348

Pages 3-34 to 3-36

Rainfall Depth = **1.12** inches  
 Post Development Runoff Coefficient = **0.16**  
 On-site Water Quality Volume = **861** cubic feet

Calculations from RG-348 Pages 3-36 to 3-37

Off-site area draining to BMP = 0.00 acres  
 Off-site Impervious cover draining to BMP = 0.00 acres  
 Impervious fraction of off-site area = 0  
 Off-site Runoff Coefficient = 0.00  
 Off-site Water Quality Volume = 0 cubic feet

Storage for Sediment = 172  
 Total Capture Volume (required water quality volume(s) x 1.20) = 1033 cubic feet

The following sections are used to calculate the required water quality volume(s) for the selected BMP.  
 The values for BMP Types not selected in cell C45 will show NA.

**7. Retention/Irrigation System** Designed as Required in RG-348 Pages 3-42 to 3-46

Required Water Quality Volume for retention basin = NA cubic feet

Irrigation Area Calculations:

Soil infiltration/permeability rate = 0.1 in/hr Enter determined permeability rate or assumed value of 0.1  
 Irrigation area = NA square feet  
 NA acres

**8. Extended Detention Basin System** Designed as Required in RG-348 Pages 3-46 to 3-51

Required Water Quality Volume for extended detention basin = NA cubic feet

**9. Filter area for Sand Filters** Designed as Required in RG-348 Pages 3-58 to 3-63

**9A. Full Sedimentation and Filtration System**

Water Quality Volume for sedimentation basin = 1033 cubic feet  
 Minimum filter basin area = 48 square feet  
 Maximum sedimentation basin area = 430 square feet For minimum water depth of 2 feet  
 Minimum sedimentation basin area = 108 square feet For maximum water depth of 8 feet


**9B. Partial Sedimentation and Filtration System**

Water Quality Volume for combined basins = 1033 cubic feet  
 Minimum filter basin area = 86 square feet  
 Maximum sedimentation basin area = 344 square feet For minimum water depth of 2 feet  
 Minimum sedimentation basin area = 22 square feet For maximum water depth of 8 feet

**Agent Authorization Form**  
For Required Signature  
Edwards Aquifer Protection Program  
Relating to 30 TAC Chapter 213  
Effective June 1, 1999

I \_\_\_\_\_ Chris Snider \_\_\_\_\_  
Print Name  
Owner \_\_\_\_\_  
Title - Owner/President/Other \_\_\_\_\_  
of \_\_\_\_\_ BLIEDERS CREEK, LLC \_\_\_\_\_  
Corporation/Partnership/Entity Name  
have authorized \_\_\_\_\_ Shane Klar \_\_\_\_\_  
Print Name of Agent/Engineer  
of \_\_\_\_\_ INK Civil \_\_\_\_\_  
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.



I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

[Signature]  
Applicant's Signature


8/19/2025  
Date

THE STATE OF Texas §

County of Comal §

BEFORE ME, the undersigned authority, on this day personally appeared Ronald Christopher Snider known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 18 day of March, 2022.



[Signature]  
NOTARY PUBLIC

Desiree Ruiz  
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 08-19-2025

# Application Fee Form

**Texas Commission on Environmental Quality**

Name of Proposed Regulated Entity: Texas Tito's

Regulated Entity Location: Within New Braunfels city limits, intersection of Loop 337 & River Rd

Name of Customer: Blieders Creek, LLC

Contact Person: James Ingalls, P.E.

Phone: 830-358-7127

Customer Reference Number (if issued): CN 606009058

Regulated Entity Reference Number (if issued): RN 111481024

**Austin Regional Office (3373)**

Hays

Travis

Williamson

**San Antonio Regional Office (3362)**

Bexar

Medina

Uvalde

Comal

Kinney

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to:

Austin Regional Office

San Antonio Regional Office

Mailed to: TCEQ - Cashier

Overnight Delivery to: TCEQ - Cashier

Revenues Section

12100 Park 35 Circle

Mail Code 214

Building A, 3rd Floor

P.O. Box 13088

Austin, TX 78753

Austin, TX 78711-3088

(512)239-0357


**Site Location (Check All That Apply):**

Recharge Zone

Contributing Zone

Transition Zone

<i>Type of Plan</i>	<i>Size</i>	<i>Fee Due</i>
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	5.129 Acres	\$ 5,000
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: 

Date: 10-20-23

# Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

## ***Water Pollution Abatement Plans and Modifications***

### ***Contributing Zone Plans and Modifications***

<b><i>Project</i></b>	<b><i>Project Area in Acres</i></b>	<b><i>Fee</i></b>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

### ***Organized Sewage Collection Systems and Modifications***

<b><i>Project</i></b>	<b><i>Cost per Linear Foot</i></b>	<b><i>Minimum Fee- Maximum Fee</i></b>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

### ***Underground and Aboveground Storage Tank System Facility Plans and Modifications***

<b><i>Project</i></b>	<b><i>Cost per Tank or Piping System</i></b>	<b><i>Minimum Fee- Maximum Fee</i></b>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

### ***Exception Requests***

<b><i>Project</i></b>	<b><i>Fee</i></b>
Exception Request	\$500

### ***Extension of Time Requests***

<b><i>Project</i></b>	<b><i>Fee</i></b>
Extension of Time Request	\$150



TCEQ Use Only

# TCEQ Core Data Form

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

## SECTION I: General Information

<b>1. Reason for Submission</b> (If other is checked please describe in space provided.)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input type="checkbox"/> Other	
<b>2. Customer Reference Number (if issued)</b>	<a href="#">Follow this link to search for CN or RN numbers in Central Registry**</a>	<b>3. Regulated Entity Reference Number (if issued)</b>
CN 606009058		RN 111481024

## SECTION II: Customer Information

<b>4. General Customer Information</b>		<b>5. Effective Date for Customer Information Updates</b> (mm/dd/yyyy)	
<input type="checkbox"/> New Customer		<input checked="" type="checkbox"/> Update to Customer Information	
<input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)		<input type="checkbox"/> Change in Regulated Entity Ownership	
<b>The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).</b>			
<b>6. Customer Legal Name</b> (If an individual, print last name first: eg: Doe, John)		If new Customer, enter previous Customer below:	
BLIEDERS CREEK LLC			
<b>7. TX SOS/CPA Filing Number</b>	<b>8. TX State Tax ID</b> (11 digits)	<b>9. Federal Tax ID</b> (9 digits)	<b>10. DUNS Number</b> (if applicable)
0804054938	32079115542	N/A	N/A
<b>11. Type of Customer:</b>	<input type="checkbox"/> Corporation	<input type="checkbox"/> Individual	Partnership: <input type="checkbox"/> General <input checked="" type="checkbox"/> Limited
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> State <input type="checkbox"/> Other	<input type="checkbox"/> Sole Proprietorship	<input type="checkbox"/> Other:	
<b>12. Number of Employees</b>		<b>13. Independently Owned and Operated?</b>	
<input checked="" type="checkbox"/> 0-20 <input type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher		<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
<b>14. Customer Role</b> (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following			
<input checked="" type="checkbox"/> Owner <input type="checkbox"/> Operator <input type="checkbox"/> Owner & Operator			
<input type="checkbox"/> Occupational Licensee <input type="checkbox"/> Responsible Party <input type="checkbox"/> Voluntary Cleanup Applicant <input type="checkbox"/> Other:			
<b>15. Mailing Address:</b>	422 Saddle Tree		
	City	New Braunfels	State TX ZIP 78130 ZIP + 4 5261
<b>16. Country Mailing Information</b> (if outside USA)		<b>17. E-Mail Address</b> (if applicable)	
		chis@texastitos.com	
<b>18. Telephone Number</b>	<b>19. Extension or Code</b>	<b>20. Fax Number</b> (if applicable)	
( ) -		( ) -	

## SECTION III: Regulated Entity Information

<b>21. General Regulated Entity Information</b> (If 'New Regulated Entity' is selected below this form should be accompanied by a permit application)
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information
<b>The Regulated Entity Name submitted may be updated in order to meet TCEQ Agency Data Standards (removal of organizational endings such as Inc, LP, or LLC).</b>
<b>22. Regulated Entity Name</b> (Enter name of the site where the regulated action is taking place.)
Texas Tito's

23. Street Address of the Regulated Entity: <i>(No PO Boxes)</i>	TBD						
	City	N.Braunfels	State	TX	ZIP	78130	ZIP + 4
24. County	Comal						

Enter Physical Location Description if no street address is provided.

25. Description to Physical Location:	Approximately 0.10 miles southeast of Loop 337 and River Rd intersection						
26. Nearest City	New Braunfels			State	TX	Nearest ZIP Code	78130
27. Latitude (N) In Decimal:	29.72778		28. Longitude (W) In Decimal:	98.12473			
Degrees	Minutes	Seconds	Degrees	Minutes	Seconds		
29	43	40.01	98	7	29.03		
29. Primary SIC Code (4 digits)	30. Secondary SIC Code (4 digits)	31. Primary NAICS Code (5 or 6 digits)		32. Secondary NAICS Code (5 or 6 digits)			
2035	N/A	311991		N/A			
33. What is the Primary Business of this entity? <i>(Do not repeat the SIC or NAICS description.)</i>							
Packaging and wholesale of pickled vegetables							
34. Mailing Address:	TBD						
	City		State		ZIP		ZIP + 4
35. E-Mail Address:							
36. Telephone Number		37. Extension or Code		38. Fax Number <i>(if applicable)</i>			
( ) -				( ) -			

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.


<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input checked="" type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
		13001528		
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Waste Water	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

#### SECTION IV: Preparer Information

40. Name:	Chad Friesenhahn, EIT		41. Title:	Graduate Engineer	
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address		
( 830 ) 358-7127		( ) -	chadfriesenhahn@ink-civil.com		

#### SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	INK Civil	Job Title:	Professional Engineer		
Name <i>(In Print)</i> :	James Ingalls, P.E.	Phone:	( 830 ) 358- 7127		
Signature:		Date:	10-12-23		