Texas Commission on Environmental Quality Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with <u>30 TAC 213</u>.

Administrative Review

1. <u>Edwards Aquifer applications</u> must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <u>http://www.tceq.texas.gov/field/eapp</u>.

- 2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
- 3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
- 4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

- 5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
- 6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

- 1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
- 2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

- 3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
- 4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity N System Forest Crest	ame: San Aı	ntonio	Wate	r	2. Re	egulat	ed Entity No.:	
3. Customer Name: S	San Antonio	Water	Syste	em	4. Cı	istom	er No.: 600529	069
5. Project Type: (Please circle/check one)	New	Modif	icatior	1	Exter	nsion	Exception	
6. Plan Type: (Please circle/check one)	WPAP CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Residential	Non-r	residen	tial		8. Sit	e (acres):	0.104
9. Application Fee:	\$3,000	10. P	ermai	nent I	BMP(s):	Proposed	
11. SCS (Linear Ft.):	N/A	12. A	ST/US	ST (N	o. Tar	nks):	1	
13. County:	Bexar	14. W	aters	hed:			Leon	

Application Distribution

Г

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

	Ausun	Kegion	
County:	Hays	Travis	Williamson
Original (1 req.)			
Region (1 req.)			
County(ies)			—
Groundwater Conservation District(s)	Edwards Aquifer Authority Barton Springs/ Edwards Aquifer Hays Trinity Plum Creek	Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	Austin Buda Dripping Springs Kyle Mountain City San Marcos Wimberley Woodcreek	Austin Bee Cave Pflugerville Rollingwood Round Rock Sunset Valley West Lake Hills	Austin Cedar Park Florence Georgetown Jerrell Leander Liberty Hill Pflugerville Round Rock

Austin Region

	Sa	an Antonio Region			
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	_X_		_		
Region (1 req.)	_X_				
County(ies)	_X_				
Groundwater Conservation District(s)	Edwards Aquifer Authority _X_Trinity-Glen Rose	Edwards Aquifer Authority	Kinney	EAA Medina	EAA Uvalde
City(ies) Jurisdiction	Castle Hills Fair Oaks Ranch Helotes Hill Country Village Hollywood Park _X_San Antonio (SAWS) Shavano Park	Bulverde Fair Oaks Ranch Garden Ridge New Braunfels Schertz	NA	San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

Aaron Bentley, E.I.T.

Print Name of Customer/Authorized Agent

Signature of Customer/Authorized Agent

Date

FOR TCEQ INTERNAL USE ONL	X			
Date(s)Reviewed:		Date Adn	ninistratively Complete	e:
Received From:		Correct N	Number of Copies:	
Received By:		Distribut	ion Date:	
EAPP File Number:		Complex	:	
Admin. Review(s) (No.):		No. AR R	lounds:	
Delinquent Fees (Y/N):		Review T	'ime Spent:	
Lat./Long. Verified:		SOS Cust	comer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee	Payable to TCEQ (Y/I	N):
Core Data Form Complete (Y/N):	Check:		Signed (Y/N):	
Core Data Form Incomplete Nos.:			Less than 90 days old	l (Y/N):

CONTRIBUTING ZONE PLAN (TCEQ 10257)

Contributing Zone Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Contributing Zone to the Edwards Aquifer and Relating to 30 TAC §213.24(1), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Contributing Zone Plan Application** is hereby submitted for TCEQ review and Executive Director approval. The application was prepared by:

Print Name of Customer/Agent: <u>Aaron Bentley, E.I.T.</u>

Date: 9/10/2024

Signature of Customer/Agent:

Regulated Entity Name: San Antonio Water System Forest Crest

Project Information

- 1. County: Bexar
- 2. Stream Basin: San Antonio
- 3. Groundwater Conservation District (if applicable): Trinity Glen Rose
- 4. Customer (Applicant):

Contact Person: Dr. Saqib Shirazi, P.E., PMPEntity: San Antonio Water SystemMailing Address: 2800 US Highway 281 NCity, State: San Antonio, TXZip: 78212Telephone: 210-704-7297Fax: _____Email Address: saqib.shirazi@saws.org

TCEQ-10257 (Rev. 02-11-15)

5. Agent/Representative (If any):

Contact Person: Aaron Bentley, E.I.T.Entity: Weston Solutions, IncMailing Address: 70 NE Loop 410 Ste 600City, State: San Antonio, TXZip: 78216Telephone: 210-308-4311Fax: _____Email Address: aaron.bentley@westonsolutions.com

6. Project Location:

The project site is located inside the city limits of _____

- The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of <u>COSA</u>.
- The project site is not located within any city's limits or ETJ.
- 7. The location of the project site is described below. Sufficient detail and clarity has been provided so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.
 - <u>The Forest Crest pump station is located in a residential area off of West Tejas Trail in</u> <u>San Antonio, Texas (Lat: 29.637600°; Long: -98.592096°). The pump station is</u> <u>surrounded by a wooden and chain link fence. The area to the West and upgradient</u> <u>of the site is primarily residential. The areas to the North, East, and South are</u> <u>primarily undeveloped, with the property to the East belonging to Camp Bullis.</u>
- 8. Attachment A Road Map. A road map showing directions to and the location of the project site is attached. The map clearly shows the boundary of the project site.
- 9. Attachment B USGS Quadrangle Map. A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') is attached. The map(s) clearly show:

Project site boundaries.
 USGS Quadrangle Name(s).

- 10. Attachment C Project Narrative. A detailed narrative description of the proposed project is attached. The project description is consistent throughout the application and contains, at a minimum, the following details:
 - Area of the site
 Offsite areas
 Impervious cover
 Permanent BMP(s)
 Proposed site use
 Site history
 Previous development
 Area(s) to be demolished

- 11. Existing project site conditions are noted below:
 - Existing commercial site
 - Existing industrial site
 - Existing residential site
 - Existing paved and/or unpaved roads
 - Undeveloped (Cleared)
 - Undeveloped (Undisturbed/Not cleared)
 - Other: Water pump station, Public utility

12. The type of project is:

Residential: # of Lots:

- Residential: # of Living Unit Equivalents:
- Commercial
- Industrial
- Other: Water pump station, Public utility
- 13. Total project area (size of site): 0.104 Acres

Total disturbed area: 0.0155 Acres

- 14. Estimated projected population: N/A
- 15. The amount and type of impervious cover expected after construction is complete is shown below:

 Table 1 - Impervious Cover

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops		÷ 43,560 =	
Parking		÷ 43,560 =	
Other paved surfaces	676.24	÷ 43,560 =	0.0155
Total Impervious Cover	676.24	÷ 43,560 =	0.0155

Total Impervious Cover 0.0155 ÷ Total Acreage 0.104 X 100 = 14.90% Impervious Cover

- 16. Attachment D Factors Affecting Surface Water Quality. A detailed description of all factors that could affect surface water quality is attached. If applicable, this includes the location and description of any discharge associated with industrial activity other than construction.
- 17. 🛛 Only inert materials as defined by 30 TAC 330.2 will be used as fill material.

For Road Projects Only

Complete questions 18 - 23 if this application is exclusively for a road project.

N/A

18. Type of project:

TXDOT road project. County road or roads built to county specifications. City thoroughfare or roads to be dedicated to a municipality. Street or road providing access to private driveways. 19. Type of pavement or road surface to be used: Concrete Asphaltic concrete pavement __ Other: 20. Right of Way (R.O.W.): Length of R.O.W.: _____ feet. Width of R.O.W.: feet. $L \times W = Ft^2 \div 43,560 Ft^2/Acre = acres.$ 21. Pavement Area: Length of pavement area: _____ feet. Width of pavement area: ______ feet. L x W =____Ft² ÷ 43,560 Ft²/Acre = _____ acres. Pavement area _____ acres ÷ R.O.W. area _____ acres x 100 = ____% impervious cover. 22. A rest stop will be included in this project. A rest stop will not be included in this project. 23. Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening

TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

Stormwater to be generated by the Proposed Project

24. Attachment E - Volume and Character of Stormwater. A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

Wastewater to be generated by the Proposed Project

25. Wastewater is to be discharged in the contributing zone. Requirements under 30 TAC §213.6(c) relating to Wastewater Treatment and Disposal Systems have been satisfied.

🛛 N/A

26. Wastewater will be disposed of by:

On-Site Sewage Facility (OSSF/Septic Tank):

Attachment F - Suitability Letter from Authorized Agent. An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

Sewage Collection System (Sewer Lines):

The sewage collection system will convey the wastewater to the _____ (name) Treatment Plant. The treatment facility is:

Existing.

🛛 N/A

Permanent Aboveground Storage Tanks(ASTs) ≥ 500 Gallons

Complete questions 27 - 33 if this project includes the installation of AST(s) with volume(s) greater than or equal to 500 gallons.

N/A

27. Tanks and substance stored:

Table 2 - Tanks and Substance Storage

AST Number	Size (Gallons)	Substance to be Stored	Tank Material
1	1700	Diesel Fuel	Double-walled Steel Tank
2			

AST Number	Size (Gallons)	Substance to be Stored	Tank Material
3			
4			
5			

Total x 1.5 = 2,550 Gallons

- 28. The AST will be placed within a containment structure that is sized to capture one and one-half (1 1/2) times the storage capacity of the system. For facilities with more than one tank system, the containment structure is sized to capture one and one-half (1 1/2) times the cumulative storage capacity of all systems.
 - Attachment G Alternative Secondary Containment Methods. Alternative methods for providing secondary containment are proposed. Specifications showing equivalent protection for the Edwards Aquifer are attached.
- 29. Inside dimensions and capacity of containment structure(s):

Table 3 - Secondary Containment

Length (L)(Ft.)	Width(W)(Ft.)	Height (H)(Ft.)	L x W x H = (Ft3)	Gallons
19.5	6.8	10.6	1,405.56	10,513

Total: 10,513 Gallons

30. Piping:

All piping, hoses, and dispensers will be located inside the containment structure.

Some of the piping to dispensers or equipment will extend outside the containment structure.

The piping will be aboveground

The piping will be underground

- 31. The containment area must be constructed of and in a material impervious to the substance(s) being stored. The proposed containment structure will be constructed of: <u>Steel; Double-walled steel tank</u>.
- 32. Attachment H AST Containment Structure Drawings. A scaled drawing of the containment structure is attached that shows the following:

Interior dimensions (length, width, depth and wall and floor thickness).
 Internal drainage to a point convenient for the collection of any spillage.

TCEQ-10257 (Rev. 02-11-15)

Tanks clearly labeled Piping clearly labeled Dispenser clearly labeled

33. Any spills must be directed to a point convenient for collection and recovery. Spills from storage tank facilities must be removed from the controlled drainage area for disposal within 24 hours of the spill.

In the event of a spill, any spillage will be removed from the containment structure within 24 hours of the spill and disposed of properly.

In the event of a spill, any spillage will be drained from the containment structure through a drain and valve within 24 hours of the spill and disposed of properly. The drain and valve system are shown in detail on the scaled drawing.

Site Plan Requirements

Items 34 - 46 must be included on the Site Plan.

34. \square The Site Plan must have a minimum scale of 1" = 400'.

Site Plan Scale: 1'' = 400'.

35. 100-year floodplain boundaries:

Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.

 \boxtimes No part of the project site is located within the 100-year floodplain.

The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): <u>Panel 0115</u>.

36. The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.

The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot contour intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.

- 37. \square A drainage plan showing all paths of drainage from the site to surface streams.
- 38. 🖂 The drainage patterns and approximate slopes anticipated after major grading activities.
- 39. \square Areas of soil disturbance and areas which will not be disturbed.
- 40. 🛛 Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
- 41. 🛛 Locations where soil stabilization practices are expected to occur.

- 42. □ Surface waters (including wetlands).☑ N/A
- 43. Locations where stormwater discharges to surface water.

There will be no discharges to surface water.

- 44. Temporary aboveground storage tank facilities.
 - Temporary aboveground storage tank facilities will not be located on this site.
- 45. Permanent aboveground storage tank facilities.

Permanent aboveground storage tank facilities will not be located on this site.

46. \boxtimes Legal boundaries of the site are shown.

Permanent Best Management Practices (BMPs)

Practices and measures that will be used during and after construction is completed.

- 47. Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
 - 🖂 N/A
- 48. These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
 - The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
 - A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: _____.

🖂 N/A

49. Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.

🛛 N/A

50. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the

TCEQ-10257 (Rev. 02-11-15)

whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

The site will be used for low density single-family residential development and has 20% or less impervious cover.

The site will be used for low density single-family residential development but has more than 20% impervious cover.

The site will not be used for low density single-family residential development.

- 51. The executive director may waive the requirement for other permanent BMPs for multifamily residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
 - Attachment I 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.

The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.

The site will not be used for multi-family residential developments, schools, or small business sites.

52. X Attachment J - BMPs for Upgradient Stormwater.

- A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
- No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.

Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.

53. X Attachment K - BMPs for On-site Stormwater.

A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.

Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.

54.	Attachment L - BMPs for Surface Streams.	A description of the BMPs and measures
	that prevent pollutants from entering surfa	ce streams is attached.

N/A

55. Attachment M - Construction Plans. Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. Construction plans for the proposed permanent BMPs and measures are attached and include: Design calculations, TCEQ Construction Notes, all proposed structural plans and specifications, and appropriate details.

N/A

56. Attachment N - Inspection, Maintenance, Repair and Retrofit Plan. A site and BMP specific plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan fulfills all of the following:

Prepared and certified by the engineer designing the permanent BMPs and measures

Signed by the owner or responsible party

Outlines specific procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofit.

Contains a discussion of record keeping procedures

- N/A
- 57. Attachment O Pilot-Scale Field Testing Plan. Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.

🛛 N/A

58. Attachment P - Measures for Minimizing Surface Stream Contamination. A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that result in water quality degradation.

🖂 N/A

Responsibility for Maintenance of Permanent BMPs and Measures after Construction is Complete.

59. The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an

TCEQ-10257 (Rev. 02-11-15)

owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.

60. A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.

Administrative Information

- 61. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions.
- 62. Any modification of this Contributing Zone Plan may require TCEQ review and Executive Director approval prior to construction, and may require submission of a revised application, with appropriate fees.
- 63. The site description, controls, maintenance, and inspection requirements for the storm water pollution prevention plan (SWPPP) developed under the EPA NPDES general permits for stormwater discharges have been submitted to fulfill paragraphs 30 TAC §213.24(1-5) of the technical report. All requirements of 30 TAC §213.24(1-5) have been met by the SWPPP document.
 - The Temporary Stormwater Section (TCEQ-0602) is included with the application.

ATTACHMENT A

ROAD MAP



ATTACHMENT B

USGS QUADRANGLE MAP



ATTACHMENT C

PROJECT NARRATIVE

PROJECT DESCRIPTION

AREA OF THE SITE

The project will consist of the construction of a new concrete generator pad, electrical wiring and controls, and a diesel powered generator. The Forest Crest pump station is an approximately 0.103 acre area located at 20940 E Tejas Trl in San Antonio, Texas (The site). The site slopes gently downward to the west. The site is currently used as a public utility site conveying potable water to the surrounding properties.

OFFSITE AREAS

The Forest Crest pump station is located in a residential area off of West Tejas Trail in San Antonio, Texas (Lat: 29.637600°; Long: -98.592096°). The pump station is surrounded by a wooden and chain link fence. The area to the West and upgradient of the site is primarily residential. The areas to the North, East, and South are primarily undeveloped, with the property to the East belonging to Camp Bullis. A geological assessment was performed as part of this CZ application (included in the geological assessment section) showed that there are no environmentally sensitive features within a 50 ft buffer of the proposed construction limits.

IMPERVIOUS COVER

The project scope involves the demolition of 0.00661 acre of existing impervious cover and installation of approximately 0.0155 acre of impervious cover.

TEMPORARY AND PERMANENT BMPs

Temporary BMPs are designed with respect to local and state regulations to ensure construction does not contaminate the nearby residential and public properties. Any defects will be repaired within one year of discovery. Due to the small size of the project site, Permanent BMPs will not be necessary after construction has concluded.

PROPOSED SITE USE

Once construction has been completed, the site will be utilized as a fully operating pump station. It will be the responsibility of the Owner to operate and maintain the system beyond the one-year warranty time frame.

SITE HISTORY

The site is currently being used as a pump station site.

PREVIOUS DEVELOPMENT

The site was previously developed to contain a Pump Station over an approximately 0.103 acre area.

AREA(S) TO BE DEMOLISHED

The project does not involve demolishing pre-existing structures.

ATTACHMENT D

FACTORS AFFECTING WATER QUALITY

FACTORS AFFECTING SURFACE WATER QUALITY

Potential sources of sediment to stormwater runoff:

Surface runoff of dirt, tracking of mud, construction debris, and wind-blown dust will be controlled through the use of temporary erosion control practices.

Potential pollutants and sources, other than sediment, to stormwater runoff:

Temporary potential sources of contamination include:

- 1. Equipment and Fuel Oil
- 2. Concrete
- 3. Asphalt pavement products

Pollution Control procedures and devices:

Pollution Control procedures include the following:

- Erosion and sedimentation controls will be installed and maintained during the project according to the Erosion and Sedimentation Control Plan. Temporary erosion controls will be provided by silt fence and mulch sock inlet protection filters. Silt fence will be deployed at all locations of potential discharge around the perimeter of the site. Silt fence prevents the escape of sediment from the site by discharging water through a filter fabric, trapping sediment.
- After construction has concluded, there will be no factors that will affect the surface water or groundwater quality based on the land use.
- Accidental spill from hazard materials such as fuel and hydrocarbons shall be contained per the Spill Response Plan included in Attachment A of the Temporary Stormwater Section.

ATTACHMENT E

VOLUME AND CHARACTER OF STORMWATER

VOLUME AND CHARACTERISTICS OF STORMWATER

Volume and Characteristics of Stormwater

All stormwater flowing from the impervious surfaces in the proposed development will discharge into adjacent storm channels. Due to the small surface area of the site and the land use after construction, the stormwater runoff will be of minimal volume. The treatment of the stormwater runoff will not be required since there will be no contamination of the stormwater. Additionally, there will be no upgradient stormwater that will flow through the developed site to impact the volume and characteristics of the stormwater runoff.

ATTACHMENT F

SUITABILITY LETTER FROM AUTHORIZED AGENT (NOT APPLICABLE)

ATTACHMENT G

ALTERNATIVE SECONDARY CONTAINMENT METHODS

ALTERNATIVE SECONDARY CONTAINMENT METHODS

The secondary containment method to be used will be a double-walled steel tank. In the event of a spill or overflow, the fuel would be contained by the second tank wall. Additionally, in the event of a leak from the primary tank, the fuel will be contained by the secondary tank wall.

ATTACHMENT H

AST CONTAINMENT STRUCTURE DRAWINGS



Confidential and Proprietary and shall not be disclosed to others in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc.

Part Number: A063J084 Part Revision: B Part Name: **OUTLINE, GENSET** Drawing Category: **Outline** State: **Released** Sheet 1 of 5



Confidential and Proprietary and shall not be disclosed to others in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc.

Part Name: OUTLINE, GENSET Drawing Category: **Outline** State: **Released** Sheet 2 of 5



in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc.

Part Number: A063J084 Part Revision: B Part Name: OUTLINE, GENSET Drawing Category: **Outline** State: **Released** Sheet 3 of 5



This document (and the information shown thereon) is **Confidential and Proprietary** and shall not be disclosed to others in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc.



	C	
	B	
	A	
Cummins Inc.		
DIMENSIONS ARE IN: MILLIMETERS SIZE: D SCALE:0.063		
DIMENSIONING AND TOLERANCING PER: ASME YI4.5-2009 THIB ANAL PROJECTION PTC® Cres® Parametr	ic	
2 1		

Drawing Category: **Outline** State: **Released**

Sheet 4 of 5



Confidential and Proprietary and shall not be disclosed to others in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc.

GMT Document Generated: 290CT2019 15:31

Part Number: A050L372 Part Revision: C Part Name: OUTLINE, ENCLOSURE Drawing Category: **Outline** State: **Released** Sheet 1 of 7



in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc.

Document Generated: 29OCT2019 15:31 GMT

Part Number: A050L372 Part Revision: C Part Name: OUTLINE, ENCLOSURE Drawing Category: **Outline** State: **Released** Sheet 2 of 7


								1						_
II4210	TR NO	PRODU	ICTION_	RELEAS	E				MRJ	CKD ZYM	APV Z_MOC	D GES	DATE JAN	
														D
NOTE :														
Ι.	DIM	MENSI	ONS	IN [] /	ARE	I N	INCH	ES.					
2	∠ SK TH	ID-BA	SE (I SS OF	IFTI 4.70	NG) 6mm	AND	FUE 9 I 1	EL T NCHF	ANK S1.	HAV	ΈA	FLA	NGE	
	(Fl	LORID 35 IN	A UN CHES:	ITS W].}	ITH	FEA	TURE	C C O	DEL	6) 8.	76m	im	
	ALI OF	LOW E MOUN	X T R A T I N G	LENG SURF/	TH (ACE.	DN H	ARDV	WARE	FOR	UN	EVEN	ESS		
$\sqrt{3}$	ZFI	FTING	BASE	E OR F	FUEL	TA	NK F	PARI	METE	RI	S SH	OWN		_
	PEF	RIMET	ER. S	SEE () BE T03(5 E X D) A	PPL	ICAT	ION	MAN	UAL.			
	_												-	
			_	PLI	EA	SE	N	от	:		_			
		This Ploa	is So	N add	דכ י	a + 1	p p	ad	dı 1 1	rav	ving	g.		
		ovei	all	lei	ngt	th	8 8	51	wid	lth		of		
		gen	erat	or w	he	en c	det	ern	nini	ng	pa	d		
	'	ayo	ut.											
Г			_										7	
	N	ΟΤΙ	E:	ON	LY	Т	HIS	5	DR	A۷	VIN	G		
	SH	IALL	BI	EU	SE	D	FO	R	STI	UB	U	Ρ		←
	DI	ME	ISIC	NAL	. IN	IFO	RN	/ A]	ΙΟΙ	N				
L														
														в
4.3 [4.5]														
														_
														A
DWN M_	JOHN	SON		anyut	385		Cu	MINS	Powe	ER C	ENERA	TION		1
APVD Z	MOGE	S						VE,	GEN	SE	[_		
FOR INTERPR OF DIMENSIO TOLERANCING	JANI ETATION NING AND SEE	FIRST USED	<mark>3</mark> - F К	PG	A		A03	35F 9	951			1	SHEET DING REV OF 2 A	
ASME TI4.	JH-1994		1			-		1					1 "	L







								1							1
I3I569 H	ко 2	DRAW	N ING HAS	BEEN		ORIA	LLY	JPDA	TED	MP	GT	APVD G_THARIVI	TLA	DATE I 5 JAN I 3	
		NOOD	1211000	41 KI U"	av rn	KASE	30	JAKE		MP	GT	G_THARIVI	TLA	- 5JAN 3	
RIBUTIO	N P	ANEL	NOTE	S :											D
:															
FUEL TR. DISTRIB AND STE PUMP WH OTHER A TO OPE RGENCY	ANS UTI P-D EN CD RAT SOU	FER ON P OWN UTIL ISTR E, S RCE	PUMP ANEL TRANS ITY P IBUTI O THE IF NO	IS I MUST FORM OWER ON P PAN PUM	NCLU BE ER T IS ANEL EL C P IS	IDED FED INT LC OUL	WI FR ERR ADS D B STA	TH OM TAI UPT AR E F LLE	THE A ED ED D.	S RA 20 VEE FR	ET, NSF V P NON DED OM	ER OWER E FOR A			
NECTION COMPLI LICABLE CONDUCT	S T ANC LO ORS	O TH E WI CAL	E AC TH TH CODES	DIST E NA AND	RIBU TION STA	ITIC IAL INDA	N P ELE RDS	ANE CTR US	L / HC HN(ARE CO 66	TO DE 0 O	BE AND R 75			
DISTRIB 120/24 ORS CON FOR #4 N-LB. T T IS LI TORQUE NNECTS DUCTORS	UTI 0, NEC TO HE STE D T INT , A	ON P SING TIN 2/0 NEUT DFO O TH COTH LOR	ANEL LE PH TO TH CONDU RAL C R #5 FT-L E GRO CU W	IS D ASE E IO CTOR ONDU TO 3 B. T UND HEN	ESIG FEED OAMP ES, CTOR OOKC HE G BAR. TORG	NED ER. AL CC MIL ROU IT	TO TH OR NNE CO NDI IS TO	BE E T BRE CU CTS NDU NG LI 17	FE WO AKE WHE ICTO CON STE	D R. N NTO D D LB	NIT NE IT TOR TH , A CTO FOR	H A IS QED E NEU L OR R, IF #I T	TR/ O	A L	с
O THE F LE FOR ION REF NDATION ONS IN	OUN DIS ERE DR	DATI TRIB NCE AWIN ARF	ON LA UTION POINT G FOR INCH	YOUT PAN (DET FS.	DRA ELS >). AILS	WIN TUB	G F -UP	OR	THE	: L	A DC	TION			¢
QAF E A , DQHAB	A E	}UL DI 145 15 16 [292 149	ATI(M_A [5.7] [0.6] [16.38 [11.5] [5.9]	DN 1 3 1 1	5; 5 54 6 5;	DIN 25 93 6 [74 25	<u>4_B</u> 60. 62. 60.	0] 7] 87] 9] 0]		; ; ;	DI 31 50 152 06 93	M_C [7.13 [5.90 [6] [8.1] [7.6]]]		В
															_
RI	B	U	ΤI	OI	N		B	C))	X					Δ
D#N J!!	OHNS	SON							MC	Down		201000-	70*'		
CKD R_E APVD R_E DATE 03-	NGEL NGEL 28-0	MANN MANN 3 DF A	01 - DEE	SITE C.F	CODE CODE	G E (opt	NSE TONS	лими , Т_ ,	NS 0U	TL	=rr (INI	JENERAT		HEET DING REV OF 3 II	
ASME Y14.5M	1994		- UF E		U	U	00	1		- 4 3			1	<u>~ , H</u>	J





												1							
REL NO	LTR	NO	REVIS	ION				_					DWN	CKD	A	PVD	DATE		
152559	A		PRC	DUC	TION	_ R E I	LAS	Ł					MLI	JCB	J_B	RODY	I 5MA	¥15	
																		_	
																		Γ	
IONS	ARE	FC)R	REF	ERE	NC	ΕO	NLY	۱.										
SHOW	NI	N (] A	RE	I N	I N	СНЕ	S.										
ENSIO SET O	N I UTL	S G INE	BEN D	ERA RAW	TOF	8 FI 5).	RAM	E S	SPE	CIF	IC								D
TTOM (NUS .:	COV 25"	E R S [6	5 A 5]	R E T O	AD. E A S	JUS Se (T A B C O N	l E D U I	VE I	R T I A T T	C A L A C H	. L Y HME N	IT.						
-COND ER COI NSURE SPACI	UIT MBI TH E M	CC NA1 AT EE1	0MB 10 WI T	INA NS, RE HE	TIC RE AMF REC	ONS FEI PAC OUTI	ME R T ITY REM	ET OA , E	NE(APPI BENI SS.	CA LIC DS	ND ABL PAC	CEC E CE							
HUNT CONJI TINUO NOMIN	TRI UNC US AL	P H TIC APF VOL	HAS DN PLI TA	NO WIT ED GE.	H A VOL	NTE NUX NA	RNA ILI GE.	L C ARY IT	CON (C((C)	TAC DNT AN	TS AC OPE	 	т ми: то те	ST					_
TRIP TAGE APPL	C A N A N D I E D	OF WI	PER. LL DLT.	ATE AC AGE	A 1 C E F	- 7 - 7 - 7	0% MOM	TO ENT	00 [AR]	0% Y C	OF R								
EAKER PTING THRU	: (2 ACC) 3 E S S	3/0 SOR	-60 IES	0 k . F	cm °GA	il PA	CON RT	IDU(NUI	СТС ИВЕ	RS R (S)332	2 - 42	78					с
REAKEI PTING THRU	R: (3 ACC) 3 E S S	3/0 SOR	-60 IES	0 k . F	cm PGA	il PA	CON R T	IDU(NUI	СТС МВЕ	RS R(18 0332	2 - 42	7					
UNIT: FOR R OF THI	S WI SE E T	ITH R E Anm	H T. Beat	ANK MS	S (Th <i>i</i>	FE.	A T U A R E	R E R E	00 200	DE I R E	LI D(16))N 1	ADD HE						
IONS OX WI	AND THO	CC UT	OND CO	U I T NDU	LC I T S	DC A	TIO	NS	ARI	ΕT	ΗE	SAN	1E FO	OR					4
GROUNI MCM- 6"-16 WRENCI D TOR AWG 275	D & 6 A UN H QUE - 3 IN-	GF WG -2E S: 75 LBS	₹00 } N	NDI - L B	NG S	ELI	ECT	RO)e i	LUG	13	S ME	СНАІ	NIC/	AL .	TYPE	,		
G IS 1 600 M 6"-16 RENCH D TOR 4 AWG	MEC CM UN QUE	HAN - 2E S : 500	NIC. 3	AL N-L	t y f B s	ΡΈ,													В
9.8-1 S PRO'	.9 V D	Nn E D	n [Wl	7.2 TH	-8. BON	8 1 D I	FT- NG	LBS JUN	S] MPEI	R.									
STEM I ING 2000 J	BON CO AMP	DIN PPE S.	IG R	JUM CAB	PEF LE	r S FOI	IZE RA	D F MA	PER AXII	NE Mum	C -	FABL 4PAC	E CITY						
EAKER LABEL	LU.	GS	-	R E F	ER	ΤO	RE	COM	IMEI	NDE	D								
RE BEI BLE 3 MECH	NDI 12. ANI	NG 6 (E C A L	SP. })	ACE USI UGS	AT NG US	Б 50 БЕД	REA 0 M AS	KEF Cm te	R TI CAE ERM	E R M B L E I N A	LIN/ S	ALS (2 V	CAL(/IRE:	CUL <i>i</i> S Pe	ATE (E R)			
CONDU 16 US BIENT	C T O I NG T E	RS CC MP	PE)PP OF	RP ER 40	HAS Cae	SE (SLE:	CAL S R	C U L A T E	ATI D /	E D A T	PEF 75'	? ' C	ON A	ł					Δ
RE BEI BLE 3 MECH	NDI 12. ANI	NG 6 (A C A L	SP. () - L	ACE USI UGS	AT NG US	G [3 GED	ROU /0- AS	ND 141 Te	TEI I C7 I RM	RMI ABL INA	NAL ES	_S ((XALCI WIRI	JLA E Pe	F E D E R				
ови ју	1 <u>.</u> le	HR					<u>×</u>	ଙ୍ଗ			CIM	MINS	Pow	ER (ENE	RATION	1		
	J_BR	ODY		-] (Suman		<u>.</u>					 			-	- 0	
DATE	5MA	YI5	,			s		CODE	ΙUL	ΙL	. 1 N	IE,	CIR	CU		R K E	AK	<u>-</u> K	
FOR INTER OF DIMENS	RPRETAT SIONING ING, SE	AND E	DFF	SED ON) F F	к	PG	F		A	05	2W3	386				SHEET OF 3	Deg Rev A	
ASME YI	oN-1	394	J . L		. · L.						-	1							I



									_1		_				
EL NO 152559	LTR	NO I	PROF	ON DUCTIO	N_REI	LEASE				Dan	CKD JCB	APVD J_BRO	DY	DATE 5MAYL5	
		,													1
											•				1
															D
															F
0.4055	<u>^''</u>	117		<u></u>		E 212	15 -	٦							
BASED	ON AT	NE(40°	20 C AN	US, AR MBIENT	AND	. E 310.) ANNEX	IS AT C								
IBLE M	ETA	L C(U D N C	IT - L	FCM)									
PFR)	T			0	NDU	I T									
75	\square														
ZE	_	Q1	Y		S	IZE		-							С
KCMIL	_	4			2	4"		-							
KCMIL	1	2			3	1/2"		1							
NCMIL	+	2			3	172									
KCMIL		2			3	1/2"									
KCMIL						4 "									
KCMIL						4 "									
KCMIL						4 "									
MIL						4									
															$\left \leftarrow\right.$
															в
															-
															A
DWN M	LE	HR	,].	TUTUE		C	CUMMIN	s Pow	ER (GENERA	TION		
CKD J	_ B R R P		,			350		E 1	не	<u></u>	<u></u>			KED	1
DATE	5MA	Y15	j		s	ITE CODE		ΙL	INE	,CIR	ιU	II B	КĿА	КFК	
FOR INTER	PRETAT		FIRST USE	DEEK DEEK	Ť	PGF	DING S I ZE	۵	0520	1386			SHE 2 ~~	ET DMG REV	1
ASME YI4		994	VELJ,	VIEN		1.01	ן ט ן	n.	- J L I				1,00	" A	J

	PTC® Creo® Parametric 6	1		5				4	↓ 3		2	
												ECO
D												
								1				
				UL/I	UGS WIRE RANGE			ACCESSORY	CONTACT		CONNECTION	_
		LUG	FRAME	MAX AMPS	COPPER	DIM_A	DIM_B	DESCRIPTION	RATING	CURRENT	ТҮРЕ	
				4004 3-POLE	#2-600 KCMIL				_			=
с				400A STOLL	(NSJ/NLG) 2/0-350 KCMII	533	132			104 267	COMPRESSION TERMINALS	
-			NSJ/NLG	600A 3-POLE	(NSJ) 2/0-500 KCMII	[20.9]	[5.2]	I EA. FORM C I AUX CONTACT +	6A AT 690 VAC 2 5A AT 48 VDC 0 3A AT 250 VDC	-	TORQUE: I.I3 Nm [IO LB-IN	11
					(NLG)			I TRIP ALARM				
										20074		
		FOY						24 VDC SHUNT TRIP	-		COMPRESSION TERMINALS	
			Р	800A 3-POLE	3/0-500 KCMIL	506 [20]	[4.5]				FOR I OR 2 #18-16 AWG.	
_								4 AUX CONTACTS +	3A AT 600 VAC, 2.5A AT 480 VAC,	-	TONGOL, I.IS NILLIO LD-IN	
								I IRIP ALARM	0.8A AT 125 VDC, 0.3A AT 250 VDC			
										200VA		
						463	160	24 VDC SHUNI IKIP	-	\wedge	COMPRESSION TERMINALS	
			Р	1200A 3-POLE	3/0-500 KCMIL	[18.2]	[6.3]	L FA FORM C	6A AT 240 VAC. 6A AT 480 VAC.		FOR I OR 2 #18-16 AWG. TORQUE: 1.13 Nm [10 LB-1N	1]
		<u> </u>						4 AUX CONTACTS +	3A AT 600 VAC, 2.5A AT 48 VDC, 0.84 AT 125 VDC 0.34 AT 250 VAC	-		
в												
-												
_												
A												
										[UNLESS OTHERWISE SPECIFIED, ALL SIM TO	A040J293
										X	DIMENSIONS ARE IN MILLIMETERS DO N ± I 0.00-4.99+0.15/-0.08 DO N	IOT SCALE PRINT
											± 0.8 🛱 10.00-17.49 +0.25/-0.13 (x± 0.38 17.50-24.99 +0.30/-0.13	
										ANG T	OL: ± 1.0° SCALE: 1/32 POWER	ERTY OF CUMMINS GENERATION GROU
	6			5				4	↑ 3		2	

											1					1
	ECO-I	L NO 52559	LTR A	KO I	PRODUC	FION_I	RELEASE					MLL	CKD JCB	APVD J_BRODY	DATE I 5MAYI 5	
																L
																с
																$ \in$
																в
																•
																^
J2 Ale	93 E PRINT	ОШН N	1_LE J_BR	HR OD 1	,		Gaugusta	"		Cu	MMINS	Powe	RG	ENERATIO	N	
€	7	APVD	J_BR	ODI]	001	LI	NE,C	I R (CUI	T BR	EAKER	
ENT C'	TIAL -	FOR INTER	5MA SPRETAT) FIRST USED ON		SITE C	ODE T	DING S I ZE	٨٥	5.211/2-	9.6			SHEET DING REV	
TIO	N GROUP	TOLERANC ASME YI	ING, SE 4.5M-1	E 994	UFEJ, DFE I	ĸ	rur		D	AU.	יכ אי שי ו	00			3 OF 5 A	J
											•					





Section V

ATTACHMENT I

20% OR LESS IMPERVIOUS COVER WAIVER (NOT APPLICABLE)

ATTACHMENT J

BMPS FOR UPGRADIENT STORMWATER

BMPs FOR UPGRADIENT STORMWATER

Since there is no surface water, groundwater, or stormwater that originates upgradient from the site or that flows across the site, BMPs for Upgradient Stormwater are not needed.

ATTACHMENT K

BMPS FOR ON-SITE STORMWATER

BMP'S FOR ON-SITE STORMWATER

On-site stormwater flowing from the impervious surfaces in the proposed development will discharge into storm channels. Due to the small surface area of the project site (approximately 4,500 sqft), the site will be graded to convey storm water runoff into the adjacent open channels and add minimal runoff volume to the drainage channels. Additionally, based on the land use, pollution of storm water is not expected post construction.

ATTACHMENT L

BMPS FOR SURFACE STREAMS (NOT APPLICABLE)

ATTACHMENT M

CONSTRUCTION PLANS (NOT APPLICABLE)

ATTACHMENT N

INSPECTION, MAINTENANCE, REPAIR, AND RETROFIT PLAN (NOT APPLICABLE)

ATTACHMENT O

PILOT-SCALE FIELD TESTING PLAN (NOT APPLICABLE)

ATTACHMENT P

MEASURES FOR MINIMIZING SURFACE STREAM CONTAMINATION (NOT APPLICABLE)

APPENDIX A

SITE PLANS



TEMPORARY STORMWATER (TCEQ 0602)

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: <u>Aaron Bentley, E.I.T.</u>

Date: 9/10/2024

Signature of Customer/Agent:

Regulated Entity Name: San Antonio Water System

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

The following fuels and/or hazardous substances will be stored on the site: <u>1,700 gal</u> <u>Diesel Fuel tank</u>

These fuels and/or hazardous substances will be stored in:

Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

TCEQ-0602 (Rev. 02-11-15)

Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
 Aboveground storage tanks with a cumulative storage capacity of 500 gallons or

more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.

Fuels and hazardous substances will not be stored on the site.

- 2. Attachment A Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. Attachment B Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

5. Attachment C - Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.

For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.

For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.

6. Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: <u>Leon Creek</u>

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

7. Attachment D – Temporary Best Management Practices and Measures. TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

		 A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site. A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site. A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer. A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8.	\boxtimes	The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
		 Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature. There will be no temporary sealing of naturally-occurring sensitive features on the site.
9.		Attachment F - Structural Practices. A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10.	\square	Attachment G - Drainage Area Map. A drainage area map supporting the following requirements is attached:
		 For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided. For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used. For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area. There are no areas greater than 10 acres within a common drainage area that will be used in combination with other erosion and sediment controls within each disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed at one time.

There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.

- 11. Attachment H Temporary Sediment Pond(s) Plans and Calculations. Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
 - 🛛 N/A
- 12. Attachment I Inspection and Maintenance for BMPs. A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
- 13. All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
- 14. If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
- 15. Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
- 16. 🖂 Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices. A schedule of the interim and permanent soil stabilization practices for the site is attached.

- 18. Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 19. Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

- 20. \square All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

ATTACHMENT A

SPILL RESPONSE ACTIONS

SPILL RESPONSE ACTIONS

Upon determination that a spill of petroleum products has occurred exceeding the Final Reportable Quantity of 25 gallons, immediate action is required. These actions include abating and containing the spill by stopping the spill, minimizing impact to the public health and environment, neutralizing the effects of the incident, removing the spilled substance, and managing the wastes. The contractor shall notify the TCEQ as soon as possible but not more than 24 hours after discovery of the spill. The notification report will include the following:

- 1. The name address and telephone number of the person making the report;
- 2. The date, time and location of the spill;
- 3. A specific description of the substance that was spilled;
- 4. An estimate of the quantity of the spill;
- 5. The duration of the incident;
- 6. The source of the spill;
- 7. A description of the extent of actual or potential harmful impacts to the environment or anticipated health risks;
- 8. A description of any actions that have been taken, are being taken, or will be taken to contain and respond to the spill;
- 9. The identity of any third parties responding to the spill.

The report shall be submitted to the State Emergency Response Center at 1-800-832-8224 or to the regional office of the TCEQ if the notification report is submitted during normal business hours.

If the spill constitutes an immediate health threat, the contractor shall immediately notify and cooperate with local emergency authorities to support and implement appropriate notification and response actions. Within two weeks of the spill, the contractor will reasonably attempt to notify the owner or occupant of the property upon which the spill occurred as well as the occupants of any property that the contractor reasonably believes will be adversely affected.

Within 30 days of the spill, the contractor shall submit in writing to the TCEQ regional manager details of the spill and verification that the spill response was adequate. The submission will include one of the following:

- 1. A statement that the spill response actions have been completed and a description of how the response action was conducted. The statement must include the information contained in the notification report.
- 2. A request for an extension of time to complete the response action along with the reasons for the request. A projected work schedule outlining the time required to complete the response action is also should also be included. The executive director may grant an extension of up to six months from the sate of the spill was reported.
- 3. A statement that the spill response has not been completed and will not be completed within the maximum allowable six month extension. The statement should include why the completion of the response actions is not feasible and a projected work schedule outlining the remaining tasks necessary to complete the response actions.

ATTACHMENT B

POTENTIAL SOURCES OF CONTAMINATION

POTENTIAL SOURCES OF CONTAMINATION

Potential sources of sediment to stormwater runoff:

Surface runoff of dirt, tracking of mud, construction debris, and windblown dust will be controlled through the use of temporary erosion control practices.

Potential pollutants and sources, other than sediment, to stormwater runoff:

Temporary potential sources of contamination include:

- 1. Equipment fuel and oil
- 2. Concrete
- 3. Asphalt pavement products

ATTACHMENT C

SEQUENCE OF MAJOR ACTIVITIES

SCHEDULE OF MAJOR ACTIVITIES

ACTIVITY	AREA DISTURBED (ac)	TEMPORARY CONTROLS
Lay crushed rock aggregate	0.0155	Silt fence
Install concrete generator pad	0.00751	Silt fence
Final Grading and Restoration	0.0155	Silt fence

ATTACHMENT D

TEMPORARY BEST MANAGEMENT PRACTICES AND MEASURES

TEMPORARY BEST MANAGEMENT PRACTICES AND MEASURES

The general construction sequence will be as follows:

- 1. Schedule and conduct the preconstruction conference.
- 2. Install temporary erosion controls, pedestrian protection measures, and traffic control measures.
- 3. Clear site and complete excavation and site work for installation of waterlines, concrete pads, and asphalt driveways.
- 4. Remove existing waterlines.
- 5. Excavate fand install new valves, tie-ins, and waterlines.
- 6. Complete demolition of existing structures as needed for installation of proposed structures.
- 7. Excavate and construct concrete generator pad and asphalt driveway.
- 8. Install electrical conduits wires, and controls.
- 9. Install generator.
- 10. Complete rough grading as major structures are completed.
- 11. Complete final grading and restoration of project site.
- 12. Final dress site and remove temporary erosion controls.

As stated in 2. the temporary erosion controls will be installed before any other construction activity commences.

The temporary erosion controls are listed below. The mulch sock inlet protection and silt fence will prevent the pollution of surface water, groundwater and stormwater by not allowing the sediment from construction activities to leave the site. All sediment contained in flows that cross the site, including flow that originates upstream of the site, will be filtered by the temporary erosion controls listed. The mulch sock inlet protection filters will filter out sediment in the stormwater as it leaves the site. The measures will then be cleaned, as described on the schedule below, to ensure that they remain functioning.

BMP Description: Silt Fence							
Installation Schedule:	Prior to commencement of construction activity						
Maintenance and	Weekly and after each significant rainfall						
Inspection:							
Responsible Staff:	TBD						
ATTACHMENT E

REQUEST TO TEMPORARILY SEAL A FEATURE (NOT APPLICABLE)

ATTACHMENT F

STRUCTURAL PRACTICES

ATTACHMENT G

DRAINAGE AREA MAP

DRAINAGE AREA MAP

There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used. These other methods include:

- 1. Material Storage
- 2. Stockpipe Management
- 3. Solid Waste Management
- 4. Silt Fence
- 5. Dust Control, Water Application

ATTACHMENT H

TEMPORARY SEDIMENT POND PLANS AND CALCULATIONS (NOT APPLICABLE)

ATTACHMENT I

INSPECTION AND MAINTENANCE FOR BEST MANAGEMENT PRACTICES

Project Name:

BEST MANAGEMENT PRACTICE INSPECTION AND MAINTENANCE REPORT FORM

SILT FENCE

Name of Inspector:	Inspection Date:	
Days Since Last Rainfall:	Amount ofLast Rainfall:	inches

Where is the Silt Fence Located?	Is the Bottom of the Fabric Still Buried?	Is the Fabric Torn or Sagging?	Are the Posts Tipping Over?	How Deep is the Sediment?

MAINTENANCE REQUIRED FOR INLET PROTECTION BARRIERS:

TO BE PERFORMED BY:_____ ON OR BEFORE: _____

ATTACHMENT J

SCHEDULE OF INTERIM AND PERMANENT SOIL STABILIZATION PRACTICES

SCHEDULE OF INTERIM AND PERMANENT SOIL STABILIZATION PRACTICES

Permanent soil stabilization practices will include:

- 1. Limitations on the steepness of finished slopes.
- 2. Permanent revegetation of finished areas.

No permanent soils slopes steeper than three horizontal to one vertical will be created as a result of this project.

BMP Description: Limitations on the steepness of finished slopes.

Installation Schedule:	Per sequence of construction
Maintenance and	N/A
Inspection:	
Responsible Staff:	TBD

	in revegetation of ministed areas.
Installation Schedule:	Upon completion of grading
Maintenance and	Watering as needed for establishment and frequent inspection to ensure
Inspection:	appropriate progress until vegetation is fully established.
Responsible Staff:	TBD

BMP Description: Permanent revegetation of finished areas.

AGENT AUTHORIZATION FORM (TCEQ 0599)

Agent Authorization Form For Required Signature Edwards Aquifer Protection Program Relating to 30 TAC Chapter 213 Effective June 1, 1999	
I Dr. Saqib Shirazi, PE, PMP Print Name	
<u>Manager – Operation Support Enginee</u> Title - Owner/President/Other	ing,
of <u>San Antonio Water System</u> Corporation/Partnership/Entity Name	1
have authorized <u>Aaron Bentley, E.I.T.</u> Print Name of Agent/Engineer	
of Weston Solutions, Inc. Print Name of Firm	
to represent and act on the behalf of the above named Corporatio	n Partnershin or Entity

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

- 1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
- 2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
- 3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
- 4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
- 5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

Applicant's Signature

7-17-2024

Date

THE STATE OF <u>TEXAS</u> §

County of <u>BEXAR</u> §

GIVEN under my hand and seal of office on this 19 day of 401, 2024.

NOTARY PUBLIC

ALBESA ELIAS CALLES Notary Public, State of Texas Comm. Expires 12-17-2024 Notary ID 130651506

Alberg Elias Celles Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 12 - 17 - 2024

APPLICATION FEE FORM (TCEQ 0574)

Application Fee Form

Texas Commission on Environmental Quality			
Name of Proposed Regulated Ent	ity: <u>San Antonio Water</u>	System Forest Crest	
Regulated Entity Location: 20940	Tejas Trl W, San Antoni	io, TX 78257	
Name of Customer: San Antonio	Water System		
Contact Person: Dr. Sagib Shirazi,	P.E., PMP Phon	ne: <u>210-704-7297</u>	
Customer Reference Number (if is	ssued):CN <u>600529069</u>		
Regulated Entity Reference Numb	per (if issued):RN		
Austin Regional Office (3373)			
Hays	Travis	W	illiamson
San Antonio Regional Office (336	52)		
🔀 Bexar	Medina		valde
Comal	 Kinney		
Application fees must be paid by	check, certified check, c	or money order, payab	le to the Texas
Commission on Environmental Q	uality. Your canceled c	heck will serve as you	r receipt. This
form must be submitted with yo	ur fee payment . This p	ayment is being submi	itted to:
Austin Regional Office	ice 🛛 🖂 San Antonio Regional Office		
Mailed to: TCEQ - Cashier	to: TCEQ - Cashier Overnight Delivery to: TCEQ - Cashier		TCEQ - Cashier
Revenues Section	1	2100 Park 35 Circle	
Mail Code 214 Building A, 3rd Floor			
P.O. Box 13088	Austin, TX 78753		
Austin, TX 78711-3088 (512)239-0357			
Site Location (Check All That Apply):			
Recharge Zone	Contributing Zone	🗌 Transi	tion Zone
Type of Pla	'n	Size	Fee Due
Water Pollution Abatement Plan,	Contributing Zone		
Plan: One Single Family Residential Dwelling		Acres	\$
Water Pollution Abatement Plan,	Contributing Zone		
Plan: Multiple Single Family Residential and Parks		Acres	\$
Water Pollution Abatement Plan, Contributing Zone			
Plan: Non-residential		0.104 Acres	\$ 3,000
Sewage Collection System		L.F.	\$
Lift Stations without sewer lines		Acres	\$
Underground or Aboveground Storage Tank Facility		Tanks	\$
Piping System(s)(only)		Each	\$
Exception		Each	\$
Extension of Time		Each	\$

Signature: _____ Date: 9/10/2024

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

	Project Area in	
Project	Acres	Fee
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional,	< 1	\$3,000
multi-family residential, schools, and other sites	1 < 5	\$4,000
where regulated activities will occur)	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

Project	Cost per Linear Foot	Minimum Fee- Maximum Fee
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

Project	Cost per Tank or Piping System	Minimum Fee- Maximum Fee
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

Project	Fee
Exception Request	\$500

Extension of Time Requests

Project	Fee
Extension of Time Request	\$150

CORE DATA FORM (TCEQ 10400)



TCEQ Core Data Form

For detailed instructions on completing this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)								
,								
New Description or Authorization (Caro Data Form should be submitted with the program application)								
	onn should be submitted with	ne program application.)						
Renewal (Core Data Form should be submitted with the	Renewal (Core Data Form should be submitted with the renewal form)							
2. Customer Reference Number (if issued)	2. Customer Reference Number (if issued) 3. Regulated Entity Reference Number (if issued)							
Follow this link to search								
for CN or RN numbers in								
Central Registry**								
CN 600529069 Central Registry** RN								
	-							

SECTION II: Customer Information

4. General Cu	Customer Information 5. Effective Date for Customer Information Updates (mm/dd/yyyy)												
New Custor	New Customer Update to Customer Information Change in Regulated Entity Ownership												
Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)													
The Custome	r Name sı	ıbmitted	l here may l	be updated a	utomatical	ly base	ed on	n what is c	urrent	and active	with th	ne Texas Seci	etary of State
(SOS) or Texas Comptroller of Public Accounts (CPA).													
6. Customer Legal Name (If an individual, print last name first: eg: Doe, John) If new Customer, enter previous Customer below:						er below:							
San Antonio W	ater Systen	ı											
7. TX SOS/CP	A Filing N	umber		8. TX State	Tax ID (11 d	igits)			9. Fe	deral Tax II	D	10. DUNS	Number (if
				32046998749	9				(9 dig	(its)		applicable)	
												057582603	
11. Type of Customer: Corporation Individual Partnership: General Limited						eral 🗌 Limited							
Government:	Government: 🛛 City 🗋 County 🗋 Federal 🗋 Local 🗋 State 🗋 Other												
12. Number of	12. Number of Employees 13. Independently Owned and Operated?							erated?					
⊠ 0-20 □ 2	21-100 [101-25	50 🗌 251-	500 🗌 501	and higher				🛛 Ye	es (🗌 No		
14. Customer	Role (Pro	posed or	Actual) – as i	t relates to the	Regulated Ei	ntity list	ted or	n this form. I	Please (check one of	the follo	owing	
Owner		Ope	erator	⊠ Ow	ner & Opera	tor				Other:			
Occupation	al Licensee	🗌 Re	esponsible Pa	rty 🗌 '	/CP/BSA App	olicant							
	2800 US	Highway	281 N										
15. Mailing													
Address:	<u></u>												l
	City	San An	tonio		State	IX		ZIP	/821.	2		ZIP + 4	
16. Country M	Mailing In	formatio	on (if outside	USA)			17. E-Mail Address (if applicable)						
18. Telephone Number 19. Ex				.9. Extensio	on or C	ode		20. Fax Number (if applicable)					

(210)704-7297

SECTION III: Regulated Entity Information

21. General Regulated Entity Information (If 'New Regulated Entity" is selected, a new permit application is also required.)									
New Regulated Entity Update to Regulated Entity Name Update to Regulated Entity Information									
The Regulated Entity Name submitted may be updated, in order to meet TCEQ Core Data Standards (removal of organizational endings such as Inc, LP, or LLC).									
22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)									
San Antonio Water System Fo	orest Crest								
23. Street Address of the Regulated Entity:	20940 Tejas Trl W								
<u>(No PO Boxes)</u>	City	San Antonio	State	ТХ	ZIP	78257		ZIP + 4	
24. County	Bexar								
		If no Stree	et Address is provi	ded, fields 25	-28 are red	quired.			
25. Description to									
Physical Location:									
26. Nearest City						State		Near	rest ZIP Code
San Antonio						ТХ		7825	7
Latitude/Longitude are required and may be added/updated to meet TCEQ Core Data Standards. (Geocoding of the Physical Address may be used to supply coordinates where none have been provided or to gain accuracy).									
	nal: 29.637646 28. Longitude (W) In Decimal: 98.592080								
27. Latitude (N) In Decima	al:	29.637646		28. Loi	ngitude (W	/) In Deci	mal:	98.59208	0
27. Latitude (N) In Decima Degrees	al: Minutes	29.637646	Seconds	28. Lor Degrees	ngitude (W	/) In Deci	mal: 1inutes	98.59208	0 Seconds
27. Latitude (N) In Decima Degrees	al: Minutes	29.637646	Seconds	28. Loi Degree	ngitude (W	/) In Deci	mal: 1inutes	98.59208	0 Seconds
27. Latitude (N) In Decima Degrees 29. Primary SIC Code	al: Minutes 30.	29.637646 Secondary SIC (Seconds Code	28. Lor Degree 31. Primary	ngitude (W	/) In Deci M	mal: finutes 32. Secor	98.592080	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits)	al: Minutes 30. (4 di	29.637646 Secondary SIC (gits)	Seconds Code	28. Lor Degree: 31. Primary (5 or 6 digits)	ngitude (W	/) In Deci	mal: finutes 32. Secor (5 or 6 dig	98.592080 ndary NAIC	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits) 4941	al: Minutes 30. (4 di	29.637646 Secondary SIC (Seconds Code	28. Lor Degree: 31. Primary (5 or 6 digits) 21310	ngitude (W	/) In Deci M	mal: 1inutes 32. Secor (5 or 6 dig	98.592080	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits) 4941 33. What is the Primary B	al: Minutes 30. (4 di usiness of t	29.637646 Secondary SIC (gits) his entity? (Do	Seconds Code	28. Lon Degree: 31. Primary (5 or 6 digits) 21310 or NAICS descrip	ngitude (W	/) In Deci	mal: 1inutes 32. Secor (5 or 6 dig	98.592080	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits) 4941 33. What is the Primary B Distribution of water to neart	al: Minutes 30. (4 di usiness of t	29.637646 Secondary SIC (gits) his entity? (Da	Seconds Code	28. Lor Degrees 31. Primary (5 or 6 digits) 21310 or NAICS descrip	NAICS Coc	/) In Deci	mal: 1inutes 32. Secor (5 or 6 dig	98.59208	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits) 4941 33. What is the Primary B Distribution of water to neart	al: Minutes 30. (4 di usiness of t by property 2800 US Hi	29.637646 Secondary SIC (gits) his entity? (Da ghway 281 N	Seconds Code	28. Lor Degrees 31. Primary (5 or 6 digits) 21310 or NAICS descrip	NAICS Coo	/) In Deci	mal: finutes 32. Secor (5 or 6 dig	98.59208	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits) 4941 33. What is the Primary B Distribution of water to neart 34. Mailing Address:	al: Minutes 30. (4 di usiness of t by property 2800 US Hi	29.637646 Secondary SIC (gits) his entity? (Do	Seconds Code	28. Lor Degree: 31. Primary (5 or 6 digits) 21310 or NAICS descrip	NAICS Coo	/) In Deci	mal: finutes 32. Secor (5 or 6 dig	98.59208	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits) 4941 33. What is the Primary B Distribution of water to nearth 34. Mailing Address:	al: Minutes 30. (4 di usiness of t py property 2800 US Hi City	29.637646 Secondary SIC (gits) his entity? (Do ghway 281 N San Antonio	Seconds Code o not repeat the SIC o State	28. Lor Degree: 31. Primary (5 or 6 digits) 21310 or NAICS descrip	NAICS Coo ntion.)	/) In Deci Me	mal: finutes 32. Secor (5 or 6 dig	98.592084	0 Seconds S Code
27. Latitude (N) In Decimal Degrees 29. Primary SIC Code (4 digits) 4941 33. What is the Primary B Distribution of water to nearth 34. Mailing Address: 35. E-Mail Address:	Al: Minutes 30. (4 di usiness of t by property 2800 US Hi City	29.637646 Secondary SIC (gits) his entity? (Do ghway 281 N San Antonio	Seconds Code o not repeat the SIC o State	28. Lor Degree: 31. Primary (5 or 6 digits) 21310 or NAICS descript TX	NAICS Coo ntion.)	/) In Deci M de 78212	mal: 1inutes 32. Secor (5 or 6 dig	98.592084	0 Seconds S Code
27. Latitude (N) In Decima Degrees 29. Primary SIC Code (4 digits) 4941 33. What is the Primary B Distribution of water to nearth 34. Mailing Address: 35. E-Mail Address: 36. Telephone Number	al: Minutes 30. (4 di usiness of t by property 2800 US Hi City	29.637646 Secondary SIC (gits) his entity? (Da ghway 281 N San Antonio	Seconds Code o not repeat the SIC o State 37. Extension or	28. Lor Degrees 31. Primary (5 or 6 digits) 21310 or NAICS descript TX	NAICS Coo otion.)	/) In Deci M de 78212 x Numbe	mal: 1inutes 32. Secor (5 or 6 dig	98.592084	0 Seconds SCode

() -

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.

Dam Safety	Districts	Edwards Aquifer	Emissions Inventory Air	Industrial Hazardous Waste
Municipal Solid Waste	☐ New Source Review Air	OSSF	Petroleum Storage Tank	D PWS
Sludge	Storm Water	🔲 Title V Air	Tires	Used Oil
Voluntary Cleanup	U Wastewater	Wastewater Agriculture	Water Rights	Other:

SECTION IV: Preparer Information

40. Name:	Aaron Bentley, E.I.T.			41. Title:	Project Engineer	
42. Telephone	Number	43. Ext./Code	44. Fax Number	45. E-Mail Address		
(210) 308-4311			() -	aaron.bentle	y@westonsolutions.com	

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	San Antonio Water System	ngineer			
Name (In Print):	Dr. Saqib Shirazi, P.E., PMP	Phone: (210) 704- 7297			
Signature:				Date:	9/10/2024