

MODIFICATION OF A PREVIOUSLY APPROVED WATER POLLUTION ABATEMENT PLAN

**VINTAGE OAKS AT THE VINEYARD WWTF
OFF HWY 46 IN THE NEW BRAUNFELS ETJ, TEXAS
COMAL COUNTY, TEXAS**

Prepared For:

TEXAS WATER RESOURCES LLC

1399 Sattler Road
Canyon Lake, TX
(408) 314-9818

Prepared By:

KIMLEY-HORN AND ASSOCIATES, INC.

5301 Southwest Parkway, Building 2, Suite 100
Austin, Texas 78735
(512) 646-2237

Firm No. 928
KHA Project No. 069277520

January 2025

Revisions related to Regulated Entity ID: RN108877069;

Table of Contents

EDWARDS AQUIFER APPLICATION	Section 1
Edwards Aquifer Application Cover Page	<i>TCEQ-20705</i>
GENERAL INFORMATION	Section 2
General Information Form	<i>TCEQ-0587</i>
Road Map	Attachment A
USGS / Edwards Recharge Zone Map	Attachment B
Project Description.....	Attachment C
GEOLOGIC ASSESSMENT	Section 3
Geologic Assessment Form	<i>TCEQ-0585</i>
Geologic Assessment Table	Attachment A
Stratigraphic Column.....	Attachment B
Site Geology.....	Attachment C
Site Geologic Map(s).....	Attachment D
MODIFICATION OF A PREVIOUSLY APPROVED PLAN	Section 4
Modification of a Previously Approved Plan Form	<i>TCEQ-0590</i>
Original Approval Letter and Approved Modification Letters	Attachment A
Narrative of a Proposed Modification	Attachment B
Current Site Plan of the Approved Project.....	Attachment C
WATER POLLUTION ABATEMENT PLAN	Section 5
Water Pollution Abatement Plan Application Form	<i>TCEQ-0584</i>
Factors Affecting Surface Water Quality.....	Attachment A
Volume and Character of Storm Water.....	Attachment B
Suitability Letter from Authorized Agent	Attachment C
Site Plan	Site Plan
TEMPORARY STORMWATER	Section 6
Temporary Stormwater Form	<i>TCEQ-0602</i>
Spill Response Actions	Attachment A
Potential Sources of Contamination	Attachment B
Sequence of Major Activities.....	Attachment C
Temporary Best Management Practices and Measures	Attachment D
Erosion Control and Details.....	Erosion Control
Structural Practices	Attachment F
Drainage Area Map	Attachment G
Inspection and Maintenance for BMPs	Attachment I
Schedule of Interim and Permanent Soil Stabilization Practices	Attachment J
PERMANENT STORMWATER	Section 7
Permanent Stormwater Form	<i>TCEQ-0600</i>
BMPs for Upgradient Stormwater.....	Attachment B
BMPs for On-site Stormwater	Attachment C
Construction Plans	Attachment F
Inspection, Maintenance, Repair and Retrofit Plan.....	Attachment G
ADDITIONAL FORMS	Section 8
Agent Authorization Form	<i>TCEQ-0599</i>
Application Fee Form.....	<i>TCEQ-0574</i>
Check Payable to the “Texas Commission on Environmental Quality”	
Core Data Form	<i>TCEQ-10400</i>
EXHIBITS	Section 9
Civil Design Plan Set	Exhibit 1

SECTION 1: EDWARDS AQUIFER APPLICATION COVER PAGE

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).

Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains “possibly sensitive” features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.

2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.
3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or if not withdrawn the application will be denied and the application fee will be forfeited.
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a “Mid-Review Modification”. Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available to you:

- You can withdraw your application, and your fees will be refunded or credited for a resubmittal.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the effected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ’s Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ’s San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: Vintage Oaks at the Vineyard WWTF					2. Regulated Entity No.: RN108877069				
3. Customer Name: Texas Water Resources LLC					4. Customer No.: 602969396				
5. Project Type: (Please circle/check one)	New	<u>Modification</u>			Extension		Exception		
6. Plan Type: (Please circle/check one)	<u>WPAP</u>	CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Residential	<u>Non-residential</u>				8. Site (acres):		1.21	
9. Application Fee:	\$4,000	10. Permanent BMP(s):				50' Natural Vegetative Filter Strip			
11. SCS (Linear Ft.):	N/A	12. AST/UST (No. Tanks):				N/A			
13. County:	Comal	14. Watershed:				Comal River-Guadalupe River- West Fork Drv Comal Creek-Comal Creek			

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the “Texas Groundwater Conservation Districts within the EAPP Boundaries” map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region			
County:	Hays	Travis	Williamson
Original (1 req.)	—	—	—
Region (1 req.)	—	—	—
County(ies)	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Barton Springs/ Edwards Aquifer <input type="checkbox"/> Hays Trinity <input type="checkbox"/> Plum Creek	<input type="checkbox"/> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<input type="checkbox"/> Austin <input type="checkbox"/> Buda <input type="checkbox"/> Dripping Springs <input type="checkbox"/> Kyle <input type="checkbox"/> Mountain City <input type="checkbox"/> San Marcos <input type="checkbox"/> Wimberley <input type="checkbox"/> Woodcreek	<input type="checkbox"/> Austin <input type="checkbox"/> Bee Cave <input type="checkbox"/> Pflugerville <input type="checkbox"/> Rollingwood <input type="checkbox"/> Round Rock <input type="checkbox"/> Sunset Valley <input type="checkbox"/> West Lake Hills	<input type="checkbox"/> Austin <input type="checkbox"/> Cedar Park <input type="checkbox"/> Florence <input type="checkbox"/> Georgetown <input type="checkbox"/> Jerrell <input type="checkbox"/> Leander <input type="checkbox"/> Liberty Hill <input type="checkbox"/> Pflugerville <input type="checkbox"/> Round Rock

San Antonio Region					
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	—	<input checked="" type="checkbox"/> X	—	—	—
Region (1 req.)	—	<input checked="" type="checkbox"/> X	—	—	—
County(ies)	—	<input checked="" type="checkbox"/> X	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Trinity-Glen Rose	<input checked="" type="checkbox"/> X Edwards Aquifer Authority	<input type="checkbox"/> Kinney	<input type="checkbox"/> EAA Medina	<input type="checkbox"/> EAA Uvalde
City(ies) Jurisdiction	<input type="checkbox"/> Castle Hills <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Helotes <input type="checkbox"/> Hill Country Village <input type="checkbox"/> Hollywood Park <input type="checkbox"/> San Antonio (SAWS) <input type="checkbox"/> Shavano Park	<input type="checkbox"/> Bulverde <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Garden Ridge <input checked="" type="checkbox"/> X New Braunfels <input type="checkbox"/> Schertz	NA	<input type="checkbox"/> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

Deirdre Lynch, P.E.

Print Name of Customer/Authorized Agent

Deirdre Lynch

01/27/2025

Signature of Customer/Authorized Agent

Date

****FOR TCEQ INTERNAL USE ONLY****

Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

SECTION 2: GENERAL INFORMATION

General Information Form

Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **General Information Form** is hereby submitted for TCEQ review. The application was prepared by:

Print Name of Customer/Agent: Deirdre Lynch, P.E.

Date: January 2025

Signature of Customer/Agent:



Project Information

1. Regulated Entity Name: Vintage Oaks at the Vineyard WWTF
2. County: Comal
3. Stream Basin: Comal River-Guadalupe River- West Fork Dry Comal Creek-Comal Creek
4. Groundwater Conservation District (If applicable): Edwards Aquifer Recharge Zone
5. Edwards Aquifer Zone:
☒ Recharge Zone
☐ Transition Zone
6. Plan Type:

<input type="checkbox"/> WPAP	<input type="checkbox"/> AST
<input type="checkbox"/> SCS	<input type="checkbox"/> UST
<input checked="" type="checkbox"/> Modification	<input type="checkbox"/> Exception Request

7. Customer (Applicant):

Contact Person: Aundrea Williams
Entity: Texas Water Resources LLC
Mailing Address: 1399 Sattler Road
City, State: Canyon Lake, TX Zip: 78132
Telephone: (408) 314-9818 Fax: N/A
Email Address: Aundrea.Williams@txwaterco.com

8. Agent/Representative (If any):

Contact Person: Deirdre Lynch, P.E.
Entity: Kimley-Horn
Mailing Address: 5301 Southwest Parkway, Building 2, Suite 100
City, State: Austin, Texas Zip: 78735
Telephone: 512-596-5918 Fax: N/A
Email Address: deirdre.lynch@kimley-horn.com

9. Project Location:

- ☐ The project site is located inside the city limits of New Braunfels.
☒ The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of New Braunfels.
☐ The project site is not located within any city's limits or ETJ.

10. ☒ The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

This project is located in the Vintage Oaks at the Vineyard subdivision "The Hills" off HWY 46.

11. ☒ **Attachment A – Road Map.** A road map showing directions to and the location of the project site is attached. The project location and site boundaries are clearly shown on the map.
12. ☒ **Attachment B - USGS / Edwards Recharge Zone Map.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached. The map(s) clearly show:
- ☒ Project site boundaries.
 - ☒ USGS Quadrangle Name(s).
 - ☒ Boundaries of the Recharge Zone (and Transition Zone, if applicable).
 - ☒ Drainage path from the project site to the boundary of the Recharge Zone.
13. ☒ **The TCEQ must be able to inspect the project site or the application will be returned.** Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment.

☐ Survey staking will be completed by this date: _____

14. ☒ **Attachment C – Project Description.** Attached at the end of this form is a detailed narrative description of the proposed project. The project description is consistent throughout the application and contains, at a minimum, the following details:

- ☒ Area of the site
- ☒ Offsite areas
- ☒ Impervious cover
- ☒ Permanent BMP(s)
- ☒ Proposed site use
- ☒ Site history
- ☒ Previous development
- ☒ Area(s) to be demolished

15. Existing project site conditions are noted below:

- ☐ Existing commercial site
- ☐ Existing industrial site
- ☐ Existing residential site
- ☒ Existing paved and/or unpaved roads
- ☐ Undeveloped (Cleared)
- ☐ Undeveloped (Undisturbed/Uncleared)
- ☒ Other: WWTF

Prohibited Activities

16. ☒ I am aware that the following activities are prohibited on the Recharge Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
- (2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
- (3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
- (4) The use of sewage holding tanks as parts of organized collection systems; and
- (5) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
- (6) New municipal and industrial wastewater discharges into or adjacent to water in the state that would create additional pollutant loading.

17. ☒ I am aware that the following activities are prohibited on the Transition Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);

- (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
- (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

Administrative Information

18. The fee for the plan(s) is based on:

- ☒ For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur.
- ☐ For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines.
- ☐ For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems.
- ☐ A request for an exception to any substantive portion of the regulations related to the protection of water quality.
- ☐ A request for an extension to a previously approved plan.

19. ☒ Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

- ☐ TCEQ cashier
- ☐ Austin Regional Office (for projects in Hays, Travis, and Williamson Counties)
- ☒ San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

20. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

21. ☒ No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.


Attachment A

Road Map



DIRECTIONS FROM TCEQ HEADQUARTERS TO PROJECT SITE

1. GET ON I-35 S. FOLLOW I-35 S TO I-35 FRONTAGE RD IN NEW BRAUNFELS.
2. TAKE EXIT 184 FROM I-35 S AND FOLLOW LOOP 337 AND STATE HWY 46.
3. TURN LEFT ON BORDEAUX LANE.



ROAD MAP

NEW BRAUNFELS, TEXAS 78132

Kimley»Horn

© 2023 KIMLEY-HORN AND ASSOCIATES, INC.
5301 SOUTHWEST PARKWAY BUILDING 2, SUITE 100
AUSTIN, TEXAS 78735
PHONE: 512-646-2237
TEXAS REGISTERED ENGINEERING FIRM F-928


Attachment B
USGS/Edwards Recharge Zone Map



U.S. DEPARTMENT OF THE INTERIOR
U.S. GEOLOGICAL SURVEY



7.5-MINUTE TOPO QUADRANGLE
Custom Extent
7.5-MINUTE TOPO





Produced by the United States Geological Survey

North American Datum of 1983 (NAD83)
World Geodetic System of 1984 (WGS84) Projection and
1:50,000-meter ellipsoidal datum (NAD83) used for
Data is provided by The National Map (1984) is the best available at the time of map
generation, and includes data current from reporting times of elevation,
Hydrography, Geographic Names, Boundaries, Transportation, Structures, Land Cover,
and Other Features. Refer to associated Federal Geographic Data Committee (FGDC)
Metadata for additional information and data collection methods.

This map is not a legal document. Boundaries may be generalized for this map scale.
Private lands within government reservations may not be shown. Obtain permission
before entering private lands. Temporal changes may have occurred since these data
were collected and some data may no longer represent actual surface conditions.

Learn More The National Map: <https://nationalmap.gov>



7.5-MINUTE TOPO, TX
2024

TCEQ MAP

NEW BRAUNFELS, TEXAS 78132

Kimley»Horn

© 2023 KIMLEY-HORN AND ASSOCIATES, INC.
5301 SOUTHWEST PARKWAY BUILDING 2, SUITE 100
AUSTIN, TEXAS 78735
PHONE: 512-646-2237
TEXAS REGISTERED ENGINEERING FIRM F-928

PLOTTED BY COUTTIS, ETHAN 1/7/2025 2:43 PM
DWG NAME K:\SAU_W\069277520_CLWSC - GROVE EQ TANK\DOCS\PERMITS\WPAP\ATTACHMENTS\ROAD MAP\ROAD MAP.DWG
LAST SAVED 12/20/2024 11:31 AM

Attachment C

Project Description

Project Description

This project proposes a modification to an approved Water Pollution Abatement Plan (WPAP) and includes the addition of a 12' diameter reinforced fiber glass equalization tank. The EQ tank will be placed on a concrete pad that extends slightly beyond the tank's footprint. The 1.21 acre project site is located in "The Hills" section of the Vintage Oaks at the Vineyard subdivision in New Braunfels, Texas, within the Dry Comal Creek watershed. The site is in the Extraterritorial Jurisdiction (ETJ) of New Braunfels and lies within the Edwards Aquifer Recharge Zone, as shown by TCEQ Edwards Aquifer Map.

A WPAP modification (#13000745) was subsequently approved on November 27, 2018, to adjust the amount of green space, project area, and impervious cover. The approved WPAP Modification (13000745) encompassed 41.12 acres and includes 1.12 acres of impervious cover, resulting in an overall WPAP coverage of 2.72%. To prevent the pollution of stormwater runoff originating onsite, an engineered vegetative filter strip and a natural vegetated filter strip (VFS) were incorporated to treat stormwater runoff in compliance with the TCEQ technical guidance document. The required total suspended solids (TSS) treatment for the modification was 1,005 pounds of TSS generated from the 1.12 acres of impervious cover. These approved measures met the required 80 percent removal of the increased load in TSS caused by the project.

The limits of construction for the proposed project will span one (1) lot comprised of 1.21 acres. The project proposes the addition of a reinforced fiber glass tank which will increase the impervious cover by 200 square feet (0.005 acres), making the total impervious cover for the WPAP site 1.125 acres (2.74% of the total WPAP area). We are modifying the existing vegetative filter strip as the proposed EQ tank location coincides with where the existing 50' natural VFS lies. The proposed modified vegetative filter strip is designed to meet the required 80 percent removal of the increased load in TSS caused by the proposed project. The proposed project will not generate any wastewater.

SECTION 3: GEOLOGIC ASSESSMENT

Attachment A
Geologic Assessment Table

Geologic Assessment

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: John Langan

Telephone: 210/342-9377

Date: 11/13/15


Fax: 210/342-9401

Representing: PSI TBPG No. 50128 (Name of Company and TBPG or TBPE registration number)

Signature of Geologist:



Regulated Entity Name: Vintage Oaks at thbe Vineyard - The Hills



Project Information

1. Date(s) Geologic Assessment was performed: 10-11/15

2. Type of Project:

☒ WPAP

☐ AST

☐ SCS

☐ UST

3. Location of Project:

☒ Recharge Zone

☐ Transition Zone

☐ Contributing Zone within the Transition Zone

4. ☒ **Attachment A - Geologic Assessment Table.** Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
5. ☐ Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Table 1 - Soil Units, Infiltration Characteristics and Thickness

Soil Name	Group*	Thickness(feet)
Anhalt clay, 1-3% Slopes	B	2
Rumple-Comfort Asso., undulating	B	2

Soil Name	Group*	Thickness(feet)

*** Soil Group Definitions (Abbreviated)**

- A. Soils having a high infiltration rate when thoroughly wetted.
- B. Soils having a moderate infiltration rate when thoroughly wetted.
- C. Soils having a slow infiltration rate when thoroughly wetted.
- D. Soils having a very slow infiltration rate when thoroughly wetted.

6. ☒ **Attachment B – Stratigraphic Column.** A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.
7. ☒ **Attachment C – Site Geology.** A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
8. ☒ **Attachment D – Site Geologic Map(s).** The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1" = 400'
- Applicant's Site Plan Scale: 1" = 400'
- Site Geologic Map Scale: 1" = 400'
- Site Soils Map Scale (if more than 1 soil type): 1" = 400'
9. Method of collecting positional data:
- ☒ Global Positioning System (GPS) technology.
- ☐ Other method(s). Please describe method of data collection: _____
10. ☒ The project site and boundaries are clearly shown and labeled on the Site Geologic Map.

11. ☒ Surface geologic units are shown and labeled on the Site Geologic Map.
12. ☒ Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
- ☐ Geologic or manmade features were not discovered on the project site during the field investigation.
13. ☐ The Recharge Zone boundary is shown and labeled, if appropriate.
14. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section.
- ☒ There are 5 (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)
- ☐ The wells are not in use and have been properly abandoned.
- ☒ The wells are not in use and will be properly abandoned.
- ☒ The wells are in use and comply with 16 TAC Chapter 76. Note: 4 wells will be abandoned
1 will remain in use (Feature 5.7)
- ☐ There are no wells or test holes of any kind known to exist on the project site.

Administrative Information

15. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

Attachment B

Stratigraphic Column

STRATIGRAPHIC COLUMN

Vintage Oaks at The Vineyard The Hills Tract
Highway 46
Comal County, Texas

FORMATION	THICKNESS	LITHOLOGIC DESCRIPTION
Georgetown Formation	2-20'	Light tan limestone identified by proximity to Del Rio clay and diagnostic marker fossil: <i>waconella wacoensis</i> brachiopod; low porosity and permeability development.
Person Formation	180-224'	Limestones and dolomites, extensive porosity development in "honeycomb" sections, interbedded with massive recrystallized limestones with more limited permeabilities (especially Regional Dense Member separating the Person and Kainer Formations).
Kainer Formation	260-310'	Hard, miliolid limestones, overlying calcified dolomites and dolomite. Leached evaporitic "Kirschberg" zone of very porous and permeable collapse breccia formed by the dissolution of gypsum. Overlies the basal nodular (Walnut) bed.
Glen Rose Limestone (upper)	350-500	Yellowish-tan thinly bedded limestone and marl. Alternating beds of varying hardness erodes to "stairstep" topography. Marine fossils common.

Attachment C

Site Geology

Narrative Description of Geology

SOILS NARRATIVE

According to the Soil Survey of Comal County, published by the United States Department of Agriculture, Soil Conservation Service, in cooperation with the Texas Agricultural Extension Service, reissued in 1984, the soils beneath the subject property have been classified as Comfort-Rock outcrop complex, undulating (CrD), Rumple-Comfort association, undulating (RUD), Anhalt clay, 1 to 3% slopes (AnB), Eckrant-Rock outcrop complex, steep (ErG) and Brackett-Rock outcrop Real complex, steep (BtG)

Comfort extremely stony clay makes up between 49 and 95% of the Comfort-Rock outcrop series, and indurated rock outcrop and soil less than 4 inches deep make up 5 to 36% of the complex. Typically, the surface layer is dark brown extremely stony soil about 6 inches thick. Cobbles, stones and "float" rock comprise about 45% of the surface. The subsoil extends to about 13 inches, and overlies the fractured limestone parent material. Comfort soil is well-drained, with slow to medium surface runoff, slow permeability, and very low water capacity.

Rumple-Comfort association soils are shallow to moderately deep soils on uplands in the Edwards Plateau. The surface layer is a dark reddish brown cherty clay loam about 10 inches thick, and overlies a subsoil of reddish brown cherty clay with abundant limestone fragments to a depth of 28 inches. The underlying parent material is an indurated limestone. The soil is well drained, with medium surface runoff, moderately slow permeability, and very low available water capacity. The soil is not suited for cropland, or cultivation, but is used as range land and habitat for wildlife.

Eckrant-Rock outcrop complex, steep is similar in profile, but are found on long, narrow slopes on high hills and ridges and along escarpments. The surface layer of Eckrant soil is very dark gray extremely stony clay about 10 inches thick. The lower portion of the surface layer is up to 75% stones and cobbles, and overlies the fractured limestone parent material.

Anhalt clays are well-drained clays that form as residuum on weathered limestones. The depth to the parent material is between 20 and 40 inches. It has low to moderately low permeability, and low water capacity, and well suited for agriculture.

Brackett-Rock outcrop series consist of shallow, loamy soils and rock outcrop on uplands in the Edwards Plateau land resource area. The surface layer is grayish brown gravelly clay loam that is between 6 and 14 inches thick. The underlying parent material is a weakly cemented limestone interbedded with a thin strata of pale yellow or pale brown shaly clay. These soils are well-drained with rapid surface runoff, moderately slow permeability, and very low available water capacity. The soils are used as rangelands or habitat for wildlife, and are not suited for pasture or crops.

SITE GEOLOGIC NARRATIVE

Physiography

Comal County lies within two physiographic provinces, the Edwards Plateau and the Blackland Prairie. Most of Comal County lies within the Edwards Plateau, which is characterized by rugged and hilly terrain, with elevations in excess of 1,400' feet above sea level in the northwestern portion of the county. This area is underlain by beds of limestone that dip gently to the southeast. South of the Edwards Plateau is the Balcones Fault Zone, which is also the northernmost limit of the Blackland Prairie. The Balcones Fault Zone extends northeast-southwest across Comal County and is composed of fault blocks of limestone, chalk, shale and marl. The undulating, hilly topography of the Blackland Prairie ranges in elevation from about 650 feet to 1100 feet above sea level. The regional dip of the lower Cretaceous rocks in Comal County is approximately 15 feet per mile towards the southeast. The faults are predominantly normal, down-to-the southeast with near vertical throws. Elevations at the Vintage Oaks at the Vineyard The Hills Tract site range from approximately 1,170 feet above mean sea level in the east area of the tract to approximately 1,000 feet above mean sea level in the northeastern "arm" area of the tract.

Stratigraphy and Structure

Rocks at the site are members of the Lower Cretaceous Edwards Kainer Formation. The site is covered with a thin veneer of soil, and scattered expanses of dense to vuggy and fractured rock outcrops which are exposed throughout the site. In general, the hillsides contained variable amounts of boulder float and soil with outcrops exhibiting varying degrees of fractures and vug development. According to "The Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Outcrop, Comal County Texas" written by the USGS, the Kainer Formation ranges between 260 and 310 feet thick and forms the lower member of the Edwards Group, beneath the Person Formation which compromises the Edwards Aquifer, a federally-designated sole source aquifer for the region. The underlying Glen Rose Formation is composed of yellowish-tan, thinly bedded marly limestone.

The rocks at the site are mapped as the Dolomitic member of the Kainer Formation, which is a mudstone to grainstone, cherty, massively bedded, crystalline limestone. The rock weathers to a light gray in outcrop, and has abundant *Toucasia* bivalves. The underlying Basal nodular member of the Kainer Formation was also observed on the tract, and consists of shaly, nodular limestone and burrowed mudstone to wackestone, with gastropods, miliolids and *exogyra texana* bivalves. It is considered regionally as a lower confining unit, but locally water bearing through dissolution along bedding planes.

Four sensitive features scoring more than 40 points on the F-0585 form was observed on the subject tract and consisted of vuggy fractured rock zones in the Little Bear Creek streambed in the northeastern extension "arm". One of the features, S-10 is a large outcrop that has been partially cleared for site development activities associated with a nearby flood control spillway. The other feature, S-11 is heavily fractured, and shows the contact between the Kainer dolomitic member and the underlying basal nodular member. The other two are



small caves on the east side of the tract (S-24 and S-25). The results of the site investigation are included in the attached TCEQ report format.


SUMMARY

Four sensitive features were noted on The Hills tract. Two are in the northeast flowing Little Bear Creek drainage way in the northeastern "arm" of the site. These features are in alignment with a mapped fault that traverses the northeast "arm" of the subject tract, and receive directed water flow during precipitation events. Two small caves are located at fairly high elevations on the east side of the tract. Other, non-sensitive, predominantly man-made features were also identified, and included water wells, stock tanks, flood control spill ways and a septic tank. Please note that subtle features, buried or obscured from view, may be present on the tract. It is possible that clearing/construction activities will reveal the presence of features currently hidden by thick vegetation and/or soil cover. If caves, sinkholes, or solution cavities are encountered during future clearing/construction activities, please contact our office for additional assistance.



Attachment D
Site Geologic Map(s)

Site Geologic Map and Geologic Assessment Tables




THE HILLS— PROPOSED SITE PLAN



U.S. DEPARTMENT OF THE INTERIOR
U. S. GEOLOGICAL SURVEY





BAT CAVE QUADRANGLE
TEXAS
7.5-MINUTE SERIES



Produced by the United States Geological Survey
North American Datum of 1983 (NAD83)
World Geodetic System of 1984 (WGS84), Projection and
1 000-meter grid; Universal Transverse Mercator, Zone 14E
10 000-foot ticks: Texas Coordinate System of 1983 (south
central zone)

Imagery.....NAIP, May 2010
Roads.....©2006-2012 TomTom
Names.....GNS, 2012
Hydrography.....National Hydrography Dataset, 2010
Contours.....National Elevation Dataset, 2004
Boundaries.....Census, BWC, BIC, 1952, 1972 - 2012




CONTOUR INTERVAL 10 FEET
NORTH AMERICAN VERTICAL DATUM OF 1988
This map was produced to conform with the
National Geospatial Program US Topo Product Standard, 2011.
A metadata file associated with this product is draft version 0.6.7



QUADRANGLE LOCATION		
Anaheim	Swanton Valley	Settler
Bulverde	Bat Cave	New Braunfels West
Lughran	Schertz	Marion

ADJOINING 7.5 QUADRANGLES




BAT CAVE, TX
2013



U.S. DEPARTMENT OF THE INTERIOR
U. S. GEOLOGICAL SURVEY





NEW BRAUNFELS WEST QUADRANGLE
TEXAS
7.5-MINUTE SERIES




Produced by the United States Geological Survey
North American Datum of 1983 (NAD83)
World Geodetic System of 1984 (WGS84) Projection and
1 000-meter grid: Universal Transverse Mercator, Zone 14R
10 000-foot ticks: Texas Coordinate System of 1983 (south
central zone)

Imagery.....NAIP, May 2010
Roads.....©2006-2012 TomTom
Names.....GNIS, 2012
Hydrography.....National Hydrography Dataset, 2010
Contours.....National Elevation Dataset, 2010
Boundaries.....Census, BWC, ISC, USGS, 1972 - 2012



CONTOUR INTERVAL 10 FEET
NORTH AMERICAN VERTICAL DATUM OF 1988
This map was produced to conform with the
National Geospatial Program US Topo Product Standard, 2011.
A metadata file associated with this product is draft version 0.6.7



QUADRANGLE LOCATION		
Brewster	Santer	Hunter
Brewster	New Braunfels West	New Braunfels East
Brewster	Marion	McGregory

ROAD CLASSIFICATION
Interstate Route
State Route
US Route
Local Road
Ramp
Interstate Route
US Route
State Route


NEW BRAUNFELS WEST, TX
2013



U.S. DEPARTMENT OF THE INTERIOR
U. S. GEOLOGICAL SURVEY





SMITHSON VALLEY QUADRANGLE
TEXAS-COMAL CO.
7.5-MINUTE SERIES



Produced by the United States Geological Survey
North American Datum of 1983 (NAD83)
World Geodetic System of 1984 (WGS84)
1 000-meter grid: Universal Transverse Mercator, Zone 14R
10 000-foot ticks: Texas Coordinate System of 1983 (south central zone)


Imagery.....NAIP, May 2010
Roads.....C2006-2012 TomTom
Names.....GNS, 2012
Hydrography.....National Hydrography Dataset, 2010
Contours.....National Elevation Dataset, 2003
Boundaries.....Census, IRWC, IBC, USGS, 1972 - 2012



CONTOUR INTERVAL 20 FEET
NORTH AMERICAN VERTICAL DATUM OF 1988
This map was produced to conform with the
National Geospatial Program US Topo Product Standard, 2011.
A metadata file associated with this product is draft version 0.6.7



ADJOINING 7.5 QUADRANGLES		
Spring Branch	Fletcher	Devils Backbone
Anaoli	Smithson Valley	Satler
Belverde	But Cave	New Burnsville West



SMITHSON VALLEY, TX
2013



U.S. DEPARTMENT OF THE INTERIOR
U. S. GEOLOGICAL SURVEY





SATTLER QUADRANGLE
TEXAS-COMAL CO.
7.5-MINUTE SERIES





Produced by the United States Geological Survey
North American Datum of 1983 (NAD83)
World Geodetic System of 1984 (WGS84). Projection and
1 000-meter grid: Universal Transverse Mercator, Zone 14E
10 000-foot ticks: Texas Coordinate System of 1983 (south
central zone)

Imagery.....NAP, May 2010
Roads.....©2006-2012 TomTom
Names.....©2012
Hydrography.....National Hydrography Dataset, 2010
Contours.....National Elevation Dataset, 2003
Boundaries.....Census, BWC, ISC, USGS, 1972-2012



CONTOUR INTERVAL 20 FEET
NORTH AMERICAN VERTICAL DATUM OF 1988
This map was produced to conform with the
National Geospatial Program US Topo Product Standard, 2011.
A metadata file associated with this product is draft version 0.6.7



SATTLER, TX
2013

SECTION 4: MODIFICATION OF A PREVIOUSLY APPROVED PLAN

Modification of a Previously Approved Plan

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Transition Zone and Relating to 30 TAC 213.4(j), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This request for a **Modification of a Previously Approved Plan** is hereby submitted for TCEQ review and executive director approval. The request was prepared by:

Print Name of Customer/Agent: Deirdre Lynch, P.E.

Date: January, 2025

Signature of Customer/Agent:



Project Information

1. Current Regulated Entity Name: Vintage Oaks at the Vineyard WWTF
Original Regulated Entity Name: Vintage Oaks at the Vineyard WWTF
Regulated Entity Number(s) (RN): RN108877069
Edwards Aquifer Protection Program ID Number(s): 13000745
☒ The applicant has not changed and the Customer Number (CN) is: 602969396
☐ The applicant or Regulated Entity has changed. A new Core Data Form has been provided.
2. ☒ **Attachment A: Original Approval Letter and Approved Modification Letters.** A copy of the original approval letter and copies of any modification approval letters are attached.

3. A modification of a previously approved plan is requested for (check all that apply):
- ☒ Physical or operational modification of any water pollution abatement structure(s) including but not limited to ponds, dams, berms, sewage treatment plants, and diversionary structures;
 - ☐ Change in the nature or character of the regulated activity from that which was originally approved or a change which would significantly impact the ability of the plan to prevent pollution of the Edwards Aquifer;
 - ☐ Development of land previously identified as undeveloped in the original water pollution abatement plan;
 - ☐ Physical modification of the approved organized sewage collection system;
 - ☐ Physical modification of the approved underground storage tank system;
 - ☐ Physical modification of the approved aboveground storage tank system.
4. ☒ Summary of Proposed Modifications (select plan type being modified). If the approved plan has been modified more than once, copy the appropriate table below, as necessary, and complete the information for each additional modification.

<i>WPAP Modification</i>	<i>Approved Project</i>	<i>Proposed Modification</i>
<i>Summary</i>		
Acres	<u>41.12</u>	<u>N/A</u>
Type of Development	<u>WWTF with Irrigation Spray Fields</u>	<u>N/A</u>
Number of Residential Lots	<u>0</u>	<u>N/A</u>
Impervious Cover (acres)	<u>1.120</u>	<u>1.125</u>
Impervious Cover (%)	<u>2.72%</u>	<u>2.74%</u>
Permanent BMPs	<u>50' Natural VFS, 15' Engineered VFS</u>	<u>Adjusting the Existing 50' Natural Vegetative Filter Strip</u>
Other	<u>N/A</u>	<u>N/A</u>
<i>SCS Modification</i>	<i>Approved Project</i>	<i>Proposed Modification</i>
<i>Summary</i>		
Linear Feet	<u>N/A</u>	<u>N/A</u>
Pipe Diameter	<u>N/A</u>	<u>N/A</u>
Other	<u>N/A</u>	<u>N/A</u>

<i>AST Modification</i>	<i>Approved Project</i>	<i>Proposed Modification</i>
<i>Summary</i>		
Number of ASTs	<u>N/A</u>	<u>N/A</u>
Volume of ASTs	<u>N/A</u>	<u>N/A</u>
Other	<u>N/A</u>	<u>N/A</u>

<i>UST Modification</i>	<i>Approved Project</i>	<i>Proposed Modification</i>
<i>Summary</i>		
Number of USTs	<u>N/A</u>	<u>N/A</u>
Volume of USTs	<u>N/A</u>	<u>N/A</u>
Other	<u>N/A</u>	<u>N/A</u>

5. ☒ **Attachment B: Narrative of Proposed Modification.** A detailed narrative description of the nature of the proposed modification is attached. It discusses what was approved, including any previous modifications, and how this proposed modification will change the approved plan.

6. ☒ **Attachment C: Current Site Plan of the Approved Project.** A current site plan showing the existing site development (i.e., current site layout) at the time this application for modification is attached. A site plan detailing the changes proposed in the submitted modification is required elsewhere.
 - ☒ The approved construction has not commenced. The original approval letter and any subsequent modification approval letters are included as Attachment A to document that the approval has not expired.
 - ☐ The approved construction has commenced and has been completed. Attachment C illustrates that the site was constructed as approved.
 - ☐ The approved construction has commenced and has been completed. Attachment C illustrates that the site was **not** constructed as approved.
 - ☐ The approved construction has commenced and has **not** been completed. Attachment C illustrates that, thus far, the site was constructed as approved.
 - ☐ The approved construction has commenced and has **not** been completed. Attachment C illustrates that, thus far, the site was **not** constructed as approved.

7. ☐ The acreage of the approved plan has increased. A Geologic Assessment has been provided for the new acreage.
- ☒ Acreage has not been added to or removed from the approved plan.

8. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

Attachment A
***Original Approval Letter and Approved
Modification Letters***

Jon Niermann, *Chairman*
Emily Lindley, *Commissioner*
Toby Baker, *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

November 27, 2018

Mr. Thad Rutherford
Southstar at Vintage Oaks, LLC
1114 Lost Creek Blvd. Suite 270
Austin, Texas 78746

Re: Edwards Aquifer, Comal County

Name of Project: Vintage Oaks at the Vineyard WWTF; located in the Vintage Oaks at the Vineyard subdivision "The Hills" off Hwy 46 in the New Braunfels ETJ, Texas

PLAN TYPE: Request for the Modification of an approved Water Pollution Abatement Plan (WPAP); 30 Texas Administrative Code (TAC) Chapter 213; Edwards Aquifer Protection Program

Regulated Entity ID: RN108877069; Additional ID No.: 13000745

Dear Mr. Rutherford:

The Texas Commission on Environmental Quality (TCEQ) has completed its review of the WPAP Modification application for the above-referenced project submitted to the San Antonio Regional Office by M&S Engineering, LLC on behalf of Southstar at Vintage Oaks, LLC on August 3, 2018. Final review of the WPAP was completed after additional material was received on November 1, 2018 and November 26, 2018. As presented to the TCEQ, the Temporary and Permanent Best Management Practices (BMPs) were selected and construction plans were prepared by a Texas Licensed Professional Engineer to be in general compliance with the requirements of 30 TAC Chapter 213. These planning materials were sealed, signed and dated by a Texas Licensed Professional Engineer. Therefore, based on the engineer's concurrence of compliance, the planning materials for construction of the proposed project and pollution abatement measures are hereby approved subject to applicable state rules and the conditions in this letter. The applicant or a person affected may file with the chief clerk a motion for reconsideration of the executive director's final action on this Edwards Aquifer Protection Plan. A motion for reconsideration must be filed no later than 23 days after the date of this approval letter. *This approval expires two (2) years from the date of this letter unless, prior to the expiration date, more than 10 percent of the construction has commenced on the project or an extension of time has been requested.*

BACKGROUND

Vintage Oaks at the Vineyard, WWTF (13000029) was approved January 26, 2016 as a commercial project of approximately 51.03 acres. It was to include the construction of a wastewater treatment facility (WWTF) accompanied with irrigation spray fields. The impervious cover was to be 0.22 acres (0.43 percent). The approved permanent BMP was a natural vegetative filter strip.

PROJECT DESCRIPTION

The proposed modification includes the relocation of the irrigation area and the addition of an access roadway for the WWTF. The project area has decreased to 41.12 acres and has 1.12 acres of impervious cover (2.72-percent). No wastewater is generated by this project

PERMANENT POLLUTION ABATEMENT MEASURES

To prevent the pollution of stormwater runoff originating on-site or upgradient of the site and potentially flowing across and off the site after construction, an engineered vegetative filter strip and a natural vegetated filter strip (VFS), designed using the TCEQ technical guidance document, Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices (2005), will be constructed to treat stormwater runoff. The required total suspended solids (TSS) treatment for this project is 1,005 pounds of TSS generated from the 1.12 acres of impervious cover. The approved measures meet the required 80 percent removal of the increased load in TSS caused by the project.

The engineered VFS shall have a uniform slope of less than 20-percent and vegetated cover of at least 80-percent which will extend along the entire length of the contributing area and will be free of gullies or rills that can concentrate overland flow. The contributing area shall be relatively flat to evenly distribute runoff, and the impervious cover in the direction of flow shall not exceed 72-feet. The proposed VFS is treating the access roadway.

The natural VFS will be 50 feet wide, a uniform grade not to exceed 10 percent, and will be free of gullies or rills that can concentrate overland flow. The natural VFS will surround the contributing area, which shall be relatively flat to evenly distribute runoff or create concentrated flow to the filter strip and shall not exceed 72 feet of impervious cover in the direction of flow.

GEOLOGY

According to the geologic assessment included with the application, the project site is underlain by the Lower Cretaceous member of the Person Formation. One (1) non-sensitive geologic feature was identified during the assessment. The San Antonio Regional Office site assessment conducted on September 28, 2018 revealed the site generally as described in the application.

SPECIAL CONDITIONS

- I. This modification is subject to all Special and Standard Conditions listed in the WPAP approval letter dated January 26, 2016.
- II. All permanent pollution abatement measures shall be inspected, and all measures be fully operational prior to first use of the newly constructed facilities.

STANDARD CONDITIONS

1. Pursuant to Chapter 7 Subchapter C of the Texas Water Code, any violations of the requirements in 30 TAC Chapter 213 may result in administrative penalties.
2. The holder of the approved Edwards Aquifer protection plan must comply with all provisions of 30 TAC Chapter 213 and all best management practices and measures contained in the approved plan. Additional and separate approvals, permits, registrations and/or

authorizations from other TCEQ Programs (i.e., Stormwater, Water Rights, UIC) can be required depending on the specifics of the plan.

3. In addition to the rules of the Commission, the applicant may also be required to comply with state and local ordinances and regulations providing for the protection of water quality.

Prior to Commencement of Construction:

4. Within 60 days of receiving written approval of an Edwards Aquifer Protection Plan, the applicant must submit to the San Antonio Regional Office, proof of recordation of notice in the county deed records, with the volume and page number(s) of the county deed records of the county in which the property is located. A description of the property boundaries shall be included in the deed recordation in the county deed records. A suggested form (Deed Recordation Affidavit, TCEQ-0625) that you may use to deed record the approved WPAP is enclosed.
5. All contractors conducting regulated activities at the referenced project location shall be provided a copy of this notice of approval. At least one complete copy of the approved WPAP and this notice of approval shall be maintained at the project location until all regulated activities are completed.
6. Modification to the activities described in the referenced WPAP application following the date of approval may require the submittal of a plan to modify this approval, including the payment of appropriate fees and all information necessary for its review and approval prior to initiating construction of the modifications.
7. The applicant must provide written notification of intent to commence construction, replacement, or rehabilitation of the referenced project. Notification must be submitted to the San Antonio Regional Office no later than 48 hours prior to commencement of the regulated activity. Written notification must include the date on which the regulated activity will commence, the name of the approved plan and program ID number for the regulated activity, and the name of the prime contractor with the name and telephone number of the contact person. The executive director will use the notification to determine if the approved plan is eligible for an extension.
8. Temporary erosion and sedimentation (E&S) controls, i.e., silt fences, rock berms, stabilized construction entrances, or other controls described in the approved WPAP, must be installed prior to construction and maintained during construction. Temporary E&S controls may be removed when vegetation is established, and the construction area is stabilized. If a water quality pond is proposed, it shall be used as a sedimentation basin during construction. The TCEQ may monitor stormwater discharges from the site to evaluate the adequacy of temporary E&S control measures. Additional controls may be necessary if excessive solids are being discharged from the site.
9. All borings with depths greater than or equal to 20 feet must be plugged with non-shrink grout from the bottom of the hole to within three (3) feet of the surface. The remainder of the hole must be backfilled with cuttings from the boring. All borings less than 20 feet must be backfilled with cuttings from the boring. All borings must be backfilled or plugged within four (4) days of completion of the drilling operation. Voids may be filled with gravel.

During Construction:

10. During the course of regulated activities related to this project, the applicant or agent shall comply with all applicable provisions of 30 TAC Chapter 213, Edwards Aquifer. The applicant shall remain responsible for the provisions and conditions of this approval until such responsibility is legally transferred to another person or entity.
11. This approval does not authorize the installation of temporary aboveground storage tanks on this project. If the contractor desires to install a temporary aboveground storage tank for

use during construction, an application to modify this approval must be submitted and approved prior to installation. The application must include information related to tank location and spill containment. Refer to Standard Condition No. 6, above.

12. If any sensitive feature (caves, solution cavities, sink holes, etc.) is discovered during construction, all regulated activities near the feature must be suspended immediately. The applicant or his agent must immediately notify the San Antonio Regional Office of the discovery of the feature. Regulated activities near the feature may not proceed until the executive director has reviewed and approved the methods proposed to protect the feature and the aquifer from potentially adverse impacts to water quality. The plan must be sealed, signed, and dated by a Texas Licensed Professional Engineer.
13. No wells exist on site. All water wells, including injection, dewatering, and monitoring wells must be in compliance with the requirements of the Texas Department of Licensing and Regulation under Title 16 TAC Chapter 76 (relating to Water Well Drillers and Pump Installers) and all other locally applicable rules, as appropriate.
14. If sediment escapes the construction site, the sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50 percent. Litter, construction debris, and construction chemicals shall be prevented from becoming stormwater discharge pollutants.
15. Intentional discharges of sediment laden water are not allowed. If dewatering becomes necessary, the discharge will be filtered through appropriately selected best management practices. These may include vegetated filter strips, sediment traps, rock berms, silt fence rings, etc.
16. The following records shall be maintained and made available to the executive director upon request: the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
17. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, and construction activities will not resume within 21 days. When the initiation of stabilization measures by the 14th day is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable.

After Completion of Construction:

18. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the San Antonio Regional Office within 30 days of site completion.
19. The applicant shall be responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. The regulated entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred. A copy of the transfer of responsibility must be filed with the executive director through San Antonio Regional Office within 30 days of the transfer. A copy of the transfer form (TCEQ-10263) is enclosed.
20. Upon legal transfer of this property, the new owner(s) is required to comply with all terms of the approved Edwards Aquifer protection plan. If the new owner intends to commence any

new regulated activity on the site, a new Edwards Aquifer protection plan that specifically addresses the new activity must be submitted to the executive director. Approval of the plan for the new regulated activity by the executive director is required prior to commencement of the new regulated activity.

21. An Edwards Aquifer protection plan approval or extension will expire, and no extension will be granted if more than 50 percent of the total construction has not been completed within ten years from the initial approval of a plan. A new Edwards Aquifer protection plan must be submitted to the San Antonio Regional Office with the appropriate fees for review and approval by the executive director prior to commencing any additional regulated activities.
22. At project locations where construction is initiated and abandoned, or not completed, the site shall be returned to a condition such that the aquifer is protected from potential contamination.

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality. If you have any questions or require additional information, please contact Ms. Lillian Butler of the Edwards Aquifer Protection Program of the San Antonio Regional Office at (210) 403-4026.

Sincerely,



Lynn Bumguardner, Water Section Manager
San Antonio Region
Texas Commission on Environmental Quality

LB/LB/eg

Enclosures: Deed Recordation Affidavit, Form TCEQ-0625
Change in Responsibility for Maintenance of Permanent BMPs, Form TCEQ-10263

cc: Mr. Trevor N. Tast, P.E., M&S Engineering, LLC
Mr. Mark Enders, City of New Braunfels
Mr. Roland Ruiz, Edwards Aquifer Authority
Mr. Thomas H. Hornseth, P.E., Comal County
Mr. H. L. Saur, Comal Trinity Groundwater Conservation District

Attachment B
Narrative of Proposed Modification

Narrative of *Proposed* Modification

A Water Pollution Abatement Plan (WPAP) modification (#13000745) was approved on November 27, 2018, for a 41.12-acre site. This approved modification adjusted the amount of green space, project area, and impervious cover and had 1.12 acres of impervious cover, resulting in 2.72% overall WPAP coverage. To prevent stormwater runoff pollution, the approved plan incorporated a 15' engineered vegetative filter strip for the gravel access road and a natural vegetated filter strip for the wastewater treatment facility so that the project was in compliance with TCEQ technical guidance. The approved modified plan treated 1,005 pounds of Total Suspended Solids (TSS) generated from the 1.12 acres of impervious cover .

The proposed project involves the addition of a reinforced fiberglass tank, which will increase the impervious cover by 200 square feet (0.0046 acres) which will bring the total proposed impervious cover for the site to 1.125 acres, for a 2.74% coverage of the total WPAP area. The increase in impervious cover leads to an additional requirement of 4 pounds of Total Suspended Solids (TSS) removal to maintain the 80% reduction standard. To address this and accommodate the new EQ tank's placement, which impacts the existing 50-foot natural Vegetative Filter Strip (VFS), the project proposes an extension of the VFS.

This modification is designed to integrate the new tank while maintaining full compliance with TCEQ regulations for Edwards Aquifer protection. The adjusted VFS configuration will ensure continued effective management of stormwater runoff and pollutant removal in accordance with the established guidelines.

Attachment C
Current Site Plan of the Approved Project

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY
WATER POLLUTION ABATEMENT PLAN
GENERAL CONSTRUCTION NOTES

SEVEN DAYS PRIOR TO CONSTRUCTION NOTIFICATION MUST BE GIVEN TO THE APPROPRIATE TCEQ REGIONAL OFFICE NO LATER THAN 48 HOURS PRIOR TO COMMENCEMENT OF THE REGULATED ACTIVITY. INFORMATION MUST INCLUDE THE DATE ON WHICH THE REGULATED ACTIVITY WILL COMMENCE, THE NAME OF THE APPROVED PLAN FOR THE REGULATED ACTIVITY, AND THE NAME OF THE PRIME CONTRACTOR AND THE NAME AND TELEPHONE NUMBER OF THE CONTACT PERSON.

CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT MUST BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED WATER POLLUTION ABATEMENT PLAN AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTORS ARE REQUIRED TO KEEP ON-SITE COPIES OF THE APPROVED PLAN AND APPROVAL LETTER.

IF ANY SENSITIVE FEATURE IS DISCOVERED DURING CONSTRUCTION, ALL REGULATED ACTIVITIES NEAR THE SENSITIVE FEATURE MUST BE STOPPED IMMEDIATELY. THE APPROPRIATE TCEQ REGIONAL OFFICE MUST BE IMMEDIATELY NOTIFIED OF ANY SENSITIVE FEATURES ENCOUNTERED DURING CONSTRUCTION. THE REGULATED ACTIVITIES NEAR THE SENSITIVE FEATURE MAY NOT PROCEED UNTIL THE TCEQ HAS REVIEWED AND APPROVED THE METHODS PROPOSED TO PROTECT THE SENSITIVE FEATURE AND THE EDWARDS AQUIFER FROM ANY POTENTIALLY ADVERSE IMPACTS TO WATER QUALITY.

A TEMPORARY ABOVEGROUND HYDROCARBON AND HAZARDOUS SUBSTANCE STORAGE TANK SYSTEM IS INSTALLED WITHIN 150 FEET OF A DOMESTIC, INDUSTRIAL, IRRIGATION, OR PUBLIC WATER SUPPLY WELL, OR OTHER SENSITIVE FEATURE.

PRIOR TO COMMENCEMENT OF CONSTRUCTION, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY DESIGNED, INSTALLED, AND MAINTAINED IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS AND GOOD ENGINEERING PRACTICES. CONTROLS SPECIFIED IN THE TEMPORARY STORM WATER SECTION OF THE APPROVED EDWARDS AQUIFER PROTECTION PLAN ARE REQUIRED DURING CONSTRUCTION. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORRECTLY, THE APPLICANT MUST REMOVE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THE CONTROLS MUST REMAIN IN PLACE UNTIL DISTURBED AREAS ARE REVEGETATED OR THE AREAS HAVE BECOME PERMANENTLY STABILIZED.

IF SEDIMENT ESCAPES THE CONSTRUCTION SITE, OFF-SITE ACCUMULATIONS OF SEDIMENT MUST BE REMOVED AT A FREQUENCY SUFFICIENT TO MINIMIZE OFFSITE IMPACTS TO WATER QUALITY (E.G., FUGITIVE SEDIMENT IN STREET BEING WASHED INTO SURFACE STREAMS OR SENSITIVE AREAS BY THE NEXT RAIN).

SEDIMENT MUST BE REMOVED FROM SEDIMENT TRAPS OR SEDIMENTATION PONDS NOT LATER THAN WHEN DESIGN CAPACITY HAS BEEN REDUCED TO 50%. A PERMANENT STAKE MUST BE PROVIDED THAT CAN INDICATE WHEN THE SEDIMENT OCCUPIES 50% OF THE BASIN VOLUME.

CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BECOMING A POTENTIAL SOURCE FOR STORMWATER DISCHARGES (E.G., SCREENING OUTFALLS, PICKED UP DAILY).

SPOILS (EXCAVATED MATERIAL) GENERATED FROM THE PROJECT SITE MUST BE STORED ON-SITE WITH PROPER E&S CONTROLS. FOR STORAGE AND DISPOSAL OF SPOILS AT ANOTHER SITE ON THE EDWARDS AQUIFER RECHARGE ZONE, THE OWNER OF THE SITE MUST RECEIVE APPROVAL OF A WATER POLLUTION ABATEMENT PLAN FOR THE PLACEMENT OF FILL MATERIAL OR MASS GRADING PRIOR TO THE PLACEMENT OF SPOILS AT THE OTHER SITE.

STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS PRACTICABLE IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY OR PERMANENTLY CEASED, BUT IN NO CASE MORE THAN 14 DAYS AFTER THE CONSTRUCTION ACTIVITY IN THAT PORTION OF THE SITE HAS TEMPORARILY OR PERMANENTLY CEASED. WHERE THE INITIATION OF STABILIZATION MEASURES BY THE 14TH DAY AFTER CONSTRUCTION ACTIVITY TEMPORARILY OR PERMANENTLY CEASE IS PRECLUDED BY WEATHER CONDITIONS, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS PRACTICABLE. WHERE CONSTRUCTION ACTIVITY ON A PORTION OF THE SITE IS TEMPORARILY CEASED, AND EARTH DISTURBING ACTIVITIES WILL RESUME WITHIN 21 DAYS, TEMPORARY STABILIZATION MEASURES DO NOT HAVE TO BE INITIATED ON THAT PORTION OF SITE. IN AREAS EXPERIENCING DROUGHTS WHERE THE INITIATION OF STABILIZATION MEASURES BY THE 14TH DAY AFTER CONSTRUCTION ACTIVITY HAS TEMPORARILY OR PERMANENTLY CEASED IS PRECLUDED BY SEASONAL ARID CONDITIONS, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS PRACTICABLE.


THE FOLLOWING RECORDS SHALL BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST: THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR; THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; AND THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.

THE HOLDER OF ANY APPROVED EDWARDS AQUIFER PROTECTION PLAN MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:

ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY WATER POLLUTION ABATEMENT STRUCTURE(S), INCLUDING BUT NOT LIMITED TO PONDS, DITCHES, BERMS, SEWAGE TREATMENT PLANTS, AND DIVERSIONARY STRUCTURES;
ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED OR A CHANGE WHICH WOULD SIGNIFICANTLY IMPACT THE ABILITY OF THE PLAN TO PREVENT POLLUTION OF THE EDWARDS AQUIFER;
ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE ORIGINAL WATER POLLUTION ABATEMENT PLAN.

REGIONAL OFFICE
35, SUITE 100
DALLAS, TEXAS 78704-5712
(214) 339-2929
339-3795

SAN ANTONIO REGIONAL OFFICE
10000 DUTCHMAN ROAD
SAN ANTONIO, TEXAS 78233-4480
(214) 490-3096



FOR A CHANGE



C. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE ORIGINAL WATER POLLUTION ABATEMENT PLAN.

AUSTIN REGIONAL OFFICE
2800 S. IH 35, SUITE 100
AUSTIN, TEXAS 78704-5712
PHONE (512) 339-2929
FAX (512) 339-3795

SAN ANTONIO REGIONAL OFFICE
14250 JUDSON ROAD
SAN ANTONIO, TEXAS 78233-4480
PHONE (210) 490-3096
FAX (210) 545-4329

THESE GENERAL CONSTRUCTION NOTES MUST BE INCLUDED ON THE
CONSTRUCTION PLANS PROVIDED TO THE CONTRACTOR AND ALL SUBCONTRACTORS.

TEMPORARY BMP NOTE:
SEE ATTACHED SHEETS FOR TEMPORARY BMP DETAILS. ADDITIONAL BMP DETAILS PROVIDED BUT NOT CALLED
OUT ON PLANS MAY BE USED AT CONTRACTOR'S DISCRETION.

SOIL DISTURBANCE NOTE

SOIL DISTURBANCES WILL OCCUR TO CLEARING, GRUBBING, AND GRADING OF AREAS TO BE USED FOR THE
RESIDENTIAL LOTS, ROADS, ROAD RIGHT-OF-WAY, AND DETENTION POND. THESE DISTURBANCES CAN BE
ATTRIBUTED TO, BUT NOT LIMITED TO, CLEARING AND GRUBBING RELATED TO BUILDING PAD, DRIVEWAY,
UTILITY INSTALLATION, AND LANDSCAPE PREPARATION. THE REMAINING PORTIONS OF THE SITE NOT INVOLVED
IN ANY OF THESE ACTIVITIES WILL REMAIN UNDISTURBED.

TEMPORARY GRAVEL CONSTRUCTION ENTRANCE SHALL BE INSTALLED TO PROVIDE A STABLE ENTRANCE/EXIT
CONDITION FROM THE CONSTRUCTION SITE TO KEEP MUD AND SEDIMENT OFF PUBLIC ROADWAYS (REFER TO
THE EDWARDS AQUIFER TECHNICAL GUIDANCE MANUAL FOR CONSTRUCTION INFORMATION).

SOIL STABILIZATION NOTE


TEMPORARY EROSION CONTROL MEASURES WILL BE USED TO STABILIZE DISTURBED AREAS (REFER TO
EDWARDS AQUIFER TECHNICAL GUIDANCE MANUAL FOR CONSTRUCTION OF EROSION CONTROL MEASURES).
TRAFFIC WILL BE ROUTED AROUND THESE AREAS TO REDUCE THE EXTENT OF DISTURBED AREAS BY REDUCING
SEDIMENT LOADS TO SURFACE WATER.

BARE SOILS SHOULD BE SEEDED OR OTHERWISE STABILIZED WITHIN 14 CALENDAR DAYS AFTER FINAL GRADING
OR WHERE CONSTRUCTION ACTIVITY HAS TEMPORARILY CEASED FOR MORE THAN 21 DAYS.

MULCHING/MATS CAN BE USED TO PROTECT THE DISTURBED AREAS WHILE VEGETATION BECOMES
ESTABLISHED.

SILT FENCE NOTE:

SILT FENCE WILL BE SITED SO THAT THE MAXIMUM DRAINAGE AREA IS $\frac{1}{4}$ ACRE/100 FT OF
FENCE. (AS REQUIRED BY TCEQ RG-348, INSTALLATION: ITEM 2)







CONCRETE WASHOUT AREA

THE PURPOSE OF CONCRETE WASHOUT AREA IS TO PREVENT
STORMWATER FROM CONCRETE WASHOUT AREA, AND TRAFFIC

THE FOLLOWING STEPS WILL BE FOLLOWED:

- INCORPORATE REQUIREMENTS OF SUBCONTRACTOR AGREEMENT
- AVOID MIXING EXCESS CONCRETE
- PERFORM WASHOUT OF CONCRETE
- DO NOT WASH OUT CONCRETE
- DO NOT ALLOW EXCESS CONCRETE
- LOCATE WASHOUT AREA AWAY FROM BODIES. DO NOT ALLOW CONCRETE TO ENOUGH FOR LIQUID AND
- WASH OUT WASTES IN CONCRETE AND DISPOSED PROPERLY.

BELOW GRADE CONCRETE WASHOUT AREA SHALL BE LARGE TO HOLD EXPECTED VOLUME OF CONCRETE. TEMPORARY CO



NOTE:
ACTUAL LAYOUT
DETERMINED IN FIELD.

CONCRETE WASHOUT AREAS

THE PURPOSE OF CONCRETE WASHOUT AREAS IS TO PREVENT OR REDUCE THE DISCHARGE OF POLLUTANTS TO STORMWATER FROM CONCRETE WASTE BY CONDUCTING WASHOUT OFFSITE, PERFORMING ONSITE WASHOUT IN A DESIGNATED AREA, AND TRAINING EMPLOYEES AND SUBCONTRACTORS.

THE FOLLOWING STEPS WILL HELP REDUCE STORMWATER POLLUTION FROM CONCRETE WASTES:

- INCORPORATE REQUIREMENTS FOR CONCRETE WASTE MANAGEMENT INTO MATERIAL SUPPLIER AND SUBCONTRACTOR AGREEMENTS.
- AVOID MIXING EXCESS AMOUNTS OF FRESH CONCRETE.
- PERFORM WASHOUT OF CONCRETE TRUCKS IN DESIGNATED AREAS ONLY.
- DO NOT WASH OUT CONCRETE TRUCKS INTO STORM DRAINS, OPEN DITCHES, STREETS, OR STREAMS.
- DO NOT ALLOW EXCESS CONCRETE TO BE DUMPED ONSITE, EXCEPT IN DESIGNATED AREAS. FOR ONSITE WASHOUT:
- LOCATE WASHOUT AREA AT LEAST 50 FEET FROM SENSITIVE FEATURES, STORM DRAINS, OPEN DITCHES, OR WATER BODIES. DO NOT ALLOW RUNOFF FROM THIS AREA BY CONSTRUCTING A TEMPORARY PIT OR BERMED AREA LARGE ENOUGH FOR LIQUID AND SOLID WASTE.
- WASH OUT WASTES INTO THE TEMPORARY PIT WHERE THE CONCRETE CAN SET, BE BROKEN UP, AND THEN DISPOSED PROPERLY.

BELOW GRADE CONCRETE WASHOUT FACILITIES ARE TYPICAL. THESE CONSIST OF A LINED EXCAVATION SUFFICIENTLY LARGE TO HOLD EXPECTED VOLUME OF WASHOUT MATERIAL. ABOVE GRADE FACILITIES ARE USED IF EXCAVATION IS NOT PRACTICAL. TEMPORARY CONCRETE WASHOUT FACILITY (TYPE ABOVE GRADE) SHOULD BE CONSTRUCTED AS SHOWN ON

NOT PROCEED UNTIL THE TCEQ HAS
DS AQUIFER FROM ANY POTENTIALLY

S INSTALLED WITHIN 150 FEET OF A

TROL MEASURES MUST BE PROPERLY
ND GOOD ENGINEERING PRACTICES.
R PROTECTION PLAN ARE REQUIRED
NCORRECTLY, THE APPLICANT MUST
DISTURBED AREAS ARE REVEGETATED

VED AT A FREQUENCY SUFFICIENT TO
O SURFACE STREAMS OR SENSITIVE

DESIGN CAPACITY HAS BEEN REDUCED
THE BASIN VOLUME.

BE PREVENTED FROM BECOMING A

PROPER E&S CONTROLS. FOR STORAGE
E SITE MUST RECEIVE APPROVAL OF A
O THE PLACEMENT OF SPOILS AT THE


RE CONSTRUCTION ACTIVITIES HAVE
N ACTIVITY IN THAT PORTION OF THE
THE 14TH DAY AFTER CONSTRUCTION
ASURES SHALL BE INITIATED AS SOON
D EARTH DISTURBING ACTIVITIES WILL
N THAT PORTION OF SITE. IN AREAS
FTER CONSTRUCTION ACTIVITY HAS
ASURES SHALL BE INITIATED AS SOON

THE DATES WHEN MAJOR GRADING
ON A PORTION OF THE SITE; AND THE

ONAL OFFICE IN WRITING AND OBTAIN

CLUDING BUT NOT LIMITED TO PONDS,

ORIGINALLY APPROVED OR A CHANGE
AQUIFER;
ON ABATEMENT PLAN.



SECTION 5: WATER POLLUTION ABATEMENT PLAN

Water Pollution Abatement Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Water Pollution Abatement Plan Application Form** is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Print Name of Customer/Agent: Deirdre Lynch, P.E.

Date: January, 2025

Signature of Customer/Agent:



Regulated Entity Name: Vintage Oaks at the Vineyard WWTF

Regulated Entity Information

1. The type of project is:

- ☐ Residential: Number of Lots: _____
- ☐ Residential: Number of Living Unit Equivalents: _____
- ☐ Commercial
- ☐ Industrial
- ☒ Other: WWTF

2. Total site acreage (size of property): 1.21

3. Estimated projected population: 0

4. The amount and type of impervious cover expected after construction are shown below:

Table 1 - Impervious Cover Table

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	200.71	$\div 43,560 =$	0.005
Parking	0	$\div 43,560 =$	0
Other paved surfaces	0	$\div 43,560 =$	0
Total Impervious Cover	200.71	$\div 43,560 =$	0.005

Total Site Impervious Cover $0.005 \div \text{Total Site Acreage } 1.21 \times 100 = 0.004\%$ **Impervious Cover**

5. ☒ **Attachment A - Factors Affecting Surface Water Quality.** A detailed description of all factors that could affect surface water and groundwater quality that addresses ultimate land use is attached.
6. ☒ Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

For Road Projects Only

Complete questions 7 - 12 if this application is exclusively for a road project.

7. Type of project:

- ☐ TXDOT road project.
- ☐ County road or roads built to county specifications.
- ☐ City thoroughfare or roads to be dedicated to a municipality.
- ☐ Street or road providing access to private driveways.

8. Type of pavement or road surface to be used:

- ☐ Concrete
- ☐ Asphaltic concrete pavement
- ☐ Other: _____

9. Length of Right of Way (R.O.W.): _____ feet.

Width of R.O.W.: _____ feet.

$L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$

10. Length of pavement area: _____ feet.

Width of pavement area: _____ feet.

$L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$

Pavement area _____ acres \div R.O.W. area _____ acres $\times 100 = \text{_____}\%$ impervious cover.

11. ☐ A rest stop will be included in this project.

☐ A rest stop will not be included in this project.

12. ☐ Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

Stormwater to be generated by the Proposed Project

13. ☒ **Attachment B - Volume and Character of Stormwater.** A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on the area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

Wastewater to be generated by the Proposed Project

14. The character and volume of wastewater is shown below:

_____ % Domestic	_____ Gallons/day
_____ % Industrial	_____ Gallons/day
_____ % Commingled	_____ Gallons/day
TOTAL gallons/day _____	

15. Wastewater will be disposed of by:

- ☐ On-Site Sewage Facility (OSSF/Septic Tank):
- ☐ **Attachment C - Suitability Letter from Authorized Agent.** An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.
- ☐ Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.
- ☐ Sewage Collection System (Sewer Lines):
- ☐ Private service laterals from the wastewater generating facilities will be connected to an existing SCS.
- ☐ Private service laterals from the wastewater generating facilities will be connected to a proposed SCS.
- ☐ The SCS was previously submitted on _____.
- ☐ The SCS was submitted with this application.
- ☐ The SCS will be submitted at a later date. The owner is aware that the SCS may not be installed prior to Executive Director approval.

- ☐ The sewage collection system will convey the wastewater to the _____ (name) Treatment Plant. The treatment facility is:
- ☐ Existing.
- ☐ Proposed.

16. ☐ All private service laterals will be inspected as required in 30 TAC §213.5.

Site Plan Requirements

Items 17 – 28 must be included on the Site Plan.

17. ☒ The Site Plan must have a minimum scale of 1" = 400'.

Site Plan Scale: 1" = 10'.

18. 100-year floodplain boundaries:

☐ Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.

☒ No part of the project site is located within the 100-year floodplain.

The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FEMA Flood Insurance Rate Map 48091C0245F (eff. 9/2/2009)

19. ☐ The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, open space, etc. are shown on the plan.

☒ The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, open space, etc. are shown on the site plan.

20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):

☐ There are _____ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)

☐ The wells are not in use and have been properly abandoned.

☐ The wells are not in use and will be properly abandoned.

☐ The wells are in use and comply with 16 TAC §76.

☒ There are no wells or test holes of any kind known to exist on the project site.

21. Geologic or manmade features which are on the site:

☐ All sensitive geologic or manmade features identified in the Geologic Assessment are shown and labeled.

☒ No sensitive geologic or manmade features were identified in the Geologic Assessment.

☐ **Attachment D - Exception to the Required Geologic Assessment.** A request and justification for an exception to a portion of the Geologic Assessment is attached.

22. ☒ The drainage patterns and approximate slopes anticipated after major grading activities.

- 23. ☒ Areas of soil disturbance and areas which will not be disturbed.
- 24. ☒ Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
- 25. ☒ Locations where soil stabilization practices are expected to occur.
- 26. ☐ Surface waters (including wetlands).
☒ N/A
- 27. ☐ Locations where stormwater discharges to surface water or sensitive features are to occur.
☒ There will be no discharges to surface water or sensitive features.
- 28. ☒ Legal boundaries of the site are shown.

Administrative Information

- 29. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
- 30. ☒ Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

Attachment A
Factors Affecting Surface Water Quality

Factors Affecting Surface Water Quality

Materials that are anticipated to be used on site that could be a potential source of contamination include the following:

During Construction:

1. Concrete and Masonry Materials
2. Wood, plastic, and metal Materials
3. Compacted Gravel for Base Stabilization
4. Oil, Grease, fuel, and hydraulic fluid from construction equipment and vehicle drippings
5. Miscellaneous construction trash and debris
6. Soil erosion and sedimentation due to construction activity

Ultimate Use:

1. Pollutants generated from vehicles utilizing the site
2. Miscellaneous trash and debris generated from the owner's representatives accessing the site

(This is not intended to be an all-inclusive list)

All practical management practices will be used to reduce the risk of spills and other exposure of any contaminant to surface or groundwater.

Attachment B
Volume and Character of Storm Water

Volume and Character of Storm Water

The proposed Vintage Oaks at the Vineyard WWTF Modification project involves the addition of an 200 Sq ft EQ tank and concrete pad to an existing wastewater treatment facility, which brings the total impervious cover for the WPAP to 1.125 acres (2.74%). The addition of the EQ tank results in an extension of the current 50' natural vegetative filter strip (VFS) surrounding the facility.

The existing site topography features a high point on the eastern side near Bordeaux Lane. Approximately half of the stormwater runoff sheet flows from this high point towards W State Highway 46, where the ridge alongside the highway guides all flows southwest. The remaining runoff, including that from the project site, flows directly westward. All of these flows ultimately converge at the point of analysis located at an existing culvert downstream of the site.

The volume and character of stormwater runoff from the proposed project are expected to be similar to existing conditions, with minimal changes due to the limited scope of construction. The extended 50' natural VFS will continue to be designed in accordance with TCEQ requirements, ensuring that runoff is released at rates below the design thresholds. The modified natural VFS, along with the existing 15' engineered VFS treating the access road from Bordeaux Lane, will help maintain the quality and quantity of stormwater runoff leaving the site.

The preservation of existing drainage patterns and the extension of the natural vegetative filter strip (VFS) are key factors in maintaining the site's stormwater management capabilities. As a result, the site will maintain its ability to effectively manage the volume and character of stormwater, ensuring that both the quality and quantity of runoff remain at levels comparable to existing conditions.

The proposed site improvements are not located in the Federal Emergency Management Agency's 100-year floodplain according to Flood Insurance Rate Map 48091C0245F.



Attachment C
Suitability Letter From Authorized Agent

Suitability Letter From Authorized Agent



Wastewater will not be generated from this proposed site. Sections 14 – 16 do not apply.


Site Plan

K:\SAL_W\069277520_C1.MXD - Grove EQ Tank\CAD\PLANSHEETS\TCEO SITE PLAN.dwg 1/20/2025 4:43 PM




- LEGEND**
- X — X — X — PROPOSED FENCE
 - SF — SILT FENCE
 - LOC — LOC — LIMITS OF CONSTRUCTION
 - [Pattern] PROPOSED CONSTRUCTION ENTRANCE
 - [Pattern] PROPOSED CONCRETE WASHOUT
 - [Pattern] NATURAL VEGETATIVE FILTER STRIP
 - [Pattern] ENGINEERED VEGETATIVE FILTER STRIP
 - — — — — PROPERTY BOUNDARY
 - - - - - APPROXIMATE CONTOURS





Kimley-Horn
P-512-446-2237
P-512-446-2237
3001 Southwest Pkwy, Bldg. 3, Suite 100, Austin TX, 78735

1/31/25



DEIRDRE ANN LYNCH
151639
PROFESSIONAL ENGINEER

Deirdre Lynch

DATE:	JANUARY 2025
DESIGN:	DAL
DRAWN:	IM
CHECKED:	INC
KHA NO.:	069277520

SITE PLAN

GROVE EQ TANK

SHEET

C5

SECTION 6: TEMPORARY STORMWATER SECTION

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.


Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Deirdre Lynch, P.E.

Date: January 2025

Signature of Customer/Agent:



Regulated Entity Name: Vintage Oaks at the Vineyard WWTF

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

☐ The following fuels and/or hazardous substances will be stored on the site:

These fuels and/or hazardous substances will be stored in:

☐ Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

☐ Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.

- ☐ Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- ☒ Fuels and hazardous substances will not be stored on the site.
- 2. ☒ **Attachment A - Spill Response Actions.** A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. ☒ Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. ☒ **Attachment B - Potential Sources of Contamination.** A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

- 5. ☒ **Attachment C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
 - ☒ For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
 - ☒ For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6. ☒ Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Comal River-Guadalupe River - West Fork Dry Comal Creek- Comal Creek

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

- 7. ☒ **Attachment D – Temporary Best Management Practices and Measures.** TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:
 - ☐ A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.

- ☒ A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
 - ☒ A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
 - ☐ A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. ☒ The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- ☐ **Attachment E - Request to Temporarily Seal a Feature.** A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
- ☒ There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. ☒ **Attachment F - Structural Practices.** A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10. ☒ **Attachment G - Drainage Area Map.** A drainage area map supporting the following requirements is attached:
- ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
 - ☐ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.
 - ☒ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11. ☐ **Attachment H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed

temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.

☒ N/A

12. ☒ **Attachment I - Inspection and Maintenance for BMPs.** A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13. ☒ All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. ☒ If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. ☒ Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. ☒ Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. ☒ **Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices.** A schedule of the interim and permanent soil stabilization practices for the site is attached.
18. ☒ Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19. ☒ Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

- 20. ☒ All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. ☒ If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. ☒ Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

Attachment A

Spill Response Actions

Spill Response Actions

If there is an accidental spill on site, the contractor shall respond with appropriate action. The contractor will be required to contact the owner and in turn the owner will contact the TCEQ in the event of a spill on site. In addition to the following guidance, reference the latest version of TCEQ's Technical Guidance Manual (TGM) RG-348 Section 1.4.16.

Cleanup

- Clean up leaks and spills immediately.
- Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.
- Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

Minor Spills

- Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.
- Use absorbent materials on small spills rather than hosing down or burying the spill.
- Absorbent materials should be promptly removed and disposed of properly.
- Follow the practice below for a minor spill:
 - Contain the spread of the spill.
 - Recover spilled materials.
 - Clean the contaminated area and properly dispose of contaminated materials.

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- Contain spread of the spill.
- Notify the project foreman immediately.
- If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities:

- Notify the TCEQ by telephone as soon as possible and within 24 hours at (512)339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.

- For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110,119, and 302, the contractor should notify the National Response Center at (800) 424-8802.
- Notification should first be made by telephone and followed up with a written report.
- The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.
- Other agencies which may need to be consulted include, but not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc.

Attachment B
Potential Sources of Contamination

Potential Sources of Contamination

Potential Source: Oil, grease, fuel, and hydraulic fluid contamination from construction equipment and vehicle dripping.

Preventative Measures: Vehicle maintenance will be performed within the construction staging area or a local maintenance shop.

Potential Source: Miscellaneous trash and litter from construction workers and material wrappings.

Preventative Measures: Trash containers will be placed throughout the site to encourage proper disposal of trash.

Potential Source: Construction Debris.

Preventative Measures: Construction debris will be monitored daily by contractor. Debris will be collected weekly and placed in disposal bins. Situations requiring immediate attention will be addressed on a case by case basis.

Potential Source: Soil and Mud from Construction Vehicle tires as they leave the site.

Preventative Measures: A stabilized construction exit shall be utilized as vehicles leave the site. Any soil, mud, etc. carried from the project onto public roads shall be cleaned up within 24 hours.

Potential Source: Silt leaving the site; Sediment from soil, sand, gravel and excavated materials stock piled on site.

Preventative Measures: Silt fence shall be installed on the down gradient side of the stock piled materials.. Contractor will install all temporary best management practices prior to start of construction including the stabilized construction entrance to prevent tracking onto adjoining streets.

Attachment C

Sequence of Major Activities

Sequence of Major Activities

The installation of erosion and sedimentation controls shall occur prior to any excavation of materials or major disturbances on the site. The sequence of major construction activities will be as follows. Approximate acreage to be disturbed is listed in parentheses next to each activity.

Intended Schedule or Sequence of Major Activities:

1. Stabilize Existing Access Road to the Site (0.398 acres).
2. Installation of Temporary BMPs (up to 1.21 Acres)
3. Concrete (Pad, flatwork) (0.005 acres)
4. Building Equalization Wastewater Process Tank (0.005 Acres)
5. Install Additional 50' Natural VFS (0.034 acres)
6. Topsoil and Stabilization of Road (up to 1.21 Acres)
7. Site Cleanup and Removal of Temporary BMPs (up to 1.21 Acres)

Maximum total construction time is not expected to exceed 12 months.


Attachment D
Temporary Best Management Practices
and Measures

Temporary Best Management Practices and Measures

Temporary BMPs will be installed prior to soil distributing and construction activity:



- A.** Sediment Control Fence – This BMP prevents the transport of sediment from going off-site during storm events. This BMP is used in grass areas and will be placed along the down-gradient sides of the property to prevent silt from escaping the construction area.
- B.** Temporary Seeding – This BMP stabilizes the soil from being washed away in a storm event
- C.** Offsite Vehicle Tracking Controls – This BMP removes excess dirt/mud on road daily, haul roads dampened for dust control, loaded haul trucks to be covered with tarpaulin, stabilized construction entrance.
- D.** Concrete Washout Pit – This BMP will be used to collect all excess concrete during construction.
- E.** Practices may also be implemented on site for interim and permanent stabilization. Stabilization practices may include but are not limited to: establishment of temporary vegetation, establishment of permanent vegetation, mulching, and other similar measures.

K:\SAL_W\069277520_C4\MSD - Grove EQ Tank\CAO\PLANS\EROSION CONTROL PLAN.dwg 1/30/2025 4:39 PM



LEGEND

- PROPOSED FENCE
- SILT FENCE
- LIMITS OF CONSTRUCTION
- PROPOSED CONSTRUCTION ENTRANCE
- PROPOSED CONCRETE WASHOUT
- PROPOSED NATURAL VEGETATIVE FILTER STRIP
- ENGINEERED VEGETATIVE FILTER STRIP
- PROPERTY BOUNDARY



DATE: JANUARY 2025

DESIGN: DAL

DRAWN: IM

CHECKED: INC

XHA NO.: 069277520

1/31/25

13.1/25

Kimley»Horn

Firm No. F-928
5201 Southwest Pkwy, Bldg 3, Suite 100, Austin TX, 78735
P: 512-646-2237

By

Date

Revision

No.

By

Date

STATE OF TEXAS

DEIRDRE ANN LYNCH

151639

PROFESSIONAL ENGINEER

EROSION CONTROL AND
BEST MEASURE
PRACTICES

GROVE EQ TANK

C4

Attachment F

Structural Practices

Structural Practices

Structural BMPs will be used to limit runoff discharge of pollutants from exposed areas of the site. BMPs will be installed prior to soil disturbing construction activity. Silt fencing will be placed along the down-gradient sides of the property to prevent silt from escaping the construction area. A temporary construction entrance will be placed at the site entry/exit point to reduce tracking onto adjoining streets. A construction staging area will be used onsite to perform all vehicle maintenance and for equipment and material storage. A concrete truck washout pit will be placed on site to provide containment and easier cleanup of waste from concrete operations. The location of all structural temporary BMP's are shown on the erosion control plan sheet and details and specifications are provided on the erosion control details sheet which can be found at the end of this report under Section 9.

Description of Temporary BMPs

Temporary Construction Entrance/Exit

The purpose of a temporary gravel construction entrance is to provide a stable entrance/exit condition from the construction site and keep mud and sediment off public roads. A stabilized construction entrance is a stabilized pad of crushed stone located at any point traffic will be entering or leaving the construction site from a public right-of-way, street, alley, sidewalk or parking area. The purpose of a stabilized construction entrance is to reduce or eliminate the tracking or flowing of sediment onto public rights-of-way. This practice should be used at all points of construction ingress and egress.

Excessive amounts of mud can also present a safety hazard to roadway users. To minimize the amount of sediment loss to nearby roads, access to the construction site should be limited to as few points as possible and vegetation around the perimeter should be protected where access is not necessary. A rock stabilized construction entrance should be used at all designated access points.

Silt Fence

The purpose of a silt fence is to intercept and detain water-borne sediment from unprotected areas of a limited extent. Silt fence is used during the period of construction near the perimeter of a disturbed area to intercept sediment while allowing water to percolate through. This fence should remain in place until the disturbed area is permanently stabilized. Silt fence should not be used where there is a concentration of water in a channel or drainage way.

Silt fencing within the site may be temporarily moved during the day to allow construction activity provided it is replaced and properly anchored to the ground at the end of the day. Silt fences on the perimeter of the site or around drainage ways should not be moved at any time.

Concrete Washout Area

The purpose of concrete washout areas is to prevent or reduce the discharge of pollutants to stormwater from concrete waste by conducting washout offsite, performing onsite washout in a designated area, and training employees and subcontractors.

The following steps will help reduce stormwater pollution from concrete wastes:

- Incorporate requirements for concrete waste management into material supplier and subcontractor agreements.
- Avoid mixing excess amounts of fresh concrete.
- Perform washout of concrete trucks in designated areas only.
- Do not wash out concrete trucks into storm drains, open ditches, streets, or streams.
- Do not allow excess concrete to be dumped onsite, except in designated areas.
- For onsite washout:



- Locate washout area at least 50 feet from sensitive features, storm drains, open ditches, or water bodies. Do not allow runoff from this area by constructing a temporary pit or bermed area large enough for liquid and solid waste.
- Wash out wastes into the temporary pit where the concrete can set, be broken up, and then disposed properly.

Below grade concrete washout facilities are typical. These consist of a lined excavation sufficiently large to hold expected volume of washout material. Above grade facilities are used if excavation is not practical. Temporary concrete washout facility (type above grade) should be constructed as shown on the details at the end of this section, with sufficient quantity and volume to contain all liquid and concrete waste generated by washout operations. Plastic lining material should be a minimum of 10 mil in polyethylene sheeting and should be free of holes, tears, or other defects that compromise the impermeability of the material.

When temporary concrete washout facilities are no longer required for the work, the hardened concrete should be removed and disposed of. Materials used to construct temporary concrete washout facilities should be removed from the site of the work and disposed of. Holes, depressions or other ground disturbance caused by the removal of the temporary concrete washout facilities should be backfilled and repaired.

Attachment G

Drainage Area Map




LEGEND

— 800 —	EXISTING 5' CONTOUR
— 801 —	EXISTING 1' CONTOUR
— > —	FLOW LINE
---	DRAINAGE BOUNDARY
→	FLOW ARROWS
EX-1	AREA TAG
6.95 ac	AREA ACREAGE

EXISTING VS PROPOSED FLOWS						
Existing DA	Proposed DA	Δ Q2	Δ Q10	Δ Q25	Δ Q100	
OFF-1	OFF-1	0.00	0.00	0.00	0.00	
OFF-2	OFF-2	0.00	0.00	0.00	0.00	
OFF-3	OFF-3	0.00	0.00	0.00	0.00	
OFF-4	OFF-4	0.01	0.02	0.02	0.03	
EX-1	A-1	0.01	0.02	0.02	0.03	

EXISTING CONDITIONS FLOW DIAGRAM



GROVE EQ TANK Existing "C" Value Calculations

D.A. Number	Drainage Area (SF)	Drainage Area (Ac)	Pervious Area (SF)	Impervious Area (SF)	I.C. (%)	Comp. C ₂	Comp. C ₁₉	Comp. C ₂₅	Comp. C ₁₀₀
OFF-1	302903.52	6.95	230396.52	72507	24%	0.43	0.49	0.53	0.60
OFF-2	273102.17	6.27	178640.84	94461	35%	0.48	0.54	0.58	0.66
OFF-3	334869.00	7.69	290736.70	44132	13%	0.39	0.44	0.48	0.55
OFF-4	264222.88	6.07	201993.27	62230	24%	0.43	0.49	0.53	0.60
EX-1	17539.73	0.40	12461.84	5078	29%	0.45	0.51	0.55	0.63

GROVE EQ TANK "Tc" Value Calculations

Drainage Area	Area (Ac.)	Sheet Flow				Unpaved Shallow Flow			Paved Shallow Flow			Channel Flow				Total Tc
		Length ft	Slope ft/ft	n	Tt min	Length ft	Slope ft/ft	Tt min	Length ft	Slope ft/ft	Tt min	Length ft	V ft/s	Slope ft/ft	Tt min	
OFF-1	6.95 Ac.	100.00	3%	0.03	2.04	927.00	4%	5.12	0.00	0.01	0.00	0.00	2.73	1%	0.00	7.15
OFF-2	6.27 Ac.	100.00	3%	0.03	2.01	1206.00	4%	5.94	0.00	0.01	0.00	0.00	2.73	1%	0.00	7.95
OFF-3	7.69 Ac.	100.00	2%	0.03	2.41	1331.00	5%	6.44	0.00	0.01	0.00	0.00	2.73	1%	0.00	8.85
OFF-4	6.07 Ac.	100.00	6%	0.03	1.59	820.00	3%	4.87	0.00	0.01	0.00	0.00	2.73	1%	0.00	6.46
EX-1	0.40 Ac.	100.00	3%	0.03	2.29	0.00	1%	0.00	0.00	0.01	0.00	1.00	2.73	1%	0.01	5.00

GROVE EQ TANK Existing Runoff (Q) Calculations- Rational Method

D.A. Number	Drainage Area (Ac)	TOTAL I.C. (%)	Comp. C ₂	Comp. C ₁₉	Comp. C ₂₅	Comp. C ₁₀₀	TOTAL T _c (Min)	i ₂ (in/hr)	i ₁₉ (in/hr)	i ₂₅ (in/hr)	i ₁₀₀ (in/hr)	Q ₂ (cfs)	Q ₁₉ (cfs)	Q ₂₅ (cfs)	Q ₁₀₀ (cfs)
OFF-1	6.95	24%	0.43	0.49	0.53	0.60	7.2	5.69	8.63	10.59	13.83	17.02	29.28	39.05	58.17
OFF-2	6.27	35%	0.48	0.54	0.58	0.66	8.0	5.49	8.33	10.22	13.34	16.36	27.97	37.11	54.85
OFF-3	7.69	13%	0.39	0.44	0.48	0.55	8.8	5.29	8.02	9.84	12.83	15.67	27.08	36.35	54.69
OFF-4	6.07	24%	0.43	0.49	0.53	0.60	6.5	5.87	8.92	10.95	14.30	15.27	26.30	35.08	52.29
EX-1	0.40	29%	0.45	0.51	0.55	0.63	5.0	6.31	9.61	11.79	15.42	1.15	1.97	2.53	3.91

Attachment I
Inspection and Maintenance for BMPs

Inspection and Maintenance for BMPs

Personnel Responsible for Inspections

The agent that performs the inspections should be knowledgeable of this general permit, familiar with the construction site, and knowledgeable of the SWPPP for the site. The contractor is to provide an inspector with a CPESC, CESSWI, or CISEC certification. Documentation of the inspector's qualifications is to be included in the attached Inspector Qualifications Log.

Inspection Schedule

The primary operator is required to choose one of the two inspections listed below.

- ☐ **Option 1:** Once every seven calendar days. If this alternative schedule is developed, then the inspection must occur regardless of whether or not there has been a rainfall event since the previous inspection.
- ☐ **Option 2:** Once every 14 calendar days and within 24 hours of the end of a storm event of two inches or greater.

The inspections may occur on either schedule provided that documentation reflects the current schedule and that any changes to the schedule are conducted in accordance with the following provisions: the schedule may be changed a maximum of one time each month, the schedule change must be implemented at the beginning of a calendar month, and the reason for the schedule change must be documented (e.g., end of “dry” season and beginning of “wet” season).

If option 2 is the chosen frequency of inspections a rain gauge must be properly maintained on site or the storm event information from a weather station that is representative of the site location. For any day of rainfall during normal business hours that measures 0.25 inches or greater, proper documentation of the total rainfall measured for that day must be recorded.

Personnel provided by the permittee must inspect:

- disturbed areas of the construction site that have not been finally stabilized;
- areas used for storage of materials that are exposed to precipitation;
- structural controls (for evidence of, or the potential for, pollutants entering the drainage system);
- sediment and erosion control measures identified in the SWP3 (to ensure they are operating correctly); and
- locations where vehicles enter or exit the site (for evidence of off-site sediment tracking).

Reductions in Inspection Frequency

Where sites have been finally or temporarily stabilized or where runoff is unlikely due to winter conditions (e.g. site is covered with snow, ice, or frozen ground exists), inspections must be conducted at least once every month. In arid, semi-arid, or drought-stricken areas, inspections must be conducted at least once every month and within 24 hours after the end of a storm event of 0.5 inches or greater. A record of the total rainfall measured, as well as the approximate beginning and ending dates of winter or drought conditions resulting in monthly frequency of inspections in the attached Rain Gauge Log.

In the event of flooding or other uncontrollable situations which prohibit access to the inspection sites, inspections must be conducted as soon as access is practicable.

Inspection Report Forms

Use the Inspection Report Forms given as a checklist to ensure that all required areas of the construction site are addressed. There is space to document the inspector's name as well as when the inspections regularly take place. The tables will document that the required area was inspected. (If there were any areas of concern, briefly describe them in this space with a more detailed description in the narrative section. Use the last table to document any discharges found during the inspections).

Describe how effective the installed BMPs are performing. Describe any BMP failures that were noted during the investigation and describe any maintenance required due to the failure. If new BMPs are needed as the construction site changes, the inspector can use the space at the bottom of the section to list BMPs to be implemented before the next inspection.

Describe the inspector's qualifications, how the inspection was conducted, and describe any areas of non-compliance in detail. If an inspection report does not identify any incidents of non-compliance, then it must contain a certifying signature stating that the facility or site is in compliance. The report must be signed by a person and in a manner required by 30 TAC 305.128. There is space at the end of the form to allow for this certifying signature.

Whenever an inspection shows that BMP modifications are needed to better control pollutants in runoff, the changes must be completed within seven calendar days following the inspection. If existing BMPs are modified or if additional BMPs are needed, you must describe your implementation schedule, and wherever possible, make the required BMP changes before the next storm event.

The Inspection Report Form functions as the required report and must be signed in accordance with TCEQ rules at 30 TAC 305.128.

Corrective Action

Personnel Responsible for Corrective Actions

Both Primary and Secondary Operators are responsible for maintaining all necessary Corrective Actions. If an individual is specifically identified as the responsible party for modifying the contact information for that individual should be documented in the attached Inspector Qualifications Log.

Corrective Action Forms

The Temporary BMPs must be modified based on the results of inspections, as necessary, to better control pollutants in runoff. Revisions must be completed within seven (7) calendar days following the inspection. If existing BMPs are modified or if additional BMPs are necessary, an implementation schedule must be described in the attached forms and wherever possible those changes implemented before the next storm event. If implementation before the next anticipated storm event is impracticable, these changes must be implemented as soon as practicable. Actions taken as a result of inspections must be properly documented by completing the corrective action forms given.

Maintenance

Below are some maintenance practices to be used to maintain erosion and sediment controls:

- All measures will be maintained in good working order. The operator should correct any damage or deficiencies as soon as practicable after the inspection, but in no case later than seven (7) calendar days after the inspection.
- Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily). See Attachment A: Spill Response Actions.
- BMP Maintenance (as applicable)
- For perimeter controls such as silt fences, berms, etc., the trapped sediment must be removed before it reaches 50% of the above-ground height.
- Silt fence will be inspected for depth of sediment, tears, to see if the fabric is securely attached to the fence posts, and to see that the fence posts are firmly in the ground.
- Temporary and permanent seeding and planting will be inspected for bare spots, washouts, and healthy growth.
- If sediment escapes the site, accumulations must be removed at a frequency that minimizes off-site impacts, and prior to the next rain event, if feasible. If the permittee does not own or operate

the off-site conveyance, then the permittee must to work with the owner or operator of the property to remove the sediment.

- Locations where vehicles enter or exit the site must be inspected for evidence of off-site sediment tracking.

To maintain the above practices, the following will be performed:

- Maintenance and repairs will be conducted before the next anticipated storm event or as necessary to maintain the continued effectiveness of storm water controls. Following an inspection, deficiencies should be corrected no later than seven (7) calendar days after the inspection.

BMP-Specific Inspection and Maintenance Schedules

Temporary Seeding

- Temporary Seeding should be inspected weekly and after each rain event to locate and repair any erosion.
- Erosion from storms or other damage should be repaired as soon as practical by regrading the area and applying new seed.
- If the vegetated cover is less than 80%, the area should be reseeded.

Offsite Vehicle Tracking Controls

- The entrance should be maintained in a condition, which will prevent tracking or flowing of sediment onto public rights-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment.
- All sediment spilled, dropped, washed or tracked onto public rights-of-way should be removed immediately by contractor.
- When necessary, wheels should be cleaned to remove sediment prior to entrance onto public right-of-way.
- When washing is required, it should be done on an area stabilized with crushed stone that drains into an approved sediment trap or sediment basin.
- All sediment should be prevented from entering any storm drain, ditch or water course by using approved methods.

Sediment Control Fence

- Inspect all fencing weekly, and after any rainfall.
- Remove sediment when buildup reaches 6 inches.
- Replace any torn fabric or install a second line of fencing parallel to the torn section.
- Replace or repair any sections crushed or collapsed in the course of construction activity. If a section of fence is obstructing vehicular access, consider relocating it to a spot where it will provide equal protection, but will not obstruct vehicles. A triangular filter dike may be preferable to a silt fence at common vehicle access points.
- When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.

Concrete Washout

- Inspect all washout facilities daily and after significant rainfall event to check for leaks and assess the condition of plastic linings and sidewalls.
- Any damage to the washout container should be repaired promptly to ensure its effectiveness.

Inspector Qualifications Log*

Inspector Name: _____
Qualifications (Check as appropriate and provide description):
☐ Training Course _____
☐ Supervised Experience _____
☐ Other _____

Inspector Name: _____
Qualifications (Check as appropriate and provide description):
☐ Training Course _____
☐ Supervised Experience _____
☐ Other _____

Inspector Name: _____
Qualifications (Check as appropriate and provide description):
☐ Training Course _____
☐ Supervised Experience _____
☐ Other _____

Inspector Name: _____
Qualifications (Check as appropriate and provide description):
☐ Training Course _____
☐ Supervised Experience _____
☐ Other _____

Inspector Name: _____
Qualifications (Check as appropriate and provide description):
☐ Training Course _____
☐ Supervised Experience _____
☐ Other _____

Inspector Name: _____
Qualifications (Check as appropriate and provide description):
☐ Training Course _____
☐ Supervised Experience _____
☐ Other _____

** The agent that performs the inspections should be knowledgeable of this general permit, familiar with the construction site, and knowledgeable of the SWPPP for the site. The contractor is to provide an inspector with a CPESC, CESSWI, or CISEC certification.*

Amendment Log

[illegible]

Construction Activity Sequence Log

Name of Operator	Projected dates Month/year	Activity Disturbing Soil clearing, excavation, etc.	Location on-site where activity will be conducted	Acreage being disturbed

*Construction activity sequences for linear projects may be conducted on a rolling basis. As a result, construction activities may be at different stages at different locations in the project area. The Contractor is required to complete and update the schedule and adjust as necessary.

Stormwater Control Installation and Removal Log

[illegible]

Stabilization Activities Log

[illegible]

Stabilization and erosion control practices may include, but are not limited to: establishing temporary or permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, and protecting existing trees and vegetation. List practices used where they are located, when they will be implemented, and whether they are temporary (interim) or permanent.

Inspection Frequency Log

[illegible]

Rain Gauge Log

[illegible]

General Information					
Name of Project		Tracking No.		Inspection Date	
Inspector Name, Title & Contact Information					
Present Phase of Construction					
Inspection Location (if multiple inspections are required, specify location where this inspection is being conducted)					
Inspection Frequency Standard Frequency: <input type="checkbox"/> Weekly <input type="checkbox"/> Every 14 days and within 24 hours of a 0.25" rain Increased Frequency: <input type="checkbox"/> Every 7 days and within 24 hours of a 0.25" rain Reduced Frequency: <input type="checkbox"/> Once per month (for stabilized areas) <input type="checkbox"/> Once per month and within 24 hours of a 0.25" rain (for arid, semi-arid, or drought-stricken areas during seasonally dry periods or during drought) <input type="checkbox"/> Once per month (for frozen conditions where earth-disturbing activities are being conducted)					
Was this inspection triggered by a 0.25" storm event? <input type="checkbox"/> Yes <input type="checkbox"/> No If yes, how did you determined whether a 0.25" storm event has occurred? <input type="checkbox"/> Rain gauge on site <input type="checkbox"/> Weather station representative of site. Specify weather station source: Total rainfall amount that triggered the inspection (in inches):					
Unsafe Conditions for Inspection Did you determine that any portion of your site was unsafe for inspection? <input type="checkbox"/> Yes <input type="checkbox"/> No If "yes", complete the following: <input type="checkbox"/> Describe the conditions that prevented you from conducting the inspection in this location: <input type="checkbox"/> Location(s) where conditions were found:					

Condition and Effectiveness of Erosion and Sediment (E&S) Controls				
Type/Location of E&S Control	Repairs or Other Maintenance Needed?	Corrective Action Required?	Date on Which Maintenance or Corrective Action First Identified?	Notes
1.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
2.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
3.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
4.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
5.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
6.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
7.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
8.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
9.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
10.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		

Condition and Effectiveness of Pollution Prevention (P2) Practices				
Type/Location of P2 Practices	Repairs or Other Maintenance Needed?	Corrective Action Required?	Identification Date	Notes
1.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
2.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
3.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
4.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
5.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
6.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
7.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
8.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
9.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		
10.	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No		

Stabilization of Exposed Soil			
Stabilization Area	Stabilization Method	Have You Initiated Stabilization?	Notes
1.		<input type="checkbox"/> YES <input type="checkbox"/> NO If yes, provide date:	
2.		<input type="checkbox"/> YES <input type="checkbox"/> NO If yes, provide date:	
3.		<input type="checkbox"/> YES <input type="checkbox"/> NO If yes, provide date:	
4.		<input type="checkbox"/> YES <input type="checkbox"/> NO If yes, provide date:	
5.		<input type="checkbox"/> YES <input type="checkbox"/> NO If yes, provide date:	
Description of Discharges			
Was a stormwater discharge or other discharge occurring from any part of your site at the time of the inspection? <input type="checkbox"/> Yes <input type="checkbox"/> No If “yes”, provide the following information for each point of discharge:			
Discharge Location	Observations		
1.	Describe the discharge: At points of discharge and the channels and banks of surface waters in the immediate vicinity, are there any visible signs of erosion and/or sediment accumulation that can be attributed to your discharge? <input type="checkbox"/> Yes <input type="checkbox"/> No If yes, describe what you see, specify the location(s) where these conditions were found, and indicate whether modification, maintenance, or corrective action is needed to resolve the issue:		
2.	Describe the discharge: At points of discharge and the channels and banks of surface waters in the immediate vicinity, are there any visible signs of erosion and/or sediment accumulation that can be attributed to your discharge? <input type="checkbox"/> Yes <input type="checkbox"/> No If yes, describe what you see, specify the location(s) where these conditions were found, and indicate whether modification, maintenance, or corrective action is needed to resolve the issue:		
3.	Describe the discharge: At points of discharge and the channels and banks of surface waters in the immediate vicinity, are there any visible signs of erosion and/or sediment accumulation that can be attributed to your discharge? <input type="checkbox"/> Yes <input type="checkbox"/> No If yes, describe what you see, specify the location(s) where these conditions were found, and indicate whether modification, maintenance, or corrective action is needed to resolve the issue:		

Contractor or Subcontractor Certification and Signature

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

Signature of Contractor or Subcontractor: _____ **Date:** _____

Printed Name and Affiliation: _____

Certification and Signature by Permittee

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

**Signature of Permittee or
"Duly Authorized Representative":** _____ **Date:** _____

Printed Name and Affiliation: _____

Section A – Initial Report				
(Complete this section <u>within 24 hours</u> of discovering the condition that triggered corrective action)				
Name of Project		Tracking No.		Today's Date
Date Problem First Discovered			Time Problem First Discovered	
Name and Contact Information of Individual Completing this Form				
<p>What site conditions triggered the requirement to conduct corrective action:</p> <p><input type="checkbox"/> A required stormwater control was never installed, was installed incorrectly, or not in accordance with the requirements in Part 2 and/or 3</p> <p><input type="checkbox"/> The stormwater controls that have been installed and maintained are not effective enough for the discharge to meet applicable water quality standards</p> <p><input type="checkbox"/> A prohibited discharge has occurred or is occurring</p> <p>Provide a description of the problem:</p> <p>Deadline for completing corrective action (<i>Enter date that is either: (1) no more than 7 calendar days after the date you discovered the problem, or (2) if it is infeasible to complete work within the first 7 days, enter the date that is as soon as practicable following the 7th day</i>):</p> <p>If your estimated date of completion falls after the 7-day deadline, explain (1) why you believe it is infeasible to complete work within 7 days, and (2) why the date you have established for making the new or modified stormwater control operational is the soonest practicable timeframe:</p>				
Section B – Corrective Action Progress				
(Complete this section <u>no later than 7 calendar days</u> after discovering the condition that triggered corrective action)				
Section B.1 – Why the Problem Occurred				
Cause(s) of Problem (Add an additional sheet if necessary)			How This Was Determined and the Date You Determined the Cause	
1.			1.	
2.			2.	
3.			3.	
Section B.2 – Stormwater Control Modifications to be Implemented to Correct the Problem				
List of Stormwater Control Modification(s) Needed to Correct Problem (Add an additional sheet if necessary)	Completion Date	SWPPP Update Necessary?	Notes	
1.		<input type="checkbox"/> Yes <input type="checkbox"/> No Date:		
2.		<input type="checkbox"/> Yes <input type="checkbox"/> No Date:		
3.		<input type="checkbox"/> Yes <input type="checkbox"/> No Date:		

Section A – Initial Report				
(Complete this section <u>within 24 hours</u> of discovering the condition that triggered corrective action)				
Name of Project		Tracking No.		Today's Date
Date Problem First Discovered			Time Problem First Discovered	
Name and Contact Information of Individual Completing this Form				
<p>What site conditions triggered the requirement to conduct corrective action:</p> <p><input type="checkbox"/> A required stormwater control was never installed, was installed incorrectly, or not in accordance with the requirements in Part 2 and/or 3</p> <p><input type="checkbox"/> The stormwater controls that have been installed and maintained are not effective enough for the discharge to meet applicable water quality standards</p> <p><input type="checkbox"/> A prohibited discharge has occurred or is occurring</p> <p>Provide a description of the problem:</p> <p>Deadline for completing corrective action (<i>Enter date that is either: (1) no more than 7 calendar days after the date you discovered the problem, or (2) if it is infeasible to complete work within the first 7 days, enter the date that is as soon as practicable following the 7th day</i>):</p> <p>If your estimated date of completion falls after the 7-day deadline, explain (1) why you believe it is infeasible to complete work within 7 days, and (2) why the date you have established for making the new or modified stormwater control operational is the soonest practicable timeframe:</p>				
Section B – Corrective Action Progress				
(Complete this section <u>no later than 7 calendar days</u> after discovering the condition that triggered corrective action)				
Section B.1 – Why the Problem Occurred				
Cause(s) of Problem (Add an additional sheet if necessary)			How This Was Determined and the Date You Determined the Cause	
1.			1.	
2.			2.	
3.			3.	
Section B.2 – Stormwater Control Modifications to be Implemented to Correct the Problem				
List of Stormwater Control Modification(s) Needed to Correct Problem (Add an additional sheet if necessary)	Completion Date	SWPPP Update Necessary?	Notes	
1.		<input type="checkbox"/> Yes <input type="checkbox"/> No Date:		
2.		<input type="checkbox"/> Yes <input type="checkbox"/> No Date:		
3.		<input type="checkbox"/> Yes <input type="checkbox"/> No Date:		

Contractor or Subcontractor Certification and Signature

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

Signature of Contractor or Subcontractor: _____ **Date:** _____

Printed Name and Affiliation: _____

Certification and Signature by Permittee

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

**Signature of Permittee or
"Duly Authorized Representative":** _____ **Date:** _____

Printed Name and Affiliation: _____

Attachment J
***Schedule of Interim and Permanent Soil
Stabilization Practices***

Schedule of Interim and Permanent Soil Stabilization

Construction practices shall disturb the minimal amount of existing ground cover as required for land clearing, grading, and construction activity for the shortest amount of time possible to minimize the potential of erosion and sedimentation from the site. Existing vegetation shall be maintained and left in place until it is necessary to disturb for construction activity.

Records of the following shall be maintained:

- a) The dates when major grading activities occur;
- b) The dates when construction activities temporarily or permanently cease on a portion of the site; and
- c) The dates when stabilization measures are initiated.

Stabilization measures must be initiated as soon as practical in portions of the site where construction activities have temporarily or permanently ceased, and except as provided in the following, must be initiated no more than fourteen (14) days after the construction activity in that portion of the site has temporarily or permanently ceased:

Where the initiation of stabilization measures by the 14th day after construction activity temporarily or permanently ceased is precluded by snow cover or frozen ground conditions, stabilization measures must be initiated as soon as practical.

Where construction activity on a portion of the site is temporarily ceased and earth disturbing activities will be resumed within twenty-one (21) days, temporary stabilization measures do not have to be initiated on that portion of the site.

In arid areas (areas with an average rainfall of 0-10 inches), semiarid areas (areas with an average annual rainfall of 10 to 20 inches), and areas experiencing droughts where the initiation of stabilization measures by the 14th day after construction activity has temporarily or permanently ceased is precluded by seasonably arid conditions, stabilization measures must be initiated as soon as practical.

SECTION 7: PERMANENT STORMWATER

Permanent Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(C), (D)(li), (E), and (5), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.


Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Permanent Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Deirdre Lynch, P.E.

Date: January 2025

Signature of Customer/Agent



Regulated Entity Name: Vintage Oaks at the Vineyard WWTF

Permanent Best Management Practices (BMPs)

Permanent best management practices and measures that will be used during and after construction is completed.

1. ☒ Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
☐ N/A
2. ☒ These practices and measures have been designed, and will be constructed, operated, and maintained to ensure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
☒ The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.

☐ A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: _____

☐ N/A

3. ☒ Owners must ensure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.

☐ N/A

4. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

☐ The site will be used for low density single-family residential development and has 20% or less impervious cover.

☐ The site will be used for low density single-family residential development but has more than 20% impervious cover.

☒ The site will not be used for low density single-family residential development.

5. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

☐ **Attachment A - 20% or Less Impervious Cover Waiver.** The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.

☐ The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.

☒ The site will not be used for multi-family residential developments, schools, or small business sites.

6. ☒ **Attachment B - BMPs for Upgradient Stormwater.**

- ☐ A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
 - ☐ No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
 - ☒ Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
7. ☒ **Attachment C - BMPs for On-site Stormwater.**
- ☒ A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
 - ☐ Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
8. ☐ **Attachment D - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is attached. Each feature identified in the Geologic Assessment as sensitive has been addressed.
- ☒ N/A
9. ☒ The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.
- ☒ The permanent sealing of or diversion of flow from a naturally-occurring sensitive feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed.
 - ☐ **Attachment E - Request to Seal Features.** A request to seal a naturally-occurring sensitive feature, that includes, for each feature, a justification as to why no reasonable and practicable alternative exists, is attached.
10. ☒ **Attachment F - Construction Plans.** All construction plans and design calculations for the proposed permanent BMP(s) and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. The plans are attached and, if applicable include:
- ☒ Design calculations (TSS removal calculations)
 - ☒ TCEQ construction notes
 - ☒ All geologic features
 - ☒ All proposed structural BMP(s) plans and specifications
- ☐ N/A

11. ☒ **Attachment G - Inspection, Maintenance, Repair and Retrofit Plan.** A plan for the inspection, maintenance, repairs, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan includes all of the following:
- ☒ Prepared and certified by the engineer designing the permanent BMPs and measures
 - ☒ Signed by the owner or responsible party
 - ☒ Procedures for documenting inspections, maintenance, repairs, and, if necessary retrofit
 - ☒ A discussion of record keeping procedures
- ☐ N/A
12. ☐ **Attachment H - Pilot-Scale Field Testing Plan.** Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
- ☒ N/A
13. ☐ **Attachment I - Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that results in water quality degradation.
- ☒ N/A

Responsibility for Maintenance of Permanent BMP(s)

Responsibility for maintenance of best management practices and measures after construction is complete.

14. ☒ The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
- ☐ N/A
15. ☐ A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.
- ☒ N/A

Attachment B
BMPs for Upgradient Stormwater

BMPs for Upgradient Stormwater

The proposed project will increase impervious cover by 200 square feet. Due to the project's limited scope, there is minimal to no impact to the existing drainage patterns. As a result, there will be no adverse impact on properties located downstream and a permanent BMP will not be required for upgradient stormwater.

Attachment C
BMPs for On-site Stormwater



BMPs for On-Site Stormwater

An existing 50' natural VFS surrounds the WWTF site and is treated accordingly. The existing 15' engineered VFS will remain as it is while the natural VFS will be extended to account for the conflict with the proposed process tank. The vegetative filter strip will effectively meet the required overall removal of 80% of the increase in Total Suspended Solids.

Attachment F

Construction Plans

K:\SAU_MRL\06927520_CLWSC - Grove EQ Tank\CAD\PLANSHEETS\TEC VFS PLAN.dwg 1/20/2025 4:45 PM



LEGEND

— X — X — X —	PROPOSED FENCE
— SF —	SILT FENCE
— LOC — LOC —	LIMITS OF CONSTRUCTION
[Pattern: Dashed lines]	PROPOSED CONSTRUCTION ENTRANCE
[Pattern: Stippled]	PROPOSED CONCRETE WASHOUT
[Pattern: Diagonal lines]	NATURAL VEGETATIVE FILTER STRIP
[Pattern: Horizontal lines]	ENGINEERED VEGETATIVE FILTER STRIP
— — — —	PROPERTY BOUNDARY
- - - - -	APPROXIMATE EXISTING CONTOURS

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_d = 27.2(A_i \times P)$

where:

L_d TOTAL PROJECT = Required TSS removal resulting from the proposed development = 80% of increased load
 A_i = Net increase in impervious area for the project
 P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

Total project area included in plan	41.12	acres
Predevelopment impervious area within the limits of the plan	1.12	acres
Total post-development impervious area within the limits of the plan	1.125	acres
Total post-development impervious cover fraction	0.03	
P	33	inches

L_d TOTAL PROJECT = 4 lbs.

4. Calculate Maximum TSS Load Removed (L_R) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7: $L_R = (BMP \text{ efficiency}) \times P \times (A_i \times 34.6 + A_p \times 0.54)$

where:

A_c = Total On-Site drainage area in the BMP catchment area
 A_i = Impervious area proposed in the BMP catchment area
 A_p = Pervious area remaining in the BMP catchment area
 L_R = TSS Load removed from this catchment area by the proposed BMP

A_c	1.21	acres
A_i	0.005	acres
A_p	1.21	acres
L_R	23	lbs

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

Desired L_d THIS BASIN = 4 lbs.

F = 0.17

16. Vegetated Filter Strips

Designed as Required in RG-348

Pages 3-55 to 3-57

There are no calculations required for determining the load or size of vegetative filter strips. The 80% removal is provided when the contributing drainage area does not exceed 72 feet (direction of flow) and the sheet flow leaving the impervious cover is directed across 15 feet of engineered filter strips with maximum slope of 20% or across 50 feet of natural vegetation with a maximum slope of 10%. There can be a break in grade as long as no slope exceeds 20%.

NOTES:

- A LAYER OF FILTER FABRIC TOPPED BY A 3" - 4" LAYER OF STONE AGGREGATE (E.G ASTM NO. 57 AGGREGATE) TO A DISTANCE OF 3 FEET FROM THE LEAD LEVEL SPREADER LIP. A 3- FOOT WIDE STRIP OF EROSION CONTROL MATTING CAN BE USED IN PLACE OF THE FILTER FABRIC AND ASTM NO. 57 AGGREGATE COMBINATION.

Kimley»Horn

Firm No. F-528
3301 Southwest Pkwy, Bldg 3, Suite 100, Austin TX, 78735
P: 512-646-2237



GROVE EQ TANK

VEGETATIVE FILTER
STRIP PLAN AND CALCS

DATE:	JANUARY 2025
DESIGN:	DAL
DRAWN:	IM
CHECKED:	IMC
KHA NO.:	069277520

SHEET

C7

Attachment G
Inspection, Maintenance, Repair, and
Retrofit Plan

Inspection, Maintenance, Repair and Retrofit Plan

The inspection and maintenance plan outlines the procedures necessary to maintain the performance of the Permanent Best Management Practices for this project. It should be noted that the plan provides guidelines that may have to be adjusted dependent on site specific and weather related conditions.

It is the responsibility of the owner to provide the inspections and maintenance as outlined in the plan for the duration of the project. The owner will maintain this responsibility until it is assumed or transferred to another entity in writing. If the property is leased or sold, the responsibility for the maintenance will be required to be transferred through the lease agreement, binding covenants, closing documents, or other binding legal instrument.

Disposal of accumulated silt shall be accomplished following Texas Commission on Environmental Quality guidelines and specifications.

Maintenance records shall be kept on the installation, maintenance, or removal of items necessary for the proper operation of the facilities. All inspections shall be documented.

An amended copy of this document will be provided to the Texas Commission on Environmental Quality within thirty (30) days of any changes in the following information.

Responsible Party: Texas Water Resources LLC
Mailing Address: 1399 Sattler Road
City, State: Canyon Lake, TX Zip: 78132
Telephone: (408) 314-9818 Fax: N/A

I, the owner, have read and understand the requirements of the attached Inspection and Maintenance Plan for the proposed Permanent Best Management Practices for my project. I acknowledge that I will maintain responsibility for the implementation and execution of the plan until the responsibility is transferred to or assumed by another party in writing through a binding legal instrument.

Signature of Responsible Party Andrea Williams Date 30/01/2025

This Maintenance Plan is based on TCEQ Maintenance Guidelines.

By: Deirdre Lynch Date 01/27/2025
Deirdre Lynch, P.E.






Grove EQ WPAP Modification Owner Maintenance

Final Audit Report

2025-01-30

Created:	2025-01-30
By:	Valerie Wernert (Valerie.Wernert@txwaterco.com)
Status:	Signed
Transaction ID:	CBJCHBCAABAAJMSmJi_IJv0K-VzjmawYMYQJDS4WL16r

"Grove EQ WPAP Modification Owner Maintenance" History

-  Document created by Valerie Wernert (Valerie.Wernert@txwaterco.com)
2025-01-30 - 7:07:01 PM GMT
-  Document emailed to Aundrea Williams (Aundrea.Williams@txwaterco.com) for signature
2025-01-30 - 7:07:05 PM GMT
-  Email viewed by Aundrea Williams (Aundrea.Williams@txwaterco.com)
2025-01-30 - 7:42:40 PM GMT
-  Document e-signed by Aundrea Williams (Aundrea.Williams@txwaterco.com)
Signature Date: 2025-01-30 - 8:50:44 PM GMT - Time Source: server
-  Agreement completed.
2025-01-30 - 8:50:44 PM GMT

Inspection and Maintenance Guidelines for Vegetative Filter Strip

Mowing. Unmowed vegetative filter strips are preferred. If mowed the cutting height shall be set to a minimum of four (4) inches for turfgrass and a minimum of 18 inches for bunchgrass. Grass clippings must be removed in order to prevent export of nutrients.

Erosion control. The basin side slopes and embankment all may periodically suffer from erosion. To correct these problems, corrective action, such as regrading and revegetation, may be necessary. Correction of erosion control should take place whenever required based on the periodic inspections.

Sediment Removal. A properly designed vegetative filter strip may still accumulate quantities of sediment over time. The accumulated sediment can detract from the appearance of the facility and reduce the pollutant removal. Accumulated Sediment shall be removed when it exceeds 2 inches in depth.

SECTION 8: ADDITIONAL FORMS

Agent Authorization Form
For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

I Aundrea Williams
Print Name
President
Title - Owner/President/Other
of SJWTX, Inc.
Corporation/Partnership/Entity Name
have authorized Deirdre Lynch, P.E.
Print Name of Agent/Engineer
of Kimley-Horn and Associates, Inc.
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

Andrea Williams
Applicant's Signature


1/16/2025
Date

THE STATE OF TEXAS §

County of COMAL §

BEFORE ME, the undersigned authority, on this day personally appeared Andrea Williams known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 16 day of January, 2025



Valerie Wernert
NOTARY PUBLIC
Valerie Wernert
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 08/01/2028



TCEQ Core Data Form

For detailed instructions on completing this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input type="checkbox"/> Other	
2. Customer Reference Number (if issued)	Follow this link to search for CN or RN numbers in Central Registry**	3. Regulated Entity Reference Number (if issued)
CN 602969396		RN 108877069

SECTION II: Customer Information

4. General Customer Information		5. Effective Date for Customer Information Updates (mm/dd/yyyy)		
<input type="checkbox"/> New Customer <input checked="" type="checkbox"/> Update to Customer Information <input checked="" type="checkbox"/> Change in Regulated Entity Ownership				
<input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)				
<i>The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).</i>				
6. Customer Legal Name (If an individual, print last name first: eg: Doe, John)			<i>If new Customer, enter previous Customer below:</i>	
SJWTX, Inc.				
7. TX SOS/CPA Filing Number	8. TX State Tax ID (11 digits)	9. Federal Tax ID (9 digits)	10. DUNS Number (if applicable)	
0800542934	12040132529			
11. Type of Customer:	<input checked="" type="checkbox"/> Corporation	<input type="checkbox"/> Individual	Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited	
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> Local <input type="checkbox"/> State <input type="checkbox"/> Other	<input type="checkbox"/> Sole Proprietorship	<input type="checkbox"/> Other:		
12. Number of Employees		13. Independently Owned and Operated?		
<input type="checkbox"/> 0-20 <input checked="" type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher		<input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
14. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following				
<input type="checkbox"/> Owner <input type="checkbox"/> Operator <input checked="" type="checkbox"/> Owner & Operator <input type="checkbox"/> Other:				
<input type="checkbox"/> Occupational Licensee <input type="checkbox"/> Responsible Party <input type="checkbox"/> VCP/BSA Applicant				
15. Mailing Address:	PO Box 1742			
	City	Canyon Lake	State	TX
			ZIP	78133
			ZIP + 4	
16. Country Mailing Information (if outside USA)			17. E-Mail Address (if applicable)	
			Aundrea.williams@txwaterco.com	
18. Telephone Number		19. Extension or Code		20. Fax Number (if applicable)

SECTION III: Regulated Entity Information**21. General Regulated Entity Information** (If 'New Regulated Entity' is selected, a new permit application is also required.)☐ New Regulated Entity ☐ Update to Regulated Entity Name ☒ Update to Regulated Entity Information

The Regulated Entity Name submitted may be updated, in order to meet TCEQ Core Data Standards (removal of organizational endings such as Inc, LP, or LLC).

22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)

Vintage Oaks at the Vineyard WWTF

23. Street Address of the Regulated Entity:

N/A

(No PO Boxes)

City

State

ZIP

ZIP + 4

24. County

If no Street Address is provided, fields 25-28 are required.

25. Description to Physical Location:

Located in the Vintage Oaks at the Vineyard subdivision "The Hills" off Hwy 46 in the New Braunfels ETJ, Texas

26. Nearest City

State

Nearest ZIP Code

New Braunfels

TX

78132

Latitude/Longitude are required and may be added/updated to meet TCEQ Core Data Standards. (Geocoding of the Physical Address may be used to supply coordinates where none have been provided or to gain accuracy).

27. Latitude (N) in Decimal:

29.770781

28. Longitude (W) in Decimal:

-98.259942

Degrees

Minutes

Seconds

Degrees

Minutes

Seconds

29

46

14 .81

98

15

35.79

29. Primary SIC Code**30. Secondary SIC Code****31. Primary NAICS Code****32. Secondary NAICS Code**

(4 digits)

(4 digits)

(5 or 6 digits)

(5 or 6 digits)

4941

221310

33. What is the Primary Business of this entity? (Do not repeat the SIC or NAICS description.)**34. Mailing Address:**

PO Box 1742

City

Canyon Lake

State

TX

ZIP

78133

ZIP + 4

35. E-Mail Address:

aundrea.williams@txwaterco.com

36. Telephone Number**37. Extension or Code****38. Fax Number** (if applicable)

(830) 312-4600

() -

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.


<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input checked="" type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Wastewater	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

SECTION IV: Preparer Information

40. Name:	Deirdre Lynch	41. Title:	Project Engineer
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address
(512) 596-5918		() -	Deirdre.Lynch@kimley-horn.com

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	SJWTX, Inc.	Job Title:	President
Name (In Print):	Aundrea Williams	Phone:	(830) 312- 4600
Signature:		Date:	1/14/2025

Application Fee Form

Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: Vintage Oaks at the Vineyard WWTF

Regulated Entity Location: Vintage Oaks at the Vineyard subdivision "The Hills" off HWY 46.

Name of Customer: Texas Water Company, LLC

Contact Person: Aundrea Williams

Phone: (408)-314-9818

Customer Reference Number (if issued): CN 602969396

Regulated Entity Reference Number (if issued): RN 108877069

Austin Regional Office (3373)

☐ Hays

☐ Travis

☐ Williamson

San Antonio Regional Office (3362)

☐ Bexar

☐ Medina

☐ Uvalde

☒ Comal

☐ Kinney

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to:

☐ Austin Regional Office

☒ San Antonio Regional Office

☐ Mailed to: TCEQ - Cashier

☐ Overnight Delivery to: TCEQ - Cashier

Revenues Section

12100 Park 35 Circle

Mail Code 214

Building A, 3rd Floor

P.O. Box 13088

Austin, TX 78753

Austin, TX 78711-3088

(512)239-0357

Site Location (Check All That Apply):

☒ Recharge Zone

☐ Contributing Zone

☐ Transition Zone

Type of Plan	Size	Fee Due
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	1.21 Acres	\$ 4,000.00
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: _____

Deirdre Lynch

Date: 1/24/2025

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications Contributing Zone Plans and Modifications

<i>Project</i>	<i>Project Area in Acres</i>	<i>Fee</i>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

<i>Project</i>	<i>Cost per Linear Foot</i>	<i>Minimum Fee- Maximum Fee</i>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

<i>Project</i>	<i>Cost per Tank or Piping System</i>	<i>Minimum Fee- Maximum Fee</i>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests


<i>Project</i>	<i>Fee</i>
Exception Request	\$500

Extension of Time Requests

<i>Project</i>	<i>Fee</i>
Extension of Time Request	\$150

SECTION 9: EXHIBITS

K:\SAU_WF_069277520_CLWSC - Grove EQ Tank\CAO\PLANSHEETS\WPAP DEMO.dwg 1/30/2025 4:27 PM



DEMOLITION NOTES

1. THE CONTRACTOR SHALL REMOVE ALL EXISTING STRUCTURES AS INDICATED ON THE PLANS ALONG WITH ANY SUPPORT OR APPURTENANCES.
2. REMOVE ALL FENCES, TREES, AND GUARDRAILS IN ACCORDANCE THE PLAN.
3. ANY OBJECT TO BE REMOVED, OTHER THAN ITEMS SPECIFIED TO BE SALVAGED AND RETURNED TO OWNER, SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND SHALL BE DISPOSED OF PROPERLY.
4. CONTRACTOR SHALL NOTIFY TWC INSPECTOR, PROJECT MANAGER, AND OPERATIONS TWO (2) WEEKS PRIOR TO COMMENCING DEMOLITION WORK TO SCHEDULE A SHUTDOWN AND SEQUENCING COORDINATION MEETING. CONTRACTOR IS RESPONSIBLE FOR COORDINATING THEIR WORK TO ACCOMMODATE AVAILABLE SHUT-DOWN WHERE NOTED. NO ADDITIONAL TIME OR COMPENSATION WILL BE ALLOWED DUE TO DELAYS TO MEET SHUT DOWN TIMES.



Kimley»Horn	
Firm No. F-928	Project No. P-512-04-2237
3301 Southwest Pkwy, Bldg 3, Suite 100, Austin TX, 78725	
By	Date
Revision	
No.	

GROVE EQ TANK

DEMOLITION PLAN

DATE:	JANUARY 2025
DESIGN:	DAL
DRAWN:	IM
CHECKED:	IMC
KHA NO.:	069277520

SHEET
C1