

WOODMONT HELOTES


LOTS 1 & 3, BLOCK 3, NCB 14867
(VOL. 20003, PG. 1628, O.P.R.B.C.)
SAN ANTONIO, TEXAS 78023

WATER POLLUTION PREVENTION PLAN (WPAP)

JANUARY 2025

PREPARED FOR:

Woodmont Helotes Lot Development, LLC
2100 W. 7th Street
Fort Worth, TX 76107



PREPARED BY:

MM
MEALS★MYERS
ENGINEERING & SURVEYING LLC

10906 LAUREATE DRIVE #101, SAN ANTONIO, TX 78249
PHONE: (210) 740-2483 | (830) 931-1269
TBPE NO. F-18576 | TBPLS NO. 101942291

SECTION 1.0

WATER POLLUTION ABATEMENT PLAN CHECKLIST

Water Pollution Abatement Plan Checklist

- Edwards Aquifer Application Cover Page (TCEQ-20705)
- General Information Form (TCEQ-0587)
 - Attachment A - Road Map
 - Attachment B - USGS / Edwards Recharge Zone Map
 - Attachment C - Project Description
- Geologic Assessment Form (TCEQ-0585)
 - Attachment A - Geologic Assessment Table (TCEQ-0585-Table)
 - Attachment B - Stratigraphic Column
 - Attachment C - Site Geology
 - Attachment D - Site Geologic Map(s)
- Water Pollution Abatement Plan Application Form (TCEQ-0584)
 - Attachment A - Factors Affecting Surface Water Quality
 - Attachment B - Volume and Character of Stormwater
 - Attachment C - Suitability Letter from Authorized Agent (if OSSF is proposed)
 - Attachment D - Exception to the Required Geologic Assessment (if requested)
 - Site Plan
- Temporary Stormwater Section (TCEQ-0602)
 - Attachment A - Spill Response Actions
 - Attachment B - Potential Sources of Contamination
 - Attachment C - Sequence of Major Activities
 - Attachment D - Temporary Best Management Practices and Measures
 - Attachment E - Request to Temporarily Seal a Feature (if requested)
 - Attachment F - Structural Practices
 - Attachment G - Drainage Area Map
 - Attachment H - Temporary Sediment Pond(s) Plans and Calculations
 - Attachment I - Inspection and Maintenance for BMPs
 - Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices
- Permanent Stormwater Section (TCEQ-0600)
 - Attachment A - 20% or Less Impervious Cover Waiver (if requested for multi-family, school, or small business site)
 - Attachment B - BMPs for Upgradient Stormwater
 - Attachment C - BMPs for On-site Stormwater
 - Attachment D - BMPs for Surface Streams
 - Attachment E - Request to Seal Features (if sealing a feature)
 - Attachment F - Construction Plans
 - Attachment G - Inspection, Maintenance, Repair and Retrofit Plan
 - Attachment H - Pilot-Scale Field Testing Plan (if proposed)
 - Attachment I - Measures for Minimizing Surface Stream Contamination

- Agent Authorization Form (TCEQ-0599), if application submitted by agent
- Application Fee Form (TCEQ-0574)
- Check Payable to the "Texas Commission on Environmental Quality"
- Core Data Form (TCEQ-10400)

SECTION 2.0

EDWARDS AQUIFER APPLICATION COVER PAGE

Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).

Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the Instructions to Geologists (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied the application fee will be forfeited.
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: Woodmont Helotes				2. Regulated Entity No.:				
3. Customer Name: Stephen Coslik Woodmont Helotes Academy, LLC				4. Customer No.:				
5. Project Type: (Please circle/check one)	<input checked="" type="radio"/> New	Modification			Extension		Exception	
6. Plan Type: (Please circle/check one)	<input checked="" type="radio"/> WPAP	<input type="radio"/> CZP	<input type="radio"/> SCS	<input type="radio"/> UST	<input type="radio"/> AST	<input type="radio"/> EXP	<input type="radio"/> EXT	Technical Clarification Optional Enhanced Measures
7. Land Use: (Please circle/check one)	<input type="radio"/> Residential	<input checked="" type="radio"/> Non-residential			8. Site (acres):		5.863	
9. Application Fee:	\$5,000	10. Permanent BMP(s):				Contech Jellyfish® Filter		
11. SCS (Linear Ft.):	N/A	12. AST/UST (No. Tanks):				N/A		
13. County:	Bexar	14. Watershed:				Leon Creek Watershed		

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region			
County:	Hays	Travis	Williamson
Original (1 req.)	—	—	—
Region (1 req.)	—	—	—
County(ies)	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Barton Springs/ Edwards Aquifer <input type="checkbox"/> Hays Trinity <input type="checkbox"/> Plum Creek	<input type="checkbox"/> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<input type="checkbox"/> Austin <input type="checkbox"/> Buda <input type="checkbox"/> Dripping Springs <input type="checkbox"/> Kyle <input type="checkbox"/> Mountain City <input type="checkbox"/> San Marcos <input type="checkbox"/> Wimberley <input type="checkbox"/> Woodcreek	<input type="checkbox"/> Austin <input type="checkbox"/> Bee Cave <input type="checkbox"/> Pflugerville <input type="checkbox"/> Rollingwood <input type="checkbox"/> Round Rock <input type="checkbox"/> Sunset Valley <input type="checkbox"/> West Lake Hills	<input type="checkbox"/> Austin <input type="checkbox"/> Cedar Park <input type="checkbox"/> Florence <input type="checkbox"/> Georgetown <input type="checkbox"/> Jerrell <input type="checkbox"/> Leander <input type="checkbox"/> Liberty Hill <input type="checkbox"/> Pflugerville <input type="checkbox"/> Round Rock

San Antonio Region					
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	<u>1</u>	—	—	—	—
Region (1 req.)	<u>1</u>	—	—	—	—
County(ies)	<u>1</u>	—	—	—	—
Groundwater Conservation District(s)	<input checked="" type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Trinity-Glen Rose	<input type="checkbox"/> Edwards Aquifer Authority	<input type="checkbox"/> Kinney	<input type="checkbox"/> EAA <input type="checkbox"/> Medina	<input type="checkbox"/> EAA <input type="checkbox"/> Uvalde
City(ies) Jurisdiction	<input type="checkbox"/> Castle Hills <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Helotes <input type="checkbox"/> Hill Country Village <input type="checkbox"/> Hollywood Park <input checked="" type="checkbox"/> San Antonio (SAWS) <input type="checkbox"/> Shavano Park	<input type="checkbox"/> Bulverde <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Garden Ridge <input type="checkbox"/> New Braunfels <input type="checkbox"/> Schertz	NA	<input type="checkbox"/> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

M. Tyler Meals

Print Name of Customer/Authorized Agent



01/10/2025

Signature of Customer/Authorized Agent

Date

****FOR TCEQ INTERNAL USE ONLY****

Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

SECTION 3.0

GENERAL INFORMATION FORM

General Information Form

Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This General Information Form is hereby submitted for TCEQ review. The application was prepared by:

Print Name of Customer/Agent: M. Tyler Meals

Date: 01/10/2025

Signature of Customer/Agent:



Project Information

1. Regulated Entity Name: Woodmont Helotes
2. County: Bexar
3. Stream Basin: Leon Creek
4. Groundwater Conservation District (If applicable): Edwards Aquifer Authority
5. Edwards Aquifer Zone:
☒ Recharge Zone
☐ Transition Zone
6. Plan Type:

<input checked="" type="checkbox"/> WPAP	<input type="checkbox"/> AST
<input type="checkbox"/> SCS	<input type="checkbox"/> UST
<input type="checkbox"/> Modification	<input type="checkbox"/> Exception Request

7. Customer (Applicant):

Contact Person: Stephen Coslik
Entity: Woodmont Helotes Academy, LLC
Mailing Address: 2100 West 7th Street
City, State: Forth Worth, TX
Telephone: (817) 377-7710
Email Address: scoslik@woodmont.com

Zip: 76107
FAX: _____

8. Agent/Representative (If any):

Contact Person: M. Tyler Meals
Entity: Meals-Myers Engineering & Surveying, LLC
Mailing Address: 10906 Laureate Drive, Suite 101
City, State: San Antonio, TX
Telephone: (210) 740-2483
Email Address: tyler@mealsmyers.com

Zip: 78249
FAX: _____

9. Project Location:

- ☒ The project site is located inside the city limits of San Antonio.
☐ The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of _____.
☐ The project site is not located within any city's limits or ETJ.

10. ☒ The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

Approx. 1,400 feet west of Loop 1604 intersection with FM 1560, on the south side of the FM 1560 right-of-way. Tracts can also be identified as Lot 1 and Lot 3, Block 3, NCB 14867 (Vol. 20003, Pg. 1628, OPRBC).

11. ☒ Attachment A – Road Map. A road map showing directions to and the location of the project site is attached. The project location and site boundaries are clearly shown on the map.

12. ☒ Attachment B - USGS / Edwards Recharge Zone Map. A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached. The map(s) clearly show:

- ☒ Project site boundaries.
☒ USGS Quadrangle Name(s).
☒ Boundaries of the Recharge Zone (and Transition Zone, if applicable).
☒ Drainage path from the project site to the boundary of the Recharge Zone.

13. ☒ The TCEQ must be able to inspect the project site or the application will be returned. Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment.

☒ Survey staking will be completed by this date: 01/13/2025

14. ☒ Attachment C – Project Description. Attached at the end of this form is a detailed narrative description of the proposed project. The project description is consistent throughout the application and contains, at a minimum, the following details:

- ☒ Area of the site
- ☒ Offsite areas
- ☒ Impervious cover
- ☒ Permanent BMP(s)
- ☒ Proposed site use
- ☒ Site history
- ☒ Previous development
- ☒ Area(s) to be demolished

15. Existing project site conditions are noted below:

- ☐ Existing commercial site
- ☐ Existing industrial site
- ☐ Existing residential site
- ☒ Existing paved and/or unpaved roads
- ☒ Undeveloped (Cleared)
- ☒ Undeveloped (Undisturbed/Uncleared)
- ☐ Other: _____

Prohibited Activities

16. ☒ I am aware that the following activities are prohibited on the Recharge Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
- (2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
- (3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
- (4) The use of sewage holding tanks as parts of organized collection systems; and
- (5) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
- (6) New municipal and industrial wastewater discharges into or adjacent to water in the state that would create additional pollutant loading.

17. ☒ I am aware that the following activities are prohibited on the Transition Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);

- (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
- (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

Administrative Information

18. The fee for the plan(s) is based on:


- ☒ For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur.
- ☐ For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines.
- ☐ For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems.
- ☐ A request for an exception to any substantive portion of the regulations related to the protection of water quality.
- ☐ A request for an extension to a previously approved plan.

19. ☒ Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

- ☐ TCEQ cashier
- ☐ Austin Regional Office (for projects in Hays, Travis, and Williamson Counties)
- ☒ San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

20. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

21. ☒ No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.



MEALS★MYERS
ENGINEERING & SURVEYING LLC


10906 LAUREATE DRIVE #101, SAN ANTONIO, TX 78249
PHONE: (210) 740-2483 | (830) 931-1269
TBPE No. F-18576 | TBPLS No. 101942291

ROAD MAP ATTACHMENT A

LOTS 1 & 3, BLOCK 3, NCB 14867
(VOL. 20003, PG. 1628, O.P.R.B.C.)
SAN ANTONIO, TX 78023

DATE: JANUARY 2025

SCALE: 1" = 600'



MEALS★MYERS
ENGINEERING & SURVEYING LLC

10906 LAUREATE DRIVE #101, SAN ANTONIO, TX 78249
PHONE: (210) 740-2483 | (830) 931-1269
TBPE No. F-18576 | TBPLS No. 101942291

USGS / EDWARDS RECHARGE ZONE MAP ATTACHMENT B

LOTS 1 & 3, BLOCK 3, NCB 14867
(VOL. 20003, PG. 1628, O.P.R.B.C.)
SAN ANTONIO, TX 78023

DATE: JANUARY 2025

SCALE: 1" = 2,000'

GENERAL INFORMATION FORM TCEQ-0587
ATTACHMENT C
PROJECT DESCRIPTION

The Woodmont Helotes project being developed by Woodmont Helotes Academy, LLC is located approximately 1,400 feet west of the intersection of FM 1560 and Loop 1604 on the south side of the FM 1560 right-of-way in San Antonio, TX 78023. The development includes two separate platted lots within the same subdivision – Kiddie Academy Hausman – and can be identified as Lots 1 and 3, Block 3, NCB 14867 (Vol. 20003, Pg. 1628). Lot 1 (approx. 5.113 acres) will be developed as a residential town home community consisting of 42 units, and Lot 2 (approx. 0.750 acres) will be developed as a commercial strip center with an approximately 4,500-SF building that may include a drive-thru facility at its end cap. It should be noted that another regulated entity, Kiddie Academy – Hausman (RN 11521845, CN 606030625), is also within this subdivision and is contained on Lot 2, Block 3, NCB 14867. For the purposes of this Study, we consider that runoff leaving Lot 2 (Kiddie Academy – Hausman) is “treated” and we assume no impervious cover. Additionally, the development includes no off-site areas draining onto the project site.

The project includes the addition of approximately 3.04-acres of impervious cover, with approximately 0.23-acres out of that total uncaptured by the proposed Best Management Practices (BMPs). The proposed BMP for this project is a Jellyfish® Filter unit by Contech® Engineered Solutions, LLC.

In its existing condition, stormwater runoff currently flows across the subject tract from north to south and into an onsite drainage easement or drainage easements on the adjacent tracts and converges immediately south of the southeastern corner of the subject tract. At that point, the runoff enters the FEMA 100-Year floodplain limits identified on FEMA FIRM No. 48029C0210G. The proposed development proposes to re-grade the site to funnel most of the runoff to the southern portion of the site and through the proposed Jellyfish® Filter before it enters the onsite drainage easement. The BMP will be sized to “over-treat” for the impervious cover (0.23-acres) that cannot be captured and routed into the treatment unit.

Prior to construction, temporary BMPs will be installed to include a combination of silt fencing and rock filter dams.

SECTION 4.0

GEOLOGIC ASSESSMENT FORM

GEOLOGIC ASSESSMENT (WPAP)

HELOTES RESIDENTIAL & COMMERCIAL TRACT +/- 5.863 ACRES HELOTES, TEXAS

**FROST GEOSCIENCES, INC. PROJECT NO.: FGS-E24234
DECEMBER 11, 2024**

Prepared exclusively for

**Meals Myers Engineering and Surveying
10906 Laureate Drive, Suite 101
San Antonio, TX 78249**

The logo features a large, dark blue, stylized swoosh that curves around the text. The text "Frost GeoSciences" is written in a bold, italicized, sans-serif font. The "Geo" part is in a lighter blue color, and the "Sciences" part is in a darker blue color.

Frost GeoSciences

***Geotechnical ▪ Construction Materials
Geologic ▪ Environmental***

Copies Submitted: (1) M. Tyler Meals, P.E.; Meals Myers Engineering and Surveying
(1) Electronic (pdf) Copy

TABLE OF CONTENTS

GEOLOGIC ASSESSMENT	1
STRATIGRAPHIC COLUMN	4
GEOLOGIC ASSESSMENT TABLE	5
LOCATION.....	6
METHODOLOGY.....	6
RESEARCH & OBSERVATIONS	7
<i>7.5 Minute Quadrangle Map Review</i>	7
<i>Bexar County Watersheds Map.....</i>	7
<i>Recharge/Transition Zone</i>	7
<i>100-Year Floodplain.....</i>	7
<i>Soils.....</i>	7
<i>Narrative Description of the Site Geology.....</i>	8
BEST MANAGEMENT PRACTICES	10
DISCLAIMER	10
REFERENCES	11
APPENDIX A - SITE LOCATION FIGURES	
<i>Figure 1: Site Layout</i>	
<i>Figure 2: Street Map</i>	
<i>Figure 3: USGS Topographic Map</i>	
<i>Figure 4: Bexar County Watersheds Map</i>	
<i>Figure 5: E.A.A. Edwards Aquifer Recharge Zone and Contributing Zone Map</i>	
<i>Figure 6: FEMA Flood Map</i>	
<i>Figure 7: USDA Web Soil Survey Aerial Photograph, 1 inch = 500 feet</i>	
<i>Figure 8: U.S. Geological Survey, Science Investigations Map 3366</i>	
<i>Figure 9: 2020 Aerial Photograph, 1 inch = 500 feet</i>	
<i>Figure 10: 2020 Aerial Photograph with PRFs, 1 inch = 50 feet</i>	
APPENDIX B - SITE PHOTOGRAPHS	
APPENDIX C - GEOLOGIC MAP	

GEOLOGIC ASSESSMENT

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: Chris Wickman, P.G.


Telephone: (210) 372-1315

Date: December 11, 2024

Fax: (210) 372-1318

Representing: Frost GeoSciences, Inc., TBPE #50040 (Name of Company and TBPG or TBPE registration number)

Signature of the Geologist:



Regulated Entity Name: Helotes Residential & Commercial Tract

Project Information

1. Date(s) Geologic Assessment was performed: December 10, 2024

2. Type of Project:

☒ WPAP
☐ SCS

☐ AST
☐ UST

3. Location of Project:

☒ Recharge Zone
☐ Transition Zone
☐ Contributing Zone within the Transition Zone

4. ☒ **Attachment A - Geologic Assessment Table.** Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
5. ☒ Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map

Table 1 - Soil Units, Infiltration Characteristics and Thickness

Soil Name	Group*	Thickness(feet)
Bexar	D	0-1
Crawford	D	0-1

Soil Group Definitions (Abbreviated)

- A. Soils having a high infiltration rate when thoroughly wetted.
- B. Soils having a moderate infiltration rate when thoroughly wetted.
- C. Soils having a slow infiltration rate when thoroughly wetted.
- D. Soils having a very slow infiltration rate when thoroughly wetted

6. ☒ **Attachment B – Stratigraphic Column.** A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.
7. ☒ **Attachment C – Site Geology.** A narrative description of the site-specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
8. ☒ **Attachment D – Site Geologic Map(s).** The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1": 400'
 Applicant's Site Plan Scale: 1" = 40'
 Site Geologic Map Scale: 1" = 40'
 Site Soils Map Scale (if more than 1 soil type): 1" = 500'
9. Method of collecting positional data:
 - ☒ Global Positioning System (GPS) technology.
 - ☒ Other method(s). Please describe method of data collection: 2023 Aerial Photograph
10. ☒ The project site and boundaries are clearly shown and labeled on the Site Geologic Map.
11. ☒ Surface geologic units are shown and labeled on the Site Geologic Map.

12. ☒ Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
- ☐ Geologic or manmade features were not discovered on the project site during the field investigation.
13. ☒ The Recharge Zone boundary is shown and labeled, if appropriate.
14. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section.
- ☐ There are _____ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)
- ☐ The wells are not in use and have been properly abandoned.
- ☐ The wells are not in use and will be properly abandoned.
- ☐ The wells are in use and comply with 16 TAC Chapter 76.
- ☒ There are no wells or test holes of any kind known to exist on the project site.

Administrative Information

15. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

STRATIGRAPHIC COLUMN

EXPLANATION OF HYDROSTRATIGRAPHIC UNITS

Group or Formation	Formal and informal member	Hydrologic unit or Informal hydrostratigraphic unit
Taylor Group (Pecan Gap)		Kpg
Austin Group		Ka
Eagle Ford Group		Kef
Buda Limestone		Kb
Del Rio Clay		Kdr
Georgetown Formation		Kg
Person Formation	Cyclic and marine, undivided	Kpcm
	Leached and collapsed	Kplc
	Regional dense member	Kprd
Kainer Formation	Grainstone	Kkg
	Kirschberg evaporite	Kkke
	Dolomitic	Kkd
	Basal nodular	Kkbn
Glen Rose Limestone	Upper Glen Rose Limestone	Kgrc
		Kgrcb
		Kgrue
		Kgruf
		Kgrlf
		Kgrle
	Lower Glen Rose Limestone	Kgrb
		Kgrlb
		Kgrts
		Kgrd
		Kgrr
		Kgrhc
Pearsall Formation	Hensell Sand	Kheh
	Cow Creek Limestone	Kcccc
	Hammett Shale	Khah

GEOLOGIC ASSESSMENT TABLE

PROJECT NAME: Helotes Residential & Commercial Tract

PROJECT NUMBER: FGS-E24234


LOCATION			FEATURE CHARACTERISTICS												EVALUATION			PHYSICAL SETTING		
1A	1B *	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11		12
FEATURE ID	LATITUDE	LONGITUDE	FEATURE TYPE	POINT S	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)	TOPOGRAPHY	
						X	Y	Z		10						<40	>40	<1.6	>1.6	
S-1	29° 34' 8.18"	-98° 39' 25.75"	CD	20	Kpcm	2	2	1	-	-	-	-	OFV	15	35	35		YES		HILLSIDE
S-2	29° 34' 6.85"	-98° 39' 26.46"	SC	20	Kpcm	1.5	4	1	-	-	-	-	COF	12	35	35		YES		HILLSIDE
S-3	29° 34' 10.69"	-98° 39' 28.86"	F	20	Kpcm	-	-	-	-	-	-	-	CF	10	30	30		YES		HILLSIDE

Datum: NAD 83

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30

8A INFILLING
N None, exposed bedrock
C Coarse - cobbles, breakdown, sand, gravel
O Loose or soft mud or soil, organics, leaves, sticks, dark colors
F Fines, compacted clay-rich sediment, soil profile, gray or red colors
V Vegetation. Give details in narrative description
FS Flowstone, cements, cave deposits
X Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Floodplain, Streambed



I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists.
The information presented here complies with that document and is a true representation of the conditions observed in the field.
My signature certifies that I am qualified as a geologist as defined by 30 TAC 213.

Chris Wickman, P.G.

Date: Dec. 11, 2024

TCEQ-0585-Table (Rev. 10-01-04)

Sheet 1 of 1

LOCATION

The project site is located along and south of Hausman Road (FM 1560), approximately 0.3-miles west of the intersection of Hausman Road and Loop 1604 in Helotes, Texas. An overall view of the area is shown on copies of the site plan, a street map, the U.S.G.S. Topographic Map, the EAA-Edwards Aquifer Recharge Zone and Contributing Zone Map, the FIRM Map, the U.S. Geological Survey, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas, Science Investigations Map 3366, and 2023 aerial photographs at a scale of 1"=500' and 1"=100', as well as an NRCS Web Soil Survey aerial photograph at a scale of 1"=500'. These maps are included as Figures 1 through 10 in Appendix A.

METHODOLOGY

The Geologic Assessment was performed by Chris Wickman, P.G., with Frost GeoSciences, Inc. Mr. Wickman is a Licensed Professional Geoscientist in the State of Texas (License # 10403).

Frost GeoSciences, Inc. researched the geology of the area west and northwest of the intersection of Hausman Road and Loop 1604. The research included, but was not limited to, the Bureau of Economic Geology-Geologic Atlas of Texas, San Antonio Sheet, FEMA maps, Edwards Aquifer Recharge Zone Maps, U.S.G.S. 7.5 Minute Quadrangle Maps, the U.S. Geological Survey, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas, Science Investigations Map 3366, the Geologic Map of the New Braunfels, Texas 30 X 60 Minute, the U.S.G.S. Water-Resources Investigations Report 95-4030, and the U.S.D.A. Soil Survey of Bexar County, Texas.

After reviewing the available information, a field investigation was performed to identify any geologic or man-made Potential Recharge Features (PRFs). A transect spacing of approximately 50 feet, or less depending on vegetation thickness, was used to inspect the project area. A 2023 aerial photograph, in conjunction with a hand-held Garmin GPS 73 Global Positioning System with an Estimated Potential Error ranging from 8 to 10 feet, was used to navigate around the property and identify the locations of PRFs, as recommended in the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04). The locations of any PRFs noted in the field were marked with blue and white flagging. The flagging is numbered with the same potential recharge feature I.D. # that is used on the Site Geologic Map. The Site Geologic Map, indicating the limits of the project site, and the locations of PRFs and rock outcrops noted on the project site, is included in Appendix C at the end of this report. A copy of a 2023 Aerial Photograph at an approximate scale of 1" =100' indicating the limits of the project site, and the locations of PRFs and rock outcrops noted on the project site, is included on Figure 10 in Appendix A. The Geologic Assessment Form TCEQ-0585, (Rev. 2-11-15), Stratigraphic Column, and the Geologic Assessment Table have been filled with the appropriate information for this project site and are included on pages 1 through 5.

RESEARCH & OBSERVATIONS

7.5 Minute Quadrangle Map Review

According to the U.S.G.S. 7.5 Minute Quadrangle Map, Helotes, Texas Quad (1992), the elevation across the project site is approximately 950 to 965 feet above mean sea level. The project site has a total relief of 15 feet. Runoff from the project site flows to the south into unnamed tributary of French Creek. Hausman Road is located along the northern property line of the project site. The intersection of Hausman Road and Loop 1604 is located east of the project site. The topographic map depicts the project site as largely undeveloped wooded land. A copy of the U.S.G.S. 7.5 Minute Quadrangle Map indicating the location of the project site is included on Figure 3 in Appendix A.

Bexar County Watersheds Map

According to the Bexar County Watersheds Map (2003), the project site is located within the Upper Leon Creek Watershed Area. A copy of the Bexar County Watersheds Map indicating the location of the project site is included on Figure 4 in Appendix A.

Recharge/Transition Zone

According to the E.A.A. Edwards Aquifer Recharge Zone and Contributing Zone Map, Helotes, Texas (2014), the Official Edwards Aquifer Recharge Zone Map, Helotes, Texas Sheet (1994), and the TCEQ website: Edwards Aquifer Viewer – <https://tceq.maps.arcgis.com/apps/webappviewer/index.html>, the project site is located within the Recharge Zone of the Edwards Aquifer. A copy of the E.A.A. Edwards Aquifer Recharge Zone and Contributing Zone Map indicating the location of the project site is included on Figure 5 in Appendix A.

100-Year Floodplain

The Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map for the Flood Insurance Map, Community Panel Number 48029C0210G, dated September 29, 2010, was reviewed to determine if the project site is located in areas prone to flooding. A review of the above-mentioned Panel No. indicates that the project site is located within "Zone X". According to the Panel Legend, Zone X represents areas determined to be outside the 0.2% annual chance floodplain. However, the site plan provided by Meals Myers Engineering and Surveying indicates a flood hazard area encroaching into the southeastern corner of the project site. A copy of the above referenced FIRM panel indicating the location of the project site is included on Figure 6 in Appendix A.

Soils

According to the United States Department of Agricultural (USDA) Natural Resources Conservation Service (NRCS) Soil Survey of Bexar County (1966) and the USDA NRCS Web Soil Survey (WSS) website: <https://websoilsurvey.nrcs.usda.gov>, the Site is located on the Crawford and Bexar Stony Soils (Cb). A copy of the 2018 aerial photo (approximate scale: 1"=500') obtained from the Web Soil Survey (WSS) website: <https://websoilsurvey.nrcs.usda.gov> has been included on Figure 7 in Appendix A

Crawford and Bexar Stony Soils (Cb) are very dark grayish brown to reddish brown clay. They are stony clay in texture and are shallow to moderately deep over hard limestone. These soils are extensive in the northern part of the county. The surface layer is non-calcareous, about 8 inches thick, and very dark grayish brown or very dark

brown. It has fine, subangular blocky and granular structure. When moist, this layer is very firm but breaks easily to a mass of fine clods. When dry, is very hard and contains many large cracks. Angular fragments of chert and limestone are common. These fragments may range in size from a quarter of an inch to 24 inches in diameter. The subsurface layer is dense, angular blocky clay. This layer is neutral or slightly acidic, but it may be limy in the lower parts. It is about 26 inches thick and either overlies a thin layer of yellowish red to pale brown, limy clay or, if the limy layer is lacking, rests on hard, fractured limestone. Crawford soils are naturally well drained. Internal drainage and permeability vary according to moisture content. Water moves rapidly when the soil is dry and cracked, but very slowly when the soil is wet. This soil has a USDA Texture Classification of Cherty Clay Loam to Loam. The Unified Classification is CG or CL. The AASHTO Classification is A-2, A-4, or A-6. This soil has an average permeability from 1.0 to 1.5 inches/hour.

Narrative Description of the Site Geology

Based on a visual inspection of the ground surface, the overall potential for fluid flow from the project site into the Edwards Aquifer appears to be low. The locations of the PRFs are identified on the 2023 aerial photograph on Figure 10 in Appendix A, and on the Site Geologic Map provided in Appendix C. Color photos of the project site and some of the PRFs are included in Appendix B.

PRF #S-1 consists of a non-karst closed depression infilled with clay, sand and fine soils. The hole may have been the result of a tree removed from the ground. Frost GeoSciences, Inc. rates the feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 35 on the sensitivity scale, column 10 of the Geologic Assessment Table included on page 5 of this report. Frost GeoSciences, Inc. does not consider the non-karst closed depression to be a sensitive feature.

PRF #S-2 is an elongate cavity between large limestone boulders. The cavity was filled with compact clay, fine soil and leaves. The cavity appears to have been the result of erosion of surface soils between a cluster of limestone boulders. A PVC pipe was observed crossing over the cavity. The cavity was about 4 feet long, 1.5 foot wide and 0.5 to 1 foot in depth. Frost GeoSciences rates the feature as low on figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores 32 points on the sensitivity scale, column 10 of the Geologic Assessment Table included on page 5 of this report. Frost GeoSciences, Inc. does not consider the solution cavity to be a sensitive feature.

PRF #S-3 is a fault identified crossing the southeast corner of the project site. The U.S. Geological Survey, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas, Science Investigations Map 3366 identified the fault. No obvious visual evidence of this fault, (i.e. fractured limestone outcrops observed in the vicinity of the fault) was observed associated with the fault. Based on the absence of direct visual evidence of the fault due to thick soil cover and road construction, Frost Geosciences, Inc. rates the feature as low on Figure 1 of the TCEQ-0585-Instructions (Rev. 10-01-04). The feature scores a 30 on the sensitivity scale, column 10 in the Geologic Assessment Table on page 5 of this report.

The project site is covered by moderately dense to dense stand of vegetative cover with gravel paved parking area and driveways. Structural improvements were observed on the project site. Site visit photos indicating the condition of the property at the time of the on-site inspection are included in Appendix B. Overall vegetation on the project site consisted of live oak, ashe juniper and hackberry trees with a dense undergrowth of thorny shrubs

and vines. The variations in the vegetative cover on the property are visible in the 2023 aerial photo on Figures 9 and 10 in Appendix A. A copy of the site layout indicating the boundary of the project site and the elevations is included on the Site Geologic Map in Appendix C of this report.

According to the U.S. Geological Survey, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas, Science Investigations Map 3366 and the Geologic Map of the New Braunfels, Texas 30 X 60 Minute Quadrangle, the project site is located on the Cyclic and Marine member of the Edwards Person limestone (Kpcm). In addition, a fault was indicated crossing the northern portion of the project site (PRF S-3). This fault was not indicated on the Bureau of Economic Geology Geologic Map of New Braunfels, Texas 30 X 60 Minute Quadrangle. Indications of the fault identified by the USGS map were not observed on the project site at the time of the site reconnaissance. A copy of the U.S. Geological Survey, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas, Science Investigations Map 3366 is included on Figure 8 in Appendix A. A copy of the Stratigraphic Column highlighting the outcropping formations is included on Page 3 of this report.

The Cyclic Marine Member of the Person Formation (Kpcm) consists of limestone, dolomitic limestone, dolomite, and lesser argillaceous limestone, approximately equivalent to Segovia Formation of eastern Edwards Plateau.

According to the site plan provided by Meals Myers Engineering and Surveying, the surveyed elevations on the project site range from 951 to 970 feet. According to this survey, the total relief on the project site is approximately 19 feet. A copy of the site plan indicating the boundary of the project site and the elevations is included on the Site Plan on Figure 1 in Appendix A and the Site Geologic Map in Appendix C of this report.

BEST MANAGEMENT PRACTICES

Based on a visual inspection of the ground surface, the overall potential for fluid flow from the project site into the Edwards Aquifer appears to range from low to moderate. The potential always exists to encounter solution cavities within the subsurface during excavating activities. Frost GeoSciences, Inc. is of the opinion that it is very important for construction personnel to be informed of the potential to encounter cavities in the subsurface that lack a surface expression. Construction personnel should also be informed of the proper protocol to follow in the event a karst feature is encountered during the development of the project site.

DISCLAIMER

This report has been prepared in general accordance with the "Instructions to Geologists", TCEQ-0585-Instructions (Rev. 10-1-04) by a Licensed Texas Professional Geoscientist. All areas of the project site were carefully inspected for features that could contribute to the recharge of the Edwards Aquifer; however, this survey cannot preclude the presence of subsurface karst features that lack surface expression. This report is not intended to be a definitive investigation of all possible geologic or karst features at this site. All conclusions, opinions, and recommendations for Best Management Practices (BMP's) in this report are based on information obtained while researching the project and on the site conditions at the time of our field investigation.


This report has been prepared for the exclusive use of Meals Myers Engineering and Surveying. This report is based on available known records, a visual inspection of the project site, and the work generally accepted for a Geologic Assessment for Regulated Activities / Developments on the Edwards Aquifer Recharge / Transition Zone, relating to 30 TAC §213.5(b)(3), effective June 1, 1999.

REFERENCES

1. USGS - 7.5 Minute Topographic Quadrangle of Helotes, Texas, 1992
2. E.A.A. Edwards Aquifer Recharge Zone and Contributing Zone Map, Helotes, Texas (2014).
3. Official Edwards Aquifer Recharge Zone Map, Helotes, Texas, 1992
4. The Texas Commission on Environmental Quality (TCEQ) website: Edwards Aquifer Viewer – <https://tceq.maps.arcgis.com/apps/webappviewer/index.html>.
5. Clark, A.K., Golab, J.A. and Morris, R.R., 2016, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas, Science Investigations Map 3366, United States Geological Survey.
6. Clark, A.K., Golab, J.A. and Morris, R.R., 2016, Geologic Framework and Hydrostratigraphy of the Edwards and Trinity Aquifers within Northern Bexar and Comal Counties, Texas, United States Geological Survey.
7. Collins, Edward, W., 2000, Geologic Map of the New Braunfels 30 X 60 Minute Quadrangle, Bureau of Economic Geology, The University of Texas at Austin, Texas.
8. Stein, W.G. and Ozuna, G.B., 1995, Geologic Framework and Hydrogeologic Characteristics of the Edwards Aquifer Recharge Zone, Bexar County, Texas, U.S. Geological Survey Water Resources Investigations 95-4030.
9. Barnes, V.L., 1982, Geologic Atlas of Texas San Antonio Sheet, Bureau of Economic Geology and University of Texas at Austin, Geologic Atlas of Texas.
10. Federal Emergency Management Agency, Federal Insurance Administration, National Flood Insurance Program, Flood Insurance Map, Community Panel Number 48029C0210G, dated September 29, 2010
11. United States Department of Agriculture Soil Conservation Service Soil Survey of Bexar County 1966.
12. USDA NRCS Web Soil Survey (WSS) website: <https://websoilsurvey.nrcs.usda.gov> (2014)
13. TCEQ-0585-Instructions (Rev. 10-1-04), "Instructions to Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zone".
14. San Antonio Water Systems, Bexar County Watersheds Map, 2004.

APPENDIX A

SITE LOCATION FIGURES



PROJECT NAME:


Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas



Site Layout

PROJECT NO.: FGS-E24234

DATE: December 11, 2024



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas


Street Map

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas


U.S.G.S. 7.5 Minute Quadrangle Map
Helotes, Texas (1992)

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas


**Bexar County Watersheds Map
Helotes Water Systems (2004)**

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas

**EAA Recharge & Contributing Zone Map
Helotes, Texas (2014)**

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024

**PROJECT NAME:**

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas

Soils Map


Bexar County Soil Survey
NRCS website: websoilsurvey.nrcs.usda.gov

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas

U.S. Geological Survey
Scientific Investigations Map 3366
Clarke (2016)

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024

**PROJECT NAME:**

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas

2023 Aerial Photograph
Google Earth Aerial

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024



PROJECT NAME:

Geologic Site Assessment (WPAP)
for Regulated Activities / Development on the
Edwards Aquifer Recharge / Transition Zone
Helotes Residential & Commercial Tract
Helotes, Texas

2023 Aerial Photograph with PRFs
Google Earth Aerial

PROJECT NO.:

FGS-E24234

DATE:

December 11, 2024

APPENDIX B

SITE PHOTOGRAPHS



Photo #1 – Typical view of the dense vegetative cover observed in the northern portion of the project site.



Photo #2 – Typical view of the dense vegetative cover observed in the northeastern portion of the project site.



Photo #3 – View of PRF #S-1.



Photo #4 – View of PRF #S-2.



Photo #5 – View of a structure observed in the northern portion of the project site.



Photo #6 – View of a paved area observed in the northwestern portion of the project site.



Photo #7 – View of a large, paved area in the west-central portion of the project site.



Photo #8 – Typical view of the dense vegetative cover observed in the western portion of the project site.



Photo #9 – Typical view of the dense vegetative cover observed in the southern portion of the project site.



Photo #10 – Typical view of the dense vegetative cover observed in the southwestern portion of the project site.

APPENDIX C
GEOLOGIC MAP

SECTION 5.0

WATER POLLUTION ABATEMENT PLAN APPLICATION FORM

Water Pollution Abatement Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This Water Pollution Abatement Plan Application Form is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Print Name of Customer/Agent: M. Tyler Meals

Date: 01/10/2025

Signature of Customer/Agent :



Regulated Entity Name: Woodmont Helotes

Regulated Entity Information

1. The type of project is:

- ☐ Residential: Number of Lots: _____
- ☒ Residential: Number of Living Unit Equivalents: 42
- ☒ Commercial
- ☐ Industrial
- ☐ Other: _____

2. Total site acreage (size of property): 5.863 Ac

3. Estimated projected population: 50

4. The amount and type of impervious cover expected after construction are shown below:

Table 1 - Impervious Cover Table

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	58,500	$\div 43,560 =$	1.343
Parking	5,565	$\div 43,560 =$	0.128
Other paved surfaces	68,450	$\div 43,560 =$	1.571
Total Impervious Cover	132,515	$\div 43,560 =$	3.042

Total Impervious Cover 3.042 \div Total Acreage 5.863 $\times 100 =$ 52% Impervious Cover

5. ☒ Attachment A - Factors Affecting Surface Water Quality. A detailed description of all factors that could affect surface water and groundwater quality that addresses ultimate land use is attached.
6. ☒ Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

For Road Projects Only

Complete questions 7 - 12 if this application is exclusively for a road project.

7. Type of project:

- ☐ TXDOT road project.
- ☐ County road or roads built to county specifications.
- ☐ City thoroughfare or roads to be dedicated to a municipality.
- ☐ Street or road providing access to private driveways.

8. Type of pavement or road surface to be used:

- ☐ Concrete
- ☐ Asphaltic concrete pavement
- ☐ Other: _____

9. Length of Right of Way (R.O.W.): _____ feet.

Width of R.O.W.: _____ feet.

$L \times W =$ _____ $\text{Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} =$ _____ acres.

10. Length of pavement area: _____ feet.

Width of pavement area: _____ feet.

$L \times W =$ _____ $\text{Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} =$ _____ acres.

Pavement area _____ acres \div R.O.W. area _____ acres $\times 100 =$ _____ % impervious cover.

11. ☐ A rest stop will be included in this project.
- ☐ A rest stop will not be included in this project.

12. ☐ Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

Stormwater to be generated by the Proposed Project

13. ☒ Attachment B - Volume and Character of Stormwater. A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on the area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

Wastewater to be generated by the Proposed Project

14. The character and volume of wastewater is shown below:

<u>100%</u> Domestic	_____ Gallons/day
_____ % Industrial	_____ Gallons/day
_____ % Commingled	_____ Gallons/day
TOTAL gallons/day _____	

15. Wastewater will be disposed of by:

☐ On-Site Sewage Facility (OSSF/Septic Tank):

☐ Attachment C - Suitability Letter from Authorized Agent. An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

☐ Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

☒ Sewage Collection System (Sewer Lines):

☒ Private service laterals from the wastewater generating facilities will be connected to an existing SCS.

☐ Private service laterals from the wastewater generating facilities will be connected to a proposed SCS.

☐ The SCS was previously submitted on _____.

☐ The SCS was submitted with this application.

☐ The SCS will be submitted at a later date. The owner is aware that the SCS may not be installed prior to Executive Director approval.

☒ The sewage collection system will convey the wastewater to the Leon Creek (name) Treatment Plant. The treatment facility is:

☒ Existing.

☐ Proposed.

16. ☒ All private service laterals will be inspected as required in 30 TAC §213.5.

Site Plan Requirements

Items 17 – 28 must be included on the Site Plan.

17. ☒ The Site Plan must have a minimum scale of 1" = 400'.

Site Plan Scale: 1" = 40'.

18. 100-year floodplain boundaries:

☐ Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.

☒ No part of the project site is located within the 100-year floodplain.

The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FIRM MAP NO. 48029C0210G Effective 9/29/2010

19. ☒ The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, open space, etc. are shown on the plan.

☐ The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, open space, etc. are shown on the site plan.

20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):

☐ There are _____ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)

☐ The wells are not in use and have been properly abandoned.

☐ The wells are not in use and will be properly abandoned.

☐ The wells are in use and comply with 16 TAC §76.

☒ There are no wells or test holes of any kind known to exist on the project site.

21. Geologic or manmade features which are on the site:

☒ All sensitive geologic or manmade features identified in the Geologic Assessment are shown and labeled.

☐ No sensitive geologic or manmade features were identified in the Geologic Assessment.

☐ Attachment D - Exception to the Required Geologic Assessment. A request and justification for an exception to a portion of the Geologic Assessment is attached.

- 22. ☒ The drainage patterns and approximate slopes anticipated after major grading activities.
- 23. ☒ Areas of soil disturbance and areas which will not be disturbed.
- 24. ☒ Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
- 25. ☒ Locations where soil stabilization practices are expected to occur.
- 26. ☐ Surface waters (including wetlands).
☒ N/A
- 27. ☐ Locations where stormwater discharges to surface water or sensitive features are to occur.
☒ There will be no discharges to surface water or sensitive features.
- 28. ☒ Legal boundaries of the site are shown.

Administrative Information

- 29. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
- 30. ☒ Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

WPAP APPLICATION FORM TCEQ-0584
ATTACHMENT A
FACTORS AFFECTING WATER QUALITY

Construction Phase

Potential sources of pollution that may reasonably be expected to affect surface water and groundwater quality include sediment from disturbed soil and stockpiled material, fuels and lubricants from vehicles and equipment, hydrocarbons from asphalt paving operations, rinse water from concrete trucks, miscellaneous construction trash or debris, and spills or overflows from portable toilets.

Post-Construction Phase

Potential sources of pollution that may reasonably be expected to affect surface water and groundwater quality include fuels and lubricants from vehicles and equipment, landscape products including fertilizers and herbicides, pest control products, domestic animal waste, and miscellaneous waste or debris.

WPAP APPLICATION FORM TCEQ-0584
ATTACHMENT B
VOLUME AND CHARACTER OF STORM WATER

The storm water runoff generated from this development will originate from rooftops, roadways, driveways, flatwork, parking areas, and landscape areas. The runoff will be treated by a Jellyfish® Filter unit by Contech® Engineered Solutions, LLC for this site, and no unusual contaminants other than those typical with commercial and residential developments are expected.

The stormwater runoff from the site in its existing, partially improved condition is currently untreated. The existing site consists largely of native trees and brush with an existing steel building and miscellaneous pavement. The proposed temporary BMPs will consist of silt fencing, rock berms, stabilized entrances, etc. as indicated in Attachment D of the Temporary Stormwater Section.

The characteristic of the stormwater leaving the site in its ultimate condition will be influenced by the features that generate non-point sources of pollution, to include: fuels and lubricants from vehicles and equipment, landscape products including fertilizers and herbicides, pest control products, domestic animal waste, and miscellaneous waste or debris.

The following volume stormwater calculations are provided for this project:

Required Total Suspended Solids (TSS) Removal				
Watershed	Drainage Area to BMP (Ac.)	Proposed Impervious Cover (Ac.)	Average Annual Rainfall (Inches)	Lm = 80% Required TSS Removal Annually (Lbs)
BMP #1 (Jellyfish)	5.62	2.81	30	2,293
Uncaptured	0.23	0.23	30	187
Total	5.85	3.04		2,480



WPAP APPLICATION FORM TCEQ-0584
ATTACHMENT C
SUITABILITY LETTER FROM AUTHORIZED AGENT

Not applicable. No OSSF proposed for this project.

WPAP APPLICATION FORM TCEQ-0584
ATTACHMENT D
EXCEPTION TO THE REQUIRED GEOLOGIC ASSESSMENT

Not applicable. No exceptions requested for this project.

WPAP APPLICATION FORM TCEQ-0584
ATTACHMENT E
SITE PLAN



IMPERVIOUS COVER TABLE

LOT 1, BLOCK 3 - RESIDENTIAL TOWN HOME DEVELOPMENT

IMPERVIOUS COVER OF PROPOSED PROJECT	SQUARE FOOTAGE	ACRES
STRUCTURES/ ROOFTOPS	53,700	1.233
PARKING	N/A	N/A
OTHER PAVED SURFACES	57,600	1.322

LOT 1, BLOCK 3 TOTAL IMPERVIOUS COVER 2,555 / TOTAL ACREAGE 5.113 X 100 = 50% IMPERVIOUS COVER

LOT 3, BLOCK 3 - COMMERCIAL STRIP DEVELOPMENT

STRUCTURES/ ROOFTOPS	4,800	0.110
PARKING	5,565	0.128
OTHER PAVED SURFACES	10,850	0.249

LOT 3, BLOCK 3 TOTAL IMPERVIOUS COVER 0.487 / TOTAL ACREAGE 0.750 X 100 = 65% IMPERVIOUS COVER

TOTAL IMPERVIOUS COVER 3.042 / TOTAL ACREAGE 5.863 X 100 = 52% IMPERVIOUS COVER

LEGEND

	PROPERTY BOUNDARY		EXISTING POWER POLE
	RIGHT-OF-WAY LINE		EXISTING LIGHT POLE
	ADJOINING PROPERTY LINE		EXISTING ELECTRIC PULL BOX
	EASEMENT LINE		EXISTING TELEPHONE PEDESTAL
	EXISTING WATER LINE		EXISTING WATER METER
	EXISTING SEWER LINE		EXISTING CONTROL VALVE
	EXISTING GAS LINE		EXISTING WATER VALVE
	EXISTING FIBER LINE		EXISTING FIRE HYDRANT
	EXISTING COMMUNICATION LINE		EXISTING COMMUNICATIONS MANHOLE
	EXISTING UNDERGROUND ELECTRIC		EXISTING STORM DRAIN MANHOLE
	EXISTING OVERHEAD ELECTRIC		EXISTING SANITARY SEWER MANHOLE
	PROPOSED WATER LINE		
	PROPOSED SANITARY SEWER LINE		
	EXISTING 1' CONTOUR LINE		
	EXISTING 5' CONTOUR LINE		
	PROPOSED 1' CONTOUR LINE		
	PROPOSED 5' CONTOUR LINE		



WOODMONT HELOTES
LOT 1, BLOCK 3, NCB 14867
(VOL. 20003, PG. 1628, O.P.R.B.C.)
SAN ANTONIO, TX 78023

SITE PLAN
ATTACHMENT E

1.0

SECTION 6.0

TEMPORARY STORMWATER SECTION

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This Temporary Stormwater Section is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: M. Tyler Meals

Date: 01/10/2025

Signature of Customer/Agent:



Regulated Entity Name: Woodmont Helotes

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

☒ The following fuels and/or hazardous substances will be stored on the site: Diesel, gasoline, hydraulic fluid, and/or lubricants

These fuels and/or hazardous substances will be stored in:

- ☒ Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- ☐ Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
- ☐ Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- ☐ Fuels and hazardous substances will not be stored on the site.
- 2. ☒ Attachment A - Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. ☒ Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. ☒ Attachment B - Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

- 5. ☒ Attachment C - Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
 - ☒ For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
 - ☐ For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6. ☒ Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: French Creek (Leon Creek Watershed)

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

- 7. ☒ Attachment D – Temporary Best Management Practices and Measures. TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

- ☒ A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
 - ☒ A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
 - ☒ A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
 - ☒ A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. ☒ The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- ☐ Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
 - ☒ There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. ☒ Attachment F - Structural Practices. A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10. ☒ Attachment G - Drainage Area Map. A drainage area map supporting the following requirements is attached:
- ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
 - ☐ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

- ☒ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11. ☐ Attachment H - Temporary Sediment Pond(s) Plans and Calculations. Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
- ☒ N/A
12. ☒ Attachment I - Inspection and Maintenance for BMPs. A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13. ☒ All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. ☒ If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. ☒ Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. ☒ Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. ☒ Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices. A schedule of the interim and permanent soil stabilization practices for the site is attached.

18. ☒ Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19. ☒ Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

20. ☒ All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21. ☒ If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22. ☒ Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT A
SPILL RESPONSE ACTIONS

In the event of accidental spills of hazardous materials or hydrocarbons, the following actions will be taken as necessary:

1. In the event of a spill, appropriate actions shall be taken to contain the spill using all available means including absorbent and/or absorbent materials and readily available mobile equipment. Absorbent and/or absorbent materials are kept in a readily available location. In the event of an uncontained discharge, available facility equipment shall immediately construct a containment berm down gradient from the discharge and absorb and/or absorb the discharged material with sand, screenings, and/or other available fines that are on hand. This material shall be properly disposed of in accordance with applicable local, state, and federal environmental regulations.
2. After containing the discharge, all media (soil, water, etc.) that came into contact with oil will be collected and stored in such a way that will not continue to affect additional media. Examples of proper materials to use for cleanup include adsorbents and/or absorbents such as: aggregates fines, sand, absorbent pads, brooms, socks, etc. Proper cleanup will be deemed complete when all the applicable response requirements are met on all local, state and/or federal levels.
3. Materials that have come into contact with the discharged fluids shall be placed in a temporary staging area until proper methods of disposal can be determined. To prevent additional contamination, impacted materials will be stored on plastic sheets until removal. Plastic sheets will also be used to cover the materials to mitigate contact with rainfall and wind. Sampling of impacted media may be required prior to determining a proper method of disposal. Determining a proper method of disposal will take into consideration all local, state, and federal environmental regulatory requirements.
4. In the event of a fire, the local fire authority shall be contacted immediately.

The following reporting procedures will be implemented after an oil/fuel discharge (of any size) has occurred.

1. Based on the size, nature, and circumstances of the discharge, the contractor shall contact the owner who will notify the appropriate regulatory authorities. In addition, federal SPCC regulations require that any discharge with the potential of reaching a navigable waterway in harmful quantities, as defined in 40 CFR 110.3, be immediately reported to the National Response Center (NRC).

- Any discharge greater than 42 U.S. gallons in volume must be immediately reported to the NRC.

National Response Center: (800) 424-8802
U.S. EPA, Region 6: (214) 655-2222

2. Texas State Regulations require that a spill or accidental discharge equal to or greater than the Reportable Quantities listed in the Title 30 TAC §327.4 be reported immediately to the TCEQ within 24 hours after the discovery of the spill or discharge. The reportable quantities are listed below:

- For petroleum product or used oil discharged to land – 25 gallons
- For petroleum product or used oil discharged to water in the state – quantity sufficient to cause a sheen.

State Emergency Response Center: (800) 832-8224 (24 hour)
TCEQ Spill Reporting Hotline: (512) 463-7727 (24 hour)
TCEQ Region 13: (210) 490-3096 (8am – 5pm)
Edwards Aquifer Authority: (210) 222-2204
CPS Energy Electric Company: (210) 353-4357

3. Pursuant to Texas regulations, the facility must also submit written information, such as a letter, describing the details of the discharge or spill and supporting the adequacy of the response action, to the appropriate TCEQ regional manager within 30 working days of the discovery of the reportable discharge spill. The written response must document the requirements outlines in 30 TAC §327.5(c).

Regional Director
TCEQ Region 13 Office
14250 Judson Road
San Antonio, TX 78233-4480

4. Transformers located at the facility are the property of CPS Energy. In the event of a spill related to the failure or explosion of a transformer, CPS Energy or specialized clean-up contractor will be contacted so that they can remove spilled material and notify the appropriate regulatory agencies.

DETAILED DISCHARGE REPORT FORM

Reporter's Name and Date: _____

Location of Discharge: _____

Date and Time Discharge Occurred: _____

Material and Amount Discharged: _____

Source of the Release: _____

Cause and Circumstances of Release: _____

Countermeasures to Contain and Clean-up Discharge: _____

Personnel/Agency Contacted Regarding Discharge Procedures: _____

Corrective Actions Implemented to Prevent Recurrence of Discharge: _____

Discharge Report Sent To: _____

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT B
POTENTIAL SOURCES OF CONTAMINATION

Potential sources of contamination during operations and preventive measures include the following:

Potential Source – Asphalt products used on this project.

Preventative Measures – After placement of asphalt, emulsion or coatings, the contractor will be responsible for immediate cleanup should an unexpected rain occur. For the duration of the asphalt product curing time, the contractor will maintain standby personnel and equipment to contain any asphalt wash-off should an unexpected rain occur. The contractor will be instructed not to place asphalt products on the ground within 48 hours of a forecasted rain.

Potential Source – Oil, grease, fuel, and hydraulic fluid contamination from equipment and vehicle dripping.

Preventive Measures – Vehicles and equipment will be parked in designated locations, visually checked daily, and drip pans will be used to catch drips as needed. Chronic drips will be repaired as soon as practicable. When maintenance must be performed, a plastic liner or disposable base pad will be utilized as secondary containment.

Potential Source – Accidental leaks or spills of oil, petroleum products, or hazardous substances, which are used or stored temporarily on site.

Preventive Measures – Contractor shall incorporate discussions of spill prevention and response actions into regular safety meetings; proper spill prevention and control measures will be adhered to strictly; oil, petroleum products, or hazardous substances will be properly stored, and spill cleanup materials will be stored and readily accessible on site.

Potential Source – Miscellaneous trash and litter from construction workers.

Preventive Measures – Trash containers will be placed throughout the site to encourage proper trash disposal.

Potential Source – Construction debris.

Preventive Measures – Construction debris will be monitored daily by contractor. Debris will be collected weekly and placed in disposal bins. Situations requiring immediate attention will be addressed on a case-by-case basis.

Potential Source – Portable toilet spills or overflows.

Preventive Measures – Contractor will locate portable toilets on level ground surfaces away from high traffic areas. Portable toilets will be routinely inspected and serviced at a frequency sufficient to maintain sanitary conditions.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT C
SEQUENCE OF MAJOR ACTIVITIES

A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) including an estimate of the total area of the site to be disturbed by each activity is as follows:

The sequence of major soil disturbance activities is as follows:

- Installation of Temporary BMPs (silt fence and rock filter dam)
- Clearing and grubbing of vegetation where applicable
- Mass grading and utilities
- Construction of roads, flatwork, buildings, parking area, and landscaping
- Stabilization of disturbed areas

Approximately 5.35 of the 5.86 acres of the overall tract will ultimately be disturbed.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT D
TEMPORARY BEST MANAGEMENT PRACTICES AND MEASURES

- A. A description of how BMPs and measures will prevent pollution of surface water, groundwater or storm water that originates upgradient from the site and flows across the site.

The highest elevations of the site are located immediately south of the FM 1560 right-of-way, which intercepts any upgradient runoff, therefore no offsite upgradient runoff is expected to enter the site.

- B. A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated storm water runoff from the site.

Temporary Best Management Practices (TBMPs) such as silt fences and rock filter dams will be placed in downgradient locations along the site's boundaries or low points to either filter or prevent any on-site surface water from leaving the site untreated.


- C. A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.

By containing the sediment and solids within the site, the placement of the aforementioned TBMPs will prevent pollutants from entering surface streams, sensitive features, or the aquifer.

- D. A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.

Flow will be maintained to the natural runoff system, to the maximum extent practicable, by using silt fences and rock filter dams. This type of TBMP slows the flow of runoff, allowing for settlement of sediments, trash, debris, etc. while allowing the flow to be maintained.

The measures utilized in this plan are intended to allow storm water to continue downstream after passing through the TBMPs. This will allow storm water runoff to continue down gradient to streams or features that may exist downstream of the site.

[illegible]1.0

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT E
REQUEST TO TEMPORARILY SEAL A FEATURE

Not applicable. No sensitive feature has been identified on-site.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT F
STRUCTURAL PRACTICES

Temporary Best Management Practices (TBMPs) proposed for the project include the erection of silt fences and rock filter dams along the downgradient boundaries of the site and at select low points where concentrated stormwater runoff is expected, along with stabilized construction entrance/exit(s), and concrete wash pits.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT G
DRAINAGE AREA MAP

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT H
TEMPORARY SEDIMENT POND(S) AND CALCULATIONS

Not applicable. No temporary sediment ponds are proposed for this project.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT I
INSPECTION AND MAINTENANCE FOR BMPS

Designated and qualified person(s) shall inspect Pollution Control Measures weekly and within 24 hours after a storm event. An inspection report that summarizes the scope of the inspection, names and qualifications of personnel conducting the inspection, date of the inspection, major observations, and actions taken as a result of the inspection shall be recorded and maintained as part of Storm Water TPDES data for a period of three years after the Notice of Termination (NOT) has been filled. A copy of the Inspection Report Form is provided in this Storm Water Pollution Prevention Plan.

As a minimum, the inspector shall observe: (1) significant disturbed areas for evidence of erosion, (2) storage areas for evidence of leakage from the exposed stored materials, (3) structural controls (silt fences, etc.) for evidence of failure or excess situation. (4) vehicle exit point for evidence of off-site sediment tracking, (5) vehicle storage areas for signs of leaking equipment or spills. Deficiencies noted during the inspection will be corrected and documented within seven calendar days following the inspection or before the next anticipated storm event if practical.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT I (CONTINUED)
INSPECTION AND MAINTENANCE FOR BMPS

Pollution Prevention Measure	Inspected in Compliance	Corrective Action Required	
		Description (use additional sheet if necessary)	Date Completed
<u>Best Management Practices</u>			
Natural vegetation buffer strips			
Temporary vegetation			
Permanent vegetation			
Sediment control basin			
Silt fences			
Rock berms			
Gravel filter bags			
Drain inlet protection			
Other structural controls			
Vehicles exits (off-site tracking)			
Material storage areas (leakage)			
Equipment area (leaks, spills)			
Concrete washout pit (leaks, failure)			
General site cleanliness			
Trash receptacles			
<u>Evidence of Erosion</u>			
Site preparation			
Roadway or parking lot construction			
Utility construction			
Drainage construction			
Building construction			
<u>Major Observations</u>			
Sediment discharges from site			
BMPs requiring maintenance			
BMPs requiring modification			
Additional BMPs required			

“I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.”

“I further certify I am an authorized signatory in accordance with the provisions of 30 TAC §305.128.”

Inspector's Name

Inspector's Signature

Date

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT J
SCHEDULE OF INTERIM AND PERMANENT SOIL STABILIZATION

Interim on-site stabilization measures, which are continuous, will include minimizing soil disturbances by exposing the smallest practical area of land required for the shortest period of time and maximizing use of natural vegetation. As soon as practical, all disturbed soil will be stabilized as per project specifications in accordance with pages 1-35 to 1-60 of TCEQ's Technical Guidance Manual (TGM) RG-348 (2005). Mulching, netting, erosion blankets, and seeding are acceptable.

Stabilization measures will be initiated as soon as practical in portions of the site where construction activities have temporarily or permanently ceased, and except as provided below, will be initiated no more than fourteen (14) days after the construction activity in that portion of the site has temporarily or permanently ceased. Where construction activity on a portion of the site is temporarily ceased, and earth disturbing activities will be resumed within twenty-one (21) days, temporary stabilization measures do not have to be initiated on that portion of site. In areas experiencing droughts where the initiation of stabilization measures by the 14th day after construction activity has temporarily or permanently ceased is precluded by seasonably and conditions, stabilization measures must be initiated as soon as practical.

TEMPORARY STORMWATER SECTION FORM TCEQ-0602
ATTACHMENT J (CONTINUED)
SCHEDULE OF INTERIM AND PERMANENT SOIL STABILIZATION

PROJECT MILESTONE DATES

Date when major site grading activities begin:

Construction Activity	Date

Dates when construction activities temporarily or permanently cease on all or a portion of the project:

Construction Activity	Date

Dates when stabilization measures are initiated:

Construction Activity	Date

SECTION 7.0

PERMANENT STORMWATER SECTION

Permanent Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC
§213.5(b)(4)(C), (D)(li), (E), and (5), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This Permanent Stormwater Section is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: M. Tyler Meals

Date: 01/10/2025

Signature of Customer/Agent



Regulated Entity Name: Woodmont Helotes

Permanent Best Management Practices (BMPs)

Permanent best management practices and measures that will be used during and after construction is completed.

1. ☒ Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
☐ N/A
2. ☒ These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
☒ The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.

- ☐ A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: _____
- ☐ N/A
3. ☒ Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
- ☐ N/A
4. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
- ☐ The site will be used for low density single-family residential development and has 20% or less impervious cover.
- ☐ The site will be used for low density single-family residential development but has more than 20% impervious cover.
- ☒ The site will not be used for low density single-family residential development.
5. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
- ☐ Attachment A - 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.
- ☒ The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.
- ☐ The site will not be used for multi-family residential developments, schools, or small business sites.
6. ☒ Attachment B - BMPs for Upgradient Stormwater.

- ☒ A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
 - ☐ No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
 - ☐ Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
7. ☒ Attachment C - BMPs for On-site Stormwater.
- ☒ A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
 - ☐ Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
8. ☒ Attachment D - BMPs for Surface Streams. A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is attached. Each feature identified in the Geologic Assessment as sensitive has been addressed.
- ☐ N/A
9. ☒ The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.
- ☒ The permanent sealing of or diversion of flow from a naturally-occurring sensitive feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed.
 - ☐ Attachment E - Request to Seal Features. A request to seal a naturally-occurring sensitive feature, that includes, for each feature, a justification as to why no reasonable and practicable alternative exists, is attached.
10. ☒ Attachment F - Construction Plans. All construction plans and design calculations for the proposed permanent BMP(s) and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. The plans are attached and, if applicable include:
- ☒ Design calculations (TSS removal calculations)
 - ☒ TCEQ construction notes
 - ☒ All geologic features
 - ☒ All proposed structural BMP(s) plans and specifications
- ☐ N/A

11. ☒ Attachment G - Inspection, Maintenance, Repair and Retrofit Plan. A plan for the inspection, maintenance, repairs, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan includes all of the following:
- ☒ Prepared and certified by the engineer designing the permanent BMPs and measures
 - ☒ Signed by the owner or responsible party
 - ☒ Procedures for documenting inspections, maintenance, repairs, and, if necessary retrofit
 - ☒ A discussion of record keeping procedures
- ☐ N/A
12. ☐ Attachment H - Pilot-Scale Field Testing Plan. Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
- ☒ N/A
13. ☐ Attachment I - Measures for Minimizing Surface Stream Contamination. A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that results in water quality degradation.
- ☒ N/A

Responsibility for Maintenance of Permanent BMP(s)

Responsibility for maintenance of best management practices and measures after construction is complete.

14. ☒ The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
- ☐ N/A
15. ☒ A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.
- ☐ N/A

PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT A
20% OR LESS IMPERVIOUS COVER WAIVER

This site will ultimately have more than 20% proposed impervious cover and therefore a request to waive the requirements for permanent BMPs is not included in this application.

PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT B
BMPS FOR UPGRADIENT STORM WATER

The highest elevations of the site are located immediately south of the FM 1560 right-of-way, which intercepts any upgradient runoff, therefore no offsite upgradient runoff is expected to enter the site.

PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT C
BMPS FOR ON-SITE STORM WATER

Most surface water flowing through the site will be directed to the Jellyfish Treatment Units. By containing the sediment and solids within the site, they will not enter surface stream and/or sensitive features which may exist down-gradient of the site. Any uncaptured impervious cover will be "over-treated" by the onsite BMPs.

The onsite BMPs proposed for the site are designed in accordance with the Texas Commission on Environmental Quality (TCEQ) Technical Guidance Manual (TGM). The Owner must notify the TCEQ in the event there are any variations in land use from the exhibits enclosed.

The following represents a calculation summary of the TSS removal requirements and calculated results:

Total Suspended Solids (TSS) Calculations							
Watershed	Drainage Area to BMP (Ac.)	Proposed Impervious Cover (Ac.)	BMP Type	BMP TSS Removal Efficiency (%)	Average Annual Rainfall (Inches)	Lm = 80% Required TSS Removal Annually (Lbs.)	TSS Removed Annually (Lbs.)
BMP #1 (Jellyfish)	5.62	2.81	Jellyfish Filter	86%	30	2,293	2,548
Uncaptured	0.23	0.23	Overtreatment	0%	30	187	0
Total	5.85	3.04				2,480	2,548

MMES F-18576



PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT D
BMPS FOR SURFACE STREAMS

Not applicable.

PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT E
REQUEST TO SEAL FEATURES

Not applicable.

PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT F
CONSTRUCTION PLANS

The following include the design calculations for the permanent BMP (Jellyfish Filter) along with details of the BMP.

Project Name: Woodmont Helotes
Date Prepared: 1/8/2025



1. The Required Load Reduction for the total project:

Calculations from RG-348
Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

$L_{M \text{ TOTAL PROJECT}}$ = Required TSS removal resulting from the proposed development = 80% of increased load
 A_N = Net increase in impervious area for the project
 P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Bexar	
Total project area included in plan *	5.45	acres
Predevelopment impervious area within the limits of the plan *	0.00	acres
Total post-development impervious area within the limits of the plan *	3.04	acres
Total post-development impervious cover fraction *	0.56	
P =	30	inches
$L_{M \text{ TOTAL PROJECT}}$ =	2481	lbs.

Number of drainage basins / outfalls areas leaving the plan area = 2

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	1	
Total drainage basin/outfall area =	5.62	acres
Predevelopment impervious area within drainage basin/outfall area =	0.00	acres
Post-development impervious area within drainage basin/outfall area =	2.81	acres
Post-development impervious fraction within drainage basin/outfall area =	0.50	
$L_{M \text{ THIS BASIN}}$ =	2293	lbs.

3. Indicate the proposed BMP Code for this basin.

Proposed BMP =	JF	abbreviation
Removal efficiency =	86	percent

4. Calculate Maximum TSS Load Removed (L_R) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7:
 $L_R = (\text{BMP efficiency}) \times P \times (A_i \times 34.6 + A_p \times 0.54)$

A_C = Total On-Site drainage area in the BMP catchment area
 A_i = Impervious area proposed in the BMP catchment area
 A_p = Pervious area remaining in the BMP catchment area
 L_R = TSS Load removed from this catchment area by the proposed BMP

A_C =	5.62	acres
A_i =	2.81	acres
A_p =	2.81	acres
L_R =	2548	lbs.

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

Desired $L_{M \text{ THIS BASIN}}$ =	2481	lbs.
F =	0.97	

6. Calculate Treated Flow required by the BMP Type for this drainage basin / outfall area.

Offsite area draining to BMP =	0.00	acres
Offsite impervious cover draining to BMP =	0.00	acres

Calculations from RG-348
Pages Section 3.2.22

Rainfall Intensity =	2.00	inches per hour
Effective Area =	2.61	acres
Cartridge Length =	54	inches


Peak Treatment Flow Required =	5.27	cubic feet per second
--------------------------------	------	-----------------------

7. Jellyfish

Designed as Required in RG-348
Section 3.2.22

Flow Through Jellyfish Size	Vault
Jellyfish Size for Flow-Based Configuration =	JFPD0812-27-6
Jellyfish Treatment Flow Rate =	5.35 cfs

Jellyfish[®] Filter Maintenance Guide





JELLYFISH® FILTER INSPECTION & MAINTENANCE GUIDE

Jellyfish units are often just one of many structures in a more comprehensive stormwater drainage and treatment system.

In order for maintenance of the Jellyfish filter to be successful, it is imperative that all other components be properly maintained. The maintenance and repair of upstream facilities should be carried out prior to Jellyfish maintenance activities.

In addition to considering upstream facilities, it is also important to correct any problems identified in the drainage area. Drainage area concerns may include: erosion problems, heavy oil loading, and discharges of inappropriate materials.

TABLE OF CONTENTS

Inspection and Maintenance Overview	3
Inspection Procedure.....	3
Maintenance Procedure.....	4
Cartridge Assembly & Cleaning.....	5
Inspection Process	7

1.0 Inspection and Maintenance Overview

The primary purpose of the Jellyfish® Filter is to capture and remove pollutants from stormwater runoff. As with any filtration system, these pollutants must be removed to maintain the filter's maximum treatment performance. Regular inspection and maintenance are required to insure proper functioning of the system.


Maintenance frequencies and requirements are site specific and vary depending on pollutant loading. Additional maintenance activities may be required in the event of non-storm event runoff, such as base-flow or seasonal flow, an upstream chemical spill or due to excessive sediment loading from site erosion or extreme runoff events. It is a good practice to inspect the system after major storm events.

Inspection activities are typically conducted from surface observations and include:

- Observe if standing water is present
- Observe if there is any physical damage to the deck or cartridge lids
- Observe the amount of debris in the Maintenance Access Wall (MAW) or inlet bay for vault systems

Maintenance activities include:

- Removal of oil, floatable trash and debris
- Removal of collected sediments
- Rinsing and re-installing the filter cartridges
- Replace filter cartridge tentacles, as needed



Note: Separator Skirt not shown

2.0 Inspection Timing

Inspection of the Jellyfish Filter is key in determining the maintenance requirements for, and to develop a history of, the site's pollutant loading characteristics. In general, inspections should be performed at the times indicated below; *or per the approved project stormwater quality documents (if applicable), whichever is more frequent.*

1. A minimum of quarterly inspections during the first year of operation to assess the sediment and floatable pollutant accumulation, and to ensure proper functioning of the system.
2. Inspection frequency in subsequent years is based on the inspection and maintenance plan developed in the first year of operation. Minimum frequency should be once per year.
3. Inspection is recommended after each major storm event.
4. Inspection is required immediately after an upstream oil, fuel or other chemical spill.


3.0 Inspection Procedure

The following procedure is recommended when performing inspections:

1. Provide traffic control measures as necessary.
2. Inspect the MAW or inlet bay for floatable pollutants such as trash, debris, and oil sheen.
3. Measure oil and sediment depth in several locations, by lowering a sediment probe until contact is made with the floor of the structure. Record sediment depth, and presences of any oil layers.
4. Inspect cartridge lids. Missing or damaged cartridge lids to be replaced.
5. Inspect the MAW (where appropriate), cartridge deck and receptacles, and backwash pool weir, for damaged or broken components.

3.1 Dry weather inspections

- Inspect the cartridge deck for standing water, and/or sediment on the deck.
- No standing water under normal operating conditions.
- Standing water inside the backwash pool, but not outside the backwash pool indicates, that the filter cartridges need to be rinsed.



Inspection Utilizing Sediment Probe

- Standing water outside the backwash pool is not anticipated and may indicate a backwater condition caused by high water elevation in the receiving water body, or possibly a blockage in downstream infrastructure.
- Any appreciable sediment ($\geq 1/16"$) accumulated on the deck surface should be removed.

3.2 Wet weather inspections

- Observe the rate and movement of water in the unit. Note the depth of water above deck elevation within the MAW or inlet bay.
- Less than 6 inches, flow should be exiting the cartridge lids of each of the draindown cartridges (i.e. cartridges located outside the backwash pool).
- Greater than 6 inches, flow should be exiting the cartridge lids of each of the draindown cartridges and each of the hi-flo cartridges (i.e. cartridges located inside the backwash pool), and water should be overflowing the backwash pool weir.
- 18 inches or greater and relatively little flow is exiting the cartridge lids and outlet pipe, this condition indicates that the filter cartridges need to be rinsed.

4.0 Maintenance Requirements

Required maintenance for the Jellyfish Filter is based upon results of the most recent inspection, historical maintenance records, or the site specific water quality management plan; whichever is more frequent. In general, maintenance requires some combination of the following:

1. Sediment removal for depths reaching 12 inches or greater, or within 3 years of the most recent sediment cleaning, whichever occurs sooner.
2. Floatable trash, debris, and oil removal.
3. Deck cleaned and free from sediment.
4. Filter cartridges rinsed and re-installed as required by the most recent inspection results, or within 12 months of the most recent filter rinsing, whichever occurs sooner.
5. Replace tentacles if rinsing does not restore adequate hydraulic capacity, remove accumulated sediment, or if damaged or missing. It is recommended that tentacles should remain in service no longer than 5 years before replacement.
6. Damaged or missing cartridge deck components must be repaired or replaced as indicated by results of the most recent inspection.
7. The unit must be cleaned out and filter cartridges inspected immediately after an upstream oil, fuel, or chemical spill. Filter cartridge tentacles should be replaced if damaged or compromised by the spill.

5.0 Maintenance Procedure

The following procedures are recommended when maintaining the Jellyfish Filter:

1. Provide traffic control measures as necessary.
2. Open all covers and hatches. Use ventilation equipment as required, according to confined space entry procedures.
Caution: Dropping objects onto the cartridge deck may cause damage.

3. Perform Inspection Procedure prior to maintenance activity.
4. To access the cartridge deck for filter cartridge service, descend into the structure and step directly onto the deck. Caution: Do not step onto the maintenance access wall (MAW) or backwash pool weir, as damage may result. Note that the cartridge deck may be slippery.
5. Maximum weight of maintenance crew and equipment on the cartridge deck not to exceed 450 lbs.

5.1 Filter Cartridge Removal

1. Remove a cartridge lid.
2. Remove cartridges from the deck using the lifting loops in the cartridge head plate. Rope or a lifting device (available from Contech) should be used. **Caution: Should a snag occur, do not force the cartridge upward as damage to the tentacles may result. Wet cartridges typically weigh between 100 and 125 lbs.**
3. Replace and secure the cartridge lid on the exposed empty receptacle as a safety precaution. Contech does not recommend exposing more than one empty cartridge receptacle at a time.

5.2 Filter Cartridge Rinsing

1. Remove all 11 tentacles from the cartridge head plate. Take care not to lose or damage the O-ring seal as well as the plastic threaded nut and connector.



Cartridge Removal & Lifting Device



2. Position tentacles in a container (or over the MAW), with the threaded connector (open end) facing down, so rinse water is flushed through the membrane and captured in the container.
3. Using the Jellyfish rinse tool (available from Contech) or a low-pressure garden hose sprayer, direct water spray onto the tentacle membrane, sweeping from top to bottom along the length of the tentacle. Rinse until all sediment is removed from the membrane. **Caution: Do not use a high pressure sprayer or focused stream of water on the membrane. Excessive water pressure may damage the membrane.**

4. Collected rinse water is typically removed by vacuum hose.
5. Reassemble cartridges as detailed later in this document. Reuse O-rings and nuts, ensuring proper placement on each tentacle.

5.3 Sediment and Floatables Extraction

1. Perform vacuum cleaning of the Jellyfish Filter only after filter cartridges have been removed from the system. Access the lower chamber for vacuum cleaning only through the maintenance access wall (MAW) opening. Be careful not to damage the flexible plastic separator skirt that is attached to the underside of the deck on manhole systems. Do not lower the vacuum wand through a cartridge receptacle, as damage to the receptacle will result.
2. Vacuum floatable trash, debris, and oil, from the MAW opening or inlet bay. Alternatively, floatable solids may be removed by a net or skimmer.



Vacuuming Sump Through MAW

3. Pressure wash cartridge deck and receptacles to remove all sediment and debris. Sediment should be rinsed into the sump area. Take care not to flush rinse water into the outlet pipe.
4. Remove water from the sump area. Vacuum or pump equipment should only be introduced through the MAW or inlet bay.
5. Remove the sediment from the bottom of the unit through the MAW or inlet bay opening.



Vacuuming Sump Through MAW

6. For larger diameter Jellyfish Filter manholes (≥ 8 -ft) and some vaults complete sediment removal may be facilitated by removing a cartridge lid from an empty receptacle and inserting a jetting wand (not a vacuum wand) through the receptacle. Use the sprayer to rinse loosened sediment toward the vacuum hose in the MAW opening, being careful not to damage the receptacle.

5.4 Filter Cartridge Reinstallation and Replacement

1. Cartridges should be installed after the deck has been cleaned. It is important that the receptacle surfaces be free from grit and debris.
2. Remove cartridge lid from deck and carefully lower the filter cartridge into the receptacle until head plate gasket is seated squarely in receptacle. **Caution: Do not force the cartridge downward; damage may occur.**
3. Replace the cartridge lid and check to see that both male threads are properly seated before rotating approximately 1/3 of a full rotation until firmly seated. Use of an approved rim gasket lubricant may facilitate installation. See next page for additional details.
4. If rinsing is ineffective in removing sediment from the tentacles, or if tentacles are damaged, provisions must be made to replace the spent or damaged tentacles with new tentacles. Contact Contech to order replacement tentacles.

5.5 Chemical Spills

Caution: If a chemical spill has been captured, do not attempt maintenance. Immediately contact the local hazard response agency and contact Contech.

5.6 Material Disposal

The accumulated sediment found in stormwater treatment and conveyance systems must be handled and disposed of in accordance with regulatory protocols. It is possible for sediments to contain measurable concentrations of heavy metals and organic chemicals (such as pesticides and petroleum products). Areas with the greatest potential for high pollutant loading include industrial areas and heavily traveled roads. Sediments and water must be disposed of in accordance with all applicable waste disposal regulations. When scheduling maintenance, consideration must be made for the disposal of solid and liquid wastes. This typically requires coordination with a local landfill for solid waste disposal. For liquid waste disposal a number of options are available including a municipal vacuum truck decant facility, local waste water treatment plant or on-site treatment and discharge.

Jellyfish Filter Components & Filter Cartridge Assembly and Installation




TABLE 1: BOM

ITEM NO.	DESCRIPTION
1	JF HEAD PLATE
2	JF TENTACLE
3	JF O-RING
4	JF HEAD PLATE GASKET
5	JF CARTRIDGE EYELET
6	JF 14IN COVER
7	JF RECEPTACLE
8	BUTTON HEAD CAP SCREW M6X14MM SS
9	JF CARTRIDGE NUT

TABLE 2: APPROVED GASKET LUBRICANTS

PART NO.	MFR	DESCRIPTION
78713	LA-CO	LUBRI-JOINT
40501	HERCULES	DUCK BUTTER
30600	OATEY	PIPE LUBRICANT
PSI LUBX 10	PROSETECT	PIPE JOINT LUBRICANT

NOTES:

Head Plate Gasket Installation:

Install Head Plate Gasket (Item 4) onto the Head Plate (Item 1) and liberally apply a lubricant from Table 2: Approved Gasket Lubricants onto the gasket where it contacts the Receptacle (Item 7) and Cartridge Lide (Item 6). Follow Lubricant manufacturer's instructions.

Lid Assembly:

Rotate Cartridge Lid counter-clockwise until both male threads drop down and properly seat. Then rotate Cartridge Lid clockwise approximately one-third of a full rotation until Cartridge Lid is firmly secured, creating a watertight seal.

Jellyfish Filter Inspection and Maintenance Log

Owner:		Jellyfish Model No:	
Location:		GPS Coordinates:	
Land Use:	Commercial:	Industrial:	Service Station:
	Roadway/Highway:	Airport:	Residential:

Date/Time:						
Inspector:						
Maintenance Contractor:						
Visible Oil Present: (Y/N)						
Oil Quantity Removed:						
Floatable Debris Present: (Y/N)						
Floatable Debris Removed: (Y/N)						
Water Depth in Backwash Pool						
Draindown Cartridges externally rinsed and recommissioned: (Y/N)						
New tentacles put on Draindown Cartridges: (Y/N)						
Hi-Flo Cartridges externally rinsed and recommissioned: (Y/N)						
New tentacles put on Hi-Flo Cartridges: (Y/N)						
Sediment Depth Measured: (Y/N)						
Sediment Depth (inches or mm):						
Sediment Removed: (Y/N)						
Cartridge Lids intact: (Y/N)						
Observed Damage:						
Comments:						



Support

- Drawings and specifications are available at www.conteches.com/jellyfish.
- Site-specific design support is available from Contech Engineered Solutions.
- Find a Certified Maintenance Provider at www.conteches.com/ccmp

Jellyfish®

CONTECH®
ENGINEERED SOLUTIONS

800.338.1122
www.ContechES.com

© 2021 Contech Engineered Solutions LLC, a QUIKRETE Company

Contech Engineered Solutions LLC provides site solutions for the civil engineering industry. Contech's portfolio includes bridges, drainage, sanitary sewer, stormwater, wastewater treatment and earth stabilization products. For information on other Contech segment offerings, visit ContechES.com or call 800.338.1122

NOTHING IN THIS CATALOG SHOULD BE CONSTRUED AS A WARRANTY. APPLICATIONS SUGGESTED HEREIN ARE DESCRIBED ONLY TO HELP READERS MAKE THEIR OWN EVALUATIONS AND DECISIONS, AND ARE NEITHER GUARANTEES NOR WARRANTIES OF SUITABILITY FOR ANY APPLICATION. CONTECH MAKES NO WARRANTY WHATSOEVER, EXPRESS OR IMPLIED, RELATED TO THE APPLICATIONS, MATERIALS, COATINGS, OR PRODUCTS DISCUSSED HEREIN. ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND ALL IMPLIED WARRANTIES OF FITNESS FOR ANY PARTICULAR PURPOSE ARE DISCLAIMED BY CONTECH. SEE CONTECH'S CONDITIONS OF SALE (AVAILABLE AT WWW.CONTECHES.COM/COS) FOR MORE INFORMATION.

**Jellyfish[®] Filter
Owner's Manual**



Table of Contents

Chapter 1	1.0 Owner Specific Jellyfish Product Information.....	4
Chapter 2	2.0 Jellyfish Filter System Operations & Functions	5
	2.1 Components & Cartridges	6
	2.2 Jellyfish Membrane Filtration Cartridges Assembly	7
	2.3 Installation of Jellyfish Membrane Filtration Cartridges.....	7
Chapter 3	3.0 Inspection and Maintenance Overview	8
Chapter 4	4.0 Inspection Timing	8
Chapter 5	5.0 Inspection Procedure.....	8
	5.1 Dry Weather Inspections	8
	5.1 Wet Weather Inspections	9
Chapter 6	6.0 Maintenance Requirements.....	9
Chapter 7	7.0 Maintenance Procedure	9
	7.1 Filter Cartridge Removal	9
	7.2 Filter Cartridge Rinsing	9
	7.3 Sediment and Flotables Extraction	10
	7.4 Filter Cartridge Reinstallation and Replacement.....	10
	7.5 Chemical Spills.....	10
	7.6 Material Disposal	10
	Jellyfish Filter Inspection and Maintenance Log	12

THANK YOU FOR PURCHASING THE JELLYFISH® FILTER!

Contech Engineered Solutions would like to thank you for selecting the Jellyfish Filter to meet your project's stormwater treatment needs. With proper inspection and maintenance, the Jellyfish Filter is designed to deliver ongoing, high levels of stormwater pollutant removal.

If you have any questions, please feel free to call us or e-mail us:


Contech Engineered Solutions

9025 Centre Pointe Drive, Suite 400 | West Chester, OH 45069

513-645-7000 | 800-338-1122

www.ContechES.com

info@conteches.com



WARNINGS / CAUTION

1. FALL PROTECTION may be required.
2. WATCH YOUR STEP if standing on the Jellyfish Filter Deck at any time; Great care and safety must be taken while walking or maneuvering on the Jellyfish Filter Deck. Attentive care must be taken while standing on the Jellyfish Filter Deck at all times to prevent stepping onto a lid, into or through a cartridge hole or slipping on the deck.
3. The Jellyfish Filter Deck can be SLIPPERY WHEN WET.
4. If the Top Slab, Covers or Hatches have not yet been installed, or are removed for any reason, great care must be taken to NOT DROP ANYTHING ONTO THE JELLYFISH FILTER DECK. The Jellyfish Filter Deck and Cartridge Receptacle Rings can be damaged under high impact loads. This type of activity voids all warranties. All damaged items to be replaced at owner's expense.
5. Maximum deck load 2 persons, total weight 450 lbs.

Safety Notice

Jobsite safety is a topic and practice addressed comprehensively by others. The inclusions here are intended to be reminders to whole areas of Safety Practice that are the responsibility of the Owner(s), Manager(s) and Contractor(s). OSHA and Canadian OSH, and Federal, State/Provincial, and Local Jurisdiction Safety Standards apply on any given site or project. The knowledge and applicability of those responsibilities is the Contractor's responsibility and outside the scope of Contech Engineered Solutions.

Confined Space Entry

Secure all equipment and perform all training to meet applicable local and OSHA regulations regarding confined space entry. It is the Contractor's or entry personnel's responsibility to proceed safely at all times.

Personal Safety Equipment

Contractor is responsible to provide and wear appropriate personal protection equipment as needed including, but not limited to safety boots, hard hat, reflective vest, protective eyewear, gloves and fall protection equipment as necessary. Make sure all equipment is staffed with trained and/or certified personnel, and all equipment is checked for proper operation and safety features prior to use.

- Fall protection equipment
- Eye protection
- Safety boots
- Ear protection
- Gloves
- Ventilation and respiratory protection
- Hard hat
- Maintenance and protection of traffic plan

Chapter 1

1.0 – Owner Specific Jellyfish Filter Product Information

Below you will find a reference page that can be filled out according to your Jellyfish Filter specification to help you easily inspect, maintain and order parts for your system.

Owner Name:	
Phone Number:	
Site Address:	
Site GPS Coordinates/unit location:	
Unit Location Description:	
Jellyfish Filter Model No.:	
Contech Project & Sequence Number	
No. of Hi-Flo Cartridges	
No. of Cartridges:	
Length of Draindown Cartridges:	
No. of Blank Cartridge Lids:	
Bypass Configuration (Online/Offline):	


Notes:

Chapter 2

2.0 – Jellyfish Filter System Operations and Functions

The Jellyfish Filter is an engineered stormwater quality treatment technology that removes a high level and wide variety of stormwater pollutants. Each Jellyfish Filter cartridge consists of eleven membrane - encased filter elements (“filtration tentacles”) attached to a cartridge head plate. The filtration tentacles provide a large filtration surface area, resulting in high flow and high pollutant removal capacity.

The Jellyfish Filter functions are depicted in Figure 1 below.




Jellyfish Filter cartridges are backwashed after each peak storm event, which removes accumulated sediment from the membranes. This backwash process extends the service life of the cartridges and increases the time between maintenance events.

For additional details on the operation and pollutant capabilities of the Jellyfish Filter please refer to additional details on our website at www.ContechES.com.

2.1 – Components and Cartridges

The Jellyfish Filter and components are depicted in Figure 2 below.



Tentacles are available in various lengths as depicted in Table 1 below.

Table 1 – Cartridge Lengths / Weights and Cartridge Lid Orifice Diameters

Cartridge Lengths	Dry Weight	Hi-Flo Orifice Diameter	Draindown Orifice Diameter
15 inches (381 mm)	10 lbs (4.5 kg)	35 mm	20 mm
27 inches (686 mm)	14.5 lbs (6.6 kg)	45 mm	25 mm
40 inches (1,016 mm)	19.5 lbs (8.9 kg)	55 mm	30 mm
54 inches (1,372 mm)	25 lbs (11.4 kg)	70 mm	35 mm

2.2 – Jellyfish Membrane Filtration Cartridge Assembly

The Jellyfish Filter utilizes multiple membrane filtration cartridges. Each cartridge consists of removable cylindrical filtration “tentacles” attached to a cartridge head plate. Each filtration tentacle has a threaded pipe nipple and o-ring. To attach, insert the top pipe nipples with the o-ring through the head plate holes and secure with locking nuts. Hex nuts to be hand tightened and checked with a wrench as shown below.

2.3 – Jellyfish Membrane Filtration Cartridge Installation

- Cartridge installation will be performed by trained individuals and coordinated with the installing site Contractor. Flow diversion devices are required to be in place until the site is stabilized (final paving and landscaping in place). Failure to address this step completely will reduce the time between required maintenance.
- Descend to the cartridge deck (see Safety Notice and page 3).
- Refer to Contech's submittal drawings to determine proper quantity and placement of Hi-Flo, Draindown and Blank cartridges with appropriate lids. Lower the Jellyfish membrane filtration cartridges into the cartridge receptacles within the cartridge deck. It is possible that not all cartridge receptacles will be filled with a filter cartridge. In that case, a blank headplate and blank cartridge lid (no orifice) would be installed.



Cartridge Assembly

Do not force the tentacles down into the cartridge receptacle, as this may damage the membranes. Apply downward pressure on the cartridge head plate to seat the lubricated rim gasket (thick circular gasket surrounding the circumference of the head plate) into the cartridge receptacle. (See Figure 3 for details on approved lubricants for use with rim gasket.)

- Examine the cartridge lids to differentiate lids with a small orifice, a large orifice, and no orifice.
 - Lids with a small orifice are to be inserted into the Draindown cartridge receptacles, outside of the backwash pool weir.
 - Lids with a large orifice are to be inserted into the Hi-Flo cartridge receptacles within the backwash pool weir.
 - Lids with no orifice (blank cartridge lids) and a blank headplate are to be inserted into unoccupied cartridge receptacles.
- To install a cartridge lid, align both cartridge lid male threads with the cartridge receptacle female threads before rotating approximately 1/3 of a full rotation until firmly seated. Use of an approved rim gasket lubricant may facilitate installation.

3.0 Inspection and Maintenance Overview

The primary purpose of the Jellyfish® Filter is to capture and remove pollutants from stormwater runoff. As with any filtration system, these pollutants must be removed to maintain the filter's maximum treatment performance. Regular inspection and maintenance are required to insure proper functioning of the system. Maintenance frequencies and requirements are site specific and vary depending on pollutant loading. Additional maintenance activities may be required in the event of non-storm event runoff, such as base-flow or seasonal flow, an upstream chemical spill or due to excessive sediment loading from site erosion or extreme runoff events. It is a good practice to inspect the system after major storm events.

Inspection activities are typically conducted from surface observations and include:


- Observe if standing water is present
- Observe if there is any physical damage to the deck or cartridge lids
- Observe the amount of debris in the Maintenance Access Wall (MAW) or inlet bay for vault systems

Maintenance activities include:

- Removal of oil, floatable trash and debris
- Removal of collected sediments
- Rinsing and re-installing the filter cartridges
- Replace filter cartridge tentacles, as needed

4.0 Inspection Timing

Inspection of the Jellyfish Filter is key in determining the maintenance requirements for, and to develop a history of, the site's pollutant loading characteristics. In general, inspections should be performed at the times indicated below; *or per the approved project stormwater quality documents (if applicable), whichever is more frequent.*



Note: Separator Skirt not shown

1. A minimum of quarterly inspections during the first year of operation to assess the sediment and floatable pollutant accumulation, and to ensure proper functioning of the system.
2. Inspection frequency in subsequent years is based on the inspection and maintenance plan developed in the first year of operation. Minimum frequency should be once per year.
3. Inspection is recommended after each major storm event.
4. Inspection is required immediately after an upstream oil, fuel or other chemical spill.

5.0 Inspection Procedure

The following procedure is recommended when performing inspections:

1. Provide traffic control measures as necessary.
2. Inspect the MAW or inlet bay for floatable pollutants such as trash, debris, and oil sheen.
3. Measure oil and sediment depth in several locations, by lowering a sediment probe until contact is made with the floor of the structure. Record sediment depth, and presences of any oil layers.
4. Inspect cartridge lids. Missing or damaged cartridge lids to be replaced.
5. Inspect the MAW (where appropriate), cartridge deck and receptacles, and backwash pool weir, for damaged or broken components.

5.1 Dry weather inspections

- Inspect the cartridge deck for standing water, and/or sediment on the deck.
- No standing water under normal operating conditions.
- Standing water inside the backwash pool, but not outside the backwash pool indicates, that the filter cartridges need to be rinsed.



Inspection Utilizing Sediment Probe

- Standing water outside the backwash pool is not anticipated and may indicate a backwater condition caused by high water elevation in the receiving water body, or possibly a blockage in downstream infrastructure.
- Any appreciable sediment ($\geq 1/16"$) accumulated on the deck surface should be removed.

5.2 Wet weather inspections

- Observe the rate and movement of water in the unit. Note the depth of water above deck elevation within the MAW or inlet bay.
- Less than 6 inches, flow should be exiting the cartridge lids of each of the draindown cartridges (i.e. cartridges located outside the backwash pool).
- Greater than 6 inches, flow should be exiting the cartridge lids of each of the draindown cartridges and each of the hi-flo cartridges (i.e. cartridges located inside the backwash pool), and water should be overflowing the backwash pool weir.
- 18 inches or greater and relatively little flow is exiting the cartridge lids and outlet pipe, this condition indicates that the filter cartridges need to be rinsed.

6.0 Maintenance Requirements

Required maintenance for the Jellyfish Filter is based upon results of the most recent inspection, historical maintenance records, or the site specific water quality management plan; whichever is more frequent. In general, maintenance requires some combination of the following:

1. Sediment removal for depths reaching 12 inches or greater, or within 3 years of the most recent sediment cleaning, whichever occurs sooner.
2. Floatable trash, debris, and oil removal.
3. Deck cleaned and free from sediment.
4. Filter cartridges rinsed and re-installed as required by the most recent inspection results, or within 12 months of the most recent filter rinsing, whichever occurs sooner.
5. Replace tentacles if rinsing does not restore adequate hydraulic capacity, remove accumulated sediment, or if damaged or missing. It is recommended that tentacles should remain in service no longer than 5 years before replacement.
6. Damaged or missing cartridge deck components must be repaired or replaced as indicated by results of the most recent inspection.
7. The unit must be cleaned out and filter cartridges inspected immediately after an upstream oil, fuel, or chemical spill. Filter cartridge tentacles should be replaced if damaged or compromised by the spill.

7.0 Maintenance Procedure

The following procedures are recommended when maintaining the Jellyfish Filter:

1. Provide traffic control measures as necessary.
2. Open all covers and hatches. Use ventilation equipment as required, according to confined space entry procedures.
Caution: Dropping objects onto the cartridge deck may cause damage.
3. Perform Inspection Procedure prior to maintenance activity.

4. To access the cartridge deck for filter cartridge service, descend into the structure and step directly onto the deck. *Caution: Do not step onto the maintenance access wall (MAW) or backwash pool weir, as damage may result. Note that the cartridge deck may be slippery.*
5. Maximum weight of maintenance crew and equipment on the cartridge deck not to exceed 450 lbs.

7.1 Filter Cartridge Removal

1. Remove a cartridge lid.
2. Remove cartridges from the deck using the lifting loops in the cartridge head plate. Rope or a lifting device (available from Contech) should be used. *Caution: Should a snag occur, do not force the cartridge upward as damage to the tentacles may result. Wet cartridges typically weigh between 100 and 125 lbs.*
3. Replace and secure the cartridge lid on the exposed empty receptacle as a safety precaution. Contech does not recommend exposing more than one empty cartridge receptacle at a time.

7.2 Filter Cartridge Rinsing

1. Remove all 11 tentacles from the cartridge head plate. Take care not to lose or damage the O-ring seal as well as the plastic threaded nut and connector.
2. Position tentacles in a container (or over the MAW), with the



Cartridge Removal & Lifting Device

threaded connector (open end) facing down, so rinse water is flushed through the membrane and captured in the container.

3. Using the Jellyfish rinse tool (available from Contech) or a low-pressure garden hose sprayer, direct water spray onto the tentacle membrane, sweeping from top to bottom along the length of the tentacle. Rinse until all sediment is removed from the membrane. *Caution: Do not use a high pressure sprayer or focused stream of water on the membrane. Excessive water pressure may damage the membrane.*
4. Collected rinse water is typically removed by vacuum hose.

5. Reassemble cartridges as detailed later in this document. Reuse O-rings and nuts, ensuring proper placement on each tentacle.

7.3 Sediment and Floatables Extraction

1. Perform vacuum cleaning of the Jellyfish Filter only after filter cartridges have been removed from the system. Access the lower chamber for vacuum cleaning only through the maintenance access wall (MAW) opening. Be careful not to damage the flexible plastic separator skirt that is attached to the underside of the deck on manhole systems. Do not lower the vacuum wand through a cartridge receptacle, as damage to the receptacle will result.
2. Vacuum floatable trash, debris, and oil, from the MAW opening or inlet bay. Alternatively, floatable solids may be removed by a net or skimmer.
3. Pressure wash cartridge deck and receptacles to remove all



Rinsing Cartridge with Contech Rinse Tool

sediment and debris. Sediment should be rinsed into the sump area. Take care not to flush rinse water into the outlet pipe.

4. Remove water from the sump area. Vacuum or pump equipment should only be introduced through the MAW or inlet bay.
5. Remove the sediment from the bottom of the unit through the MAW or inlet bay opening.
6. For larger diameter Jellyfish Filter manholes (≥ 8 -ft) and some



Vacuuming Sump Through MAW

vaults complete sediment removal may be facilitated by removing a cartridge lid from an empty receptacle and inserting a jetting wand (not a vacuum wand) through the receptacle. Use the sprayer to rinse loosened sediment toward the vacuum hose in the MAW opening, being careful not to damage the receptacle.

7.4 Filter Cartridge Reinstallation and Replacement

1. Cartridges should be installed after the deck has been cleaned. It is important that the receptacle surfaces be free from grit and debris.
2. Remove cartridge lid from deck and carefully lower the filter cartridge into the receptacle until head plate gasket is seated squarely in receptacle. *Caution: Do not force the cartridge downward; damage may occur.*
3. Replace the cartridge lid and check to see that both male threads are properly seated before rotating approximately 1/3 of a full rotation until firmly seated. Use of an approved rim gasket lubricant may facilitate installation. See next page for additional details.
4. If rinsing is ineffective in removing sediment from the tentacles, or if tentacles are damaged, provisions must be made to replace the spent or damaged tentacles with new tentacles. Contact Contech to order replacement tentacles.

7.5 Chemical Spills

Caution: If a chemical spill has been captured, do not attempt maintenance. Immediately contact the local hazard response agency and contact Contech.

7.6 Material Disposal

The accumulated sediment found in stormwater treatment and conveyance systems must be handled and disposed of in accordance with regulatory protocols. It is possible for sediments to contain measurable concentrations of heavy metals and organic chemicals (such as pesticides and petroleum products). Areas with the greatest potential for high pollutant loading include industrial areas and heavily traveled roads. Sediments and water must be disposed of in accordance with all applicable waste disposal regulations. When scheduling maintenance, consideration must be made for the disposal of solid and liquid wastes. This typically requires coordination with a local landfill for solid waste disposal. For liquid waste disposal a number of options are available including a municipal vacuum truck decant facility, local waste water treatment plant or on-site treatment and discharge.

Jellyfish Filter Components & Filter Cartridge Assembly and Installation





TABLE 1: BOM

ITEM NO.	DESCRIPTION
1	JF HEAD PLATE
2	JF TENTACLE
3	JF O-RING
4	JF HEAD PLATE GASKET
5	JF CARTRIDGE EYELET
6	JF 14IN COVER
7	JF RECEPTACLE
8	BUTTON HEAD CAP SCREW M6X14MM SS
9	JF CARTRIDGE NUT

TABLE 2: APPROVED GASKET LUBRICANTS

PART NO.	MFR	DESCRIPTION
78713	LA-CO	LUBRI-JOINT
40501	HERCULES	DUCK BUTTER
30600	OATEY	PIPE LUBRICANT
PSLUBXL1Q	PROSELECT	PIPE JOINT LUBRICANT

NOTES:

Head Plate Gasket Installation:

Install Head Plate Gasket (Item 4) onto the Head Plate (Item 1) and liberally apply a lubricant from Table 2: Approved Gasket Lubricants onto the gasket where it contacts the Receptacle (Item 7) and Cartridge Lid (Item 6). Follow Lubricant manufacturer's instructions.

Lid Assembly:

Rotate Cartridge Lid counter-clockwise until both male threads drop down and properly seat. Then rotate Cartridge Lid clock-wise approximately one-third of a full rotation until Cartridge Lid is firmly secured, creating a watertight seal.

Jellyfish Filter Inspection and Maintenance Log

Owner: _____ Jellyfish Model No.: _____

Location: _____ GPS Coordinates: _____

Land Use: Commercial: _____ Industrial: _____ Service Station: _____

Road/Highway: _____ Airport: _____ Residential: _____ Parking Lot: _____

Date/Time:					
Inspector:					
Maintenance Contractor:					
Visible Oil Present: (Y/N)					
Oil Quantity Removed					
Floatable Debris Present: (Y/N)					
Floatable Debris removed: (Y/N)					
Water Depth in Backwash Pool					
Cartridges externally rinsed/re-commissioned: (Y/N)					
New tentacles put on Cartridges: (Y/N)					
Sediment Depth Measured: (Y/N)					
Sediment Depth (inches or mm):					
Sediment Removed: (Y/N)					
Cartridge Lids intact: (Y/N)					
Observed Damage:					
Comments:					


PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT G
INSPECTION, MAINTENANCE, REPAIR AND RETROFIT PLAN

The proposed Jellyfish® Treatment Unit will be manufactured by Contech® Engineered Solutions. Contech® Engineered Solutions also provides an Owner's Manual for each unit, which include inspection schedules and procedures (including logs), along with maintenance and repair procedures. Both Owner's Manuals are included herein.

The engineer of the civil site plan for grading and drainage, M. Tyler Meals, P.E., specified the use of the proposed treatment units and further recommends adoption and implementation of the Owner's Manual for each of the proposed treatment units.

Signature

As the Owner of this Regulated Entity, Woodmont Helotes, I intend to adopt and implement the inspection, maintenance, and repair procedures as indicated in the Owner's Manual for each of the proposed treatment units included herein.

Signed by:	
	1/9/2025
Signature of Customer	Date

WOODMONT HELOTES ACADEMY
By: Woodmont KA Helotes GP LLC, its manager
By: Stephen Coslik, Manager
Print Name of Customer

PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT H
PILOT-SCALE FIELD TESTING PLAN

Not applicable.

PERMANENT STORMWATER SECTION FORM TCEQ-0600
ATTACHMENT I
MEASURES FOR MINIMIZING SURFACE STREAM CONTAMINATION

Not applicable.

SECTION 8.0

AGENT AUTHORIZATION FORM

Agent Authorization Form
For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

I STEPHEN COSLIK
Print Name

OWNER
Title - Owner/President/Other

of WOODMONT HELOTES ACADEMY, LLC
Corporation/Partnership/Entity Name

have authorized M. TYLER MEALS
Print Name of Agent/Engineer

of MEALS-MYERS ENGINEERING & SURVEYING, LLC
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

WOODMONT HELOTES ACADEMY LLC

By: Woodmont KA Helotes GP LLC, its manager

By: Stephen Coslik, Manager

Stephen Coslik

Applicant's Signature

1-7-25
Date

THE STATE OF Texas §


County of Tarrant §

BEFORE ME, the undersigned authority, on this day personally appeared Stephen Coslik known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 7 day of Jan, 2025

[Signature]
NOTARY PUBLIC

Tabitha Carter
Typed or Printed Name of Notary



MY COMMISSION EXPIRES: 1-12-27

SECTION 9.0

APPLICATION FEE FORM

Application Fee Form

Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: Woodmont Helotes

Regulated Entity Location: Approx. 1,400 feet west of Loop 1604 intersection with FM 1560, on the south side of the FM 1560 right-of-way

Name of Customer: Woodmont Helotes Academy, LLC

Contact Person: Stephen Coslik

Phone: (817) 377-7710

Customer Reference Number (if issued):CN _____

Regulated Entity Reference Number (if issued):RN _____

Austin Regional Office (3373)

☐ Hays

☐ Travis

☐ Williamson

San Antonio Regional Office (3362)

☒ Bexar

☐ Medina

☐ Uvalde

☐ Comal

☐ Kinney

Application fees must be paid by check, certified check, or money order, payable to the Texas Commission on Environmental Quality. Your canceled check will serve as your receipt. This form must be submitted with your fee payment. This payment is being submitted to:

☐ Austin Regional Office

☒ San Antonio Regional Office

☐ Mailed to: TCEQ - Cashier

☐ Overnight Delivery to: TCEQ - Cashier

Revenues Section

Mail Code 214

P.O. Box 13088

Austin, TX 78711-3088

12100 Park 35 Circle

Building A, 3rd Floor

Austin, TX 78753

(512)239-0357

Site Location (Check All That Apply):

☒ Recharge Zone

☐ Contributing Zone

☐ Transition Zone

Type of Plan	Size	Fee Due
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	5.863 Acres	\$ 5,000
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: 

Date: 01/10/2025

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

Project	Project Area in Acres	Fee
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

Project	Cost per Linear Foot	Minimum Fee- Maximum Fee
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

Project	Cost per Tank or Piping System	Minimum Fee- Maximum Fee
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

Project	Fee
Exception Request	\$500

Extension of Time Requests

Project	Fee
---------	-----

Project	Fee
Extension of Time Request	\$150

SECTION 10.0

CORE DATA FORM



TCEQ Use Only

TCEQ Core Data Form

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)	
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)	
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input type="checkbox"/> Other
2. Customer Reference Number (if issued)	3. Regulated Entity Reference Number (if issued)
CN	RN

[Follow this link to search for CN or RN numbers in Central Registry**](#)

SECTION II: Customer Information

4. General Customer Information		5. Effective Date for Customer Information Updates (mm/dd/yyyy)	
<input checked="" type="checkbox"/> New Customer <input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)		<input type="checkbox"/> Update to Customer Information <input type="checkbox"/> Change in Regulated Entity Ownership	
The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).			
6. Customer Legal Name (If an individual, print last name first: eg: Doe, John)		If new Customer, enter previous Customer below:	
Woodmont Helotes Academy, LLC			
7. TX SOS/CPA Filing Number	8. TX State Tax ID (11 digits)	9. Federal Tax ID (9 digits)	10. DUNS Number (if applicable)
804307820	87-3735603	87-3498419	
11. Type of Customer:	<input checked="" type="checkbox"/> Corporation	<input type="checkbox"/> Individual	Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> State <input type="checkbox"/> Other	<input type="checkbox"/> Sole Proprietorship	<input type="checkbox"/> Other:	
12. Number of Employees		13. Independently Owned and Operated?	
<input checked="" type="checkbox"/> 0-20 <input type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher		<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
14. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following			
<input checked="" type="checkbox"/> Owner <input type="checkbox"/> Operator <input type="checkbox"/> Owner & Operator <input type="checkbox"/> Occupational Licensee <input type="checkbox"/> Responsible Party <input type="checkbox"/> Voluntary Cleanup Applicant <input type="checkbox"/> Other:			
15. Mailing Address:	2100 West 7 th Street		
	City	Fort Worth	State TX ZIP 76017 ZIP + 4
16. Country Mailing Information (if outside USA)		17. E-Mail Address (if applicable)	
		scoslik@woodmont.com	
18. Telephone Number	19. Extension or Code	20. Fax Number (if applicable)	
(817) 377-7710		() -	

SECTION III: Regulated Entity Information

21. General Regulated Entity Information (If 'New Regulated Entity' is selected below this form should be accompanied by a permit application)
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information
The Regulated Entity Name submitted may be updated in order to meet TCEQ Agency Data Standards (removal of organizational endings such as Inc, LP, or LLC).
22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)
Woodmont Helotes

23. Street Address of the Regulated Entity: <i>(No PO Boxes)</i>	2100 West 7 th Street							
	City	Fort Worth	State	TX	ZIP	76017	ZIP + 4	
24. County								

Enter Physical Location Description if no street address is provided.

25. Description to Physical Location:	Approx. 1,400 feet west of Loop 1604 intersection with FM 1560, on the south side of the FM 1560 right-of-way.								
26. Nearest City	San Antonio				State	TX		Nearest ZIP Code	78023
27. Latitude (N) In Decimal:	29.568444			28. Longitude (W) In Decimal:	98.657731				
Degrees	Minutes	Seconds	Degrees	Minutes	Seconds				
29	34	6.4	98	39	27.83				
29. Primary SIC Code (4 digits)	30. Secondary SIC Code (4 digits)		31. Primary NAICS Code (5 or 6 digits)		32. Secondary NAICS Code (5 or 6 digits)				
1522	5311		23611		2362				
33. What is the Primary Business of this entity? <i>(Do not repeat the SIC or NAICS description.)</i>									
Residential Town Homes (Lot 3) / Commercial Strip Center (Lot 1)									
34. Mailing Address:	2100 West 7 th Street								
	City	Forth Worth	State	TX	ZIP	76017	ZIP + 4		
35. E-Mail Address:	scoslik@woodmont.com								
36. Telephone Number	37. Extension or Code		38. Fax Number <i>(if applicable)</i>						
() -			() -						

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.


<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input checked="" type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Waste Water	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

SECTION IV: Preparer Information

40. Name:	M. Tyler Meals	41. Title:	P.E.
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address
(210) 740-2483		() -	tyler@mealsmyers.com

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	Woodmont Helotes Academy, LLC	Job Title:	Manager
Name <i>(In Print)</i> :	By: Woodmont KA Helotes GP LLC Its manager, By: Stephen Coslik		Phone:
Signature:			Date:
			1/25/2025

F1394D00138D43C...



MEALS★MYERS
ENGINEERING & SURVEYING LLC