TEXAS SOIL AND STONE TCEQ CONTRIBUTING ZONE PLAN 27220 BULVERDE ROAD

July 15, 2025

MBC Job. No.33109-1480

PREPARED BY:





MACINA · BOSE · COPELAND AND ASSOCIATES, INC.
dba MBC Engineers

Texas Registered Engineering Firm F-784 | SBE Certified #214046463

TBPLS Firm Registration No. 10011700

1035 Central Parkway North | San Antonio, Texas 78232

(210) 545-1122 Phone | (210) 545-9302 Fax

www.mbcengineers.com

Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with 30 TAC 213.

Administrative Review

- Edwards Aquifer applications must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.
 - To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: http://www.tceq.texas.gov/field/eapp.
- 2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
- 3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
- 4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.
 - An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.
- 5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
- 6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

- When an application is deemed administratively complete, the technical review period begins. The regional
 office will distribute copies of the application to the identified affected city, county, and groundwater
 conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days
 to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
- 2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

- clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.
- 3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
- 4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

Regulated Entity Name: Texas Soil and Stone Outfitters			2. Regulated Entity No.:					
3. Customer Name: L Cinco Properties, LLC		4. Customer No.:						
5. Project Type: (Please circle/check one)	New	Modif	ication	1	Exter	nsion	Exception	
6. Plan Type: (Please circle/check one)	WPAP CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Residential	Non-r	esiden	tial		8. Sit	e (acres):	5.338
9. Application Fee:	\$5,000.00	10. Permanent B		BMP(s):		N/A		
11. SCS (Linear Ft.):	N/A	12. AST/UST (No			o. Tar	o. Tanks): N/A		
13. County:	Bexar	14. Watershed:				Cibolo Creek		

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%2oGWCD%2omap.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region						
County:	Hays	Travis	Williamson			
Original (1 req.)	_	_	_			
Region (1 req.)	_	_	_			
County(ies)		_	_			
Groundwater Conservation District(s)	Edwards Aquifer AuthorityBarton Springs/ Edwards AquiferHays TrinityPlum Creek	Barton Springs/ Edwards Aquifer	NA			
City(ies) Jurisdiction	AustinBudaDripping SpringsKyleMountain CitySan MarcosWimberleyWoodcreek	AustinBee CavePflugervilleRollingwoodRound RockSunset ValleyWest Lake Hills	AustinCedar ParkFlorenceGeorgetownJerrellLeanderLiberty HillPflugervilleRound Rock			

San Antonio Region							
County:	Bexar	Comal	Kinney	Medina	Uvalde		
Original (1 req.)	⊻	_	_	_	_		
Region (1 req.)	$\underline{\checkmark}$	_	_		_		
County(ies)	$\underline{\checkmark}$	_	_		_		
Groundwater Conservation District(s)	√_Edwards Aquifer AuthorityTrinity-Glen Rose	Edwards Aquifer Authority	Kinney	EAA Medina	EAA Uvalde		
City(ies) Jurisdiction	Castle HillsFair Oaks RanchHelotesHill Country VillageHollywood Park √_San Antonio (SAWS)Shavano Park	BulverdeFair Oaks RanchGarden RidgeNew BraunfelsSchertz	NA	San Antonio ETJ (SAWS)	NA		

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.
Richard Hendrix, P.E.
Print Name of Customer/Authorized Agent
M HW 7/15/2025
Signature of Customer/Authorized Agent Date

FOR TCEQ INTERNAL USE ON	LY			
Date(s)Reviewed:		Date Adr	ninistratively Complet	te:
Received From:		Correct N	Number of Copies:	'
Received By:	2	Distribut	ion Date:	
EAPP File Number:		Complex:		
Admin. Review(s) (No.):		No. AR Rounds:		
Delinquent Fees (Y/N):		Review Time Spent:		
Lat./Long. Verified:		SOS Customer Verification:		
Agent Authorization Complete/Notarized (Y/N):		Fee	Payable to TCEQ (Y/	'N):
Core Data Form Complete (Y/N):		Check: Signed (Y/N):		
Core Data Form Incomplete Nos.:		Less than 90 days old (Y/N):		d (Y/N):

Contributing Zone Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Contributing Zone to the Edwards Aquifer and Relating to 30 TAC §213.24(1), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Contributing Zone Plan Application** is hereby submitted for TCEQ review and Executive Director approval. The application was prepared by:

Print Name of Customer/Agent: Richard Hendrix, P.E.

Date: 7/15/2025

Signature of Customer/Agent:

Regulated Entity Name: <u>Texas Soil and Stone Outfitters</u>

Project Information

1. County: Bexar

2. Stream Basin: Cibolo Creek

3. Groundwater Conservation District (if applicable): Edwards Aquifer Authority

4. Customer (Applicant):

Contact Person: <u>Matt Lackey</u> Entity: <u>L Cinco Properties</u>, LLC

Mailing Address: 2301 Flushing Meadows

City, State: Weslaco, Texas Zip: 78596 Telephone: (210)865-2953 Fax: N/A

Email Address: matt@jrproducesupply.com

5.	Agent/Representative (If any):
	Contact Person: Richard Hendrix, P.E. Entity: Macina, Bose, Copeland & Asscoiates Mailing Address: 1035 Central Parkway N. City, State: San Antonio, Texas Telephone: 210.545.1122 Email Address: rhendrix@mbcengineers.com
6.	Project Location:
	 ☐ The project site is located inside the city limits of ☐ The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of <u>San Antonio</u>. ☐ The project site is not located within any city's limits or ETJ.
7.	The location of the project site is described below. Sufficient detail and clarity has been provided so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.
	27220 Bulverde Road, 3,700' N of Hwy 281 and Bulverde Road, City of San Antonio, Bexar County.
8.	Attachment A - Road Map. A road map showing directions to and the location of the project site is attached. The map clearly shows the boundary of the project site.
9.	Attachment B - USGS Quadrangle Map. A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') is attached. The map(s) clearly show:
	✓ Project site boundaries.✓ USGS Quadrangle Name(s).
10	Attachment C - Project Narrative. A detailed narrative description of the proposed project is attached. The project description is consistent throughout the application and contains, at a minimum, the following details:
	 ✓ Area of the site ✓ Offsite areas ✓ Impervious cover ✓ Permanent BMP(s) ✓ Proposed site use ✓ Site history ✓ Previous development ✓ Area(s) to be demolished
11	. Existing project site conditions are noted below:
	Existing commercial site Existing industrial site

	 □ Existing residential site □ Existing paved and/or unpaved roads □ Undeveloped (Cleared) □ Undeveloped (Undisturbed/Not cleared) □ Other: Cleared with existing buildings, drive aisle/pavement and material storage areas.
12.	The type of project is:
	Residential: # of Lots: Residential: # of Living Unit Equivalents: Commercial Industrial Other:
13.	Total project area (size of site): <u>5.338</u> Acres
	Total disturbed area: <u>5.338</u> Acres
14.	Estimated projected population: N/A

Table 1 - Impervious Cover

below:

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	2,669	÷ 43,560 =	0.061
Parking	175,961	÷ 43,560 =	4.040
Other paved surfaces	0	÷ 43,560 =	0
Total Impervious Cover	178,630	÷ 43,560 =	4.101

15. The amount and type of impervious cover expected after construction is complete is shown

Total Impervious Cover $4.101 \div$ Total Acreage $5.338 \times 100 = 76.81\%$ Impervious Cover

16. Attachment D - Factors Affecting Surface Water Quality. A detailed description of all
factors that could affect surface water quality is attached. If applicable, this includes the
location and description of any discharge associated with industrial activity other than
construction.

17. \boxtimes Only inert materials as defined by 30 TAC 330.2 will be used as fill material.

For Road Projects Only

Complete questions 18 - 23 if this application is exclusively for a road project.

X	N/A

18. Type of project:
 TXDOT road project. County road or roads built to county specifications. City thoroughfare or roads to be dedicated to a municipality. Street or road providing access to private driveways.
19. Type of pavement or road surface to be used:
Concrete Asphaltic concrete pavement Other:
20. Right of Way (R.O.W.):
Length of R.O.W.: feet. Width of R.O.W.: feet. $L \times W = Ft^2 \div 43,560 Ft^2/Acre = acres.$
21. Pavement Area:
Length of pavement area: feet. Width of pavement area: feet. L x W = Ft 2 ÷ 43,560 Ft 2 /Acre = acres. Pavement area acres ÷ R.O.W. area acres x 100 = % impervious cover.
22. A rest stop will be included in this project.
A rest stop will not be included in this project.
23. Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.
Stormwater to be generated by the Proposed Project
24. Attachment E - Volume and Character of Stormwater. A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.
Wastewater to be generated by the Proposed Project
25. Wastewater is to be discharged in the contributing zone. Requirements under 30 TAC §213.6(c) relating to Wastewater Treatment and Disposal Systems have been satisfied. N/A

5		To	 otal x 1.5 = Gallons
5			
"			
4			
3			
2			
AST Number	Size (Gallons)	Substance to be Stored	Tank Material
Table 2 - Tanks and	Substance Storage	T	T
27. Tanks and substanc	e stored:		
⊠N/A			
greater than or equal t	o 500 gallons.		
Gallons	- 33 if this project inclu		-
<u> </u>	oveground Sto	rage Tanks(AS)	Ts) ≥ 500
⊠ N/A			
Existing. Proposed.			
The sewage collecti Recycling Center (na	on System (Sewer Lines) on system will convey thame) Treatment Plant	ne wastewater to the <u>Le</u>	
	on Custom (Course Lines)		
the requiren relating to O Each lot in th size. The sys	•	e facilities as specified un t is at least one (1) acre to a licensed professional	nder 30 TAC Chapter 285 (43,560 square feet) in engineer or registered
will be used licensing aut	F - Suitability Letter fro to treat and dispose of the chority's (authorized age uitable for the use of pri	the wastewater from the ent) written approval is a	attached. It states that
On-Site Sewage	Facility (OSSF/Septic Ta	nk):	
20. Wastewater will be	disposed of by:		

5 of 11

•	stem, the containm umulative storage c		ed to capture one an ns.	d one-half (1 1/2)
for providin		nment are propose	ent Methods. Alternd. Specifications sho	
	ons and capacity of o		ure(s):	
Length (L)(Ft.)	Width(W)(Ft.)	Height (H)(Ft.)	L x W x H = (Ft3)	Gallons
			To	otal: Gallons
Some of the structure. The piping v The piping v The contain	e piping to dispense vill be aboveground vill be underground ment area must be	rs or equipment wi constructed of and	side the containmen Il extend outside the I in a material imper ment structure will b	e containment vious to the
	t H - AST Containme It structure is attach		ings. A scaled drawifollowing:	ing of the
Internal Tanks cle	, -	•	wall and floor thickn collection of any sp	•
storage tan			For collection and recontrolled drainage a	
	vent of a spill, any s 4 hours of the spill	_	oved from the contai operly.	nment structure

In the event of a spill, any spillage will be drained from the containment structure through a drain and valve within 24 hours of the spill and disposed of properly. The drain and valve system are shown in detail on the scaled drawing.
Site Plan Requirements
tems 34 - 46 must be included on the Site Plan.
4. \square The Site Plan must have a minimum scale of 1" = 400'.
Site Plan Scale: 1" = <u>40</u> '.
5. 100-year floodplain boundaries:
 Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled. No part of the project site is located within the 100-year floodplain. The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FEMA Map Panel No. 48029C0130G 9-29-2010.
6. The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot contour intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
7. \boxtimes A drainage plan showing all paths of drainage from the site to surface streams.
8. $igwidge$ The drainage patterns and approximate slopes anticipated after major grading activities.
9. 🔀 Areas of soil disturbance and areas which will not be disturbed.
0. \(\sum \) Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
1. $igsquare$ Locations where soil stabilization practices are expected to occur.
2. Surface waters (including wetlands).
⊠ N/A
3. Locations where stormwater discharges to surface water.
There will be no discharges to surface water.
4. Temporary aboveground storage tank facilities.
$oxed{\boxtimes}$ Temporary aboveground storage tank facilities will not be located on this site.

45. 🗌	Permanent aboveground storage tank facilities.
\boxtimes	Permanent aboveground storage tank facilities will not be located on this site.
46. 🔀	Legal boundaries of the site are shown.
Pern	nanent Best Management Practices (BMPs)
Practic	es and measures that will be used during and after construction is completed.
	Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
48. 🔀	N/A These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
	 The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site. A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is:
	N/A
	Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
	N/A
less per per who App	ere a site is used for low density single-family residential development and has 20 % or impervious cover, other permanent BMPs are not required. This exemption from manent BMPs must be recorded in the county deed records, with a notice that if the cent impervious cover increases above 20% or land use changes, the exemption for the ole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to olication Processing and Approval), may no longer apply and the property owner must ify the appropriate regional office of these changes.
	 □ The site will be used for low density single-family residential development and has 20% or less impervious cover. □ The site will be used for low density single-family residential development but has more than 20% impervious cover. □ The site will not be used for low density single-family residential development.


far im rec ind the an	e executive director may waive the requirement for other permanent BMPs for multi- mily residential developments, schools, or small business sites where 20% or less pervious cover is used at the site. This exemption from permanent BMPs must be corded in the county deed records, with a notice that if the percent impervious cover creases above 20% or land use changes, the exemption for the whole site as described in e property boundaries required by 30 TAC §213.4(g) (relating to Application Processing d Approval), may no longer apply and the property owner must notify the appropriate gional office of these changes.
	 Attachment I - 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached. ☑ The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover. ☑ The site will not be used for multi-family residential developments, schools, or small business sites.
52. 🔀	Attachment J - BMPs for Upgradient Stormwater.
	 A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached. No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached. Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
53. 🔀	Attachment K - BMPs for On-site Stormwater.
	 A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached. Permanent BMPs or measures are not required to prevent pollution of surface wate or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
54. 🔀	Attachment L - BMPs for Surface Streams. A description of the BMPs and measures that prevent pollutants from entering surface streams is attached.
] N/A
55. 🔀	Attachment M - Construction Plans. Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. Construction plans for the proposed permanent BMPs and measures are

	attached and include: Design calculations, TCEQ Construction Notes, all proposed structural plans and specifications, and appropriate details.
	N/A
56.	Attachment N - Inspection, Maintenance, Repair and Retrofit Plan . A site and BMP specific plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan fulfills all of the following:
	 ☑ Prepared and certified by the engineer designing the permanent BMPs and measures ☑ Signed by the owner or responsible party
	Outlines specific procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofit. Contains a discussion of record keeping procedures
	N/A
57.	Attachment O - Pilot-Scale Field Testing Plan . Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
\boxtimes	N/A
58.	Attachment P - Measures for Minimizing Surface Stream Contamination. A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that result in water quality degradation.
\boxtimes	N/A
-	consibility for Maintenance of Permanent BMPs and sures after Construction is Complete.
59.	The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
60.	A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development,

or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.

Administrative Information


- 61. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions.
- 62. Any modification of this Contributing Zone Plan may require TCEQ review and Executive Director approval prior to construction, and may require submission of a revised application, with appropriate fees.
- 63. The site description, controls, maintenance, and inspection requirements for the storm water pollution prevention plan (SWPPP) developed under the EPA NPDES general permits for stormwater discharges have been submitted to fulfill paragraphs 30 TAC §213.24(1-5) of the technical report. All requirements of 30 TAC §213.24(1-5) have been met by the SWPPP document.
 - The Temporary Stormwater Section (TCEQ-0602) is included with the application.





1035 Central Parkway North San Antonio, Texas 78232 (210) 545–1122 FAX (210) 545–9302 TEXAS REGISTERED ENGINEERING FIRM F–784 TEXAS SOIL & STONE 27220 BULVERDE ROAD SAN ANTONIO, TEXAS ROAD MAP

DESIGN RH			
DRAWNRH			
CHECKED RH	_		
	—		
DATE MAY 2025			
_{JOB NO.} 1480-3310	9		
ATTACHMENT A			






1035 Central Parkway North San Antonio, Texas 78232 (210) 545-1122 FAX (210) 545-9302 FIRM REGISTRATION NUMBER: T.B.P.E. F-784 & T.B.P.L.S. 10011700

TEXAS SOIL & STONE CZP **BULVERDE ROAD** VICINITY MAP



DESIGN RHDRAWN RHCHECKED 05-15-2025 DATE 33109-1480 JOB NO. 1 OF 1 **PAGE**





1035 Central Parkway North San Antonio, Texas 78232 (210) 545–1122 FAX (210) 545–9302 TEXAS REGISTERED ENGINEERING FIRM F–784 TEXAS SOIL AND STONE
BULVERDE ROAD
SAN ANTONIO, TEXAS
USGS EXHIBIT

DESIGN _	RH
DRAWN	RH
J	RH
CHECKED	05-15-2025
DAIL	
JOB NO.	33109-1480

CONTRIBUTING ZONE PLAN APPLICATION

Texas Soil and Stone Outfitters
TCEQ Form-10257

Attachment "C" - Project Narrative

Introduction

Texas Soil and Stone is an existing commercial development. The 5.34-acre site is located at 27220 Bulverde Road. The property is located within the ETJ of the City of San Antonio and Bexar County. The site is developed as a commercial soil and stone wholesale business, and has mild slopes averaging 3% to 5%, sloping from south to north. As part of this CZP report, the existing onsite detention pond will be reconstructed as a batch detention pond to provide water quality treatment and vegetated filter strips will be installed along the property boundary to treat runoff that does not drain to the pond. The limits of construction associated with the proposed project cover an area of approximately 5.34 acres. There will be no increase in impervious cover with this application.

No portion of the site is located in the Federal Emergency Management Agency's 100-year floodplain according to FIRM 48029C0130G dated September 29, 2010. The site is located within the Edwards Aquifer Contributing Zone according to TCEQ Edwards Aquifer Map.

Attachment "D" - Factors Affecting Surface Water Quality

The only factor will be the sedimentation runoff off from the existing site. This will be addressed with erosion control measures as expressed in detail on the erosion control plan sheet to include silt fencing, construction entrance, rock berm, vegetated filter strips, and batch detention pond.

Attachment "E" - Volume and Character of Stormwater

Since the proposed project will have no increase in impervious cover, there will be no increase in storm water runoff or pollutants resulting from the site to treat.

The volume of storm water runoff is a function of rainfall rate, runoff rate, and the duration of time measurement. Storm water runoff generated from the site will come from pervious areas. Runoff will be treated by silt fencing and construction entrance. No unusual contaminants other than oil and grease from construction equipment are expected. The following runoff coefficients are based on City of San Antonio Drainage Criteria Manual:

- Pre-Development Runoff Coefficient = 0.87
- Post-Development Runoff Coefficient = 0.87

Attachment "F" - Sustainability Letter from Authorized Agent

Not applicable.

Attachment "G" – Alternative Secondary Containment Methods

Not applicable.

Attachment "H" – AST Containment Structure Drawings

CONTRIBUTING ZONE PLAN APPLICATION

Texas Soil and Stone Outfitters
TCEQ Form-10257

Not applicable.

Attachment "I" – 20% or Less Impervious Cover Waiver

Not applicable.

Attachment "J" – BMP for Upgradient Storm Water

No storm water flow originates upgradient from the site.

Attachment "K" - BMP for On-Site Storm Water


The proposed post development of the Texas Soil and Stone Outfitters project will utilize permanent grass and concrete (within the paving) swales located throughout the site that will direct the storm water run-off to the batch detention basin. The BMP has been designed to remove a minimum of 80% of the "TSS" from the storm water runoff.

Attachment "L" - BMP for Surface Streams

The proposed batch detention basin will remove pollutants from stormwater runoff before it leaves the site.

Attachment "M" - Construction Plans

See attached construction plans on the following pages.



PRIMARY CONTACT: RICHARD HENDRIX, P.E.

180498 33109-1480

EROSION CONTROL PLAN

EX-003

CONCRETE TRUCK WASHOUT PIT

WASHOUT PIT GENERAL NOTES:


DETAILS ILLUSTRATE MINIMUM DIMENSIONS PIT CAN F INCREASED IN SIZE DEPENDING ON EXPECTED FREQUENCY OF

IF HAY BALES ARE USED FOR BERM, THEY SHALL BE ANCHORED IN PLACE WITH 2 REBARS PER BALE, DRIVEN INTO GROUND ENOUGH TO PROVIDE REASONABLE STABILITY.

WASHOUT PIT SHALL BE LOCATED IN AN AREA EASILY ACCESSIBLE TO CONSTRUCTION TRAFFIC.

WASHOUT PIT SHALL NOT BE LOCATED IN AREA SUBJECT TO INUNDATION FROM STORM WATER RUNOFF. PIT SHALL NOT BE LOCATED OVER OR IN THE IMMEDIATE VICINITY

OF A FEATURE OF GROUNDWATER RECHARGE.



SILT FENCE DETAIL

SILT FENCE NOTES:

. STEEL POSTS, WHICH SUPPORT THE SILT FENCE, SHOULD BE INSTALLED ON A SLIGHT ANGLE TOWARD THE ANTICIPATED RUNOFF SOURCE. POST MUST BE EMBEDDED A

2. LAY OUT FENCING DOWN-SLOPE OF DISTURBED AREA, FOLLOWING THE CONTOUR AS CLOSELY AS POSSIBLE. THE FENCE SHOULD BE SITED SO THAT THE MAXIMUM DRAINAGE AREA IS 130 ACRE/100 FEET OF FENCE.

THE TOE OF THE SILT FENCE SHOULD BE TRENCHED IN WITH A SPADE OR MECHANICAL TRENCHER, SO THAT THE DOWN-SLOPE FACE OF THE TRENCH IS FLAT. AND PERPENDICULAR TO THE LINE OF FLOW. WHERE FENCE CANNOT BE TRENCHED IN (E.G., PAVEMENT OR ROCK OUTCROP), WEIGHT FABRIC FLAP WITH 3 INCHES OF PEA GRAVEL ON UPHILL SIDE TO PREVENT FLOW FROM SEEPING UNDER FENCE

4. THE TRENCH MUST BE A MINIMUM OF 6 INCHES DEEP AND 6 INCHES WIDE TO ALLOW FOR THE SILT FENCE FABRIC TO BE LAID IN THE GROUND AND BACKFILLED WITH COMPACTED

5. SILT FENCE SHOULD BE SECURELY FASTENED TO EACH STEEL SUPPORT POST OR TO WOVEN WIRE, WHICH IS IN TURN ATTACHED TO THE STEEL FENCE POST. THERE SHOULD BE A 3-FOOT OVERLAP, SECURELY FASTENED WHERE ENDS OF FABRIC MEET.

6. INSPECT ALL FENCING WEEKLY, AND AFTER ANY RAINFALL. REPAIR OR REPLACEMENT SHALL BE MADE PROMPTLY, AS NEEDED.

7. ACCUMULATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF 6 INCHES. THE SILT SHALL BE DISPOSED OF IN AN APPROVED SITE AND IN SUCH A MANNER AS TO NOT

CONTRIBUTE TO ADDITIONAL SILTATION.


B. REPLACE ANY TORN FABRIC OR INSTALL A SECOND LINE OF FENCING PARALLEL TO THE


. REPLACE OR REPAIR ANY SECTIONS CRUSHED OR COLLAPSED IN THE COURSE OF CONSTRUCTION ACTIVITY. IF A SECTION OF FENCE IS OBSTRUCTING VEHICULAR ACCESS, CONSIDER RELOCATING IT TO A SPOT WHERE IT WILL PROVIDE EQUAL PROTECTION, BUT VILL NOT OBSTRUCT VEHICLES. A TRIANGULAR FILTER DIKE MAY BE PREFERABLE TO A SILT FENCE AT COMMON VEHICLE ACCESS POINTS.

10. WHEN CONSTRUCTION IS COMPLETE, THE SEDIMENT SHOULD BE DISPOSED OF IN A MANNER THAT WILL NOT CAUSE ADDITIONAL SILTATION AND THE PRIOR LOCATION OF THE SILT FENCE SHOULD BE REVEGETATED. THE FENCE ITSELF SHOULD BE DISPOSED OF IN A PPROVED LANDFILL.

1. DESIGNATED SILT FENCE CONSIST OF THE FOLLOWING: GEOTECHNICAL FILTER FABRIC, STRETCHED AND SECURED TO THREE FOOT HIGH WIRE FENCING AND SUPPORTED BY STEEL POSTS AT A MAXIMUM SPACING OF 6 FEET. THE BOTTOM 6 INCHES OF FABRIC SHALL

2. MAINTENANCE AND INSPECTIONS SHALL BE AS DESIGNATED IN THE STORM WATER





THE BERM STRUCTURE SHOULD BE SECURED WITH A WOVEN WIRE SHEATHING HAVING MAXIMUM OPENING OF 1 INCH AND A MINIMUM WIRE DIAMETER OF 20 GAUGE GALVANIZED AND SHOULD BE SECURED WITH SHOAT

. CLEAN, OPEN GRADED 3 TO 5 INCH DIAMETER ROCK SHOULD BE USED EXCEPT IN AREAS WHERE HIGH VELOCITIES OR LARGE VOLUMES OF FLOW ARE EXPECTED, WHERE 5 TO 8 INCH DIAMETER ROCKS MAY BE USED.

BERM SHOULD HAVE A TOP WIDTH OF 2 FEET MINIMUM WITH SIDE SLOPES BEING 2:1 (H:V) OR FLATTER. HEIGHT OF ROCK BERM SHALL NOT BE LESS THAN

. WRAP THE WIRE SHEATHING AROUND THE ROCK AND SECURE WITH TIE WIRE SO THAT THE ENDS OF THE SHEATHING OVERLAP AT LEAST 2 INCHES. AND THE BERM RETAINS ITS SHAPE WHEN WALKED UPON.

5. THE ENDS OF THE BERM SHOULD BE TIED INTO EXISTING UPSLOPE GRADE AND THE BERM SHOULD BE BURIED IN A TRENCH APPROXIMATELY 3 TO 4

BERM SHALL BE INSTALLED PERPENDICULAR TO DIRECTION OF FLOW.

'. INSPECTION SHOULD BE MADE WEEKLY AND AFTER EACH RAINFALL. FOR INSTALLATIONS IN STREAMBEDS, ADDITIONAL DAILY INSPECTIONS SHOULD BE

3. REMOVE SEDIMENT AND OTHER DEBRIS WHEN BUILDUP REACHES 6 INCHES. DISPOSE OF THE ACCUMULATED SILT IN AN APPROVED MANNER THAT WILL NOT CAUSE ANY ADDITIONAL SILTATION.

). THE BERM SHOULD BE RESHAPED AND REPAIRED AS NEEDED DURING O. THE BERM SHOULD BE REPLACED WHEN THE STRUCTURE CEASES TO

FUNCTION AS INTENDED DUE TO SILT ACCUMULATION AMONG THE ROCKS /ASHOUT, CONSTRUCTION TRAFFIC DAMAGE, ETC. . THE ROCK BERM SHOULD BE LEFT IN PLACE UNTIL ALL UPSTREAM AREAS

ARE STABILIZED AND ACCUMULATED SITE REMOVED.

FILL MATERIAL ORIGINATING FROM THE LAND THAT IS THE SUBJECT OF A

SUBDIVISION APPLICATION MAY BE TEMPORARILY STORED ON SAID LAND

a) THE FILL MATERIAL SHALL BE STORED AT THE LOCATION SHOWN ON

ORIGINATING FROM THE SUBDIVISION ONLY. SHALL REMAIN FREE

FROM DEBRIS. AND SHALL BE SUITABLE FOR USE AS FILL MATERIAL

MATERIAL MAY NOT INCLUDE ANY MATERIAL FROM OUTSIDE OF THE

STORAGE OF THE FILL MATERIAL SHALL COMPLY WITH THE STORM WATER POLLUTION PREVENTION PLAN INCLUDING REVEGETATION OF

THE FILL MATERIAL WILL BE PLACED AND STORED IN SUCH MANNER

THE FILL MATERIAL WILL BE LOCATED SO AS NOT TO DISTURB ANY

WETLAND AREAS THAT MAY EXIST IN THE SUBDIVISION, AND WILL BE

AFFECT THE NATURAL COURSE OF DRAINAGE ACROSS THE LAND OR

COST OF REMOVAL OF THE FILL MATERIAL WILL BE FILED WITH THE

GENERATES THE FILL MATERIAL. THE FISCAL SURETY WILL BE BASED

ON AN ESTIMATE PREPARED BY THE ENGINEER FOR THE SUBDIVISION

PLACED IN A MANNER AND LOCATION SO AS NOT TO ADVERSELY

DISTURBED AREAS AND OTHER SEDIMENTATION AND EROSION

PROVIDED THAT THE DEVELOPER COMPLIES AT ALL TIMES WITH THE

THE FILL MATERIAL SHALL CONSIST OF EARTHEN MATERIAL

ON THE FUTURE PHASES OF THE SUBDIVISION. THE FILL

CONTROLS ADOPTED BY THE TEXAS COMMISSION ON

IMPEDE DRAINAGE FROM NEIGHBORING PROPERTIES.

FISCAL SURETY THAT COMPLIES WITH SECTION 28 OF THIS ORDINANCE IN AN AMOUNT EQUAL TO 110% OF THE

CITY PRIOR TO THE ACCEPTANCE OF THE SUBDIVISION THAT

THE HEIGHT OF THE FILL MATERIAL SHALL NOT EXCEED TEN (10')

EXPIRE AND TERMINATE IN THE EVENT THAT A PRELIMINARY PLAT,

CONSTRUCTION PLANS, OR A FINAL PLAT FOR ANY PORTION OF THE

LAND EXPIRES. OR AT SUCH TIME THAT THE IMPROVEMENTS FOR THE

PERMISSION TO STORE FILL MATERIAL IN THE SUBDIVISION WILL

SO THAT IT IS STABLE, WITH THE SIDE SLOPES NO

FOLLOWING REQUIREMENTS:

ENVIRONMENTAL QUALITY.


STEEPER THAN A 3:1 (H:V) SLOPE.

AND APPROVED BY THE CITY ENGINEER.

LAST PHASE OF THE SUBDIVISION ARE ACCEPTED.

SUBDIVISION

THE APPROVED CONSTRUCTION PLANS.



GEOTEXTILE FABRIC TO STABILIZE FOUNDATION

STABILIZED CONSTRUCTION ENTRANCE (S. C. E.)

WITH INSTALLATION.

. GRADE THE AREA FOR THE ENTRANCE TO FLOW BACK ON TO THE CONSTRUCTION SITE. RUNOFF FROM THE S.C.E. ONTO A PUBLIC STREET WILL NOT BE ACCEPTED.

3. PLACE ROCK AS REQUIRED. (3"-5" OPEN GRADED CLEAN CRUSHED STONE) 4. SIDE CONTAINMENT, AT THE CONTRACTOR'S DISCRETION, IS SUGGESTED. THE SPECIFIED 8" THICKNESS OF CRUSHED STONE MUST BE MAINTAINED.

DIVERSION RIDGE

STABILIZED CONSTRUCTION

ENTRANCE

ALL AREAS WITHIN PROPERTY ARE EXPECTED TO BE DISTURBED AND

STABILIZATION MEASURES ARE ESTABLISHMENT OF TEMPORARY

GEOTEXTILES, SOD STABILIZATION, VEGETATIVE BUFFER STRIPS,

SOIL STABILIZATION METHOD USED IN THIS PROJECT SHALL BE AN

STABILIZED. EXAMPLES OF ACCEPTABLE TEMPORARY AND PERMANENT SOIL

VEGETATION, ESTABLISHMENT OF PERMANENT VEGETATION, MULCHING,

PROTECTION OF TREES, OR PRESERVATION OF MATURE VEGETATION. THE

APPROVED METHOD WITHIN THE TCEQ TECHNICAL GUIDANCE MANUAL AND

SILT FENCING SHALL FOLLOW LIMITS OF CONSTRUCTION UNLESS SHOWN

"IF DISTURBED AREA IS NOT TO BE WORKED ON FOR MORE THAN 14 DAYS,

IN-COMPLIANCE WITH THE CITY OF SAN ANTONIO RULES AND REGULATIONS.

CONTRACTOR SHALL UTILIZE DUST CONTROL MEASURES DURING THE SITE

THE CONTRACTOR WILL CLEAN UP SPOILS THAT MIGRATE ONTO THE ROADS

CONSTRUCTION SUCH AS IRRIGATION TRUCKS AND MULCHING, OR AS

DISTURBED AREA NEEDS TO BE STABILIZED BY REVEGETATION, MULCH,

ENVIRONMENTAL INSPECTOR HAS THE AUTHORITY TO ADD/OR MODIFY

EROSION/SEDIMENTATION CONTROLS ON SITE TO KEEP PROJECT

TARP OR REVEGETATION MATTING.

A MINIMUM OF ONCE DAILY.

DIRECTED BY THE ENVIRONMENTAL INSPECTOR.

MUST BE APPROVED BY MBC ENGINEERS BEFORE IT IS IMPLEMENTED IN THE

. CLEAR THE AREA OF DEBRIS, ROCKS, OR PLANTS THAT WILL INTERFERE

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY CONTRIBUTING ZONE PLAN GENERAL CONSTRUCTION NOTES

EDWARDS AQUIFER PROTECTION PROGRAM CONSTRUCTION NOTES - LEGAL DISCLAIMER

E FOLLOWING/LISTED "CONSTRUCTION NOTES" ARE INTENDED TO BE ADVISORY IN NATURE ONLY AND DO NOT CONSTITUTE AN APPROVAL OR CONDITI PROVAL BY THE EXECUTIVE DIRECTOR (ED), NOR DO THEY CONSTITUTE A COMPREHENSIVE LISTING OF RULES OR CONDITIONS TO BE FOLLOWED DURI. ISTRUCTION. FURTHER ACTIONS MAY BE REQUIRED TO ACHIEVE COMPLIANCE WITH TCEQ REGULATIONS FOUND IN TITLE 30, TEXAS ADMINISTRATIVE COI C). CHAPTERS 213 AND 217. AS WELL AS LOCAL ORDINANCES AND REGULATIONS PROVIDING FOR THE PROTECTION OF WATER QUALITY. ADDITIONA IG CONTAINED IN THE FOLLOWING/LISTED "CONSTRUCTION NOTES" RESTRICTS THE POWERS OF THE ED, THE COMMISSION OR ANY OTHER GOVERNME TY TO PREVENT, CORRECT, OR CURTAIL ACTIVITIES THAT RESULT OR MAY RESULT IN POLLUTION OF THE EDWARDS AQUIFER OR HYDROLOGIC. INECTED SURFACE WATERS. THE HOLDER OF ANY EDWARDS AQUIFER PROTECTION PLAN CONTAINING "CONSTRUCTION NOTES" IS STILL RESPONSIBLE FO MPLIANCE WITH TITLE 30, TAC, CHAPTERS 213 OR ANY OTHER APPLICABLE TCEQ REGULATION, AS WELL AS ALL CONDITIONS OF AN EDWARDS AQUIFE OTECTION PLAN THROUGH ALL PHASES OF PLAN IMPLEMENTATION. FAILURE TO COMPLY WITH ANY CONDITION OF THE ED'S APPROVAL, WHETHER OR NOT I. TRADICTION OF ANY "CONSTRUCTION NOTES," IS A VIOLATION OF TCEQ REGULATIONS AND ANY VIOLATION IS SUBJECT TO ADMINISTRATIVE RULES, ORDEF ID PENALTIES AS PROVIDED UNDER TITLE 30, TAC § 213.10 (RELATING TO ENFORCEMENT). SUCH VIOLATIONS MAY ALSO BE SUBJECT TO CIVIL PENALTIES AND INCTION. THE FOLLOWING/LISTED "CONSTRUCTION NOTES" IN NO WAY REPRESENT AN APPROVED EXCEPTION BY THE ED TO ANY PART OF TITLE 30 T. APTERS 213 AND 217, OR ANY OTHER TCEQ APPLICABLE REGULATION

A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS PRIOR TO THE START OF ANY GROUND DISTURBANCE OR CONSTRUCTION ACTIVITIES. THIS NOTICE MUST INCLUDE:

THE NAME OF THE APPROVED PROJECT. THE ACTIVITY START DATE: AND

THE CONTACT INFORMATION OF THE PRIME CONTRACTOR. ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT SHOULD BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED CONTRIBUTING ZONE PLAN (CZP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTOR(S) SHOULD KEEP COPIES OF THE APPROVED PLAN AND APPROVAL LETTER

NO HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.

PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY. OR INCORRECTLY. THE APPLICANT MUST REPLACE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THESE CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED

ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES,

SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS WHEN IT OCCUPIES 50% OF THE BASIN'S DESIGN CAPACITY

LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE.

ALL EXCAVATED MATERIAL THAT WILL BE STORED ON-SITE MUST HAVE PROPER E&S CONTROLS.

IF PORTIONS OF THE SITE WILL HAVE A CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS. SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE FOLIRTEENTH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE TWENTY FIRST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE FOURTEENTH DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE

THE FOLLOWING RECORDS SHOULD BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST: THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR: THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A

PORTION OF THE SITE: AND THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.

THE HOLDER OF ANY APPROVED CZP MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING

A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY BEST MANAGEMENT PRACTICES (BMPS) O STRUCTURE(S). INCLUDING BUT NOT LIMITED TO TEMPORARY OR PERMANENT PONDS, DAMS, BERMS, SIL FENCES. AND DIVERSIONARY STRUCTURES:

B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED:

C. ANY CHANGE THAT WOULD SIGNIFICANTLY IMPACT THE ABILITY TO PREVENT POLLUTION OF THE EDWARDS AQUIFER: OR

D. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE APPROVED

AUSTIN REGIONAL OFFICE 12100 PARK 35 CIRCLE, BUILDING.

CONTRIBUTING ZONE PLAN

AUSTIN, TEXAS 78753-1808 PHONE (512) 339-2929 FAX (512) 339-3795

> SAN ANTONIO REGIONAL OFFICE 14250 JUDSON ROAD SAN ANTONIO TEXAS 78233-4480 FAX (210) 545-4329

THESE GENERAL CONSTRUCTION NOTES MUST BE INCLUDED ON THE CONSTRUCTION PLANS PROVIDED TO THE

GENERAL EROSION CONTROL NOTES

. TEMPORARY EROSION AND SEDIMENTATION CONTROLS: AS DICTATED BY THE T.C.E.Q. WHILE CONSTRUCTION IS IN PROGRESS, THE CONTRACTOR SHALL ENDEAVOR TO IMPEDE THE TRANSMISSION OFF THE CONSTRUCTION SITE OF ERODED TOPSOIL AND SHALL AVOID POLLUTION OF TOPSOIL/RUNOFF DUE TO FUELING OR SERVICING OF EQUIPMENT OR IMPROPER MATERIALS.

. EXCAVATED MATERIAL NOT USED FOR STREET FILL ON-SITE SHALL NOT BE STOCKPILED INDEFINITELY ON-SITE. BUT SHALL BE PROMPTLY TRANSPORTED OFF THE SITE. A SILT FENCE SHALL BE INSTALLED DOWN- SLOPE OF ANY PLACED FILL TO INHIBIT EROSION OF THE FILL MATERIAL

. THE DEVELOPER WILL SEED CLEARED STREET PARKWAYS WITH BERMUDA GRASS OR SOME OTHER FORM OF HARDY GRASS/PLANTS AS SOON AS POSSIBLE AFTER STREET AND UTILITY CONSTRUCTION IS COMPLETED.

. THE SILT FENCING AND ROCK BERM SHOWN HERE-ON IS DESIGNED T INTERCEPT SILT-CARRYING RUNOFF ON A UNIT-BY-UNIT BASIS AND INHIBIT ITS BEING CARRIED OUTSIDE THE BOUNDARIES OF THE UNIT AND THE DEVELOPMENT TO DOWNGRADE FEATURES IT IS OUR INTENTION AND ANY CONTRACTOR'S DIRECTION TO INSTALL SILT FENCES AND ROCK BERM AS SHOWN PRIOR TO ANY EXCAVATION OR TRENCHING WITHIN A DELINEATED


REFERENCE POLLUTION PREVENTION PLAN AND WATER POLLUTION ABATEMENT PLAN FOR ADDITIONAL INFORMATION AND REQUIREMENTS.

LOCATION OF SILT FENCE AND ROCK BERM IS APPROXIMATE CONTRACTOR TO DETERMINE EXACT LOCATION BASED ON WORK TO BE PERFORMED UNDER THIS CONTRACT AND WORK TO BE PERFORMED BY VARIOUS AGENCIES INVOLVED WITH THIS PROJECT.

. LOCATION OF STABILIZED CONSTRUCTION ENTRANCE IS TO BE AS SHOWN ON THIS PLAN UNLESS CONTRACTOR RECEIVES PRIOR WRITTEN APPROVAL


. THIS SHEET IS TO BE USED FOR EROSION CONTROL PURPOSES ONLY.

. CONTRACTOR TO INSTALL ROCK GABION IN LOCATIONS WHERE SIGNIFICANT CONCENTRATED STORM WATER DISCHARGE OCCURS TOWARDS



TYP. CONSTRUCTION STAGING AREA DTL.

ISSUED FOR REVIEW 7/14/2025




RICHARD HENDRIX, P.E

rexas soil Water ex 7230 BULVE ANTONIO, T

180498 33109-1480

07/15/2025

EROSION CONTROL **DETAILS**



RICHARD W. HENDRIX
107385

CENSE

RICHARD W. HENDRIX

RICHARD W. H

PRIMARY CONTACT: RICHARD HENDRIX, P.E

COPELAND & ASSOC.,

GINEERS AND LAND SURVEYOR

Parkway North, San Antonio, Texas 78232

MACINA • BOSE

CONSULTING E

S SOIL & STONE ER EXTENSION SULVERDE ROAD ONIO, TEXAS, 78260

Call before you dig.

REVISIONS:

DATE No. DESCRIPTION BY

- - - - - |

PLAT ID#:

180498

JOB NO.

33109-1480

ISSUED FOR:

33109-1480

ISSUED FOR:

CZP


DATE:

07/15/2024

07/15/2025

POND PLAN

C09.00



REFERENCE GENERAL NOTES ON SHEET C02.00

PRIOR TO BID AND CONSTRUCTION

1255


1250

SITE CONCRETE DRAINAGE NOTES:

EXPOSED CONCRETE SURFACES SHALL BE BROOM FINISHED.

ALL EXPOSED EDGES SHALL RECEIVE A 3/4" CHAMFER.

ANY IRREGULAR AREA SHALL BE HAND RUBBED TO A SMOOTH FINISH.



LEGEND EXISTING TOP OF CURB AND GUTTER ELEVATIONS EXISTING SPOT ELEVATION PROPOSED CONTOUR (REPRESENT FINISHED TOP OF PAVEMENT OR TOPSOIL) **EXISTING CONTOUR** ---- 950 -----PROPOSED RIDGE DEFINED SWALE FF=1000.00 PROPOSED FIN. FLOOR ELEVATION PROPOSED FOUNDATION BREAKS **─**~~ OVERLAND FLOW DIRECTION BENCHMARK GRATE PROPOSED STORM DRAIN -4-SD-4-EXISTING STORM DRAIN PROPOSED POND INVERT PROPOSED TOP OF RETAINING WALL PROPOSED BOTTOM OF RETAINING WALL

PROPOSED TOP OF FOOTING

PROPOSED SPOT ELEVATION (REPRESENT FINISHED TOP OF PAVEMENT OR TOPSOIL)

PROPOSED GRASS SWALE ELEVATIONS

CONTRACTOR SHALL SEQUENCE CONSTRUCTION SO THAT THE DETENTION POND IS

ALL FILL MATERIAL, WHICH MAY CONSIST OF APPROVED ONSITE SOILS AND/OR OFFSITE BORROW MATERIAL, SHALL BE FREE OF ALL DEBRIS, ORGANIC MATERIAL, AND CLUMPS AND SHALL BE ADJUSTED TO THE PROPER MOISTURE CONTENT. ALL FILL SHALL BE PLACED IN 8"LOOSE LIFTS AND COMPACTED TO 95% DENSITY PER ASTM D1557.

COMPLETED AS EARLY AS POSSIBLE ONCE SITE WORK HAS COMMENCED.

POND BOTTOM AND SIDE SLOPES SHALL BE SODDED, SEEDED OR HYDROMULCHED. CONTRACTOR TO COORDINATE WITH LANDSCAPE ARCHITECT PLANS FOR ANY ADDITIONAL SPECIFICATIONS. CONTRACTOR TO PROVIDE WATER AS REQUIRED TO ESTABLISH 85% VEGETATIVE COVER PRIOR TO ACCEPTANCE.

CONTRACTOR TO COORDINATE WITH STRUCTURAL ENGINEER FOR INSPECTIONS AND CERTIFICATION OF RETAINING WALLS AS REQUIRED.

SITE CONCRETE DRAINAGE NOTES:

CONCRETE SHALL ACHIEVE A MINIMUM OF 3000 P.S.I. 28 DAY STRENGTH.

REINFORCEMENT STEEL SHALL CONFORM TO ASTM A-615 GRADE 60.

EXPOSED CONCRETE SURFACES SHALL BE BROOM FINISHED.

ANY IRREGULAR AREA SHALL BE HAND RUBBED TO A SMOOTH FINISH.

ALL EXPOSED EDGES SHALL RECEIVE A 3/4" CHAMFER.

CONTRACTOR WILL BE RESPONSIBLE FOR PROTECTING ALL UTILITIES, SUCH AS MANHOLES CLEANOUTS, WATER VALVES, FIRE HYDRANTS, UNDERGROUND ELECTRIC TRANSFORMERS, ADJUSTMENTS PRIOR TO FINAL ACCEPTANCE BY THE OWNER.

ALL FILL PLACED WITHIN DRAIN EASEMENT SHALL BE COMPACTED TO 95% MAXIMUM DR'

ALL CONSTRUCTION SHALL BE DONE IN ACCORDANCE WITH CITY OF SAN ANTONIO STANDARD SPECIFICATIONS.

FOR PRECAST CONCRETE PRODUCTS, USE NEW BASIS CHARLOTTE'S CONCRETE, INC., OF APPROVED EQUAL.

SEQUENCE OF OPERATION:

1. UPON ACTIVATION OF FLOAT SWITCH, DDC CONTROLLER TO START DETENTION TIMER #1.

DETENTION TIMER #1 TO BE MANUALLY SET TO 12 HOURS AND TO BE USER ADJUSTABLE VALUE. WHEN DETENTION TIMER #1 HAS ELAPSED, A 6" BUTTERFLY VALVE IS TO OPEN AND RELEASE DETAINED WATER

UPON DEACTIVATION OF FLOAT SWITCH, DDC CONTROLLER TO START DETENTION TIMER #2. DETENTION TIMER #2 TO BE MANUALLY SET TO 24 HOURS AND TO BE USER ADJUSTABLE.

WHEN DETENTION TIMER #2 HAS ELAPSED, THE 6"BUTTERFLY VALVE IS TO CLOSE. VALVE TO BE ACTIVATED PERIODICALLY TO SHOW ACTIVE REGARDLESS OF FLOAT SWITCH OPERATION.

EARTHERN BERM BEYOND -#3 BARS @ 12" O.C.E.W. #4 BARS VERTICAL @ 18" O.C. BOTTOM OF WEIR EL. 621.84 PERMISSABLE KEYED CONSTRUCTION JOINT #4- BARS @ 12" O.C. \(\)

1.) ALL REINFORCING STEEL SHALL BE A.S.T.M. A-615 GRADE 60. ALL STEEL NOT PROPERLY MARKED MUST BE TESTED FOR ACCEPTABILITY. MILL TESTS WILL NOT BE ACCEPTED.

2.) ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 3000 P.S.I. AT 28 DAYS. TESTING SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR. ANY SUB STANDARD STRENGTHS SHALL BE REPORTED TO MBC ENGINEERS. ALL CONCRETE SHALL BE PLACED AND CURED IN COMPLIANCE WITH CURRENT A.C.I. SPECIFICATIONS. 3.) PROVIDE 1/2" EXPANSION JOINTS AT 30'-0" MAX. SPACING. PROVIDE 2-#4 BAR DOWELS @ 18" O.C. VERTICAL MAX. SPACING. WRAP ONE END W/ FELT. 4.) THIS DESIGN SHALL NOT BE CONSIDERED VALID, AND ENGINEER ACCEPTS NO RESPONSIBILITY UNLESS PRE-POUR INSPECTIONS ARE PERFORMED, AND APPROVAL FOR PLACEMENT OF CONCRETE IS PROVIDED BY MBC ENGINEERS. NOTIFY OFFICE OF ENGINEER 24 HOURS IN ADVANCE TO SCHEDULE PRE-POUR INSPECTIONS.

0'-0" - 3'-0" 2'-0" #5 @ 12" O.C. #4 @ 12" O.C. 3'-0" - 5'-0" 4'-0" #6 @ 18" O.C. #4 @ 12" O.C.

NOTE: GUARD RAIL / HAND RAIL SHALL BE DESIGNED AND CERTIFIED BY A QUALIFIED LICENSED STRUCTURAL ENGINEER THAT THE RAIL IS ADEQUATE FOR THE INTENDED APPLICATION ON THIS SITE.

SECTION "G-G"

ISSUED FOR REVIEW 7/14/2025

PRIMARY CONTACT: RICHARD HENDRIX, P.E


180498

33109-1480

07/15/2025

DETENTION POND **DETAILS**


C09.01



LINER DETAIL

LINER AND PROTECTIVE GEOTEXTILE FABRIC, ARE TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS.


GEOTEXTILE FABRIC SPECIFICATIONS




NOTES:

- 1. MINIMUM DIAMETER = 4" SCHEDULE 40 PVC.
- 2. THE MAXIMUM SPACING BETWEEN ROWS OF PERFORATIONS SHOULD NOT EXCEED 6".
- SET PERFORATION DOWNS.
- 4. PERFORATIONS SHOULD BE LESS THAN 1/2".
- 5. PIPES SHOULD LIE FLAT ON CONCRETE BOTTOM WHICH HAS BEEN GRADED TO DRAIN AS SHOWN ON PLAN VIEW.
- 6. ALL CLEANOUTS SHALL BE SOLID PIPE WITH A CLEANOUT AT THE END OF EACH LINE.


PERFORATED PIPE



CLEANOUT DETAIL (DUAL DIRECTION) N.T.S.



PIPE DISCHARGE AT LINER DETAIL



GEOTEXTILE FABRIC SPECIFICATIONS

PROPERTY	TEST METHOD	<u>UNIT</u>	SPECIFICATION
UNIT WEIGHT	ASTM D-5261	OZ/SY	8
FLITRATION RATE	ASTM D-4491	CM/SEC	0.20
PUNCTURE STRENGTH	ASTM D-4833	LB	125
MULLEN BURST STRENGTH	ASTM D-3786	PSI	400
TENSILE STRENGTH	ASTM D-4632	LB	200
EQUIV. OPENING SIZE US	S STANDARD SIEVE	NO.	80

NOTE: FILTER FABRIC TO BE INSTALLED PER

CONCRETE RIP-RAP

CONTINUOUS BATTEN 2"X4" WOOD STUD

-3/8"x3" STAINLESS

STEEL ANCHOR BOLT

4" OF 6" DISCHARGE PIPE


MANUFACTURER'S SPECIFICATIONS.


REINFORCING STEEL-


(IF REQUIRED)

4" OR 6" PIPE

FROM BASIN







CONCRETE END TREATMENT DETAIL

GEOTEXTILE FABRIC SPECIFICATIONS

Property	Test Method	Unit	Specification (min)
Unit Weight		oz/yd ²	8
Filtration Rate		in/sec	0.08
Puncture Strength	ASTM D-751*	lb	125
Mullen Burst Strength	ASTM D-751	psi	400
Tensile Strength	ASTM D-1682	lb	200
Equiv. Opening Size	US Standard Sieve	No.	80

ANCHORING DETAIL NOTE: CONTRACTOR TO PLACE ANCHOR BOLTS AT 5'-0" O.C. (STD. SAWS VALVE BOX) 2"x2"x6" CONCRETE COLLAR — 4" CLEANOUT \sim 4" or 6" flapper valve

FILTER FABRIC


CLAY LINER SPECIFICATIONS

Table 3-6 Clay Liner Specifications (COA, 2004)

Property	Test Method	Unit	Specification
Permeability	ASTM D-2434	cm/sec	1 x 10 ⁻⁶
Plasticity Index of Clay	ASTM D-423 & D-424	%	Not less than 15
Liquid Limit of Clay	ASTM D-2216	%	Not less than 30
Clay Particles Passing	ASTM D-422	%	Not less than 30
Clay Compaction	ASTM D-2216	%	95% of Standard Proctor Density

4" OR 6" GATE & FLAPPER VALVE DETAIL

1. VALVE WILL BE SET PARTIALLY CLOSED SO AS TO PROVIDE A MINIMUM DRAWDOWN TIME 2. CONTRACTOR SHALL PROVIDE OWNER WITH VALVE OPERATING KEY/ROD PRIOR TO PROJECT COMPLETION.



OVERLAP. A SHARPENED MASON'S TROWEL IS A HANDY TOOL FOR TUCKING DOWN THE ENDS AND <u>BUTTING</u> — ANGLED ENDS CAUSED BY THE AUTOMATIC SOD CUTTER MUST BE MATCHED CORRECTLY.

- ROLL SOD IMMEDIATELY TO ACHIEVE FIRM CONTACT WITH THE SOIL.
- WATER TO A DEPTH OF 4" AS NEEDED. WATER WELL AS SOON AS THE SOD IS LAID.

nspection and Maintenance Guidelines:


should be repaired as soon as practical.


to locate and repair any damage.

(1) Sod should be inspected weekly and after each rain event

(2) Damage from storms or normal construction activities such as tire ruts or disturbance of swale stabilization

• MOW WHEN THE SOD IS ESTABLISHED - IN 2-3 WEEKS. SET THE MOWER HIGH (2"-3").





SOD INSTALLATION

IN CRITICAL AREAS, SECURE SOD WITH NETTING. USE STAPLES.

USE PEGS OR SIAPLES TO FASTEN
SOD FIRMLY – AT THE ENDS OF
STRIPS AND IN THE CENTER, OR
EVERY 3–4 FEET IF THE STRIPS ARE
LONG. WHEN READY TO MOW, DRIVE

SOD INSTALLATION

- CORRECT
- (3) Fertilize according to soil tests. Fertilizer needs can be determined by a soil testing laboratory or regional recommendations can be made by county agricultural extension agents. Fertilizer should be worked into the soil to a depth of 3 inches with a disc, springtooth harrow or other suitable equipment. On sloping land, the final barrowing or disciple progration should be on the final harrowing or discing operation should be or

Installation in Channels: (1) Sod strips in waterways should be laid perpendicula

General Installation (VA Dept. of Conservation, 1992):

Site Preparation:

butt ends of strips tightly (see Figure above). (2) After rolling or tamping, sod should be pegged or stapled to resist washout during the establishment period. Mesh or other netting may be pegged over the sod for extra protection in critical areas.

(1) Sod should be machine cut at a uniform soil

(2) Pieces of sod should be cut to the supplier's

grasp on one end of the section.

1/4" inch) at the time of cutting. This thickness

prieces of sod should be cut to the supplier's standard width and length, with a maximum allowable deviation in any dimension of 5%. Torn or uneven pads should not be acceptable.

) Standard size sections of sod should be strong enough to support their own weight and retain their size and shape when suspended from a firm

(4) Sod should be harvested, delivered, and installed within a period of 36

in accordance with the approved plan.

(1) Prior to soil preparation, areas to be sodded should be brought to final grade

(2) The surface should be cleared of all trash, debris and of all roots, brush, wire, grade stakes and other objects that would interfere with planting, fertilizing or

thickness of 3/4" inch (\pm

growth and thatch.

- (2) During periods of high temperature, the soil should be lightly irrigated
- immediately prior to laying the sod, to cool the soil and reduce root burning

(1) Sod should not be cut or laid in excessively wet or dry weather. Sod also

- (3) The first row of sod should be laid in a straight line with subsequent rows placed parallel to and butting tightly against each other. Lateral joints should be staggered to promote more uniform growth and strength. Care should be excercised to ensure that sod is not stretched or overlapped and that all joints with the stretched to the stretched or overlapped and that all joints to the stretched or overlapped and that all joints are stretched. are butted tight in order to prevent voids which would cause drying of the roots
- (4) On slopes 3:1 or greater, or wherever erosion may be a problem, sod should be laid with staggered joints and secured by stapling or other approved methods. Sod should be installed with the length perpendicular to the slope (on contour).
- (5) As sodding of clearly defined areas is completed, sod should be rolled or tamped to provide firm contact between roots and soil.
- (6) After rolling, sod should be irrigated to a depth sufficient that the underside of the sod pad and the soil 4 inches below the sod is thorougly wet. (7) Until such time a good root system becomes developed, in the absence of adequate rainfall, watering should be performed as often as necessary to maintain moist soil to a depth of at least 4 Inches.
- (8) The first mowing should not be attempted until the sod is firmly rooted, usually 2-3 weeks. Not more than one third of the grass leaf should be removed at

FILTER FABRIC SPECIFICATIONS

THE SEPARATION LAYER BETWEEN THE FILTER, SAND, AND GRAVEL LAYERS SHALL BE A DRAINAGE MATTING CONSISTING OF NON-WOVEN FILTER FABRIC MEETING THE FOLLOWING SPECIFICATIONS:

<u>PROPERTY</u>	TEST METHOD	<u>SPECIFICATION</u>
WEIGHT (OZ/SY)	ASTM D 3776	4.0
GRAB STRENGTH (LBS.)	ASTM D 4632	90
ELONGATIONS (%)	ASTM D 4632	55
PUNCTURE (LBS)	ASTM D 3787	60
AOS (SIEVE #)	ASTM D 4751	70-80
FLOW RATE (GPM/SF)	ASTM D 4491	120

FABRIC OVERLAP SHALL BE A MINIMUM OF 24". ALL OVERLAPS SHALL BE WIRE TIED AT A MAXIMUM OF 36" INTERVALS


SAND FILTER MATERIAL SHALL BE ASTM C33 0.0165 IN #40 SIEVE TO 0.0469 IN (#16 SIEVE) SILICA BASED WASHED SAND.

ROCK FOR GRAVEL LATER SHALL BE 1/2" TO 1" DIAMETER WASHED RIVER GRAVEL.

GEOMEMBRANE POLY LINER SPECIFICATION

- ULTRAVIOLET RESISTANT
- THICKNESS = 40 MILS MINIMUM
- JOINTS SHALL BE WATER TIGHT AT SEAMS.
- ANCHOR TO WALLS
- WATERTIGHT SEAL BETWEEN POLY LINER AND TRANSITION SURFACES. - BEDDING MATERIAL SHALL BE SUITABLY COMPACTED MATERIAL (NOT SAND) IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- PROTECTIVE GEOTEXTILE FABRIC TO BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.

ISSUED FOR REVIEW 7/14/2025



TEXAS SOIL WATER EXT 7230 BULVEF ANTONIO, T

PRIMARY CONTACT: RICHARD HENDRIX, P.E

180498

33109-1480

07/15/2025

DETENTION **POND DETAILS**

C09.02

EXAS COMMISSION ON ENVIRONMENTAL QUALITY WATER POLLUTION ABATEMENT PLAN GENERAL CONSTRUCTION NOTES

EDWARDS AQUIFER PROTECTION PROGRAM CONSTRUCTION NOTES - LEGAL DISCLAIMER HE FOLLOWING/LISTED "CONSTRUCTION NOTES" ARE INTENDED TO BE ADVISORY IN NATURE ONLY AND DO NOT CONSTITUTE AN APPROVAL OR CONDITIONAL APPROVAL BY THE EXECUTIVE DIRECTOR (ED), NOR DO THEY CONSTITUTE A COMPREHENSIVE LISTING OF RULES OR CONDITIONS TO BE FOLLOWED DURING CONSTRUCTION. FURTHER ACTIONS MAY BE REQUIRED TO ACHIEVE COMPLIANCE WITH TCEQ REGULATIONS FOUND IN TITLE 30, TEXAS ADMINISTRATIVE CODE (TAC) HAPTERS 213 AND 217, AS WELL AS LOCAL ORDINANCES AND REGULATIONS PROVIDING FOR THE PROTECTION OF WATER QUALITY. ADDITIONALLY, NOTHING INTAINED IN THE FOLLOWING/LISTED "CONSTRUCTION NOTES" RESTRICTS THE POWERS OF THE ED. THE COMMISSION OR ANY OTHER GOVERNMENTAL ENTITY TO PREVENT, CORRECT, OR CURTAIL ACTIVITIES THAT RESULT OR MAY RESULT IN POLLUTION OF THE EDWARDS AQUIFER OR HYDROLOGICALLY CONNECTED SURFACE WATERS. THE HOLDER OF ANY EDWARDS AQUIFER PROTECTION PLAN CONTAINING "CONSTRUCTION NOTES" IS STILL RESPONSIBLE FOR COMPLIANCE WITH TITLE 30, TAC, CHAPTERS 213 OR ANY OTHER APPLICABLE TCEQ REGULATION, AS WELL AS ALL CONDITIONS OF AN EDWARDS AQUIFER PROTECTION PLAN THROUGH ALL PHASES OF PLAN IMPLEMENTATION. FAILURE TO COMPLY WITH ANY CONDITION OF THE ED'S APPROVAL, WHETHER OR NOT IN CONTRADICTION OF ANY "CONSTRUCTION NOTES. IS A VIOLATION OF TCEQ REGULATIONS AND ANY VIOLATION IS SUBJECT TO ADMINISTRATIVE RULES, ORDERS, AND PENALTIES AS PROVIDED UNDER TITLE 30, TAC §

A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS PRIOR TO THE START OF ANY REGULATED ACTIVITIES. THIS NOTICE MUST INCLUDE: THE NAME OF THE APPROVED PROJECT:

13.10 (RELATING TO ENFORCEMENT). SUCH VIOLATIONS MAY ALSO BE SUBJECT TO CIVIL PENALTIES AND INJUNCTION. THE FOLLOWING/LISTED "CONSTRUCTION

NOTES" IN NO WAY REPRESENT AN APPROVED EXCEPTION BY THE ED TO ANY PART OF TITLE 30 TAC, CHAPTERS 213 AND 217, OR ANY OTHER TCEQ APPLICABLE

THE ACTIVITY START DATE; AND THE CONTACT INFORMATION OF THE PRIME CONTRACTOR.

ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT MUST BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED WATER POLLUTION ABATEMENT PLAN (WPAP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTORS ARE REQUIRED TO KEEP ON-SITE COPIES OF THE APPROVED PLAN AND APPROVAL LETTER.

IF ANY SENSITIVE FEATURE(S) (CAVES, SOLUTION CAVITY, SINK HOLE, ETC.) IS DISCOVERED DURING CONSTRUCTION, ALL REGULATED ACTIVITIES NEAR THE SENSITIVE FEATURE MUST BE SUSPENDED IMMEDIATELY. THE APPROPRIATE TCEQ REGIONAL OFFICE MUST BE IMMEDIATELY NOTIFIED OF ANY SENSITIVE FEATURES ENCOUNTERED DURING CONSTRUCTION. CONSTRUCTION ACTIVITIES MAY NOT BE RESUMED UNTIL THE TCEQ HAS REVIEWED AND APPROVED THE APPROPRIATE PROTECTIVE MEASURES IN ORDER TO PROTECT ANY SENSITIVE FEATURE AND THE EDWARDS AQUIFER FROM POTENTIALLY ADVERSE IMPACTS TO WATER QUALITY.

NO TEMPORARY OR PERMANENT HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.

PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE APPROVED PLANS AND MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORRECTLY, THE APPLICANT MUST REPLACE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THESE CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED.

ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES, ETC.

SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS NOT LATER THAN WHEN IT OCCUPIES 50% OF THE BASIN'S DESIGN CAPACITY.

LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORM WATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE

ALL SPOILS (EXCAVATED MATERIAL) GENERATED FROM THE PROJECT SITE MUST BE STORED ON-SITE WITH PROPER E&S CONTROLS. FOR STORAGE OR DISPOSAL OF SPOILS AT ANOTHER SITE ON THE EDWARDS AQUIFER RECHARGE ZONE, THE OWNER OF THE SITE MUST RECEIVE APPROVAL OF A WATER POLLUTION ABATEMENT PLAN FOR THE PLACEMENT OF FILL MATERIAL OR MASS GRADING PRIOR TO THE PLACEMENT OF SPOILS AT THE OTHER SITE.

IF PORTIONS OF THE SITE WILL HAVE A TEMPORARY OR PERMANENT CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE 14TH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE 21ST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE 14TH DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE.

THE FOLLOWING RECORDS SHALL BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST: THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR;

- THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; AND
- THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.

THE HOLDER OF ANY APPROVED EDWARD AQUIFER PROTECTION PLAN MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE

A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY WATER POLLUTION ABATEMENT STRUCTURE(S), INCLUDING BUT NOT LIMITED TO PONDS, DAMS, BERMS, SEWAGE TREATMENT PLANTS, AND DIVERSIONARY

B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED OR A CHANGE WHICH WOULD SIGNIFICANTLY IMPACT THE ABILITY OF THE PLAN TO PREVENT POLLUTION OF THE EDWARDS AQUIFER;

C. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE ORIGINAL WATER POLLUTION ABATEMENT PLAN

AUSTIN REGIONAL OFFICE 12100 PARK 35 CIRCLE, BUILDING A AUSTIN, TEXAS 78753-1808

PHONE (512) 339-2929 FAX (512) 339-3795

SAN ANTONIO REGIONAL OFFICE 14250 JUDSON ROAD

SAN ANTONIO, TEXAS 78233-4480

PHONE (210) 490-3096 FAX (210) 545-4329

THESE GENERAL CONSTRUCTION NOTES MUST BE INCLUDED ON THE CONSTRUCTION PLANS PROVIDED TO THE CONTRACTOR AND ALL SUBCONTRACTORS.

NOTES TO CONTRACTOR:

EDGE AT THE TOP OF WALL

BEEN COMPLETELY

THIS SHEET HAS BEEN PREPARED FOR THE PURPOSES OF POLLUTION ABATEMENT ONLY. ALL OTHER CIVIL ENGINEERING RELATED INFORMATION SHOULD BE ACQUIRED FROM THE APPROPRIATE SHEET IN THE CIVIL IMPROVEMENT PLANS. CONTRACTOR IS ADVISED THAT TCEQ DOES NOT ALLOW CHANGES TO PERMANENT POLLUTION ABATEMENT MEASURES ITHOUT THEIR PRIOR APPROVAL.

CONTRACTOR SHALL INSTALL THE PERMANENT BMP BASIN PER CIVIL AND STRUCTURAL PLANS AT THE START OF PHASE 1 CONSTRUCTION. IN PLACE OF THE PERMANENT RISER, A TEMPORARY RISER PIPE MAY BE INSTALLED AS SHOWN ON THE TEMPORARY SEDIMENT POND DETAIL, SHEET C04.01. ALSO, THE CONTRACTOR IS TO INSTALL A SEDIMENT DEPTH MARKER AT 50% CAPACITY OF THE TEMPORARY BASIN INSPECTIONS SHALL BE MADE WEEKLY AND AFTER EACH RAINFALL. TRASH AND OTHER DEBRIS SHALL BE REMOVED WHEN FOUND TO PREVENT CLOGGING OF THE OUTLET STRUCTURE. ONCE SEDIMENT REACHES THE 50% MARKER THEN ALL SEDIMENT SHALL BE REMOVED FROM THE TEMPORARY BASIN. UPON COMPLETION OF PHASE 1 THE TEMPORARY RISER SHALL BE REPLACED WITH THE RISER/TRASH RACK AND ELECTRIC VALVE & CONTROL SYSTEM.

THE CONTRACTOR SHALL COORDINATE WITH THE WNER/ARCHITECT PRIOR TO BID AND CONSTRUCTION REGARDING THE FINISH OF THE EXPOSED EXTERIOR WALLS. THE CONCRETE WALLS SHALL BE CONSTRUCTED WITH A CHAMFERED

CONTRACTOR TO SUBMIT STRUCTURAL DESIGN FOR POND SEALED BY LICENSED PROFESSIONAL ENGINEER.

CONTRACTOR SHALL NOTIFY CERTIFYING ENGINEER WHEN BASIN CONSTRUCTION HAS PROGRESSED TO THE FOLLOWING

A.) REINFORCING STEEL FOR BASIN WALL HAS BEEN SET, CONCRÉTE HAS NOT BEEN PLACED AND DRAIN PIPE IS IN B.) CONCRETE WALLS IN PLACE AND UNDER DRAIN SYSTEM IS IN PLACE WITHOUT GRAVEL. C.) GRAVEL AROUND UNDER DRAIN SYSTEM IS IN PLACE AND FILTER FABRIC IS INSTALLED AND ATTACHED TO WALLS OR. D.) SAND FILTER MEDIA HAS BEEN PLACED AND BASIN HAS

ELEVATIONS SHOWN INSIDE BASIN ARE AT BASIN FLOOR UNLESS NOTED OTHERWISE.

FINISHED.

DIMENSIONS ARE FROM FACE OF WALL. WALL THICKNESS BE DETERMINED BY A STRUCTURAL ENGINEER

WORK SHALL NOT CONTINUE ON THE BASIN UNTIL THE ENGINEER HAS HAD AN OPPORTUNITY TO OBSERVE THE STATUS OF CONSTRUCTION AT EACH STAGE CONTRACTOR SHALL PROVIDE ENGINEER A MINIMUM OF 24 HOURS ADVANCE NOTICE PRIOR TO TIME THE BASIN WILL BE AT THE REQUIRED STAGE.

CONTRACTOR TO PROVIDE CERTIFYING ENGINEER WITH FIELD SHOTS VERIFYING ELEVATIONS OF THE FOLLOWING: -TOP OF SLOPE AT EACH CORNER OF BASIN -TOE OF SLOPE AT EACH CORNER OF BASIN (INSIDE BASIN

PRIOR TO PROCEEDING TO NEXT STAGE OF CONSTRUCTION.

-SPLASH PAD/INLET PIPES -OVERFLOW WEIRS

UPON COMPLETION OF CONSTRUCTION AND IN ACCORDANCE WITH TCEQ REGULATIONS, ALL PERMANENT BMP'S (BASIN) MUST BE CERTIFIED BY A LICENSED PROFESSIONAL

BEFORE FINAL ACCEPTANCE OF CONSTRUCTION BY THE OWNER, THE STORM DRAIN SYSTEM MUST BE CLEAN OF ALL SEDIMENT AND ALL TRASH, DEBRIS, AND ACCUMULATED SILT FROM THE BASIN REMOVED AND REESTABLISHED TO THE PROPER PERATING CONDITION.

ALL AREAS DISTURBED AS PART OF CONSTRUCTION OF BASIN SHALL BE REVEGETATED PRIOR TO COMPLETION. POND BOTTOM AND SIDE SLOPES SHALL BE SODDED, SEEDED OR HYDROMULCHED. CONTRACTOR TO COORDINATE WITH LANDSCAPE ARCHITECT PLANS FOR ANY ADDITIONAL SPECIFICATIONS. CONTRACTOR TO PROVIDE WATER AS REQUIRED TO ESTABLISH 85% VEGETATIVE COVER PRIOR TO ACCEPTANCE. SITE WORK CONTRACTOR SHALL CONSIDER THE TYPE OF GRASS TO BE USED WHEN ROUGH CUTTING THE BASIN SUCH THAT THE FINAL GRADE MATCHES THE FINISHED GRADES. SHOWN ON THIS PLAN. SITE WORK CONTRACTOR SHALL FINE GRADE THE BOTTOM OF THE BASIN JUST PRIOR TO GRASS INSTALLATION TO ENSURE IT DRAINS AS INTENDED.

ALL FILL MATERIAL. WHICH MAY CONSIST OF APPROVED ONSITE SOILS AND/OR OFFSITE BORROW MATERIAL SHALL BE FREE OF ALL DEBRIS, ORGANIC MATERIAL, AND CLUMPS AND SHALL BE ADJUSTED TO THE PROPER MOISTURE CONTENT. ALL FILL SHALL BE PLACED IN 8" LOOSE LIFTS AND COMPACTED TO 95% DENSITY PER ASTM D1557.

SITE CONCRETE DRAINAGE NOTES:

. EXPOSED CONCRETE SURFACES SHALL BE BROOM FINISHED. 2. ANY IRREGULAR AREA SHALL BE HAND RUBBED TO A SMOOTH

B. ALL EXPOSED EDGES SHALL RECEIVE A 3/4" CHAMFER.

ALL MATERIALS AND WORKMANSHIP SHALL BE DONE II ACCORDANCE WITH CITY OF SAN ANTONIO STANDARD SPECIFICATIONS, AS WELL AS ITEM 360 (TXDOT STD SPECS,

. JOINTS TO BE COMPLETED PRIOR TO CONCRETE SHRINKAGE

. CONCRETE RIP-RAP SHALL BE CLASS "A" 3,000 PSI.

CENTER OF BARS UNLESS OTHERWISE SHOWN.

NEW RIP-RAP SHALL BE ATTACHED TO EXISTING RIP-RAP BY NO. 4 BARS DOWELED 6" INTO EXISTING RIP-RAP. THESE BARS ARE TO BE PLACED 18" O.C. AND HAVE A LENGTH OF 18"

. CONCRETE RIP-RAP SHALL BE 5" THICK, WITH NO. REINFORCING BARS AT 18" O.C.E.W. (MIN. GRADE 40 STEEL). ALL DIMENSIONS RELATING TO REINFORCING STEEL ARE TO


SUMMARY OF PERMANENT POLLUTION ABATEMENT MEASURES:


TEMPORARY BMP'S WILL BE MAINTAINED UNTIL THE RESPECTIVE WATERSHED HAS BEEN STABILIZED. ALL AREAS OF DISTURBED SOIL WHICH WILL NOT OTHERWISE


BE STABILIZED SHALL BE REVEGETATED TO STABILIZE SOIL USING SOLID BLOCK SOD IN A STAGGERED PATTERN. FOR AREAS DUTSIDE THE BASINS, THE CONTRACTOR MAY SUBSTITUTE SEED-IMPREGNATED EROSION CONTROL MATS OR HYDRAULIC MULCHING AND WATERING UNTIL VEGETATION IS ESTABLISHED. SEED MIXTURE AND/OR GRASS TYPE TO BE DETERMINED BY


PERMANENT BMP'S FOR THIS SITE INCLUDE ONE (1) BATCH DÉTENTION POND. THIS PERMANENT BMP HAVE BEEN DÉSIGNED O REMOVE 80% OF THE INCREASED TOTAL SUSPENDED SOLIDS SS) FOR DRAINAGE AREAS "A" AND "B" (UNCAPTURED) IN ACCORDANCE WITH THE TCEQ'S TECHNICAL GUIDANCE MANUAL RG 348 (2005).


ENERGY DISSIPATERS (TO HELP REDUCE EROSION) WILL BE PROVIDED AT POINTS OF CONCENTRATED DISCHARGE WHERE EXCESSIVE VELOCITIES MAY BE ENCOUNTERED.












ISSUED FOR REVIEW 7/14/2025



PRIMARY CONTACT: RICHARD HENDRIX, P.E



TEXAS SOIL WATER EXT 7230 BULVEI ANTONIO, T

180498 33109-1480

07/15/2025

DETENTION POND **DETAILS**

CONTRIBUTING ZONE PLAN APPLICATION

Texas Soil and Stone Outfitters TCEQ Form-10257

Attachment "N" -Inspection, Maintenance, Repair and Retrofit Plan

The project is addressing previously installed impervious cover and will install a batch detention pond and vegetative filter strips to treat pollutants from the site.

Maintenance plans included with the CZP submittal.

ATTACHMENT "N" Maintenance Plan and Schedule for Batch Detention Basins

PROJECT NAME	Texas Soil and Stone Outfitters	
ADDRESS	27220 Bulverde Road	
CITY, STATE ZIP	San Antonio, TX 78260	

BATCH DETENTION BASIN

Batch detention basins may have somewhat higher maintenance requirements than an extended detention basin since they are active stormwater controls. The maintenance activities are identical to those of extended detention basins with the addition of maintenance and inspections of the automatic controller and the valve at the outlet.

Inspections. Inspections should take place a minimum of twice a year. One inspection should take place during wet weather to determine if the basin is meeting the target detention time of 12 hours and a drawdown time of no more than 48 hours. The remaining inspections should occur between storm events so that manual operation of the valve and controller can be verified. The level sensor in the basin should be inspected and any debris or sediment in the area should be removed. The outlet structure and the trash screen should be inspected for signs of clogging. Debris and sediment should be removed from the orifice and outlet(s) as described in previous sections. Debris obstructing the valve should be removed. During each inspection, erosion areas inside and downstream of this BMP should be identified and repaired/revegetated immediately.

Mowing. The basin, basin side-slopes, and embankment of the basin must be mowed to prevent woody growth and control weeds. A mulching mower should be used, or the grass clippings should be caught and removed. Mowing should take place at least twice a year, or more frequently if vegetation exceeds 18 inches in height. More frequent mowing to maintain aesthetic appeal may be necessary in landscaped areas.

Litter and Debris Removal. Litter and debris removal should take place at least twice a year, as part of the periodic mowing operations and inspections. Debris and litter should be removed from the surface of the basin. Particular attention should be paid to floatable debris around the outlet structure. The outlet should be checked for possible clogging or obstructions and any debris removed.

Erosion control. The basin side slopes and embankment all may periodically suffer from slumping and erosion. To correct these problems, corrective action, such as regrading and revegetation, may be necessary. Correction of erosion control should take place whenever required based on the periodic inspections.

Nuisance Control. Standing water or soggy conditions may occur in the basin. Some standing water may occur after a storm event since the valve may close with 2 to 3 inches of water in the basin. Some flow into the basin may also occur between storms due to spring flow and residential water use that enters the storm sewer system. Twice a year,

the facility should be evaluated in terms of nuisance control (insects, weeds, odors, algae, etc.).

Structural Repairs and Replacement. With each inspection, any damage to structural elements of the basin (pipes, concrete drainage structures, retaining walls, etc.) should be identified and repaired immediately. An example of this type of repair can include patching of cracked concrete, sealing of voids, removal of vegetation from cracks and joints. The various inlet/outlet structures in a basin will eventually deteriorate and must be replaced.

Sediment Removal. A properly designed batch detention basin will accumulate quantities of sediment over time. The accumulated sediment can detract from the appearance of the facility and reduce the pollutant removal performance of the facility. The sediment also tends to accumulate near the outlet structure and can interfere with the level sensor operation. Sediment shall be removed from the basin at least every 5 years, when sediment depth exceeds 6 inches, when the sediment interferes with the level sensor or when the basin does not drain within 48 hours. Care should be taken not to compromise the basin lining during maintenance.

Logic Controller. The Logic Controller should be inspected as part of the twice yearly investigations. Verify that the external indicators (active, cycle in progress) are operating properly by turning the controller off and on, and by initiating a cycle by triggering the level sensor in the basin. The valve should be manually opened and closed using the open/close switch to verify valve operation and to assist in inspecting the valve for debris. The solar panel should be inspected and any dust or debris on the panel should be carefully removed. The controller and all other circuitry and wiring should be inspected for signs of corrosion, damage from insects, water leaks, or other damage. At the end of the inspection, the controller should be reset.

BATCH DETENTION BASIN

After Rainfall The water quality pond shall be checked after each rainfall occurrence to insure that it drains within 24 to 48 hours after the rain event. If it does not drain within this time, corrective measures shall be undertaken. At a minimum, such measures shall include removal of silt build-up on the surface of the pond. If draw-down time exceeds 48 hours, more extensive remediation measures are likely required and the condition of the filtration media should be investigated. In addition, if the basin fails to drain properly the owner must notify the SAWS Aquifer Protection at (210)-233-3537.

Following any required maintenance, the surface in the pond shall be raked and leveled to restore the system to its designed condition.

With each inspection, any damage to the structural elements of the system (pipes retaining walls, etc.) must be identified and repaired immediately.

"Proper" disposal of accumulated silt shall be accomplished following Texas Commission on Environmental Quality specifications. BMP maintenance frequently requires the disposal of accumulated sediment and other material. These materials are normally classified as special wastes when disposed of in municipal landfills. A Type 1

Municipal Solid Waste (MSW) landfill can accept household waste; anything else is a special waste as defined in 30TAC 330.2 (137). Special waste is a waste that requires special handling at a Type 1 MSW landfill. Labeling a filter media or sediment as a waste is not a waste characterization. The process to obtain authorization to dispose of a special waste begins with a request for approval called the "Request for Authorization for Disposal Waste, TCEQ Form 0152." The request is completed by the generator and submitted to the MSW permits section of the TCEQ for Executive Director review/approval. The MSW permits section performs the review described in 30 TAC 330.136.

An amended copy of this document will be provided to the Texas Commission on Environmental Quality within thirty (30) days of any changes in the following information.

After all inspections, results shall be written and records maintained and made available upon request by TCEQ officials.

Upon transfer of ownership or maintenance responsibility: The seller must inform the buyer of all requirements of the basin maintenance. TCEQ must be notified and receive the form "TCEQ -10623 change in responsibility for maintenance on permanent Best Management Practices and Measures". In addition, TCEQ and SAWS Resource Protection Division shall receive a signed, dated copy of this maintenance plan from the new owner.

VEGETATIVE FILTER STRIPS

Once a vegetated area is well established, little additional maintenance is generally necessary. The key to establishing a viable vegetated feature is the care and maintenance it receives in the first few months after it is plant ed. Once established, all vegetated BMPs require some basic maintenance to insure the health of the plants including:

Pest Management. An Integrated Pest Management (IPM) Plan should be developed for vegetated areas. This plan should specify how problem insects and weeds will be controlled with minimal or no use of insecticides and herbicides.

Seasonal Mowing and Lawn Care. If the filter strip is made up of turf grass, it should be mowed as needed to limit vegetation height to 18 inches, using a mulching mower (or removal of clippings). If native grasses are used, the filter may require less frequent mowing, but a minimum of twice annually. Grass clippings and brush debris should not be deposited on vegetated filter strip areas. Regular mowing should also include weed control practices, however herbicide use should be kept to a minimum (Urbonas et al., 1992). Healthy grass can be maintained without using fertilizers because runoff usually contains sufficient nutrients. Irrigation of the site can help assure a dense and healthy vegetative cover.

Inspection. Inspect filter strips at least twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable. The strip should be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few

years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance needs. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish shallow overland flow.

Debris and Litter Removal. Trash tends to accumulate in vegetated areas, particularly along highways. Any filter strip structures (i.e. level spreaders) should be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but should be performed no less than 4 times per year.

Sediment Removal. Sediment removal is not normally required in filter strips, since the vegetation normally grows through it and binds it to the soil. However, sediment may accumulate along the upstream boundary of the strip preventing uniform overland flow. Excess sediment should be removed by hand or with flat-bottomed shovels.

Grass Reseeding and Mulching. A healthy dense grass should be maintained on the filter strip. If areas are eroded, they should be filled, compacted, and reseeded so that the final grade is level. Grass damaged during the sediment removal process should be promptly replaced using the same seed mix used during filter strip establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Corrective maintenance, such as weeding or replanting should be done more frequently in the first two to three years after installation to ensure stabilization. Dense vegetation may require irrigation immediately after planting, and during particularly dry periods, particularly as the vegetation is initially established.

Responsible Party for Maintenance	L Cinco Properties, LLC
Address	2301 Flushing Meadows
City, State Zip	Weslaco, TX 78596
Telephone Number	(210) 865-2953
Signature of Responsible Party	
Print name of Responsible Party	Matt Lackey

CONTRIBUTING ZONE PLAN APPLICATION

Texas Soil and Stone Outfitters
TCEQ Form-10257

<u>Attachment "O" – Pilot-Scale Field Testing Plan</u>

Not applicable.

Attachment "P" - Measure for Minimizing Surface Stream Contamination

There will be no appreciable increase in velocity that would cause surface stream contamination associated with this development. Storm water by-pass structures have been designed for the 25-year storm for the basin to surface drain storm water run-off. Energy dissipaters have been designed at the outlet structure, as necessary, in order to further minimize the possibility for erosion and surface stream contamination.

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

The Harrie of Castofficity Agent. Internation Trending, 1.2.		
Date: 7/15/2025		
Signature of Customer/Agent:		
N w. Hew		
Regulated Entity Name: Texas Soil and Stone Outfitters		

Print Name of Customer/Agent: Richard Hendrix P.F.

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

L.	Fuels for construction equipment and hazardous substances which will be used during construction:
	The following fuels and/or hazardous substances will be stored on the site:
	These fuels and/or hazardous substances will be stored in:
	Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

	 Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year. Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
	Fuels and hazardous substances will not be stored on the site.
2.	Attachment A - Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
3.	Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
4.	Attachment B - Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.
Se	equence of Construction
5.	Attachment C - Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
	 For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given. For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
6.	Name the receiving water(s) at or near the site which will be disturbed or which will

Temporary Best Management Practices (TBMPs)

receive discharges from disturbed areas of the project: Cibolo Creek

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

7. Attachment D – Temporary Best Management Practices and Measures. TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

	 A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site. A description of how BMPs and measures will prevent pollution of surface water or
	groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
	A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
	A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. 🔀	The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
	Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
	There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. 🔀	Attachment F - Structural Practices. A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10.	Attachment G - Drainage Area Map. A drainage area map supporting the following requirements is attached:
	For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
	For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
	For areas that will have more than 10 acres within a common drainage area
	disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect
	down slope and side slope boundaries of the construction area. There are no areas greater than 10 acres within a common drainage area that will be
	disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

	There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11. 🗌	Attachment H - Temporary Sediment Pond(s) Plans and Calculations. Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
\boxtimes	N/A
12. 🔀	Attachment I - Inspection and Maintenance for BMPs. A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13. 🔀	All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. 🔀	If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. 🔀	Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. 🔀	Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices. A schedule of the interim and permanent soil stabilization practices for the site is attached.

- 18. Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 19. Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

- 20. All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

FORM 0602 ATTACHMENTS

ATTACHMENT "A" - SPILL RESPONSE

In the event of a spill involving hydrocarbons or other hazardous substances, the contractor will immediately notify TCEQ (at 210-490-3096) and the engineer (210 545-1122) explaining the type and nature of the spill. The contractor shall be required to maintain a sufficient stockpile of sand material in the staging area. This sand material shall be used to immediately isolate and provide containment of the spill by constructing dikes. Furthermore, this sand material shall act as an absorbent material that can be disposed of offsite and out of the Recharge Zone during cleanup operations. All contaminated soils resulting from an accidental release will be required to be removed and disposed of in accordance with all local, state, and federal regulations.

The objective of this attachment is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees. The following steps will help reduce the storm water impacts of leaks and spills:

Education

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a "significant spill" is for each material they use, and what is the appropriate response for "significant" and "insignificant" spills. Employees should also be aware of when spill must be reported to the TCEQ. Information is available in 30 TAC 327.4 and 40 CFR 302.4.
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor's superintendent or representative oversee and enforce proper spill prevention and control measures.

General Measures

(1) To the extent that the work can be accomplished safely, spills of oil, petroleum products, and substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.

- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.
- (6) Spills should be covered and protected from storm-water runoff during rainfall to the extent that it does not compromise clean-up activities.
- (7) Do not bury or wash spills with water.
- (8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.
- (9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.
- (10) Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.
- (11) Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.
- (12) Keep waste storage areas clean, well organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

Cleanup

- (1) Clean up leaks and spills immediately.
- (2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.
- (3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

Minor Spills

- (1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.
- (2) Use absorbent materials on small spills rather than hosing down or burying the spill.
- (3) Absorbent materials should be promptly removed and disposed of properly.
- (4) Follow the practice below for a minor spill:
- (5) Contain the spread of the spill.
- (6) Recover spilled materials.
- (7) Clean the contaminated area and properly dispose of contaminated materials.

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman immediately.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities:

(1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM.

After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site. (2) For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110,119, and 302, the contractor should notify the National Response Center at (800) 424-8802.

- (3) Notification should first be made by telephone and followed up with a written report.
- (4) The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.
- (5) Other agencies which may need to be consulted include, but are not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc.

More information on spill rules and appropriate responses is available on the TCEQ website at: https://www.tceq.texas.gov/response/spills

Vehicle and Equipment Maintenance

- (1) If maintenance must occur onsite, use a designated area and a secondary containment, located away from drainage courses, to prevent the run-on of storm-water and the runoff of spills.
- (2) Regularly inspect onsite vehicles and equipment for leaks and repair immediately
- (3) Check incoming vehicles and equipment (including delivery trucks, employee, and subcontractor vehicles) for leaking oil and fluids. Do not allow leaking vehicles or equipment onsite.
- (4) Always use secondary containment, such as a drain pan or drop cloth, to catch spills or leaks when removing or changing fluids.
- (5) Place drip pans or absorbent materials under paving equipment when not in use.
- (6) Use absorbent materials on small spills rather than hosing down or burying the spill. Remove the absorbent materials promptly and dispose of properly.
- (7) Promptly transfer used fluids to the proper waste or recycling drums. Do not leave full drip pans or other open containers lying around.
- (8) Oil filters disposed of in trashcans or dumpsters can leak oil and pollute storm-water. Place the oil filter in a funnel over a waste oil-recycling drum to drain excess oil before disposal. Oil filters can also be recycled. Ask the oil supplier or recycler about recycling oil filters.

(9) Store cracked batteries in a non-leaking secondary container. Do this with all cracked batteries even if you think all the acid has drained out. If you drop a battery, treat it as if it is cracked. Put it into the containment area until you are sure it is not leaking.

Vehicle and Equipment Fueling

- (1) If fueling must occur on site, use designated areas, located away from drainage courses, to prevent the run-on of storm-water and the runoff of spills.
- (2) Discourage "topping off" of fuel tanks.
- (3) Always use secondary containment, such as a drain pan, when fueling to catch spills/leaks.

ATTACHMENT "B" – POTENTIAL SOURCES OF CONTAMINATION

Other potential sources are:

- 1. Oil and gasoline leaks from construction equipment.
- 2. Vehicles tracking in and out of the project.
- 3. Asphaltic paving and associated materials.
- 4. Minor leakage or spillage of paints, lacquers, solvents, etc., used in conjunctions with building construction which may occur simultaneously with infrastructure construction.
- 5. Leakage from self-contained portable toilet facilities.

ATTACHMENT "C" – SEQUENCE OF MAJOR ACTIVITIES

- 1. Install all Temporary BMP's (silt fencing, rock berms), construction entrance, concrete washout pit, and tree protection for on-site construction. (1.25 acres)
- 2. Clear site & prepare area for construction (5.338 acres)
- 3. Excavate and fill site as dictated by the grading plan (5.338 acres)
- 4. Fine grade site (5.338 acres)
- 5. Clean site (5.338 acres)
- 6. Revegetate/stabilize site (5.338 acres)
- 7. Remove temporary BMPs (1.25 acres)

ATTACHMENT "D" - Temporary Best Management Practices

- **A)** There is no up-gradient water flowing onto the site. Surface storm drain systems are proposed to take the treated and untreated run-off through site. The run-off will then discharge through outfall structures and be allowed to flow toward Ciboloe Creek north of the site.
- **B**) All contractors, subcontractors, and builders shall endeavor to avoid the pollution of runoff water by using "best management practices" and reasonable foresight to avoid contact between runoff water and polluting materials.

Some best management practices to which all parties are expected to conform are as follows:

- 1. Prior to the beginning of the work listed in "Attachment C", the contractor will install the sediment control barriers as specified on the separate "Temporary Pollution Abatement Plan" which is attached at the end of this section. These barriers (silt fences, etc.) will be maintained during the entire time construction is in progress. Thus, erodible material and pollution that might be generated during construction will be intercepted by these same barriers.
- 2. The installation of a stabilized construction entrance/exit(s) to reduce the dispersion of sediment from the site.
- 3. The silt fences specified on the "Temporary Pollution Abatement Plan" were positioned to be down gradient of all construction zones. Thus, with proper installation and maintenance these barriers shall be effective in preventing potentially contaminated runoff from leaving the site.
- 4. The general contractor shall develop a written plan to control the generation of dust during construction phase and submit it to the developer.
- 5. Builders and their contractors shall clean equipment only onto areas protected by their silt fences or dikes. Set forth in the TBMP's plan is a location where a "Concrete Truck Washout Pit" will be constructed. The builder shall inform his concrete supplier that this Washout Pit is the only point in the project where washout and waste concrete mix may be discharged.
- 6. Stockpiles of erodible material (topsoil, sand, etc.) shall be placed in areas only protected by silt fences or other erosion barriers.
- 7. All contractors shall provide self-contained toilet facilities for their employees.
- 8. Chemicals, solvents, paints, and other potentially toxic materials must be stored in such a manner that they are protected from rainfall and surface runoff water.

- 9. All contractors shall provide waste receptacles at locations convenient to their construction area; to protect from leaching by rainfall; and provide regular collection.
- C) Once site grading has commenced, swales will be constructed (shaped and sloped as depicted by the grading plan) to direct storm-water run-off to the various outlets located throughout the project. These swales will be used on a temporary and permanent basis. The location of theses swales once constructed will be permanent. Temporary measures installed onsite are intended to provide a method of slowing the flow of runoff from the construction site in order to allow sediment and suspended solids to settle out of the runoff. By containing the sediment and solids within the site, they will not enter the aquifer, sensitive features, or surface streams downgradient of the site
- **D)** BMP measures utilized in this plan are intended to allow stormwater to continue downstream after passing through the BMP's. This will allow stormwater runoff to continue downgradient to streams or features that may exist downstream of the site. The proposed silt fences should be adequate measures to maintain flow to any naturally occurring sensitive features downstream.

If any sensitive features are discovered during construction, all regulated activities near the sensitive feature shall be suspended. The TCEQ Regional office will be notified immediately and a plan will be submitted to TCEQ for treatment of the feature. See note 3 of TCEQ WPAP General Construction Notes.

San Antonio Regional Office 14250 Judson Road	State of Texas Spill-Reporting Hotline (800) 832-8224
San Antonio, Texas 78233-4480	
Phone (210) 490-3096	Bexar County Storm Water Quality
Fax (210) 545-4329	(210) 335-6663

ATTACHMENT "E" – Request to Temporarily Seal a Feature

Not Applicable

<u>ATTACHMENT "F" – Structural Practices</u>

The following measures will be installed as part of the site preparation activities:

- Erection of silt fences along the down gradient boundary of construction activities.
- Stabilized construction entrance/exit(s) will be installed.
- A construction staging area will be designated.
- Concrete truck washout pit(s) will be installed where required to facilitate controlled disposal of concrete truck washout.

ATTACHMENT "G" - Drainage Area Map

Please reference the attached drawing illustrating the proposed drainage areas and subareas. Other erosion controls within each disturbed area will be used, such as silt fencing and inlet protection.

ATTACHMENT "H"- Temporary Sediment Pond Plans and Calculations

Not Applicable. No areas greater than 10 acres with a common drainage area will be disturbed at one time. Batch detention basins, vegetative filter strips, storm drain treatment devices exist for the existing site improvements and have been designed for ultimate development of the drainage areas.

ATTACHMENT "I" - Inspection and Maintenance

All TBMP'S shall be inspected by the contractor on a weekly basis and after all substantial rain events. The contractor shall keep records of all inspections that were made. Also, the contractor shall repair or replace any damaged or dysfunctional TBMP's. The contactor shall insure that all TBMP's are maintained and inspected according to TCEQ's Technical Guidance Manual.

Inspection and Maintenance shall include but is not limited to:

For the Construction Entrance:

- The contractor shall maintain the entrance in a condition which will prevent tracking or flowing of sediment onto public right-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment.
- The contractor shall immediately remove any and all sediment spilled, dropped, washed or tracked onto public rights-of-way.
- When necessary, the contractor shall clean wheels to remove sediment prior to entrance onto public rights-of-way.
- When washing is required, it should be done on an area stabilized with crushed stone that drains into an approved sediment trap or sediment basin.
- The contractor shall prevent all sediment from entering any storm drain, ditch, or watercourse by using approved methods.
- Records will be kept with the construction site Superintendent of all inspection and maintenance actions. See maintenance record chart.

For Silt Fencing:

 The contractor shall inspect all silt fencing weekly and after any rainfall for sediment accumulation, torn fabric and crushed or collapsed sections throughout the duration of construction.

- Sediment shall be removed when sediment buildup reaches 6 inches, or a second line of fencing shall be installed parallel to the original fence.
- Torn fabric shall be replaced by the contractor; a second line of fencing shall be erected parallel to the torn section if replacement is not feasible.
- Contractor shall replace or repair any fence sections crushed or collapsed during the course of construction. Silt fence may be relocated by the contractor to a location where it will provide equal protection should the original/planned installation obstruct vehicular access to the site.
- When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.
- Records will be kept with the construction site Superintendent of all inspection and maintenance actions. See maintenance record chart.

For Rock Berms:

- The contractor shall inspect all rock berms weekly and after any rainfall for sediment accumulation, debris building up, or damage throughout the duration of construction.
- Sediment and other debris shall be removed when sediment buildup reaches 6 inches. The accumulated silt and debris shall be disposed in an approved manner that will not cause any additional siltation.
- The contractor to repair any loose wire sheathing.
- The contractor shall reshape the berm as needed during inspection throughout the duration of construction.
- The contractor shall replace the berm when the structure ceases to function as intended due to silt accumulation among the rocks, washout, construction traffic damage, etc.
- The rock berm shall remain in place until all upstream areas are stabilized and accumulated silt removed.

For Concrete Washout Pit

- The contractor shall inspect all concrete washout pits weekly and after any rainfall.
- Contractor shall ensure that all excess concrete is being washed out into the designated washout pits only.
- The hardened concrete shall be disposed of when the pit is no longer required and when it becomes full.

General

- Records will be kept with the construction site superintendent of all inspections and maintenance actions. See the attached maintenance record chart.
- Litter, construction debris, and construction chemicals exposed to storm water shall be prevented from becoming a pollutant source for storm water discharges (e.g., screening outfalls, picked up daily).

• If sediment escapes the construction site, off site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).

Temporary Stormwater Section Attachment "I" continued

ITEM#	DATE	DESCRIPTION OF ACTION(S) TAKEN	INITIALS


ATTACHMENT "J" - Interim and Permanent Soil Stabilization


Interim on-site stabilization measures, which are continuous, will include minimizing soil disturbances by exposing only the smallest practical area of land required for the shortest period of time and maximizing use of natural vegetation. As soon as practical, all disturbed soil will be stabilized as per project specifications in accordance with pages 1-35 to 1-60 of TCEQ's Technical Guidance Manual (TGM) RG-348 (2005).

All disturbed permeable areas shall be stabilized. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, but in no case more than 14 days after the construction activity in that portion of the site has temporarily or permanently ceased. Where the initiation of stabilization measures by the 14th day after construction activity temporary or permanently cease is prevented by weather conditions, stabilization measures shall be initiated as soon as practicable. Where construction activity on a portion of a site is temporarily ceased, and the earth disturbing activities will be resumed within 21 days, temporary stabilization measures do not have to be initiated on that portion of the site. In areas experiencing droughts where the initiation of stabilization measures by the 14th day after the construction activity has temporarily or permanently ceased is precluded by seasonal arid conditions, stabilization measures shall be initiated as soon as practicable.

Examples of acceptable temporary and permanent soil stabilization measures are establishment of temporary vegetation, establishment of permanent vegetation, mulching, geo-textiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation. The soil stabilization method used in this project **SHALL** be an approved method within the TCEQ Technical Guidance Manuel and **MUST** be approved by MBC Engineers before it is implemented in the project. The method of soil stabilization approved for this project will be a combination of sod stabilization around the buildings and parking areas, tree protection, and hydro mulching those areas disturbed which will not be landscaped.

If construction is to temporary cease and temporary stabilization is required as noted above, the exposed soil shall be stabilized by mulch until construction resumes.





DRAINAGE FLOW

DRAINAGE AREA LABEL

CALCULATION/STUDY POINT

PRIMARY CONTACT: RICHARD HENDRIX, P.E.

180498 33109-1480


PERMIT
DATE: 01/15/2025

PROPOSED/ ULTIMATE DAM

6/26/2025

EX-18

REFERENCE GENERAL NOTES ON SHEET C02.00 PRIOR TO BID AND CONSTRUCTION



PRIMARY CONTACT: RICHARD HENDRIX, P.E

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY CONTRIBUTING ZONE PLAN GENERAL CONSTRUCTION NOTES

EDWARDS AQUIFER PROTECTION PROGRAM CONSTRUCTION NOTES - LEGAL DISCLAIMER

E FOLLOWING/LISTED "CONSTRUCTION NOTES" ARE INTENDED TO BE ADVISORY IN NATURE ONLY AND DO NOT CONSTITUTE AN APPROVAL OR CONDITI APPROVAL BY THE EXECUTIVE DIRECTOR (ED), NOR DO THEY CONSTITUTE A COMPREHENSIVE LISTING OF RULES OR CONDITIONS TO BE FOLLOWED DURING NSTRUCTION. FURTHER ACTIONS MAY BE REQUIRED TO ACHIEVE COMPLIANCE WITH TCEQ REGULATIONS FOUND IN TITLE 30, TEXAS ADMINISTRATIVE COL TAC), CHAPTERS 213 AND 217, AS WELL AS LOCAL ORDINANCES AND REGULATIONS PROVIDING FOR THE PROTECTION OF WATER QUALITY. ADDITIONALL HING CONTAINED IN THE FOLLOWING/LISTED "CONSTRUCTION NOTES" RESTRICTS THE POWERS OF THE ED, THE COMMISSION OR ANY OTHER GOVERNMEN TITY TO PREVENT, CORRECT, OR CURTAIL ACTIVITIES THAT RESULT OR MAY RESULT IN POLLUTION OF THE EDWARDS AQUIFER OR HYDROLOGICALL NECTED SURFACE WATERS. THE HOLDER OF ANY EDWARDS AQUIFER PROTECTION PLAN CONTAINING "CONSTRUCTION NOTES" IS STILL RESPONSIBLE FO OMPLIANCE WITH TITLE 30, TAC, CHAPTERS 213 OR ANY OTHER APPLICABLE TCEQ REGULATION, AS WELL AS ALL CONDITIONS OF AN EDWARDS AQUIFER ROTECTION PLAN THROUGH ALL PHASES OF PLAN IMPLEMENTATION. FAILURE TO COMPLY WITH ANY CONDITION OF THE ED'S APPROVAL, WHETHER OR NOT NTRADICTION OF ANY "CONSTRUCTION NOTES," IS A VIOLATION OF TCEQ REGULATIONS AND ANY VIOLATION IS SUBJECT TO ADMINISTRATIVE RULES, ORDERS ND PENALTIES AS PROVIDED UNDER TITLE 30, TAC § 213.10 (RELATING TO ENFORCEMENT). SUCH VIOLATIONS MAY ALSO BE SUBJECT TO CIVIL PENALTIES AN. INJUNCTION. THE FOLLOWING/LISTED "CONSTRUCTION NOTES" IN NO WAY REPRESENT AN APPROVED EXCEPTION BY THE ED TO ANY PART OF TITLE 30 TAI HAPTERS 213 AND 217, OR ANY OTHER TCEQ APPLICABLE REGULATION

PRIOR TO THE START OF ANY GROUND DISTURBANCE OR CONSTRUCTION ACTIVITIES. THIS NOTICE MUST INCLUDE: - THE NAME OF THE APPROVED PROJECT;

THE CONTACT INFORMATION OF THE PRIME CONTRACTOR.

CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORPECTIVE THE ARRIVANT MILET REDITACE OR MODIEV THE CONTROL FOR SITE SITUATIONS. THES

BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES,

SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS WHEN IT OCCUPIES 50% OF THE BASIN'S DESIGN CAPACITY.

LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE.

ALL EXCAVATED MATERIAL THAT WILL BE STORED ON-SITE MUST HAVE PROPER E&S CONTROLS.

THE FOLLOWING RECORDS SHOULD BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST:

THE HOLDER OF ANY APPROVED CZP MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTA APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:

A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY BEST MANAGEMENT PRACTICES (BMPS) OR STRUCTURE(S), INCLUDING BUT NOT LIMITED TO TEMPORARY OR PERMANENT PONDS, DAMS, BERMS, SILT FENCES, AND DIVERSIONARY STRUCTURES; B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS

ORIGINALLY APPROVED;

. ANY CHANGE THAT WOULD SIGNIFICANTLY IMPACT THE ABILITY TO PREVENT POLLUTION OF THE EDWARDS

D. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE APPROVED CONTRIBUTING ZONE PLAN.

AUSTIN REGIONAL OFFICE 12100 PARK 35 CIRCLE, BUILDING A AUSTIN, TEXAS 78753-1808 PHONE (512) 339-2929

THESE GENERAL CONSTRUCTION NOTES MUST BE INCLUDED ON THE CONSTRUCTION PLANS PROVIDED TO THE CONTRACTOR AND ALL SUBCONTRACTORS.

SUMMARY OF PERMANENT POLLUTION ABATEMENT MEASURES:


1.) TEMPORARY BMP'S WILL BE MAINTAINED UNTIL THE RESPECTIVE WATERSHED HAS BEEN STABILIZED.

2.) ALL AREAS OF DISTURBED SOIL WHICH WILL NOT OTHERWISE BE STABILIZED SHALL BE REVEGETATED TO STABILIZE SOIL USING SOLID BLOCK SOD IN A STAGGERED PATTERN. FOR AREAS OUTSIDE THE BASINS, THE CONTRACTOR MAY SUBSTITUTE SEED-IMPREGNATED EROSION CONTROL MATS OR HYDRAULIC MULCHING AND WATERING UNTIL VEGETATION IS

3.) PERMANENT BMP'S FOR THIS SITE INCLUDE BATCH DETENTION BASIN "A" AND VEGETATIVE FILTER STRIPS. THESE PERMANENT BMP'S HAVE BEEN DESIGNED TO REMOVE 80% OF THE INCREASED TOTAL SUSPENDED SOLIDS (TSS) FOR DRAINAGE AREAS "A", "B", "C" AND "D" IN ACCORDANCE WITH THE TCEQ'S TECHNICAL GUIDANCE MANUAL RG 348 (2005).

4.) ENERGY DISSIPATERS (TO HELP REDUCE EROSION) ARE PROVIDED AT POINTS OF

ISSUED FOR REVIEW 7/14/2025



AERIAL IMAGERY NOTE:

AERIAL IMAGE SHOWN IS FROM 2018 AND DEPICTS THE EXISTING CONDITION OF THE PROPERTY AS TWO (2) SINGLE-FAMILY HOMESTEADS.

A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS

THE ACTIVITY START DATE; AND

ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT SHOULD BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED CONTRIBUTING ZONE PLAN (CZP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTOR(S) SHOULD KEEP COPIES OF THE APPROVED PLAN AND APPROVAL LETTER

NO HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.

PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED.

ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF

IF PORTIONS OF THE SITE WILL HAVE A CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE FOURTEENTH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE TWENTY FIRST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE FOURTEENTH DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE.

THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR; THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; AND THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.

AQUIFER; OR

FAX (512) 339-3795 SAN ANTONIO REGIONAL OFFICE 14250 JUDSON ROAD SAN ANTONIO, TEXAS 78233-4480 PHONE (210) 490-3096 FAX (210) 545-4329

ESTABLISHED. SEED MIXTURE AND/OR GRASS TYPE TO BE DETERMINED BY OWNER.

CONCENTRATED DISCHARGE WHERE EXCESSIVE VELOCITIES MAY BE ENCOUNTERED.

PLAN

180498


33109-1480

07/15/2025

PERMANENT

POLLUTION

ABATEMENT



PRIMARY CONTACT: RICHARD HENDRIX, P.E

PROPERTY AS ONE (1) SINGLE-FAMILY HOMESTEAD AND A CONSTRUCTION LAYDOWN YARD.

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY CONTRIBUTING ZONE PLAN

FOLLOWING/LISTED "CONSTRUCTION NOTES" ARE INTENDED TO BE ADVISORY IN NATURE ONLY AND DO NOT CONSTITUTE AN APPROVAL OR CONDITI APPROVAL BY THE EXECUTIVE DIRECTOR (ED), NOR DO THEY CONSTITUTE A COMPREHENSIVE LISTING OF RULES OR CONDITIONS TO BE FOLLOWED DURING NSTRUCTION. FURTHER ACTIONS MAY BE REQUIRED TO ACHIEVE COMPLIANCE WITH TCEQ REGULATIONS FOUND IN TITLE 30, TEXAS ADMINISTRATIVE COD AC), CHAPTERS 213 AND 217, AS WELL AS LOCAL ORDINANCES AND REGULATIONS PROVIDING FOR THE PROTECTION OF WATER QUALITY. ADDITIONALL ING CONTAINED IN THE FOLLOWING/LISTED "CONSTRUCTION NOTES" RESTRICTS THE POWERS OF THE ED, THE COMMISSION OR ANY OTHER GOVERNMEN TITY TO PREVENT, CORRECT, OR CURTAIL ACTIVITIES THAT RESULT OR MAY RESULT IN POLLUTION OF THE EDWARDS AQUIFER OR HYDROLOGICALL NNECTED SURFACE WATERS. THE HOLDER OF ANY EDWARDS AQUIFER PROTECTION PLAN CONTAINING "CONSTRUCTION NOTES" IS STILL RESPONSIBLE FO OMPLIANCE WITH TITLE 30, TAC, CHAPTERS 213 OR ANY OTHER APPLICABLE TCEQ REGULATION, AS WELL AS ALL CONDITIONS OF AN EDWARDS AQUIFER OTECTION PLAN THROUGH ALL PHASES OF PLAN IMPLEMENTATION. FAILURE TO COMPLY WITH ANY CONDITION OF THE ED'S APPROVAL, WHETHER OR NOT ITRADICTION OF ANY "CONSTRUCTION NOTES," IS A VIOLATION OF TCEQ REGULATIONS AND ANY VIOLATION IS SUBJECT TO ADMINISTRATIVE RULES, ORDERS ID PENALTIES AS PROVIDED UNDER TITLE 30, TAC § 213.10 (RELATING TO ENFORCEMENT). SUCH VIOLATIONS MAY ALSO BE SUBJECT TO CIVIL PENALTIES AN. NJUNCTION. THE FOLLOWING/LISTED "CONSTRUCTION NOTES" IN NO WAY REPRESENT AN APPROVED EXCEPTION BY THE ED TO ANY PART OF TITLE 30 TAC

PRIOR TO THE START OF ANY GROUND DISTURBANCE OR CONSTRUCTION ACTIVITIES. THIS NOTICE MUST INCLUDE:

THE CONTACT INFORMATION OF THE PRIME CONTRACTOR.

ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT SHOULD BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED CONTRIBUTING ZONE PLAN (CZP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTOR(S) SHOULD KEEP COPIES OF THE APPROVED PLAN AND APPROVAL LETTER

PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORPECTIVE THE ARRIVANT MILET REDITACE OR MODIEV THE CONTROL FOR SITE SITUATIONS. THES

ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES,

SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS WHEN IT OCCUPIES 50%

LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE.

ALL EXCAVATED MATERIAL THAT WILL BE STORED ON-SITE MUST HAVE PROPER E&S CONTROLS.

IF PORTIONS OF THE SITE WILL HAVE A CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE FOURTEENTH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE TWENTY FIRST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE FOURTEENTH DAY,

THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR;

APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:

A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY BEST MANAGEMENT PRACTICES (BMPS) OR STRUCTURE(S), INCLUDING BUT NOT LIMITED TO TEMPORARY OR PERMANENT PONDS, DAMS, BERMS, SILT FENCES, AND DIVERSIONARY STRUCTURES; B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS

ORIGINALLY APPROVED;

. ANY CHANGE THAT WOULD SIGNIFICANTLY IMPACT THE ABILITY TO PREVENT POLLUTION OF THE EDWARDS

FAX (512) 339-3795 SAN ANTONIO REGIONAL OFFICE 14250 JUDSON ROAD SAN ANTONIO, TEXAS 78233-4480

FAX (210) 545-4329 THESE GENERAL CONSTRUCTION NOTES MUST BE INCLUDED ON THE CONSTRUCTION PLANS PROVIDED TO THE CONTRACTOR AND ALL SUBCONTRACTORS.


SUMMARY OF PERMANENT POLLUTION ABATEMENT MEASURES:

2.) ALL AREAS OF DISTURBED SOIL WHICH WILL NOT OTHERWISE BE STABILIZED SHALL BE REVEGETATED TO STABILIZE SOIL USING SOLID BLOCK SOD IN A STAGGERED PATTERN. FOR AREAS OUTSIDE THE BASINS, THE CONTRACTOR MAY SUBSTITUTE SEED-IMPREGNATED EROSION CONTROL MATS OR HYDRAULIC MULCHING AND WATERING UNTIL VEGETATION IS ESTABLISHED. SEED MIXTURE AND/OR GRASS TYPE TO BE DETERMINED BY OWNER.

3.) PERMANENT BMP'S FOR THIS SITE INCLUDE BATCH DETENTION BASIN "A" AND VEGETATIVE FILTER STRIPS. THESE PERMANENT BMP'S HAVE BEEN DESIGNED TO REMOVE 80% OF THE INCREASED TOTAL SUSPENDED SOLIDS (TSS) FOR DRAINAGE AREAS "A", "B", "C" AND "D" IN ACCORDANCE WITH THE TCEQ'S TECHNICAL GUIDANCE MANUAL RG 348 (2005).

4.) ENERGY DISSIPATERS (TO HELP REDUCE EROSION) ARE PROVIDED AT POINTS OF CONCENTRATED DISCHARGE WHERE EXCESSIVE VELOCITIES MAY BE ENCOUNTERED.

> ISSUED FOR REVIEW 7/14/2025



AERIAL IMAGERY NOTE:

AERIAL IMAGE SHOWN IS FROM 2022 AND DEPICTS THE EXISTING CONDITION OF THE

GENERAL CONSTRUCTION NOTES

EDWARDS AQUIFER PROTECTION PROGRAM CONSTRUCTION NOTES - LEGAL DISCLAIMER

IAPTERS 213 AND 217, OR ANY OTHER TCEQ APPLICABLE REGULATION

A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS - THE NAME OF THE APPROVED PROJECT;

THE ACTIVITY START DATE; AND

NO HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY

SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.

CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED.

OF THE BASIN'S DESIGN CAPACITY.

STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE.

THE FOLLOWING RECORDS SHOULD BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST:

THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; AND THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.

THE HOLDER OF ANY APPROVED CZP MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTA

AQUIFER; OR

D. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE APPROVED CONTRIBUTING ZONE PLAN.

AUSTIN REGIONAL OFFICE 12100 PARK 35 CIRCLE, BUILDING A AUSTIN, TEXAS 78753-1808 PHONE (512) 339-2929

PHONE (210) 490-3096

1.) TEMPORARY BMP'S WILL BE MAINTAINED UNTIL THE RESPECTIVE WATERSHED HAS BEEN STABILIZED.

180498

33109-1480

07/15/2025

PERMANENT

POLLUTION

ABATEMENT

PLAN

LEGEND

EXISTING IMPERVIOUS

COVER (2018 IMAGE) -

EXISTING IMPERVIOUS COVER (2022 IMAGE) -ZACHRÝ LAYDOWN ÝARD EXISTING IMPERVIOUS COVER (2025 IMAGE) -TEXAS SOIL & STONE YARD

ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT SHOULD BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED CONTRIBUTING ZONE PLAN (CZP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED

NO HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.

PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S)

ACTIVITIES, THE CONTRACTOR(S) SHOULD KEEP COPIES OF THE APPROVED PLAN AND APPROVAL LETTER

A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS PRIOR TO THE START OF ANY GROUND DISTURBANCE OR CONSTRUCTION ACTIVITIES. THIS NOTICE MUST

EDWARDS AQUIFER PROTECTION PROGRAM CONSTRUCTION NOTES - LEGAL DISCLAIMER THE FOLLOWING/LISTED "CONSTRUCTION NOTES" ARE INTENDED TO BE ADVISORY IN NATURE ONLY AND DO NOT CONSTITUTE AN APPROVAL OR CONDITI APPROVAL BY THE EXECUTIVE DIRECTOR (ED), NOR DO THEY CONSTITUTE A COMPREHENSIVE LISTING OF RULES OR CONDITIONS TO BE FOLLOWED DURING CONSTRUCTION. FURTHER ACTIONS MAY BE REQUIRED TO ACHIEVE COMPLIANCE WITH TCEQ REGULATIONS FOUND IN TITLE 30, TEXAS ADMINISTRATIVE COL (TAC), CHAPTERS 213 AND 217, AS WELL AS LOCAL ORDINANCES AND REGULATIONS PROVIDING FOR THE PROTECTION OF WATER QUALITY. ADDITIONALL THING CONTAINED IN THE FOLLOWING/LISTED "CONSTRUCTION NOTES" RESTRICTS THE POWERS OF THE ED, THE COMMISSION OR ANY OTHER GOVERNMEN ENTITY TO PREVENT, CORRECT, OR CURTAIL ACTIVITIES THAT RESULT OR MAY RESULT IN POLLUTION OF THE EDWARDS AQUIFER OR HYDROLOGICALL CONNECTED SURFACE WATERS. THE HOLDER OF ANY EDWARDS AQUIFER PROTECTION PLAN CONTAINING "CONSTRUCTION NOTES" IS STILL RESPONSIBLE FO COMPLIANCE WITH TITLE 30, TAC, CHAPTERS 213 OR ANY OTHER APPLICABLE TCEQ REGULATION, AS WELL AS ALL CONDITIONS OF AN EDWARDS AQUIFER PROTECTION PLAN THROUGH ALL PHASES OF PLAN IMPLEMENTATION. FAILURE TO COMPLY WITH ANY CONDITION OF THE ED'S APPROVAL, WHETHER OR NOT CONTRADICTION OF ANY "CONSTRUCTION NOTES," IS A VIOLATION OF TCEQ REGULATIONS AND ANY VIOLATION IS SUBJECT TO ADMINISTRATIVE RULES, ORDERS AND PENALTIES AS PROVIDED UNDER TITLE 30, TAC § 213.10 (RELATING TO ENFORCEMENT). SUCH VIOLATIONS MAY ALSO BE SUBJECT TO CIVIL PENALTIES AN INJUNCTION. THE FOLLOWING/LISTED "CONSTRUCTION NOTES" IN NO WAY REPRESENT AN APPROVED EXCEPTION BY THE ED TO ANY PART OF TITLE 30 TAG

CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORRECTLY THE APPLICANT MUST REPLACE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THES CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED. ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES,

SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS WHEN IT OCCUPIES 50% OF THE BASIN'S DESIGN CAPACITY.

LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE.

ALL EXCAVATED MATERIAL THAT WILL BE STORED ON-SITE MUST HAVE PROPER E&S CONTROLS.

IF PORTIONS OF THE SITE WILL HAVE A CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE FOURTEENTH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE TWENTY FIRST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE FOURTEENTH DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE

THE FOLLOWING RECORDS SHOULD BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST:

THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR; THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; AND THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.

THE HOLDER OF ANY APPROVED CZP MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:

A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY BEST MANAGEMENT PRACTICES (BMPS) OR STRUCTURE(S), INCLUDING BUT NOT LIMITED TO TEMPORARY OR PERMANENT PONDS, DAMS, BERMS, SILT FENCES, AND DIVERSIONARY STRUCTURES;

B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED;

C. ANY CHANGE THAT WOULD SIGNIFICANTLY IMPACT THE ABILITY TO PREVENT POLLUTION OF THE EDWARDS AQUIFER; OR

D. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE APPROVED CONTRIBUTING ZONE PLAN.

AUSTIN REGIONAL OFFICE 12100 PARK 35 CIRCLE, BUILDING A AUSTIN, TEXAS 78753-1808 PHONE (512) 339-2929 FAX (512) 339-3795

AERIAL IMAGERY NOTE:

INCLUDE:

COMMERCIAL APPLICATIONS.

CHAPTERS 213 AND 217, OR ANY OTHER TCEQ APPLICABLE REGULATION

- THE NAME OF THE APPROVED PROJECT THE ACTIVITY START DATE; AND

THE CONTACT INFORMATION OF THE PRIME CONTRACTOR.

SAN ANTONIO REGIONAL OFFICE 14250 JUDSON ROAD SAN ANTONIO, TEXAS 78233-4480 PHONE (210) 490-3096 FAX (210) 545-4329

STABILIZED.

THESE GENERAL CONSTRUCTION NOTES MUST BE INCLUDED ON THE CONSTRUCTION PLANS PROVIDED TO THE CONTRACTOR AND ALL SUBCONTRACTORS.

SUMMARY OF PERMANENT POLLUTION ABATEMENT MEASURES:

1.) TEMPORARY BMP'S WILL BE MAINTAINED UNTIL THE RESPECTIVE WATERSHED HAS BEEN

2.) ALL AREAS OF DISTURBED SOIL WHICH WILL NOT OTHERWISE BE STABILIZED SHALL BE REVEGETATED TO STABILIZE SOIL USING SOLID BLOCK SOD IN A STAGGERED PATTERN. FOR AREAS OUTSIDE THE BASINS, THE CONTRACTOR MAY SUBSTITUTE SEED-IMPREGNATED EROSION CONTROL MATS OR HYDRAULIC MULCHING AND WATERING UNTIL VEGETATION IS ESTABLISHED. SEED MIXTURE AND/OR GRASS TYPE TO BE DETERMINED BY OWNER.

3.) PERMANENT BMP'S FOR THIS SITE INCLUDE BATCH DETENTION BASIN "A" AND VEGETATIVE FILTER STRIPS. THESE PERMANENT BMP'S HAVE BEEN DESIGNED TO REMOVE 80% OF THE INCREASED TOTAL SUSPENDED SOLIDS (TSS) FOR DRAINAGE AREAS "A", "B", "C" AND "D" IN ACCORDANCE WITH THE TCEQ'S TECHNICAL GUIDANCE MANUAL RG 348 (2005).

4.) ENERGY DISSIPATERS (TO HELP REDUCE EROSION) ARE PROVIDED AT POINTS OF CONCENTRATED DISCHARGE WHERE EXCESSIVE VELOCITIES MAY BE ENCOUNTERED.

> ISSUED FOR REVIEW 7/14/2025



DRAINAGE AREA NAME DRAINAGE AREA IN ACRES

—780— EXISTING CONTOUR

PROJECT LIMITS DRAINAGE BOUNDARY ORIGINAL PROJECT LIMITS

→ FLOW PATH

[100] PROPOSED CONTOUR

AERIAL IMAGE SHOWN IS FROM 2025 AND DEPICTS THE EXISTING CONDITION OF THE PROPERTY IN ITS CURRENT STATE AS A FACILITY THAT SELLS SOIL AND STONE FOR TEXAS COMMISSION ON ENVIRONMENTAL QUALITY CONTRIBUTING ZONE PLAN GENERAL CONSTRUCTION NOTES

180498 33109-1480

07/15/2025 PERMANENT

POLLUTION ABATEMENT PLAN

TSS Removal Calculations 04-20-2009

Project Name: TSS SITE

Date Prepared: 6/26/2025

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_{M} = 27.2(A_{N} \times P)$

where:

 $L_{M \, TOTAL \, PROJECT}$ = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Bexar	
Total project area included in plan *=	5.34	acres
Predevelopment impervious area within the limits of the plan * =	0.41	acres
Total post-development impervious area within the limits of the plan* =	4.10	acres
Total post-development impervious cover fraction * =	0.77	
P =	30	inches

L_{M TOTAL PROJECT} = 3010 lb

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area =

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. = SITE

Total drainage basin/outfall area = 5.34 acres

Predevelopment impervious area within drainage basin/outfall area = 0.41 acres

Post-development impervious area within drainage basin/outfall area = 4.10
Post-development impervious fraction within drainage basin/outfall area = 0.77

 $L_{M \text{ THIS BASIN}} = 3010$ lbs.

3. Indicate the proposed BMP Code for this basin.

Proposed BMP = Batch Detention Basin Removal efficiency = 91 percent

4. Calculate Maximum TSS Load Removed (LR) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7: L_R = (BMP efficiency) x P x (A_I x 34.6 + A_P x 0.54)

where:

A_C = Total On-Site drainage area in the BMP catchment area

A_I = Impervious area proposed in the BMP catchment area

acres

 A_P = Pervious area remaining in the BMP catchment area

 L_{R} = TSS Load removed from this catchment area by the proposed BMP

 $A_C = 5.34$ acres $A_I = 4.10$ acres $A_P = 1.24$ acres $A_P = 3892$ lbs

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

Desired $L_{M THIS BASIN} = 3010$ lbs.

F = 0.77

6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area.

Calculations from RG-348

Pages 3-34 to 3-36

0.97 inches

Rainfall Depth =
Post Development Runoff Coefficient =
On-site Water Quality Volume =

0.58 10963

2193

cubic feet

Calculations from RG-348 Pages 3-36 to 3-37

Off-site area draining to BMP =
Off-site Impervious cover draining to BMP =
Impervious fraction of off-site area =
Off-site Runoff Coefficient =
Off-site Water Quality Volume = 0.00 0.00 0 acres acres

0.00

cubic feet

Storage for Sediment =

Total Capture Volume (required water quality volume(s) x 1.20) = 13156 cubic feet

TSS Removal Calculations 04-20-2009

Project Name: TSS POND Date Prepared: 6/26/2025

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_M = 27.2(A_N x P)$

where:

L_{M TOTAL PROJECT} = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Bexar	
Total project area included in plan *=	5.34	acres
Predevelopment impervious area within the limits of the plan *=	0.41	acres
Total post-development impervious area within the limits of the plan* =	4.10	acres
Total post-development impervious cover fraction * =	0.77	1
P =	30	inches

L_M TOTAL PROJECT =

lbs.

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area =

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	Basin A	
Total drainage basin/outfall area =	3.71	acres
Predevelopment impervious area within drainage basin/outfall area =	0.26	acres
Post-development impervious area within drainage basin/outfall area =	3.18	acres
Post-development impervious fraction within drainage basin/outfall area =	0.86	
L _{M THIS BASIN} =	2383	lbs.

Dunimana Banin/Outfall Assa Na

3. Indicate the proposed BMP Code for this basin.

Proposed BMP = Batch Detention Basin Removal efficiency = percent

4. Calculate Maximum TSS Load Removed (LR) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7: L_R = (BMP efficiency) x P x (A_I x 34.6 + A_P x 0.54)

where:

 A_{C} = Total On-Site drainage area in the BMP catchment area

A_I = Impervious area proposed in the BMP catchment area

A_P = Pervious area remaining in the BMP catchment area

 L_R = TSS Load removed from this catchment area by the proposed BMP

A_c = 3.71 acres 3.18 acres 0.53 acres 3012 lbs

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

Desired L_{M THIS BASIN} = 2385 lbs.

0.79

Rainfall Depth = Post Development Runoff Coefficient = On-site Water Quality Volume = 1.04 inches 0.70

9804 cubic feet

Calculations from RG-348 Pages 3-36 to 3-37

Off-site area draining to BMP =
Off-site Impervious cover draining to BMP =
Impervious fraction of off-site area =
Off-site Runoff Coefficient =
Off-site Water Quality Volume = 0.00 0.00 0 acres acres

0.00

cubic feet 0

> Storage for Sediment = 1961

Total Capture Volume (required water quality volume(s) x 1.20) = 11765 cubic feet

TSS Removal Calculations 04-20-2009

Project Name: VFS P1
Date Prepared: 6/26/2025

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

3010

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_{M} = 27.2(A_{N} \times P)$

where:

 $L_{\text{M TOTAL PROJECT}} = \text{Required TSS removal resulting from the proposed development} = 80\% \text{ of increased load}$

 A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Bexar	
Total project area included in plan *=	5.34	acres
Predevelopment impervious area within the limits of the plan *=	0.41	acres
Total post-development impervious area within the limits of the plan* =	4.10	acres
Total post-development impervious cover fraction * =	0.77	7
P =	30	inches

L_M TOTAL PROJECT =

* The values entered in these fields should be for the total project area.


Number of drainage basins / outfalls areas leaving the plan area =

2. Drainage Basin Parameters (This information should be provided for each basin):

	VFS P1	Drainage Basin/Outfall Area No. =
acres	0.23	Total drainage basin/outfall area =
acres	0.00	Predevelopment impervious area within drainage basin/outfall area =
acres	0.07	Post-development impervious area within drainage basin/outfall area =
	0.30	Post-development impervious fraction within drainage basin/outfall area =
lbs.	57	L _{M THIS BASIN} =

3. Indicate the proposed BMP Code for this basin.

Proposed BMP = Vegetated Filter Strips
Removal efficiency = 85 percent



TSS Removal Calculations 04-20-2009

Project Name: VFS P3
Date Prepared: 6/26/202

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_{M} = 27.2(A_{N} \times P)$

where:

 $L_{\text{M TOTAL PROJECT}} = \text{Required TSS removal resulting from the proposed development} = 80\% \text{ of increased load}$

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Bexar	
Total project area included in plan *=	5.34	acres
Predevelopment impervious area within the limits of the plan *=	0.41	acres
Total post-development impervious area within the limits of the plan* =	4.10	acres
Total post-development impervious cover fraction * =	0.77	
P =	30	inches

L_{M TOTAL PROJECT} = 3010 lbs.

Number of drainage basins / outfalls areas leaving the plan area =

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	VEC D2

Diamage DasimOutian Alea No	VF3 F3	
Total drainage basin/outfall area =	0.53	acres
Predevelopment impervious area within drainage basin/outfall area =	0.00	acres
Post-development impervious area within drainage basin/outfall area =	0.19	acres
Post-development impervious fraction within drainage basin/outfall area =	0.36	
L _{M THIS BASIN} =	155	lbs.

3. Indicate the proposed BMP Code for this basin.

Proposed BMP = Vegetated Filter Strips
Removal efficiency = 85 percent



^{*} The values entered in these fields should be for the total project area.

TSS Removal Calculations 04-20-2009

Project Name: VFS P4
Date Prepared: 6/26/2025

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields.

Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Calculations from RG-348

Pages 3-27 to 3-30

Page 3-29 Equation 3.3: $L_{M} = 27.2(A_{N} \times P)$

where:

 $L_{M \; TOTAL \; PROJECT}$ = Required TSS removal resulting from the proposed development = 80% of increased load A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

County =	Bexar	
Total project area included in plan *=	5.34	acres
Predevelopment impervious area within the limits of the plan * =	0.41	acres
Total post-development impervious area within the limits of the plan* =	4.10	acres
Total post-development impervious cover fraction * =	0.77	
P =	30	inches

L_M TOTAL PROJECT =

3010

0 lbs

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area =

1

2. Drainage Basin Parameters (This information should be provided for each basin):

Dialitage Dasili/Outlail Alea No	VF3 F4	
Total drainage basin/outfall area =	0.87	acres
Predevelopment impervious area within drainage basin/outfall area =	0.10	acres
Post-development impervious area within drainage basin/outfall area =	0.67	acres
Post-development impervious fraction within drainage basin/outfall area =	0.77	
L _{M THIS BASIN} =	465	lbs.

3. Indicate the proposed BMP Code for this basin.

Proposed BMP = Vegetated Filter Strips
Removal efficiency = 85 percent





Notice of Intent (NOI) for an Authorization for Stormwater Discharges Associated with Construction Activity under TPDES General Permit TXR150000

IMPORTANT INFORMATION

Please read and use the General Information and Instructions prior to filling out each question in the NOI form.

Use the NOI Checklist to ensure all required information is completed correctly. **Incomplete applications delay approval or result in automatic denial.**

Once processed your permit authorization can be viewed by entering the following link into your internet browser: http://www2.tceq.texas.gov/wq_dpa/index.cfm or you can contact TCEO Stormwater Processing Center at 512-239-3700.

ePERMITS

Effective September 1, 2018, this paper form must be submitted to TCEQ with a completed electronic reporting waiver form (TCEQ-20754).

To submit an NOI electronically, enter the following web address into your internet browser and follow the instructions: https://www3.tceq.texas.gov/steers/index.cfm

APPLICATION FEE AND PAYMENT

The application fee for submitting a paper NOI is \$325. The application fee for electronic submittal of a NOI through the TCEQ ePermits system (STEERS) is \$225.

Payment of the application fee can be submitted by mail or through the TCEQ ePay system. The payment and the NOI must be mailed to separate addresses. To access the TCEQ ePay system enter the following web address into your internet browser: http://www.tceq.texas.gov/epay.

Provide your payment information for verification of payment:

- If payment was mailed to TCEQ, provide the following:
 - Check/Money Order Number:
 - Name printed on Check:
- If payment was made via ePay, provide the following:
 - o Voucher Number:
 - o A copy of the payment voucher is attached to this paper NOI form.

RE	NEWAL (This portion of the NOI is not applicable after June 3, 2018)
Is t	his NOI for a renewal of an existing authorization? \square Yes \boxtimes No
If Y	Yes, provide the authorization number here: TXR15
NC	TE: If an authorization number is not provided, a new number will be assigned.
SE	CTION 1. OPERATOR (APPLICANT)
a)	If the applicant is currently a customer with TCEQ, what is the Customer Number (CN) issued to this entity? CN
	(Refer to Section 1.a) of the Instructions)
b)	What is the Legal Name of the entity (applicant) applying for this permit? (The legal name must be spelled exactly as filed with the Texas Secretary of State, County, or in the legal document forming the entity.)
	<u>L Cinco Properties, LLC</u>
c)	What is the contact information for the Operator (Responsible Authority)?
	Prefix (Mr. Ms. Miss): <u>Mr.</u>
	First and Last Name: <u>Matt</u> Suffix: <u>Lackey</u>
	Title: Credentials:
	Phone Number: (210) 865-2953 Fax Number:
	E-mail: matt@jrproducesupply.com
	Mailing Address: <u>2301 Flushing Meadows</u>
	City, State, and Zip Code: Weslaco, Texas 78596
	Mailing Information if outside USA:
	Territory: Mak here to enter text
	Country Code: Postal Code:
d)	Indicate the type of customer:
	□ Individual □ Federal Government
	□ County Government
	☐ General Partnership ☐ State Government
	☐ Trust ☐ City Government
	☐ Sole Proprietorship (D.B.A.) ☐ Other Government
	□ Corporation □ Other:
	□ Estate
e)	Is the applicant an independent operator? $ extstyle e$

	(If a governmental entity	a subsidiary or	part of a larger corporation, check No.)	
f)		•	pplicable to your company.	
<i>1)</i>	№ 0-20	rect the runge a	□ 251-500	
	□ 21-100		□ 501 or higher	
			in Jot of Higher	
_ \	□ 101-250	and male and the state of	(Demains of Control of	
g)			ers: (Required for Corporations and Lim lls, Government, or Sole Proprietors.)	ıted
	State Franchise Tax ID Nu	mber: <u>3208306</u>	<u>5337</u>	
	Federal Tax ID: <u>88-0677</u>	911		
	Texas Secretary of State C	Charter (filing) N	Jumber: <u>0804431963</u>	
	DUNS Number (if known)	Click here to e	nter text.	
SE	CTION 2. APPLICATION C	ONTACT		
Ic t	the application contact the	a cama ac tha an	unlicant identified above?	
15 (\boxtimes Yes, go to Section 3	same as the ap	plicant lucitineu above:	
		otion		
Dag	☐ No, complete this se	Ction		
	efix (Mr. Ms. Miss):		Confficu	
	st and Last Name:	Cuadantial	Suffix:	
Tit		Credential:		
	ganization Name:	re to enter text.	Alamah am	
	one Number:	Fax	Number:	
	nail:			
	iling Address:	o enter text.		
	ernal Routing (Mail Code,	ETC.):	to enter text	
	y, State, and Zip Code:	ck nere to enter		
	iling information if outsid	e USA:		
	rritory:	Text.		
Co	untry Code:	Posta	l Code:	
SE	CTION 3. REGULATED ENT	TITY (RE) INFOR	MATION ON PROJECT OR SITE	
a)	If this is an existing permissued to this site? RN	nitted site, what	is the Regulated Entity Number (RN)	
	(Refer to Section 3.a) of the	ne Instructions)		
	(Iterer to beenon bid) of the	ic moducuons)		

- b) Name of project or site (the name known by the community where it's located): Texas Soil and Stone Outfitters
- c) In your own words, briefly describe the type of construction occurring at the regulated site (residential, industrial, commercial, or other): Bulk soil and stone
- d) County or Counties (if located in more than one): Bexar
- e) Latitude: 29.703172 N Longitude: -98.454661 W
- f) Site Address/Location

If the site has a physical address such as 12100 Park 35 Circle, Austin, TX 78753, complete *Section A*.

If the site does not have a physical address, provide a location description in *Section B*. Example: located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1.

Section A:

Street Number and Name:27230 Bulverde

City, State, and Zip Code: San Antonio, TX, 78260

Section B:

Location Description: east side of Bulverde Road

City (or city nearest to) where the site is located: San Antonio

Zip Code where the site is located: <u>78260</u>

SECTION 4. GENERAL CHARACTERISTICS

a)	Is the project or site located on Indian Country Lands?
	☐ Yes, do not submit this form. You must obtain authorization through EPA Region 6.
	⊠ No
b)	Is your construction activity associated with a facility that, when completed, would be associated with the exploration, development, or production of oil or gas or geothermal

resources?

Yes. Note: The construction stormwater runoff may be under jurisdiction of the Railroad Commission of Texas and may need to obtain authorization through EPA

Region 6.

⊠ No

- c) What is the Primary Standard Industrial Classification (SIC) Code that best describes the construction activity being conducted at the site? $\underline{1542}$
- d) What is the Secondary SIC Code(s), if applicable? <u>1522</u>
- e) What is the total number of acres to be disturbed? 5.33 + / -
- f) Is the project part of a larger common plan of development or sale?

□ Yes

	No. The total number of acres disturbed, provided in e) above, must be 5 or n If the total number of acres disturbed is less than 5, do not submit this form the requirements in the general permit for small construction sites.	
g)	What is the estimated start date of the project? March 15, 2025	
h)	What is the estimated end date of the project? <u>September 12, 2025</u>	
i)	Will concrete truck washout be performed at the site? $\ oxtimes$ Yes $\ oxtimes$ No	
j)	What is the name of the first water body(ies) to receive the stormwater runoff or potential runoff from the site? <u>Upper Cibolo Creek</u>	
k)	What is the segment number(s) of the classified water body(ies) that the discharge eventually reach? <u>1908</u>	will
1)	Is the discharge into a Municipal Separate Storm Sewer System (MS4)?	
	⊠ Yes □ No	
	If Yes, provide the name of the MS4 operator: San Antonio Water System	
	Note: The general permit requires you to send a copy of this NOI form to the MS4 operator.	
m)	Is the discharge or potential discharge from the site within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer, as defined in 30 TAC Chapter 213?	
	oxtimes Yes, complete the certification below.	
	□ No, go to Section 5	
	I certify that the copy of the TCEQ-approved Plan required by the Edwards Aquifer (30 TAC Chapter 213) that is included or referenced in the Stormwater Pollution Prevention Plan will be implemented.	r Rule Yes
SE	CTION 5. NOI CERTIFICATION	
2)	I certify that I have obtained a copy and understand the terms and conditions of the	ho
a)	•	Yes
b)	I certify that the full legal name of the entity applying for this permit has been proand is legally authorized to do business in Texas.	ovided Ves
c)	I understand that a Notice of Termination (NOT) must be submitted when this authorization is no longer needed.	☑ Yes
d)	I certify that a Stormwater Pollution Prevention Plan has been developed, will be implemented prior to construction and to the best of my knowledge and belief is compliant with any applicable local sediment and erosion control plans, as require the Construction General Permit (TXR150000).	ed in Yes
	Note: For multiple operators who prepare a shared SWP3, the confirmation of an	

operator may be limited to its obligations under the SWP3, provided all obligations are

confirmed by at least one operator.

Operator Signatory Name:
Operator Signatory Title:
I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.
I further certify that I am authorized under 30 Texas Administrative Code §305.44 to sign and submit this document, and can provide documentation in proof of such authorization upon request.
Signature (use blue ink): Date:

SECTION 6. APPLICANT CERTIFICATION SIGNATURE

NOTICE OF INTENT CHECKLIST (TXR150000)

Did you complete everything? Use this checklist to be sure!

Are you ready to mail your form to TCEQ? Go to the General Information Section of the Instructions for mailing addresses.

Confirm each item (or applicable item) in this form is complete. This checklist is for use by the applicant to ensure a complete application is being submitted. **Missing information may result in denial of coverage under the general permit.** (See NOI process description in the General Information and Instructions.)

APPLICATION FEE
If paying by check:
☐ Check was mailed separately to the TCEQs Cashier's Office. (See Instructions for Cashier's address and Application address.)
\square Check number and name on check is provided in this application.
If using ePay:
\square The voucher number is provided in this application and a copy of the voucher is attached
RENEWAL
☐ If this application is for renewal of an existing authorization, the authorization number is provided.
OPERATOR INFORMATION
☑ Customer Number (CN) issued by TCEQ Central Registry
☑ Legal name as filed to do business in Texas. (Call TX SOS 512-463-5555 to verify.)
☑ Name and title of responsible authority signing the application.
☑ Phone number and e-mail address
☑ Mailing address is complete & verifiable with USPS. <u>www.usps.com</u>
☑ Type of operator (entity type). Is applicant an independent operator?
☑ Number of employees.
☑ For corporations or limited partnerships – Tax ID and SOS filing numbers.
■ Application contact and address is complete & verifiable with USPS. http://www.usps.com
REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

⊠ Regulated Entity Number (RN) (if site is already regulated by TCEQ)

☑ Latitude and longitude http://www.tceq.texas.gov/gis/sqmaview.html

⊠ Site/project name and construction activity description

⊠ County

⊠ Site Address/Location. Do not use a rural route or post office box.

GENERAL CHARACTERISTICS

- ☑ Indian Country Lands -the facility is not on Indian Country Lands.
- ☑ Construction activity related to facility associated to oil, gas, or geothermal resources
- ☑ Primary SIC Code that best describes the construction activity being conducted at the site. www.osha.gov/oshstats/sicser.html
- ☑ Estimated starting and ending dates of the project.
- ☑ Confirmation of concrete truck washout.
- ☑ Acres disturbed is provided and qualifies for coverage through a NOI.
- ⊠ Common plan of development or sale.
- ⊠ Receiving water body or water bodies.
- ⊠ Segment number or numbers.
- \boxtimes MS4 operator.
- ⊠ Edwards Aquifer rule.

CERTIFICATION

- ☑ Certification statements have been checked indicating Yes.
- ⊠ Signature meets 30 Texas Administrative Code (TAC) §305.44 and is original.

Instructions for Notice of Intent (NOI) for Stormwater Discharges Associated with Construction Activity under TPDES General Permit (TXR150000)

GENERAL INFORMATION

Where to Send the Notice of Intent (NOI):

By Regular Mail: By Overnight or Express Mail:

TCEQ TCEQ

Stormwater Processing Center (MC228) Stormwater Processing Center (MC228)

P.O. Box 13087 12100 Park 35 Circle

Austin, Texas 78711-3087 Austin, TX

Application Fee:

The application fee of \$325 is required to be paid at the time the NOI is submitted. Failure to submit payment at the time the application is filed will cause delays in acknowledgment or denial of coverage under the general permit. Payment of the fee may be made by check or money order, payable to TCEQ, or through EPAY (electronic payment through the web).

Mailed Payments:

Use the attached General Permit Payment Submittal Form. The application fee is submitted to a different address than the NOI. Read the General Permit Payment Submittal Form for further instructions, including the address to send the payment.

ePAY Electronic Payment: http://www.tceq.texas.gov/epay

When making the payment you must select Water Quality, and then select the fee category "General Permit Construction Storm Water Discharge NOI Application". You must include a copy of the payment voucher with your NOI. Your NOI will not be considered complete without the payment voucher.

TCEQ Contact List:

Application – status and form questions: 512-239-3700, swpermit@tceq.texas.gov 512-239-4671, swgp@tceq.texas.gov

Environmental Law Division: 512-239-0600 Records Management - obtain copies of forms: 512-239-0900

Reports from databases (as available): 512-239-DATA (3282)

Cashier's office: 512-239-0357 or 512-239-0187

Notice of Intent Process:

When your NOI is received by the program, the form will be processed as follows:

Administrative Review: Each item on the form will be reviewed for a
complete response. In addition, the operator's legal name must be
verified with Texas Secretary of State as valid and active (if applicable).
The address(es) on the form must be verified with the US Postal service
as receiving regular mail delivery. Do not give an overnight/express
mailing address.

- **Notice of Deficiency:** If an item is incomplete or not verifiable as indicated above, a notice of deficiency (NOD) will be mailed to the operator. The operator will have 30 days to respond to the NOD. The response will be reviewed for completeness.
- **Acknowledgment of Coverage:** An Acknowledgment Certificate will be mailed to the operator. This certificate acknowledges coverage under the general permit.

or

Denial of Coverage: If the operator fails to respond to the NOD or the response is inadequate, coverage under the general permit may be denied. If coverage is denied, the operator will be notified.

General Permit (Your Permit)

For NOIs submitted **electronically** through ePermits, provisional coverage under the general permit begins immediately following confirmation of receipt of the NOI form by the TCEQ.

For paper NOIs, provisional coverage under the general permit begins 7 days after a completed NOI is postmarked for delivery to the TCEQ.

You should have a copy of your general permit when submitting your application. You may view and print your permit for which you are seeking coverage, on the TCEQ web site http://www.tceq.texas.gov. Search using keyword TXR150000.

Change in Operator

An authorization under the general permit is not transferable. If the operator of the regulated project or site changes, the present permittee must submit a Notice of Termination and the new operator must submit a Notice of Intent. The NOT and NOI must be submitted no later than 10 days prior to the change in Operator status.

TCEQ Central Registry Core Data Form

The Core Data Form has been incorporated into this form. Do not send a Core Data Form to TCEQ. After final acknowledgment of coverage under the general permit, the program will assign a Customer Number and Regulated Entity Number, if one has not already been assigned to this customer or site.

For existing customers and sites, you can find the Customer Number and Regulated Entity Number by entering the following web address into your internet browser: http://www15.tceq.texas.gov/crpub/ or you can contact the TCEQ Stormwater Processing Center at 512-239-3700 for assistance. On the website, you can search by your permit number, the Regulated Entity (RN) number, or the Customer Number (CN). If you do not know these numbers, you can select "Advanced Search" to search by permittee name, site address, etc.

The Customer (Permittee) is responsible for providing consistent information to the TCEQ, and for updating all CN and RN data for all authorizations as changes occur. For this permit, a Notice of Change form must be submitted to the program area.

INSTRUCTIONS FOR FILLING OUT THE NOI FORM

Renewal of General Permit. Dischargers holding active authorizations under the expired General Permit are required to submit a NOI to continue coverage. The existing permit number is required. If the permit number is not provided or has been terminated, expired, or denied, a new permit number will be issued.

Section 1. OPERATOR (APPLICANT)

a) Customer Number (CN)

TCEQ's Central Registry will assign each customer a number that begins with CN, followed by nine digits. This is not a permit number, registration number, or license number.

If the applicant is an existing TCEQ customer, the Customer Number is available at the following website: http://www15.tceq.texas.gov/crpub/. If the applicant is not an existing TCEQ customer, leave the space for CN blank.

b) Legal Name of Applicant

Provide the current legal name of the applicant. The name must be provided exactly as filed with the Texas Secretary of State (SOS), or on other legal documents forming the entity, as filed in the county. You may contact the SOS at 512-463-5555, for more information related to filing in Texas. If filed in the county, provide a copy of the legal documents showing the legal name.

c) Contact Information for the Applicant (Responsible Authority)

Provide information for the person signing the application in the Certification section. This person is also referred to as the Responsible Authority.

Provide a complete mailing address for receiving mail from the TCEQ. The mailing address must be recognized by the US Postal Service. You may verify the address on the following website: https://tools.usps.com/go/ZipLookupAction!input.action.

The phone number should provide contact to the applicant.

The fax number and e-mail address are optional and should correspond to the applicant.

d) Type of Customer (Entity Type)

Check only one box that identifies the type of entity. Use the descriptions below to identify the appropriate entity type. Note that the selected entity type also indicates the name that must be provided as an applicant for an authorization.

Individual

An individual is a customer who has not established a business, but conducts an activity that needs to be regulated by the TCEQ.

Partnership

A customer that is established as a partnership as defined by the Texas Secretary of State Office (TX SOS). If the customer is a 'General Partnership' or 'Joint Venture' filed in the county (not filed with TX SOS), the legal name of each partner forming the 'General Partnership' or 'Joint Venture' must be provided. Each 'legal entity' must apply as a co-applicant.

Trust or Estate

A trust and an estate are fiduciary relationships governing the trustee/executor with respect to the trust/estate property.

Sole Proprietorship (DBA)

A sole proprietorship is a customer that is owned by only one person and has not been incorporated. This business may:

- 1. be under the person's name
- 2. have its own name (doing business as or DBA)
- 3. have any number of employees.

If the customer is a Sole Proprietorship or DBA, the 'legal name' of the individual business 'owner' must be provided. The DBA name is not recognized as the 'legal name' of the entity. The DBA name may be used for the site name (regulated entity).

Corporation

A customer that meets all of these conditions:

- 1. is a legally incorporated entity under the laws of any state or country
- 2. is recognized as a corporation by the Texas Secretary of State
- 3. has proper operating authority to operate in Texas

The corporation's 'legal name' as filed with the Texas Secretary of State must be provided as applicant. An 'assumed' name of a corporation is not recognized as the 'legal name' of the entity.

Government

Federal, state, county, or city government (as appropriate)

The customer is either an agency of one of these levels of government or the governmental body itself. The government agency's 'legal name' must be provided as the applicant. A department name or other description of the organization is not recognized as the 'legal name'.

Other

This may include a utility district, water district, tribal government, college district, council of governments, or river authority. Provide the specific type of government.

e) Independent Entity

Check No if this customer is a subsidiary, part of a larger company, or is a governmental entity. Otherwise, check Yes.

f) Number of Employees

Check one box to show the number of employees for this customer's entire company, at all locations. This is not necessarily the number of employees at the site named in the application.

g) Customer Business Tax and Filing Numbers

These are required for Corporations and Limited Partnerships. These are not required for Individuals, Government, and Sole Proprietors.

State Franchise Tax ID Number

Corporations and limited liability companies that operate in Texas are issued a franchise tax identification number. If this customer is a corporation or limited liability company, enter the Tax ID number.

Federal Tax ID

All businesses, except for some small sole proprietors, individuals, or general partnerships should have a federal taxpayer identification number (TIN). Enter this number here. Use no prefixes, dashes, or hyphens. Sole proprietors, individuals, or general partnerships do not need to provide a federal tax ID.

TX SOS Charter (filing) Number

Corporations and Limited Partnerships required to register with the Texas Secretary of State are issued a charter or filing number. You may obtain further information by calling SOS at 512-463-5555.

DUNS Number

Most businesses have a DUNS (Data Universal Numbering System) number issued by Dun and Bradstreet Corp. If this customer has one, enter it here.

Section 2. APPLICATION CONTACT

Provide the name and contact information for the person that TCEQ can contact for additional information regarding this application.

Section 3. REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

a) Regulated Entity Number (RN)

The RN is issued by TCEQ's Central Registry to sites where an activity is regulated by TCEQ. This is not a permit number, registration number, or license number. Search TCEQ's Central Registry to see if the site has an assigned RN at http://www15.tceq.texas.gov/crpub/. If this regulated entity has not been assigned an RN, leave this space blank.

If the site of your business is part of a larger business site, an RN may already be assigned for the larger site. Use the RN assigned for the larger site.

If the site is found, provide the assigned RN and provide the information for the site to be authorized through this application. The site information for this authorization may vary from the larger site information.

An example is a chemical plant where a unit is owned or operated by a separate corporation that is accessible by the same physical address of your unit or facility. Other examples include industrial parks identified by one common address but different corporations have control of defined areas within the site. In both cases, an RN would be assigned for the physical address location and the permitted sites would be identified separately under the same RN.

b) Name of the Project or Site

Provide the name of the site or project as known by the public in the area where the site is located. The name you provide on this application will be used in the TCEQ Central Registry as the Regulated Entity name.

c) Description of Activity Regulated

In your own words, briefly describe the primary business that you are doing that requires this authorization. Do not repeat the SIC Code description.

d) County

Provide the name of the county where the site or project is located. If the site or project is located in more than one county, provide the county names as secondary.

e) Latitude and Longitude

Enter the latitude and longitude of the site in degrees, minutes, and seconds or decimal form. For help obtaining the latitude and longitude, go to: http://www.tceq.texas.gov/gis/sqmaview.html.

f) Site Address/Location

If a site has an address that includes a street number and street name, enter the complete address for the site in *Section A*. If the physical address is not recognized as a USPS delivery address, you may need to validate the address with your local police (911 service) or through an online map site used to locate a site. Please confirm this to be a complete and valid address. Do not use a rural route or post office box for a site location.

If a site does not have an address that includes a street number and street name, provide a complete written location description in *Section B.* For example: "The site is located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1."

Provide the city (or nearest city) and zip code of the site location.

Section 4. GENERAL CHARACTERISTICS

a) Indian Country Lands

If your site is located on Indian Country Lands, the TCEQ does not have authority to process your application. You must obtain authorization through EPA Region 6, Dallas. Do not submit this form to TCEO.

b) Construction activity associated with facility associated with exploration, development, or production of oil, gas, or geothermal resources

If your activity is associated with oil and gas exploration, development, or production, you may be under jurisdiction of the Railroad Commission of Texas (RRC) and may need to obtain authorization from EPA Region 6.

Construction activities associated with a facility related to oil, gas or geothermal resources may include the construction of a well site; treatment or storage facility; underground hydrocarbon or natural gas storage facility; reclamation plant; gas processing facility; compressor station; terminal facility where crude oil is stored prior to refining and at which refined products are stored solely for use at the facility; a carbon dioxide geologic storage facility; and a gathering, transmission, or distribution

pipeline that will transport crude oil or natural gas, including natural gas liquids, prior to refining of such oil or the use of the natural gas in any manufacturing process or as a residential or industrial fuel.

Where required by federal law, discharges of stormwater associated with construction activities under the RRC's jurisdiction must be authorized by the EPA and the RRC, as applicable. Activities under RRC jurisdiction include construction of a facility that, when completed, would be associated with the exploration, development, or production of oil or gas or geothermal resources, such as a well site: treatment or storage facility; underground hydrocarbon or natural gas storage facility; reclamation plant; gas processing facility; compressor station; terminal facility where crude oil is stored prior to refining and at which refined products are stored solely for use at the facility; a carbon dioxide geologic storage facility under the jurisdiction of the RRC; and a gathering, transmission, or distribution pipeline that will transport crude oil or natural gas, including natural gas liquids, prior to refining of such oil or the use of the natural gas in any manufacturing process or as a residential or industrial fuel. The RRC also has jurisdiction over stormwater from land disturbance associated with a site survey that is conducted prior to construction of a facility that would be regulated by the RRC. Under 33 U.S.C. §1342(l)(2) and §1362(24), EPA cannot require a permit for discharges of stormwater from field activities or operations associated with {oil and gas} exploration, production, processing, or treatment operations, or transmission facilities, including activities necessary to prepare a site for drilling and for the movement and placement of drilling equipment, whether or not such field activities or operations may be considered to be construction activities unless the discharge is contaminated by contact with any overburden, raw material, intermediate product, finished product, byproduct, or waste product located on the site of the facility. Under §3.8 of this title (relating to Water Protection), the RRC prohibits operators from causing or allowing pollution of surface or subsurface water. Operators are encouraged to implement and maintain best management practices (BMPs) to minimize discharges of pollutants, including sediment, in stormwater during construction activities to help ensure protection of surface water quality during storm events.

For more information about the jurisdictions of the RRC and the TCEQ, read the Memorandum of Understanding (MOU) between the RRC and TCEQ at 16 Texas Administrative Code, Part 1, Chapter 3, Rule 3.30, by entering the following link into an internet browser:

http://texreg.sos.state.tx.us/public/readtac\$ext.TacPage?sl=R&app=9&p_dir=&p_rloc=&p_tloc=&p_ploc=&p_tac=&ti=16&pt=1&ch=3&rl=30 or contact the TCEQ Stormwater Team at 512-239-4671 for additional information.

c) Primary Standard Industrial Classification (SIC) Code

Provide the SIC Code that best describes the construction activity being conducted at this site.

Common SIC Codes related to construction activities include:

- 1521 Construction of Single Family Homes
- 1522 Construction of Residential Buildings Other than Single Family Homes
- 1541 Construction of Industrial Buildings and Warehouses

- 1542 Construction of Non-residential Buildings, other than Industrial Buildings and Warehouses
- 1611 Highway and Street Construction, except Highway Construction
- 1622 Bridge, Tunnel, and Elevated Highway Construction
- 1623 Water, Sewer, Pipeline and Communications, and Power Line Construction

For help with SIC Codes, enter the following link into your internet browser: http://www.osha.gov/pls/imis/sicsearch.html or you can contact the TCEQ Small Business and Local Government Assistance Section at 800-447-2827 for assistance.

d) Secondary SIC Code

Secondary SIC Code(s) may be provided. Leave this blank if not applicable. For help with SIC Codes, enter the following link into your internet browser: http://www.osha.gov/pls/imis/sicsearch.html or you can contact the TCEQ Small Business and Environmental Assistance Section at 800-447-2827 for assistance.

e) Total Number of Acres Disturbed

Provide the approximate number of acres that the construction site will disturb. Construction activities that disturb less than one acre, unless they are part of a larger common plan that disturbs more than one acre, do not require permit coverage. Construction activities that disturb between one and five acres, unless they are part of a common plan that disturbs more than five acres, do not require submission of an NOI. Therefore, the estimated area of land disturbed should not be less than five, unless the project is part of a larger common plan that disturbs five or more acres. Disturbed means any clearing, grading, excavating, or other similar activities.

If you have any questions about this item, please contact the stormwater technical staff by phone at 512-239-4671 or by email at swgp@tceq.texas.gov.

f) Common Plan of Development

Construction activities that disturb less than five acres do not require submission of an NOI unless they are part of a common plan of development or for sale where the area disturbed is five or more acres. Therefore, the estimated area of land disturbed should not be less than five, unless the project is part of a larger common plan that disturbs five or more acres. Disturbed means any clearing, grading, excavating, or other similar activities.

For more information on what a common plan of development is, refer to the definition of "Common Plan of Development" in the Definitions section of the general permit or enter the following link into your internet browser:

www.tceq.texas.gov/permitting/stormwater/common_plan_of_development_steps.html

For further information, go to the TCEQ stormwater construction webpage enter the following link into your internet browser: www.tceq.texas.gov/goto/construction and search for "Additional Guidance and Quick Links". If you have any further questions about the Common Plan of Development you can contact the TCEQ Stormwater Team at 512-239-4671 or the TCEQ Small Business and Environmental Assistance at 800-447-2827.

g) Estimated Start Date of the Project

This is the date that any construction activity or construction support activity is initiated at the site. If renewing the permit provide the original start date of when construction activity for this project began.

h) Estimated End Date of the Project

This is the date that any construction activity or construction support activity will end and final stabilization will be achieved at the site.

i) Will concrete truck washout be performed at the site?

Indicate if you expect that operators of concrete trucks will washout concrete trucks at the construction site.

j) Identify the water body(s) receiving stormwater runoff

The stormwater may be discharged directly to a receiving stream or through a MS4 from your site. It eventually reaches a receiving water body such as a local stream or lake, possibly via a drainage ditch. You must provide the name of the water body that receives the discharge from the site (a local stream or lake).

If your site has more than one outfall you need to include the name of the first water body for each outfall, if they are different.

k) Identify the segment number(s) of the classified water body(s)

Identify the classified segment number(s) receiving a discharge directly or indirectly. Enter the following link into your internet browser to find the segment number of the classified water body where stormwater will flow from the site: www.tceq.texas.gov/waterquality/monitoring/viewer.html or by contacting the TCEQ Water Quality Division at (512) 239-4671 for assistance.

You may also find the segment number in TCEQ publication GI-316 by entering the following link into your internet browser: www.tceq.texas.gov/publications/gi/gi-316 or by contacting the TCEQ Water Quality Division at (512) 239-4671 for assistance.

If the discharge is into an unclassified receiving water and then crosses state lines prior to entering a classified segment, select the appropriate watershed:

- 0100 (Canadian River Basin)
- 0200 (Red River Basin)
- 0300 (Sulfur River Basin)
- 0400 (Cypress Creek Basin)
- 0500 (Sabine River Basin)

Call the Water Ouality Assessments section at 512-239-4671 for further assistance.

1) Discharge into MS4 - Identify the MS4 Operator

The discharge may initially be into a municipal separate storm sewer system (MS4). If the stormwater discharge is into an MS4, provide the name of the entity that operates the MS4 where the stormwater discharges. An MS4 operator is often a city, town, county, or utility district, but possibly can be another form of government. Please note that the Construction General Permit requires the Operator to supply the MS4 with a

copy of the NOI submitted to TCEQ. For assistance, you may call the technical staff at 512-239-4671.

m) Discharges to the Edwards Aquifer Recharge Zone and Certification

The general permit requires the approved Contributing Zone Plan or Water Pollution Abatement Plan to be included or referenced as a part of the Stormwater Pollution Prevention Plan.

See maps on the TCEQ website to determine if the site is located within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer by entering the following link into an internet browser: www.tceq.texas.gov/field/eapp/viewer.html or by contacting the TCEQ Water Quality Division at 512-239-4671 for assistance.

If the discharge or potential discharge is within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer, a site-specific authorization approved by the Executive Director under the Edwards Aquifer Protection Program (30 TAC Chapter 213) is required before construction can begin.

For questions regarding the Edwards Aquifer Protection Program, contact the appropriate TCEQ Regional Office. For projects in Hays, Travis and Williamson Counties: Austin Regional Office, 12100 Park 35 Circle, Austin, TX 78753, 512-339-2929. For Projects in Bexar, Comal, Kinney, Medina and Uvalde Counties: TCEQ San Antonio Regional Office, 14250 Judson Rd., San Antonio, TX 78233-4480, 210-490-3096.

Section 5. NOI CERTIFICATION

Note: Failure to indicate Yes to all of the certification items may result in denial of coverage under the general permit.

a) Certification of Understanding the Terms and Conditions of Construction General Permit (TXR150000)

Provisional coverage under the Construction General Permit (TXR150000) begins 7 days after the completed paper NOI is postmarked for delivery to the TCEQ. Electronic applications submitted through ePermits have immediate provisional coverage. You must obtain a copy and read the Construction General Permit before submitting your application. You may view and print the Construction General Permit for which you are seeking coverage at the TCEQ web site by entering the following link into an internet browser: www.tceq.texas.gov/goto/construction or you may contact the TCEQ Stormwater processing Center at 512-239-3700 for assistance.

b) Certification of Legal Name

The full legal name of the applicant as authorized to do business in Texas is required. The name must be provided exactly as filed with the Texas Secretary of State (SOS), or on other legal documents forming the entity, that is filed in the county where doing business. You may contact the SOS at 512-463 5555, for more information related to filing in Texas.

c) Understanding of Notice of Termination

A permittee shall terminate coverage under the Construction General Permit through the submittal of a NOT when the operator of the facility changes, final stabilization has been reached, the discharge becomes authorized under an individual permit, or the construction activity never began at this site.

d) Certification of Stormwater Pollution Prevention Plan

The SWP3 identifies the areas and activities that could produce contaminated runoff at your site and then tells how you will ensure that this contamination is mitigated. For example, in describing your mitigation measures, your site's plan might identify the devices that collect and filter stormwater, tell how those devices are to be maintained, and tell how frequently that maintenance is to be carried out. You must develop this plan in accordance with the TCEQ general permit requirements. This plan must be developed and implemented before you complete this NOI. The SWP3 must be available for a TCEQ investigator to review on request.

Section 6. APPLICANT CERTIFICATION SIGNATURE

The certification must bear an original signature of a person meeting the signatory requirements specified under 30 Texas Administrative Code (TAC) §305.44.

If you are a corporation:

The regulation that controls who may sign an NOI or similar form is 30 Texas Administrative Code §305.44(a)(1) (see below). According to this code provision, any corporate representative may sign an NOI or similar form so long as the authority to sign such a document has been delegated to that person in accordance with corporate procedures. By signing the NOI or similar form, you are certifying that such authority has been delegated to you. The TCEQ may request documentation evidencing such authority.

If you are a municipality or other government entity:

The regulation that controls who may sign an NOI or similar form is 30 Texas Administrative Code §305.44(a)(3) (see below). According to this code provision, only a ranking elected official or principal executive officer may sign an NOI or similar form. Persons such as the City Mayor or County Commissioner will be considered ranking elected officials. In order to identify the principal executive officer of your government entity, it may be beneficial to consult your city charter, county or city ordinances, or the Texas statute(s) under which your government entity was formed. An NOI or similar document that is signed by a government official who is not a ranking elected official or principal executive officer does not conform to §305.44(a)(3). The signatory requirement may not be delegated to a government representative other than those identified in the regulation. By signing the NOI or similar form, you are certifying that you are either a ranking elected official or principal executive officer as required by the administrative code. Documentation demonstrating your position as a ranking elected official or principal executive officer may be requested by the TCEQ.

If you have any questions or need additional information concerning the signatory requirements discussed above, please contact the TCEQ's Environmental Law Division at 512-239-0600.

30 Texas Administrative Code

§305.44. Signatories to Applications

- (a) All applications shall be signed as follows.
- (1) For a corporation, the application shall be signed by a responsible corporate officer. For purposes of this paragraph, a responsible corporate officer means a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the

corporation; or the manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25 million (in second-quarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures. Corporate procedures governing authority to sign permit or post-closure order applications may provide for assignment or delegation to applicable corporate positions rather than to specific individuals.

- (2) For a partnership or sole proprietorship, the application shall be signed by a general partner or the proprietor, respectively.
- (3) For a municipality, state, federal, or other public agency, the application shall be signed by either a principal executive officer or a ranking elected official. For purposes of this paragraph, a principal executive officer of a federal agency includes the chief executive officer of the agency, or a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., regional administrator of the EPA).

Texas Commission on Environmental Quality General Permit Payment Submittal Form

Use this form to submit your Application Fee only if you are mailing your payment.

Instructions:

- Complete items 1 through 5 below:
- Staple your check in the space provided at the bottom of this document.
- Do not mail this form with your NOI form.
- Do not mail this form to the same address as your NOI.

Mail this form and your check to either of the following:

By Regular U.S. Mail
Texas Commission on Environmental Quality
Financial Administration Division
Cashier's Office, MC-214
P.O. Box 13088
Austin, TX 78711-3088

By Overnight or Express Mail
Texas Commission on Environmental Quality
Financial Administration Division
Cashier's Office, MC-214
12100 Park 35 Circle
Austin, TX 78753

Fee Co	ode:	GPA •	General	Permit:	TXR150000

- 1. Check or Money Order No:
- 2. Amount of Check/Money Order:
- 3. Date of Check or Money Order:
- 4. Name on Check or Money Order:
- 5. NOI Information:

If the check is for more than one NOI, list each Project or Site (RE) Name and Physical Address exactly as provided on the NOI. **Do not submit a copy of the NOI with this form, as it could cause duplicate permit application entries!**

If there is not enough space on the form to list all of the projects or sites the authorization will cover, then attach a list of the additional sites.

Project/Site (RE) Name:		
Project/Site (RE) Physica	l Address:	

Staple the check or money order to this form in this space.

Agent Authorization Form

For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

and the second s	Matt Lackey	
THE SALE BEAUTIFUL CONTROL OF THE	Print Name	
	Manager Member	
	Title - Owner/President/Other	
of	L Cinco Properties, LLC Corporation/Partnership/Entity Name	
have authorized	MACINA, BOSE, COPELAND & ASSOCIATES, INC	
	Print Name of Agent/Engineer	
of	MACINA, BOSE, COPELAND & ASSOCIATES, INC	

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

- 1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
- 2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
- 3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
- 4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
- 5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:


Applicant's Signature

 $\frac{7/3/25}{\text{Date}}$

THE STATE OF TEXAS §
County of Hidalgo §

BEFORE ME, the undersigned authority, on this day personally appeared <u>Matt Lackeu</u>known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 3rd day of July ,2025.



Corrie Mc grice

Connie McDaniel
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 9-25-2025

Application re	E FUIIII				
Texas Commission on Environm Name of Proposed Regulated En Regulated Entity Location: 27220	tity: <u>Texas Soil and Sto</u>		ıd Bul	verde intersection	
Name of Customer: L Cinco Prop Contact Person: Matt Lackey	erties, LLC	one: (210) 865-29		verde intersection	
Customer Reference Number (if Regulated Entity Reference Num	issued):CN <u></u>				
Austin Regional Office (3373)					
☐ Hays San Antonio Regional Office (33	☐ Travis 62)		□ W	/illiamson	
⊠ Bexar □ Comal	☐ Medina ☐ Kinney		U U	valde	
Application fees must be paid by Commission on Environmental C form must be submitted with yo	Quality. Your canceled	check will serve a	as you	ır receipt. This	
form must be submitted with your fee payment. This payment is being submitted to: Austin Regional Office Mailed to: TCEQ - Cashier Revenues Section Mail Code 214 P.O. Box 13088 Austin, TX 78711-3088 Austin, TX 78711-3088 This payment is being submitted to: San Antonio Regional Office Overnight Delivery to: TCEQ - Cashier 12100 Park 35 Circle Building A, 3rd Floor Austin, TX 78753 (512)239-0357					
Site Location (Check All That App	oly):				
Recharge Zone	Contributing Zone		Γransi	ition Zone	
Type of Pla	n	Size		Fee Due	
Water Pollution Abatement Plan, Plan: One Single Family Residenti	A	cres	\$		
Water Pollution Abatement Plan, Plan: Multiple Single Family Resid	A	cres	\$		
Water Pollution Abatement Plan, Plan: Non-residential	5.338 A	cres	\$ 5,000.00		
Sewage Collection System			L.F.	\$	

Water Pollution Abatement Plan, Contributing Zone		
Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone		
Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone		
Plan: Non-residential	5.338 Acres	\$ 5,000.00
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

	Project Area in	_
Project	Acres	Fee
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional,	< 1	\$3,000
multi-family residential, schools, and other sites	1 < 5	\$4,000
where regulated activities will occur)	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

organized serrage concerns and	· ········	
	Cost per Linear	Minimum Fee-
Project	Foot	Maximum Fee
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

Project	Cost per Tank or Piping System	Minimum Fee- Maximum Fee
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

Project	Fee
Exception Request	\$500

Extension of Time Requests

Project	Fee
Extension of Time Request	\$150



TCEQ Core Data Form

 $For detailed instructions \ on \ completing \ this \ form, \ please \ read \ the \ Core \ Data \ Form \ Instructions \ or \ call \ 512-239-5175.$

SECTION I: General Information

1. Reason for	Submissi	on (If other is checked	l please desci	ribe in space pr	ovided.))						
New Pern	nit, Registra	ation or Authorization	(Core Data F	orm should be	submitte	ed wit	h the prog	ıram apı	plication.)			
Renewal (Core Data Form should be submitted with the renewal form)							Other					
2. Customer	Reference	Number (if issued)		Follow this li			3. Reg	3. Regulated Entity Reference Number (if issued)				
				for CN or RN Central R			RN					
SECTIO	N II:	Custome	r Info	rmatio	<u>n</u>							
4. General Cu	ıstomer In	formation	5. Effectiv	ve Date for Cu	ustome	er Info	ormation	Updat	es (mm/dd/	[/] уууу)		
New Custor	mer		pdate to Cus	tomer Informa	ition		Char	nge in R	egulated En	tity Own	ership	
Change in Le	egal Name	(Verifiable with the Te	xas Secretary	of State or Te	xas Com	ptroll	er of Publi	ic Accou	nts)			
The Custome	r Name su	ıbmitted here may ı	be updated	automatical	llv base	d on	what is c	urrent	and active	with th	ne Texas Sec	retary of State
		oller of Public Accou	-		,							
6. Customer	Legal Nam	ne (If an individual, pri	nt last name	first: eg: Doe, J	John)			<u>If new</u>	/ Customer,	enter pro	evious Custom	er below:
L Cinco Propert	ties, LLC											
7. TX SOS/CP	A Filing N	umber	8. TX Stat	e Tax ID (11 d	ligits)			9. Federal Tax ID 10. DUNS Number (Number (if	
0804431963			32083065337				(9 digits)					
								88-0677911				
11. Type of C	ustomer:	☐ Corpora	tion				☐ Individ	lual	ual Partnership: ☐ General ☒ Limited			eral 🛛 Limited
Government:	City 🔲 (County Federal	Local 🗌 Sta	ite 🗌 Other			Sole P	roprieto	rship	Otl	her:	
12. Number o	of Employ	ees						13. lr	ndepender	itly Ow	ned and Ope	erated?
⊠ 0-20 □ 2	21-100] 101-250 251-	500 🗌 50	1 and higher				⊠ Ye	es	☐ No		
14. Customer	r Role (Pro	posed or Actual) – as i	t relates to th	ne Regulated E	ntity list	ed on	this form.	Please (check one of	the follo	owing	
⊠Owner ☐Occupationa												
	2301 Flus	shing Meadows										
15. Mailing												
Address:	City	Weslaco		State	TX		ZIP	78596	5		ZIP + 4	
16. Country N	Mailing Inf	formation (if outside	USA)			17.	E-Mail A	ddress	(if applicable	e)		
	matt@jrproducesupply.com											
18. Telephone Number 19. Extension or Cod					ode	de 20. Fax Number (if applicable)						

TCEQ-10400 (11/22) Page 1 of 3

(210) 865-2953	() -	

SECTION III: Regulated Entity Information

21. General Regulated Entity Information (If 'New Regulated Entity" is selected, a new permit application is also required.)											
New Regulated Entity	Update to	Regulated Entity	Name Update	to Regulated	Entity Inform	nation					
The Regulated Entity Nat as Inc, LP, or LLC).	me submitte	ed may be upda	ated, in order to me	et TCEQ Co	re Data Stai	ndards (ren	noval of o	rganization	al endings such		
22. Regulated Entity Nan	ne (Enter nam	ne of the site whe	re the regulated action	n is taking pl	ace.)						
Texas Soil and Stone Outfitte	ers										
23. Street Address of the Regulated Entity:											
(No PO Boxes)	City	San Antonio	State	ТХ	ZIP	78260		ZIP + 4			
24. County	Bexar										
		If no Stre	et Address is provid	ded, fields 2	25-28 are re	quired.					
25. Description to	Located along the east side of Bulverde Road										
Physical Location:											
26. Nearest City State Nearest ZIP Code											
San Antonio	TX 78260										
Latitude/Longitude are r used to supply coordinat	-	-	-		Data Standa	ırds. (Geoc	oding of th	ne Physical	Address may be		
27. Latitude (N) In Decimal: 29.703172			28. L	28. Longitude (W) In Decin		mal: -98.454661		51			
Degrees	Minutes		Seconds	Degre	ees	Mi	Minutes		Seconds		
29		42	11.42		98 27 16.7				16.78		
29. Primary SIC Code	30.	Secondary SIC	Code	31. Primary NAICS Cod			e 32. Secondary NAICS Code				
(4 digits)					or 6 digits) (5 or			6 digits)			
1542	1522 236220										
33. What is the Primary I	Business of 1	this entity? (D	o not repeat the SIC o	r NAICS desci	ription.)						
Construction of commercial	retail										
04.04.11	2301 Flushing Meadows										
34. Mailing											
Address:				T		78596		ZIP + 4			
	City	Weslaco	State	TX	ZIP	78330					
35. E-Mail Address:		Weslaco tt@jrproducesup		IX	ZIP	78330					
35. E-Mail Address: 36. Telephone Number						ax Number	· (if applicab				

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.

TCEQ-10400 (11/22) Page 2 of 3

		☐ Districts ☐ Edwards Aquifer		Emissions ir		nventory Air	Industrial Hazardous Waste		
_		New Source							
Municipal Solid Waste		Review Air OSSF		☐ Petroleum		Storage Tank	□ PWS		
Sludge		Storm Water	☐ Title V Air] Tires		☐ Used Oil		
Понаде			- Inde v / III						
☐ Voluntary Cleanup		Wastewater	☐ Wastewater Agriculture		☐ Water Rights		Other:		
voluntary cleanup		Wastewater					Other.		
SECTION	IV: Pr	<u>eparer In</u>	<u>formation</u>						
40. Name: Ri	Richard Hendrix, P.E.			41. Title: Project Manager					
42. Telephone Nu	ımber	43. Ext./Code	44. Fax Number	45. E-Mai	l Address				
(210) 545-1122			() -	rhendrix@mbcengineers.com					
SECTION	V: Au	thorized S	Signature						
46. By my signature	below, I certif	y, to the best of my kn		ation provided required for the	in this form is e updates to t	true and comp he ID numbers	lete, and that I have signature authorit identified in field 39.		
Company:	Macina, Bose, Copeland & Associates, Inc			Job Title:	Project M	ct Manager			
Name (In Print):	Richard Hendrix, P.E.					Phone:	(210) 545- 1122		
ignature: M (His						Date:	7/15/2025		
							1.21		