



# Texas Commission on Environmental Quality Monitor Well Data Sheet for Municipal Solid Waste Permits

- |  |  |
|--|--|
| 1. Name of Facility:   | 2. MSW Permit No.:                               |
| 3. County:   | 4. Monitor Well I.D. No.:                        |
| 5. Date of Monitor Well Installation:  | 6. Date of Well Development:                     |
| 7. Monitor Well Latitude:  | 8. Longitude:                                    |
| 10. Monitor Well Hydraulic Position:<br>Upgradient                      Downgradient | 9. Monitor Well Driller<br>Name:<br>License No.: |
| 11. Geologist, Hydrologist, or Engineer Supervising Well Installation:               |  |
| 12. Static Water Level Elevation (with respect to MSL) after Well Development:       |  |
| 13. Name of Geologic Formation(s) in which Well is completed:                        |  |
| 14. Type of Locking Device:  | 15. Type of Casing Protection:                   |
| 16. Concrete Surface Pad (with steel reinforcement) Dimensions:                      |  |

**Notes:**

- Report all depths from Surface Elevation and all Elevations relative to Mean Sea Level (MSL), to nearest hundredth of a foot.
- Diameter of boring should be at least 4 inches larger than diameter of well casing.
- Use flush screw joint casing only, 2-inch diameter or larger, with o-rings or PTFE tape in joints (4-inch diameter recommend).
- Well development should continue until water is clear, and pH and conductivity are stable.

